

# TEST REPORT

**Reference No.**..... : WTX21X06058149W-1  
**FCC ID** ..... : 2AD56HLK-SS02  
**Applicant** ..... : Shenzhen Hi-Link Electronic co., Ltd.  
**Address** ..... : 3F Caiyue Mansion, No.24 Liuxian blvd, LongHua District, Shenzhen,  
Guangdong, China  
**Product Name** ..... : AI smart WiFi & Voice plug  
**Test Model.** ..... : HLK-SS02  
**Standards** ..... : FCC Part 15.247  
**Date of Receipt sample ....** : Jun. 16, 2021  
**Date of Test**..... : Jun. 16, 2021 to Jul. 05, 2021  
**Date of Issue** ..... : Jul. 05, 2021  
**Test Result**..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China


Tel.: +86-755-33663308

Fax.: +86-755-33663309


Tested by:

Reviewed By:


Approved & Authorized By:



Mike Shi / Project Engineer



Lion Cai / RF Manager



Silin Chen / Manager

**TABLE OF CONTENTS**

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION .....</b>                         | <b>4</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 4         |
| 1.2 TEST STANDARDS.....                                     | 5         |
| 1.3 TEST METHODOLOGY .....                                  | 5         |
| 1.4 TEST FACILITY .....                                     | 5         |
| 1.5 EUT SETUP AND TEST MODE .....                           | 6         |
| 1.6 MEASUREMENT UNCERTAINTY .....                           | 7         |
| 1.7 TEST EQUIPMENT LIST AND DETAILS .....                   | 8         |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                     | <b>10</b> |
| <b>3. ANTENNA REQUIREMENT .....</b>                         | <b>11</b> |
| 3.1 STANDARD APPLICABLE.....                                | 11        |
| 3.2 EVALUATION INFORMATION .....                            | 11        |
| <b>4. POWER SPECTRAL DENSITY .....</b>                      | <b>12</b> |
| 4.1 STANDARD APPLICABLE.....                                | 12        |
| 4.2 TEST SETUP BLOCK DIAGRAM .....                          | 12        |
| 4.3 TEST PROCEDURE.....                                     | 12        |
| 4.4 SUMMARY OF TEST RESULTS/PLOTS .....                     | 12        |
| <b>5. DTS BANDWIDTH.....</b>                                | <b>13</b> |
| 5.1 STANDARD APPLICABLE.....                                | 13        |
| 5.2 TEST SETUP BLOCK DIAGRAM .....                          | 13        |
| 5.3 TEST PROCEDURE.....                                     | 13        |
| 5.4 SUMMARY OF TEST RESULTS/PLOTS .....                     | 13        |
| <b>6. RF OUTPUT POWER .....</b>                             | <b>14</b> |
| 6.1 STANDARD APPLICABLE.....                                | 14        |
| 6.2 TEST SETUP BLOCK DIAGRAM .....                          | 14        |
| 6.3 TEST PROCEDURE.....                                     | 14        |
| 6.4 SUMMARY OF TEST RESULTS/PLOTS .....                     | 14        |
| <b>7. FIELD STRENGTH OF SPURIOUS EMISSIONS .....</b>        | <b>15</b> |
| 7.1 STANDARD APPLICABLE.....                                | 15        |
| 7.2 TEST PROCEDURE.....                                     | 15        |
| 7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....           | 17        |
| 7.4 SUMMARY OF TEST RESULTS/PLOTS .....                     | 17        |
| <b>8. OUT OF BAND EMISSIONS.....</b>                        | <b>25</b> |
| 8.1 STANDARD APPLICABLE.....                                | 25        |
| 8.2 TEST PROCEDURE.....                                     | 25        |
| 8.3 SUMMARY OF TEST RESULTS/PLOTS .....                     | 26        |
| <b>9. CONDUCTED EMISSIONS .....</b>                         | <b>36</b> |
| 9.1 TEST PROCEDURE.....                                     | 36        |
| 9.2 BASIC TEST SETUP BLOCK DIAGRAM.....                     | 36        |
| 9.3 TEST RECEIVER SETUP .....                               | 36        |
| 9.4 SUMMARY OF TEST RESULTS/PLOTS .....                     | 36        |
| <b>APPENDIX SUMMARY .....</b>                               | <b>39</b> |
| <b>APPENDIX A.....</b>                                      | <b>40</b> |
| <b>APPENDIX B.....</b>                                      | <b>45</b> |
| <b>APPENDIX C.....</b>                                      | <b>50</b> |
| <b>APPENDIX D.....</b>                                      | <b>55</b> |
| <b>APPENDIX PHOTOGRAPHS.....</b>                            | <b>63</b> |

**Report version**

| Version No. | Date of issue | Description |
|-------------|---------------|-------------|
| Rev.00      | Jul. 05, 2021 | Original    |
| /           | /             | /           |

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Shenzhen Hi-Link Electronic co., Ltd.  
Address of applicant: 3F Caiyue Mansion, No.24 Liuxian blvd, LongHua District,  
Shenzhen, Guangdong, China

Manufacturer: Shenzhen Hi-Link Electronic co., Ltd.  
Address of manufacturer: 3F Caiyue Mansion, No.24 Liuxian blvd, LongHua District,  
Shenzhen, Guangdong, China

| General Description of EUT                                                             |                            |
|----------------------------------------------------------------------------------------|----------------------------|
| Product Name:                                                                          | AI smart WiFi & Voice plug |
| Trade Name:                                                                            | HI-LINK                    |
| Model No.:                                                                             | HLK-SS02                   |
| Adding Model(s):                                                                       | /                          |
| Rated Voltage:                                                                         | AC90-250V                  |
| Power Adapter Model:                                                                   | /                          |
| Note: The test data is gathered from a production sample provided by the manufacturer. |                            |

| Technical Characteristics of EUT |                                                                      |
|----------------------------------|----------------------------------------------------------------------|
| Support Standards:               | 802.11b, 802.11g, 802.11n                                            |
| Frequency Range:                 | 2412-2462MHz for 802.11b/g/n(HT20)<br>2422-2452MHz for 802.11n(HT40) |
| RF Output Power:                 | 14.56dBm (Conducted)                                                 |
| Type of Modulation:              | DBPSK, BPSK, DQPSK, QPSK, 16QAM, 64QAM                               |
| Quantity of Channels:            | 11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)                        |
| Channel Separation:              | 5MHz                                                                 |
| Type of Antenna:                 | PCB Antenna                                                          |
| Antenna Gain:                    | 1dBi                                                                 |

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.247:** Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

**558074 D01 15.247 Meas Guidance v05r02:** Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

**662911 D01 Multiple Transmitter Output v02r01:** Emissions Testing of Transmitters with Multiple Outputs in the Same Band.

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 662911 D01 Multiple Transmitter Output v02r01

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List |              |                                          |
|----------------|--------------|------------------------------------------|
| Test Mode      | Description  | Remark                                   |
| TM1            | 802.11b      | Low:2412MHz, Middle:2437MHz,High:2462MHz |
| TM2            | 802.11g      | Low:2412MHz, Middle:2437MHz,High:2462MHz |
| TM3            | 802.11n-HT20 | Low:2412MHz, Middle:2437MHz,High:2462MHz |
| TM4            | 802.11n-HT40 | Low:2422MHz, Middle:2437MHz,High:2452MHz |

| Test Conditions    |           |
|--------------------|-----------|
| Temperature:       | 22~25 °C  |
| Relative Humidity: | 45~55 %.  |
| ATM Pressure:      | 1019 mbar |

| EUT Cable List and Details |            |                     |                        |
|----------------------------|------------|---------------------|------------------------|
| Cable Description          | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| /                          | /          | /                   | /                      |

| Special Cable List and Details |            |                     |                        |
|--------------------------------|------------|---------------------|------------------------|
| Cable Description              | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| /                              | /          | /                   | /                      |

| Auxiliary Equipment List and Details |              |       |               |
|--------------------------------------|--------------|-------|---------------|
| Description                          | Manufacturer | Model | Serial Number |
| /                                    | /            | /     | /             |

## 1.6 Measurement Uncertainty

| Measurement uncertainty        |            |                                |
|--------------------------------|------------|--------------------------------|
| Parameter                      | Conditions | Uncertainty                    |
| RF Output Power                | Conducted  | $\pm 0.42\text{dB}$            |
| Occupied Bandwidth             | Conducted  | $\pm 1.5\%$                    |
| Power Spectral Density         | Conducted  | $\pm 1.8\text{dB}$             |
| Conducted Spurious Emission    | Conducted  | $\pm 2.17\text{dB}$            |
| Conducted Emissions            | Conducted  | 9-150kHz $\pm 3.74\text{dB}$   |
|                                |            | 0.15-30MHz $\pm 3.34\text{dB}$ |
| Transmitter Spurious Emissions | Radiated   | 30-200MHz $\pm 4.52\text{dB}$  |
|                                |            | 0.2-1GHz $\pm 5.56\text{dB}$   |
|                                |            | 1-6GHz $\pm 3.84\text{dB}$     |
|                                |            | 6-26GHz $\pm 3.92\text{dB}$    |

**1.7 Test Equipment List and Details**

| No.       | Description             | Manufacturer           | Model                 | Serial No.  | Cal Date   | Due. Date  |
|-----------|-------------------------|------------------------|-----------------------|-------------|------------|------------|
| SEMT-1075 | Communication Tester    | Rohde & Schwarz        | CMW500                | 148650      | 2021-03-27 | 2022-03-26 |
| SEMT-1063 | GSM Tester              | Rohde & Schwarz        | CMU200                | 114403      | 2021-03-27 | 2022-03-26 |
| SEMT-1072 | Spectrum Analyzer       | Agilent                | E4407B                | MY41440400  | 2021-03-27 | 2022-03-26 |
| SEMT-1079 | Spectrum Analyzer       | Agilent                | N9020A                | US47140102  | 2021-03-27 | 2022-03-26 |
| SEMT-1080 | Signal Generator        | Agilent                | 83752A                | 3610A01453  | 2021-03-27 | 2022-03-26 |
| SEMT-1081 | Vector Signal Generator | Agilent                | N5182A                | MY47070202  | 2021-03-27 | 2022-03-26 |
| SEMT-1028 | Power Divider           | Weinschel              | 1506A                 | PM204       | 2021-03-27 | 2022-03-26 |
| SEMT-1082 | Power Divider           | RF-Lambda              | RFLT4W5M18G           | 14110400027 | 2021-03-27 | 2022-03-26 |
| SEMT-1031 | Spectrum Analyzer       | Rohde & Schwarz        | FSP30                 | 836079/035  | 2021-03-27 | 2022-03-26 |
| SEMT-1007 | EMI Test Receiver       | Rohde & Schwarz        | ESVB                  | 825471/005  | 2021-03-27 | 2022-03-26 |
| SEMT-1008 | Amplifier               | Agilent                | 8447F                 | 3113A06717  | 2021-04-12 | 2022-04-11 |
| SEMT-1043 | Amplifier               | C&D                    | PAP-1G18              | 2002        | 2021-04-12 | 2022-04-11 |
| SEMT-1069 | Loop Antenna            | Schwarz beck           | FMZB 1516             | 9773        | 2021-03-19 | 2023-03-18 |
| SEMT-1068 | Broadband Antenna       | Schwarz beck           | VULB9163              | 9163-333    | 2021-03-19 | 2023-03-18 |
| SEMT-1042 | Horn Antenna            | ETS                    | 3117                  | 00086197    | 2021-03-19 | 2023-03-18 |
| SEMT-1121 | Horn Antenna            | Schwarzbeck            | BBHA 9170             | BBHA9170582 | 2021-04-27 | 2023-04-26 |
| SEMT-1169 | Pre-amplifier           | Direction Systems Inc. | PAP-2640              | 14145-14153 | 2021-04-27 | 2022-04-26 |
| SEMT-1163 | Spectrum Analyzer       | Rohde & Schwarz        | FSP40                 | 100612      | 2021-03-27 | 2022-03-26 |
| SEMT-1166 | Power Limiter           | Agilent                | N9356B                | MY45450376  | 2021-03-27 | 2022-03-26 |
| SEMT-1076 | RF Switcher             | Top Precision          | RCS03-A2              | /           | 2021-03-19 | 2023-03-18 |
| SEMT-C001 | Cable                   | Zheng DI               | LL142-07-07-10M(A)    | /           | /          | /          |
| SEMT-C002 | Cable                   | Zheng DI               | ZT40-2.92J-2.92J-6M   | /           | /          | /          |
| SEMT-C003 | Cable                   | Zheng DI               | ZT40-2.92J-2.92J-2.5M | /           | /          | /          |
| SEMT-C004 | Cable                   | Zheng DI               | 2M0RFC                | /           | /          | /          |
| SEMT-C005 | Cable                   | Zheng DI               | 1M0RFC                | /           | /          | /          |
| SEMT-C006 | Cable                   | Zheng DI               | 1M0RFC                | /           | /          | /          |

| Software List                              |              |        |         |
|--------------------------------------------|--------------|--------|---------|
| Description                                | Manufacturer | Model  | Version |
| EMI Test Software<br>(Radiated Emission)*  | Farad        | EZ-EMC | RA-03A1 |
| EMI Test Software<br>(Conducted Emission)* | Farad        | EZ-EMC | RA-03A1 |

\*Remark: indicates software version used in the compliance certification testing

## 2. SUMMARY OF TEST RESULTS

---

| FCC Rules                 | Description of Test Item          | Result    |
|---------------------------|-----------------------------------|-----------|
| §15.203; §15.247(b)(4)(i) | Antenna Requirement               | Compliant |
| §15.205                   | Restricted Band of Operation      | Compliant |
| §15.207(a)                | Conducted Emission                | Compliant |
| §15.247(e)                | Power Spectral Density            | Compliant |
| §15.247(a)(2)             | DTS Bandwidth                     | Compliant |
| §15.247(b)(3)             | RF Output Power                   | Compliant |
| §15.209(a)                | Radiated Emission                 | Compliant |
| §15.247(d)                | Band Edge (Out of Band Emissions) | Compliant |

N/A: Not applicable

### **3. Antenna Requirement**

---

#### **3.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **3.2 Evaluation Information**

This product has a PCB antenna, fulfill the requirement of this section.


## 4. Power Spectral Density

---

### 4.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 4.2 Test Setup Block Diagram



### 4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 4.4 Summary of Test Results/Plots

Please refer to Appendix A


## 5. DTS Bandwidth

---

### 5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 5.2 Test Setup Block Diagram



### 5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times \text{RBW}$ .
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 5.4 Summary of Test Results/Plots

Please refer to Appendix B


## 6. RF Output Power

---

### 6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 6.2 Test Setup Block Diagram



### 6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This gives bin-to-bin spacing  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

### 6.4 Summary of Test Results/Plots

Please refer to Appendix C

## 7. Field Strength of Spurious Emissions

### 7.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


### 7.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.


The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



The test setup for emission measurement above 1 GHz..



|                          |                              |                              |
|--------------------------|------------------------------|------------------------------|
| Frequency :9kHz-30MHz    | Frequency :30MHz-1GHz        | Frequency :Above 1GHz        |
| RBW=10KHz,               | RBW=120KHz,                  | RBW=1MHz,                    |
| VBW =30KHz               | VBW=300KHz                   | VBW=3MHz(Peak), 10Hz(AV)     |
| Sweep time= Auto         | Sweep time= Auto             | Sweep time= Auto             |
| Trace = max hold         | Trace = max hold             | Trace = max hold             |
| Detector function = peak | Detector function = peak, QP | Detector function = peak, AV |

### 7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


### 7.4 Summary of Test Results/Plots

*Note: 1.This EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

*All test modes (different data rate and different modulation) are performed, but only the worst case(802.11b\_11Mbps) is recorded in this report.*


➤ Spurious Emissions Below 1GHz

|                |     |           |            |
|----------------|-----|-----------|------------|
| 802.11b_11Mbps |     |           |            |
| Test Channel   | Low | Polarity: | Horizontal |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 33.0950            | 29.17               | -9.42           | 19.75              | 40.00             | -20.25         | -             | -              | peak   |
| 2   | 53.1313            | 29.11               | -8.52           | 20.59              | 40.00             | -19.41         | -             | -              | peak   |
| 3   | 101.6443           | 27.61               | -8.63           | 18.98              | 43.50             | -24.52         | -             | -              | peak   |
| 4   | 294.1137           | 26.16               | -5.75           | 20.41              | 46.00             | -25.59         | -             | -              | peak   |
| 5   | 341.9787           | 29.86               | -4.87           | 24.99              | 46.00             | -21.01         | -             | -              | peak   |
| 6   | 744.8661           | 28.94               | 1.09            | 30.03              | 46.00             | -15.97         | -             | -              | peak   |

|                |     |           |          |
|----------------|-----|-----------|----------|
| 802.11b_11Mbps |     |           |          |
| Test Channel   | Low | Polarity: | Vertical |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 42.0066            | 36.04               | -7.89           | 28.15              | 40.00             | -11.85         | -             | -              | peak   |
| 2   | 52.2079            | 36.38               | -8.37           | 28.01              | 40.00             | -11.99         | -             | -              | peak   |
| 3   | 75.1823            | 35.87               | -12.01          | 23.86              | 40.00             | -16.14         | -             | -              | peak   |
| 4   | 193.7728           | 26.29               | -9.14           | 17.15              | 43.50             | -26.35         | -             | -              | peak   |
| 5   | 537.5891           | 27.50               | -1.99           | 25.51              | 46.00             | -20.49         | -             | -              | peak   |
| 6   | 909.6667           | 27.33               | 3.56            | 30.89              | 46.00             | -15.11         | -             | -              | peak   |

|                |        |           |            |
|----------------|--------|-----------|------------|
| 802.11b_11Mbps |        |           |            |
| Test Channel   | Middle | Polarity: | Horizontal |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 33.2112            | 30.76               | -9.40           | 21.36              | 40.00             | -18.64         | -             | -              | peak   |
| 2   | 52.3913            | 29.38               | -8.40           | 20.98              | 40.00             | -19.02         | -             | -              | peak   |
| 3   | 107.8877           | 26.57               | -8.68           | 17.89              | 43.50             | -25.61         | -             | -              | peak   |
| 4   | 375.9385           | 27.97               | -4.28           | 23.69              | 46.00             | -22.31         | -             | -              | peak   |
| 5   | 696.8567           | 27.72               | 0.58            | 28.30              | 46.00             | -17.70         | -             | -              | peak   |
| 6   | 922.5157           | 27.38               | 3.67            | 31.05              | 46.00             | -14.95         | -             | -              | peak   |

|                |        |           |          |
|----------------|--------|-----------|----------|
| 802.11b_11Mbps |        |           |          |
| Test Channel   | Middle | Polarity: | Vertical |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 33.0950            | 36.75               | -9.42           | 27.33              | 40.00             | -12.67         | -             | -              | peak   |
| 2   | 42.7496            | 35.73               | -7.89           | 27.84              | 40.00             | -12.16         | -             | -              | peak   |
| 3   | 61.9951            | 36.29               | -10.06          | 26.23              | 40.00             | -13.77         | -             | -              | peak   |
| 4   | 112.1305           | 26.44               | -8.83           | 17.61              | 43.50             | -25.89         | -             | -              | peak   |
| 5   | 374.6226           | 25.27               | -4.31           | 20.96              | 46.00             | -25.04         | -             | -              | peak   |
| 6   | 906.4824           | 27.03               | 3.53            | 30.56              | 46.00             | -15.44         | -             | -              | peak   |

|                |      |           |            |
|----------------|------|-----------|------------|
| 802.11b_11Mbps |      |           |            |
| Test Channel   | High | Polarity: | Horizontal |



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 33.0950            | 29.00               | -9.42           | 19.58              | 40.00             | -20.42         | -             | -              | peak   |
| 2   | 54.8348            | 30.12               | -8.81           | 21.31              | 40.00             | -18.69         | -             | -              | peak   |
| 3   | 104.9033           | 28.27               | -8.66           | 19.61              | 43.50             | -23.89         | -             | -              | peak   |
| 4   | 264.7457           | 27.25               | -6.33           | 20.92              | 46.00             | -25.08         | -             | -              | peak   |
| 5   | 504.7062           | 27.49               | -2.58           | 24.91              | 46.00             | -21.09         | -             | -              | peak   |
| 6   | 945.4399           | 27.48               | 3.86            | 31.34              | 46.00             | -14.66         | -             | -              | peak   |

|                |      |           |          |
|----------------|------|-----------|----------|
| 802.11b_11Mbps |      |           |          |
| Test Channel   | High | Polarity: | Vertical |



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 35.8747            | 35.78               | -8.80           | 26.98              | 40.00             | -13.02         | -             | -              | peak   |
| 2   | 51.3005            | 35.97               | -8.22           | 27.75              | 40.00             | -12.25         | -             | -              | peak   |
| 3   | 62.8708            | 35.54               | -10.23          | 25.31              | 40.00             | -14.69         | -             | -              | peak   |
| 4   | 114.9169           | 27.93               | -9.02           | 18.91              | 43.50             | -24.59         | -             | -              | peak   |
| 5   | 283.9792           | 26.50               | -5.94           | 20.56              | 46.00             | -25.44         | -             | -              | peak   |
| 6   | 785.0935           | 27.29               | 1.53            | 28.82              | 46.00             | -17.18         | -             | -              | peak   |

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- Spurious Emissions Above 1GHz
- Test Mode: 802.11b\_11Mbps (worst case)

| Frequency              | Reading  | Correct | Result   | Limit    | Margin | Polar | Detector |
|------------------------|----------|---------|----------|----------|--------|-------|----------|
| (MHz)                  | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | H/V   |          |
| Low Channel-2412MHz    |          |         |          |          |        |       |          |
| 4824.000               | 56.54    | -3.87   | 52.67    | 74       | -21.33 | H     | PK       |
| 4824.000               | 53.17    | -3.87   | 49.30    | 54       | -4.70  | H     | AV       |
| 7236.000               | 53.95    | 1.14    | 55.09    | 74       | -18.91 | H     | PK       |
| 7236.000               | 37.03    | 1.19    | 38.22    | 54       | -15.78 | H     | AV       |
| 4824.000               | 54.89    | -3.86   | 51.03    | 74       | -22.97 | V     | PK       |
| 4824.000               | 50.46    | -3.86   | 46.60    | 54       | -7.40  | V     | AV       |
| 7236.000               | 54.02    | 1.10    | 55.12    | 74       | -18.88 | V     | PK       |
| 7236.000               | 36.36    | 1.10    | 37.46    | 54       | -16.54 | V     | AV       |
| Middle Channel-2437MHz |          |         |          |          |        |       |          |
| 4874.000               | 56.60    | -3.74   | 52.86    | 74       | -21.14 | H     | PK       |
| 4874.000               | 52.33    | -3.74   | 48.59    | 54       | -5.41  | H     | AV       |
| 7311.000               | 54.30    | 1.47    | 55.77    | 74       | -18.23 | H     | PK       |
| 7311.000               | 37.04    | 1.47    | 38.51    | 54       | -15.49 | H     | AV       |
| 4874.000               | 54.41    | -3.74   | 50.67    | 74       | -23.33 | V     | PK       |
| 4874.000               | 50.06    | -3.74   | 46.32    | 54       | -7.68  | V     | AV       |
| 7311.000               | 55.03    | 1.47    | 56.50    | 74       | -17.50 | V     | PK       |
| 7311.000               | 35.35    | 1.47    | 36.82    | 54       | -17.18 | V     | AV       |
| High Channel-2462MHz   |          |         |          |          |        |       |          |
| 4924.000               | 56.12    | -3.59   | 52.53    | 74       | -21.47 | H     | PK       |
| 4924.000               | 51.33    | -3.59   | 47.74    | 54       | -6.26  | H     | AV       |
| 7386.000               | 53.91    | 1.79    | 55.70    | 74       | -18.30 | H     | PK       |
| 7386.000               | 37.34    | 1.79    | 39.13    | 54       | -14.87 | H     | AV       |
| 4924.000               | 54.91    | -3.59   | 51.32    | 74       | -22.68 | V     | PK       |
| 4924.000               | 50.55    | -3.59   | 46.96    | 54       | -7.04  | V     | AV       |
| 7386.000               | 54.59    | 1.79    | 56.38    | 74       | -17.62 | V     | PK       |
| 7386.000               | 35.27    | 1.79    | 37.06    | 54       | -16.94 | V     | AV       |

*Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*

## 8. Out of Band Emissions

---

### 8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 8.2 Test Procedure

According to the KDB 558074D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

#### A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement

KDB publication number: 913591 may be used for the radiated bandedge measurements.

#### B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b)  $VBW \geq [3 \times RBW]$ .
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

**Table 9—RBW as a function of frequency**

| Frequency          | RBW                |
|--------------------|--------------------|
| 9 kHz to 150 kHz   | 200 Hz to 300 Hz   |
| 0.15 MHz to 30 MHz | 9 kHz to 10 kHz    |
| 30 MHz to 1000 MHz | 100 kHz to 120 kHz |
| >1000 MHz          | 1 MHz              |


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

### 8.3 Summary of Test Results/Plots


➤ Radiated test

|                |     |           |                        |
|----------------|-----|-----------|------------------------|
| 802.11b_11Mbps |     |           |                        |
| Test Channel   | Low | Polarity: | Horizontal(worst case) |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2310.000           | 40.96               | -9.66           | 31.30              | 54.00             | -22.70         | Average Detector |
|     | 2310.000           | 54.02               | -9.66           | 44.36              | 74.00             | -29.64         | Peak Detector    |
| 2   | 2386.800           | 60.12               | -9.50           | 50.62              | 54.00             | -3.38          | Average Detector |
|     | 2385.960           | 70.35               | -9.51           | 60.84              | 74.00             | -13.16         | Peak Detector    |
| 3   | 2390.000           | 53.36               | -9.50           | 43.86              | 54.00             | -10.14         | Average Detector |
|     | 2390.000           | 64.09               | -9.50           | 54.59              | 74.00             | -19.41         | Peak Detector    |
| 4   | 2400.000           | 70.77               | -9.48           | 61.29              | Delta=32.84dBc    |                | Average Detector |
| 5   | 2412.840           | 103.59              | -9.46           | 94.13              |                   |                | Average Detector |

|                |      |           |                      |
|----------------|------|-----------|----------------------|
| 802.11b_11Mbps |      |           |                      |
| Test Channel   | High | Polarity: | Vertical(worst case) |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2461.300           | 99.97               | -9.36           | 90.61              | /                 | /              | Average Detector |
|     | 2462.200           | 107.27              | -9.36           | 97.91              | /                 | /              | Peak Detector    |
| 2   | 2483.500           | 44.46               | -9.31           | 35.15              | 54.00             | -18.85         | Average Detector |
|     | 2483.500           | 57.14               | -9.31           | 47.83              | 74.00             | -26.17         | Peak Detector    |
| 3   | 2487.150           | 47.15               | -9.30           | 37.85              | 54.00             | -16.15         | Average Detector |
|     | 2487.700           | 59.38               | -9.30           | 50.08              | 74.00             | -23.92         | Peak Detector    |
| 4   | 2500.000           | 39.93               | -9.28           | 30.65              | 54.00             | -23.35         | Average Detector |
|     | 2500.000           | 53.75               | -9.28           | 44.47              | 74.00             | -29.53         | Peak Detector    |

|                |     |           |                      |
|----------------|-----|-----------|----------------------|
| 802.11g_54Mbps |     |           |                      |
| Test Channel   | Low | Polarity: | Vertical(worst case) |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2310.000           | 41.72               | -9.66           | 32.06              | 54.00             | -21.94         | Average Detector |
|     | 2310.000           | 55.03               | -9.66           | 45.37              | 74.00             | -28.63         | Peak Detector    |
| 2   | 2390.000           | 55.91               | -9.50           | 46.41              | 54.00             | -7.59          | Average Detector |
|     | 2390.000           | 78.03               | -9.50           | 68.53              | 74.00             | -5.47          | Peak Detector    |
| 3   | 2400.000           | 69.05               | -9.48           | 59.57              | Delta=30.81dBc    |                | Average Detector |
| 4   | 2413.680           | 99.83               | -9.45           | 90.38              |                   |                | Average Detector |

|                |      |           |                      |
|----------------|------|-----------|----------------------|
| 802.11g_54Mbps |      |           |                      |
| Test Channel   | High | Polarity: | Vertical(worst case) |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2460.750           | 93.45               | -9.36           | 84.09              | /                 | /              | Average Detector |
|     | 2463.050           | 104.94              | -9.36           | 95.58              | /                 | /              | Peak Detector    |
| 2   | 2483.500           | 43.79               | -9.31           | 34.48              | 54.00             | -19.52         | Average Detector |
|     | 2483.500           | 59.11               | -9.31           | 49.80              | 74.00             | -24.20         | Peak Detector    |
| 3   | 2500.000           | 39.92               | -9.28           | 30.64              | 54.00             | -23.36         | Average Detector |
|     | 2500.000           | 53.09               | -9.28           | 43.81              | 74.00             | -30.19         | Peak Detector    |

|                   |     |           |                      |
|-------------------|-----|-----------|----------------------|
| 802.11n-HT20_MCS7 |     |           |                      |
| Test Channel      | Low | Polarity: | Vertical(worst case) |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2310.000           | 42.21               | -9.66           | 32.55              | 54.00             | -21.45         | Average Detector |
|     | 2310.000           | 53.11               | -9.66           | 43.45              | 74.00             | -30.55         | Peak Detector    |
| 2   | 2390.000           | 57.40               | -9.50           | 47.90              | 54.00             | -6.10          | Average Detector |
|     | 2390.000           | 74.09               | -9.50           | 64.59              | 74.00             | -9.41          | Peak Detector    |
| 3   | 2400.000           | 69.87               | -9.48           | 60.39              | Delta=31.12dBc    |                | Average Detector |
| 4   | 2411.280           | 100.97              | -9.46           | 91.51              |                   |                | Average Detector |

|                   |      |           |                      |
|-------------------|------|-----------|----------------------|
| 802.11n-HT20_MCS7 |      |           |                      |
| Test Channel      | High | Polarity: | Vertical(worst case) |




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2461.250           | 93.45               | -9.36           | 84.09              | /                 | /              | Average Detector |
|     | 2460.600           | 104.35              | -9.36           | 94.99              | /                 | /              | Peak Detector    |
| 2   | 2483.500           | 44.44               | -9.31           | 35.13              | 54.00             | -18.87         | Average Detector |
|     | 2483.500           | 60.18               | -9.31           | 50.87              | 74.00             | -23.13         | Peak Detector    |
| 3   | 2500.000           | 39.90               | -9.28           | 30.62              | 54.00             | -23.38         | Average Detector |
|     | 2500.000           | 52.30               | -9.28           | 43.02              | 74.00             | -30.98         | Peak Detector    |

|                   |     |           |                      |
|-------------------|-----|-----------|----------------------|
| 802.11n-HT40_MCS7 |     |           |                      |
| Test Channel      | Low | Polarity: | Vertical(worst case) |



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2310.000           | 42.39               | -9.66           | 32.73              | 54.00             | -21.27         | Average Detector |
|     | 2390.000           | 73.25               | -9.50           | 63.75              | 74.00             | -10.25         | Peak Detector    |
| 2   | 2390.000           | 59.62               | -9.50           | 50.12              | 54.00             | -3.88          | Average Detector |
|     | 2390.000           | 73.25               | -9.50           | 63.75              | 74.00             | -10.25         | Peak Detector    |
| 3   | 2400.000           | 63.18               | -9.48           | 53.70              | Delta=30.85dBc    |                | Average Detector |
| 4   | 2415.560           | 94.01               | -9.46           | 84.55              |                   |                | Average Detector |

|                   |      |           |                      |
|-------------------|------|-----------|----------------------|
| 802.11n-HT40_MCS7 |      |           |                      |
| Test Channel      | High | Polarity: | Vertical(worst case) |



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2459.890           | 87.90               | -9.35           | 78.55              | /                 | /              | Average Detector |
|     | 2459.330           | 99.29               | -9.36           | 89.93              | /                 | /              | Peak Detector    |
| 2   | 2483.500           | 47.86               | -9.31           | 38.55              | 54.00             | -15.45         | Average Detector |
|     | 2483.500           | 64.52               | -9.31           | 55.21              | 74.00             | -18.79         | Peak Detector    |
| 3   | 2500.000           | 40.36               | -9.28           | 31.08              | 54.00             | -22.92         | Average Detector |
|     | 2500.000           | 52.72               | -9.28           | 43.44              | 74.00             | -30.56         | Peak Detector    |

➤ Conducted test

**Please refer to Appendix D**

9. Conducted Emissions


9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

|                                    |         |
|------------------------------------|---------|
| Start Frequency .....              | 150 kHz |
| Stop Frequency .....               | 30 MHz  |
| Sweep Speed .....                  | Auto    |
| IF Bandwidth.....                  | 10 kHz  |
| Quasi-Peak Adapter Bandwidth ..... | 9 kHz   |
| Quasi-Peak Adapter Mode .....      | Normal  |


9.4 Summary of Test Results/Plots

|           |               |             |           |         |
|-----------|---------------|-------------|-----------|---------|
| Test Mode | Communication | AC120V 60Hz | Polarity: | Neutral |
|-----------|---------------|-------------|-----------|---------|



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Detector |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|----------|
| 1*  | 0.1660             | 47.56             | 10.26           | 57.82            | 65.16           | -7.34          | QP       |
| 2   | 0.2060             | 28.95             | 10.27           | 39.22            | 53.37           | -14.15         | AVG      |
| 3   | 1.1220             | 36.54             | 10.21           | 46.75            | 56.00           | -9.25          | QP       |
| 4   | 1.1220             | 24.83             | 10.21           | 35.04            | 46.00           | -10.96         | AVG      |
| 5   | 1.9340             | 36.35             | 10.28           | 46.63            | 56.00           | -9.37          | QP       |
| 6   | 1.9940             | 24.23             | 10.29           | 34.52            | 46.00           | -11.48         | AVG      |

|           |               |             |           |      |
|-----------|---------------|-------------|-----------|------|
| Test Mode | Communication | AC120V 60Hz | Polarity: | Line |
|-----------|---------------|-------------|-----------|------|



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Detector |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|----------|
| 1*  | 0.1860             | 43.99             | 10.26           | 54.25            | 64.21           | -9.96          | QP       |
| 2   | 0.2300             | 27.07             | 10.26           | 37.33            | 52.45           | -15.12         | AVG      |
| 3   | 1.1260             | 34.44             | 10.21           | 44.65            | 56.00           | -11.35         | QP       |
| 4   | 1.2420             | 23.17             | 10.22           | 33.39            | 46.00           | -12.61         | AVG      |
| 5   | 1.9620             | 22.23             | 10.28           | 32.51            | 46.00           | -13.49         | AVG      |
| 6   | 2.1140             | 35.01             | 10.29           | 45.30            | 56.00           | -10.70         | QP       |

## APPENDIX SUMMARY

---




|                   |                 |               |           |
|-------------------|-----------------|---------------|-----------|
| Project No.       | WTX21X06058149W | Test Engineer | Gala      |
| Start date        | 2021/6/30       | Finish date   | 2021/6/30 |
| Temperature       | 25℃             | Humidity      | 48%       |
| RF specifications | WIFI-2.4G       |               |           |

| APPENDIX | Description of Test Item        | Result    |
|----------|---------------------------------|-----------|
| A        | Power Spectral Density          | Compliant |
| B        | DTS Bandwidth                   | Compliant |
| C        | RF Output Power                 | Compliant |
| D        | Conducted Out of Band Emissions | Compliant |

## APPENDIX A

---

| Power Spectral Density |                     |                                    |                   |
|------------------------|---------------------|------------------------------------|-------------------|
| Test Mode              | Test Channel<br>MHz | Power Spectral Density<br>dBm/3kHz | Limit<br>dBm/3kHz |
| 802.11b_11Mbps         | 2412                | -25.95                             | 8                 |
|                        | 2437                | -25.20                             | 8                 |
|                        | 2462                | -25.85                             | 8                 |
| 802.11g_54Mbps         | 2412                | -21.23                             | 8                 |
|                        | 2437                | -20.41                             | 8                 |
|                        | 2462                | -19.90                             | 8                 |
| 802.11n-HT20_MCS7      | 2412                | -21.42                             | 8                 |
|                        | 2437                | -20.15                             | 8                 |
|                        | 2462                | -19.79                             | 8                 |
| 802.11n-HT40_MCS7      | 2422                | -27.18                             | 8                 |
|                        | 2437                | -26.77                             | 8                 |
|                        | 2452                | -26.73                             | 8                 |

|                |                                                                                      |
|----------------|--------------------------------------------------------------------------------------|
| 802.11b-Low    |    |
| 802.11b-Middle |   |
| 802.11b-High   |  |

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11g-Low    | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.41230 GHz</div><div>-21.23 dBm</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.412300000 GHz</div><div>-21.23 dBm</div></div><div><div>Center 2.412 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 5.425 s (1001 pts)</div><div>Span 30 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div> |
| 802.11g-Middle | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.43637 GHz</div><div>-20.41 dBm</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.436370000 GHz</div><div>-20.41 dBm</div></div><div><div>Center 2.437 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 5.425 s (1001 pts)</div><div>Span 30 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div> |
| 802.11g-High   | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.46137 GHz</div><div>-19.9 dBm</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.461370000 GHz</div><div>-19.9 dBm</div></div><div><div>Center 2.462 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 5.425 s (1001 pts)</div><div>Span 30 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div>   |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11n-HT20-Low    | <div><div><div>Agilent</div><div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.41169 GHz</div><div>-21.42 dBm</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.411690000 GHz</div><div>-21.42 dBm</div></div><div><div>Center 2.414 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 5.425 s (1001 pts)</div><div>Span 30 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div> |
| 802.11n-HT20-Middle | <div><div><div>Agilent</div><div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.43670 GHz</div><div>-20.15 dBm</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.436700000 GHz</div><div>-20.15 dBm</div></div><div><div>Center 2.437 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 5.425 s (1001 pts)</div><div>Span 30 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div> |
| 802.11n-HT20-High   | <div><div><div>Agilent</div><div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.46170 GHz</div><div>-19.79 dBm</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.461700000 GHz</div><div>-19.79 dBm</div></div><div><div>Center 2.462 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 5.425 s (1001 pts)</div><div>Span 30 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div> |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11n-HT40-Low    | <div><div><div>Agilent</div><div>R T</div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.42572 GHz</div><div>-27.18 dBm</div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>M1 S2</div><div>S3 FC</div><div>AA</div><div>Marker</div><div>2.425720000 GHz</div><div>-27.18 dBm</div><div>Center 2.422 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 10.85 s (1001 pts)</div><div>Span 60 MHz</div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More</div><div>1 of 2</div></div></div> |
| 802.11n-HT40-Middle | <div><div><div>Agilent</div><div>R T</div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.43574 GHz</div><div>-26.77 dBm</div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>M1 S2</div><div>S3 FC</div><div>AA</div><div>Marker</div><div>2.435740000 GHz</div><div>-26.77 dBm</div><div>Center 2.437 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 10.85 s (1001 pts)</div><div>Span 60 MHz</div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More</div><div>1 of 2</div></div></div> |
| 802.11n-HT40-High   | <div><div><div>Agilent</div><div>R T</div><div>Ref 0 dBm</div><div>Atten 10 dB</div><div>Mkr1 2.45074 GHz</div><div>-26.73 dBm</div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>M1 S2</div><div>S3 FC</div><div>AA</div><div>Marker</div><div>2.450740000 GHz</div><div>-26.73 dBm</div><div>Center 2.452 GHz</div><div>#Res BW 3 kHz</div><div>#VBW 10 kHz</div><div>Sweep 10.85 s (1001 pts)</div><div>Span 60 MHz</div></div><div><div>Peak Search</div><div>Meas Tools ▶</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More</div><div>1 of 2</div></div></div> |

## APPENDIX B

---

| DTS Bandwidth     |                     |                       |              |
|-------------------|---------------------|-----------------------|--------------|
| Test Mode         | Test Channel<br>MHz | 6 dB Bandwidth<br>MHz | Limit<br>kHz |
| 802.11b_11Mbps    | 2412                | 10.105                | ≥500         |
|                   | 2437                | 10.092                | ≥500         |
|                   | 2462                | 11.078                | ≥500         |
| 802.11g_54Mbps    | 2412                | 15.446                | ≥500         |
|                   | 2437                | 15.680                | ≥500         |
|                   | 2462                | 15.518                | ≥500         |
| 802.11n-HT20_MCS7 | 2412                | 15.520                | ≥500         |
|                   | 2437                | 15.492                | ≥500         |
|                   | 2462                | 15.493                | ≥500         |
| 802.11n-HT40_MCS7 | 2422                | 35.176                | ≥500         |
|                   | 2437                | 35.136                | ≥500         |
|                   | 2452                | 35.308                | ≥500         |

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11b-Low    | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.412 GHz</div><div>Trig Free</div></div><div>Occupied Bandwidth</div><div>x dB -6.00 dB</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.412 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div></div><div><div>Occupied Bandwidth</div><div>15.7015 MHz</div><div>Occ BW % Pwr 99.00 %</div><div>x dB -6.00 dB</div><div>Transmit Freq Error 118.841 kHz</div><div>x dB Bandwidth 10.105 MHz</div></div></div></div><div><div>Trace/View</div><div>Trace 1 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div>        |
| 802.11b-Middle | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.437 GHz</div><div>Trig Free</div></div><div>Occupied Bandwidth</div><div>Center 2.43700000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.437 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div></div><div><div>Occupied Bandwidth</div><div>15.7220 MHz</div><div>Occ BW % Pwr 99.00 %</div><div>x dB -6.00 dB</div><div>Transmit Freq Error 49.470 kHz</div><div>x dB Bandwidth 10.092 MHz</div></div></div></div><div><div>Trace/View</div><div>Trace 1 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11b-High   | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.462 GHz</div><div>Trig Free</div></div><div>Occupied Bandwidth</div><div>Center 2.46200000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.462 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div></div><div><div>Occupied Bandwidth</div><div>15.7044 MHz</div><div>Occ BW % Pwr 99.00 %</div><div>x dB -6.00 dB</div><div>Transmit Freq Error 89.876 kHz</div><div>x dB Bandwidth 11.078 MHz</div></div></div></div><div><div>Trace/View</div><div>Trace 1 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11g-Low    | <div><div><div>Agilent</div><div>Ch Freq 2.412 GHz</div><div>Trig Free</div><div>Occupied Bandwidth</div><div>Center 2.41200000 GHz</div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>Center 2.412 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div><div>Occupied Bandwidth</div><div>16.2903 MHz</div><div>Occ BW % Pwr</div><div>99.00 %</div><div>x dB</div><div>-6.00 dB</div><div>Transmit Freq Error</div><div>19.045 kHz</div><div>x dB Bandwidth</div><div>15.446 MHz</div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11g-Middle | <div><div><div>Agilent</div><div>Ch Freq 2.437 GHz</div><div>Trig Free</div><div>Occupied Bandwidth</div><div>Center 2.43700000 GHz</div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>Center 2.437 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div><div>Occupied Bandwidth</div><div>16.3079 MHz</div><div>Occ BW % Pwr</div><div>99.00 %</div><div>x dB</div><div>-6.00 dB</div><div>Transmit Freq Error</div><div>905.516 Hz</div><div>x dB Bandwidth</div><div>15.680 MHz</div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11g-High   | <div><div><div>Agilent</div><div>Ch Freq 2.462 GHz</div><div>Trig Free</div><div>Occupied Bandwidth</div><div>Center 2.46200000 GHz</div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>Center 2.462 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div><div>Occupied Bandwidth</div><div>16.2933 MHz</div><div>Occ BW % Pwr</div><div>99.00 %</div><div>x dB</div><div>-6.00 dB</div><div>Transmit Freq Error</div><div>7.606 kHz</div><div>x dB Bandwidth</div><div>15.518 MHz</div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div>  |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11n-HT20-Low    | <div><div><div><div>Agilent</div><div>R</div><div>T</div></div><div><div>Ch Freq</div><div>2.412 GHz</div><div>Trig</div><div>Free</div></div><div><div>Occupied Bandwidth</div><div></div></div><div><div>Center 2.412000000 GHz</div></div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.412 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div></div><div><div>Occupied Bandwidth</div><div>17.3096 MHz</div><div>Occ BW % Pwr</div><div>99.00 %</div><div>x dB</div><div>-6.00 dB</div></div><div><div>Transmit Freq Error</div><div>30.686 kHz</div><div>x dB Bandwidth</div><div>15.520 MHz</div></div></div><div><div>Trace/View</div><div>1</div><div>Trace</div><div>2</div><div>3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More</div><div>1 of 2</div></div></div> |
| 802.11n-HT20-Middle | <div><div><div><div>Agilent</div><div>R</div><div>T</div></div><div><div>Ch Freq</div><div>2.437 GHz</div><div>Trig</div><div>Free</div></div><div><div>Occupied Bandwidth</div><div></div></div><div><div>Center 2.437000000 GHz</div></div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.437 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div></div><div><div>Occupied Bandwidth</div><div>17.3285 MHz</div><div>Occ BW % Pwr</div><div>99.00 %</div><div>x dB</div><div>-6.00 dB</div></div><div><div>Transmit Freq Error</div><div>17.058 kHz</div><div>x dB Bandwidth</div><div>15.492 MHz</div></div></div><div><div>Trace/View</div><div>1</div><div>Trace</div><div>2</div><div>3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More</div><div>1 of 2</div></div></div> |
| 802.11n-HT20-High   | <div><div><div><div>Agilent</div><div>R</div><div>T</div></div><div><div>Ch Freq</div><div>2.462 GHz</div><div>Trig</div><div>Free</div></div><div><div>Occupied Bandwidth</div><div></div></div><div><div>Center 2.462000000 GHz</div></div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.462 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 30 MHz</div></div><div><div>Occupied Bandwidth</div><div>17.2981 MHz</div><div>Occ BW % Pwr</div><div>99.00 %</div><div>x dB</div><div>-6.00 dB</div></div><div><div>Transmit Freq Error</div><div>14.068 kHz</div><div>x dB Bandwidth</div><div>15.493 MHz</div></div></div><div><div>Trace/View</div><div>1</div><div>Trace</div><div>2</div><div>3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More</div><div>1 of 2</div></div></div> |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11n-HT40-Low    | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.422 GHz</div><div>Trig Free</div></div><div>Occupied Bandwidth</div><div>Center 2.42200000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.422 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 60 MHz</div></div><div><div>Occupied Bandwidth</div><div>35.8212 MHz</div><div>Occ BW % Pwr 99.00 %</div><div>x dB -6.00 dB</div><div>Transmit Freq Error 83.090 kHz</div><div>x dB Bandwidth 35.176 MHz</div></div></div><div><div>Trace/View</div><div>1 2 3</div><div>Trace</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11n-HT40-Middle | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.437 GHz</div><div>Trig Free</div></div><div>Occupied Bandwidth</div><div>Center 2.43700000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.437 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 60 MHz</div></div><div><div>Occupied Bandwidth</div><div>35.8960 MHz</div><div>Occ BW % Pwr 99.00 %</div><div>x dB -6.00 dB</div><div>Transmit Freq Error 43.269 kHz</div><div>x dB Bandwidth 35.136 MHz</div></div></div><div><div>Trace/View</div><div>1 2 3</div><div>Trace</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11n-HT40-High   | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.452 GHz</div><div>Trig Free</div></div><div>Occupied Bandwidth</div><div>Center 2.45200000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.452 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 60 MHz</div></div><div><div>Occupied Bandwidth</div><div>35.8841 MHz</div><div>Occ BW % Pwr 99.00 %</div><div>x dB -6.00 dB</div><div>Transmit Freq Error 45.378 kHz</div><div>x dB Bandwidth 35.308 MHz</div></div></div><div><div>Trace/View</div><div>1 2 3</div><div>Trace</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |

## APPENDIX C

---

| Test Mode         | Frequency<br>MHz | Reading<br>dBm | Limit<br>dBm |
|-------------------|------------------|----------------|--------------|
| 802.11b _ 11Mbps  | 2412             | 13.45          | 30.00        |
|                   | 2437             | 14.29          | 30.00        |
|                   | 2462             | 14.56          | 30.00        |
| 802.11g_54Mbps    | 2412             | 10.99          | 30.00        |
|                   | 2437             | 12.17          | 30.00        |
|                   | 2462             | 12.81          | 30.00        |
| 802.11n HT20_MCS7 | 2412             | 10.70          | 30.00        |
|                   | 2437             | 11.85          | 30.00        |
|                   | 2462             | 12.43          | 30.00        |
| 802.11n HT40_MCS7 | 2422             | 8.11           | 30.00        |
|                   | 2437             | 8.71           | 30.00        |
|                   | 2452             | 8.56           | 30.00        |

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11b-Low    | <div><div><div>Agilent</div><div>Ch Freq 2.412 GHz</div><div>Channel Power</div><div>Trig Free</div></div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.412 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>13.45 dBm / 20.0000 MHz</div><div>-59.56 dBm/Hz</div></div></div> <div><div>Trace/View</div><div>Trace 1 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div>                                  |
| 802.11b-Middle | <div><div><div>Agilent</div><div>Ch Freq 2.437 GHz</div><div>Channel Power</div><div>Trig Free</div></div><div>Center 2.437000000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.437 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>14.29 dBm / 20.0000 MHz</div><div>-58.72 dBm/Hz</div></div></div> <div><div>Trace/View</div><div>Trace 1 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div> |
| 802.11b-High   | <div><div><div>Agilent</div><div>Ch Freq 2.462 GHz</div><div>Channel Power</div><div>Trig Free</div></div><div>Center 2.462000000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.462 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>14.56 dBm / 20.0000 MHz</div><div>-58.45 dBm/Hz</div></div></div> <div><div>Trace/View</div><div>Trace 1 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div> |

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11g-Low    | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.412 GHz</div><div>Trig Free</div></div><div><div>Channel Power</div><div></div></div><div><div>Center 2.41200000 GHz</div></div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.412 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>10.99 dBm / 20.0000 MHz</div><div>-62.02 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11g-Middle | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.437 GHz</div><div>Trig Free</div></div><div><div>Channel Power</div><div></div></div><div><div>Center 2.43700000 GHz</div></div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.437 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>12.17 dBm / 20.0000 MHz</div><div>-60.84 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11g-High   | <div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ch Freq 2.462 GHz</div><div>Trig Free</div></div><div><div>Channel Power</div><div></div></div><div><div>Center 2.46200000 GHz</div></div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div></div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div><div><div>Center 2.462 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>12.81 dBm / 20.0000 MHz</div><div>-60.20 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |


|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11n-HT20-Low    | <div><div><div>Agilent</div><div>Ch Freq 2.412 GHz</div><div>Trig Free</div><div>Channel Power</div><div>Center 2.41200000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div></div><div><div>Center 2.412 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>10.70 dBm / 20.0000 MHz</div><div>-62.31 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11n-HT20-Middle | <div><div><div>Agilent</div><div>Ch Freq 2.437 GHz</div><div>Trig Free</div><div>Channel Power</div><div>Center 2.43700000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div></div><div><div>Center 2.437 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>11.85 dBm / 20.0000 MHz</div><div>-61.16 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11n-HT20-High   | <div><div><div>Agilent</div><div>Ch Freq 2.462 GHz</div><div>Trig Free</div><div>Channel Power</div><div>Center 2.46200000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div></div><div><div>Center 2.462 GHz</div><div>Res BW 300 kHz</div><div>#VBW 1 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 30 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>12.43 dBm / 20.0000 MHz</div><div>-60.99 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 Trace 2 3</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 802.11n-HT40-Low    | <div><div><div>Agilent</div><div>Ch Freq 2.422 GHz</div><div>Trig Free</div><div>Channel Power</div><div>Center 2.422000000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div></div><div><div>Center 2.422 GHz</div><div>#Res BW 1 MHz</div><div>#VBW 3 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 60 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>8.11 dBm / 40.0000 MHz</div><div>-67.91 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 2 3</div><div>Trace</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11n-HT40-Middle | <div><div><div>Agilent</div><div>Ch Freq 2.437 GHz</div><div>Trig Free</div><div>Channel Power</div><div>Center 2.437000000 GHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div></div><div><div>Center 2.437 GHz</div><div>#Res BW 1 MHz</div><div>#VBW 3 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 60 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>8.71 dBm / 40.0000 MHz</div><div>-67.31 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 2 3</div><div>Trace</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div> |
| 802.11n-HT40-High   | <div><div><div>Agilent</div><div>Ch Freq 2.452 GHz</div><div>Trig Free</div><div>Channel Power</div><div>RBW 1.000000000 MHz</div><div><div>Ref 20 dBm</div><div>Atten 30 dB</div><div><div>#Avg</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div></div></div><div><div>Center 2.452 GHz</div><div>#Res BW 1 MHz</div><div>#VBW 3 MHz</div><div>Sweep 8 ms (401 pts)</div><div>Span 60 MHz</div></div><div><div>Channel Power</div><div>Power Spectral Density</div><div>8.56 dBm / 40.0000 MHz</div><div>-67.46 dBm/Hz</div></div></div><div><div>Trace/View</div><div>1 2 3</div><div>Trace</div><div>Clear Write</div><div>Max Hold</div><div>Min Hold</div><div>View</div><div>Blank</div><div>More 1 of 2</div></div></div>    |


APPENDIX D

Conducted Out of Band Emissions



|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>802.11b-Low</p>    | <div><div><div>Agilent</div><div><div>Ref 15 dBm</div><div>Atten 25 dB</div><div>Mkr1 2.41152 GHz</div><div>-3.981 dBm</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>DI</div><div>34.0</div><div>dBm</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Center</div><div>2.412000000 GHz</div></div><div><div>Center 2.412 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 60 MHz</div></div></div><div><div>Freq/Channel</div><div>Center Freq</div><div>2.41200000 GHz</div><div>Start Freq</div><div>2.38200000 GHz</div><div>Stop Freq</div><div>2.44200000 GHz</div><div>CF Step</div><div>6.00000000 MHz</div><div>Auto</div><div>Man</div><div>Freq Offset</div><div>0.00000000 Hz</div><div>Signal Track</div><div>On</div><div>Off</div><div>Scale Type</div><div>Log</div><div>Lin</div></div></div>    |
|                       | <div><div><div>Agilent</div><div><div>Ref 15 dBm</div><div>Atten 25 dB</div><div>Mkr1 10.314 GHz</div><div>53.31 dBm</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>DI</div><div>34.0</div><div>dBm</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Start</div><div>30.00000000 MHz</div></div><div><div>Start 30 MHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 2.691 s (1001 pts)</div><div>Stop 26 GHz</div></div></div><div><div>Freq/Channel</div><div>Center Freq</div><div>13.01500000 GHz</div><div>Start Freq</div><div>30.00000000 MHz</div><div>Stop Freq</div><div>26.00000000 GHz</div><div>CF Step</div><div>2.597000000 GHz</div><div>Auto</div><div>Man</div><div>Freq Offset</div><div>0.00000000 Hz</div><div>Signal Track</div><div>On</div><div>Off</div><div>Scale Type</div><div>Log</div><div>Lin</div></div></div>     |
| <p>802.11b-Middle</p> | <div><div><div>Agilent</div><div><div>Ref 15 dBm</div><div>Atten 25 dB</div><div>Mkr1 2.43598 GHz</div><div>-3.557 dBm</div></div><div><div>#Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1</div><div>dB</div><div>DI</div><div>33.6</div><div>dBm</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Center</div><div>2.437000000 GHz</div></div><div><div>Center 2.437 GHz</div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 10 ms (1001 pts)</div><div>Span 60 MHz</div></div></div><div><div>Freq/Channel</div><div>Center Freq</div><div>2.437000000 GHz</div><div>Start Freq</div><div>2.407000000 GHz</div><div>Stop Freq</div><div>2.467000000 GHz</div><div>CF Step</div><div>6.00000000 MHz</div><div>Auto</div><div>Man</div><div>Freq Offset</div><div>0.00000000 Hz</div><div>Signal Track</div><div>On</div><div>Off</div><div>Scale Type</div><div>Log</div><div>Lin</div></div></div> |




|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>802.11g-Low</p>    | <div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm    Atten 25 dB    Mkr1 2.41326 GHz    0.725 dBm</div><div><div>#Peak</div><div>Log</div><div>dB/</div><div>Offset</div><div>dB</div><div>DI</div><div>-29.2</div><div>dBm</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div>Center<br/>2.41200000 GHz</div><div>Center 2.412 GHz    Span 60 MHz<br/>#Res BW 100 kHz    #VBW 300 kHz    Sweep 10 ms (1001 pts)</div></div><div><div>Freq/Channel</div><div>Center Freq<br/>2.41200000 GHz</div><div>Start Freq<br/>2.38200000 GHz</div><div>Stop Freq<br/>2.44200000 GHz</div><div>CF Step<br/>6.00000000 MHz<br/>Auto    Man</div><div>Freq Offset<br/>0.00000000 Hz</div><div>Signal Track<br/>On    Off</div><div>Scale Type<br/>Log    Lin</div></div></div> |
|                       | <div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm    Atten 25 dB    Mkr1 6.782 GHz    53.12 dBm</div><div><div>#Peak</div><div>Log</div><div>dB/</div><div>Offset</div><div>dB</div><div>DI</div><div>-29.2</div><div>dBm</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div>Start<br/>30.00000000 MHz</div><div>Start 30 MHz    Stop 26 GHz<br/>#Res BW 100 kHz    #VBW 300 kHz    Sweep 2.691 s (1001 pts)</div></div><div><div>Freq/Channel</div><div>Center Freq<br/>13.01500000 GHz</div><div>Start Freq<br/>30.00000000 MHz</div><div>Stop Freq<br/>26.00000000 GHz</div><div>CF Step<br/>2.59700000 GHz<br/>Auto    Man</div><div>Freq Offset<br/>0.00000000 Hz</div><div>Signal Track<br/>On    Off</div><div>Scale Type<br/>Log    Lin</div></div></div>  |
| <p>802.11g-Middle</p> | <div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm    Atten 25 dB    Mkr1 2.43952 GHz    1.51 dBm</div><div><div>#Peak</div><div>Log</div><div>dB/</div><div>Offset</div><div>dB</div><div>DI</div><div>-28.5</div><div>dBm</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div>Center<br/>2.437000000 GHz</div><div>Center 2.437 GHz    Span 60 MHz<br/>#Res BW 100 kHz    #VBW 300 kHz    Sweep 10 ms (1001 pts)</div></div><div><div>Freq/Channel</div><div>Center Freq<br/>2.43700000 GHz</div><div>Start Freq<br/>2.40700000 GHz</div><div>Stop Freq<br/>2.46700000 GHz</div><div>CF Step<br/>6.00000000 MHz<br/>Auto    Man</div><div>Freq Offset<br/>0.00000000 Hz</div><div>Signal Track<br/>On    Off</div><div>Scale Type<br/>Log    Lin</div></div></div> |




802.11n-HT20-Low





802.11n-HT20-Middle







802.11n-HT40-Low



802.11n-HT40-Middle





## **APPENDIX PHOTOGRAPHS**

---

**Please refer to “ANNEX”**

**\*\*\*\*\* END OF REPORT \*\*\*\*\***