

TEST REPORT



Dt&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042

Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2609-0084

2. Customer

• Name (FCC) : PARTRON CO., LTD / Name (ISED): PARTRON CO., LTD.

• Address (FCC) : 22,Samsung1-ro2-gil, Hwaseong-si, Gyeonggi-do, Hwaseong, South Korea

Address (ISED) : (Seoku-dong), 22 Samsung1-ro20gil Hwaseong-si, Gyeonggi-do 18449 Korea (Republic Of)

3. Use of Report : FCC & ISED Original Certification

4. Product Name / Model Name : TMS / PTHRT1

FCC ID : 2AD5K-TMS001

IC : 22232-TMS001

5. FCC Regulation(s): Part 15.247

ISED Standard(s): RSS-247 Issue 4, RSS-Gen Issue 6

Test Method used: KDB558074 D01v05r02, ANSI C63.10-2020

6. Date of Test : 2026.08.27 ~ 2026.08.28

7. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

8. Testing Environment : See appended test report.

9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager
	Name : SeungMin Gil 	Name : JaeJin Lee 

2026 . 09 . 08 .

Dt&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2609-0084	Sep, 08. 2026	Initial issue	SeungMin Gil	JaeJin Lee

Table of Contents

1. General Information	4
1.1. Description of EUT	4
1.2. Support Equipment	4
1.3. Testing Laboratory	5
1.4. Testing Environment	5
1.5. Measurement Uncertainty	5
1.6. Test Equipment List	6
2. Test Methodology	7
2.1. EUT Configuration	7
2.2. EUT Exercise	7
2.3. General Test Procedures	7
2.4. Instrument Calibration	7
2.5. Description of Test Modes	7
3. Antenna Requirements	8
4. Summary of Test Results	9
5. Test Result	10
5.1. Maximum Peak Conducted Output Power	10
5.1.1. Test Setup	10
5.1.2. Test Procedures	10
5.1.3. Test Results	10
5.2. 6 dB Bandwidth	13
5.2.1. Test Setup	13
5.2.2. Test Procedures	13
5.2.3. Test Results	13
5.3. Power Spectral Density	16
5.3.1. Test Setup	16
5.3.2. Test Procedures	16
5.3.3. Test Results	16
5.4. Unwanted Emissions (Conducted)	19
5.4.1. Test Setup	19
5.4.2. Test Procedures	19
5.4.3. Test Results	20
5.5. Unwanted Emissions (Radiated)	29
5.5.1. Test Setup	31
5.5.2. Test Procedures	31
5.5.3. Test Results	33
5.6. AC Power-Line Conducted Emissions	34
5.6.1. Test Setup	34
5.6.2. Test Procedures	34
5.6.3. Test Results	34
5.7. Occupied Bandwidth	35
5.7.1. Test Setup	35
5.7.2. Test Procedures	35
5.7.3. Test Results	35
APPENDIX I	38
APPENDIX II	39

1. General Information

1.1. Description of EUT

Equipment Class	Digital Transmission System (DTS)
Product Name	TMS
Product Marketing Name(s)	PTHRT1, PTHPZ1, PTHTZ1
Model Name(s)	PTHRT1, PTHPZ1, PTHTZ1
Firmware Version Identification Number	1.0.10
EUT Serial Number	No Specified
Power Supply	DC : 3 V
Frequency Range	2 402 MHz ~ 2 480 MHz
Max. RF Output Power	-8.18 dBm (0.0002 W)
Modulation Technique (Data rate)	GFSK (1 Mbps)
Antenna Specification	Antenna Type: PCB Printed Antenna Gain : 1.07 dBi

1.2. Support Equipment

N/A

1.3. Testing Laboratory

Dt&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.		
The test site complies with the requirements of Part 2.948.		
- FCC Designation No.: KR0034		
- FCC Test Firm Registration No.: 704742		
- ISED CAB identifier: KR0034		
- ISED#: 5740A		
www.dtnet.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.4. Testing Environment

Ambient Condition	
▪ Temperature	+24 °C ~ +25 °C
▪ Relative Humidity	+45 % ~ +55 %

1.5. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.10-2020. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
Antenna-port conducted emission	0.8 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (1 GHz Below)	4.9 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (1 GHz ~ 18 GHz)	4.9 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (18 GHz Above)	5.3 dB (The confidence level is about 95 %, $k = 2$)

1.6. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	KEYSIGHT	N9020A	25/11/19	26/11/19	MY50410272
Spectrum Analyzer	Agilent Technologies	N9020A	26/05/15	27/05/15	US47360812
Spectrum Analyzer	Agilent Technologies	N9020A	25/11/18	26/11/18	MY50410399
DC Power Supply	SM techno	SDP30-5D	26/05/21	27/05/21	305DMG304
DC Power Supply	Agilent Technologies	66332A	25/11/21	26/11/21	US37470950
Multimeter	FLUKE	17B	25/11/21	26/11/21	26030065WS
Signal Generator	Rohde Schwarz	SMBV100A	25/11/20	26/11/20	255571
Signal Generator	ANRITSU	MG3695C	25/11/18	26/11/18	173501
Thermohygrometer	BODYCOM	BJ5478	25/11/24	26/11/24	090205-4
Thermohygrometer	BODYCOM	BJ5478	25/11/24	26/11/24	120612-2
Thermohygrometer	BODYCOM	BJ5478	26/05/13	27/05/13	N/A
Loop Antenna	ETS-Lindgren	6502	25/11/06	27/11/06	00060496
Hybrid Antenna	Schwarzbeck	VULB9163	25/05/27	27/05/27	9163-572
Horn Antenna	ETS-Lindgren	3117	26/05/15	27/05/15	00143278
Horn Antenna	A.H.Systems Inc.	SAS-574	26/05/29	27/05/29	155
PreAmplifier	Agilent Technologies	8449B	25/11/17	26/11/17	3008A00161
PreAmplifier	tsj	MLA-1840-J02-45	26/05/21	27/05/21	16966-10728
PreAmplifier	H.P	8447D	25/11/17	26/11/17	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	26/05/15	27/05/15	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	26/05/15	27/05/15	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	26/05/15	27/05/15	3
Attenuator	Aeroflex/Weinschel	56-3	26/05/15	27/05/15	Y2370
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2488B MA2472A	25/11/25	26/11/25	0926003 030031
Cable	Dt&C	Cable	26/01/02	27/01/02	G-2
Cable	OMT	YSS21S	26/01/02	27/01/02	G-5
Cable	Microwave	HF-290	26/01/02	27/01/02	G-6
Cable	Junkosha	MWX241	26/01/02	27/01/02	mmW-1
Cable	Junkosha	MWX241	26/01/02	27/01/02	mmW-4
Cable	HUBER+SUHNER	SUCOFLEX100	26/01/02	27/01/02	M-01
Cable	HUBER+SUHNER	SUCOFLEX100	26/01/02	27/01/02	M-02
Cable	JUNKOSHA	MWX241/B	26/01/02	27/01/02	M-03
Cable	JUNKOSHA	J12J101757-00	26/01/02	27/01/02	M-07
Cable	HUBER+SUHNER	SUCOFLEX106	26/01/02	27/01/02	M-09
Cable	Radiall	TESTPRO3	26/01/02	27/01/02	RFC-70
Test Software (Radiated)	tsj	EMI Measurement	NA	NA	Version 2.00.0185
Test Software	tsj	Noise Terminal Measurement	NA	NA	Version 2.00.0190
3m Semi Anechoic Chamber	SYC	3m-SAC	26/06/12(NSA) 26/06/17(VSWR)	27/06/12(NSA) 27/06/17(VSWR)	3m-SAC-1
3m Semi Anechoic Chamber	SYC	3m-SAC	26/01/09(NSA) 26/01/14(VSWR)	27/01/09(NSA) 27/01/14(VSWR)	3m-SAC-2

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.

Note2: The cable is not a regular calibration item, so it has been calibrated by Dt&C itself.

2. Test Methodology

The measurement procedures described in the ANSI C63.10-2020 and the guidance provided in KDB558074 D01v05r02 were used in measurement of the EUT.

The EUT was tested per the guidance of KDB558074 D01v05r02. And ANSI C63.10-2020 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the test mode to fix the TX frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB558074 D01v05r02.

So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2020.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

Basically the radiated tests were performed with KDB558074 D01v05r02. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2020 as stated on section 3 of the KDB558074 D01v05r02.

The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

2.4. Instrument Calibration

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.5. Description of Test Modes

The EUT has been tested with the operating condition for maximizing the emission characteristics. A test program is used to control the EUT for staying in continuous transmitting. The Bluetooth low energy mode with below low, middle and high channels were tested and reported.

Test Mode	Description	Tested Frequency (MHz)		
		Lowest Frequency	Middle Frequency	Highest Frequency
TM 1	BT LE(1 Mbps)	2 402	2 426	2 480

Note: The EUT supports advertising mode only.

EUT Operation test setup

- Test Software: Simplicity Studio V5
- Power setting: 0

3. Antenna Requirements

■ **According to Part 15.203**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

The antenna is permanently attached on the device.

Therefore this E.U.T complies with the requirement of Part 15.203

4. Summary of Test Results

FCC part section(s)	RSS section(s)	Test Description	Limit	Test Condition	Status Note 1
15.247(a)	RSS-247[6.3.1]	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	RSS-247[6.3.2]	Maximum Peak Output Power	< 1 Watt (conducted), FCC & ISSED < 4 Watt (e.i.r.p), ISSED		C
15.247(d)	RSS-247[6.6]	Unwanted Emissions(Conducted)	20 dBc in any 100 kHz BW		C
15.247(e)	RSS-247[6.3.1]	Power Spectral Density	< 8 dBm / 3 kHz		C
-	RSS-Gen[5.1]	Occupied Bandwidth (99 %)	NA		C
15.247(d) 15.209 15.205	RSS-247[6.6] RSS-Gen[7.4.3] RSS-Gen[7.5]	Unwanted Emissions(Radiated)	Part 15.209 limits (Refer to section 5.5)	Radiated	C Note 2
15.207	RSS-Gen[7.4.2]	AC Power-Line Conducted Emissions	Part 15.207 limits (Refer to section 5.6)	AC Line Conducted	NA Note 3
15.203	-	Antenna Requirements	Part 15.203 (Refer to section 3)	-	C

Note 1: **C**=Comply **NC**=Not Comply **NT**=Not Tested **NA**=Not Applicable
Note 2: This test item was performed in three orthogonal EUT positions and the worst case data was reported.
Note 3: This device is operated only from internal batteries and there is no port to connect to the AC Line.

5. Test Result

5.1. Maximum Peak Conducted Output Power

■ Test Requirements and limit, Part 15.247(b) & RSS-247[6.3.2]

A transmitter antenna terminal of EUT is connected to the input of a spectrum analyzer.

Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

The e.i.r.p. shall not exceed 4 W, except as provided in section 6.3.2 of RSS-247.

5.1.1. Test Setup

Refer to the APPENDIX I.

5.1.2. Test Procedures

- KDB558074 D01v05r02 - Section 8.3.1.1
- ANSI C63.10-2020 – Section 11.9.1.1

RBW ≥ DTS bandwidth

1. Set the RBW ≥ DTS bandwidth. **Actual RBW = 2 MHz or 2.4 MHz**
2. Set VBW ≥ 3 x RBW. **Actual VBW = 6 MHz or 8 MHz**
3. Set span ≥ 3 x RBW.
4. Sweep time = No faster than coupled (auto) time.
5. Detector = **peak**
6. Trace mode = **max hold**
7. Allow trace to fully stabilize
8. Use peak marker function to determine the peak amplitude level.

5.1.3. Test Results

Test Mode	Tested Channel	Burst Average Output Power (dBm)	Peak Conducted Output Power (dBm)	Antenna Gain(dBi)	e.i.r.p ^{Note3} (dBm)
TM 1	Lowest	-9.41	-8.69	1.07	-7.62
	Middle	-9.17	-8.76	1.07	-7.69
	Highest	-8.60	-8.18	1.07	-7.11

Note 1: The average output power was tested using an average power meter for reference only.

Note 2: See next pages for actual measured spectrum plots.


Note 3: e.i.r.p = $P_{\text{cond}} + G_{\text{EUT}}$

P_{cond} = measured power at feed point of the EUT antenna, in dBm (Peak Conducted Output Power)

G_{EUT} = gain of the EUT radiating element (antenna), in dBi


Peak Output Power

TM 1 Test Channel : Lowest




Peak Output Power

TM 1 Test Channel : Middle



Peak Output Power

TM 1 Test Channel : Highest



5.2. 6 dB Bandwidth

■ Test Requirements and limit, Part 15.247(a) & RSS-247[6.3.1]

The bandwidth at 6 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the EUT's antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6 dB bandwidth is 500 kHz.

5.2.1. Test Setup

Refer to the APPENDIX I.

5.2.2. Test Procedures

- KDB558074 D01v05r02 - Section 8.2
- ANSI C63.10-2020 – Section 11.8

Option 1

1. Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
2. Set the VBW $\geq 3 \times$ RBW.
3. Detector = **Peak**.
4. Trace mode = **max hold**.
5. Sweep = No faster than coupled (auto) time.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

Option 2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times$ RBW, and peak detector with maximum hold) is implemented by the instrumentation function.


When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

5.2.3. Test Results

Test Mode	Tested Channel	Test Results (MHz)
TM 1	Lowest	0.650
	Middle	0.648
	Highest	0.646


6 dB Bandwidth

TM 1 Test Channel : Lowest




6 dB Bandwidth

TM 1 Test Channel : Middle



6 dB Bandwidth

TM 1 Test Channel : Highest



5.3. Power Spectral Density

■ Test requirements and limit, Part 15.247(e) & RSS-247[6.3.1]

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.3.1. Test Setup

Refer to the APPENDIX I.

5.3.2. Test Procedures

- KDB558074 D01v05r02 - Section 8.4
- ANSI C63.10-2020 – Section 11.10.2

Method PKPSD (peak PSD)


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span >1.5 times the DTS bandwidth.
3. Set the RBW to **3 kHz ≤ RBW ≤ 100 kHz**.
4. Set the VBW ≥ **3 x RBW**.
5. Detector = **peak**.
6. Sweep time = No faster than coupled (auto) time.
7. Trace mode = **max hold**.
8. Allow trace to fully stabilize.
9. Use the **peak marker function** to determine the maximum amplitude level within the RBW.
10. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

5.3.3. Test Results

Test Mode	Tested Channel	RBW	PKPSD (dBm)	Limit (dBm / 3 kHz)
TM 1	Lowest	3 kHz	-24.13	8.00
	Middle	3 kHz	-24.14	8.00
	Highest	3 kHz	-23.45	8.00


Maximum PKPSD

TM 1 Test Channel : Lowest




Maximum PKPSD

TM 1 Test Channel : Middle



Maximum PKPSD

TM 1 Test Channel : Highest



5.4. Unwanted Emissions (Conducted)

■ Test requirements and limit, Part 15.247(d) & RSS-247[6.6]

In any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions :

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured inband average PSD level.

In either case, attenuation to levels below the general emission limits specified in §15.209(a) is not required.

5.4.1. Test Setup

Refer to the APPENDIX I including path loss

5.4.2. Test Procedures

- KDB558074 D01v05r02 - Section 8.5
- ANSI C63.10-2020 – Section 11.11

Reference level measurement

1. Set instrument center frequency to DTS channel center frequency.
2. Set the span to ≥ 1.5 times the DTS bandwidth.
3. Set the RBW = 100 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = No faster than coupled (auto) time.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum PSD level

LIMIT LINE = 20 dB below of the reference level.

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the RBW = **100 kHz.(Actual 1 MHz , See below note)**
3. Set the VBW $\geq 3 \times$ RBW.(Actual 3 MHz, See below note)
4. Detector = **peak**.
5. Sweep time = No faster than coupled (auto) time.
6. Trace mode = **max hold**.
7. Allow the trace to stabilize
8. Use the peak marker function to determine the maximum amplitude level.


Note: The unwanted(conducted) emission was tested with below settings.

Frequency range	RBW	VBW	Detector	Trace	Sweep Point
9 kHz ~ 30 MHz	100 kHz	300 kHz	Peak	Max Hold	40 001
30 MHz ~ 10 GHz	1 MHz	3 MHz			
10 GHz ~ 25 GHz	1 MHz	3 MHz			


If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2 001 to get accurate emission level within 100 kHz BW.

5.4.3. Test Results


TM 1 Reference (Test Channel : Lowest)




TM 1 Low Band-edge (Test Channel : Lowest)




TM 1 Conducted Spurious Emissions 1 (Test Channel : Lowest)




TM 1 Conducted Spurious Emissions 2 (Test Channel : Lowest)




TM 1 Conducted Spurious Emissions 2 (Test Channel : Lowest) - Zoom




TM 1 Conducted Spurious Emissions 3 (Test Channel : Lowest)




TM 1 Reference (Test Channel : Middle)




TM 1 Conducted Spurious Emissions 1 (Test Channel : Middle)




TM 1 Conducted Spurious Emissions 2 (Test Channel : Middle)




TM 1 Conducted Spurious Emissions 2 (Test Channel : Middle) - Zoom




TM 1 Conducted Spurious Emissions 3 (Test Channel : Middle)




TM 1 Reference (Test Channel : Highest)




TM 1 High Band-edge (Test Channel : Highest)




TM 1 Conducted Spurious Emissions 1 (Test Channel : Highest)




TM 1 Conducted Spurious Emissions 2 (Test Channel : Highest)



TM 1 Conducted Spurious Emissions 2 (Test Channel : Highest) - Zoom



TM 1 Conducted Spurious Emissions 3 (Test Channel : Highest)



5.5. Unwanted Emissions (Radiated)

■ Test Requirements and limit,

Part 15.247(d), Part 15.209, Part 15.205 & RSS-247[6.6], RSS-Gen[7.4.3], RSS-Gen[7.5]

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of Part 15.247 the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

- Part 15.209 & RSS-Gen[7.4.3]: General requirements

Frequency (MHz)	FCC Limit (uV/m)	ISED Limit (uA/m)	Measurement Distance (m)
0.009 – 0.490	2 400 / F (kHz)	6.37/F (F in kHz)	300
0.490 – 1.705	24 000 / F (kHz)	63.7/F (F in kHz)	30
1.705 – 30.0	30	0.08	30

Frequency (MHz)	FCC Limit (uV/m)	ISED Limit (uV/m)	Measurement Distance (m)
30 ~ 88	100 **	100	3
88 ~ 216	150 **	150	3
216 ~ 960	200 **	200	3
Above 960	500	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §15.231 and 15.241.

- Part 15.205(a): Restricted band of operation

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.414 25 ~ 8.414 75	108 ~ 121.94	1 300 ~ 1 427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1 435 ~ 1 626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.173 5 ~ 2.190 5	12.519 75 ~ 12.520 25	149.9 ~ 150.05	1 645.5 ~ 1 646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.576 75 ~ 12.577 25	156.524 75 ~ 156.525	1 660 ~ 1 710	8.025 ~ 8.5	22.01 ~ 23.12
4.177 25 ~ 4.177 75	13.36 ~ 13.41	25	1 718.8 ~ 1 722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.207 25 ~ 4.207 75	16.42 ~ 16.423	156.7 ~ 156.9	2 200 ~ 2 300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.694 75 ~ 16.695 25	162.012 5 ~ 167.17	2 310 ~ 2 390	10.6 ~ 12.7	36.43 ~ 36.5
6.267 75 ~ 6.268 25	16.804 25 ~ 16.804 75	167.72 ~ 173.2	2 483.5 ~ 2 500	13.25 ~ 13.4	Above 38.6
6.311 75 ~ 6.312 25	25.5 ~ 25.67	240 ~ 285	2 655 ~ 2 900		
8.291 ~ 8.294	37.5 ~ 38.25	322 ~ 335.4	3 260 ~ 3 267		
8.362 ~ 8.366	73 ~ 74.6	399.90 ~ 410	3 332 ~ 3 339		
8.376 25 ~ 8.386 75	74.8 ~ 75.2	608 ~ 614	3 345.8 ~ 3 358		
		960 ~ 1 240	3 600 ~ 4 400		

- RSS-Gen[7.5]: Restricted frequency bands

MHz	MHz	MHz	MHz	MHz	GHz
0.090 ~ 0.110	8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3 345.8 ~ 3 358	9.0 ~ 9.2
0.495 ~ 0.505	8.376 25 ~ 8.386 75	74.8 ~ 75.2	960 ~ 1 427	3 500 ~ 4 400	9.3 ~ 9.5
2.173 5 ~ 2.190 5	8.414 25 ~ 8.414 75	108 ~ 138	1 435 ~ 1 626.5	4 500 ~ 5 150	10.6 ~ 12.7
3.020 ~ 3.026	12.29 ~ 12.293	149.9 ~ 150.05	1 645.5 ~ 1 646.5	5 350 ~ 5 460	13.25 ~ 13.4
4.125 ~ 4.128	12.519 75 ~ 12.520 25	156.524 75 ~	1 660 ~ 1 710	7 250 ~ 7 750	14.47 ~ 14.5
4.177 25 ~ 4.177 75	12.576 75 ~ 12.577 25	156.525 25	1 718.8 ~ 1 722.2	8 025 ~ 8 500	15.35 ~ 16.2
4.207 25 ~ 4.207 75	13.36 ~ 13.41	156.7 ~ 156.9	2 200 ~ 2 300		17.7 ~ 21.4
5.677 ~ 5.683	16.42 ~ 16.423	162.01 25 ~ 167.17	2 310 ~ 2 390		22.01 ~ 23.12
6.215 ~ 6.218	16.694 75 ~ 16.695 25	167.72 ~ 173.2	2 483.5 ~ 2 500		23.6 ~ 24.0
6.267 75 ~ 6.268 25	16.804 25 ~ 16.804 75	240 ~ 285	2 655 ~ 2 900		31.2 ~ 31.8
6.311 75 ~ 6.312 25	25.5 ~ 25.67	322 ~ 335.4	3 260 ~ 3 267		36.43 ~ 36.5
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3 332 ~ 3 339		Above 38.6

5.5.1. Test Setup

Refer to the APPENDIX I.

5.5.2. Test Procedures

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

Note: Measurement Instrument Setting for Radiated Emission Measurements.

- KDB558074 D01v05r02 - Section 8.6
- ANSI C63.10-2020 – Section 11.12

Frequency Range Below 1 GHz

RBW = As specified in table, VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak^{Note1} or Quasi Peak,

Trace mode = Max Hold until the trace stabilize

Frequency	RBW
9 kHz - 150 kHz	200 Hz - 300 Hz
0.15 MHz - 30 MHz	9 kHz -10 kHz
30 MHz - 1 000 MHz	100 kHz - 120 kHz

Note1: Measurements were performed using the peak detector.

The data measured using the peak detector of a spectrum analyzer will represent the worst-case results.

Frequency Range > 1 GHz

Peak Measurement > 1 GHz



RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Sweep time = Auto, Trace mode = Max Hold until the trace stabilizes

Average Measurement > 1 GHz

The average result was calculated from the measured peak result by applying the duty cycle correction factor.

Note: The EUT operates with a limited duty cycle. The worst-case duty cycle is shown below.

Duty cycle correction factor information.



Transmit on time	Repetition period	Transmit on time within 100 ms	Duty cycle correction factor
289 us	2.05 s	289 us	$20 \times \log (289 \text{ us}/100 \text{ ms}) = -50.78 \text{ dB}$

5.5.3. Test Results

- Test Notes

- The radiated emissions were investigated 9 kHz to 25 GHz. And no other spurious and harmonic emissions were found below listed frequencies.
- Information of Distance Correction Factor
For finding emissions, measurements may be performed at a distance closer than that specified in the regulations.
In this case, the distance factor is applied to the result.
- Calculation of distance correction factor
At frequencies below 30 MHz = $40 \log(\text{tested distance} / \text{specified distance})$
At frequencies at or above 30 MHz = $20 \log(\text{tested distance} / \text{specified distance})$
When distance factor is "N/A", the measurements were performed at the specified distance and distance factor is not applied.
- Sample Calculation.
 $\text{Margin} = \text{Limit} - \text{Result}$ / $\text{Result} = \text{Reading} + \text{TF} + \text{DCCF} + \text{DCF}$ / $\text{TF} = \text{AF} + \text{CL} + \text{HL} + \text{AL} - \text{AG}$
Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain, HL = High pass filter Loss, AL = Attenuator Loss,
DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- Please refer to the appendix II for worst-case plots.

Frequency Range : 9 kHz ~ 25 GHz_TM 1

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 386.39	H	X	PK	42.23	7.87	N/A	N/A	50.10	74.00	23.90
2 386.39	H	X	AV	42.23	7.87	-50.78	N/A	-0.68	54.00	54.68
4 803.48	H	X	PK	57.31	10.45	N/A	N/A	67.76	74.00	6.24
4 803.48	H	X	AV	57.31	10.45	-50.78	N/A	16.98	54.00	37.02
7 206.75	V	Z	PK	57.41	13.57	N/A	N/A	70.98	74.00	3.02
7 206.75	V	Z	AV	57.41	13.57	-50.78	N/A	20.20	54.00	33.80

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4 851.60	H	X	PK	57.02	10.63	N/A	N/A	67.65	74.00	6.35
4 851.60	H	X	AV	57.02	10.63	-50.78	N/A	16.87	54.00	37.13
7 278.81	V	Z	PK	58.39	13.57	N/A	N/A	71.96	74.00	2.04
7 278.81	V	Z	AV	58.39	13.57	-50.78	N/A	21.18	54.00	32.82

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2 483.65	H	X	PK	47.83	8.26	N/A	N/A	56.09	74.00	17.91
2 483.65	H	X	AV	47.83	8.26	-50.78	N/A	5.31	54.00	48.69
4 959.68	H	X	PK	52.76	10.89	N/A	N/A	63.65	74.00	10.35
4 959.68	H	X	AV	52.76	10.89	-50.78	N/A	12.87	54.00	41.13
7 439.39	V	Z	PK	58.97	13.65	N/A	N/A	72.62	74.00	1.38
7 439.39	V	Z	AV	58.97	13.65	-50.78	N/A	21.84	54.00	32.16

5.6. AC Power-Line Conducted Emissions

■ Test Requirements and limit, Part 15.207 & RSS-Gen[7.4.2]

An intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5.0	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

5.6.1. Test Setup

NA

5.6.2. Test Procedures

Conducted emissions from the EUT were measured according to the ANSI C63.10-2020.

1. The test procedure is performed in a shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

5.6.3. Test Results

NA

5.7. Occupied Bandwidth

■ Test Requirements, RSS-Gen [5.1]

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99 % emission bandwidth, as calculated or measured.

5.7.1. Test Setup

Refer to the APPENDIX I.

5.7.2. Test Procedures

The 99 % power bandwidth was measured with a calibrated spectrum analyzer.


The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately $3 \times \text{RBW}$.

5.7.3. Test Results

Test Mode	Tested Channel	Test Results (MHz)
TM 1	Lowest	1.017
	Middle	1.016
	Highest	1.019


Occupied Bandwidth

TM 1 Test Channel : Lowest



Occupied Bandwidth

TM 1 Test Channel : Middle



Occupied Bandwidth


TM 1 Test Channel : Highest




APPENDIX I

Test set up diagrams

▪ Radiated Measurement



▪ Conducted Measurement



Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	0.51	15	1.62
1	0.76	20	1.72
2.402 & 2.426 & 2.480	0.96	25	1.93
5	0.99	-	-
10	1.19	-	-

Note 1 : The path loss from EUT to Spectrum analyzer was measured and used for test.

Path loss (S/A's correction factor) = Cable A


(Attenuator, Applied only when it was used externally)

APPENDIX II

Unwanted Emissions (Radiated) Test Plot


TM 1 & Lowest & X & Hor

Detector Mode : PK




TM 1 & Highest & X & Hor

Detector Mode : PK



TM 1 & Highest & Z & Ver

Detector Mode : PK



- End of test report -