

# TEST REPORT

of


FCC Part 15 Subpart C §15.209, §15.231  
IC RSS-210 Issue 9, RSS-Gen Issue 5

FCC ID: 2AD5KMWB300  
IC Certification: 22232-MWB300

Equipment Under Test : SMARTKEY BAND  
Model Name : MWB-300A7  
Variant Model Name : MWB-300A3  
Applicant : PARTRON CO., LTD.  
Manufacturer : PARTRON CO., LTD.  
Date of Receipt : 2019.05.22  
Date of Test(s) : 2019.05.27 ~ 2019.06.18  
Date of Issue : 2019.07.04

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Jinhyoung Cho

Date:

2019.07.04

Technical  
Manager:



Jungmin Yang

Date:

2019.07.04

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## TABLE OF CONTENTS

|                                                             |    |
|-------------------------------------------------------------|----|
| 1. General Information -----                                | 3  |
| 2. Field Strength of Fundamental and Spurious Emission----- | 7  |
| 3. Bandwidth of Operation Frequency-----                    | 15 |
| 4. Occupied Bandwidth-----                                  | 17 |
| 5. Transmission Time-----                                   | 19 |
| 6. Duty Cycle Correction Factor-----                        | 21 |
| 7. Antenna Requirement-----                                 | 23 |

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 1. General Information

### 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : +82 31 688 0901

FAX : +82 31 688 0921

### 1.2. Details of Applicant

Applicant : PARTRON CO., LTD.

Address : 22, Samsung1-ro 2-gil, Hwaseong-si, Gyeonggi-do, Korea

Contact Person : Byun, Jae-beom

Phone No. : +82 31 201 7906

### 1.3. Details of Manufacturer

Company : Same as applicant

Address : Same as applicant

### 1.4. Description of EUT

|                    |                                |
|--------------------|--------------------------------|
| Kind of Product    | SMARTKEY BAND                  |
| Model Name         | MWB-300A7                      |
| Variant Model Name | MWB-300A3                      |
| Power Supply       | DC 3.7 V                       |
| Frequency Range    | Tx: 433.92 MHz, Rx: 125.00 kHz |
| Modulation Type    | FSK                            |
| Number of Channel  | 1                              |
| Antenna Type       | PCB Antenna                    |

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

## 1.5. Test Equipment List

| Equipment         | Manufacturer                | Model                                | S/N                    | Cal. Date     | Cal. Interval | Cal. Due      |
|-------------------|-----------------------------|--------------------------------------|------------------------|---------------|---------------|---------------|
| Signal Generator  | R&S                         | SMBV100A                             | 255834                 | Jun. 10, 2019 | Annual        | Jun. 10, 2020 |
| Spectrum Analyzer | R&S                         | FSV30                                | 103210                 | Dec. 05, 2018 | Annual        | Dec. 05, 2019 |
| Spectrum Analyzer | Agilent                     | N9020A                               | MY53421758             | Sep. 21, 2018 | Annual        | Sep. 21, 2019 |
| Preamplifier      | H.P.                        | 8447F                                | 2944A03909             | Aug. 07, 2018 | Annual        | Aug. 07, 2019 |
| Preamplifier      | Agilent                     | 8449B                                | 3008A01932             | Feb. 22, 2019 | Annual        | Feb. 22, 2020 |
| High Pass Filter  | Mini-Circuits               | NHP-800+                             | V8207600724            | Mar. 08, 2019 | Annual        | Mar. 08, 2020 |
| High Pass Filter  | Wainwright Instrument GmbH  | WHKX10-900-1000-18000-40ss           | 7                      | Mar. 12, 2019 | Annual        | Mar. 12, 2020 |
| Loop Antenna      | Schwarzbeck Mess-Elektronik | FMZB 1519                            | 1519-039               | Aug. 23, 2017 | Biennial      | Aug. 23, 2019 |
| Bilog Antenna     | Schwarzbeck Mess-Elektronik | VULB9163                             | 01126                  | Mar. 26, 2018 | Biennial      | Mar. 26, 2020 |
| Horn Antenna      | R&S                         | HF907                                | 100145                 | Jan. 31, 2019 | Biennial      | Jan. 31, 2021 |
| Test Receiver     | R&S                         | ESU26                                | 100109                 | Jan. 31, 2019 | Annual        | Jan. 31, 2020 |
| Controller        | Innco systems GmbH          | CONTROLLER CO3000-4P                 | CO3000/963/3 8330516/L | N.C.R.        | N/A           | N.C.R.        |
| Turn Table        | Innco systems GmbH          | DS 1200 S                            | N/A                    | N.C.R.        | N/A           | N.C.R.        |
| Antenna Master    | Innco systems GmbH          | MA4640-XP-ET                         | MA4640/536/3 8330516/L | N.C.R.        | N/A           | N.C.R.        |
| Anechoic Chamber  | SY Corporation              | L × W × H<br>(9.6 m × 6.4 m × 6.6 m) | N/A                    | N.C.R.        | N/A           | N.C.R.        |
| Coaxial Cable     | SUCOFLEX                    | 104 (3 m)                            | MY3258414              | Jan. 04, 2019 | Semi-annual   | Jul. 04, 2019 |
| Coaxial Cable     | SUCOFLEX                    | 104 (10 m)                           | MY3145814              | Jan. 04, 2019 | Semi-annual   | Jul. 04, 2019 |

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm × 297 mm)

## 1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

| Applied standard: FCC Part15 Subpart C, IC RSS-210 Issue 9, RSS-Gen Issue 5 |                                                              |                                                                              |                   |
|-----------------------------------------------------------------------------|--------------------------------------------------------------|------------------------------------------------------------------------------|-------------------|
| Section in FCC                                                              | Section in IC                                                | Test Item                                                                    | Result            |
| 15.209(a)<br>15.231(b)                                                      | RSS-210 Issue 9,<br>A.1, Table A1<br>RSS-Gen Issue 5,<br>8.9 | Radiated emission,<br>Spurious Emission and<br>Field Strength of Fundamental | Complied          |
| 15.231(c)                                                                   | -                                                            | Bandwidth of Operation Frequency                                             | Complied          |
| 15.231(a)                                                                   | RSS-210 Issue 9,<br>A.1.1                                    | Transmission Time                                                            | Complied          |
| -                                                                           | RSS-210 Issue 9,<br>A.1.3<br>RSS-Gen Issue 5,<br>6.7         | Occupied Bandwidth                                                           | Complied          |
| 15.207                                                                      | RSS-Gen Issue 5<br>8.8                                       | AC Power Line Conducted Emission                                             | N/A <sup>1)</sup> |

### Note;

1) The AC power line test was not performed because the EUT does not operate while charging.

## 1.7. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter                             | Uncertainty (dB) |
|---------------------------------------|------------------|
| Occupied Bandwidth                    | ± 9.66 kHz       |
| Radiated Disturbance, 9 kHz to 30 MHz | ± 3.59 dB        |
| Radiated Disturbance, below 1 GHz     | ± 5.88 dB        |
| Radiated Disturbance, above 1 GHz     | ± 5.94 dB        |

Uncertainty figures are valid to a confidence level of 95 %.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 1.8. Test Report Revision

| Revision | Report Number          | Date of Issue | Description         |
|----------|------------------------|---------------|---------------------|
| 0        | F690501/RF-RTL013989   | 2019.06.24    | Initial             |
| 1        | F690501/RF-RTL013989-1 | 2019.07.04    | Revised test report |

## 1.9. Description of Variant Model

|                                           | Basic Model                | Variant Model              |
|-------------------------------------------|----------------------------|----------------------------|
|                                           | MWB-300A7                  | MWB-300A3                  |
| ImmoInterface                             | 3D                         | 3D                         |
| Transponder                               | HT-2, HT-3, HT-AES, HT-Pro | HT-2, HT-3, HT-AES, HT-Pro |
| EROM                                      | 16 KB / 24 KB / 32 KB      | 16 KB / 24 KB / 32 KB      |
| EEPROM                                    | 2048B                      | 2048B                      |
| Package                                   | HVQFN32, HVQFN40           | HVQFN32                    |
| LF cap tune                               | No                         | No                         |
| LF polling                                | yes                        | No                         |
| LF 3D Boost Mode<br>(0.1mVpp, 14 $\mu$ A) | No                         | No                         |
| Mechanical Motion<br>Sensor IF            | yes                        | No                         |

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)


## 2. Field Strength of Fundamental and Spurious Emission

### 2.1. Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission below 30 MHz.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz.



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10<sup>th</sup> harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 2.2. Limit

### 2.2.1. FCC

#### 2.2.1.1. Radiated Emission Limits; general requirements.

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meter) |
|-----------------|-----------------------------------|------------------------------|
| 0.009-0.490     | 2 400/F(kHz)                      | 300                          |
| 0.490-1.705     | 24 000/F(kHz)                     | 30                           |
| 1.705-30.0      | 30                                | 30                           |
| 30-88           | 100**                             | 3                            |
| 88-216          | 150**                             | 3                            |
| 216-960         | 200**                             | 3                            |
| Above 960       | 500                               | 3                            |

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

#### 2.2.1.2. Periodic operation in the band 40.66-40.70 MHz and above 70 MHz

According to §15.231(b), in addition to the provisions of §15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

| Fundamental Frequency (MHz) | Field Strength of Fundamental (microvolts/meter) | Field Strength of Spurious Emissions (microvolts/meter) |
|-----------------------------|--------------------------------------------------|---------------------------------------------------------|
| 40.66-40.70                 | 2,250                                            | 225                                                     |
| 70-130                      | 1,250                                            | 125                                                     |
| 130-174                     | <sup>1</sup> 1,250 to 3,750                      | <sup>1</sup> 125 to 375                                 |
| 174-260                     | 3,750                                            | 375                                                     |
| 260-470                     | <sup>1</sup> 3,750 to 12,500                     | <sup>1</sup> 375 to 1,250                               |
| Above 470                   | 12,500                                           | 1,250                                                   |

<sup>1</sup>linear interpolations

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz,  $\mu\text{V}/\text{m}$  at 3 meters =  $56.81818(F) - 6136.3636$ ; for the band 260-470 MHz,  $\mu\text{V}/\text{m}$  at 3 meters =  $41.6667(F) - 7083.3333$ . The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 2.2.2. IC

### 2.2.2.1. Transmitter Emission Limits

According to RSS-Gen Issue 5, 8.9.

Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

**Table 5 - General field strength limits at frequencies above 30 MHz**

| Frequency (MHz) | Field Strength ( $\mu V/m$ at 3 m) |
|-----------------|------------------------------------|
| 30-88           | 100                                |
| 88-216          | 150                                |
| 216-960         | 200                                |
| Above 960       | 500                                |

**Table 6 - General field strength limits at frequencies below 30 MHz**

| Frequency              | Magnetic Field Strength (H-Field) ( $\mu A/m$ ) | Measurement Distance (m) |
|------------------------|-------------------------------------------------|--------------------------|
| 9-490 kHz <sup>1</sup> | 6.37/F (F in kHz)                               | 300                      |
| 490-1 705 kHz          | 63.7/F (F in kHz)                               | 30                       |
| 1.705-30 MHz           | 0.08                                            | 30                       |

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

### 2.2.2.2. Momentarily Operated Devices

According to A.1 of RSS-210 Issue 9.

The frequency bands and field strength limits in tables A1 and A2 of this annex are reserved exclusively for the transmission of a control signal, such as that used with alarm systems, door openers, remote switches, etc. Data may be sent with a control signal. Radio control of toys or model aircraft, as well as continuous transmissions, such as voice or video, are not permitted, except as provided in Section A.1.4 below.

**Table A1 - Permissible Field Strength Limits for Momentarily Operated Devices**

| Fundamental Frequency (MHz),<br>Excluding Restricted Frequency Bands<br>Specified in RSS-Gen | Field Strength of<br>the Fundamental Emissions<br>( $\mu\text{V/m}$ at 3 m) |
|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| 70-130                                                                                       | 1,250                                                                       |
| 130-174                                                                                      | 1,250 to 3,750*                                                             |
| 174-260 <sup>(Note 1)</sup>                                                                  | 3,750                                                                       |
| 260-470 <sup>(Note 1)</sup>                                                                  | 3,750 to 12,500*                                                            |
| Above 470                                                                                    | 12,500                                                                      |

\* Linear interpolation with frequency, f, in MHz:

For 130-174 MHz: Frequency Strength ( $\mu\text{V/m}$ ) = (56.82 x f) - 6136

For 260-470 MHz: Frequency Strength ( $\mu\text{V/m}$ ) = (41.67 x f) - 7083

**Note 1:** Frequency bands 225-328.6 MHz and 335.4-399.9 MHz are designated for the exclusive use of the Government of Canada. Manufacturers should be aware of possible harmful interference and degradation of their licence-exempt radio equipment in these frequency bands.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.10-2013

### 2.3.1. Test Procedures for emission below 30 MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

### 2.3.2. Test Procedures for emission from 30 MHz to 1 000 MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.

### 2.3.3. Test Procedures for emission above 1 GHz

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1 GHz.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

## 2.4. Test Result

Ambient temperature : (23 ± 1) °C  
Relative humidity : 47 % R.H.

### 2.4.1. Field Strength of Fundamental


The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

| Frequency (MHz) | Detect Mode | Ant. Pol. | Reading (dBμV) | AF (dB/m) | CL (dB) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|-------------|-----------|----------------|-----------|---------|-----------------|----------------|-------------|
| 433.96          | Peak        | V         | 48.22          | 22.18     | 5.37    | 75.77           | 100.83         | 25.06       |
| 433.96          | Average     | V         | 40.48          | 22.18     | 5.37    | 68.03           | 80.83          | 12.80       |

#### Remark;

- To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes (X, Y, Z). Worst orthogonal plan of EUT is Y – axis.  
Definition of DUT for three orthogonal planes is described in the test setup photos.
- 3 m Limit (dBμV/m) =  $20\log[41.67(F_{MHz}) - 7083] = 80.83$
- Result = Reading + Antenna Factor + Cable Loss
- Average Reading = Peak Reading + Duty Cycle Correction Factor
- Duty Cycle Correction Factor:  $20\log(T_{on} / 100 \text{ ms}) = 20\log(41.01 / 100) = -7.74$   
-  $T_{on} = 41.01 \text{ ms}$ .  
-  $T_{on+off} = 100 \text{ ms}$  (pulse train is 100 ms instead of 168 ms).

#### - Test plot



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

## 2.4.2. Spurious Emission

The following table shows the highest levels of radiated emissions.

The frequency spectrum from 9 kHz to 4 400 MHz was investigated.

| Radiated Emissions |                |             | Ant. | Correction Factors |               | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP + CL (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 0.009        | Not detected   | -           | -    | -                  | -             | -               | -              | -           |

### Remark;

- To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes (X, Y, Z). Worst orthogonal plan of EUT is **X – axis**.  
Definition of DUT for three orthogonal planes is described in the test setup photos.
- 3 m Limit (dBμV/m) =  $20\log[41.67(F_{MHz}) - 7083] - 20$  dBμV/m = 60.83 dBμV/m
- Correction Factors = AF + AMP + CL
- Actual = Reading + AF + AMP + CL
- Average Reading = Peak Reading + Duty Cycle Correction Factor
- Duty Cycle Correction Factor:  $20\log(T_{on} / 100 \text{ ms}) = 20\log(41.01 / 100) = -7.74$   
-  $T_{on} = 41.01 \text{ ms}$ .  
-  $T_{on+off} = 100 \text{ ms}$  (pulse train is 100 ms instead of 168 ms).
- “\*” means the restricted band.
- According to § 15.31(o), Emission levels are not reported much lower than the limits by over 20 dB.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

### 3. Bandwidth of Operation Frequency

#### 3.1. Test Setup



#### 3.2. Limit

According to §15.231(c), the bandwidth of the emission shall be no wider than 0.25 % of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5 % of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

#### 3.3. Test Procedure

1. The transmitter output is connected to the spectrum analyzer.
2. The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3 x RBW.
3. The bandwidth of fundamental frequency was measured and recorded.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*


**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

### 3.4. Test Result

Ambient temperature : (23 ± 1) °C  
Relative humidity : 47 % R.H.

| Frequency (MHz) | Bandwidth of Operation Frequency (kHz) | Limit (kHz) | Remark                                          |
|-----------------|----------------------------------------|-------------|-------------------------------------------------|
| 433.92          | 97.680                                 | 1 084.80    | The point 20 dB down from the modulated carrier |

#### - Test plot




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

## 4. Occupied Bandwidth

### 4.1. Test Setup



### 4.2. Limit

According to A.1.3 of RSS-210 Issue 9, the 99 % bandwidth of momentarily operated devices shall be less or equal to 0.25 % of the centre frequency for devices operating between 70 MHz and 900 MHz. For devices operating above 900 MHz, the 99 % bandwidth shall be less or equal to 0.5 % of the centre frequency.

### 4.3. Test Procedure

1. The transmitter output is connected to the spectrum analyzer.
2. The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3 x RBW.
3. The bandwidth of fundamental frequency was measured and recorded.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*


**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

## 4.4. Test Result

Ambient temperature : (23 ± 1) °C  
Relative humidity : 47 % R.H.

| Frequency (MHz) | Occupied Bandwidth (kHz) | Limit (kHz) | Remark                  |
|-----------------|--------------------------|-------------|-------------------------|
| 433.92          | 95.514                   | 1 084.80    | 99 % Occupied bandwidth |

### - Test plot



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 5. Transmission Time

### 5.1. Test Setup



### 5.2. Limit

#### 5.2.1. FCC

According to §15.231(a)(1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

#### 5.2.2. IC

According to A1.1 (a) of RSS-210 Issue 9, a manually operated transmitter shall be equipped with a push-to-operate switch and be under manual control at all times during transmission. When released, the transmitter shall cease transmission within no more than 5 seconds of being released.

### 5.3. Test Procedure

1. The transmitter output is connected to the spectrum analyzer.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW = 1 MHz, VBW = 1 MHz, Span = 0 Hz, Sweep Time = 10 sec.
3. The bandwidth of fundamental frequency was measured and recorded.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)


## 5.4. Test Result

Ambient temperature : (23 ± 1) °C

Relative humidity : 47 % R.H.

| Frequency (MHz) | Transmission Time (sec) | Limit (sec)         | Remark |
|-----------------|-------------------------|---------------------|--------|
| 433.92          | 0.39                    | Same or less than 5 | Pass   |

### - Test plot



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 6. Duty Cycle Correction Factor

### 6.1. Test Setup



### 6.2. Limit

None (No dedicated Limit specified in the Rules)

### 6.3. Test Procedure

1. The transmitter output is connected to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW = 1 MHz, VBW = Auto, Span = 0 Hz, Sweep Time = 0.5 sec.

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

## 6.4. Test Result

Ambient temperature : (23 ± 1) °C

Relative humidity : 47 % R.H.

CALCULATION:

Average Reading = Peak Reading (dB $\mu$ V/m) + 20log (Duty Cycle)

In order to determine possible Maximum Modulation percentage, alternations are made to the EUT.  
We measured;

| T <sub>on+off</sub> | T <sub>on</sub> | M % = (T <sub>on</sub> / T <sub>on+off</sub> ) * 100 % | Duty Correction Factor |
|---------------------|-----------------|--------------------------------------------------------|------------------------|
| 100 ms              | 41.01 ms        | 41.01                                                  | -7.74 dB               |

T<sub>on+off</sub> = 100 ms

T<sub>on</sub> = 41.01 ms


Duty Cycle = 20log(T<sub>on</sub> / T<sub>on+off</sub>) = 20log(0.4101) = -7.74 dB

Remark;

- T<sub>on</sub> = 41.01 ms.

- T<sub>on+off</sub> = 100 ms (pulse train is 100 ms instead of 168 ms).

- Test plot



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

## 7. Antenna Requirement

### 7.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 7.2. Antenna Connected Construction

Antenna used in this product is PCB Antenna with gain of -11.48 dB i.

**- End of the Test Report -**

*The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2019.04.24)(1)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)