



MPE ESTIMATION

FCC ID: 2AD66-DMR818SU

1, According to §1.1310, Limit for Occupational / Controlled Exposure

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/300	6
1.5GHz---100GHz	5	6

Note: F= Frequency in MHz

2, Estimation Result

Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm ²)	Limit (mW/cm ²)
450.0125	30.243	30±1(31)	1258.925	1.0	1.26	0.31546	1.5000

$$Pd = \frac{P_{out} * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power in mW.

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna in cm

Conducted power see the test report **HK2607150724-E**, antenna gain=1dBi.

When the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.31546mW/cm² which is <1.5000mW/cm², RF Exposure testing is not required.

-----The End-----