

**FCC RF EXPOSURE REPORT**

EUT	Firewall Appliance
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☒ WLAN: 2.422GHz ~ 2.452GHz ☒ WLAN: 5.180GHz ~ 5.240GHz ☒ WLAN: 5.190GHz ~ 5.230GHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Max. output power	22.50dBm (177.83mW)
Antenna gain (Max)	3.0dBi(Numeric gain:2.0)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Note:

1. The maximum output power is 22.50dBm (177.83mW) at 2462MHz (with numeric 2.0 antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.



TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



Maximum Permissible Exposure

EUT Output Power=177.83mW

Numeric antenna gain=2.0

Substituting the MPE safe distance using $d=20$ cm into **Equation 1** :

Yields

The power density $S = 30 \times 177.83 \times 2.0 / (3770 \times 400) \text{ cm}^2 = 7.075 \times 10^{-3} \text{ mW/cm}^2$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.)