

EMC TEST REPORT



Report No.: 15020077-FCC-E

Supersede Report No.: N/A

Applicant	NXECO INC	
Product Name	Smart Weather-Based 12-zone Irrigation Controller	
Main Model	HWN12-100	
Test Standard	FCC Part 15 Subpart B Class B:2014, ANSI C63.4: 2009	
Test Date	January 28, 2015	
Issue Date	February 03, 2015	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
		
Herith Shi Test Engineer	Alex Liu Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:
SIEMIC (Nanjing-China) Laboratories
2-1 Longcang Avenue Yuhua Economic and
Technology Development Park, Nanjing, China
Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	15020077-FCC-E
Page	3 of 26

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 AC POWER LINE CONDUCTED EMISSIONS.....	8
6.2 RADIATED EMISSIONS.....	11
ANNEX A. TEST INSTRUMENT	13
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	14
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	22
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST.....	25
ANNEX E. DECLARATION OF SIMILARITY	26

Test Report No.	15020077-FCC-E
Page	5 of 26

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15020077-FCC-E	NONE	Original	February 03, 2015

2. Customer information

Applicant Name	NXECO INC
Applicant Add	1300 Briston Street North Suite 100,Office 32,Newport Beach,California 92660 United States
Manufacturer	Nanjing Yansheng electronics,Inc
Manufacturer Add	No 9,Gaohu Road Jiangning district Nanjing

3. Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	986914
IC Test Site No.	4842B-1
Test Software	Labview of SIEMIC version 1.0

Test Report No.	15020077-FCC-E
Page	6 of 26

4. Equipment under Test (EUT) Information

Description of EUT:	Smart Weather-Based 12-zone Irrigation Controller
Main Model:	HWN12-100
Serial Model:	N/A
Date EUT received:	January 26, 2015
Test Date(s):	January 28, 2015
Port:	USB Port, LAN Port, Power Port, Control Port
Input Power:	120V 60Hz
Trade Name :	NXECO
FCC ID:	2AD6UHWN12-100

Test Report No.	15020077-FCC-E
Page	7 of 26

5. Test Summary

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.107; ANSI C63.4: 2009	AC Power Line Conducted Emissions	Compliance
§15.109; ANSI C63.4: 2009	Radiated Emissions	Compliance

Measurement Uncertainty


Test Item	Description	Uncertainty
Radiated Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	3.952dB

6. Measurements, Examination And Derived Results

6.1 AC Power Line Conducted Emissions

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	January 28, 2015
Tested By :	Herith Shi


Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.107	a)	1. For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒														
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBμV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBμV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBμV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.																
		Procedure	2. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.														
			3. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.														

Test Report No.	15020077-FCC-E
Page	9 of 26

Remark	
Result	☒ Pass ☐ Fail
Test Data	☒ Yes ☐ N/A
Test Plot	☒ Yes ☐ N/A

Test Mode:	Normal Working
------------	----------------




Test Data

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
0.60	36.18	56.00	-19.82	30.73	46.00	-15.27	11.01
0.63	36.18	56.00	-19.82	29.71	46.00	-16.29	10.98
0.51	34.73	56.00	-21.27	30.49	46.00	-15.51	11.08
0.78	29.56	56.00	-26.44	24.04	46.00	-21.96	10.86
0.43	30.96	57.25	-26.29	25.84	47.25	-21.41	11.19
0.83	26.86	56.00	-29.14	22.19	46.00	-23.81	10.82

Test Mode: Normal Working



Test Data

Phase Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
0.63	29.01	56.00	-26.99	23.16	46.00	-22.84	10.98
0.61	27.68	56.00	-28.32	22.67	46.00	-23.33	11.00
0.48	30.09	56.37	-26.28	25.06	46.37	-21.32	11.12
1.39	24.21	56.00	-31.79	19.48	46.00	-26.52	10.76
1.23	26.46	56.00	-29.54	21.48	46.00	-24.52	10.73
1.19	26.32	56.00	-29.68	21.37	46.00	-24.63	10.72

6.2 Radiated Emissions

Temperature	20°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	January 28, 2015
Tested By :	Herith Shi

Requirement(s):

Spec	Item	Requirement	Applicable	
47CFR§15.10 7(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges		
		Frequency range (MHz)		Field Strength (µV/m)
		30 – 88		100
		88 – 216		150
		216 960		200
		Above 960		500

Test Setup	
------------	--

Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - For emission frequencies measured below and above 1GHz, set the spectrum analyzer on a 100kHz and 1MHz resolution bandwidth respectively for each frequency measured. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
-----------	---

Remark	
--------	--

Result	☒ Pass ☐ Fail
--------	--

Test Data ☒ Yes

☐ N/A


Test Plot ☒ Yes (See below)

☐ N/A

Test Mode: Normal Working

(Below 1GHz)

Peak Detector 
Quasi Peak Limit 



Test Data

Vertical & Horizontal Polarity Plot @3m

Frequency (MHz)	Quasi Peak (dBμV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBμV/m)	Margin (dB)
886.63	25.68	276.00	H	100.00	-18.52	46.00	-20.32
400.00	45.35	317.00	V	101.00	-28.24	46.00	-0.65
425.02	45.07	329.00	H	100.00	-28.32	46.00	-0.93
200.01	36.14	312.00	H	175.00	-32.04	43.50	-7.36
862.40	41.28	268.00	H	103.00	-18.06	46.00	-4.72
910.93	41.16	282.00	H	101.00	-18.59	46.00	-4.84

Note: The highest frequency of the internal sources of the EUT is less than 108MHz, so the measurement shall only be made up to 1GHz.

Test Report No.	15020077-FCC-E
Page	13 of 26

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted Emissions					
R&S EMI Test Receiver	ESPI3	101216	11/04/2014	11/03/2015	☒
V-LISN	ESH3-Z5	838979/005	09/27/2014	09/26/2015	☒
SIEMIC Labview Conducted Emissions software	V1.0	N/A	N/A	N/A	☒
Radiated Emissions					
Hp Spectrum Analyzer	8563E	3821A09023	10/09/2014	10/08/2015	☒
R&S EMI Receiver	ESPI3	101216	10/09/2014	10/08/2015	☒
Antenna (30MHz~6GHz)	JB6	A121411	04/15/2014	04/14/2015	☒
Hp Agilent Pre-Amplifier	8447F	1937A01160	10/27/2014	10/26/2015	☒
SIEMIC Labview Radiated Emissions software	V1.0	N/A	N/A	N/A	☒

Annex B. EUT And Test Setup Photographs


Annex B.i. Photograph EUT Internal Photo



Front View of EUT



Rear View of EUT



Top View of EUT



Bottom View of EUT

Test Report No.	15020077-FCC-E
Page	16 of 26




Left View of EUT




Right View of EUT

Annex B.ii. Photograph EUT Internal Photo




Uncover- Front View




LCD – Front View

Test Report No.	15020077-FCC-E
Page	18 of 26




LCD – Rear View



EUT PCBA – Front View

Test Report No.	15020077-FCC-E
Page	19 of 26



EUT PCBA – Rear View



EUT – Port Front View

Annex B.iii. Photograph: Test Setup Photo



Conducted Emissions Setup Front View



Conducted Emissions Setup Side View

Test Report No.	15020077-FCC-E
Page	21 of 26




Radiated Emissions Setup Below 1GHz Front View


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.i. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Test Report No.	15020077-FCC-E
Page	24 of 26

Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description	Model	Calibration Date
Gateway Laptop	MS2288 & LXWHF02013951C3CA92200	N/A
Valve(24V AC 50/60Hz)	RAIN BIRD	N/A

Test Report No.	15020077-FCC-E
Page	25 of 26

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see Attachment

Test Report No.	15020077-FCC-E
Page	26 of 26

Annex E. DECLARATION OF SIMILARITY

N/A