

Channel Band width: 5MHz

Channel 5230 (751.0MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5255 (753.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



QPSK_IoT Signal at Bottom (Chain 2)

Channel Band width: 5MHz

Channel 5205 (748.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5230 (751.0MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5255 (753.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



QPSK_IoT Signal at Bottom (Chain 3)

Channel Band width: 5MHz

Channel 5205 (748.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5230 (751.0MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5255 (753.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz



Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



QPSK_IoT Signal at Top (Chain 0)

Channel Band width: 5MHz

Channel 5205 (748.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5230 (751.0MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5255 (753.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



QPSK_IoT Signal at Top (Chain 1)

Channel Band width: 5MHz

Channel 5205 (748.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz



Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5230 (751.0MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5255 (753.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



QPSK_IoT Signal at Top (Chain 2)

Channel Band width: 5MHz

Channel 5205 (748.5MHz)


Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5230 (751.0MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5255 (753.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



QPSK_IoT Signal at Top (Chain 3)

Channel Band width: 5MHz

Channel 5205 (748.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz



Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5230 (751.0MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz



Frequency Range : 775MHz~793MHz



Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz



Channel Band width: 5MHz

Channel 5255 (753.5MHz)

Frequency Range : 9kHz~763MHz



Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~10GHz




Channel Bandwidth: 10MHz

QPSK_IoT Signal at Bottom (Chain 0)



Frequency Range : 1.610GHz~9GHz




QPSK_IoT Signal at Bottom (Chain 1)


Channel Band width: 10MHz

Channel 5230 (751.0MHz)


Frequency Range : 9kHz~763MHz




Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~9GHz




QPSK_IoT Signal at Bottom (Chain 2)


Channel Band width: 10MHz

Channel 5230 (751.0MHz)


Frequency Range : 9kHz~763MHz




Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~9GHz




QPSK_IoT Signal at Bottom (Chain 3)


Channel Band width: 10MHz

Channel 5230 (751.0MHz)


Frequency Range : 9kHz~763MHz




Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~9GHz




QPSK_IoT Signal at Top (Chain 0)


Channel Band width: 10MHz

Channel 5230 (751.0MHz)


Frequency Range : 9kHz~763MHz




Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~9GHz




QPSK_IoT Signal at Top (Chain 1)


Channel Band width: 10MHz

Channel 5230 (751.0MHz)


Frequency Range : 9kHz~763MHz




Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~9GHz




QPSK_IoT Signal at Top (Chain 2)


Channel Band width: 10MHz

Channel 5230 (751.0MHz)


Frequency Range : 9kHz~763MHz




Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~9GHz




QPSK_IoT Signal at Top (Chain 3)


Channel Band width: 10MHz

Channel 5230 (751.0MHz)


Frequency Range : 9kHz~763MHz




Frequency Range : 763MHz~775MHz




Frequency Range : 775MHz~793MHz




Frequency Range : 793MHz~805MHz




Frequency Range : 805MHz~1.559GHz



Frequency Range : 1.559GHz~1.610GHz



Frequency Range : 1.610GHz~9GHz



4.8 Radiated Emission Measurement

4.8.1 Limits of Radiated Emission Measurement

According to FCC 27.53(c), on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, the emission limit equal to -13dBm.

4.8.2 Test Procedure

- a. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels (low, middle and high channel of operational frequency range.)
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution antenna}$.


Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.8.3 Deviation from Test Standard


No deviation.

4.8.4 Test Setup

For Radiated Emission below or equal 1GHz



For Radiated Emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.8.5 Test Results

NB-IOT Guard Band

Below 1GHz


Channel Bandwidth: 10MHz

Mode	TX channel 5230 (751.0MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Han Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	84.32	-57.30	-65.80	0.40	-65.40	-13.00	-52.40
2	181.32	-59.90	-67.20	-3.00	-70.20	-13.00	-57.20
3	349.13	-62.20	-71.60	3.90	-67.70	-13.00	-54.70
4	444.19	-67.20	-72.90	3.50	-69.40	-13.00	-56.40
5	500.45	-65.50	-71.60	3.80	-67.80	-13.00	-54.80
6	601.33	-69.20	-73.60	3.80	-69.80	-13.00	-56.80

Remarks:

1. $ERP (dBm) = S.G \text{ Value (dBm)} + \text{Correction Factor (dB)}$.
2. $\text{Correction Factor (dB)} = \text{Substitution Antenna Gain (dB)} + \text{Cable Loss (dB)}$.




Mode	TX channel 5230 (751.0MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Han Wu		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	82.38	-53.10	-60.20	0.40	-59.80	-13.00	-46.80
2	124.09	-53.90	-59.20	-3.10	-62.30	-13.00	-49.30
3	337.49	-63.60	-70.20	4.00	-66.20	-13.00	-53.20
4	491.72	-64.50	-70.50	3.70	-66.80	-13.00	-53.80
5	583.87	-68.20	-71.70	3.80	-67.90	-13.00	-54.90
6	703.18	-69.70	-69.40	3.50	-65.90	-13.00	-52.90

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



Above 1GHz

QPSK_IoT Signal at Bottom

Channel Bandwidth: 10MHz

Mode	TX channel 5230 (751.0MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Han Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-62.20	-54.70	1.50	-53.20	-13.00	-40.20
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-62.10	-55.70	1.50	-54.20	-13.00	-41.20

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

QPSK_IoT Signal at Top

Channel Bandwidth: 10MHz

Mode	TX channel 5230 (751.0MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Han Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-60.70	-53.20	1.50	-51.70	-13.00	-38.70
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-62.50	-56.10	1.50	-54.60	-13.00	-41.60

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

NB-IOT In-Band

Below 1GHz


Channel Bandwidth: 5MHz

Mode	TX channel 5230 (751.0MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	31.94	-49.50	-30.00	-18.30	-48.30	-13.00	-35.30
2	100.81	-51.80	-60.80	-1.60	-62.40	-13.00	-49.40
3	259.89	-50.20	-55.60	-1.50	-57.10	-13.00	-44.10
4	396.66	-61.60	-67.70	3.30	-64.40	-13.00	-51.40
5	533.43	-67.00	-72.60	3.80	-68.80	-13.00	-55.80
6	952.47	-69.80	-67.30	3.80	-63.50	-13.00	-50.50

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).




Mode	TX channel 5230 (751.0MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	51.34	-40.50	-42.60	-7.30	-49.90	-13.00	-36.90
2	141.55	-52.20	-53.70	-3.00	-56.70	-13.00	-43.70
3	284.14	-55.20	-53.30	-1.60	-54.90	-13.00	-41.90
4	399.57	-62.20	-68.50	3.30	-65.20	-13.00	-52.20
5	799.21	-66.80	-66.20	3.90	-62.30	-13.00	-49.30
6	948.59	-65.20	-61.80	3.70	-58.10	-13.00	-45.10

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).




Channel Bandwidth: 10MHz

Mode	TX channel 5230 (751.0MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Han Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	50.37	-56.4	-51.5	-7.9	-59.4	-13.0	-46.4
2	68.80	-53.2	-61.2	-0.8	-62.0	-13.0	-49.0
3	139.61	-53.7	-58.5	-3.1	-61.6	-13.0	-48.6
4	159.98	-56.5	-61.0	-3.0	-64.0	-13.0	-51.0
5	250.19	-48.3	-55.5	-1.3	-56.8	-13.0	-43.8
6	307.42	-53.2	-63.6	3.9	-59.7	-13.0	-46.7

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).




Mode	TX channel 5230 (751.0MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Han Wu		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	33.88	-36.5	-32.2	-17.1	-49.3	-13.0	-36.3
2	152.22	-52.5	-53.7	-2.8	-56.5	-13.0	-43.5
3	213.33	-52.1	-55.7	-2.0	-57.7	-13.0	-44.7
4	274.44	-54.6	-52.4	-1.6	-54.0	-13.0	-41.0
5	308.39	-55.9	-61.8	3.9	-57.9	-13.0	-44.9
6	379.20	-60.9	-67.1	3.6	-63.5	-13.0	-50.5

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



Above 1GHz

QPSK_IoT Signal at Bottom

Channel Bandwidth: 5MHz

Mode	TX channel 5205 (748.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1497.00	-62.20	-54.90	1.50	-53.40	-13.00	-40.40
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1497.00	-60.80	-54.50	1.50	-53.00	-13.00	-40.00

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

Mode	TX channel 5230 (751.0MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-62.00	-54.50	1.50	-53.00	-13.00	-40.00
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-60.60	-54.30	1.50	-52.80	-13.00	-39.80

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

Mode	TX channel 5255 (753.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1507.00	-62.50	-55.00	1.50	-53.50	-13.00	-40.50
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1507.00	-61.10	-54.70	1.50	-53.20	-13.00	-40.20

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

Channel Bandwidth: 10MHz

Mode	TX channel 5230 (751.0MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Han Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-63.0	-55.6	1.5	-54.1	-13.0	-41.1
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-61.6	-55.3	1.5	-53.8	-13.0	-40.8

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

QPSK_IoT Signal at Top

Channel Bandwidth: 5MHz

Mode	TX channel 5205 (748.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1497.00	-63.20	-55.90	1.50	-54.40	-13.00	-41.40
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1497.00	-61.90	-55.60	1.50	-54.10	-13.00	-41.10

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

Mode	TX channel 5230 (751.0MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-63.00	-55.50	1.50	-54.00	-13.00	-41.00
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-61.80	-55.40	1.50	-53.90	-13.00	-40.90

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

Mode	TX channel 5255 (753.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1507.00	-63.30	-55.90	1.50	-54.40	-13.00	-41.40
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1507.00	-62.10	-55.70	1.50	-54.20	-13.00	-41.20

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

Channel Bandwidth: 10MHz

Mode	TX channel 5230 (751.0MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Han Wu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-62.5	-55.1	1.5	-53.6	-13.0	-40.6
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1502.00	-62.0	-55.6	1.5	-54.1	-13.0	-41.1

Remarks:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---