

MEASUREMENT REPORT

FCC PART 24 Subpart E

FCC ID: 2AD8UAHFIH01

Application: Nokia Solutions and Networks, OY

Application Type: Certification

Product: AirScale Indoor Radio ASiR-pRRH

Model No.: AHFIH

Brand Name: Nokia

FCC Rule Part(s): Part 24 Subpart E

Test Procedure(s): ANSI C63.26-2015

Test Date: October 27 ~ November 11, 2020

Reviewed:

Paddy Chen

(Paddy Chen)

Approved By:

Chenz Ker

(Chenz Ker)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.26-2015. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2006TW0003-U2	Rev. 01	Initial Report	12-05-2020	Valid

Note: This report is prepared for FCC Class II permissive supplement to MRT Original report no. 2006TW0003-U1, to evaluate an updated Duplexer component of the Band 25 circuit and spot check data.

CONTENTS

Description	Page
General Information.....	5
1. INTRODUCTION.....	6
1.1. Scope.....	6
1.2. MRT Test Location	6
2. PRODUCT INFORMATION	7
2.1. Equipment Description	7
2.2. Description of Available Antennas	7
2.3. Test Mode and Channel Detail	7
2.4. EMI Suppression Device(s)/Modifications.....	7
2.5. Labeling Requirements.....	8
2.6. Test Environment Condition.....	8
3. DESCRIPTION of TEST.....	9
3.1. Evaluation Procedure	9
3.2. Radiated Emissions.....	9
4. TEST EQUIPMENT CALIBRATION DATE.....	11
5. MEASUREMENT UNCERTAINTY	12
6. TEST RESULT	13
6.1. Summary.....	13
6.2. Equivalent Isotropically Radiated Power Measurement (Report Only)	14
6.2.1. Test Limit	14
6.2.2. Test Procedures Used	14
6.2.3. Test Setting.....	14
6.2.4. Test Setup	15
6.2.5. Test Result.....	16
6.3. Band Edge Measurement.....	20
6.3.1. Test Limit	20
6.3.2. Test Procedure Used	20
6.3.3. Test Setting.....	20
6.3.4. Test Setup	21
6.3.5. Test Result.....	22
6.4. Radiated Spurious Emissions Measurements	27
6.4.1. Test Limit	27
6.4.2. Test Procedure Used	27

6.4.3.	Test Setting.....	27
6.4.4.	Test Setup	28
6.4.5.	Test Result.....	29
7.	CONCLUSION	33

General Information

Applicant:	Nokia Solutions and Networks, OY
Applicant Address:	2000 W. Lucent Lane, Naperville, Illinois, United States, 60563
Manufacturer:	Nokia Solutions and Networks, OY
Manufacturer Address:	2000 W. Lucent Lane, Naperville, Illinois, United States, 60563
Test Site:	MRT Technology (Taiwan) Co., Ltd
Test Site Address:	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Fuxing Rd., Taoyuan, Taiwan (R.O.C)

- MRT facility is a FCC registered (Reg. No. TW3261) test facility with the site description report on file and is designated by the FCC as an Accredited Test Film.
- MRT facility is an IC registered (MRT Reg. No. 21723-1) test laboratory with the site description on file at Industry Canada.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (TAF) under the American Association for Laboratory Accreditation Program (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC, Industry Taiwan, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	AirScale Indoor Radio ASiR-pRRH
Model No.:	AHFIH
Brand Name:	Nokia
Test Device Serial No.:	NH203500565
Hardware Version:	A103
Software Version:	FL18A
Voltage Range:	PoE: 52Vdc ~ 57Vdc
LTE Operating Band (s):	FDD Band 25
Modulation Type:	QPSK, 16QAM, 64QAM, 256QAM
T _x Frequency Range:	Band 25: 1930 ~ 1995 MHz
R _x Frequency Range:	Band 25: 1850 ~ 1915 MHz

2.2. Description of Available Antennas

Band Support	Antenna Type	Model	Antenna Gain
LTE Band 25	Omni-Directional	CMQ69273P	5.7dBi

2.3. Test Mode and Channel Detail

Spot Check Test Item	Channel Bandwidth	Modulation
Equivalent Isotropically Radiated Power (Report Only)	5 MHz, 10 MHz	QPSK, 16QAM, 64QAM, 256QAM
Band Edge Measurements	15 MHz, 20MHz	QPSK
Radiated Spurious Emissions		QPSK

Note: The spot check test items are based on duplexer change with Band 25 circuit.

2.4. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.5. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

2.6. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20% ~ 75%RH

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedure described in the document titled “American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services (ANSI C63.26-2015) was used in the measurement.

Deviation from measurement procedure.....None

3.2. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable

containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, which produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. TEST EQUIPMENT CALIBRATION DATE

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Active Loop Antenna	SCHWARZBECK	FMZB 1519	MRTSUE06025	1 year	2021/11/13
Bilog Period Antenna	SCHWARZBECK	VULB 9162	MRTSUE06022	1 year	2021/10/13
Broadband Hornantenna	SCHWARZBECK	BBHA 9120D	MRTSUE06023	1 year	2021/10/13
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTSUE06024	1 year	2020/12/29
Broadband Coaxial Preamplifier	SCHWARZBECK	BBV 9718	MRTSUE06176	1 year	2021/11/15
Preamplifier	SCHWARZBECK	BBV 9721	MRTSUE06121	1 year	2021/06/11
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2021/04/14
EMI Test Receiver	R&S	ESR3	MRTSUE06612	1 year	2021/07/31
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTSUE06559	1 year	2021/08/08
EMC Cable	HUBERSUHNER	SF106	MRTSUE06594	1 year	2021/11/14
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTSUE06362	1 year	2021/03/29

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTSUE06446	1 year	2021/06/30
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTSUE06446	1 year	2021/06/30
Wideband Radio Communication Taster	R&S	CMW 500	MRTSUE06243	1 year	2021/11/17
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTSUE06559	1 year	2021/08/08
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2021/04/14
DC Power Supply	GWINSTEK	SPS-606	MRTSUE06016	Check by TRUE RMS MULTIMETER	
TRUE RMS MULTIMETER	FLUKE	117	MRTSUE06080	1 year	2021/05/06
Temperature & Humidity Chamber	TEN BILLION	TTH-B3UP	MRTSUE06051	1 year	2021/11/07
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTSUE06362	1 year	2021/03/29

Software	Version	Function
EMI Software	V3	EMI Test Software

5. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

Conducted Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 2.65dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 9kHz ~ 30MHz: 3.92dB 30MHz ~ 1GHz: 4.25dB 1GHz ~ 18GHz: 4.40dB

6. TEST RESULT

6.1. Summary

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1046; 24.232(a)(2)	Equivalent Isotropically Radiated Power	Refer to Section 6.2	Conducted & Radiated	Pass	Section 6.2
24.238(a)	Band Edge Measurements	Refer to Section 6.3	Conducted	Pass	Section 6.3
2.1053; 24.238(a)	Radiated Spurious Emissions	Refer to Section 6.4	Radiated	Pass	Section 6.4

Notes:

- 1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) The Channel Band-edge, Radiated Spurious Emission were presented the worst test data of modulation & antenna port in the test report.

6.2. Equivalent Isotropically Radiated Power Measurement (Report Only)

6.2.1. Test Limit

The Radiated Equivalent Isotropically Power shall be according to the specific rule Part 24.232(a)(2) that are limited to EIRP of 1640 watts/MHz when transmitting with an emission bandwidth greater than 1 MHz.

6.2.2. Test Procedures Used

KDB 971168 D01v03r01 - Section 5.2.4 & 5.8

ANSI C63.26-2015 - Section 5.2.4.2 & 5.2.7

6.2.3. Test Setting

Average Power Measurement


Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

Radiated Equivalent Isotropically Power Measurement


1. $RBW \geq OBW$
2. $VBW \geq 3 \times RBW$
3. Sweep time $\geq 10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})$
4. Detector = power averaging (rms)
5. Set sweep trigger to "free run"
6. If the EUT can be configured to transmit continuously, then set the trigger to free run
7. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple.
To accurately determine the average power over the on and off time of the transmitter, it can be necessary to increase the number of traces to be averaged above 100, or if using a manually configured sweep time, increase the sweep time
8. The trace was allowed to stabilize
9. Use the peak marker function to determine the peak amplitude level.
10. $EIRP = \text{Output Power Level of S.G} - T_x \text{ Cable Loss} + \text{Antenna Gain of Substitution Antenna}.$

6.2.4. Test Setup

Conducted Measurement of Output Power



Radiated Measurement of Equivalent Isotropically Radiated Power



6.2.5. Test Result

Product	AirScale Indoor Radio ASiR-pRRH	Test Engineer	Peter Xu
Test Site	SR2	Test Date	2020/10/27
Test Configuration	LTE Band 25 (Single Carrier)		

Frequency (MHz)	Channel Bandwidth (MHz)	Ant 0 Power (dBm)	Ant 1 Power (dBm)	Total Power (dBm)
QPSK				
1932.5	5	22.87	22.60	25.75
1962.5	5	23.45	23.19	26.33
1992.5	5	23.88	23.97	26.94
1935.0	10	23.33	23.27	26.31
1962.5	10	23.55	23.27	26.42
1990.0	10	23.86	23.77	26.83
1937.5	15	23.38	23.52	26.46
1962.5	15	23.46	23.44	26.46
1987.5	15	23.72	23.54	26.64
1940.0	20	23.18	22.95	26.08
1962.5	20	23.34	23.27	26.32
1985.0	20	23.81	23.72	26.78
16QAM				
1932.5	5	22.77	22.62	25.71
1962.5	5	23.38	23.27	26.34
1992.5	5	23.86	23.93	26.91
1935.0	10	23.35	23.31	26.34
1962.5	10	23.51	23.40	26.47
1990.0	10	23.87	23.80	26.85
1937.5	15	23.46	23.42	26.45
1962.5	15	23.35	23.33	26.35
1987.5	15	23.80	23.58	26.70
1940.0	20	23.13	22.97	26.06
1962.5	20	23.27	23.25	26.27
1985.0	20	23.72	23.65	26.70

Frequency (MHz)	Channel Bandwidth (MHz)	Ant 0 Power (dBm)	Ant 1 Power (dBm)	Total Power (dBm)
64QAM				
1932.5	5	22.66	22.61	25.65
1962.5	5	23.39	23.10	26.26
1992.5	5	23.97	23.92	26.96
1935.0	10	23.19	23.20	26.21
1962.5	10	23.31	23.24	26.29
1990.0	10	23.83	23.71	26.78
1937.5	15	23.47	23.51	26.50
1962.5	15	23.34	23.22	26.29
1987.5	15	23.77	23.50	26.65
1940.0	20	23.13	22.89	26.02
1962.5	20	23.19	23.18	26.20
1985.0	20	23.78	23.68	26.74
256QAM				
1932.5	5	22.70	22.58	25.65
1962.5	5	23.31	23.21	26.27
1992.5	5	23.81	23.95	26.89
1935.0	10	23.22	23.17	26.21
1962.5	10	23.32	23.26	26.30
1990.0	10	23.72	23.66	26.70
1937.5	15	23.44	23.52	26.49
1962.5	15	23.40	23.37	26.40
1987.5	15	23.67	23.58	26.64
1940.0	20	23.06	23.04	26.06
1962.5	20	23.26	23.22	26.25
1985.0	20	23.81	23.52	26.68

Note: Total Power (dBm) = $10 \cdot \log \{ 10^{[ANT\ 0\ Power\ (dBm) / 10]} + 10^{[ANT\ 1\ Power\ (dBm) / 10]} \}$ (dBm).

Product	AirScale Indoor Radio ASiR-pRRH	Test Engineer	Kevin Ker
Test Site	AC1	Test Date	2020/11/03
Test Configuration	LTE Band 25 (Single Carrier)		

Frequency (MHz)	Channel Bandwidth (MHz)	Reading Level (dBm)	Factor (dB)	EIRP (dBm)	Limit (dBm)
QPSK					
1932.5	5	26.4	5.0	31.4	< 62.15
1962.5	5	26.4	4.9	31.3	< 62.15
1992.5	5	25.2	5.9	31.1	< 62.15
1935.0	10	26.6	4.9	31.5	< 62.15
1962.5	10	26.1	4.9	31.0	< 62.15
1990.0	10	24.9	5.9	30.8	< 62.15
1937.5	15	26.7	4.8	31.5	< 62.15
1962.5	15	26.5	4.9	31.4	< 62.15
1987.5	15	24.8	5.8	30.6	< 62.15
1940.0	20	25.7	4.8	30.5	< 62.15
1962.5	20	26.2	4.9	31.1	< 62.15
1985.0	20	25.7	5.7	31.4	< 62.15
16QAM					
1932.5	5	25.9	5.0	30.9	< 62.15
1962.5	5	26.5	4.9	31.4	< 62.15
1992.5	5	24.8	5.9	30.7	< 62.15
1935.0	10	26.4	4.9	31.3	< 62.15
1962.5	10	25.5	4.9	30.4	< 62.15
1990.0	10	24.8	5.9	30.7	< 62.15
1937.5	15	26.7	4.8	31.5	< 62.15
1962.5	15	26.4	4.9	31.3	< 62.15
1987.5	15	25.0	5.8	30.8	< 62.15
1940.0	20	26.7	4.8	31.5	< 62.15
1962.5	20	26.3	4.9	31.2	< 62.15
1985.0	20	25.1	5.7	30.8	< 62.15

Frequency (MHz)	Channel Bandwidth (MHz)	Reading Level (dBm)	Factor (dB)	EIRP (dBm)	Limit (dBm)
64QAM					
1932.5	5	26.4	5.0	31.4	< 62.15
1962.5	5	26.1	4.9	31.0	< 62.15
1992.5	5	24.7	5.9	30.6	< 62.15
1935.0	10	26.6	4.9	31.5	< 62.15
1962.5	10	25.7	4.9	30.6	< 62.15
1990.0	10	24.6	5.9	30.5	< 62.15
1937.5	15	26.3	4.8	31.1	< 62.15
1962.5	15	26.2	4.9	31.1	< 62.15
1987.5	15	24.8	5.8	30.6	< 62.15
1940.0	20	26.4	4.8	31.2	< 62.15
1962.5	20	25.9	4.9	30.8	< 62.15
1985.0	20	24.9	5.7	30.6	< 62.15
256QAM					
1932.5	5	25.8	5.0	30.8	< 62.15
1962.5	5	26.4	4.9	31.3	< 62.15
1992.5	5	24.5	5.9	30.4	< 62.15
1935.0	10	26.1	4.9	31.0	< 62.15
1962.5	10	25.5	4.9	30.4	< 62.15
1990.0	10	24.7	5.9	30.6	< 62.15
1937.5	15	26.5	4.8	31.3	< 62.15
1962.5	15	26.1	4.9	31.0	< 62.15
1987.5	15	25.0	5.8	30.8	< 62.15
1940.0	20	25.9	4.8	30.7	< 62.15
1962.5	20	25.5	4.9	30.4	< 62.15
1985.0	20	24.8	5.7	30.5	< 62.15

6.3. Band Edge Measurement

6.3.1. Test Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

This device can be implement MIMO function, so the limit of spurious emissions needs to be reduced by $10 \cdot \log(\text{Numbers}_{\text{Ant}})$ according to FCC KDB 662911 D01 guidance.

The limit is adjusted to $-13 \text{ dBm} - 10 \cdot \log(2) = -16.01 \text{ dBm}$

6.3.2. Test Procedure Used

KDB 971168 D01v03r01 - Section 6.1

ANSI C63.26-2015 - Section 5.7.1


6.3.3. Test Setting

1. Set the analyzer frequency to Bottom or Top channel.
1. RBW = The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW;
2. VBW $\geq 3 \cdot \text{RBW}$
3. Sweep time = auto
4. Detector = power averaging (rms)
5. Set sweep trigger to "free run."
6. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple.

To accurately determine the average power over the on and off time of the transmitter, it can be necessary to increase the number of traces to be averaged above 100, or if using a manually configured sweep time, increase the sweep time.

6.3.4. Test Setup

Spectrum Analyzer




6.3.5. Test Result

Product	AirScale Indoor Radio ASiR-pRRH	Test Engineer	Peter Xu
Test Site	SR2	Test Date	2020/10/27
Test Configuration	LTE Band 25 (Single Carrier), QPSK		

Frequency (MHz)	Channel Bandwidth (MHz)	Max Band Edge (dBm)		Limit (dBm)	Result
		Ant 0	Ant 1		
1932.5	5	-34.1	-36.14	≤ -16.01	Pass
1992.5	5	-35.81	-36.61	≤ -16.01	Pass
1935.0	10	-36.70	-38.32	≤ -16.01	Pass
1990.0	10	-37.96	-38.10	≤ -16.01	Pass
1937.5	15	-37.94	-39.45	≤ -16.01	Pass
1987.5	15	-39.19	-38.65	≤ -16.01	Pass
1940.0	20	-39.01	-40.13	≤ -16.01	Pass
1985.0	20	-39.86	-38.66	≤ -16.01	Pass

5MHz Channel Bandwidth - Ant 0

Bottom Channel




Top Channel



5MHz Channel Bandwidth - Ant 1

Bottom Channel




Top Channel



10MHz Channel Bandwidth - Ant 0

Bottom Channel




Top Channel



10MHz Channel Bandwidth - Ant 1

Bottom Channel




Top Channel



15MHz Channel Bandwidth - Ant 0

Bottom Channel




Top Channel



15MHz Channel Bandwidth - Ant 1

Bottom Channel




Top Channel



20MHz Channel Bandwidth - Ant 0

Bottom Channel




Top Channel



20MHz Channel Bandwidth - Ant 1

Bottom Channel



Top Channel



6.4. Radiated Spurious Emissions Measurements

6.4.1. Test Limit

Out of band emissions: The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

$E \text{ (dB}\mu\text{V/m)} = \text{EIRP (dBm)} - 20 \log D + 104.8$; where D is the measurement distance in meters. The emission limit equal to 82.3dB μ V/m.

6.4.2. Test Procedure Used

KDB 971168 D01v03r01 - Section 5.8 & 7


ANSI C63.26-2015 - Section 5.2.7 & 5.5

6.4.3. Test Setting


1. RBW = 100kHz or 1MHz
2. VBW $\geq 3 \times$ RBW
3. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period)
4. Detector = Peak
5. Trace mode = max hold
6. The trace was allowed to stabilize

6.4.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.4.5. Test Result

Product	AirScale Indoor Radio ASiR-pRRH	Test Engineer	Kevin Ker
Test Site	AC1	Test Date	2020/11/11
Test Configuration	LTE Band 25 (Single Carrier), QPSK, BW = 5MHz		

Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
Bottom Channel							
130.9	25.9	16.3	42.2	82.3	-40.1	Peak	Horizontal
195.9	20.7	19.1	39.8	82.3	-42.5	Peak	Horizontal
52.8	21.8	21.5	43.3	82.3	-39.0	Peak	Vertical
189.1	23.4	18.8	42.2	82.3	-40.1	Peak	Vertical
8582.0	42.4	12.7	55.1	82.3	-27.2	Peak	Horizontal
9661.5	44.3	14.7	59.0	82.3	-23.3	Peak	Horizontal
8582.0	37.1	12.7	49.8	82.3	-32.5	Peak	Vertical
9661.5	43.6	14.7	58.3	82.3	-24.0	Peak	Vertical
Middle Channel							
129.9	20.6	16.3	36.9	82.3	-45.4	Peak	Horizontal
193.0	18.3	19.0	37.3	82.3	-45.0	Peak	Horizontal
41.6	17.4	21.3	38.7	82.3	-43.6	Peak	Vertical
186.2	21.1	18.3	39.4	82.3	-42.9	Peak	Vertical
8582.0	40.6	12.7	53.3	82.3	-29.0	Peak	Horizontal
9661.5	42.7	14.7	57.4	82.3	-24.9	Peak	Horizontal
8582.0	40.5	12.7	53.2	82.3	-29.1	Peak	Vertical
9653.0	40.4	14.7	55.1	82.3	-27.2	Peak	Vertical
Top Channel							
132.8	24.3	16.2	40.5	82.3	-41.8	Peak	Horizontal
191.5	21.2	19.0	40.2	82.3	-42.1	Peak	Horizontal
56.2	21.5	20.9	42.4	82.3	-39.9	Peak	Vertical
130.9	25.5	16.3	41.8	82.3	-40.5	Peak	Vertical
8582.0	42.6	12.7	55.3	82.3	-27.0	Peak	Horizontal
11956.5	38.1	17.9	56.0	82.3	-26.3	Peak	Horizontal
8582.0	39.7	12.7	52.4	82.3	-29.9	Peak	Vertical
11948.0	37.0	17.9	54.9	82.3	-27.4	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	AirScale Indoor Radio ASiR-pRRH	Test Engineer	Kevin Ker
Test Site	AC1	Test Date	2020/11/11
Test Configuration	LTE Band 25 (Single Carrier), QPSK, BW = 10MHz		

Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
Bottom Channel							
274.9	9.4	20.9	30.3	82.3	-52.0	Peak	Horizontal
424.8	6.6	24.5	31.1	82.3	-51.2	Peak	Horizontal
56.2	15.8	20.9	36.7	82.3	-45.6	Peak	Vertical
186.2	19.5	18.3	37.8	82.3	-44.5	Peak	Vertical
8582.0	37.0	12.7	49.7	82.3	-32.6	Peak	Horizontal
9670.0	42.0	14.7	56.7	82.3	-25.6	Peak	Horizontal
8590.5	36.2	12.7	48.9	82.3	-33.4	Peak	Vertical
9670.0	38.1	14.7	52.8	82.3	-29.5	Peak	Vertical
Middle Channel							
132.3	20.5	16.2	36.7	82.3	-45.6	Peak	Horizontal
191.0	18.2	19.0	37.2	82.3	-45.1	Peak	Horizontal
41.6	23.9	21.3	45.2	82.3	-37.1	Peak	Vertical
188.1	24.1	18.6	42.7	82.3	-39.6	Peak	Vertical
8582.0	37.0	12.7	49.7	82.3	-32.6	Peak	Horizontal
11778.0	34.0	18.1	52.1	82.3	-30.2	Peak	Horizontal
8582.0	35.7	12.7	48.4	82.3	-33.9	Peak	Vertical
11778.0	34.1	18.1	52.2	82.3	-30.1	Peak	Vertical
Top Channel							
126.0	24.3	16.7	41.0	82.3	-41.3	Peak	Horizontal
198.8	20.7	19.2	39.9	82.3	-42.4	Peak	Horizontal
40.7	23.4	21.2	44.6	82.3	-37.7	Peak	Vertical
188.6	25.0	18.7	43.7	82.3	-38.6	Peak	Vertical
8582.0	37.1	12.7	49.8	82.3	-32.5	Peak	Horizontal
11939.5	36.2	17.9	54.1	82.3	-28.2	Peak	Horizontal
8582.0	35.5	12.7	48.2	82.3	-34.1	Peak	Vertical
11939.5	34.3	17.9	52.2	82.3	-30.1	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	AirScale Indoor Radio ASiR-pRRH	Test Engineer	Kevin Ker
Test Site	AC1	Test Date	2020/11/11
Test Configuration	LTE Band 25 (Single Carrier), QPSK, BW = 15MHz		

Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
Bottom Channel							
274.9	9.6	20.9	30.5	82.3	-51.8	Peak	Horizontal
406.4	7.1	24.2	31.3	82.3	-51.0	Peak	Horizontal
38.2	13.1	20.4	33.5	82.3	-48.8	Peak	Vertical
192.0	14.3	19.0	33.3	82.3	-49.0	Peak	Vertical
8565.0	35.1	12.6	47.7	82.3	-34.6	Peak	Horizontal
11786.5	33.4	18.1	51.5	82.3	-30.8	Peak	Horizontal
8590.5	34.0	12.7	46.7	82.3	-35.6	Peak	Vertical
11778.0	34.2	18.1	52.3	82.3	-30.0	Peak	Vertical
Middle Channel							
274.9	11.0	20.9	31.9	82.3	-50.4	Peak	Horizontal
424.8	7.5	24.5	32.0	82.3	-50.3	Peak	Horizontal
39.2	12.9	20.8	33.7	82.3	-48.6	Peak	Vertical
189.6	13.2	18.8	32.0	82.3	-50.3	Peak	Vertical
8590.5	35.6	12.7	48.3	82.3	-34.0	Peak	Horizontal
11769.5	33.0	18.1	51.1	82.3	-31.2	Peak	Horizontal
8582.0	33.7	12.7	46.4	82.3	-35.9	Peak	Vertical
11778.0	33.4	18.1	51.5	82.3	-30.8	Peak	Vertical
Top Channel							
193.4	10.6	19.0	29.6	82.3	-52.7	Peak	Horizontal
380.7	8.3	23.7	32.0	82.3	-50.3	Peak	Horizontal
38.7	13.9	20.6	34.5	82.3	-47.8	Peak	Vertical
194.9	11.6	19.1	30.7	82.3	-51.6	Peak	Vertical
7179.5	34.4	10.8	45.2	82.3	-37.1	Peak	Horizontal
10673.0	33.5	17.3	50.8	82.3	-31.5	Peak	Horizontal
8599.0	34.7	12.7	47.4	82.3	-34.9	Peak	Vertical
10775.0	31.8	17.5	49.3	82.3	-33.0	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	AirScale Indoor Radio ASiR-pRRH	Test Engineer	Kevin Ker
Test Site	AC1	Test Date	2020/11/11
Test Configuration	LTE Band 25 (Single Carrier), QPSK, BW = 20MHz		

Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
Bottom Channel							
92.1	12.0	17.4	29.4	82.3	-52.9	Peak	Horizontal
193.9	12.7	19.0	31.7	82.3	-50.6	Peak	Horizontal
38.7	14.6	20.6	35.2	82.3	-47.1	Peak	Vertical
193.4	9.3	19.0	28.3	82.3	-54.0	Peak	Vertical
7205.0	34.6	10.9	45.5	82.3	-36.8	Peak	Horizontal
9687.0	35.6	14.8	50.4	82.3	-31.9	Peak	Horizontal
8582.0	35.4	12.7	48.1	82.3	-34.2	Peak	Vertical
11642.0	32.7	18.3	51.0	82.3	-31.3	Peak	Vertical
Middle Channel							
193.9	12.6	19.0	31.6	82.3	-50.7	Peak	Horizontal
275.9	9.1	20.9	30.0	82.3	-52.3	Peak	Horizontal
38.2	12.6	20.4	33.0	82.3	-49.3	Peak	Vertical
194.4	11.0	19.1	30.1	82.3	-52.2	Peak	Vertical
8590.5	34.3	12.7	47.0	82.3	-35.3	Peak	Horizontal
11786.5	33.8	18.1	51.9	82.3	-30.4	Peak	Horizontal
7196.5	34.9	10.9	45.8	82.3	-36.5	Peak	Vertical
11939.5	33.2	17.9	51.1	82.3	-31.2	Peak	Vertical
Top Channel							
274.9	10.1	20.9	31.0	82.3	-51.3	Peak	Horizontal
374.8	7.9	23.6	31.5	82.3	-50.8	Peak	Horizontal
38.2	13.7	20.4	34.1	82.3	-48.2	Peak	Vertical
189.6	13.4	18.8	32.2	82.3	-50.1	Peak	Vertical
9236.5	33.7	14.0	47.7	82.3	-34.6	Peak	Horizontal
11897.0	33.7	17.9	51.6	82.3	-30.7	Peak	Horizontal
7919.0	33.2	12.4	45.6	82.3	-36.7	Peak	Vertical
10809.0	32.5	17.5	50.0	82.3	-32.3	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

7. CONCLUSION

The data collected relate only the item(s) tested and show that the **AirScale Indoor Radio ASiR-pRRH** is compliance with FCC Rules.

The End