
January 10, 2017

Module Approval Request

FCC ID : 2AD8UFW2HBDPM01

* Please provide a detailed explanation if the answer is “No.”

Item	Modular requirement	Yes	No
1	The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly;	V	
2	The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;	V	
3	The module must contain power supply regulation on the module;	V	
4	The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);	V	
5	The module must demonstrate compliance in a stand-alone configuration;		This is a limited modular approval. Module will always be installed with FW2XXXX host assembly which provides digital base band data during normal operation and testing.
6	The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements);	V	
7	The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee;	V	
8	The module must comply with RF exposure requirements	V	


(Signature)

Terry Schwenk
R&D Engineer
Nokia Solutions and Networks, OY
Tel: 8478096952
Fax: 2242488208
E-mail: terry.schwenk@nsn.com