

FCC PART 22H, PART 24E
MEASUREMENT AND TEST REPORT

For

**ENSAMBLADORA Y DISTRIBUIDORA DE
TECNOLOGIA S.A.**

OFICINA 440, EDIFICIO TRADE BUILDING, AV. JOAQUIN ORRANTIA Y LEOPOLDO
BENITEZ, GUAYAQUIL, ECUADOR

FCC ID: 2AD9BQN5926

Report Type: Original Report	Product Type: 3G Mobile Phone
Test Engineer: Dean Liu	
Report Number: RDG150210001-00C	
Report Date: 2015-02-13	
Reviewed By: Sula Huang RF Engineer	
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §2.1047 - MODULATION CHARACTERISTIC	10
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA	12
FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH	16
APPLICABLE STANDARD	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA	16
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	22
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	34
FCC §22.917(A) & §24.238(A) - BAND EDGES.....	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST EQUIPMENT LIST AND DETAILS.....	38
TEST DATA	38
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY	48

APPLICABLE STANDARD48

TEST PROCEDURE48

TEST EQUIPMENT LIST AND DETAILS.....49

TEST DATA49

DECLARATION LETTER54

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A.'s product, model number: QN5926 (FCC ID: 2AD9BQN5926) (or the "EUT") in this report was a 3G Mobile Phone, which was measured approximately: 14.45 cm (L) x 7.15 cm (W) x 0.85 cm (H), rated input voltage: DC3.7 V rechargeable Li-ion or DC5V charging from adapter.

Note: The series product, model QN5926 and B5025 are electrically identical, the differences between them is model name, we selected QN5926 for testing, the details was explained in the attached declaration letter.

** All measurement and test data in this report was gathered from production sample serial number: 150210001 (Assigned by applicant). The EUT was received on 2015-02-10.*

Objective

This report is prepared on behalf of ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A. in accordance with Part 2-Subpart J, Part 22-Subpart H, and Part 24-Subpart E of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2AD9BQN5926.
FCC Part15C DSS submissions with FCC ID: 2AD9BQN5926.
FCC Part15C DTS submissions with FCC ID: 2AD9BQN5926.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services
Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D-2010, ANSI C63.4-2009.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp.(Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FINAL

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D-2010.

The test items were performed with the EUT operating at testing mode.


Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R & S	Universal Radio Communication Tester	CMU200	109038

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310, §2.1093	RF Exposure	Compliance
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RDG150210001-20.

FINAL

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FINAL

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

Test Procedure

GSM

Function: Menu select > GSM Mobile Station > GSM 850/1900
Press Connection control to choose the different menus
Press RESET > choose all the reset all settings
Connection Press Signal Off to turn off the signal and change settings
Network Support > GSM + only
MS Signal
 > 33 dBm for GSM 850
 > 30 dBm for GSM 1900
BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel
Frequency Offset > + 0 Hz
Mode > BCCH and TCH
BCCH Level > -85 dBm (May need to adjust if link is not stable)
BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]
Channel Type > Off
P0 > 4 dB
TCH > choose desired test channel
Hopping > Off
AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
Connection Press Signal on to turn on the signal and change settings

GPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900
Press Connection control to choose the different menus
Press RESET > choose all the reset all settings
Connection Press Signal Off to turn off the signal and change settings
Network Support > GSM + GPRS or GSM + EGSM
Main Service > Packet Data
Service selection > Test Mode A – Auto Slot Config. off
MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting
 > Slot configuration > Uplink/Gamma
 > 33 dBm for GPRS 850
 > 30 dBm for GPRS 1900
BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel
Frequency Offset > + 0 Hz
Mode > BCCH and TCH
BCCH Level > -85 dBm (May need to adjust if link is not stable)
BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off
 P0 > 4 dB
 Slot Config > Unchanged (if already set under MS signal)
 TCH > choose desired test channel
 Hopping > Off
 Main Timeslot > 3
 Network Coding Scheme > CS4 (GPRS)
 Bit Stream > 2E9-1 PSR Bit Stream
 AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
 Connection Press Signal on to turn on the signal and change settings

Radiated method:

ANSI/TIA 603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-19
Giga	Signal Generator	1026	320408	2014-05-09	2015-05-09
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2012-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.5 °C
Relative Humidity:	42%
ATM Pressure:	101.3kPa

The testing was performed by Dean Liu on 2015-02-11

Conducted Power:**Cellular Band (Part 22H) & PCS Band (Part 24E)**

Band	Channel No.	Peak Output Power (dBm)				
		GSM	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
Cellular	128	31.80	31.83	30.93	29.15	28.41
	190	31.60	31.72	30.80	29.06	28.30
	251	31.60	31.69	30.78	29.09	28.37
PCS	512	28.50	28.41	27.25	25.43	24.61
	661	28.40	28.24	27.12	25.30	24.72
	810	28.30	28.23	27.12	25.29	24.73

WCDMA Band II

Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel (Ave. Power)	Low Channel (PAR)	Middle Channel (Ave. Power)	Middle Channel (PAR)	High Channel (Ave. Power)	High Channel (PAR)
Rel 99	1	21.66	2.77	21.59	3.08	21.37	2.96
HSDPA	1	20.68	2.76	20.68	3.09	20.41	3.00
	2	20.74	2.78	20.67	3.04	20.36	2.93
	3	20.50	2.80	20.56	3.11	20.42	2.94
	4	20.53	2.72	20.55	3.11	20.37	2.92
HSUPA	1	20.73	2.76	20.55	3.13	20.45	2.95
	2	20.49	2.74	20.58	3.12	20.33	2.92
	3	20.56	2.76	20.43	3.10	20.43	2.93
	4	20.72	2.73	20.52	3.05	20.32	2.99
	5	20.51	2.80	20.58	3.04	20.44	2.95

WCDMA Band V

Mode	3GPP Sub Test	Average Output Power (dBm)					
		Low Channel	Low Channel (PAR)	Middle Channel	Middle Channel (PAR)	High Channel	High Channel (PAR)
Rel 99	1	22.38	3.15	22.56	3.20	22.24	2.94
HSDPA	1	21.46	3.19	21.39	3.20	21.14	2.94
	2	21.30	3.14	21.55	3.24	21.08	2.90
	3	21.33	3.17	21.44	3.23	21.23	2.91
	4	21.31	3.13	21.62	3.24	21.08	2.90
HSUPA	1	21.19	3.13	21.50	3.16	21.29	2.97
	2	21.40	3.11	21.43	3.19	21.24	2.97
	3	21.38	3.15	21.39	3.18	21.07	2.91
	4	21.32	3.14	21.64	3.15	21.12	2.91
	5	21.24	3.19	21.60	3.25	21.25	2.97

Note: peak-to-average ratio (PAR) <13 dB

ERP & EIRP

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850								
824.200	H	93.52	18.5	0.0	1	17.5	38.5	21.0
824.200	V	103.46	31.5	0.0	1	30.5	38.5	8.0
836.600	H	92.96	18	0.0	1	17.0	38.5	21.5
836.600	V	102.78	31	0.0	1	30.0	38.5	8.5
848.800	H	92.73	17.9	0.0	1	16.9	38.5	21.6
848.800	V	102.18	30.5	0.0	1	29.5	38.5	9.0
PCS 1900								
1850.200	H	89.38	17.5	11.4	1.4	27.5	33.0	5.5
1850.200	V	86.19	14.3	11.4	1.4	24.3	33.0	8.7
1880.000	H	89.13	17.5	11.7	1.4	27.8	33.0	5.2
1880.000	V	86.63	15.2	11.7	1.4	25.5	33.0	7.5
1909.800	H	89.37	18	11.8	1.4	28.4	33.0	4.6
1909.800	V	86.89	15.8	11.8	1.4	26.2	33.0	6.8
WCDMA Band II								
1852.400	H	82.63	10.8	11.5	1.4	20.9	33.0	12.1
1852.400	V	80.67	8.8	11.5	1.4	18.9	33.0	14.1
1880.000	H	82.68	11.1	11.7	1.4	21.4	33.0	11.6
1880.000	V	80.11	8.7	11.7	1.4	19.0	33.0	14.0
1907.400	H	82.78	11.4	11.8	1.4	21.8	33.0	11.2
1907.400	V	79.99	8.9	11.8	1.4	19.3	33.0	13.7
Band V								
826.400	H	82.45	7.4	0.0	1	6.4	38.5	32.1
826.400	V	95.15	23.3	0.0	1	22.3	38.5	16.2
836.600	H	83.52	8.6	0.0	1	7.6	38.5	30.9
836.600	V	95.34	23.5	0.0	1	22.5	38.5	16.0
846.600	H	82.63	7.8	0.0	1	6.8	38.5	31.7
846.600	V	95.08	23.4	0.0	1	22.4	38.5	16.1


FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH**Applicable Standard**

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	21.1-21.5 °C
Relative Humidity:	40-42%
ATM Pressure:	101.3-101.7 kPa

The testing was performed by Dean Liu on 2015-02-10 & 2015-02-11.


Band	Channel No.	Mode	99% Occupied Bandwidth (kHz)	26 dB Occupied Bandwidth (kHz)
Cellular	190	GSM	242.48	316.63
PCS	661	GSM	246.49	320.64
WCDMA Band II	9400	Rel 99	4208.42	4769.54
	9400	HSDPA	4188.38	4749.5
	9400	HSUPA	4208.42	4749.5
WCDMA Band V	4183	Rel 99	4188.38	4729.46
	4183	HSDPA	4168.34	4709.42
	4183	HSUPA	4168.34	4729.46

Please refer to the following plots.


GMSK Cellular Band




GMSK PCS Band




WCDMA Band II




HSDPA Band II




HSUPA Band II




WCDMA Band V



HSDPA Band V



HSUPA Band V



FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data



Environmental Conditions

Temperature:	21.1-21.5 °C
Relative Humidity:	40-42%
ATM Pressure:	101.3-101.7 kPa



The testing was performed by Dean Liu on 2015-02-10 & 2015-02-11.


Please refer to the following plots.



GMSK, GSM850_Low Channel





GMSK, PCS 1900_Middle Channel











Band II HSDPA_Low Channel







Band II HSUPA_ Low Channel









WCDMA Band V_Low Channel



Band V HSDPA_Low Channel



Band V HSUPA_Low Channel



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg(\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \lg(\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-19
Giga	Signal Generator	1026	320408	2014-05-09	2015-05-09
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2012-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	23.4 °C
Relative Humidity:	64%
ATM Pressure:	101.3kPa

The testing was performed by Dean Liu on 2015-02-11

EUT Operation Mode: Transmitting

Cellular Band

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:824.200 MHz								
1648.400	H	60.57	-40.6	10.5	1.5	-31.6	-13.0	18.6
1648.400	V	60.23	-41.4	10.5	1.5	-32.4	-13.0	19.4
2472.600	H	38.22	-59.8	12.9	2.6	-49.5	-13.0	36.5
2472.600	V	36.15	-60.6	12.9	2.6	-50.3	-13.0	37.3
42.610	H	34.16	-46	-23.0	0.2	-69.2	-13.0	56.2
392.780	V	33.72	-59.9	0.0	0.6	-60.5	-13.0	47.5
Frequency:836.600 MHz								
1673.200	H	61.20	-39.9	10.6	1.5	-30.8	-13.0	17.8
1673.200	V	60.87	-40.5	10.6	1.5	-31.4	-13.0	18.4
2509.800	H	38.38	-59.6	13.1	2.8	-49.3	-13.0	36.3
2509.800	V	36.32	-60.8	13.1	2.8	-50.5	-13.0	37.5
42.610	H	34.36	-45.8	-23.0	0.2	-69.0	-13.0	56.0
392.780	V	33.88	-59.7	0.0	0.6	-60.3	-13.0	47.3
Frequency:848.800 MHz								
1697.600	H	61.93	-39.1	10.8	1.5	-29.8	-13.0	16.8
1697.600	V	61.72	-39.5	10.8	1.5	-30.2	-13.0	17.2
2546.400	H	38.40	-58.2	13.1	2.8	-47.9	-13.0	34.9
2546.400	V	36.33	-60.8	13.1	2.8	-50.5	-13.0	37.5
42.610	H	34.23	-45.9	-23.0	0.2	-69.1	-13.0	56.1
392.780	V	33.74	-59.8	0.0	0.6	-60.4	-13.0	47.4

PCS Band

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:1850.200 MHz								
3700.400	H	46.82	-47.9	14.0	2.5	-36.4	-13.0	23.4
3700.400	V	45.36	-49	14.0	2.5	-37.5	-13.0	24.5
42.610	H	33.12	-47	-23.0	0.2	-70.2	-13.0	57.2
392.780	V	32.24	-61.3	0.0	0.6	-61.9	-13.0	48.9
Frequency:1880.000 MHz								
3760.000	H	48.65	-45.6	13.8	2.9	-34.7	-13.0	21.7
3760.000	V	47.14	-45.9	13.8	2.9	-35.0	-13.0	22.0
42.610	H	33.15	-47	-23.0	0.2	-70.2	-13.0	57.2
392.780	V	32.26	-61.3	0.0	0.6	-61.9	-13.0	48.9
Frequency:1909.800 MHz								
3819.600	H	51.24	-42.6	13.6	3.3	-32.3	-13.0	19.3
3819.600	V	49.25	-42.9	13.6	3.3	-32.6	-13.0	19.6
42.610	H	33.13	-47	-23.0	0.2	-70.2	-13.0	57.2
392.780	V	32.17	-61.4	0.0	0.6	-62.0	-13.0	49.0

WCDMA Band II

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:1852.400 MHz								
3704.800	H	38.74	-56	13.9	2.5	-44.6	-13.0	31.6
3704.800	V	37.35	-56.9	13.9	2.5	-45.5	-13.0	32.5
42.610	H	33.12	-47	-23.0	0.2	-70.2	-13.0	57.2
392.780	V	32.24	-61.3	0.0	0.6	-61.9	-13.0	48.9
Frequency:1880.000 MHz								
3760.000	H	39.64	-54.7	13.8	2.9	-43.8	-13.0	30.8
3760.000	V	38.55	-54.5	13.8	2.9	-43.6	-13.0	30.6
42.610	H	33.13	-47	-23.0	0.2	-70.2	-13.0	57.2
392.780	V	32.41	-61.2	0.0	0.6	-61.8	-13.0	48.8
Frequency:1907.600 MHz								
3815.200	H	41.66	-52.2	13.6	3.3	-41.9	-13.0	28.9
3815.200	V	40.46	-51.7	13.6	3.3	-41.4	-13.0	28.4
42.610	H	33.28	-46.9	-23.0	0.2	-70.1	-13.0	57.1
392.780	V	32.39	-61.2	0.0	0.6	-61.8	-13.0	48.8

WCDMA Band V

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:826.400 MHz								
1652.800	H	38.24	-62.9	10.5	1.5	-53.9	-13.0	40.9
1652.800	V	37.25	-64.3	10.5	1.5	-55.3	-13.0	42.3
42.610	H	33.17	-47	-23.0	0.2	-70.2	-13.0	57.2
392.780	V	32.26	-61.3	0.0	0.6	-61.9	-13.0	48.9
Frequency:836.600 MHz								
1673.200	H	39.45	-61.6	10.6	1.5	-52.5	-13.0	39.5
1673.200	V	38.12	-63.3	10.6	1.5	-54.2	-13.0	41.2
42.610	H	33.12	-47	-23.0	0.2	-70.2	-13.0	57.2
392.780	V	32.26	-61.3	0.0	0.6	-61.9	-13.0	48.9
Frequency:846.600MHz								
1693.200	H	41.68	-59.4	10.7	1.5	-50.2	-13.0	37.2
1693.200	V	40.37	-60.8	10.7	1.5	-51.6	-13.0	38.6
42.610	H	33.19	-47	-23.0	0.2	-70.2	-13.0	57.2
392.780	V	32.26	-61.3	0.0	0.6	-61.9	-13.0	48.9

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data



Environmental Conditions

Temperature:	21.1-21.5 °C
Relative Humidity:	40-42%
ATM Pressure:	101.3-101.7 kPa


The testing was performed by Dean Liu on 2015-02-10 & 2015-02-11.

Please refer to the following tables and plots.


Band	Mode	Band Edge	Reading	Limit
			dBm	dBm
Cellular	GSM	Left	-14.56	≤ -13
		Right	-13.81	≤ -13
PCS	GSM	Left	-15.96	≤ -13
		Right	-15.93	≤ -13
WCDMA Band II	Rel 99	Left	-14.12	≤ -13
		Right	-15.27	≤ -13
	HSDPA	Left	-13.33	≤ -13
		Right	-14.37	≤ -13
	HSUPA	Left	-13.64	≤ -13
		Right	-14.04	≤ -13
WCDMA Band V	Rel 99	Left	-13.68	≤ -13
		Right	-14.20	≤ -13
	HSDPA	Left	-14.08	≤ -13
		Right	-13.26	≤ -13
	HSUPA	Left	-13.76	≤ -13
		Right	-15.85	≤ -13

GSM 850, Left Band Edge**GSM 850, Right Band Edge**


GSM 1900, Left Band Edge




GSM 1900, Right Band Edge





WCDMA Band II, Left Band Edge




WCDMA Band II, Right Band Edge




HSDPA Band II , Left Band Edge**HSDPA Band II, Right Band Edge**


HSUPA Band II, Left Band Edge




HSUPA Band II, Right Band Edge




WCDMA Band V, Left Band Edge



WCDMA Band V, Right Band Edge




HSDPA Band V, Left Band Edge

Date: 10.FEB.2015 22:20:59

HSDPA Band V, Right Band Edge

Date: 10.FEB.2015 22:22:37

HSUPA Band V, Left Band Edge



Date: 10.FEB.2015 22:20:44

HSUPA Band V, Right Band Edge



Date: 10.FEB.2015 22:22:22

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set from 85% to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-3	2014-08-11	2015-08-11
R&S	Universal Radio Communication Tester	CMU200	109 038	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	21.5 °C
Relative Humidity:	42 %
ATM Pressure:	101.3 kPa

The testing was performed by Dean Liu on 2015-02-11

Cellular Band (Part 22H)

GMSK, Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	22	0.026	2.5
-20	3.7	14	0.017	2.5
-10	3.7	15	0.018	2.5
0	3.7	16	0.019	2.5
10	3.7	14	0.017	2.5
20	3.7	23	0.027	2.5
30	3.7	19	0.023	2.5
40	3.7	14	0.017	2.5
50	3.7	15	0.018	2.5
25	3.5	15	0.018	2.5
25	4.2	19	0.023	2.5

PCS Band (Part 24E)

GMSK, Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	29	0.015	Pass
-20	3.7	36	0.019	Pass
-10	3.7	31	0.016	Pass
0	3.7	29	0.015	Pass
10	3.7	26	0.014	Pass
20	3.7	27	0.014	Pass
30	3.7	29	0.015	Pass
40	3.7	30	0.016	Pass
50	3.7	31	0.016	Pass
25	3.5	30	0.016	Pass
25	4.2	37	0.020	Pass

WCDMA Band II

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-18	-0.010	Pass
-20	3.7	-17	-0.009	Pass
-10	3.7	-19	-0.010	Pass
0	3.7	-16	-0.009	Pass
10	3.7	-23	-0.012	Pass
20	3.7	-19	-0.010	Pass
30	3.7	-20	-0.011	Pass
40	3.7	-17	-0.009	Pass
50	3.7	-22	-0.012	Pass
25	3.5	-18	-0.010	Pass
25	4.2	-23	-0.012	Pass

HSDPA Band II

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-21	-0.011	Pass
-20	3.7	-17	-0.009	Pass
-10	3.7	-25	-0.013	Pass
0	3.7	-20	-0.011	Pass
10	3.7	-21	-0.011	Pass
20	3.7	-22	-0.012	Pass
30	3.7	-19	-0.010	Pass
40	3.7	-20	-0.011	Pass
50	3.7	-25	-0.013	Pass
25	3.5	-23	-0.012	Pass
25	4.2	-24	-0.013	Pass

HSUPA Band II

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.7	-19	-0.010	Pass
-20	3.7	-17	-0.009	Pass
-10	3.7	-15	-0.008	Pass
0	3.7	-19	-0.010	Pass
10	3.7	-18	-0.010	Pass
20	3.7	-21	-0.011	Pass
30	3.7	-17	-0.009	Pass
40	3.7	-24	-0.013	Pass
50	3.7	-22	-0.012	Pass
25	3.5	-18	-0.010	Pass
25	4.2	-22	-0.012	Pass

WCDMA Band V

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-11	-0.013	2.5
-20	3.7	-16	-0.019	2.5
-10	3.7	-15	-0.018	2.5
0	3.7	-18	-0.022	2.5
10	3.7	-16	-0.019	2.5
20	3.7	-17	-0.020	2.5
30	3.7	-14	-0.017	2.5
40	3.7	-19	-0.023	2.5
50	3.7	-18	-0.022	2.5
25	3.5	-15	-0.018	2.5
25	4.2	-12	-0.014	2.5

HSDPA Band V

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-19	-0.023	2.5
-20	3.7	-17	-0.020	2.5
-10	3.7	-21	-0.025	2.5
0	3.7	-16	-0.019	2.5
10	3.7	-18	-0.022	2.5
20	3.7	-12	-0.014	2.5
30	3.7	-18	-0.022	2.5
40	3.7	-15	-0.018	2.5
50	3.7	-17	-0.020	2.5
25	3.5	-15	-0.018	2.5
25	4.2	-19	-0.023	2.5

HSUPA Band V

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.7	-13	-0.016	2.5
-20	3.7	-19	-0.023	2.5
-10	3.7	-13	-0.016	2.5
0	3.7	-17	-0.020	2.5
10	3.7	-15	-0.018	2.5
20	3.7	-16	-0.019	2.5
30	3.7	-18	-0.022	2.5
40	3.7	-14	-0.017	2.5
50	3.7	-11	-0.013	2.5
25	3.5	-14	-0.017	2.5
25	4.2	-12	-0.014	2.5

DECLARATION LETTER

ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A.
Add: OFICINA 440, EDIFICIO TRADE BUILDING, AV. JOAQUIN ORRANTIA Y
LEOPOLDO BENITEZ, GUAYAQUIL, ECUADOR
Tel: +59345103027 Fax: 59342004140ext.104

Product Similarity Declaration

Date: 2015-02-13

To Whom It May Concern,

We, ENSAMBLADORA Y DISTRIBUIDORA DE TECNOLOGIA S.A., hereby declare that our product 3G Smart Phone, Model Number: QN5926, B5025 are electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics. Model Numbers: B5025 is electrically identical with the Model Number: QN5926 that was certified by BACL. Their only difference is the model name.

The rest are the same.

Please contact me if you have any question.

Signature: *Kerlyn Velez*

Kerlyn Velez
General Manager Assistant

***** END OF REPORT *****