



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Wave Central

Model: AXTX1-5G

Description: 5.73-5.84GHz RF Microwave Transmitter

Serial Number: 6607

FCC ID: 2AD9D-AXIS5GTX

To

FCC Part 1.1310

Date of Issue: May 29, 2015

On the behalf of the applicant:

**Wave Central
99 Garden Parkway
Suite C
Carlisle, PA 17013**

Attention of:

**Tom Doyle, General Manager
Ph: (888) 736-9283
E-Mail: tom@wave-central.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1510015**

**Alex Macon
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	May 29, 2015	Alex Macon	Original Document



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: AXTX1-5G

Description: 5.73-5.84GHz RF Microwave Transmitter

Firmware: N/A

Software: N/A

Serial Number: 6607

Additional Information: The EUT is a 5.8 GHz transmitter intended to be used on commercial video cameras with a DC battery pack.



Source Based Time Averaged Power Calculation

Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle %	Average Power (mW)
5800	73.1 mW	100	73.1 mW



MPE Evaluation

This is a fixed/mobile device used in uncontrolled /general population exposure environment.

Limits Uncontrolled Exposure	0.3-1.234 MHz	Limit [mW/cm ²] = 100
47 CFR 1.1310	1.34-30 MHz	Limit [mW/cm ²] = (180/f ²)
Table 1, (B)	30-300 MHz	Limit [mW/cm ²] = 0.2
	300-1500 MHz	Limit [mW/cm ²] = f/1500
	1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	5730
Power, Conducted, mW (P)	73.1
Antenna Gain Isotropic	6dBi
Antenna Gain Numeric (G)	3.98
Antenna Type	Omni
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm ²	Power mW (P)	Numeric Gain (G)	Distance (r ²) cm
	73.1	3.98	20

Power Density (S) =	0.057
Limit =(from above table) =	1.0

END OF TEST REPORT