RF TEST REPORT

SIEMIC
GLOBAL TESTING & CERTIFICATIONS
YOUR CHOICE FOR- TCB FCB CB NB CAB RCB

Report No.: 16070816-FCC-R5

Supersede Report No.: N/A

Applicant	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Product Name	4G LTE SMARTPHONE
Model No.	N551
Serial No.	N/A
Test Standard	FCC Part 27: 2015; ANSI/TIA-603-D: 2010
Test Date	July 19 to August 14, 2016
Issue Date	August 15, 2016
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 5

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 6

5. TEST SUMMARY 9

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 10

6.1 RF EXPOSURE (SAR) 10

6.2 RF OUTPUT POWER 11

6.3 PEAK-AVERAGE RATIO 22

6.4 OCCUPIED BANDWIDTH 25

6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS 34

6.6 SPURIOUS RADIATED EMISSIONS 36

6.7 BAND EDGE 39

6.8 BAND EDGE 27.53(M) 46

6.9 FREQUENCY STABILITY 47

ANNEX A. TEST INSTRUMENT 50

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 52

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 58

ANNEX C.II. EUT OPERATING CONKITIONS 60

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 61

ANNEX E. DECLARATION OF SIMILARITY 62

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070816-FCC-R5	NONE	Original	August 15, 2016

2. Customer information

Applicant Name	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Applicant Add	No.999,Dacheng East Road,Fenghua City,Zhejiang
Manufacturer	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Manufacturer Add	No.999,Dacheng East Road,Fenghua City,Zhejiang

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	4G LTE SMARTPHONE
Main Model:	N551
Serial Model:	N/A
Date EUT received:	July 18, 2016
Test Date(s):	July 19 to August 14, 2016
Equipment Category：	PCE
Antenna Gain:	GSM850: -3dBi PCS1900: -1dBi UMTS-FDD Band V: -3dBi UMTS-FDD Band II:-1dBi LTE Band IV: -3dBi Bluetooth/BLE/WIFI: -1dBi GPS: -1dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK

RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz LTE Band IV TX: 1712.5 ~ 1752.5 MHz; RX : 2112.5 ~ 2152.5 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz GPS: 1575.42 MHz
Number of Channels:	GSM 850: 124CH PCS1900: 299CH UMTS-FDD Band V: 102CH UMTS-FDD Band II: 277CH WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH GPS:1CH
Maximum Conducted AV Power to Antenna:	LTE Band 4: 23.59 dBm
ERP/EIRP:	LTE Band 4: 21.40 dBm / EIRP
Port:	Power Port, Earphone Port, USB Port
Input Power:	Adapter: Model: S005UA0500100 Input: AC100-240V~50/60Hz,150mA Output: DC 5.0V,1000mA Battery: Spec: 3.8V,3000mAh(11.4Wh)
Trade Name :	Noblex
GPRS/EGPRS Multi-slot class	8/10/12

FCC ID: 2ADA4N551

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046;§ 27.50(c.10); § 27.50(d.4)	RF Output Power	Compliance
§ 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1047	Modulation Characteristics	N/A
§ 2.1049; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053;§ 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 27.53(h)	Out of band emission, Band Edge	Compliance
§ 27.53(m)	Band Edge 27.53(m)	N/A
§ 2.1055; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	**Description**	**Uncertainty**
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass

The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 16070816-FCC-H.

6.2 RF Output Power

Temperature	25℃
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	July 28, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§27.50 (c)	c)	EIRP: 30dBm	☑
Test Setup			
Test Procedure	For Conducted Power: - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. For ERP/EIRP: - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental frequency was investigated. - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-		

	radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = 10 log (TX power in Watts/0.001) – the absolute level - Spurious attenuation limit in dB = 43 + 10 Log10 (power out in Watts.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☑ N/A

Conducted Power

LTE Band 4:

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	Tune up Power tolerant
20MHz	20050	1720.0	QPSK	1	0	0	23.57	23±1
				1	49	0	23.56	23±1
				1	99	0	23.50	23±1
				50	0	1	22.53	23±1
				50	24	1	22.54	23±1
				50	49	1	22.59	23±1
				100	0	1	22.51	23±1
			16QAM	1	0	1	22.75	22±1
				1	49	1	22.73	22±1
				1	99	1	22.76	22±1
				50	0	2	21.56	22±1
				50	24	2	21.53	22±1
				50	49	2	21.59	22±1
				100	0	2	21.58	22±1
	20175	1732.5	QPSK	1	0	0	23.55	23±1
				1	49	0	23.54	23±1
				1	99	0	23.52	23±1
				50	0	1	22.48	23±1
				50	24	1	22.43	23±1
				50	49	1	22.47	23±1
				100	0	1	22.44	23±1
			16QAM	1	0	1	22.45	22±1
				1	49	1	22.43	22±1
				1	99	1	22.47	22±1
				50	0	2	21.63	22±1
				50	24	2	21.76	22±1
				50	49	2	21.75	22±1
				100	0	2	21.54	22±1
	20300	1745.0	QPSK	1	0	0	23.54	23±1
				1	49	0	23.53	23±1
				1	99	0	**23.59**	23±1
				50	0	1	22.45	23±1
				50	24	1	22.43	23±1
				50	49	1	22.49	23±1
				100	0	1	22.41	23±1
			16QAM	1	0	1	22.94	22±1
				1	49	1	22.95	22±1
				1	99	1	22.96	22±1
				50	0	2	21.93	22±1
				50	24	2	21.94	22±1
				50	49	2	22.10	22±1
				100	0	2	21.46	22±1

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	Tune up Power tolerant
15MHz	20025	1717.5	QPSK	1	0	0	23.43	22.5±1
				1	37	0	23.44	22.5±1
				1	74	0	23.49	22.5±1
				36	0	1	22.52	22.5±1
				36	16	1	22.56	22.5±1
				36	35	1	22.55	22.5±1
				75	0	1	22.58	22.5±1
			16QAM	1	0	1	23.03	22.5±1
				1	37	1	23.01	22.5±1
				1	74	1	23.00	22.5±1
				36	0	2	22.15	22.5±1
				36	16	2	22.18	22.5±1
				36	35	2	22.16	22.5±1
				75	0	2	21.63	22.5±1
	20175	1732.5	QPSK	1	0	0	23.52	23±1
				1	37	0	23.54	23±1
				1	74	0	23.59	23±1
				36	0	1	22.49	23±1
				36	16	1	22.51	23±1
				36	35	1	22.59	23±1
				75	0	1	22.52	23±1
			16QAM	1	0	1	22.33	22±1
				1	37	1	22.32	22±1
				1	74	1	22.35	22±1
				36	0	2	21.56	22±1
				36	16	2	21.54	22±1
				36	35	2	21.57	22±1
				75	0	2	21.55	22±1
	20325	1747.5	QPSK	1	0	0	23.38	23±1
				1	37	0	23.36	23±1
				1	74	0	23.37	23±1
				36	0	1	22.35	23±1
				36	16	1	22.34	23±1
				36	35	1	22.38	23±1
				75	0	1	22.37	23±1
			16QAM	1	0	1	22.63	22±1
				1	37	1	22.64	22±1
				1	74	1	22.69	22±1
				36	0	2	21.95	22±1
				36	16	2	21.92	22±1
				36	35	2	21.93	22±1
				75	0	2	21.36	22±1

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	Tune up Power tolerant
10MHz	20000	1715.0	QPSK	1	0	0	23.41	23±1
				1	24	0	23.42	23±1
				1	49	0	23.40	23±1
				25	0	1	22.52	23±1
				25	12	1	22.53	23±1
				25	24	1	22.52	23±1
				50	0	1	22.54	23±1
			16QAM	1	0	1	23.04	22.3±1
				1	24	1	23.10	22.3±1
				1	49	1	23.16	22.3±1
				25	0	2	22.35	22.3±1
				25	12	2	22.37	22.3±1
				25	24	2	22.35	22.3±1
				50	0	2	21.59	22.3±1
	20175	1732.5	QPSK	1	0	0	23.49	23±1
				1	24	0	23.46	23±1
				1	49	0	23.48	23±1
				25	0	1	22.44	23±1
				25	12	1	22.45	23±1
				25	24	1	22.41	23±1
				50	0	1	22.48	23±1
			16QAM	1	0	1	22.31	22±1
				1	24	1	22.30	22±1
				1	49	1	22.35	22±1
				25	0	2	21.47	22±1
				25	12	2	21.48	22±1
				25	24	2	21.36	22±1
				50	0	2	21.53	22±1
	20350	1750.0	QPSK	1	0	0	23.31	23±1
				1	24	0	23.29	23±1
				1	49	0	23.24	23±1
				25	0	1	22.28	23±1
				25	12	1	22.16	23±1
				25	24	1	22.18	23±1
				50	0	1	22.30	23±1
			16QAM	1	0	1	22.27	22±1
				1	24	1	22.26	22±1
				1	49	1	22.22	22±1
				25	0	2	21.35	22±1
				25	12	2	21.32	22±1
				25	24	2	21.31	22±1
				50	0	2	21.37	22±1

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	Tune up Power tolerant
5MHz	20000	1715.0	QPSK	1	0	0	23.56	23±1
				1	12	0	23.59	23±1
				1	24	0	23.52	23±1
				12	0	1	22.56	23±1
				12	6	1	22.53	23±1
				12	11	1	22.58	23±1
				25	0	1	22.53	23±1
			16QAM	1	0	1	22.49	22±1
				1	12	1	22.41	22±1
				1	24	1	22.36	22±1
				12	0	2	22.05	22±1
				12	6	2	22.08	22±1
				12	11	2	21.98	22±1
				25	0	2	21.70	22±1
	20175	1732.5	QPSK	1	0	0	23.61	23±1
				1	12	0	23.59	23±1
				1	24	0	23.51	23±1
				12	0	1	22.51	23±1
				12	6	1	22.48	23±1
				12	11	1	22.50	23±1
				25	0	1	22.43	23±1
			16QAM	1	0	1	22.56	22±1
				1	12	1	22.51	22±1
				1	24	1	22.57	22±1
				12	0	2	21.95	22±1
				12	6	2	21.91	22±1
				12	11	2	21.87	22±1
				25	0	2	21.49	22±1
	20350	1750.0	QPSK	1	0	0	23.30	23±1
				1	12	0	23.26	23±1
				1	24	0	23.29	23±1
				12	0	1	22.34	23±1
				12	6	1	22.36	23±1
				12	11	1	22.46	23±1
				25	0	1	22.28	23±1
			16QAM	1	0	1	22.60	22±1
				1	12	1	22.63	22±1
				1	24	1	22.51	22±1
				12	0	2	21.79	22±1
				12	6	2	21.77	22±1
				12	11	2	21.68	22±1
				25	0	2	21.37	22±1

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	Tune up Power tolerant
3MHz	19965	1711.5	QPSK	1	0	0	23.35	23±1
				1	7	0	23.34	23±1
				1	14	0	23.37	23±1
				8	0	1	22.47	23±1
				8	4	1	22.49	23±1
				8	7	1	22.35	23±1
				15	0	1	22.51	23±1
			16QAM	1	0	1	22.96	22.3±1
				1	7	1	22.98	22.3±1
				1	14	1	22.91	22.3±1
				8	0	2	21.54	22.3±1
				8	4	2	21.53	22.3±1
				8	7	2	21.55	22.3±1
				15	0	2	21.66	22.3±1
	20175	1732.5	QPSK	1	0	0	23.46	23±1
				1	7	0	23.49	23±1
				1	14	0	23.44	23±1
				8	0	1	22.43	23±1
				8	4	1	22.49	23±1
				8	7	1	22.47	23±1
				15	0	1	22.44	23±1
			16QAM	1	0	1	22.30	22±1
				1	7	1	22.35	22±1
				1	14	1	22.32	22±1
				8	0	2	21.45	22±1
				8	4	2	21.48	22±1
				8	7	2	21.43	22±1
				15	0	2	21.44	22±1
	20385	1753.5	QPSK	1	0	0	23.32	23±1
				1	7	0	23.36	23±1
				1	14	0	23.31	23±1
				8	0	1	22.24	23±1
				8	4	1	22.26	23±1
				8	7	1	22.19	23±1
				15	0	1	22.33	23±1
			16QAM	1	0	1	22.28	22±1
				1	7	1	22.21	22±1
				1	14	1	22.19	22±1
				8	0	2	21.21	22±1
				8	4	2	21.16	22±1
				8	7	2	21.15	22±1
				15	0	2	21.40	22±1

BW (MHz)	Ch	Freq. (MHz)	Mode	UL RB Allocation	UL RB Offset	MPR	Average power (dBm)	Tune up Power tolerant
1.4MHz	19957	1710.7	QPSK	1	0	0	23.41	23±1
				1	2	0	23.37	23±1
				1	5	0	23.35	23±1
				3	0	0	23.58	23±1
				3	1	0	23.53	23±1
				3	2	0	23.52	23±1
				6	0	1	22.46	23±1
			16QAM	1	0	1	22.10	22±1
				1	2	1	22.13	22±1
				1	5	1	22.09	22±1
				3	0	1	21.44	22±1
				3	1	1	21.42	22±1
				3	2	1	21.43	22±1
				6	0	2	21.47	22±1
	20175	1732.5	QPSK	1	0	0	23.46	23±1
				1	2	0	23.43	23±1
				1	5	0	23.48	23±1
				3	0	0	23.59	23±1
				3	1	0	23.53	23±1
				3	2	0	23.54	23±1
				6	0	1	22.40	23±1
			16QAM	1	0	1	22.30	22±1
				1	2	1	22.35	22±1
				1	5	1	22.36	22±1
				3	0	1	21.76	22±1
				3	1	1	21.79	22±1
				3	2	1	21.72	22±1
				6	0	2	21.42	22±1
	20393	1754.3	QPSK	1	0	0	23.33	23±1
				1	2	0	23.36	23±1
				1	5	0	23.34	23±1
				3	0	0	23.40	23±1
				3	1	0	23.26	23±1
				3	2	0	23.16	23±1
				6	0	1	22.27	23±1
			16QAM	1	0	1	22.28	22±1
				1	2	1	22.16	22±1
				1	5	1	22.17	22±1
				3	0	1	21.62	22±1
				3	1	1	21.64	22±1
				3	2	1	21.69	22±1
				6	0	2	21.19	22±1

ERP & EIRP

EIRP for LTE Band 4 (Part 27)

Frequency (MHz)	BW (MHz)	Modulation	RB Size/Offset	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1710.7	1.4	QPSK	1/0	14.22	V	7.95	0.79	21.38	30
1732.5	1.4	QPSK	1/0	14.24	V	7.95	0.79	**21.40**	30
1754.3	1.4	QPSK	1/0	14.16	V	7.95	0.79	21.32	30
1710.7	1.4	QPSK	1/0	13.45	H	7.95	0.79	20.61	30
1732.5	1.4	QPSK	1/0	13.43	H	7.95	0.79	20.59	30
1754.3	1.4	QPSK	1/0	13.26	H	7.95	0.79	20.42	30
1710.7	1.4	16-QAM	1/5	11.89	V	7.95	0.79	19.05	30
1732.5	1.4	16-QAM	1/0	12.21	V	7.95	0.79	19.37	30
1754.3	1.4	16-QAM	1/0	12.18	V	7.95	0.79	19.34	30
1710.7	1.4	16-QAM	1/5	11.23	H	7.95	0.79	18.39	30
1732.5	1.4	16-QAM	1/0	11.47	H	7.95	0.79	18.63	30
1754.3	1.4	16-QAM	1/0	11.52	H	7.95	0.79	18.68	30
1711.5	3	QPSK	1/0	13.21	V	7.95	0.79	20.37	30
1732.5	3	QPSK	1/0	13.06	V	7.95	0.79	20.22	30
1753.5	3	QPSK	1/0	13.37	V	7.95	0.79	20.53	30
1711.5	3	QPSK	1/0	11.56	H	7.95	0.79	18.72	30
1732.5	3	QPSK	1/0	11.79	H	7.95	0.79	18.95	30
1753.5	3	QPSK	1/0	12.04	H	7.95	0.79	19.20	30
1711.5	3	16-QAM	1/0	13.01	V	7.95	0.79	20.17	30
1732.5	3	16-QAM	1/0	12.21	V	7.95	0.79	19.37	30
1753.5	3	16-QAM	1/0	12.17	V	7.95	0.79	19.33	30
1711.5	3	16-QAM	1/0	12.36	H	7.95	0.79	19.52	30
1732.5	3	16-QAM	1/0	11.25	H	7.95	0.79	18.41	30
1753.5	3	16-QAM	1/0	11.42	H	7.95	0.79	18.58	30
1712.5	5	QPSK	1/0	13.89	V	7.95	0.79	21.05	30
1732.5	5	QPSK	1/0	13.41	V	7.95	0.79	20.57	30
1752.5	5	QPSK	1/24	13.28	V	7.95	0.79	20.44	30
1712.5	5	QPSK	1/0	12.06	H	7.95	0.79	19.22	30
1732.5	5	QPSK	1/0	11.98	H	7.95	0.79	19.14	30
1752.5	5	QPSK	1/24	11.73	H	7.95	0.79	18.89	30
1712.5	5	16-QAM	1/0	12.47	V	7.95	0.79	19.63	30
1732.5	5	16-QAM	1/0	12.42	V	7.95	0.79	19.58	30

1752.5	5	16-QAM	1/24	12.13	V	7.95	0.79	19.29	30
1712.5	5	16-QAM	1/0	11.79	H	7.95	0.79	18.95	30
1732.5	5	16-QAM	1/0	11.51	H	7.95	0.79	18.67	30
1752.5	5	16-QAM	1/24	11.45	H	7.95	0.79	18.61	30
1715	10	QPSK	1/0	13.28	V	7.95	0.79	20.44	30
1732.5	10	QPSK	1/49	13.37	V	7.95	0.79	20.53	30
1750	10	QPSK	1/0	13.19	V	7.95	0.79	20.35	30
1715	10	QPSK	1/0	12.41	H	7.95	0.79	19.57	30
1732.5	10	QPSK	1/49	12.16	H	7.95	0.79	19.32	30
1750	10	QPSK	1/0	12.35	H	7.95	0.79	19.51	30
1715	10	16-QAM	1/0	12.83	V	7.95	0.79	19.99	30
1732.5	10	16-QAM	1/49	12.13	V	7.95	0.79	19.29	30
1750	10	16-QAM	1/0	12.24	V	7.95	0.79	19.40	30
1715	10	16-QAM	1/0	11.46	H	7.95	0.79	18.62	30
1732.5	10	16-QAM	1/49	11.68	H	7.95	0.79	18.84	30
1750	10	16-QAM	1/0	11.12	H	7.95	0.79	18.28	30
1717.5	15	QPSK	1/0	13.21	V	7.95	0.79	20.37	30
1732.5	15	QPSK	1/74	13.18	V	7.95	0.79	20.34	30
1747.5	15	QPSK	1/0	13.19	V	7.95	0.79	20.35	30
1717.5	15	QPSK	1/0	12.53	H	7.95	0.79	19.69	30
1732.5	15	QPSK	1/74	12.37	H	7.95	0.79	19.53	30
1747.5	15	QPSK	1/0	12.28	H	7.95	0.79	19.44	30
1717.5	15	16-QAM	1/0	13.01	V	7.95	0.79	20.17	30
1732.5	15	16-QAM	1/74	12.13	V	7.95	0.79	19.29	30
1747.5	15	16-QAM	1/0	12.45	V	7.95	0.79	19.61	30
1717.5	15	16-QAM	1/0	12.38	H	7.95	0.79	19.54	30
1732.5	15	16-QAM	1/74	12.27	H	7.95	0.79	19.43	30
1747.5	15	16-QAM	1/0	12.19	H	7.95	0.79	19.35	30
1720	20	QPSK	1/99	13.34	V	7.95	0.79	20.50	30
1732.5	20	QPSK	1/99	13.36	V	7.95	0.79	20.52	30
1745	20	QPSK	1/0	13.31	V	7.95	0.79	20.47	30
1720	20	QPSK	1/99	12.56	H	7.95	0.79	19.72	30
1732.5	20	QPSK	1/99	12.49	H	7.95	0.79	19.65	30
1745	20	QPSK	1/0	12.62	H	7.95	0.79	19.78	30
1720	20	16-QAM	1/99	12.61	V	7.95	0.79	19.77	30
1732.5	20	16-QAM	1/99	12.25	V	7.95	0.79	19.41	30
1745	20	16-QAM	1/0	13.03	V	7.95	0.79	20.19	30
1720	20	16-QAM	1/99	11.26	H	7.95	0.79	18.42	30

1732.5	20	16-QAM	1/99	11.11	H	7.95	0.79	18.27	30
1745	20	16-QAM	1/0	12.15	H	7.95	0.79	19.31	30

6.3 Peak-Average Ratio

Temperature	25℃
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	July 28, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	☑
Test Setup			
Test Procedure	According with KDB 971168 v02r02 5.7.2 Alternate procedure for PAPR 5.1.2 Peak power measurements with a peak power meter The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector. 5.2.3 Average power measurement with average power meter As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions If the EUT can be configured to transmit continuously (i.e., the burst duty		

	cycle ≥ 98%) and at all times the EUT is transmitting at is maximum output power level, then a conventional wide-band RF power meter can be used. If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to 10log(1/duty cycle)
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☑ N/A

LTE Band 4 (part 27)

BW(MHz)	Frequency (MHz)	Mode	Modulation	Conducted Power (dBm)		Peak-Average Ratio (PAR)
				Peak	Average	
1.4	1732.5	RB 1/0	QPSK	24.52	23.46	1.06
			16QAM	23.49	22.3	1.19
3	1732.5	RB 1/0	QPSK	25.46	23.46	2.00
			16QAM	23.33	22.3	1.03
5	1732.5	RB 1/0	QPSK	25.51	23.61	1.90
			16QAM	24.96	22.56	2.40
10	1732.5	RB 1/0	QPSK	25.31	23.49	1.82
			16QAM	25.75	22.31	3.44
15	1732.5	RB 1/0	QPSK	24.88	23.52	1.36
			16QAM	24.63	22.33	2.30
20	1732.5	RB 1/0	QPSK	24.91	23.55	1.36
			16QAM	25.01	22.45	2.56

6.4 Occupied Bandwidth

Temperature	25℃
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	July 28, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §27.53(a)	a)	99% Occupied Bandwidth(kHz)	☑
	b)	26 dB Bandwidth(kHz)	☑
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

LTE Band 4 (Part 27)

BW(MHz)	Channel	Frequency (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1.4	19957	1710.7	16QAM	1.0979	1.264
			QPSK	1.0951	1.270
1.4	20175	1732.5	16QAM	1.1067	1.273
			QPSK	1.1025	1.269
1.4	20393	1754.3	16QAM	1.1029	1.278
			QPSK	1.1008	1.277
3	19965	1711.5	16QAM	2.7551	3.127
			QPSK	2.7426	3.075
3	20175	1732.5	16QAM	2.7368	3.103
			QPSK	2.7360	3.096
3	20385	1753.5	16QAM	2.7427	3.124
			QPSK	2.7414	3.104
5	19975	1712.5	16QAM	4.5291	5.062
			QPSK	4.5196	5.044
5	20175	1732.5	16QAM	4.5223	5.046
			QPSK	4.5363	5.094
5	20375	1752.5	16QAM	4.5452	5.050
			QPSK	4.5311	5.013
10	20000	1715	16QAM	9.0553	10.267
			QPSK	9.0579	10.258
10	20175	1732.5	16QAM	9.0426	10.261
			QPSK	9.0554	10.254
10	20350	1750	16QAM	9.0529	10.214
			QPSK	9.0871	10.251
15	20025	1717.5	16QAM	13.4816	14.986
			QPSK	13.5092	14.969
15	20175	1732.5	16QAM	13.4693	14.955
			QPSK	13.4530	14.984
15	20325	1747.5	16QAM	13.4736	14.887
			QPSK	13.4893	14.829

20	20050	1720	16QAM	17.9557	19.439
			QPSK	17.9510	19.386
20	20175	1732.5	16QAM	17.8967	19.431
			QPSK	17.8596	19.590
20	20300	1745	16QAM	17.9101	19.592
			QPSK	17.9175	19.688

Test Plots

LTE Band 4 (Part 27)



LTE band 4 - Low CH QPSK-1.4



LTE band 4 - Low CH 16QAM-1.4



LTE band 4 - Middle CH QPSK-1.4



LTE band 4 - Middle CH 16QAM-1.4



LTE band 4 - High CH QPSK-1.4



LTE band 4 - High CH 16QAM-1.4



LTE band 4 - Low CH QPSK-3



LTE band 4 - Low CH 16QAM-3



LTE band 4 - Middle CH QPSK-3



LTE band 4 - Middle CH 16QAM-3



LTE band 4 - High CH QPSK-3



LTE band 4 - High CH 16QAM-3



LTE band 4 - Low CH QPSK-5



LTE band 4 - Low CH 16QAM-5



LTE band 4 - Middle CH QPSK-5



LTE band 4 - Middle CH 16QAM-5



LTE band 4 - High CH QPSK-5



LTE band 4 - High CH 16QAM-5



LTE band 4 - Low CH QPSK-10



LTE band 4 - Low CH 16QAM-10



LTE band 4 - Middle CH QPSK-10



LTE band 4 - Middle CH 16QAM-10



LTE band 4 - High CH QPSK-10



LTE band 4 - High CH 16QAM-10



LTE band 4 - Low CH QPSK-15



LTE band 4 - Low CH 16QAM-15



LTE band 4 - Middle CH QPSK-15



LTE band 4 - Middle CH 16QAM-15



LTE band 4 - High CH QPSK-15



LTE band 4 - High CH 16QAM-15



LTE band 4 - Low CH QPSK-20



LTE band 4 - Low CH 16QAM-20



LTE band 4 - Middle CH QPSK-20



LTE band 4 - Middle CH 16QAM-20



LTE band 4 - High CH QPSK-20



LTE band 4 - High CH 16QAM-20

6.5 Spurious Emissions at Antenna Terminals

Temperature	25℃
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	July 28, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1051, § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB	☑
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100.		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Plots 30MHz-20GHz

LTE Band 4 (Part27) result



LTE Band 4 - Low Channel-1



LTE Band 4 - Low Channel-2



LTE Band 4 - Middle Channel-1



LTE Band 4 - Middle Channel-2



LTE Band 4 - High Channel-1



LTE Band 4 - High Channel-2

6.6 Spurious Radiated Emissions

Temperature	25℃
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	July 28, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	☑
Test setup			
Test Procedure	1. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. 3. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)		

Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☑ N/A

LTE Band 4(Part27) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3440	-47.12	V	10.06	2.52	-39.58	-13	-26.58
3440	-45.36	H	10.06	2.52	-37.82	-13	-24.82
51.3	-43.33	V	-4.2	0.11	-47.64	-13	-34.64
205.6	-46.59	H	4.6	0.18	-42.17	-13	-29.17

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3465	-47.33	V	10.09	2.52	-39.76	-13	-26.76
3465	-45.69	H	10.09	2.52	-38.12	-13	-25.12
51.6	-43.16	V	-4.2	0.11	-47.47	-13	-34.47
204.1	-46.22	H	4.6	0.18	-41.8	-13	-28.8

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3490	-48.03	V	10.09	2.52	-40.46	-13	-27.46
3490	-46.21	H	10.09	2.52	-38.64	-13	-25.64
52.7	-42.95	V	-4.2	0.11	-47.26	-13	-34.26
204.8	-46.88	H	4.6	0.18	-42.46	-13	-29.46

Note:

*1, The testing has been conformed to 10*1752.5MHz=17,525MHz*
2, All other emissions more than 30 dB below the limit
3, X-Axis, Y-Axis and Z–Axis were investigated. The results above show only the worst case.

6.7 Band Edge

Temperature	25℃
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	July 28, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.	☑
Test setup			
Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

LTE Band 4 (Part 27) result

BW(MHz)	Channel	Frequency (MHz)	Mode	Emission (dBm)	Limit (dBm)
1.4	19957	1710	QPSK	-24.52	-13
			16QAM	-24.26	-13
1.4	20393	1755	QPSK	-24.52	-13
			16QAM	-23.54	-13
3	19965	1710	QPSK	-25.23	-13
			16QAM	-26.84	-13
3	20385	1755	QPSK	-27.99	-13
			16QAM	-27.53	-13
5	19975	1710	QPSK	-16.40	-13
			16QAM	-16.14	-13
5	20375	1755	QPSK	-19.53	-13
			16QAM	-17.92	-13
10	20000	1710	QPSK	-16.73	-13
			16QAM	-17.62	-13
10	20350	1755	QPSK	-15.23	-13
			16QAM	-14.80	-13
15	20025	1710	QPSK	-16.51	-13
			16QAM	-20.58	-13
15	20325	1755	QPSK	-19.65	-13
			16QAM	-19.34	-13
20	20050	1710	QPSK	-20.65	-13
			16QAM	-20.98	-13
20	20300	1755	QPSK	-22.98	-13
			16QAM	-23.00	-13

Test Plots

LTE Band 4 (Part 27)



LTE Band 4 - Low Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log (12.70/10)=4.5+1.0=5.5 dB



LTE Band 4 - High Channel QPSK-1.4

Note: Offset=Cable loss (4.5) + 10log (12.77/10)=4.5+1.1=5.6 dB



LTE Band 4 - Low Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log (12.64/10)=4.5+1.0=5.5 dB



LTE Band 4 - High Channel 16QAM-1.4

Note: Offset=Cable loss (4.5) + 10log ((12.78/10)=4.5+1.1=5.6 dB



LTE Band 4 - Low Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log (30.75/30)=4.5+0.1=4.6 dB



LTE Band 4 - High Channel QPSK-3

Note: Offset=Cable loss (4.5) + 10log (31.04/30)=4.5+0.1=4.6 dB



LTE Band 4 - Low Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log (31.27/30)=4.5+0.2=4.7 dB



LTE Band 4 - High Channel 16QAM-3

Note: Offset=Cable loss (4.5) + 10log (31.24/30)=4.5+0.2=4.7 dB



LTE Band 4 - Low Channel QPSK-5



LTE Band 4 - High Channel QPSK-5

Note: Offset=Cable loss (4.5) + 10log (50.44/30)=4.5+2.3=6.8 dB



LTE Band 4 - Low Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log (50.13/30)=4.5+2.3=6.8 dB



LTE Band 4 - High Channel 16QAM-5

Note: Offset=Cable loss (4.5) + 10log (50.62/30)=4.5+2.3=6.8 dB



LTE Band 4 - Low Channel QPSK-10

Note: Offset=Cable loss (4.5) + 10log (50.5/30)=4.5+2.3=6.8 dB



LTE Band 4 - High Channel QPSK-10



LTE Band 4 - Low Channel 16QAM-10



LTE Band 4 - High Channel 16QAM-10



LTE Band 4 - Low Channel QPSK-15

Note: Offset=Cable loss (4.5) + 10log (149.7/100)=4.5+1.8=6.3 dB



LTE Band 4 - High Channel QPSK-15

Note: Offset=Cable loss (4.5) + 10log (148.3/100)=4.5+1.7=6.2 dB



LTE Band 4 - Low Channel 16QAM-15

Note: Offset=Cable loss (4.5) + 10log (149.9/100)=4.5+1.8=6.3 dB



LTE Band 4 - High Channel 16QAM-15

Note: Offset=Cable loss (4.5) + 10log (148.9/100)=4.5+1.7=6.2 dB



LTE Band 4 - Low Channel QPSK-20



LTE Band 4 - High Channel QPSK-20

Note: Offset=Cable loss (4.5) + 10log (193.9/100)=4.5+2.9=7.4 dB	Note: Offset=Cable loss (4.5) + 10log (196.9/100)=4.5+2.9=7.4 dB
	
LTE Band 4 - Low Channel 16QAM-20	LTE Band 4 - High Channel 16QAM-20
Note: Offset=Cable loss (4.5) + 10log (194.4/100)=4.5+2.9=7.4dB	Note: Offset=Cable loss (4.5) + 10log (195.9/100)=4.5+2.9=7.4 dB

6.8 Band Edge 27.53(m)

Temperature	23℃
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	----------
Tested By :	Loren Luo

Requirement(s):

Spec	Requirement	Applicable
§27.53(m)	According to FCC 27.53(m)(4) specified that power of any emmission ouutside of the channel edge must be attenuated below the transmitting power(P) by a factor shall be not less than 43+10log (P)dB at the channel edge, the limit of emission equal to -13dBm. And 55+10log (P)dB at 5.5MHz from the channel edges, the limit of emission equal to -25dBm. In the 1MHz bands immediately outside and adjacent to the frenqency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.	☐
Test Setup		
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.	
Remark		
Result	☐ Pass ☐ Fail ☑ N/A	

Test Data ☐ Yes ☑ N/A

Test Plot ☐ Yes (See below) ☑ N/A

6.9 Frequency Stability

Temperature	25℃
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	July 28, 2016
Tested By :	Loren Luo

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>§2.1055,
§ 27.5(h);
§ 27.54</td><td>a)</td><td>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:
Frequency Tolerance for Transmitters in the Public Mobile Services
<table>
<tr><th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr>
<tr><td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr>
<tr><td>to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr>
<tr><td>450 to 512</td><td>2.5</td><td>5.0</td><td>5 0</td></tr>
<tr><td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr>
<tr><td>928 to 929.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr>
<tr><td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr>
<tr><td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr>
</table>
According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.
According to §27.54, The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.</td><td>☑</td></tr>
</table>

Test setup	
Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.
Remark	Frequency Stability versus Temperature: The Frequency tolerance of the carrier signal shall be maintained within 2.5ppm of the operating frequency over a temperature variation of -10ºC to +55ºC at normal supply voltage.
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☑ N/A

LTE Band 4 (Part 27) result

Middle Channel, f_o = 1732.5 MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0092	2.5
0		14	0.0081	2.5
10		11	0.0063	2.5
20		9	0.0052	2.5
30		11	0.0063	2.5
40		12	0.0069	2.5
50		16	0.0092	2.5
55		18	0.0104	2.5
25	4.2	12	0.0069	2.5
	3.5	12	0.0069	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/16/2015	09/15/2016	☑
Power Splitter	1#	1#	09/01/2015	08/31/2016	☑
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	☑
Wideband Radio Communication Tester	CMW500	120906	03/27/2016	03/26/2017	☑
Temperature/Humidity Chamber	UHL-270	001	10/09/2015	10/08/2016	☑
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	☑
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/17/2015	09/16/2016	☑
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	☑
Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	09/01/2015	08/31/2016	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	☑
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/21/2015	09/20/2016	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/24/2015	09/23/2016	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	☑
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/17/2015	09/16/2016	☑
Tunable Notch Filter	3NF-800/1000-S	AA4	09/01/2015	08/31/2016	☑

Tunable Notch Filter	3NF-1000/2000-S	AM 4	09/01/2015	08/31/2016	☑

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View

Adapter - Front View

EUT - Front View

EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1

Cover Off - Top View 2



Battery - Front View



Battery - Rear View



Mainboard with Shielding - Front View



Mainboard without Shielding - Front View



Mainboard with Shielding - Rear View



Mainboard without Shielding - Rear View

LCD – Front View

LCD – Rear View

GSM/PCS/UMTS-FDD Antenna View

WIFI/BT/BLE/GPS - Antenna View

LTE Antenna View	

Annex B.iii. Photograph: Test Setup Photo

	
Radiated Spurious Emissions Test Setup Below 1GHz	Radiated Spurious Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. il. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
MOBIWIRE MOBILES (NINGBO) CO.,LTD	Adapter	S005UA0500100	CBA3000AH0C1

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	CBA3000AH0C1

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A