



FCC RADIO TEST REPORT-BLE

FCC ID:2ADBD-PRIDE8

Product: HEXA Pride 8

Trade Name: HEXA

Model Name: Pride 8

Serial Model: Em-l8880

Report No.: NTEK-2015NT1112537F3

Prepared for

Shen zhen Vinsdom Electronics Co.,Ltd.
4th Floor,Building 2 Huang Tian Heng Chang Rong High-Tech
Industrial Park,BaoAn District,Shen Zhen, China.

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website:www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name Shen zhen Vinsdom Electronics Co.,Ltd.
Address 4th Floor,Building 2 Huang Tian Heng Chang Rong High-Tech
 Industrial Park,BaoAn District,Shen Zhen, China.
Manufacture's Name... Hallmark Global LTD dba HEXA
Address Unit 1, 196 Drumlin Circle, Vaughan, Ontario, Canada, L4K 3E5

Product description

Product name HEXA Pride 8
Model and/or type Pride 8
reference
Serial Model Em-l8880

Standards FCC Part15.247: 01 Oct. 2015

Test procedure ANSI C63.10-2013 and KDB 558074: June 5, 2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests 12 Nov. 2015 ~26 Nov. 2015

Date of Issue..... 26 Nov. 2015

Test Result..... **Pass**

Testing Engineer :

Susan

(Susan Su)

Technical Manager :

Brown Lu

(Brown Lu)

Authorized Signatory :

Sam. Chen

(Sam Chen)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	23
3.2.1 RADIATED EMISSION LIMITS	23
3.2.2 TEST PROCEDURE	24
3.2.3 DEVIATION FROM TEST STANDARD	24
3.2.4 TEST SETUP	25
3.2.5 EUT OPERATING CONDITIONS	26
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	27
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	28
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	30
4 . POWER SPECTRAL DENSITY TEST	31
4.1 APPLIED PROCEDURES / LIMIT	31
4.1.1 TEST PROCEDURE	31
4.1.2 DEVIATION FROM STANDARD	31
4.1.3 TEST SETUP	31
4.1.4 EUT OPERATION CONDITIONS	31
4.1.5 TEST RESULTS	32
5 . BANDWIDTH TEST	34
5.1 APPLIED PROCEDURES / LIMIT	34
5.1.1 TEST PROCEDURE	34

Table of Contents

	Page
TEST SETUP	34
5.1.2 EUT OPERATION CONDITIONS	34
5.1.3 TEST RESULTS	35
6 . PEAK OUTPUT POWER TEST	37
6.1 APPLIED PROCEDURES / LIMIT	37
6.1.1 TEST PROCEDURE	37
6.1.2 DEVIATION FROM STANDARD	37
6.1.3 TEST SETUP	37
6.1.4 EUT OPERATION CONDITIONS	37
6.1.5 TEST RESULTS	38
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	39
7.1 DEVIATION FROM STANDARD	39
7.2 TEST SETUP	39
7.3 EUT OPERATION CONDITIONS	39
7.4 TEST RESULTS	40
8 . ANTENNA REQUIREMENT	42
8.1 STANDARD REQUIREMENT	42
8.2 EUT ANTENNA	42
9 . EUT TEST PHOTO	43
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	HEXA Pride 8	
Trade Name	HEXA	
Model Name	Pride 8	
Serial Model	Em-I8880	
Model Difference	All the model are the same circuit and RF module, except the model name.	
Product Description	The EUT is a HEXA Pride 8	
	Operation Frequency:	2402~2480MHz
	Modulation Type:	GFSK
	Number Of Channel	40CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	1.0dBi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Ratings	DC 3.7V	
Adapter	Model:JK050200-S04USA Input: 100-240V~,50/60 Hz,0.5A Output: 5V $\overline{\text{---}}$,2000mA	
Battery	DC 3.7V, 3500mAh	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency (MHz)
00	2402
01	2404
.....	
.....	
...	...
.....	
38	2478
39	2480

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	FPCB Antenna	N/A	1.0	BT Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Link Mode


Note:

(1) The measurements are performed at the highest, middle, lowest available channels.


2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test


1)



2)



Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	HEXA Pride 8	HEXA	Pride 8	N/A	EUT
E-2	ADAPTER	N/A	JK050200-S04USA	N/A	
E-3	Earphone	N/A	2688	N/A	
E-4	Monitor	SONY	KDL-24EX520	6450750	
E-5	Notebook	Lenove	Thinkpad Edge E430	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.2m	
C-2	NO	NO	1.0m	
C-3	NO	NO	1.0m	
C-4	NO	NO	0.8m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.07	2016.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
2	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.07	2016.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2015.06.08	2016.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2015.06.08	2016.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	26 °C	Relative Humidity:	56%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5.0V form Adapter AC 120V/60Hz	Test Mode:	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1912	43.34	9.46	52.80	63.98	-11.18	QP
0.1912	30.21	9.46	39.67	53.98	-14.31	AVG
0.3002	42.26	9.44	51.70	60.23	-8.53	QP
0.3002	29.76	9.44	39.20	50.23	-11.03	AVG
0.4349	37.45	9.45	46.90	57.16	-10.26	QP
0.4349	26.61	9.45	36.06	47.16	-11.10	AVG
0.6219	35.96	9.44	45.40	56.00	-10.60	QP
0.6219	24.40	9.44	33.84	46.00	-12.16	AVG
1.0740	35.26	9.44	44.70	56.00	-11.30	QP
1.0740	25.58	9.44	35.02	46.00	-10.98	AVG
1.7217	35.76	9.45	45.21	56.00	-10.79	QP
1.7217	22.02	9.45	31.47	46.00	-14.53	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	26 °C	Relative Humidity:	56%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5.0V form Adapter AC 120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2127	40.64	9.46	50.10	63.10	-13.00	QP
0.2127	26.37	9.46	35.83	53.10	-17.27	AVG
0.2878	34.96	9.44	44.40	60.59	-16.19	QP
0.2878	21.18	9.44	30.62	50.59	-19.97	AVG
0.6895	35.27	9.43	44.70	56.00	-11.30	QP
0.6895	22.42	9.43	31.85	46.00	-14.15	AVG
1.1895	33.58	9.44	43.02	56.00	-12.98	QP
1.1895	21.83	9.44	31.27	46.00	-14.73	AVG
2.5299	30.83	9.47	40.30	56.00	-15.70	QP
2.5299	19.45	9.47	28.92	46.00	-17.08	AVG
3.1018	30.53	9.47	40.00	56.00	-16.00	QP
3.1018	18.19	9.47	27.66	46.00	-18.34	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5.0V from adapter AC 240V/60Hz	Test Mode:	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.2340	41.45	9.45	50.90	62.30	-11.40	QP
0.2340	29.96	9.45	39.41	52.30	-12.89	AVG
0.3940	37.26	9.44	46.70	57.98	-11.28	QP
0.3940	24.94	9.44	34.38	47.98	-13.60	AVG
0.5816	35.25	9.45	44.70	56.00	-11.30	QP
0.5816	22.83	9.45	32.28	46.00	-13.72	AVG
1.5820	34.35	9.45	43.80	56.00	-12.20	QP
1.5820	22.85	9.45	32.30	46.00	-13.70	AVG
2.4660	34.43	9.46	43.89	56.00	-12.11	QP
2.4660	22.33	9.46	31.79	46.00	-14.21	AVG
4.4138	31.12	9.48	40.60	56.00	-15.40	QP
4.4138	21.70	9.48	31.18	46.00	-14.82	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5.0V from adapter AC 240V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2479	37.05	9.45	46.50	61.82	-15.32	QP
0.2479	20.78	9.45	30.23	51.82	-21.59	AVG
0.3497	34.30	9.44	43.74	58.97	-15.23	QP
0.3497	16.00	9.44	25.44	48.97	-23.53	AVG
0.65	33.56	9.44	43.00	56.00	-13.00	QP
0.65	17.66	9.44	27.10	46.00	-18.90	AVG
1.3099	32.55	9.45	42.00	56.00	-14.00	QP
1.3099	16.68	9.45	26.13	46.00	-19.87	AVG
2.0619	31.04	9.46	40.50	56.00	-15.50	QP
2.0619	20.16	9.46	29.62	46.00	-16.38	AVG
4.0339	29.63	9.47	39.10	56.00	-16.90	QP
4.0339	14.86	9.47	24.33	46.00	-21.67	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	26 °C	Relative Humidity:	56%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5.0V form PC AC 120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1995	41.10	9.46	50.56	63.63	-13.07	QP
0.1995	24.38	9.46	33.84	53.63	-19.79	AVG
0.3940	37.26	9.44	46.70	57.98	-11.28	QP
0.3940	24.94	9.44	34.38	47.98	-13.60	AVG
0.6895	33.07	9.43	42.50	56.00	-13.50	QP
0.6895	17.23	9.43	26.66	46.00	-19.34	AVG
1.6814	34.42	9.45	43.87	56.00	-12.13	QP
1.6814	20.80	9.45	30.25	46.00	-15.75	AVG
2.4060	33.62	9.46	43.08	56.00	-12.92	QP
2.4060	14.60	9.46	24.06	46.00	-21.94	AVG
3.1339	32.67	9.47	42.14	56.00	-13.86	QP
3.1339	18.97	9.47	28.44	46.00	-17.56	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	26 °C	Relative Humidity:	56%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5.0V form PC AC 120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1862	43.64	9.46	53.10	64.20	-11.10	QP
0.1862	30.61	9.46	40.07	54.20	-14.13	AVG
0.5180	37.74	9.46	47.20	56.00	-8.80	QP
0.5180	25.08	9.46	34.54	46.00	-11.46	AVG
0.9979	33.16	9.44	42.60	56.00	-13.40	QP
0.9979	19.20	9.44	28.64	46.00	-17.36	AVG
2.1499	32.74	9.46	42.20	56.00	-13.80	QP
2.1499	20.99	9.46	30.45	46.00	-15.55	AVG
2.4500	32.74	9.46	42.20	56.00	-13.80	QP
2.4500	21.10	9.46	30.56	46.00	-15.44	AVG
4.5099	31.52	9.48	41.00	56.00	-15.00	QP
4.5099	18.92	9.48	28.40	46.00	-17.60	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5.0V from PC AC 240V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2104	38.94	9.46	48.40	63.19	-14.79	QP
0.2104	25.36	9.46	34.82	53.19	-18.37	AVG
0.3059	36.36	9.44	45.80	60.08	-14.28	QP
0.3059	24.16	9.44	33.60	50.08	-16.48	AVG
0.6500	32.06	9.44	41.50	56.00	-14.50	QP
0.6500	17.70	9.44	27.14	46.00	-18.86	AVG
1.3420	33.42	9.45	42.87	56.00	-13.13	QP
1.3420	17.37	9.45	26.82	46.00	-19.18	AVG
1.8340	30.81	9.46	40.27	56.00	-15.73	QP
1.8340	11.81	9.46	21.27	46.00	-24.73	AVG
2.3380	31.64	9.46	41.10	56.00	-14.90	QP
2.3380	17.44	9.46	26.90	46.00	-19.10	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5.0V from PC AC 240V/60Hz	Test Mode:	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1621	43.44	9.46	52.90	65.35	-12.45	QP
0.1621	24.76	9.46	34.22	55.35	-21.13	AVG
0.262	36.25	9.45	45.70	61.36	-15.66	QP
0.262	20.57	9.45	30.02	51.36	-21.34	AVG
0.5701	32.95	9.45	42.40	56.00	-13.60	QP
0.5701	13.93	9.45	23.38	46.00	-22.62	AVG
1.2459	31.86	9.44	41.30	56.00	-14.70	QP
1.2459	19.01	9.44	28.45	46.00	-17.55	AVG
2.1299	31.94	9.46	41.40	56.00	-14.60	QP
2.1499	10.37	9.46	19.83	46.00	-26.17	AVG
4.1539	29.83	9.47	39.30	56.00	-16.70	QP
4.1539	13.29	9.47	22.76	46.00	-23.24	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Peak	1 MHz	10 Hz

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage:	DC 3.7V
Test Mode:	TX	Polarization:	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode:	TX-MID CH		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	34.2760	8.54	17.46	26.00	40.00	-14.00	QP
V	40.1347	8.92	14.48	23.40	40.00	-16.60	QP
V	97.7980	8.79	10.42	19.21	43.50	-24.29	QP
V	145.3505	12.75	11.31	24.06	43.50	-19.44	QP
V	369.4045	12.67	14.63	27.30	46.00	-18.70	QP
V	444.8514	11.88	15.87	27.75	46.00	-18.25	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	31.1798	10.66	19.14	29.80	40.00	-10.20	QP
H	34.5172	9.22	17.38	26.60	40.00	-13.40	QP
H	109.4116	11.13	10.24	21.37	43.50	-22.13	QP
H	163.1818	14.07	11.63	25.70	43.50	-17.80	QP
H	204.2375	15.64	11.56	27.20	43.50	-16.30	QP
H	261.0581	18.23	10.97	29.20	46.00	-16.80	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode:	TX		

Frequency (MHz)	Reading (dBμV)	Factor (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Polar (H/V)
Low Channel (2402 MHz)-Above 1G							
4804.127	58.61	-3.64	62.25	74.00	-11.75	Pk	Vertical
4804.127	41.45	-3.64	45.09	54.00	-8.91	AV	Vertical
7206.136	56.71	-0.95	57.66	74.00	-16.34	Pk	Vertical
7206.136	36.68	-0.95	37.63	54.00	-16.37	AV	Vertical
4804.217	58.78	-3.64	62.42	74.00	-11.58	Pk	Horizontal
4804.217	41.24	-3.64	44.88	54.00	-9.12	AV	Horizontal
7206.024	56.95	-0.95	57.90	74.00	-16.10	Pk	Horizontal
7206.024	36.77	-0.95	37.72	54.00	-16.28	AV	Horizontal
Mid Channel (2440 MHz)-Above 1G							
4880.147	59.12	-3.68	62.80	74.00	-11.20	Pk	Vertical
4880.147	41.34	-3.68	45.02	54.00	-8.98	AV	Vertical
7320.207	58.71	-0.82	59.53	74.00	-14.47	Pk	Vertical
7320.207	39.52	-0.82	40.34	54.00	-13.66	AV	Vertical
4880.174	61.25	-3.68	64.93	74.00	-9.07	Pk	Horizontal
4880.174	44.38	-3.68	48.06	54.00	-5.94	AV	Horizontal
7320.088	58.68	-0.82	59.50	74.00	-14.50	Pk	Horizontal
7320.088	38.85	-0.82	39.67	54.00	-14.33	AV	Horizontal
High Channel (2480MHz)- Above 1G							
4960.213	58.67	-3.59	62.26	74.00	-11.74	Pk	Vertical
4960.213	41.54	-3.59	45.13	54.00	-8.87	AV	Vertical
7440.031	57.14	-0.68	57.82	74.00	-16.18	Pk	Vertical
7440.031	41.44	-0.68	42.12	54.00	-11.88	AV	Vertical
4960.148	58.58	-3.59	62.17	74.00	-11.83	Pk	Horizontal
4960.148	41.68	-3.59	45.27	54.00	-8.73	AV	Horizontal
7440.205	60.06	-0.68	60.74	74.00	-13.26	Pk	Horizontal
7440.205	38.96	-0.68	39.64	54.00	-14.36	AV	Horizontal

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. 3 kHz $\leq$ Set the RBW $\leq$ 100 kHz.
4. Set the VBW $\geq$ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	25 °C	Relative Humidity:	56%
Pressure:	1015 hPa	Test Voltage:	DC 3.7V
Test Mode:	TX Mode /CH00, CH19, CH39		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2402 MHz	-18.93	8	PASS
2440 MHz	-18.75	8	PASS
2480 MHz	-18.71	8	PASS





5. BANDWIDTH TEST


5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP




5.1.2 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.3 TEST RESULTS

EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	25 °C	Relative Humidity:	56%
Pressure:	1012 hPa	Test Voltage:	DC 3.7V
Test Mode:	TX Mode /CH00, CH19, CH39		

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	683.275	500	Pass
Middle	2440	686.978	500	Pass
High	2480	693.005	500	Pass





6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage:	DC 3.7V
Test Mode:	TX Mode		

Test Channe	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
CH00	2402	-1.14	30
CH20	2440	-1.21	30
CH39	2480	-1.17	30

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

7.1 DEVIATION FROM STANDARD

No deviation.

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.4 TEST RESULTS

EUT:	HEXA Pride 8	Model Name:	Pride 8
Temperature:	25 °C	Relative Humidity:	56%
Pressure:	1012 hPa	Test Voltage:	DC 3.7V


Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
2400	54.65	20	Pass
2483.5	54.80	20	Pass

Radiated band edge:


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
2390	57.07	-13.06	44.01	74	-29.99	peak	Vertical
2390	56.87	-13.06	43.81	74	-30.19	peak	Horizontal
2483.5	58.02	-12.78	45.24	74	-28.76	peak	Vertical
2483.5	58.05	-12.78	45.27	74	-28.73	peak	Horizontal

Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average not record.

Left Side



Right Side



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

9. EUT TEST PHOTO

Radiated Measurement Photos



Conducted Measurement Photos

