

FCC SAR Exclusion Report

Product name : WISR LR
Applicant : Orlaco
FCC ID : 2ADBX-PR1U

Test report No. : 201001090 FCC RF exposure Ver 1.0

Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

Test Site	Kiwa NV
Test Site location	Wilmersdorf 50 7327 AC Apeldoorn The Netherlands Tel. +31 88998 3393

Revision History

Version	Date	Remarks	By
v1.00	11-01-2021	Release version	PvW

Table of Contents

Revision History	2
1 General Description	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Tested Equipment Under Test (EUT)	4
1.4 SAR Measurement Evaluation	5
1.4.1 Maximum Output Power	5
1.4.2 SAR Testing Exclusions	5
1.5 Summary	5

1 General Description

1.1 Applicant

Client name:	Orlaco Products B.V.
Address:	Postbus 193, Barneveld, the Netherlands
Zip code:	3770 AD
Telephone:	0342 404 555
E-mail:	info@orlaco.nl
Contact name:	Mr. A. Canrinus

1.2 Manufacturer

Manufacturer name:	Orlaco Products B.V.
Address:	Postbus 193, Barneveld, the Netherlands
Zip code:	3770 AD
Telephone:	0342 404 555
E-mail:	compliance@orlaco.com
Contact name:	--

1.3 Tested Equipment Under Test (EUT)

Product name:	WISR LR
Brand name:	Orlaco
FCC ID:	2ADBX-PR1U
Product type:	Wireless Send Receive Long Range
Model(s):	--
Batch and/or serial No.	--
Software version:	V1.1.2.8
Hardware version:	PR1UXXXXX

1.4 SAR Measurement Evaluation

1.4.1 Maximum Output Power

The maximum radiated power including tune-up tolerance is shown as below.

Mode	Max power level
802.11n	20.6 dBm*

* from Telefication report 200100090 001.

1.4.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

- For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

- For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Ant. to Surface (mm)	Calculated limit	Require SAR Testing?
802.11n	20.6	114.8	200	1503 mW	No

Note:

- When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 , the SAR testing exclusion is applied.
- When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

1.5 Summary

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.