

TEST REPORT

Applicant: Acuity Brands Lighting, Inc.

Address: One Lithonia Way Conyers, Georgia 30012, United States.

Product Name: Atrius Wireless Module

FCC ID: 2ADCB-AMODIT

IC: 6715C-AMODIT

HVIN: AMODIT, AMODITX

47 CFR Part 15, Subpart C(15.247)

RSS-247 Issue 4, July 24, 2025

Standard(s): RSS-Gen, Issue 5, February 2021 Amendment 2
ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to
C63.10a-2024

KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: 2602U03664E-RF-00A

Report Date: 2026/8/28

The above device has been tested and found compliant with the requirement of the relevant standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Alice Tan

Pedro Yun

Reviewed By: Alice Tan

Approved By: Pedro Yun

Title: RF Engineer

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	5
1.4 EQUIPMENT MODIFICATIONS	5
2. SUMMARY OF TEST RESULTS	6
3. DESCRIPTION OF TEST CONFIGURATION	7
3.1 OPERATION FREQUENCY DETAIL	7
3.2 EUT OPERATION CONDITION	7
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	7
3.4 SUPPORT CABLE LIST AND DETAILS	7
3.5 BLOCK DIAGRAM OF TEST SETUP	8
3.6 TEST FACILITY	10
3.7 MEASUREMENT UNCERTAINTY	10
4. REQUIREMENTS AND TEST PROCEDURES	11
4.1 AC LINE CONDUCTED EMISSIONS	11
4.1.1 Applicable Standard	11
4.1.2 EUT Setup	13
4.1.3 EMI Test Receiver Setup	13
4.1.4 Test Procedure	14
4.1.5 Corrected Amplitude & Margin Calculation	14
4.1.6 Test Result	14
4.2 RADIATION SPURIOUS EMISSIONS	15
4.2.1 Applicable Standard	15
4.2.2 EUT Setup	15
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	17
4.2.4 Test Procedure	17
4.2.5 Corrected Result & Margin Calculation	17
4.2.6 Test Result	18
4.3 MINIMUM 6 DB EMISSION BANDWIDTH	19
4.3.1 Applicable Standard	19
4.3.2 EUT Setup	19
4.3.3 Test Procedure	19
4.3.4 Test Result	19
4.4 99% OCCUPIED BANDWIDTH:	20
4.4.1 Applicable Standard	20
4.4.2 EUT Setup	20
4.4.3 Test Procedure	21
4.4.4 Test Result	21
4.5 MAXIMUM CONDUCTED OUTPUT POWER:	22
4.5.1 Applicable Standard	22
4.5.2 EUT Setup	22
4.5.3 Test Procedure	22
4.5.4 Test Result	22

4.6 MAXIMUM POWER SPECTRAL DENSITY:	23
4.6.1 Applicable Standard	23
4.6.2 EUT Setup	23
4.6.3 Test Procedure	23
4.6.4 Test Result	23
4.7 CONDUCTED SPURIOUS EMISSION:	24
4.7.1 Applicable Standard	24
4.7.2 EUT Setup	24
4.7.3 Test Procedure	24
4.7.4 Test Result	25
4.8 DUTY CYCLE:	26
4.8.1 EUT Setup	26
4.8.2 Test Procedure	26
4.8.3 Judgment	26
4.9 ANTENNA REQUIREMENT	27
4.9.1 Applicable Standard	27
4.9.2 Judgment	27
5. TEST DATA AND RESULTS	28
5.1 AC LINE CONDUCTED EMISSIONS	28
5.2 RADIATION SPURIOUS EMISSIONS	33
5.3 6dB EMISSION BANDWIDTH	53
5.4 99% OCCUPIED BANDWIDTH	55
5.5 MAXIMUM CONDUCTED OUTPUT POWER	57
5.6 POWER SPECTRAL DENSITY	59
5.7 CONDUCTED SPURIOUS EMISSION	61
5.8 DUTY CYCLE	63
EXHIBIT A - EUT PHOTOGRAPHS	64
EXHIBIT B - TEST SETUP PHOTOGRAPHS	65
EXHIBIT C - RF EXPOSURE EVALUATION	66
MAXIMUM PERMISSIBLE EXPOSURE (MPE)	66
EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION	67

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2602U03664E-RF-00A	Original Report	2026/8/28

1. GENERAL INFORMATION

1.1 General Description Of Equipment under Test

EUT Name:	Atrius Wireless Module
EUT Model:	AMODIT
Multiple Model:	AMODITX
Operation Frequency:	2402-2480 MHz
Maximum Peak Output Power (Conducted):	3.73dBm
Modulation Type:	GFSK
Rated Input Voltage:	120VAC
Serial Number:	CE& RE: 3OOV-2 (Model: AMODIT) CE& RE: 3OOV-3 (Model: AMODITX) RF Conducted: 3OOV-1(Model: AMODIT)
EUT Received Date:	2026/6/22
EUT Received Status:	Good
Note: There are two models of the equipment, they are electrically identical. The difference is Model AMODIT have BLE PCB Antenna and Model AMODITX have BLE external Antenna. Please refer to the declaration letter for more detail, which was provided by manufacturer. Two model was tested for AC line conducted emissions and Radiated Spurious Emissions, and only model AMODIT was tested for RF Conducted.	

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.3 Antenna Information Detail▲

Antenna Type	input impedance (Ohm)	Frequency Range (MHz)	Antenna Gain (dBi)
PCB Antenna (Model: AMODIT)	50	2402-2480	3
Monopole Antenna (Model: AMODITX)	50	2402-2480	4
The design of compliance with §15.203:			
☒ Unit uses a permanently attached antenna. ☐ Unit uses a unique coupling to the intentional radiator. ☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.			

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a) RSS-Gen Clause 8.8	AC line conducted emissions	Compliant
§15.205, §15.209, §15.247(d) RSS-Gen Clause 8.10 RSS-247 Clause 6.6	Radiated Spurious Emissions	Compliant
§15.247 (a)(2) RSS-247 Clause 6.3.1 a)	Minimum 6 dB Bandwidth	Compliant
RSS-Gen Clause 6.7	99% Occupied Bandwidth	Compliant
§15.247(b)(3) RSS-247 Clause 6.3.2	Maximum Conducted Output Power	Compliant
§15.247(e) RSS-247 Clause 6.3.1 b)	Power Spectral Density	Compliant
§15.247(d) RSS-247 Clause 6.6	Conducted Spurious Emission	Compliant
FCC §15.203 RSS-Gen Clause 6.8	Antenna Requirement	Compliant
FCC §1.1310&§2.1091& §15.247 (i)	Maximum Permissible Exposure (MPE)	Compliant
RSS-102 Clause 6.6	Exemption Limits For Routine Evaluation-RF Exposure Evaluation	Compliant

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
...	...	38	2478
19	2440	39	2480

Note 1: The above frequencies in bold were performed the test.

Note 2: For AC line conducted emissions, the maximum output power mode and channel was tested.

Note 3: For Radiated Spurious Emissions 9kHz~1GHz and 18~25GHz, the maximum output power mode and channel was tested.

3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software:	Engineering mode		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
BLE 1Mbps	Default	Default	Default

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Lamp Bulb	Unknown	Unknown
Unknown	Socket	Unknown	Unknown

3.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	2	Lamp Bulb	EUT
AC Cable	No	No	1	AC Mains	EUT
AC Cable	No	No	1	Socket	EUT

3.5 Block Diagram of Test Setup


AC line conducted emissions:



Spurious Emissions:
Below 1GHz:



Spurious Emissions:
Above 1GHz:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.55 dB
Power Spectral Density, conducted	±0.55 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.06dB, 30MHz~1GHz: 6.13 dB, 1GHz~6GHz: 4.79 dB, 6GHz~18GHz: 4.63 dB, 18GHz~26.5GHz: 4.79 dB, 26.5GHz~40GHz: 4.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.83 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

- (1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.
- (2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.
- (3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits


Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard

FCC §15.247 (d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 Clause 6.6


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power -based on either an RF conducted or a radiated measurement -provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

4.2.2 EUT Setup


9kHz-30MHz:



30MHz~1GHz:



1-25GHz:



The radiated emissions were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247, RSS-247, RSS-Gen limits.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz-150 kHz	QP/AV	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz-30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30 MHz-1000 MHz	Peak	120 kHz	500 kHz	/	PK
	QP	/	/	120 kHz	QP

Above 1GHz:

Pre-scan:

Frequency Range	Measurement	RBW	Video B/W	Detector
Above 1 GHz	Peak	1MHz	3 MHz	PK
	AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	≥1/T

Note: T is minimum transmission duration

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was required in Quasi-peak measurement for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average measurement, peak and Average measurement for frequencies above 1 GHz.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

4.2.5 Corrected Result & Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

E_{Linear} is the field strength of the emission, in $\mu V/m$

E_{Log} is the field strength of the emission, in dB $\mu V/m$

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{limit-measure} = E_{limit-Standard} + 40 \times \log_{10} (d_{standard}/d_{measure})$$

The basic equation is as follows:

Factor = Antenna Factor + Cable Loss - Amplifier Gain

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

For the spurious emission below 30MHz, the limit was convert from dBμA/m to dBμV/m by adding 51.5 dB.

4.2.6 Test Result

Please refer to section 5.2.

4.3 Minimum 6 dB Emission Bandwidth

4.3.1 Applicable Standard


FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

RSS-247 Clause 6.3.1 a

The minimum 6 dB bandwidth shall be 500 kHz.

4.3.2 EUT Setup



4.3.3 Test Procedure

According to ANSI C63.10-2020 Section 11.8

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

4.3.4 Test Result

Please refer to section 5.3.

4.4 99% Occupied Bandwidth:

4.4.1 Applicable Standard

RSS-Gen Clause 6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.


The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

4.4.2 EUT Setup



4.4.3 Test Procedure

According to ANSI C63.10-2020 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.4.4 Test Result

Please refer to section 5.4.

4.5 Maximum Conducted Output Power:

4.5.1 Applicable Standard


FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

RSS-247 Clause 6.3.2

For DTS operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W, and the e.i.r.p. shall not exceed 4 W, except as provided in section 6.5 a) and b).

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.5.3 Test Procedure

According to ANSI C63.10-2020 Section 11.9.1.1

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Set span $\geq [3 \times \text{RBW}]$.
- Sweep time = No faster than coupled (auto) time.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

4.5.4 Test Result

Please refer to section 5.5.

4.6 Maximum power spectral density:

4.6.1 Applicable Standard


FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

RSS-247 Clause 6.3.1b

The transmitter power spectral density conducted from the transmitter to the antenna(s) shall not be greater than 8 dBm/3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 6.3.2. The power spectral density shall be determined using the same method as is used to determine the maximum conducted output power.

4.6.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.6.3 Test Procedure

According to ANSI C63.10-2020 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span >1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

4.6.4 Test Result

Please refer to section 5.6.

4.7 Conducted Spurious Emission:

4.7.1 Applicable Standard


FCC §15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 Clause 6.6

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement –provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

4.7.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.7.3 Test Procedure

According to ANSI C63.10-2020 Section 11.11.3

- Set the center frequency and span to encompass frequency range to be measured.
 - Set the RBW = 100 kHz.
 - Set the VBW $\geq [3 \times \text{RBW}]$.
 - Detector = peak.
 - Sweep time = No faster than coupled (auto) time.
 - Trace mode = max hold.
 - Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum amplitude level.
- Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding


restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

4.7.4 Test Result

Please refer to section 5.7.

4.8 Duty Cycle:

4.8.1 EUT Setup



4.8.2 Test Procedure

According to ANSI C63.10-2020 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.8.3 Judgment

Report Only. Please refer to section 5.8.

4.9 Antenna Requirement

4.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. TEST DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	300V-2,300V-3	Test Date:	2026/08/17
Test Site:	CE	Test Mode:	Transmitting
Tester:	Joe Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	57	ATM Pressure: (kPa)	99.7
----------------------	------	---------------------------	----	------------------------	------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2026/6/15	2027/6/14
Unknown	Coaxial Cable	RG 142	C-0200-05	2026/4/9	2027/4/8
R&S	EMI Test Receiver	ESCI	100340	2026/6/15	2027/6/14
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Please refer to the below plots.
Note: BLE 1Mbps Low channel was tested.

Model: AMODIT

Project No.: 2602U03664E-RF
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 300V-2
Tester: Joe Li
Note: BLE

Date: 2026-08-17




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.366	37.83	10.92	48.75	58.59	9.84	QP
2	0.366	35.95	10.92	46.87	48.59	1.72	Average
3	0.388	40.36	10.86	51.22	58.11	6.89	QP
4	0.388	30.28	10.86	41.14	48.11	6.97	Average
5	0.412	38.84	10.79	49.63	57.62	7.99	QP
6	0.412	23.65	10.79	34.44	47.62	13.18	Average
7	0.710	35.78	10.54	46.32	56.00	9.68	QP
8	0.710	18.26	10.54	28.80	46.00	17.20	Average
9	0.751	37.25	10.61	47.86	56.00	8.14	QP
10	0.751	17.38	10.61	27.99	46.00	18.01	Average
11	2.858	35.37	10.91	46.28	56.00	9.72	QP
12	2.858	13.17	10.91	24.08	46.00	21.92	Average

Project No.: 2602U03664E-RF
Port: neutral
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 300V-2
Tester: Joe Li
Note: BLE

Date: 2026-08-17




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.373	30.54	10.73	41.27	58.44	17.17	QP
2	0.373	19.50	10.73	30.23	48.44	18.21	Average
3	0.508	32.04	10.23	42.27	56.00	13.73	QP
4	0.508	15.33	10.23	25.56	46.00	20.44	Average
5	0.695	31.00	10.33	41.33	56.00	14.67	QP
6	0.695	7.00	10.33	17.33	46.00	28.67	Average
7	0.774	30.84	10.51	41.35	56.00	14.65	QP
8	0.774	6.90	10.51	17.41	46.00	28.59	Average
9	1.444	23.12	11.14	34.26	56.00	21.74	QP
10	1.444	5.17	11.14	16.31	46.00	29.69	Average
11	3.174	21.40	11.19	32.59	56.00	23.41	QP
12	3.174	3.56	11.19	14.75	46.00	31.25	Average

Model: AMODITX

Project No.: 2602U03664E-RF
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 300V-3
Tester: Joe Li
Note: BLE

Date: 2026-08-17




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.358	42.47	10.95	53.42	58.79	5.37	QP
2	0.358	36.43	10.95	47.38	48.79	1.41	Average
3	0.370	43.21	10.91	54.12	58.51	4.39	QP
4	0.370	34.91	10.91	45.82	48.51	2.69	Average
5	0.386	41.37	10.86	52.23	58.14	5.91	QP
6	0.386	29.99	10.86	40.85	48.14	7.29	Average
7	0.397	40.53	10.83	51.36	57.92	6.56	QP
8	0.397	26.84	10.83	37.67	47.92	10.25	Average
9	0.588	35.22	10.53	45.75	56.00	10.25	QP
10	0.588	22.42	10.53	32.95	46.00	13.05	Average
11	0.693	33.82	10.53	44.35	56.00	11.65	QP
12	0.693	19.05	10.53	29.58	46.00	16.42	Average
13	0.727	33.55	10.57	44.12	56.00	11.88	QP
14	0.727	18.32	10.57	28.89	46.00	17.11	Average
15	0.756	33.62	10.61	44.23	56.00	11.77	QP
16	0.756	18.45	10.61	29.06	46.00	16.94	Average
17	1.380	32.57	10.95	43.52	56.00	12.48	QP
18	1.380	13.32	10.95	24.27	46.00	21.73	Average
19	3.349	31.64	10.88	42.52	56.00	13.48	QP
20	3.349	12.87	10.88	23.75	46.00	22.25	Average

Project No.: 2602U03664E-RF
 Port: neutral
 Test Mode: Transmitting
 IF B/W 9kHz PK/AV

Serial No.: 300V-3
 Tester: Joe Li
 Note: BLE

Date: 2026-08-17



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.368	37.00	10.75	47.75	58.54	10.79	QP
2	0.368	28.10	10.75	38.85	48.54	9.69	Average
3	0.496	33.02	10.25	43.27	56.07	12.80	QP
4	0.496	17.45	10.25	27.70	46.07	18.37	Average
5	0.675	35.00	10.32	45.32	56.00	10.68	QP
6	0.675	13.66	10.32	23.98	46.00	22.02	Average
7	0.723	33.95	10.38	44.33	56.00	11.67	QP
8	0.723	14.51	10.38	24.89	46.00	21.11	Average
9	0.754	30.74	10.47	41.21	56.00	14.79	QP
10	0.754	11.73	10.47	22.20	46.00	23.80	Average
11	1.360	33.25	11.12	44.37	56.00	11.63	QP
12	1.360	9.73	11.12	20.85	46.00	25.15	Average

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	300V-2, 300V-3	Test Date:	2026/7/18
Test Site:	Chamber 10m	Test Mode:	Transmitting
Tester:	Mikey Lin	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.2	Relative Humidity: (%)	53	ATM Pressure: (kPa)	100
----------------------	------	---------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Coaxial Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2026/6/15	2027/6/14
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2026/6/15	2027/6/14
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2026/6/15	2027/6/14
Sonoma	Amplifier	310N	185914	2025/8/25	2026/8/24
R&S	EMI Test Receiver	ESR3	102453	2026/6/15	2027/6/14
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case(X axes) is refer to the below plots.

Note: BLE 1Mbps Low channel was tested.


9kHz~30MHz:

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

Model: AMODIT

Project No.: 2602U03664E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: RBW:200Hz VBW:1kHz


Serial No.: 300V-2
Tester: Mikey Lin



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.010	8.42	55.20	63.62	127.86	64.24	Peak
2	0.012	12.98	54.70	67.68	126.05	58.37	Peak
3	0.017	6.20	53.38	59.58	122.76	63.18	Peak
4	0.021	10.79	52.53	63.32	120.99	57.67	Peak
5	0.024	8.02	52.08	60.10	120.02	59.92	Peak
6	0.035	15.91	49.81	65.72	116.63	50.91	Peak

Project No.: 2602U03664E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: RBW:9kHz VBW:30kHz


Serial No.: 300V-2
Tester: Mikey Lin



Model: AMODITX

Project No.: 2602U03664E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: RBW:200Hz VBW:1kHz


Serial No.: 300V-3
Tester: Mikey Lin



No.	Frequency	Reading	Factor	Result	Limit	Margin	Measurement
	(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	
1	0.009	15.05	55.25	70.30	128.38	58.08	Peak
2	0.011	14.13	54.90	69.03	126.69	57.66	Peak
3	0.012	14.07	54.70	68.77	126.05	57.28	Peak
4	0.020	11.07	52.81	63.88	121.65	57.77	Peak
5	0.024	10.52	52.08	62.60	120.02	57.42	Peak
6	0.035	15.92	49.81	65.73	116.63	50.90	Peak

Project No.: 2602U03664E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: RBW:9kHz VBW:30kHz


Serial No.: 300V-3
Tester: Mikey Lin



30MHz-1GHz:
Model: AMODIT

Project No.: 2602U03664E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: RBW:120kHz VBW:500kHz


Serial No.: 300V-2
Tester: Mikey Lin



No.	Frequency	Reading	Factor	Result	Limit	Margin	Measurement
	(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	
1	30.00	26.38	-1.28	25.10	40.00	14.90	Peak
2	56.19	42.66	-14.66	28.00	40.00	12.00	Peak
3	71.71	37.67	-14.54	23.13	40.00	16.87	Peak
4	77.53	41.39	-14.49	26.90	40.00	13.10	Peak
5	123.12	35.29	-8.61	26.68	43.50	16.82	Peak
6	176.47	36.70	-11.14	25.56	43.50	17.94	Peak

Project No.: 2602U03664E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: RBW:120kHz VBW:500kHz

Serial No.: 300V-2
Tester: Mikey Lin



No.	Frequency	Reading	Factor	Result	Limit	Margin	Measurement
	(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	
1	40.67	43.84	-8.63	35.21	40.00	4.79	QP
2	54.25	39.78	-14.53	25.25	40.00	14.75	Peak
3	83.35	43.76	-14.55	29.21	40.00	10.79	Peak
4	174.53	41.93	-11.09	30.84	43.50	12.66	Peak
5	208.48	35.19	-10.70	24.49	43.50	19.01	Peak
6	229.82	39.16	-11.41	27.75	46.00	18.25	Peak

Model: AMODITX

Project No.: 2602U03664E-RF


Serial No.: 300V-3

Polarization: Horizontal

Tester: Mikey Lin

Test Mode: Transmitting


Note: RBW:120kHz VBW:500kHz



No.	Frequency	Reading	Factor	Result	Limit	Margin	Measurement
	(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	
1	30.97	27.97	-2.05	25.92	40.00	14.08	Peak
2	77.53	41.67	-14.49	27.18	40.00	12.82	Peak
3	105.66	38.42	-10.77	27.65	43.50	15.85	Peak
4	146.40	46.15	-10.00	36.15	43.50	7.35	Peak
5	159.01	37.88	-10.38	27.50	43.50	16.00	Peak
6	206.54	33.57	-10.62	22.95	43.50	20.55	Peak

Project No.: 2602U03664E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: RBW:120kHz VBW:500kHz

Serial No.: 300V-3
Tester: Mikey Lin



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	31.94	40.18	-3.19	36.99	40.00	3.01	QP
2	77.53	46.17	-14.49	31.68	40.00	8.32	Peak
3	98.87	38.45	-12.46	25.99	43.50	17.51	Peak
4	136.70	35.51	-9.36	26.15	43.50	17.35	Peak
5	146.40	33.86	-10.00	23.86	43.50	19.64	Peak
6	163.86	34.32	-10.61	23.71	43.50	19.79	Peak

2) 1-25GHz:

Serial Number:	3OOV-2, 3OOV-3	Test Date:	2026/7/6~2026/8/5
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Leo Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3-27.6	Relative Humidity: (%)	55-60	ATM Pressure: (kPa)	99.9-100.1
----------------------	-----------	---------------------------	-------	------------------------	------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2026/2/21	2029/2/20
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2025/11/17	2026/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2025/11/14	2026/11/13
AH	Preamplifier	PAM-0118P	469	2026/5/18	2027/5/17
AH	Preamplifier	PAM-1840VH	191	2025/9/4	2026/9/3
R&S	Spectrum Analyzer	FSV40	101944	2025/8/8	2026/8/7
Audix	Test Software	E3	191218 V9	N/A	N/A
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2025/8/25	2026/8/24

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case(X axes) is refer to the below plots.

1-18GHz:
External Antenna(AMODITX):

BLE 1M Low channel Horizontal

Project No.: 2602U03664E-RF

Serial No.: 300V-3

Polarization: Horizontal

Tester: Leo Xiao

Test Mode: Transmitting

Note: BLE 1M low channel 2402MHz External Antenna

Peak: RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Frequency (MHz)

2026-08-05

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3896.20	50.68	-1.53	49.15	74.00	24.85	Peak

Project No.: 2602U03664E-RF

Serial No.: 300V-3

Polarization: Vertical

Tester: Leo Xiao

Test Mode: Transmitting

Note: BLE 1M low channel 2402MHz External Antenna

Peak: RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Frequency (MHz)

2026-08-05

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2273.80	55.62	-7.26	48.36	74.00	25.64	Peak

Project No.: 2602U03664E-RF

Serial No.: 300V-3

Polarization: Horizontal

Tester: Leo Xiao

Test Mode: Transmitting

Note: BLE 1M low channel 2402MHz External Antenna

Peak: RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

2026-08-05

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4804.00	55.55	-6.38	49.17	74.00	24.83	Peak
2	7206.00	51.78	-2.58	49.20	74.00	24.80	Peak
3	17932.80	50.61	9.60	60.21	74.00	13.79	Peak
4	17932.80	37.60	9.60	47.20	54.00	6.80	Average

Project No.: 2602U03664E-RF

Serial No.: 300V-3

Polarization: Vertical

Tester: Leo Xiao

Test Mode: Transmitting

Note: BLE 1M low channel 2402MHz External Antenna

Peak: RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Level (dBuV/m)

Frequency (MHz)




2026-08-05

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4804.00	56.26	-6.38	49.88	74.00	24.12	Peak
2	7206.00	52.94	-2.58	50.36	74.00	23.64	Peak
3	17988.80	49.83	9.95	59.78	74.00	14.22	Peak
4	17988.80	37.70	9.95	47.65	54.00	6.35	Average

BLE 1M Middle channel Horizontal



BLE 1M Middle channel Vertical



BLE 1M High channel Horizontal							
Project No.: 2602U03664E-RF Polarization: Horizontal Test Mode: Transmitting Note: BLE 1M high channel 2480MHz External Antenna Peak:RBW:1MHz,VBW:3MHz				Serial No.: 300V-3 Tester: Leo Xiao			
Date: 2026-08-05							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2608.00	55.24	-5.80	49.44	74.00	24.56	Peak

BLE 1M High channel Vertical							
Project No.: 2602U03664E-RF Polarization: Vertical Test Mode: Transmitting Note: BLE 1M high channel 2480MHz External Antenna Peak:RBW:1MHz,VBW:3MHz				Serial No.: 300V-3 Tester: Leo Xiao			
Date: 2026-08-05							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2351.80	55.50	-6.82	48.68	74.00	25.32	Peak

Project No.: 2602U03664E-RF Polarization: Horizontal Test Mode: Transmitting Note: BLE 1M high channel 2480MHz External Antenna Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 300V-3 Tester: Leo Xiao			
Date: 2026-08-05							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4960.00	49.63	-6.31	43.32	74.00	30.68	Peak
2	7440.00	49.82	-1.60	48.22	74.00	25.78	Peak
3	17918.80	50.09	9.58	59.67	74.00	14.33	Peak
4	17918.80	37.61	9.58	47.19	54.00	6.81	Average

Project No.: 2602U03664E-RF Polarization: Vertical Test Mode: Transmitting Note: BLE 1M high channel 2480MHz External Antenna Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 300V-3 Tester: Leo Xiao			
Date: 2026-08-05							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4960.00	51.06	-6.31	44.75	74.00	29.25	Peak
2	7440.00	51.86	-1.60	50.26	74.00	23.74	Peak
3	17994.40	49.70	10.09	59.79	74.00	14.21	Peak
4	17994.40	37.65	10.09	47.74	54.00	6.26	Average


Onboard PCB Antenna (AMODIT):

BLE 1M Low channel Horizontal				BLE 1M Low channel Vertical																																																																																			
Project No.: 2602U03664E-RF Serial No.: 300V-2 Polarization: Horizontal Tester: Leo Xiao Test Mode: Transmitting Note: BLE 1M low channel 2402MHz Onboard PCB Antenna Peak: RBW:1MHz,VBW:3MHz Date: 2026-08-05 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>2530.00</td><td>55.41</td><td>-6.12</td><td>49.29</td><td>74.00</td><td>24.71</td><td>Peak</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	2530.00	55.41	-6.12	49.29	74.00	24.71	Peak	Project No.: 2602U03664E-RF Serial No.: 300V-2 Polarization: Vertical Tester: Leo Xiao Test Mode: Transmitting Note: BLE 1M low channel 2402MHz Onboard PCB Antenna Peak: RBW:1MHz,VBW:3MHz Date: 2026-08-05 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>3932.80</td><td>50.08</td><td>-1.70</td><td>48.38</td><td>74.00</td><td>25.62</td><td>Peak</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	3932.80	50.08	-1.70	48.38	74.00	25.62	Peak																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	2530.00	55.41	-6.12	49.29	74.00	24.71	Peak																																																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	3932.80	50.08	-1.70	48.38	74.00	25.62	Peak																																																																																
Project No.: 2602U03664E-RF Serial No.: 300V-2 Polarization: Horizontal Tester: Leo Xiao Test Mode: Transmitting Note: BLE 1M low channel 2402MHz Onboard PCB Antenna Peak: RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Date: 2026-08-05 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>4804.00</td><td>49.63</td><td>-6.38</td><td>43.25</td><td>74.00</td><td>30.75</td><td>Peak</td></tr><tr><td>2</td><td>7206.00</td><td>50.09</td><td>-2.58</td><td>47.51</td><td>74.00</td><td>26.49</td><td>Peak</td></tr><tr><td>3</td><td>17988.00</td><td>49.69</td><td>9.95</td><td>59.64</td><td>74.00</td><td>14.36</td><td>Peak</td></tr><tr><td>4</td><td>17988.00</td><td>37.89</td><td>9.95</td><td>47.84</td><td>54.00</td><td>6.16</td><td>Average</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	4804.00	49.63	-6.38	43.25	74.00	30.75	Peak	2	7206.00	50.09	-2.58	47.51	74.00	26.49	Peak	3	17988.00	49.69	9.95	59.64	74.00	14.36	Peak	4	17988.00	37.89	9.95	47.84	54.00	6.16	Average	Project No.: 2602U03664E-RF Serial No.: 300V-2 Polarization: Vertical Tester: Leo Xiao Test Mode: Transmitting Note: BLE 1M low channel 2402MHz Onboard PCB Antenna Peak: RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Date: 2026-08-05 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>4804.00</td><td>48.89</td><td>-6.38</td><td>42.51</td><td>74.00</td><td>31.49</td><td>Peak</td></tr><tr><td>2</td><td>7206.00</td><td>50.74</td><td>-2.58</td><td>48.16</td><td>74.00</td><td>25.84</td><td>Peak</td></tr><tr><td>3</td><td>17913.20</td><td>50.56</td><td>9.59</td><td>60.15</td><td>74.00</td><td>13.85</td><td>Peak</td></tr><tr><td>4</td><td>17913.20</td><td>37.86</td><td>9.59</td><td>47.45</td><td>54.00</td><td>6.55</td><td>Average</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	4804.00	48.89	-6.38	42.51	74.00	31.49	Peak	2	7206.00	50.74	-2.58	48.16	74.00	25.84	Peak	3	17913.20	50.56	9.59	60.15	74.00	13.85	Peak	4	17913.20	37.86	9.59	47.45	54.00	6.55	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	4804.00	49.63	-6.38	43.25	74.00	30.75	Peak																																																																																
2	7206.00	50.09	-2.58	47.51	74.00	26.49	Peak																																																																																
3	17988.00	49.69	9.95	59.64	74.00	14.36	Peak																																																																																
4	17988.00	37.89	9.95	47.84	54.00	6.16	Average																																																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	4804.00	48.89	-6.38	42.51	74.00	31.49	Peak																																																																																
2	7206.00	50.74	-2.58	48.16	74.00	25.84	Peak																																																																																
3	17913.20	50.56	9.59	60.15	74.00	13.85	Peak																																																																																
4	17913.20	37.86	9.59	47.45	54.00	6.55	Average																																																																																

BLE 1M Middle channel Horizontal

Project No.: 2602U03664E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BLE 1M middle channel 2442MHz Onboard PCB Antenna
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 300V-2
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2570.20	56.18	-6.12	50.06	74.00	23.94	Peak

BLE 1M Middle channel Vertical

Project No.: 2602U03664E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BLE 1M middle channel 2442MHz Onboard PCB Antenna
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 300V-2
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3986.80	50.55	-1.57	48.98	74.00	25.02	Peak

Project No.: 2602U03664E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BLE 1M middle channel 2442MHz Onboard PCB Antenna
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 300V-2
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4884.00	49.08	-6.33	42.75	74.00	31.25	Peak
2	7326.00	50.07	-2.09	47.98	74.00	26.02	Peak
3	17955.20	50.57	9.72	60.29	74.00	13.71	Peak
4	17955.20	38.00	9.72	47.72	54.00	6.28	Average


Project No.: 2602U03664E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BLE 1M middle channel 2442MHz Onboard PCB Antenna
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 300V-2
Tester: Leo Xiao






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4884.00	49.72	-6.33	43.39	74.00	30.61	Peak
2	7326.00	49.95	-2.09	47.86	74.00	26.14	Peak
3	17938.40	50.89	9.63	60.52	74.00	13.48	Peak
4	17938.40	37.63	9.63	47.26	54.00	6.74	Average

BLE 1M High channel Horizontal



BLE 1M High channel Vertical



No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power.

External Antenna (AMODITX):

Horizontal

Project No.: 2602U03664E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: BLE External Antenna
Peak: RBW: 1MHz, VBW: 30Hz

Serial No.: 300V-3
Tester: Leo Xiao

Date: 2026-07-06

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	19929.20	48.38	3.99	52.37	74.00	21.63	Peak

Vertical

Project No.: 2602U03664E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: BLE External Antenna
Peak: RBW: 1MHz, VBW: 30Hz

Serial No.: 300V-3
Tester: Leo Xiao

Date: 2026-07-06

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	21819.20	47.29	5.16	52.45	74.00	21.55	Peak


Horizontal								Vertical							
Project No.: 2682U03664E-RF Polarization: Horizontal Test Mode: Transmitting Note: BLE Onboard PCB Antenna Peak: RBW:1MHz, VBW:3MHz								Project No.: 2682U03664E-RF Polarization: Vertical Test Mode: Transmitting Note: BLE Onboard PCB Antenna Peak: RBW:1MHz, VBW:3MHz							
Serial No.: 300V-2 Tester: Leo Xiao								Serial No.: 300V-2 Tester: Leo Xiao							
No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	24246.80	45.76	7.20	52.96	74.00	21.04	Peak	1	24399.40	45.00	7.35	52.35	74.00	21.65	Peak

Bandedge:
External Antenna (AMODITX):

BLE 1M Low channel Bandedge Horizontal	BLE 1M Low channel Bandedge Vertical																																
Project No.: 2602U03664E-RF Polarization: Horizontal Test Mode: Transmitting Note: BLE 1M low channel 2402MHz External Antenna Peak:RBW:1MHz,VBW:3MHz Serial No.: 300V-3 Tester: Leo Xiao Level (dBuV/m) Date: 2026-08-05 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>2390.00</td><td>49.10</td><td>-1.30</td><td>47.80</td><td>74.00</td><td>26.20</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	2390.00	49.10	-1.30	47.80	74.00	26.20	Peak	Project No.: 2602U03664E-RF Polarization: Vertical Test Mode: Transmitting Note: BLE 1M low channel 2402MHz External Antenna Peak:RBW:1MHz,VBW:3MHz Serial No.: 300V-3 Tester: Leo Xiao Level (dBuV/m) Date: 2026-08-05 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>2390.00</td><td>49.47</td><td>-1.30</td><td>48.17</td><td>74.00</td><td>25.83</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	2390.00	49.47	-1.30	48.17	74.00	25.83	Peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																										
1	2390.00	49.10	-1.30	47.80	74.00	26.20	Peak																										
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																										
1	2390.00	49.47	-1.30	48.17	74.00	25.83	Peak																										
BLE 1M High channel Bandedge Horizontal	BLE 1M High channel Bandedge Vertical																																
Project No.: 2602U03664E-RF Polarization: Horizontal Test Mode: Transmitting Note: BLE 1M high channel 2480MHz External Antenna Peak:RBW:1MHz,VBW:3MHz Serial No.: 300V-3 Tester: Leo Xiao Level (dBuV/m) Date: 2026-08-05 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>2483.50</td><td>51.11</td><td>-1.05</td><td>50.06</td><td>74.00</td><td>23.94</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	2483.50	51.11	-1.05	50.06	74.00	23.94	Peak	Project No.: 2602U03664E-RF Polarization: Vertical Test Mode: Transmitting Note: BLE 1M high channel 2480MHz External Antenna Peak:RBW:1MHz,VBW:3MHz Serial No.: 300V-3 Tester: Leo Xiao Level (dBuV/m) Date: 2026-08-05 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>2483.50</td><td>51.92</td><td>-1.05</td><td>50.87</td><td>74.00</td><td>23.13</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	2483.50	51.92	-1.05	50.87	74.00	23.13	Peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																										
1	2483.50	51.11	-1.05	50.06	74.00	23.94	Peak																										
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																										
1	2483.50	51.92	-1.05	50.87	74.00	23.13	Peak																										

Onboard PCB Antenna (AMODIT):**BLE 1M Low channel Bandedge Horizontal**


Project No.: 2602U03664E-RF Serial No.: 300V-2
Polarization: Horizontal Tester: Leo Xiao
Test Mode: Transmitting
Note: BLE 1M low channel 2402MHz Onboard PCB Antenna
Peak: RBW:1MHz, VBW:3MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2390.00	49.43	-1.30	48.13	74.00	25.87	Peak

BLE 1M Low channel Bandedge Vertical


Project No.: 2602U03664E-RF Serial No.: 300V-2
Polarization: Vertical Tester: Leo Xiao
Test Mode: Transmitting
Note: BLE 1M low channel 2402MHz Onboard PCB Antenna
Peak: RBW:1MHz, VBW:3MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2390.00	49.02	-1.30	47.72	74.00	26.28	Peak

BLE 1M High channel Bandedge Horizontal


Project No.: 2602U03664E-RF Serial No.: 300V-2
Polarization: Horizontal Tester: Leo Xiao
Test Mode: Transmitting
Note: BLE 1M high channel 2480MHz Onboard PCB Antenna
Peak: RBW:1MHz, VBW:3MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	53.12	-1.05	52.07	74.00	21.93	Peak

BLE 1M High channel Bandedge Vertical

Project No.: 2602U03664E-RF Serial No.: 300V-2
Polarization: Vertical Tester: Leo Xiao
Test Mode: Transmitting
Note: BLE 1M high channel 2480MHz Onboard PCB Antenna
Peak: RBW:1MHz, VBW:3MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	49.46	-1.05	48.41	74.00	25.59	Peak

5.3 6dB Emission Bandwidth

Test Information:

Serial No.:	30OV-1	Test Date:	2026/07/24
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.8	Relative Humidity: (%)	65	ATM Pressure: (kPa)	100.1
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HUBER+SUHNER	Coaxial Attenuator	6610_SMA-50-1	0064	2026/03/30	2027/03/29
R&S	Spectrum Analyzer	FSV40	101589	2026/07/08	2027/07/07
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Channel	Result (MHz)	Limit (MHz)	Verdict
BLE 1Mbps Low	0.701	≥0.5	Pass
BLE 1Mbps Middle	0.708	≥0.5	Pass
BLE 1Mbps High	0.709	≥0.5	Pass

BLE_1M_Low_Channel




ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:54:57

BLE_1M_Middle_Channel



ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:45:34

BLE_1M_High_Channel



ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:52:32

5.4 99% Occupied Bandwidth

Test Information:

Serial No.:	3OOV-1	Test Date:	2026/07/24
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	/

Environmental Conditions:

Temperature: (°C)	26.8	Relative Humidity: (%)	65	ATM Pressure: (kPa)	100.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HUBER+SUHNER	Coaxial Attenuator	6610_SMA-50-1	0064	2026/03/30	2027/03/29
R&S	Spectrum Analyzer	FSV40	101589	2026/07/08	2027/07/07
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Channel	99% OBW (MHz)
BLE 1Mbps Low	1.044
BLE 1Mbps Middle	1.040
BLE 1Mbps High	1.040


BLE_1M_Low_Channel



BLE_1M_Middle_Channel



BLE_1M_High_Channel



5.5 Maximum Conducted Output Power

Test Information:

Serial No.:	3OOV-1	Test Date:	2026/07/24
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.8	Relative Humidity: (%)	65	ATM Pressure: (kPa)	100.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HUBER+SUHNER	Coaxial Attenuator	6610_SMA-50-1	0064	2026/03/30	2027/03/29
R&S	Spectrum Analyzer	FSV40	101589	2026/07/08	2027/07/07
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Channel	Peak Output Power (dBm)	Limit (dBm)	Verdict
BLE 1Mbps Low	3.73	30.00	Pass
BLE 1Mbps Middle	3.58	30.00	Pass
BLE 1Mbps High	3.59	30.00	Pass
Max EIRP	7.73	36.00	Pass

BLE_1M_Low_Channel




ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:55:14

BLE_1M_Middle_Channel



ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:50:24

BLE_1M_High_Channel



ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:52:46

5.6 Power Spectral Density

Test Information:

Serial No.:	3OOV-1	Test Date:	2026/07/24
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.8	Relative Humidity: (%)	65	ATM Pressure: (kPa)	100.1
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HUBER+SUHNER	Coaxial Attenuator	6610_SMA-50-1	0064	2026/03/30	2027/03/29
R&S	Spectrum Analyzer	FSV40	101589	2026/07/08	2027/07/07
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Channel	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
BLE 1Mbps Low	-11.53	8	Pass
BLE 1Mbps Middle	-11.63	8	Pass
BLE 1Mbps High	-11.56	8	Pass

BLE_1M_Low_Channel




ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:56:42

BLE_1M_Middle_Channel



ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:51:41

BLE_1M_High_Channel



ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:54:10

5.7 Conducted Spurious Emission

Test Information:

Serial No.:	3OOV-1	Test Date:	2026/07/24
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.8	Relative Humidity: (%)	65	ATM Pressure: (kPa)	100.1
----------------------	------	------------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HUBER+SUHNER	Coaxial Attenuator	6610_SMA-50-1	0064	2026/03/30	2027/03/29
R&S	Spectrum Analyzer	FSV40	101589	2026/07/08	2027/07/07
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A


* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Note: The maximum path attenuation of 30MHz-25GHz was added into the offset.




BLE_1M_Low_Channel




ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:56:16

BLE_1M_Middle_Channel




ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:50:35

BLE_1M_Middle_Channel




ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:51:15

BLE_1M_High_Channel




ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:52:55

BLE_1M_High_Channel



ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:53:13

BLE_1M_High_Channel



ProjectNo.:2602U03664E-RF Tester:Jojo Zhou
Date: 24.JUL.2026 09:53:44

5.8 Duty Cycle

Test Information:

Serial No.:	3OOV-1	Test Date:	2026/08/28
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	26.5	Relative Humidity: (%)	59	ATM Pressure: (kPa)	99.8
----------------------	------	------------------------------	----	------------------------	------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HUBER+SUHNER	Coaxial Attenuator	6610_SMA-50-1	0064	2026/03/30	2027/03/29
Rohde&Schwarz	Spectrum Analyzer	FSV40	101461	2026/07/08	2027/07/07
JD	Test Software	JD Auto Test System	V1.0	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Channel	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
BLE 1Mbps Middle	0.381	0.626	60.86	2.16	2625	3

BLE_1M_Middle_Channel




EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2602U03664E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2602U03664E-RF-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2602U03664E-RF-00A-TSP TEST SETUP PHOTOGRAPHS.

EXHIBIT C - RF EXPOSURE EVALUATION

Maximum Permissible Exposure (MPE)

Applicable Standard

According to subpart §1.1310,15.247(i) systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Operation Mode	Frequency (MHz)	Antenna Gain [▲]		Conducted output power including Tune-up Tolerance [▲]		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402-2480	4.0	2.51	4.0	2.51	20.00	0.0013	1.0

Note:

The Antenna Gain and Conducted output power including Tune-up Tolerance provided by manufacturer.

Result: Compliant. The devices meet FCC MPE at 20 cm distance

Exemption Limits For Routine Evaluation-RF Exposure Evaluation

Applicable Standard

RSS-102, Issue 6, Clause 6.6:

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain [▲]	Conducted output power including Tune-up Tolerance [▲]	EIRP		Exemption limits (mW)
		(dBi)	(dBm)	(dBm)	(mW)	
BLE	2402-2480	4.0	4.0	8.0	6.31	2676

Note:

1. The Antenna Gain and Conducted output power including Tune-up Tolerance provided by manufacturer.

Result: So the device is compliance with the exemption from Routine Evaluation Limits –RF exposure Evaluation.

***** END OF REPORT *****