

rLSXR

1720

000-251356

INPUT: 120-277 VAC 50/60Hz

MAX LOAD: 16A Electronic Ballast

20A Tungsten, Ballast, General Purpose

1/2 HP Motor

0-10 DIM: 100 mA SINK

Temp -10C to 50C @20A; -10C to 60C @12A

Suitable for Plenum Mounting

FCC ID: 2ADCB-RMODIT, IC: 6715C-RMODIT

THE ENCLOSED DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION.

BLK - HOT

WHT - NEUTRAL

BLU - SWITCHED OUT

VIO - DIM 0-10V

GRY - DIM-

GRN - GROUND

E326029



3D62

ENERGY

MGMT EQPT

Factory ID:74

Assembled In MEX

1.800.535.2465

AcuityControls.com

AcuityControls

nLight

CAUTION:

Risk of Electric Shock - More than one disconnect switch may be required to de-energize the equipment before servicing. For supply connections, use 14 AWG or larger wires rated for at least 75°C. CU ONLY