



REPORT No.: SZ25120367S01

Annex F Test Position Consideration

Exposure Position	Wireless Interface	BT	2.4GHz WLAN ANT 1	2.4GHz WLAN ANT 2	5GHz WLAN ANT 1	5GHz WLAN ANT 2
Exposure Position	Calculated Frequency	2480MHz	2462MHz	2462MHz	5825MHz	5825MHz
	Maximum power (dBm)	16.41	28.43	28.61	18.49	19.09
	Maximum rated power(mW)	44.0	697.0	726.0	71.0	81.0
Bottom Face	Separation distance(mm)	0.0	0.0	0.0	0.0	0.0
	exclusion threshold	13.9	218.7	227.8	34.3	39.1
	Testing required?	Yes	Yes	Yes	Yes	Yes
Front Side	Separation distance(mm)	0.0	0.0	0.0	0.0	0.0
	exclusion threshold	13.9	218.7	227.8	34.3	39.1
	Testing required?	Yes	Yes	Yes	Yes	Yes
Edge 1	Separation distance(mm)	0.0	0.0	0.0	0.0	0.0
	exclusion threshold	13.9	218.7	227.8	34.3	39.1
	Testing required?	Yes	Yes	Yes	Yes	Yes
Edge 2	Separation distance(mm)	0.0	0.0	60.0	0.0	60.0
	exclusion threshold	13.9	218.7	196.0	34.3	162.0
	Testing required?	Yes	Yes	Yes	Yes	No
Edge 3	Separation distance(mm)	120.0	120.0	120.0	120.0	120.0
	exclusion threshold	795.0	796.0	796.0	762.0	762.0
	Testing required?	No	No	No	No	No
Edge 4	Separation distance(mm)	0.0	60.0	0.0	60.0	0.0
	exclusion threshold	13.9	196.0	227.8	162.0	39.1
	Testing required?	Yes	Yes	Yes	No	Yes