



REPORT No.: SZ25120367W01

TEST REPORT

APPLICANT : Wuxi iData Technology Co., Ltd.

PRODUCT NAME : New Mobile Computer

MODEL NAME : Refer to section 2.2

BRAND NAME : iData

FCC ID : 2ADE3IDATAW7

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2026-01-26

TEST DATE : 2026-02-04 to 2026-04-10

ISSUE DATE : 2026-05-09



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	7
1.4. Testing Laboratory	7
2. General Description	8
2.1. Information of Applicant and Manufacturer	8
2.2. Information of EUT	8
2.3. Channel List of EUT	10
2.4. Test Configuration of EUT	11
2.5. Test Conditions	11
2.6. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Antenna Requirement	14
3.2. Duty Cycle of Test Signal	15
3.3. Maximum Peak Conducted Output Power	16
3.4. Maximum Average Conducted Output Power	17
3.5. 6 dB Bandwidth	18
3.6. Conducted Spurious Emissions and Band Edge	19
3.7. Power Spectral Density	20
3.8. Conducted Emission	21
3.9. Restricted Frequency Bands	22
3.10. Radiated Emission	23
Annex A Test Data and Result	25
Notes	77



REPORT No.: SZ25120367W01

Change History		
Version	Date	Reason for change
1.0	2026-05-09	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	Feb. 27, 2026	Lin Haoyang	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	Feb. 27, 2026	Lin Haoyang	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	Feb. 27, 2026	Lin Haoyang	PASS	/
5	15.247(a)	Bandwidth	Feb. 27, 2026	Lin Haoyang	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Feb. 27, 2026	Lin Haoyang	PASS	/
7	15.247(e)	Power Spectral Density	Feb. 27, 2026	Lin Haoyang	PASS	/
8	15.207	Conducted Emission	Feb. 26 to 28, 2026	Wang Yapeng	PASS	/
9	15.247(d)	Restricted Frequency Bands	Feb. 06 to 25, 2026	Xiong Xianhong	PASS	/
10	15.209, 15.247(d)	Radiated Emission	Feb. 06 to 25, 2026	Xiong Xianhong	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020 and KDB 558074 D01 v05r02.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the “Remark”.

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.12.24	2026.12.23
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2025.05.15	2026.05.14
LISN	103131	ENV 216	R&S	2025.04.18	2026.04.17
INTELLIGENT PURE SINE- WAVE POWER SUPPLY	1008004	TPS 500B	EVERFINE	2025.09.11	2026.09.10
RF Coaxial Cable (DC-100MHz)	EMC-CE- 00514	N/A	N/A	2025.05.06	2026.05.05

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-274	VULB 9163	Schwarzbeck	2025.06.28	2026.06.27
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna – Horn	9120D-963	BBHA 9120D	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2025.06.20	2026.06.19
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2025.09.03	2026.09.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.06.21	2028.06.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Wuxi iData Technology Co., Ltd.
Applicant Address:	Floor 11, Building B1, No.999 Gaolang East Road Wuxi City, P.R.C.
Manufacturer:	Wuxi iData Technology Co., Ltd.
Manufacturer Address:	Floor 11, Building B1, No.999 Gaolang East Road Wuxi City, P.R.C.

2.2. Information of EUT

Product Name:	New Mobile Computer	
Sample No.:	1#, 3#, 11#	
Model Name:	iDataW7, iDataW7S, iDataW7Pro, iDataW7Turbo, iDataW7A, iDataW7G, iDataW7L, iDataW7COLD, iDataW7SCOLD, iDataW7ProCOLD, iDataW7TurboCOLD, iDataW7ACOLD, iDataW7GCOLD, iDataW7LCOLD, iDataW7HC, iDataW7SHC, iDataW7ProHC, iDataW7TurboHC, iDataW7AHC, iDataW7GHC, iDataW7LHC, iDataW7XHC, iDataW7XSHC, iDataW7XProHC, iDataW7XTurboHC, iDataW7XAHC, iDataW7XGHC, iDataW7XLHC	
Hardware Version:	B1-1	
Software Version:	15.00	
Equipment Type:	Bluetooth LE	
Bluetooth Version:	5.3	
Modulation Type:	GFSK	
Data Rate:	1Mbps, 2Mbps	
Operating Frequency Range:	2402MHz-2480MHz	
Antenna Type:	PIFA Antenna	
Antenna Gain:	2.19dBi	
Accessory Information:	Battery 1	
	Brand Name:	N/A
	Model No.:	CLP1287
	Serial No.:	N/A
	Capacity:	3300mAh



	Rated Voltage:	3.6V
	Charge Limit:	4.2V
	Manufacturer:	SHENZHEN CHOLIPower TECHNOLOGY CO.,LTD.
	Battery 2	
	Brand Name:	N/A
	Model No.:	ZWD301322HM
	Serial No.:	N/A
	Capacity:	65mAh
	Rated Voltage:	3.85V
	Charge Limit:	4.4V
	Manufacturer:	ZHONGSHAN ZHONGWANGDE NEWENERGY TECHNOLOGY C..LTD
	AC Adapter	
	Brand Name:	N/A
	Model No.:	TPD-203R120167CF01
	Serial No.:	N/A
	Rated Output:	5V $\pm$ 3A or 9V $\pm$ 2.22A or 12V $\pm$ 1.67A
	Rated Input:	100-240V $\sim$ 50/60Hz, 0.6A
	Manufacturer:	SHENZHEN TIANYIN ELECTRONICS CO., LTD.
	USB cable	
	Model No.:	K395-11230-R0
	Manufacturer:	C- Victory Electronics Co.,Ltd.

Note 1: According to the certificate holder, they declared that the models iDataW7, iDataW7S, iDataW7Pro, iDataW7Turbo, iDataW7A, iDataW7G, iDataW7L, iDataW7COLD, iDataW7SCOLD, iDataW7ProCOLD, iDataW7TurboCOLD, iDataW7ACOLD, iDataW7GCOLD, iDataW7LCOLD, iDataW7HC, iDataW7SHC, iDataW7ProHC, iDataW7TurboHC, iDataW7AHC, iDataW7GHC, iDataW7LHC, iDataW7XHC, iDataW7XSHC, iDataW7XProHC, iDataW7XTurboHC, iDataW7XAHc, iDataW7XGHC, iDataW7XLHC only the model names are different, their electrical circuit design, layout, components used and internal wiring are identical. No other changes. The main measuring model is iDataW7, only the results for iDataW7 were recorded in this report.

Note 2: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


The EUT is controlled by dedicated software to transmit at the default maximum power level.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☒ PIFA Antenna	☐ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☒ Metal Shrapnel ☐ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration(T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e.,no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.



3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.



3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100\text{ kHz}$, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6\text{ dB}$.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.



3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.7. Power Spectral Density

3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4. Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10.

3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.4. Test Result

Refer to Annex A.8 in this report.

3.9. Restricted Frequency Bands

3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.9 in this report.

3.10. Radiated Emission

3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.10.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.10.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.10.4.Test Result


Refer to Annex A.10 in this report.




Annex A Test Data and Result

A.1. Duty Cycle of Test Signal


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	61.76	2.09	2.59
NVNT	BLE 1M	2440	Ant1	61.79	2.09	2.59
NVNT	BLE 1M	2480	Ant1	61.76	2.09	2.59
NVNT	BLE 2M	2404	Ant1	32.32	4.91	4.95
NVNT	BLE 2M	2440	Ant1	32.32	4.91	4.95
NVNT	BLE 2M	2478	Ant1	32.32	4.91	4.95




Duty Cycle NVNT BLE 1M 2402MHz Ant1




Duty Cycle NVNT BLE 1M 2440MHz Ant1




Duty Cycle NVNT BLE 1M 2480MHz Ant1



Duty Cycle NVNT BLE 2M 2404MHz Ant1




Duty Cycle NVNT BLE 2M 2440MHz Ant1




Duty Cycle NVNT BLE 2M 2478MHz Ant1

**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	2.32	0	2.32	0.00171	30	Pass
NVNT	BLE 1M	2440	Ant1	3.26	0	3.26	0.00212	30	Pass
NVNT	BLE 1M	2480	Ant1	2.81	0	2.81	0.00191	30	Pass
NVNT	BLE 2M	2404	Ant1	2.37	0	2.37	0.00173	30	Pass
NVNT	BLE 2M	2440	Ant1	3.18	0	3.18	0.00208	30	Pass
NVNT	BLE 2M	2478	Ant1	2.54	0	2.54	0.00179	30	Pass




Peak Power NVNT BLE 1M 2402MHz Ant1



Peak Power NVNT BLE 1M 2440MHz Ant1



Peak Power NVNT BLE 1M 2480MHz Ant1



Peak Power NVNT BLE 2M 2404MHz Ant1



Peak Power NVNT BLE 2M 2440MHz Ant1



Peak Power NVNT BLE 2M 2478MHz Ant1

**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-0.03	2.09	2.06	0.00161	30	Pass
NVNT	BLE 1M	2440	Ant1	0.9	2.09	2.99	0.00199	30	Pass
NVNT	BLE 1M	2480	Ant1	0.25	2.09	2.34	0.00171	30	Pass
NVNT	BLE 2M	2404	Ant1	-2.84	4.91	2.07	0.00161	30	Pass
NVNT	BLE 2M	2440	Ant1	-1.86	4.91	3.05	0.00202	30	Pass
NVNT	BLE 2M	2478	Ant1	-2.59	4.91	2.32	0.00171	30	Pass




Average Power NVNT BLE 1M 2402MHz Ant1



Average Power NVNT BLE 1M 2440MHz Ant1




Average Power NVNT BLE 1M 2480MHz Ant1



Average Power NVNT BLE 2M 2404MHz Ant1




Average Power NVNT BLE 2M 2440MHz Ant1



Average Power NVNT BLE 2M 2478MHz Ant1

**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.7111	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.7055	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.7064	0.5	Pass
NVNT	BLE 2M	2404	Ant1	1.15	0.5	Pass
NVNT	BLE 2M	2440	Ant1	1.267	0.5	Pass
NVNT	BLE 2M	2478	Ant1	1.364	0.5	Pass



-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2404MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2478MHz Ant1

**A.5. Conducted Spurious Emissions**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-40.76	-20	Pass
NVNT	BLE 1M	2440	Ant1	-41.48	-20	Pass
NVNT	BLE 1M	2480	Ant1	-41.13	-20	Pass
NVNT	BLE 2M	2404	Ant1	-39.99	-20	Pass
NVNT	BLE 2M	2440	Ant1	-41.02	-20	Pass
NVNT	BLE 2M	2478	Ant1	-40.96	-20	Pass




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission




Tx. Spurious NVNT BLE 2M 2404MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2404MHz Ant1 Emission




Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2478MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2478MHz Ant1 Emission




REPORT No.: SZ25120367W01

A.6. Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-55.51	-20	Pass
NVNT	BLE 1M	2480	Ant1	-55.4	-20	Pass
NVNT	BLE 2M	2404	Ant1	-54.54	-20	Pass
NVNT	BLE 2M	2478	Ant1	-56.35	-20	Pass




Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Band Edge NVNT BLE 1M 2402MHz Ant1 Emission




Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission




Band Edge NVNT BLE 2M 2404MHz Ant1 Ref



Band Edge NVNT BLE 2M 2404MHz Ant1 Emission




Band Edge NVNT BLE 2M 2478MHz Ant1 Ref




Band Edge NVNT BLE 2M 2478MHz Ant1 Emission

**A.7. Power Spectral Density**


Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-12.85	0	-12.85	8	Pass
NVNT	BLE 1M	2440	Ant1	-11.86	0	-11.86	8	Pass
NVNT	BLE 1M	2480	Ant1	-12.51	0	-12.51	8	Pass
NVNT	BLE 2M	2404	Ant1	-14.91	0	-14.91	8	Pass
NVNT	BLE 2M	2440	Ant1	-14	0	-14	8	Pass
NVNT	BLE 2M	2478	Ant1	-14.63	0	-14.63	8	Pass




PSD NVNT BLE 1M 2402MHz Ant1




PSD NVNT BLE 1M 2440MHz Ant1



PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2404MHz Ant1



PSD NVNT BLE 2M 2440MHz Ant1



PSD NVNT BLE 2M 2478MHz Ant1



A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+USB cable+BLE TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1590	46.33	29.55	65.52	55.52	Line	PASS
2	0.1815	45.07	29.29	64.42	54.42		PASS
3	0.2310	41.47	27.16	62.41	52.41		PASS
4	0.2940	35.85	24.35	60.41	50.41		PASS
5	0.4515	38.10	32.08	56.85	46.85		PASS
6	13.8312	27.21	15.31	60.00	50.00		PASS



(N Phase)


No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1500	47.72	30.36	66.00	56.00	Neutral	PASS
2	0.1635	45.83	30.57	65.28	55.28		PASS
3	0.1815	43.93	28.55	64.42	54.42		PASS
4	0.2040	42.63	27.93	63.45	53.45		PASS
5	0.4515	39.56	30.64	56.85	46.85		PASS
6	14.5961	29.06	20.94	60.00	50.00		PASS

A.9. Restricted Frequency Bands

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition was recorded in this test report.

1Mbps


Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2384.71	17.1	49.61	32.530	74.00	24.39	165	171	PK	PASS
2385.11	4.7	37.21	32.530	54.00	16.79	165	105	AV	PASS
2386.80	17.8	50.30	32.530	74.00	23.70	165	332	PK	PASS
2387.19	4.6	37.12	32.530	54.00	16.88	165	17	AV	PASS
2388.88	4.7	37.22	32.540	54.00	16.78	165	344	AV	PASS
2389.27	17.1	49.68	32.540	74.00	24.32	165	53	PK	PASS



Plot for Channel 39




Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.53	5.0	38.01	33.030	54.00	15.99	165	68	AV	PASS
2483.68	18.1	51.16	33.030	74.00	22.84	165	142	PK	PASS
2484.38	5.0	38.03	33.030	54.00	15.97	165	339	AV	PASS
2484.58	21.3	54.35	33.030	74.00	19.65	165	316	PK	PASS
2485.34	17.1	50.14	33.030	74.00	23.86	165	177	PK	PASS
2485.39	5.0	38.03	33.030	54.00	15.97	165	135	AV	PASS



2Mbps


Plot for Channel 1



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2379.77	4.5	37.04	32.510	54.00	16.96	165	178	AV	PASS
2381.72	16.6	49.10	32.510	74.00	24.90	165	119	PK	PASS
2383.93	16.9	49.39	32.520	74.00	24.61	165	359	PK	PASS
2384.97	4.7	37.26	32.530	54.00	16.74	165	134	AV	PASS
2388.36	16.5	49.05	32.540	74.00	24.95	165	119	PK	PASS
2389.14	4.7	37.22	32.540	54.00	16.78	165	149	AV	PASS



Plot for Channel 38



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.78	5.0	37.98	33.030	54.00	16.02	165	260	AV	PASS
2483.83	19.8	52.85	33.030	74.00	21.15	165	136	PK	PASS
2484.23	19.7	52.70	33.030	74.00	21.30	165	128	PK	PASS
2484.88	5.0	38.04	33.030	54.00	15.96	165	61	AV	PASS
2485.34	4.9	37.97	33.030	54.00	16.03	165	120	AV	PASS
2485.54	18.5	51.55	33.030	74.00	22.45	165	136	PK	PASS



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.

Field strength of fundamental:


Frequency [MHz]	Reading [dB μ V]	Level [dB μ V/m]	Factor [dB/m]	Detector	Polarity
2402.24	59.3	91.91	32.600	PK	Horizontal

The field strength (the lowest) of fundamenta is more than 20dB higher than the unwanted emissions, in accordance with FCC part 15.215(b).




1Mbps

Plot for Channel 0




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
42.29	1.1	16.25	15.130	40.00	23.75	165	22	PK	PASS
96.02	0.6	13.47	12.890	43.50	30.03	165	256	PK	PASS
197.85	1.2	14.48	13.240	43.50	29.02	165	0	PK	PASS
334.66	1.9	19.29	17.350	46.00	26.71	165	190	PK	PASS
729.91	1.5	25.58	24.040	46.00	20.42	165	349	PK	PASS
992.12	2.5	29.27	26.770	54.00	24.73	165	77	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2401.88	41.3	42.04	0.750	-	-	165	108	PK	NA
2402.28	36.9	37.66	0.750	-	-	165	237	AV	NA
12689.42	48.4	52.05	3.700	74.00	21.95	165	360	PK	PASS
12799.99	38.5	42.42	3.940	54.00	11.58	165	201	AV	PASS
17924.14	35.3	46.85	11.520	54.00	7.15	165	125	AV	PASS
17995.71	43.1	55.43	12.330	74.00	18.57	165	201	PK	PASS



(Antenna Vertical, 30MHz to 1GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
46.81	0.6	15.88	15.330	40.00	24.12	165	345	PK	PASS
102.37	0.5	13.46	13.010	43.50	30.04	165	360	PK	PASS
201.44	2.8	15.68	12.930	43.50	27.82	165	359	PK	PASS
343.18	1.5	19.04	17.540	46.00	26.96	165	353	PK	PASS
653.48	2.2	25.16	22.940	46.00	20.84	165	208	PK	PASS
997.77	1.4	28.55	27.190	54.00	25.45	165	357	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2402.28	35.7	36.46	0.750	-	-	165	152	AV	NA
2481.50	40.7	41.59	0.910	74.00	32.41	165	349	PK	PASS
13344.72	47.0	52.13	5.150	74.00	21.87	165	66	PK	PASS
13545.73	38.6	43.31	4.760	54.00	10.69	165	359	AV	PASS
17972.14	33.4	45.47	12.070	54.00	8.53	165	360	AV	PASS
17980.29	41.1	53.29	12.160	74.00	20.71	165	84	PK	PASS

Plot for Channel 19




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
43.46	0.4	15.67	15.260	40.00	24.33	165	191	PK	PASS
107.25	0.7	13.47	12.810	43.50	30.03	165	350	PK	PASS
217.96	0.6	14.24	13.690	46.00	31.76	165	1	PK	PASS
325.37	2.7	19.39	16.680	46.00	26.61	165	78	PK	PASS
582.82	1.9	23.71	21.810	46.00	22.29	165	238	PK	PASS
982.95	2.1	28.76	26.650	54.00	25.24	165	1	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2475.50	47.5	48.47	0.940	74.00	25.53	165	322	PK	PASS
2475.90	42.9	43.88	0.940	54.00	10.12	165	322	AV	PASS
12798.28	47.2	51.15	3.930	74.00	22.85	165	48	PK	PASS
12867.71	38.3	42.34	4.010	54.00	11.66	165	197	AV	PASS
17975.57	42.7	54.85	12.110	74.00	19.15	165	274	PK	PASS
17978.14	34.9	47.04	12.130	54.00	6.96	165	143	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
41.88	0.8	15.86	15.070	40.00	24.14	165	253	PK	PASS
96.67	1.1	14.03	12.960	43.50	29.47	165	58	PK	PASS
195.32	1.2	14.66	13.500	43.50	28.84	165	320	PK	PASS
349.18	1.5	18.83	17.350	46.00	27.17	165	66	PK	PASS
783.00	2.7	27.30	24.560	46.00	18.70	165	10	PK	PASS
986.60	1.4	28.15	26.710	54.00	25.85	165	359	PK	PASS




(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2439.89	37.1	38.13	1.010	-	-	165	197	AV	NA
2440.29	43.8	44.77	1.010	-	-	165	197	PK	NA
12908.00	48.5	52.54	4.030	74.00	21.46	165	122	PK	PASS
13989.74	37.9	43.29	5.410	54.00	10.71	165	222	AV	PASS
17970.43	41.7	53.71	12.040	74.00	20.29	165	68	PK	PASS
17994.43	32.6	44.90	12.310	54.00	9.10	165	106	AV	PASS




Plot for Channel 39




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
44.64	0.5	15.83	15.310	40.00	24.17	165	163	PK	PASS
96.20	0.0	12.92	12.910	43.50	30.58	165	15	PK	PASS
183.27	0.5	12.30	11.780	43.50	31.20	165	208	PK	PASS
302.38	1.3	17.32	15.990	46.00	28.68	165	0	PK	PASS
654.84	2.0	24.95	22.980	46.00	21.05	165	1	PK	PASS
999.12	1.2	28.59	27.360	54.00	25.41	165	246	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2479.90	42.9	43.83	0.920	-	-	165	129	PK	NA
2480.30	35.7	36.58	0.920	-	-	165	119	AV	NA
14352.75	38.1	43.01	4.900	54.00	10.99	165	10	AV	PASS
14365.61	47.0	51.91	4.910	74.00	22.09	165	142	PK	PASS
17922.43	44.1	55.58	11.510	74.00	18.42	165	360	PK	PASS
17981.57	35.3	47.47	12.170	54.00	6.53	165	84	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
47.64	0.1	15.47	15.330	40.00	24.53	165	264	PK	PASS
75.74	3.9	12.36	8.440	40.00	27.64	165	180	PK	PASS
105.72	0.6	13.48	12.930	43.50	30.02	165	273	PK	PASS
200.91	1.6	14.49	12.920	43.50	29.01	165	10	PK	PASS
516.97	2.5	23.20	20.720	46.00	22.80	165	353	PK	PASS
984.36	2.4	29.07	26.680	54.00	24.93	165	310	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2479.90	35.9	36.79	0.920	-	-	165	172	AV	NA
2480.30	43.0	43.88	0.920	-	-	165	342	PK	NA
13810.59	46.4	51.90	5.460	74.00	22.10	165	144	PK	PASS
13996.17	38.4	43.86	5.470	54.00	10.14	165	295	AV	PASS
17975.57	42.5	54.61	12.110	74.00	19.39	165	10	PK	PASS
17982.86	34.0	46.15	12.190	54.00	7.85	165	360	AV	PASS



Notes

1. The report shall have report stamp or our company stamp.
2. The report shall be invalid without all the signatures of the editor and approver.
3. The report shall not be changed.
4. Any objections must be raised to Morlab within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.
5. Conformity declaration:
 - ☒ Morlab issues a statement of conformity based on the corresponding standards (default)
 - ☐ Morlab issues a statement of conformity based on the applicant requirement
6. Use of uncertainty of measurement for decisions on conformity (decision rule):

No decision rule is specified by the testing standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule).

————— END OF REPORT —————