



CMA Testing and Certification Laboratories

廠商會檢定中心

RF EXPOSURE EVALUATION

Report No. : AW0020565(7) Date: Apr 20, 2018

Application No. : LW5674(0)

Applicant : Kondor Limited

Sample Description : One(1) item of submitted sample stated to be

Product Description : DIGGIT Bluetooth outdoor portable speaker with
removable stake IP55 Splashproof

Model : Diggit

Sample registration No. : RW030396

Radio Frequency : 2402 – 2480MHz

Supply voltage : DC 3.7V (Li-ion Rechargeable battery)
DC 5.0V (charging port)

No. of submitted sample : 2

FCC ID : 2ADFF-KSDIGGIT

Date Received : February 27, 2018

Evaluation Period : March 8, 2018 – March 27, 2018

Evaluation Method : 447498 D01 General RF Exposure Guidance v06 - RF Exposure Procedure and
Equipment Authorization Policies for Mobile and Portable Devices

Conclusion : The maximum simultaneous power of Bluetooth operation were satisfied RF
exposure requirements.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____


Mr. WONG Lap-pong, Andrew
Manager
Electrical Division

Page 1 of 2

Document name: FCC RF exposure - Document Ref No: RT-EL-EMC-008 - Issue Date: 01 Dec 2017 - Edition: 1

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

RF EXPOSURE EVALUATION

Report No. : AW0020565(7)

Date: Apr 20, 2018

Simultaneous power

Not applicable because only Bluetooth transmitter installed on the device

RF Exposure Evaluation

According to KDB 447498 D01 clause 4.3.1 a), transmission from 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

Calculation

-Frequency : 2.480GHz
-Max. power of channel in EIRP , including tune-up tolerance : 0.813mW
-Minimum test separation distances : <5mm

where

-f(GHz) is the RF channel transmit frequency in GHz.

-Power and distance are rounded to the nearest mW and mm before calculation.

-The result is rounded to two decimal place for comparison.

Substitute above reading for calculation.

$$[(\text{mW}) / (\text{mm})] \times \sqrt{\text{GHz}}$$

Result = 0.256

Requirements: ≤ 3.00 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

Conclusion

The corresponding SAR test exclusion threshold was satisfied 4.3.1a) requirements. Measurement or numerical simulation is not required.

***** End of Evaluation *****