



No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM141000561801
Page: 1 of 17

FCC REPORT

Application No. : SZEM1410005618RF (SGS SZ NO.: SZTY1410000805EM)
Applicant: Jam'n Products Inc
Manufacturer: XIONGFA TOYS
Buyer: JAM'N
Product Name: FORD RADIO CONTROL CAR 1:24
Model No.(EUT): 22410
Add Model No.: 22411, 22412, 22413, 22414, 22420, 22421, 22422, 22423, 22424
FCC ID: 2ADFZ20141049
Standards: 47 CFR Part 15, Subpart C (2014)
Date of Receipt: 2014-10-14
Date of Test: 2014-10-21 to 2014-11-07
Date of Issue: 2015-05-19

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.


The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-05-19		Original

Authorized for issue by:				
Tested By		 (Draca Chen) /Project Engineer		2014-11-07
				Date
Prepared By		 (Hedy Wen) /Clerk		2015-05-19
				Date
Checked By		 (Owen Zhou) /Reviewer		2015-05-19
				Date



3 Test Summary

Test Item	Test Requirement	Test method	Result
Radiated Emission	47 CFR Part 15, Subpart C Section 15.235	ANSI C63.10 (2009)	PASS**
Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.235	ANSI C63.10 (2009)	PASS

Remark:

Model No.: 22410, 22411, 22412, 22413, 22414, 22420, 22421, 22422, 22423, 22424

Only the Model 22410 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models, only different on model name and color.

** : The EUT passed the Radiated Emission test after modification. This modification method is only for the purpose of fixing the EMC compliance problem while other subject matters or issues such as safety compliance, hazards, RoHS compliance or even production issue etc., are not addressed in this report.



4 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENTS	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST ENVIRONMENT AND MODE	5
5.4 DESCRIPTION OF SUPPORT UNITS	5
5.5 TEST LOCATION.....	6
5.6 TEST FACILITY.....	6
5.7 DEVIATION FROM STANDARDS	7
5.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
5.10 EQUIPMENT LIST.....	8
6 TEST RESULT & MEASUREMENT DATA	9
6.1 ANTENNA REQUIREMENT	9
6.2 RADIATED EMISSIONS.....	10
6.3 OCCUPIED BANDWIDTH	16-17



5 General Information

5.1 Client Information

Applicant:	Jam'n Products Inc
Address of Applicant:	4199 Bandini Bl. Suite A Vernon, CA 90058 USA
Manufacturer:	XIONGFA TOYS
Buyer:	JAM'N

5.2 General Description of EUT

Product Name:	FORD RADIO CONTROL CAR 1:24
Model No.:	22410, 22411, 22412, 22413, 22414, 22420, 22421, 22422, 22423, 22424
P.O./Ref. No.:	PO2385
Request Age Grading:	6+
Country of Origin:	SHANTOU
Country of Destination:	USA
Sample Type:	Portable production
Operation Frequency:	49.860MHz
Modulation Type:	AM
Antenna Type:	Integral
Power Supply:	Tx: DC 9.0V (1 x 9.0V "6LR61" Size Battery) RX:DC 4.5V (3 x 1.5V "AA" Size Battery)
Test Voltage:	DC 9.0V new batteries for TX DC 4.5V new batteries for RX

5.3 Test Environment and Mode

Operating Environment:	
Temperature:	23.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1020 mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode.
Receiving mode:	Keep the EUT in receiving mode.

5.4 Description of Support Units

The EUT has been tested independent unit.





5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.



5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

The EUT passed the Radiated Emission test after modification.

5.9 Other Information Requested by the Customer

None.


**5.10 Equipment List**

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	Coaxial cable	SGS	N/A	SEL0027	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0189	2015-05-29
6	Coaxial cable	SGS	N/A	SEL0121	2015-05-29
7	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
8	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24
9	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24
10	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16
11	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24
12	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
13	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
14	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
15	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24
16	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16
17	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04

Note: The calibration interval is one year, all the instruments are valid.

6 Test Result & Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
 The antenna is integrated on the main PCB and no consideration of replacement.	





6.2 Radiated Emissions

Test Requirement:	47 CFR Part 15C Section 15.235				
Test Method:	ANSI C63.10: 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Spurious Emissions)	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					
Limit: (Field strength of the fundamental signal)	Carrier frequency will not exceed 80dBuV/m AT 3m.				
	Frequency	Limit (dBuV/m @3m)		Remark	
	49.860MHz	80		Average Value	
		100		Peak Value	



Test Procedure:	- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. - The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
-----------------	--

Test Setup:	
	
Figure 1. Below 30MHz Figure 2. 30MHz to 1GHz	
Test Mode:	Transmitting mode Remark: Pre-scan the operation mode at forward, backward, right turn and left turn mode, and found the forward mode was the worst case.
Test Instruments:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data

Intentional emission

Test Frequency (MHz)	Peak (dB μ V/m)		Limits (dB μ V/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
49.860	71.82	48.05	100.0	-28.18	-51.95


Test Frequency (MHz)	Average (dB μ V/m)		Limits (dB μ V/m)	Margin (dB)	
	Vertical	Horizontal		Vertical	Horizontal
49.860	66.68	32.99	100.0	-33.32	-67.01



Other emissions (QP value)

Vertical

Data: 56



Condition: FCC PART C 49MHz 3m 3142C Vertical

Job No. : 5618RF


Test mode: TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	100.07	1.20	9.10	27.20	39.57	22.67	43.50	-20.83	
2	149.60	1.32	8.96	26.91	28.74	12.11	43.50	-31.39	
3	399.10	2.20	16.29	27.13	34.65	26.01	46.00	-19.99	
4	449.11	2.40	16.88	27.44	28.61	20.45	46.00	-25.55	
5	704.38	2.91	21.60	27.41	25.16	22.26	46.00	-23.74	
6	992.65	3.69	24.01	26.33	24.01	25.38	54.00	-28.62	



Horizontal

Data: 57



Condition: FCC PART C 49MHZ 3m 3142C Horizontal

Job No. : 5618RF

Test mode: TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	100.07	1.20	9.10	27.20	28.09	11.19	43.50	-32.31	
2	149.60	1.32	8.97	26.91	27.15	10.53	43.50	-32.97	
3	399.10	2.20	16.29	27.13	25.75	17.11	46.00	-28.89	
4	590.07	2.69	19.53	27.55	25.07	19.74	46.00	-26.26	
5	722.80	2.98	21.60	27.39	25.65	22.84	46.00	-23.16	
6	922.05	3.62	23.29	26.68	24.22	24.45	46.00	-21.55	




Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) The disturbance below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



6.3 Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.235
Test Method:	ANSI C63.10: 2009
Limit::	The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the un-modulated carrier or to the general limits in Section 15.209, whichever permits the higher emission levels.
Test Setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Mode:	Transmitting mode
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

