



RF Exposure Report

FCC ID: 2ADG3-DL46

FCC 47 CFR Part 15 Subpart C

Product : Tablet PC

Trade Name : EVG7

Model Number : DL46

Issued for

NKAAY Science and Technology Development Co.,Ltd

Plant 3,Puxia industrial area,Liuyue community, Henggang street,Longgang district. 518116, Shenzhen,China

Issued by

Shenzhen STONE Testing Technology Co., Ltd.

F/6, Bldg.12, Zhongxing Industrial City, Chuangye Rd.,
Nanshan District, Shenzhen, Guangdong, China

Tel.: +86-0755-26582862 Fax.: +86-0755-61673854

Website: www.stt-lab.org

*Note: This report shall not be reproduced except in full, without the written approval of Shenzhen STONE Testing Technology Co., Ltd.. This document may be altered or revised by Shenzhen STONE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document.
The test results in the report only apply to the tested sample.*



MPE Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies V05.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0$ for 10-g SAR

Calculation:

The maximum power is 9.62 dBm(9.162 mW) @2.437GHz

Separation Distance: 5mm

For 1-g SAR Result: $2.861 \leq 3.0$

Pass

So standalone SAR measurements are not required.

**2. Calculation:**

$$\text{EIRP} = \text{P} + \text{G}$$

Where P=Conducted Output Power (dBm)

G=Power Gain of the Antenna (dBi)

So

Columniform mini bluetooth speaker				
802.11b				
Test Mode	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)
2412 MHz	9.36	0	9.36	8.630
2437 MHz	9.45	0	9.45	8.810
2462 MHz	9.51	0	9.51	8.933
802.11g				
Test Mode	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)
2412 MHz	9.47	0	9.47	8.851
2437 MHz	9.59	0	9.59	9.099
2462 MHz	9.52	0	9.52	8.954
802.11n(HT20)				
Test Mode	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)
2412 MHz	9.25	0	9.25	8.414
2437 MHz	9.62	0	9.62	9.162
2462 MHz	9.47	0	9.47	8.851
802.11n(HT40)				
Test Mode	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)
2422 MHz	9.52	0	9.52	8.954
2437 MHz	9.61	0	9.61	9.141
2452 MHz	9.47	0	9.47	8.851

3. Conclusion:

No SAR Evaluation required since Transmitter EIRP is bellow FCC threshold.