

Test Report

Report No. : MTi250905014-0111E2

Date of Issue : 2025-10-09

Applicant : E-Filliate Incorporated

**Product : MAGNETIC WIRELESS CHARGER WITH
KICKSTAND**




**Model(s) : DXMA1410016, 141 0016 DW2, 141 0016 DW3,
141 0016 DWM, 141 0016 DWG, 141 0016 DWE,
141 0016 DWX, 141 0016 XXX, 141 0016,
DXMA1410016E, DXMA1410016X**

FCC ID : 2ADH6-1410016

Shenzhen Microtest Co., Ltd.

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	4
1.3	Description of support units	5
2	Measurement uncertainty	5
3	Test facilities and accreditations	5
3.1	Test laboratory	5
4	List of test equipment	6
5	Test result	7
5.2	Test setup	8
5.3	Test Procedures	8
5.4	Information of test equipment	9
5.5	Test results	10
	Photographs of the Test Setup	13
	Photographs of the EUT	14

Test Result Certification		
Applicant	E-Filliate Incorporated	
Applicant Address	11321 White Rock Rd. Rancho Cordova, CA 95742, USA.	
Manufacturer	E-Filliate Incorporated	
Manufacturer Address	11321 White Rock Rd. Rancho Cordova, CA 95742, USA.	
Factory 1	Versogo Tech (Shenzhen) Co., Ltd.	
Factory Address	Building 3rd, Xialingpai Industrial Zone, Dalang Street, Longhua District, Shenzhen City, Guangdong Province, China	
Factory 2	Versogo Tech (Vietnam) Technology Company Limited	
Factory Address	TS7 Road, Tien Son Industrial Park, Tam Son Ward, Bac Ninh Province, Viet Nam	
Product description		
Product name	MAGNETIC WIRELESS CHARGER WITH KICKSTAND	
Trademark	DEWALT	
Model name	DXMA1410016	
Series Model(s)	141 0016 DW2, 141 0016 DW3, 141 0016 DWM, 141 0016 DWG, 141 0016 DWE, 141 0016 DWX, 141 0016 XXX, 141 0016, DXMA1410016E, DXMA1410016X	
Standards	FCC CFR 47 PART 1, § 1.1310 FCC CFR 47 Part 2.1091	
Test method	KDB 680106 D01 Wireless Power Transfer v04	
Testing Information		
Date of test	2025-09-12 to 2025-09-30	
Test Result	Pass	
Prepared by:	Yanice Xie	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

1 General Description

1.1 Description of the EUT

Product name:	MAGNETIC WIRELESS CHARGER WITH KICKSTAND
Model name:	DXMA1410016
Series Model(s):	141 0016 DW2, 141 0016 DW3, 141 0016 DWM, 141 0016 DWG, 141 0016 DWE, 141 0016 DWX, 141 0016 XXX, 141 0016, DXMA1410016E, DXMA1410016X
Model difference:	All the models are the same circuit and module, except the model name.
Electrical rating:	Input: DC5V/3A,9V/2.2A Output:5W/7.5W/10W/15W
Accessories:	Cable: USB-A/Type-C to Type-C 1.8m
Hardware version:	NO:L02 DATE:20240528
Software version:	0x988E2A93
Test sample(s) number:	MTi250905014-01-R001
RF specification:	
Operation frequency:	115-205kHz(5W-EPP15W)&360kHz(MPP 15W)
Modulation type:	ASK
Antenna type:	Coil

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Power by USB-A adapter+Wireless Output(5W)
Mode2	Power by USB-A adapter+Wireless Output(7.5W)
Mode3	Power by USB-A adapter+Wireless Output(10W)
Mode4	Power by USB-A adapter+Wireless output(EPP15W)
Mode5	Power by USB-A adapter+Wireless output(MPP15W)
Mode6	Power by USB-C adapter+Wireless Output(5W)
Mode7	Power by USB-C adapter+Wireless Output(7.5W)
Mode8	Power by USB-C adapter+Wireless Output(10W)
Mode9	Power by USB-C adapter+Wireless output(EPP15W)
Mode10	Power by USB-C adapter+Wireless output(MPP15W)
Mode11	Standby

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
Mobile phone	Find X3	/	OPPO
Mobile phone	iPhone 16 pro	/	Apple
Lenovo USB-C adapter	C65B	1SGX21B35621Z13F1D4W	Lenovo
Support cable list			
Description	Length (m)	From	To
/	/	/	/

2 Measurement uncertainty

Parameter	Expanded Uncertainty
Magnetic field measurements(3kHz~10MHz)	$\pm 14.8\%$
Electric field measurements(3kHz~10MHz)	$\pm 17.5\%$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 Test facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	SPEAG	MAGPy-8H3 D+ED3	3101	2024/3/12	2027/3/11

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.6	2.6	/	/

5 Test result

5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30


f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

5.2 Test setup



5.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

5.4 Information of test equipment

Test equipment: MAGPy-8H3D+ED3	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm ² arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)
	
Test probe, without the casing	

Item	Specification
Test frequency range:	3kHz ~ 10MHz
Probe sensitivity	E-field: 0.08-2000 V/m H-field: 0.1-3200 A/m
Probe level response	E-field: ±1dB H-field: ±1dB
linearity error	E-field: ±0.3dB H-field: ±0.3dB
Isotropy	E-field: ±0.8dB H-field: ±0.6dB

5.5 Test results

Test condition 1: Mode 4 operating mode with client device (1 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	4.01	614	0.65%	0.02	1.63	3.07%
Bottom	2.56			0.05		
Left	3.1			0.01		
Right	2.03			0.02		
Front	1.23			0.01		
Back	0.77			0.009		

Test condition 2: Mode 4 operating mode with client device (50 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Top	3.21	614	0.52%	0.02	1.63	2.45%
Bottom	2.05			0.04		
Left	2.48			0.008		
Right	1.62			0.02		
Front	0.98			0.008		
Back	0.62			0.007		

Test condition 3: Mode 4 operating mode with client device (99 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	2.61	614	0.42%	0.01	1.63	1.99%
Bottom	1.66			0.03		
Left	2.02			0.007		
Right	1.32			0.01		
Front	0.80			0.007		
Back	0.50			0.006		

Test condition 1: Mode 5 operating mode with client device (1 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	0.75	614	0.12%	0.009	1.63	0.61%
Bottom	0.56			0.01		
Left	0.62			0.009		
Right	0.53			0.007		
Front	0.47			0.007		
Back	0.36			0.006		

Test condition 2: Mode 5 operating mode with client device (50 % battery status of client device)

Probe Position	E –field (V/m)			H–field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Top	0.60	614	0.10%	0.007	1.63	0.49%
Bottom	0.45			0.008		
Left	0.50			0.007		
Right	0.42			0.006		
Front	0.38			0.006		
Back	0.29			0.005		

Test condition 3: Mode 5 operating mode with client device (99 % battery status of client device)

Probe Position	E-field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Top	0.49	614	0.08%	0.006	1.63	0.40%
Bottom	0.36			0.007		
Left	0.40			0.006		
Right	0.34			0.005		
Front	0.31			0.005		
Back	0.23			0.004		

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****