

Prüfbericht-Nr.: <i>Test report no.:</i>	CN26NQ37 001	Auftrags-Nr.: <i>Order no.:</i>	48308150	Seite 1 von 24 Page 1 of 24
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2026-07-22	
Auftraggeber: <i>Client:</i>	Microchip Technology Inc. 2355 West Chandler Blvd. Chandler, Arizona 85224-6199, United States			
Prüfgegenstand: <i>Test item:</i>	IEEE 802.11 b/g/n SmartConnect IoT Module			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	ATWINC1500-MR210UB, ATWINC1510-MR210UB			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C Test report (WiFi 2.4GHz)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2026-08-07			
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003648659-004 A003938566-009 A004358425-007, 008 A004358425-001, 003, 004			
Prüfzeitraum: <i>Testing period:</i>	2026-08-17 - 2026-08-19			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland Taiwan Ltd. New Taipei Branch			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories			
Prüfergebnis*: <i>Test result*:</i>	Pass			
zusammengestellt von: <i>compiled by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i>	Ausstellungsdatum: <i>Issue date:</i>			
Stellung / Position:	Stellung / Position:			
Sonstiges / Other:	This report proposes alternative components for C6, C7, C15, C16, C18, C20, C23, C24, and Y1, featuring capacitance changes for C6/C7 (10pF) and a tighter frequency tolerance for Y1 (SIWARD, XTL581150-M197-002). To evaluate these changes, only the Output Power and RSE tests were performed. For the other test results, please refer to the TUV report No. CN25TIXC 001.			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN26NQ37 001

Seite 2 von 24
Page 2 of 24

Anmerkungen
Remarks

- | | |
|---|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(3)	Peak Output Power	Pass
5.1.3	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT	6
1. GENERAL REMARKS	7
1.1 COMPLEMENTARY MATERIALS	7
1.2 DECISION RULE OF CONFORMITY	7
2. TEST SITES	8
2.1 TEST LABORATORY	8
2.2 TEST FACILITY	8
2.3 TRACEABILITY	9
2.4 CALIBRATION	9
2.5 MEASUREMENT UNCERTAINTY	9
3. GENERAL PRODUCT INFORMATION	10
3.1 PRODUCT FUNCTION AND INTENDED USE	10
3.2 SYSTEM DETAILS AND RATINGS	10
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
3.4 SUBMITTED DOCUMENTS	11
4. TEST SET-UP AND OPERATION MODES	12
4.1 PRINCIPLE OF CONFIGURATION SELECTION	12
4.2 CARRIER FREQUENCY AND CHANNEL	12
4.3 TEST OPERATION AND TEST SOFTWARE	13
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	15
4.5 TEST SETUP DIAGRAM	15
4.6 DUTY CYCLE OF TEST SIGNAL	16
5. TEST RESULTS	17
5.1 TRANSMITTER REQUIREMENT & TEST SUITES	17
5.1.1 Antenna Requirement	17
5.1.2 Peak Output Power	18
5.1.3 Radiated Spurious Emissions and Band Edges	20

Prüfbericht - Nr.: **CN26NQ37 001**
Test Report No.

Seite 5 von 24
Page 5 of 24

APPENDIX A - TEST RESULT OF RADIATED EMISSIONS FOR DIPOLE ANTENNA

APPENDIX B - TEST RESULT OF RADIATED EMISSIONS FOR PCB ANTENNA

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: **CN26NQ37 001**
Test Report No.

Seite 6 von 24
Page 6 of 24

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2026-08-31

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Radiated Emissions for Dipole Antenna

Appendix B - Test Result of Radiated Emissions for PCB Antenna

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart C Section 15.247
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2. Test Sites

2.1 Test Laboratory

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

No.458-18, 458-19, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 180491 (TW3567)
ISED Registration No.: 25563 (TW3567)

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a IEEE 802.11 b/g/n SmartConnect IoT Module. It contains a WLAN compatible module enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	IEEE 802.11 b/g/n SmartConnect IoT Module
Type Identification	ATWINC1500-MR210UB, ATWINC1510-MR210UB
FCC ID	2ADHKATWINC1500U

Technical Specification of EUT

Item	EUT information
Operating Frequency	2412 MHz ~ 2462 MHz
Channel Spacing	5 MHz
Channel Number	802.11b/g/n HT20: 11
Data Rate	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7
Operation Voltage	3.0 ~ 4.2 Vdc (Typical = 3.3 Vdc)
Modulation	DSSS (DBPSK, DQPSK, CCK) OFDM (BPSK, QPSK, 16QAM, 64QAM)
Maximum Output Power (mW)	802.11b: 132.74 802.11g: 197.70 802.11n HT20: 190.99
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

Note:

1. All models are listed as below.

Type Identification	Difference
ATWINC1500-MR210UB	Identical HW designed (layout and BoM), ATWINC1500-MR210UB is 4Mb flash ; ATWINC1510-MR210UB is 8Mb flash
ATWINC1510-MR210UB	

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

Prüfbericht - Nr.: **CN26NQ37 001**
Test Report No.

Seite 11 von 24
Page 11 of 24

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

4.2 Carrier Frequency and Channel

802.11b, 802.11g and 802.11n HT20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	MCHPRT2_v1.7.6.1
---------------	------------------

The samples were used as follows:

A003648659-004

A003938566-009

A004358425-007, 008

A004358425-001, 003, 004

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	-	Dipole Antenna
-	√	√	√	-	PCB Antenna

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **X-plane**.
2. "-" means no effect.
3. The antenna has been evaluated, and only the worst-case scenario has been recorded.

Antenna Port Conducted Measurement

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
Power Only	802.11b	1 to 11	1	1.0
Power Only	802.11g	1 to 11	6	6.0
Power Only	802.11n HT20	1 to 11	6	MCS0

*Only the worst-case channel has been evaluated.

Radiated Spurious Emissions (Above 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
Power Only	802.11b	1 to 11	1	1.0
Power Only	802.11g	1 to 11	6	6.0
Power Only	802.11n HT20	1 to 11	6	MCS0

Radiated Spurious Emissions (Below 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11g	1 to 11	6	6.0

Prüfbericht - Nr.: **CN26NQ37 001**
Test Report No.

Seite 14 von 24
Page 14 of 24

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement (Power Only)	22.7-23.4 °C	63-64 %	Jerome Chang
Radiated Spurious Emissions above 1 GHz	24.5-26.8 °C	54-59 %	Chuan Chu
Radiated Spurious Emissions below 1 GHz	24.5-26.8 °C	54-59 %	Chuan Chu

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT


None.

Support Unit

Support Unit								
No	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
1	Adapter	Lenovo	ADLX65NCC3A	-	-	-	155	Radiated Test
2	Notebook	Lenovo	81BL	MP1DCD6Y	-	-	-	
3	USB Cable	TUV	TUV-01		-	-	180	
-	Notebook	Lenovo	81BL	MP1DCD6Y	-	-	-	Conducted Test
-	Power Supply	GWINSTEK	GPS-3303	GEU915620	-	-	-	

4.5 Test Setup Diagram

<Radiated Spurious Emissions Mode>



Prüfbericht - Nr.: **CN26NQ37 001**
Test Report No.

Seite 16 von 24
Page 16 of 24

4.6 Duty Cycle of Test Signal

Please refer to TUV report no. CN25TIXC 001.

5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the antenna information is as listed below. The antenna is with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

*Antennas no.: 3 and 4 are selected for the worst-case.

Sino.	P/N	Vendor	Antenna Gain @ 2.4GHz Band	Antenna Type	Remarks
1	RFA-02-P33	Aristotle	2 dBi	PCB	Cable length 150mm
2	RFA-02-D3	Aristotle	2 dBi	Dipole-no encl.	--
3	RFA-02-L2H1	Aristotle	2 dBi	Dipole	--
4	RFA-02-P05	Aristotle	2 dBi	PCB	Cable length 150mm
5	86254	Delock	2 dBi	PCB	
6	RFA-02-C2M2	Aristotle	2 dBi	Dipole	--
7	W3525B039	Pulse Electronics Corporation	2 dBi	PCB	Cable length 100mm
8	RFDPA870920IMLB301	WALSIN	1.84 dBi	Dipole-DB	Dual Band
9	RN-SMA-S	Microchip	0.56 dBi	Dipole-short	--

*Refer to EUT photo for details.

5.1.2 Peak Output Power

Limit 1 watt (30 dBm)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2026/02/24	2027/02/23	2026/08/17	2026/08/17
Power Sensor	Anritsu	MA2411B	1725269	2026/02/24	2027/02/23	2026/08/17	2026/08/17


Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

Gate Setup:

1. Select the [Gates] tab in the software.
2. Check the box (e.g., Gate 1) to display it on the trace.
3. Set Gate Position
 - Drag the gate line with the mouse to the desired point on the waveform, or
 - Enter Values using the [Set] button and input start/stop times.
4. Switch to the next measurement channel and repeat the same gate setup procedure.
5. The instrument calculates average/peak power only within the defined gate interval.



Test Result**Peak Output Power**

Mode	Channel	Channel Frequency (MHz)	Peak Output Power		Limit (dBm)
			(dBm)	(mW)	
802.11b	1	2412	21.23	132.74	30
802.11g	6	2437	22.96	197.70	30
802.11n HT20	6	2437	22.81	190.99	30

Average Power

Mode	Channel	Channel Frequency (MHz)	Average Power	
			(dBm)	(mW)
802.11b	1	2412	18.53	71.29
802.11g	6	2437	16.23	41.98
802.11n HT20	6	2437	15.56	35.97

5.1.3 Radiated Spurious Emissions and Band Edges

Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup


<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Prüfbericht - Nr.: CN26NQ37 001
Test Report No.

Seite 22 von 24
Page 22 of 24

Test Instruments

Test Date: 2026/08/17 ~ 2026/08/19

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1 GHz					
Signal Analyzer	R&S	FSV40	101508	2026/04/28	2027/04/27
Horn Antenna	ETS-Lindgren	3117	00218930	2025/12/11	2026/12/10
Amplifier	EM	EM01G18GA	060967	2026/03/31	2027/03/30
HF-AMP + AC source	EMCI	EMC184045SE	980657	2026/02/06	2027/02/05
Horn Antenna	SCHWARZBECK	BBHA 9170	00887	2026/03/26	2027/03/25
RF Cable	EM	EM102A	EM102A-KMKM-700	2026/05/08	2027/05/07
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	800901/2EA	2025/10/23	2026/10/22
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	801027/2EA	2025/10/23	2026/10/22
3G High Pass Filter	Warison	WFIL-H3000-12000F	WRP19FWC2B2	2026/06/01	2027/05/31
7G High Pass Filter	EMCI	HPF0718	G001	2026/04/10	2027/04/09
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A
30 MHz 1 GHz					
Receiver	R&S	ESR7	102108	2026/07/02	2027/07/01
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2026/05/11	2027/05/10
LF-AMP	Agilent	8447D	2944A107722	2026/03/19	2027/03/18
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104EA	800056/4EA	2026/03/20	2027/03/19
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	804680/4	2026/03/20	2027/03/19
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	MY37202/4	2026/03/20	2027/03/19
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A
Below 30 MHz					
Receiver	R&S	ESR7	102108	2026/07/02	2027/07/01
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2025/12/16	2026/12/15
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104EA	800056/4EA	2026/03/20	2027/03/19
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	804680/4	2026/03/20	2027/03/19
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht - Nr.: **CN26NQ37 001**
Test Report No.

Seite 24 von 24
Page 24 of 24

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Amplifier (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix A and B.

Note: The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated at least 20 dB below the permissible value to be reported.