

Prüfbericht-Nr.: <i>Test report no.:</i>	CN2646ET 001	Auftrags-Nr.: <i>Order no.:</i>	48302355	Seite 1 von 32 Page 1 of 32
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2026-03-05	
Auftraggeber: <i>Client:</i>	Microchip Technology Inc. 2355 West Chandler Blvd. Chandler, Arizona 85224-6199, United States			
Prüfgegenstand: <i>Test item:</i>	Wireless MCU Module with Bluetooth® Low Energy 6.0 qualified, IEEE® 802.15.4			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	PIC32WM-BZ6602CE, PIC32WM-BZ6602CC			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C Test report (BLE)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2026-03-18			
Prüfmuster-Nr.: <i>Test sample no:</i>	A004228028-002 A004228028-003			
Prüfzeitraum: <i>Testing period:</i>	2026-03-25 - 2026-04-27			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland Taiwan Ltd. New Taipei Branch			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories			
Prüfergebnis*: <i>Test result*:</i>	Pass			
zusammengestellt von: <i>compiled by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i>	2026-05-05	Ausstellungsdatum: <i>Issue date:</i>	2026-05-05	
Stellung / Position:	Senior Project Manager	Stellung / Position:	Section Manager	
Sonstiges / Other:	This EUT includes the secondary source. This change involves the substitution of alternate parts for certain capacitors, inductors, ferrite beads, and the 16 MHz crystal. The component type, nominal value, and original function remain unchanged; the only differences are the part numbers and supply sources.			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN2646ET 001

Seite 2 von 32
Page 2 of 32

Anmerkungen
Remarks

- | | |
|----------|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.
Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.
Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i>
<i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

Prüfbericht-Nr.: CN2646ET 001
Test report no.:Seite 3 von 32
Page 3 of 32

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(3)	Peak Output Power	Pass
0	15.247(a)(2)	6 dB Bandwidth	Pass
0	2.1049	99% Occupied Bandwidth	Pass
5.1.4	15.247(e)	Power Spectral Density	Pass
5.1.5	15.247(d)	Conducted Spurious Emissions and Band Edges	Pass
5.1.6	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT	6
1. GENERAL REMARKS	7
1.1 COMPLEMENTARY MATERIALS	7
1.2 DECISION RULE OF CONFORMITY	7
2. TEST SITES	8
2.1 TEST LABORATORY	8
2.2 TEST FACILITY	8
2.3 TRACEABILITY	9
2.4 CALIBRATION	9
2.5 MEASUREMENT UNCERTAINTY	9
3. GENERAL PRODUCT INFORMATION	10
3.1 PRODUCT FUNCTION AND INTENDED USE	10
3.2 SYSTEM DETAILS AND RATINGS	10
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS	11
3.4 SUBMITTED DOCUMENTS	11
4. TEST SET-UP AND OPERATION MODES	12
4.1 PRINCIPLE OF CONFIGURATION SELECTION	12
4.2 CARRIER FREQUENCY AND CHANNEL	12
4.3 TEST OPERATION AND TEST SOFTWARE	13
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	14
4.5 TEST SETUP DIAGRAM	15
4.6 DUTY CYCLE OF TEST SIGNAL	16
5. TEST RESULTS	17
5.1 TRANSMITTER REQUIREMENT & TEST SUITES	17
5.1.1 Antenna Requirement	17
5.1.2 Peak Output Power	18
5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth	23
5.1.4 Power Spectral Density	24
5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth	25
5.1.6 Radiated Spurious Emissions and Band Edges	26
5.2 MAINS EMISSION	31
5.2.1 Mains Conducted Emission	31

Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 5 von 32
Page 5 of 32

APPENDIX A - TEST RESULT OF CONDUCTED

APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 6 von 32
Page 6 of 32

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2026-05-05

Prüfbericht-Nr.: CN2646ET 001
Test report no.:Seite 7 von 32
Page 7 of 32

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Conducted

Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart C Section 15.247
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 8 von 32
Page 8 of 32

2. Test Sites

2.1 Test Laboratory

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 180491 (TW3567)
ISED Registration No.: 25563 (TW3567)

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Wireless MCU Module with Bluetooth® Low Energy 6.0 qualified, IEEE® 802.15.4. It contains a Bluetooth compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Wireless MCU Module with Bluetooth® Low Energy 6.0 qualified, IEEE® 802.15.4
Type Identification	PIC32WM-BZ6602CE, PIC32WM-BZ6602CC
FCC ID	2ADHKBZ6602

Technical Specification of EUT

Item	EUT information
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Number	40
Data Rate	1Mbps, 2Mbps, S=2 and S=8
Operation Voltage	Non ECC variants: 1.9Vdc to 3.6Vdc ECC variant: 2Vdc to 3.6Vdc
Modulation	GFSK
Maximum Output Power (mW)	10.21
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

Note:

1.All models are listed as below.

Brand	Type Identification	ECC Mode	Difference
Main	PIC32WM-BZ6602CE	Without	All models are electrically identical, different model names are for marketing purpose and with/without ECC mode.
Series	PIC32WM-BZ6602CC	with	

* PIC32WM-BZ6602CC was selected as the worst-case representative sample, and both primary and secondary source configurations were evaluated in this report.

2. ECC (Trust and Go IC).

Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 11 von 32
Page 11 of 32

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

Channel	Frequency (MHz)	Power Setting		
		S2	S8	2Mbps
Low	2404	11	11	11
Middle	2440	11	11	11
High	2478	11	11	11
Channel	Frequency (MHz)	1Mbps		
Low	2402	11		
Middle	2440	11		
High	2480	11		

4.2 Carrier Frequency and Channel

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 13 von 32
Page 13 of 32

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	MCHPRT3_v1.0.2.8463
---------------	---------------------

The samples were used as follows:

A004228028-002

A004228028-003

Full test was applied on all test modes, but only worst case was shown.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	√	Primary Source (ECC)
-	√	√	-	-	Secondary Source (ECC)

Note:

1. The EUT had been pre-tested on the position of each 3 axis. The worst case was found when position on **Z-plane**.
2. "-" means no effect.
3. The secondary source was only tested for the worst case of output power and RSE tests.

Antenna Port Conducted Measurement

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402, 2440, 2480	1
-	2402 to 2480	2402, 2440, 2480	2
-	2404 to 2478	2404, 2440, 2478	S2
-	2404 to 2478	2404, 2440, 2478	S8

Radiated Spurious Emissions (Above 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402, 2440, 2480	1
-	2404 to 2478	2404, 2440, 2478	2

Radiated Spurious Emissions (Below 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402	1

Mains Conducted Emission

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Frequency (MHz)	Tested Frequency (MHz)	Date Rate (Mbps)
-	2402 to 2480	2402	1

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 14 von 32
Page 14 of 32

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	22.3-23.7 °C	53-65 %	Nick Hsu & Jerome Chang
Radiated Spurious Emissions above 1 GHz	25.7-27.2 °C	45-53 %	Chuan Chu
Radiated Spurious Emissions below 1 GHz	25.7-27.2 °C	45-53 %	Chuan Chu
Mains Conducted Emission	23.5 °C	54 %	Chuan Chu

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT


None.

Support Unit


Support Unit								
No	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
1	AC Adapter	HP	TPN-LA16	-	-	-	200	Radiated and Mains Conducted Tests
2	Notebook	HP	15s-du0007TX	CND93662WV	-	-	-	
3	USB to type-C	E-books	E-IPD186	-	-	-	150	
1	AC Adapter	HP	TPN-LA16	-	-	-	-	Conducted Test
-	Notebook	DELL	Latitude 7490	887V7Y2	-	-	-	

4.5 Test Setup Diagram

<Radiated Spurious Emissions Mode>



<Mains Conducted Emission Mode>




Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 16 von 32
Page 16 of 32

4.6 Duty Cycle of Test Signal

Mode	On + Off Time (ms)	On Time (ms)	Duty Cycle (%)	Duty Factor (dB)
1Mbps	2.5	2.14	85.60	0.68
2Mbps	1.255	1.02	81.27	0.90



Prüfbericht-Nr.: CN2646ET 001
Test report no.:Seite 17 von 32
Page 17 of 32

5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.38 dBi. The antenna is a chip antenna with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.
Refer to EUT photo for details.

Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 18 von 32
Page 18 of 32

5.1.2 Peak Output Power

Limit 1 watt (30 dBm)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2026/02/24	2027/02/23	2026/03/25	2026/04/22
Power Sensor	Anritsu	MA2411B	1725269	2026/02/24	2027/02/23	2026/03/25	2026/04/22


Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

Gate Setup:

1. Select the [Gates] tab in the software.
2. Check the box (e.g., Gate 1) to display it on the trace.
3. Set Gate Position
 - Drag the gate line with the mouse to the desired point on the waveform, or
 - Enter Values using the [Set] button and input start/stop times.
4. Switch to the next measurement channel and repeat the same gate setup procedure.
5. The instrument calculates average/peak power only within the defined gate interval.



Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 19 von 32
Page 19 of 32

Test Result
Peak Output Power, Primary Source
<1Mbps>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2402	10.09	10.21	30
Middle Channel	2440	9.97	9.93	30
High Channel	2480	9.82	9.59	30

<2Mbps>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2404	10.08	10.19	30
Middle Channel	2440	9.96	9.91	30
High Channel	2478	9.82	9.59	30

<S2>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2404	9.82	9.59	30
Middle Channel	2440	9.68	9.29	30
High Channel	2478	9.54	8.99	30

<S8>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2404	9.79	9.53	30
Middle Channel	2440	9.67	9.27	30
High Channel	2478	9.54	8.99	30

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 20 von 32
 Page 20 of 32

Peak Output Power, Secondary Source

<1Mbps>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2402	9.89	9.75	30
Middle Channel	2440	9.76	9.46	30
High Channel	2480	9.54	8.99	30

<2Mbps>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2404	9.82	9.59	30
Middle Channel	2440	9.72	9.38	30
High Channel	2478	9.60	9.12	30

<S2>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2404	9.54	8.99	30
Middle Channel	2440	9.46	8.83	30
High Channel	2478	9.31	8.53	30

<S8>

Channel	Channel Frequency	Peak Output Power		Limit (dBm)
	(MHz)	(dBm)	(mW)	
Low Channel	2404	9.57	9.06	30
Middle Channel	2440	9.42	8.75	30
High Channel	2478	9.32	8.55	30

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

 Seite 21 von 32
 Page 21 of 32

Average Power, Primary Source
<1Mbps>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	10.03	10.07
Middle Channel	2440	9.92	9.82
High Channel	2480	9.78	9.51

<2Mbps>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2404	10.03	10.07
Middle Channel	2440	9.92	9.82
High Channel	2478	9.78	9.51

<S2>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2404	9.76	9.46
Middle Channel	2440	9.64	9.20
High Channel	2478	9.49	8.89

<S8>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2404	9.75	9.44
Middle Channel	2440	9.63	9.18
High Channel	2478	9.48	8.87

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 22 von 32
Page 22 of 32

Average Power, Secondary Source
<1Mbps>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2402	9.82	9.59
Middle Channel	2440	9.70	9.33
High Channel	2480	9.50	8.91

<2Mbps>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2404	9.77	9.48
Middle Channel	2440	9.66	9.25
High Channel	2478	9.51	8.93

<S2>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2404	9.47	8.85
Middle Channel	2440	9.41	8.73
High Channel	2478	9.21	8.34

<S8>

Channel	Channel Frequency	Average Power	
	(MHz)	(dBm)	(mW)
Low Channel	2404	9.52	8.95
Middle Channel	2440	9.33	8.57
High Channel	2478	9.21	8.34

Prüfbericht-Nr.: CN2646ET 001
Test report no.:


Seite 23 von 32
Page 23 of 32

5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth

Limit The minimum 6 dB bandwidth shall be at least 500 kHz.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2026/02/24	2027/02/23	2026/03/25	2026/04/07

Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- For 99% occupied bandwidth measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

Test Results

Please refer to Appendix A.

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 24 von 32
 Page 24 of 32


5.1.4 Power Spectral Density

Limit

The power spectral density shall not be greater than 8 dBm in any 3 kHz band.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2026/02/24	2027/02/23	2026/03/25	2026/04/07

Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

Test Results

Please refer to Appendix A.

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 25 von 32
 Page 25 of 32


5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100kHz Bandwidth

Limit

20dB (below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2026/02/24	2027/02/23	2026/03/25	2026/04/07

Test Procedure

Measurement procedure REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement procedure OOBE

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

Test Results

Please refer to Appendix A.

5.1.6 Radiated Spurious Emissions and Band Edges

Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup

<Radiated Emissions below 30 MHz>




<Radiated Emissions 30 MHz to 1 GHz>



Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 27 von 32
Page 27 of 32

<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 28 von 32
Page 28 of 32

Test Instruments

Test Date: 2026/04/02 ~ 2026/04/27

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1 GHz					
Signal Analyzer	R&S	FSV40	101508	2025/04/29	2026/04/28
Horn Antenna	ETS-Lindgren	3117	00218929	2025/11/20	2026/11/19
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2025/04/30	2026/04/29
HF-AMP + AC source	EMCI	EMC051845SE	980633	2025/01/15	2026/01/14
HF-AMP + AC source	EMCI	EMC051845SE	980656	2026/01/15	2027/01/14
Microwave Cable	EMCI	EM102A-KMKM-700	504231101002	2025/05/23	2026/05/22
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	800902/2EA	2025/06/06	2026/06/05
Microwave Cable	HUBER+SUHNER	SUCOFLEX 102EA	801026/2EA	2025/06/06	2026/06/05
3G High Pass Filter	EMCI	ZHPF3180	08223315	2025/12/18	2026/12/17
7G High Pass Filter	EMCI	ZHPF3180	08223317	2025/05/27	2026/05/26
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A
30 MHz – 1 GHz					
Receiver	R&S	ESR7	102109	2026/02/04	2027/02/03
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2025/04/08	2026/04/07
LF-AMP	Agilent	8447D	2727A05146	2026/01/15	2027/01/14
Microwave Cable	EMCI	RG 214_U/2*11N/7M	24038601	2026/02/25	2027/02/24
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	802244/4	2026/02/25	2027/02/24
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	MY37203/4	2026/02/25	2027/02/24
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A
Below 30 MHz					
Receiver	R&S	ESR7	102109	2026/02/04	2027/02/03
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2025/12/16	2026/12/15
Microwave Cable	EM	RG 214_U/2*11N/7M	24038601	2026/02/25	2027/02/24
Microwave Cable	HUBER+SUHNER	SUCOFLEX 104	802244/4	2026/02/25	2027/02/24
Test Software	Audix E3	15914a_20191106_tuv	PK-001087	N/A	N/A

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H0 and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 30 von 32
Page 30 of 32

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Amplifier (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

Note: The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated at least 20 dB below the permissible value to be reported.

Prüfbericht-Nr.: CN2646ET 001
Test report no.:

Seite 31 von 32
Page 31 of 32

5.2 Mains Emission


5.2.1 Mains Conducted Emission

Limit

Mains Conducted Emission as defined in §15.207 must comply with the mains conducted emission limits.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Test Date: 2026/04/21

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Two-Line V-Network	SCHWARZBECK	NSLK 8127	8127-00976	2026/01/07	2027/01/06
EMI Test Receiver	R&S	ESCI	101094	2025/11/19	2026/11/18

Prüfbericht-Nr.: **CN2646ET 001**
Test report no.:

Seite 32 von 32
Page 32 of 32

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

Test Results


Please refer to Appendix B.

Appendix A: Test Results of Conducted Test

Test Result of 6 dB Bandwidth


BLE_1M

Channel	Channel Frequency (MHz)	6 dB Bandwidth (kHz)	Limit (kHz)	Result
Low Channel	2402	684.32	> 500	Pass
Middle Channel	2440	689.31	> 500	Pass
High Channel	2480	694.31	> 500	Pass



BLE_2M


Channel	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2404	1.15	> 0.5	Pass
Middle Channel	2440	1.13	> 0.5	Pass
High Channel	2478	1.15	> 0.5	Pass



Test Result of 99% Occupied Bandwidth


BLE_1M

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2402	1.04
Middle Channel	2440	1.04
High Channel	2480	1.05



BLE_2M


Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2404	2.07
Middle Channel	2440	2.07
High Channel	2478	2.06



Test Result of Power Spectral Density


BLE_1M

Channel	Channel Frequency (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	2402	-4.63	8	Pass
Middle Channel	2440	-4.82	8	Pass
High Channel	2480	-4.87	8	Pass




BLE_2M

Channel	Channel Frequency (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	2404	-6.26	8	Pass
Middle Channel	2440	-6.34	8	Pass
High Channel	2478	-6.34	8	Pass




Test Result of Conducted Spurious Emissions

BLE_1M




BLE_2M



Test Result of Conducted Band Edge

BLE_1M



BLE_2M

