APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
Xiamen Prima Technology Inc

Bluetooth module
Model No.: BT03B110

FCC ID: 2ADID-BT03B110

Prepared for	:	Xiamen Prima Technology Inc.
Address	:	No.178, Xinfeng Road, Xiamen, Fujian, P.R. China
Prepared by	:	ACCURATE TECHNOLOGY CO., LTD
Address	:	F1, Bldg. A, Chan Yuan New Material Port, Keyuan Rd. Science & Industry Park, Nan Shan, Shenzhen, Guangdong P.R. China
		Tel: (0755) 26503290 Fax: (0755) 26503396

Report No.	:	ATE20161327
Date of Test	:	May 13, 2016--Jun 29, 2016
Date of Report	:	Jun 30, 2016

TABLE OF CONTENTS

Description Page

Test Report Certification
1. GENERAL INFORMATION 5
1.1. Description of Device (EUT) 5
1.2. Accessory and Auxiliary Equipment 5
1.3. Description of Test Facility 6
1.4. Measurement Uncertainty 6
2. MEASURING DEVICE AND TEST EQUIPMENT 7
3. OPERATION OF EUT DURING TESTING 8
3.1. Operating Mode 8
3.2. Configuration and peripherals 8
4. TEST PROCEDURES AND RESULTS 9
5. 20DB BANDWIDTH TEST 10
5.1. Block Diagram of Test Setup 10
5.2. The Requirement For Section 15.247(a)(1) 10
5.3. EUT Configuration on Measurement 10
5.4. Operating Condition of EUT 10
5.5. Test Procedure 10
5.6. Test Result 11
6. CARRIER FREQUENCY SEPARATION TEST 17
6.1. Block Diagram of Test Setup 17
6.2. The Requirement For Section 15.247(a)(1) 17
6.3. EUT Configuration on Measurement 17
6.4. Operating Condition of EUT 17
6.5. Test Procedure 18
6.6. Test Result 18
7. NUMBER OF HOPPING FREQUENCY TEST 24
7.1. Block Diagram of Test Setup 24
7.2. The Requirement For Section 15.247(a)(1)(iii) 24
7.3. EUT Configuration on Measurement 24
7.4. Operating Condition of EUT 24
7.5. Test Procedure 24
7.6. Test Result 25
8. DWELL TIME TEST 27
8.1. Block Diagram of Test Setup 27
8.2. The Requirement For Section 15.247(a)(1)(iii) 27
8.3. EUT Configuration on Measurement 27
8.4. Operating Condition of EUT 27
8.5. Test Procedure 27
8.6. Test Result 28
9. MAXIMUM PEAK OUTPUT POWER TEST 43
9.1. Block Diagram of Test Setup 43
9.2. The Requirement For Section 15.247(b)(1) 43
9.3. EUT Configuration on Measurement 43
9.4. Operating Condition of EUT 43
9.5. Test Procedure 43

9.6. Test Result 44
10. RADIATED EMISSION TEST 50
10.1. Block Diagram of Test Setup 50
10.2. The Limit For Section 15.247(d) 51
10.3. Restricted bands of operation 52
10.4. Configuration of EUT on Measurement 52
10.5. Test Procedure 53
10.6. The Field Strength of Radiation Emission Measurement Results 53
11. BAND EDGE COMPLIANCE TEST 66
11.1. Block Diagram of Test Setup 66
11.2. The Requirement For Section 15.247(d) 66
11.3. EUT Configuration on Measurement 66
11.4. Operating Condition of EUT 66
11.5. Test Procedure 67
11.6. Test Result 67
12. AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) 90
12.1. Power Line Conducted Emission Measurement Limits 90
12.2. Test Procedure 90
12.3. Power Line Conducted Emission Measurement Results 90
13. ANTENNA REQUIREMENT 91
13.1. The Requirement 91
13.2. Antenna Construction 91

Test Report Certification

Applicant : Xiamen Prima Technology Inc

Manufacturer : Xiamen Prima Technology Inc

EUT Description : Bluetooth module

(A) MODEL NO.: BT03B110

(B) Trade Mark : PRIMA

(C) Voltage: DC 3.3～5.5V

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.10: 2013

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : May 13, 2016--Jun 29, 2016
Date of Report: Jun 30, 2016

Prepared by : Tim Zhang
(Tim.zhang, Engineer)

Approved & Authorized Signer : Sean Liu
(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1.Description of Device (EUT)

EUT	:	Bluetooth module
Model Number	:	BT03B110
Bluetooth version	:	BT V4.0 Dual Mode This report is for BT classic mode
Frequency Range	:	2402MHz-2480MHz
Number of Channels	:	40 for BT V4.0 LE 79 for BT classic mode
Antenna Gain	:	2dBi
Antenna type	:	PIFA Antenna
Trade Name	:	PRIMA
Test Voltage	:	DC 3.3～5.5V
Modulation mode	:	GFSK for BT V4.0 LE GFSK, π/4 DQPSK, 8DPSK for BT classic mode
Applicant	:	Xiamen Prima Technology Inc
Address	:	No.178, Xinfeng Road, Xiamen, Fujian, P.R. China.
Manufacturer	:	Xiamen Prima Technology Inc
Address	:	Wanlida, Industry Zone Building C, Nanjing Fujian, P.R. China.
Date of sample received	:	May 13, 2016
Date of Test	:	May 13, 2016--Jun 29, 2016

1.2.Accessory and Auxiliary Equipment

PC	Manufacturer: LENOVO M/N: 4290-RT8 S/N: R9-FW93G 11/08

1.3.Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen Listed by FCC The Registration Number is 752051 Listed by Industry Canada The Registration Number is 5077A-2 Accredited by China National Accreditation Committee for Laboratories The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.4.Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 10, 2016	Jan. 09, 2017
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 10, 2016	Jan. 09, 2017
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 10, 2016	Jan. 09, 2017
Pre-Amplifier	Rohde&Schwarz	CBLU1183540-01	3791	Jan. 10, 2016	Jan. 09, 2017
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 14, 2016	Jan. 13, 2017
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 14, 2016	Jan. 13, 2017
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 14, 2016	Jan. 13, 2017
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 14, 2016	Jan. 13, 2017
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 10, 2016	Jan. 09, 2017
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 10, 2016	Jan. 09, 2017
Highpass Filter	Wainwright Instruments	WHKX3.6/18G-10SS	N/A	Jan. 10, 2016	Jan. 09, 2017
Band Reject Filter	Wainwright Instruments	WRCG2400/2485-2375/2510-60/11SS	N/A	Jan. 10, 2016	Jan. 09, 2017

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: Transmitting mode
Low Channel: 2402MHz
Middle Channel: 2441MHz
High Channel: 2480MHz
Hopping

3.2.Configuration and peripherals



4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission Test	N/A
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.203	Antenna Requirement	Compliant

Note: The power supply mode of the EUT is DC 3.3-5.5V, According to the FCC standard requirements, conducted emission is not applicable.

5. 20DB BANDWIDTH TEST

5.1.Block Diagram of Test Setup



(EUT: Bluetooth module)

5.2.The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.3.EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

5.5.Test Procedure

5.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2.Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.

5.5.3.The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.6.Test Result

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	Π/4-DQPSK 20dB Bandwidth (MHz)	8DPSK 20dB Bandwidth (MHz)	Result
Low	2402	0.955	1.363	1.346	Pass
Middle	2441	0.960	1.363	1.346	Pass
High	2480	0.960	1.359	1.350	Pass

The spectrum analyzer plots are attached as below.

GFSK Mode

Low channel



Date: 20.JUN.2016 15:47:29

Middle channel



Date: 20.JUN.2016 15:49:15

High channel



Date: 20.JUN.2016 15:50:20

Π/4-DQPSK Mode

Low channel



Date: 20.JUN.2016 15:50:53

Middle channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4408263 GHz	-6.93 dBm	ndB down	1.3632 MHz
T1		1	2.4403271 GHz	-26.84 dBm	ndB	20.00 dB
T2		1	2.4416903 GHz	-27.35 dBm	Q factor	1790.5

Date: 20.JUN.2016 15:51:16

High channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.479822 GHz	-6.94 dBm	ndB down	1.3589 MHz
T1		1	2.4793271 GHz	-26.90 dBm	ndB	20.00 dB
T2		1	2.480686 GHz	-26.52 dBm	Q factor	1824.9

Date: 20.JUN.2016 15:51:39

8DPSK Mode

Low channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4021346 GHz	-7.34 dBm	ndB down	1.3459 MHz
T1		1	2.4013314 GHz	-27.17 dBm	ndB	20.00 dB
T2		1	2.4026773 GHz	-27.08 dBm	Q factor	1784.8

Date: 20.JUN.2016 15:52:05

Middle channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4411346 GHz	-6.96 dBm	ndB down	1.3459 MHz
T1		1	2.4403314 GHz	-26.63 dBm	ndB	20.00 dB
T2		1	2.4416773 GHz	-27.01 dBm	Q factor	1813.8

Date: 20.JUN.2016 15:52:33

High channel



Date: 20.JUN.2016 15:53:03

6. CARRIER FREQUENCY SEPARATION TEST

6.1.Block Diagram of Test Setup



(EUT: Bluetooth module)

6.2.The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.3.EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4.Operating Condition of EUT

6.4.1.Setup the EUT and simulator as shown as Section 6.1.

6.4.2.Turn on the power of all equipment.

6.4.3.Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5.Test Procedure

6.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2.Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 2MHz.

6.5.3.Set the adjacent channel of the EUT Maxhold another trace.

6.5.4.Measurement the channel separation

6.6.Test Result

GFSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.0022	25KHz or 20dB bandwidth	PASS
	2403			
Middle	2440	1.0014	25KHz or20dB bandwidth	PASS
	2441			
High	2479	1.0014	25KHz or 20dB bandwidth	PASS
	2480			

Π/4-DQPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2440	1.0072	25KHz or 2/3*20dB bandwidth	PASS
	2441			
High	2479	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2480			

8DPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.0029	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2440	1.0072	25KHz or 2/3*20dB bandwidth	PASS
	2441			
High	2479	1.0072	25KHz or 2/3*20dB bandwidth	PASS
	2480			

The spectrum analyzer plots are attached as below.

GFSK Mode

Low channel



Date: 20.JUN.2016 16:21:57

Middle channel



Date: 20.JUN.2016 16:25:49

High channel



Date: 20.JUN.2016 16:28:01

Π/4-DQPSK Mode

Low channel



Date: 20.JUN.2016 16:30:02

Middle channel



Date: 20.JUN.2016 16:31:08

High channel



Date: 20.JUN.2016 16:32:18

8DPSK Mode

Low channel



Date: 20.JUN.2016 16:33:35

Middle channel



Date: 20.JUN.2016 16:34:25

High channel



Date: 20.JUN.2016 16:36:03

7. NUMBER OF HOPPING FREQUENCY TEST

7.1.Block Diagram of Test Setup



(EUT: Bluetooth module)

7.2.The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3.EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4.Operating Condition of EUT

7.4.1.Setup the EUT and simulator as shown as Section 7.1.

7.4.2.Turn on the power of all equipment.

7.4.3.Let the EUT work in TX (Hopping on) modes measure it.

7.5.Test Procedure

7.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2.Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.

7.5.3.Max hold, view and count how many channel in the band.

7.6.Test Result

Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	⩾15

The spectrum analyzer plots are attached as below.

Number of hopping channels(GFSK)



Number of hopping channels(Π/4-DQPSK)



Date: 20.JUN.2016 16:14:23

Number of hopping channels(8DPSK)



Date: 20.JUN.2016 16:18:26

8. DWELL TIME TEST

8.1.Block Diagram of Test Setup



(EUT: Bluetooth module)

8.2.The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3.EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4.Operating Condition of EUT

8.4.1.Setup the EUT and simulator as shown as Section 8.1.

8.4.2.Turn on the power of all equipment.

8.4.3.Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

8.5.Test Procedure

8.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2.Set center frequency of spectrum analyzer = operating frequency.

8.5.3.Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=5ms, 10ms, 15ms. Get the pulse time.

8.5.4.Repeat above procedures until all frequency measured were complete.

8.6.Test Result

GFSK Mode

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.428	136.96	400
	2441	0.438	140.16	400
	2480	0.442	141.44	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(2*79))×31.6				
DH3	2402	1.746	279.36	400
	2441	1.790	286.40	400
	2480	1.761	281.76	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(4*79))×31.6				
DH5	2402	2.978	317.65	400
	2441	2.978	317.65	400
	2480	3.000	320.00	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(6*79))×31.6				

Π/4-DQPSK

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.446	142.72	400
	2441	0.442	141.44	400
	2480	0.438	140.16	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(2*79))×31.6				
DH3	2402	1.714	274.24	400
	2441	1.714	274.24	400
	2480	1.728	276.48	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(4*79))×31.6				
DH5	2402	3.000	320.00	400
	2441	3.022	322.35	400
	2480	2.978	317.65	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(6*79))×31.6				

8DPSK Mode

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.449	143.68	400
	2441	0.446	142.72	400
	2480	0.446	142.72	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(2*79))×31.6				
DH3	2402	1.736	277.76	400
	2441	1.721	275.36	400
	2480	1.736	277.76	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(4*79))×31.6				
DH5	2402	3.040	324.27	400
	2441	2.975	317.33	400
	2480	3.062	326.61	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(6*79))×31.6				

The spectrum analyzer plots are attached as below.

GFSK Mode

DH1 Low channel



Date: 20.JUN.2016 15:47:20

DH1 Middle channel



Date: 20.JUN.2016 15:49:50

DH1 High channel



Date: 20.JUN.2016 15:50:48

DH3 Low channel



Date: 20.JUN.2016 15:52:54

DH3 Middle channel



Date: 20.JUN.2016 15:53:38

DH3 High channel



Date: 20.JUN.2016 15:54:25

DH5 Low channel



Date: 20.JUN.2016 15:57:51

DH5 Middle channel



Date: 20.JUN.2016 15:57:03

DH5 High channel



Date: 20.JUN.2016 15:56:09

Π/4-DQPSK

2DH1 Low channel



Date: 20.JUN.2016 16:00:11

2DH1 Middle channel



Date: 20.JUN.2016 16:01:19

2DH1 High channel



Date: 20.JUN.2016 16:01:53

2DH3 Low channel



Date: 20.JUN.2016 16:03:40

2DH3 Middle channel



Date: 20.JUN.2016 16:05:30

2DH3 High channel



Date: 20.JUN.2016 16:06:26

2DH5 Low channel



Date: 20.JUN.2016 16:07:43

2DH5 Middle channel



Date: 20.JUN.2016 16:08:26

2DH5 High channel



Date: 20.JUN.2016 16:09:00

8DPSK Mode

3DH1 Low channel



Date: 20.JUN.2016 16:11:15

3DH1 Middle channel



Date: 20.JUN.2016 16:12:15

3DH1 High channel



Date: 20.JUN.2016 16:12:52

3DH3 Low channel



Date: 20.JUN.2016 16:13:45

3DH3 Middle channel



Date: 20.JUN.2016 16:14:20

3DH3 High channel



Date: 20.JUN.2016 16:15:02

3DH5 Low channel



Date: 20.JUN.2016 16:15:54

3DH5 Middle channel



Date: 20.JUN.2016 16:16:28

3DH5 High channel



Date: 20.JUN.2016 16:17:05

9. MAXIMUM PEAK OUTPUT POWER TEST

9.1.Block Diagram of Test Setup



(EUT: Bluetooth module)

9.2.The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4.Operating Condition of EUT

9.4.1.Setup the EUT and simulator as shown as Section 9.1.

9.4.2.Turn on the power of all equipment.

9.4.3.Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5.Test Procedure

9.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2.Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz for GFSK mode

9.5.3.Set RBW of spectrum analyzer to 3MHz and VBW to 3MHz for other mode

9.5.4.Measurement the maximum peak output power.

9.6.Test Result

GFSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	-1.65/0.0007	30 / 1.0
Middle	2441	-1.32/0.0007	30 / 1.0
High	2480	-1.31/0.0007	30 / 1.0

Π/4-DQPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	0.82/0.0012	21 / 0.125
Middle	2441	1.35/0.0014	21 / 0.125
High	2480	1.37/0.0014	21 / 0.125

8DPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	1.27/0.0013	21 / 0.125
Middle	2441	1.63/0.0015	21 / 0.125
High	2480	1.66/0.0015	21 / 0.125

The spectrum analyzer plots are attached as below.

GFSK Mode

Low channel



Date: 20.JUN.2016 15:55:34

Middle channel



Date: 20.JUN.2016 15:56:04

High channel



Date: 20.JUN.2016 15:56:28

Π/4-DQPSK Mode

Low channel



Date: 20.JUN.2016 15:56:59

Middle channel



Date: 20.JUN.2016 15:57:20

High channel



Date: 20.JUN.2016 15:57:43

8DPSK Mode

Low channel



Date: 20.JUN.2016 15:58:05

Middle channel



Date: 20.JUN.2016 15:58:27

High channel



Date: 20.JUN.2016 15:58:48

10. RADIATED EMISSION TEST

10.1. Block Diagram of Test Setup

10.1.1. Block diagram of connection between the EUT and peripherals



Figure 1 Setup: Transmitting mode

10.1.2. Semi-Anechoic Chamber Test Setup Diagram

Below 1GHz



Above 1GHz



10.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

[1]Until February 1, 1999, this restricted band shall be 0.490-0.510
[2]Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground(Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

10.6.The Field Strength of Radiation Emission Measurement Results

Note: 1.We tested GFSK mode, Π/4-DQPSK Mode & 8QPSK mode and recorded the worst case data (GFSK mode) for all test mode.

2. The test frequency is from 30MHz to 25GHz, The 18-25GHz emissions are not reported, because the levels are too low against the limit.

Below 1GHz

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1421	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016/06/28
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 13:59:46
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report No.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	70.9536	53.69	-22.90	30.79	40.00	-9.21	QP			
2	241.8377	57.46	-18.23	39.23	46.00	-6.77	QP			
3	580.0705	47.29	-10.37	36.92	46.00	-9.08	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1422	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016/06/28
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:00:29
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report No.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	106.6551	55.20	-21.61	33.59	43.50	-9.91	QP			
2	241.8377	55.36	-18.23	37.13	46.00	-8.87	QP			
3	580.0705	45.84	-10.37	35.47	46.00	-10.53	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1424	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016/06/28
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:02:24
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2441MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report No.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	71.2032	53.80	-22.92	30.88	40.00	-9.12	QP			
2	241.8377	57.24	-18.23	39.01	46.00	-6.99	QP			
3	731.4627	43.44	-7.20	36.24	46.00	-9.76	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1423	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016/06/28
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:01:06
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2441MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report No.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	108.1648	54.44	-21.36	33.08	43.50	-10.42	QP			
2	241.8377	55.24	-18.23	37.01	46.00	-8.99	QP			
3	580.0705	45.84	-10.37	35.47	46.00	-10.53	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1425	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016/06/28
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:03:55
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report No.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	71.2032	54.09	-22.92	31.17	40.00	-8.83	QP			
2	241.8377	55.81	-18.23	37.58	46.00	-8.42	QP			
3	580.0705	46.70	-10.37	36.33	46.00	-9.67	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1426	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016/06/28
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14:04:31
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report No.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	106.2811	55.26	-21.68	33.58	43.50	-9.92	QP			
2	241.8377	55.14	-18.23	36.91	46.00	-9.09	QP			
3	580.0705	46.39	-10.37	36.02	46.00	-9.98	QP			

Above 1GHz

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1150	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016-5-24
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 0:56:37
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report NO.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.672	95.56	-7.45	88.11			peak			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1149	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016-5-24
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 0:54:51
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2402MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report NO.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.672	90.68	-7.45	83.23			peak			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1151	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016-5-24
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 0:59:17
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2441MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report NO.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.751	94.31	-7.35	86.96			peak			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1152	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016-5-24
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 1:01:35
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2441MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report NO.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.751	90.31	-7.35	82.96			peak			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1154	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016-5-24
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 1:05:16
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report NO.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.310	95.62	-7.37	88.25			peak			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2015 #1153	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 5V
Test item: Radiation Test	Date: 2016-5-24
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 1:03:25
EUT: Bluetooth module	Engineer Signature:
Mode: TX 2480MHz	Distance: 3m
Model: BT03B110	
Manufacturer: Xiamen Prima Technology Inc	

Note: Report NO.:ATE20161327



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.310	90.43	-7.37	83.06			peak			

11.BAND EDGE COMPLIANCE TEST

11.1.Block Diagram of Test Setup



(EUT: Bluetooth module)

11.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 11.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

11.5.Test Procedure

11.5.1.The transmitter output was connected to the spectrum analyzer via a low loss cable.

11.5.2.Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

11.5.3.The band edges was measured and recorded.

11.6.Test Result

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
GFSK		
2400.00	54.03	> 20dBc
2483.50	54.35	> 20dBc
Π/4-DQPSK Mode		
2400.00	51.62	> 20dBc
2483.50	53.90	> 20dBc
8DPSK		
2400.00	34.13	> 20dBc
2483.50	51.72	> 20dBc

GFSK



Date: 20.JUN.2016 16:00:49



Date: 20.JUN.2016 16:03:40

Π/4-DQPSK Mode



Date: 20.JUN.2016 16:02:07



Date: 20.JUN.2016 16:04:24

8DPSK



Date: 20.JUN.2016 16:02:41



Date: 20.JUN.2016 16:05:03