



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Emotiv Inc.

Model: Emotiv EPOC Model 1.1

Description: EEG Neuroheadset for consumer use - Trademarked as EPOC+

Serial Number: N/A

FCC ID: 2ADIH-EPOC02

To

FCC Part 1.1310

Date of Issue: March 3, 2015

On the behalf of the applicant:

Emotiv Inc.
490 Post Street
Suite 824
San Francisco, CA 94102

Attention of:

Geoffrey Mackellar, CTO
Ph: (415) 828-9895
E-Mail: geoff@emotiv.co

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p14a0008

Alex Macon
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	November 25, 2014	Alex Macon	Original Document



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: Emotiv EPOC Model 1.1

Description: EEG Neuroheadset for consumer use - Trademarked as EPOC+

S/N: N/A

Additional Information: None



MPE Evaluation

This is a portable device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	2402
Power, Radiated, mW (P)	0.0302
Antenna Gain Isotropic	0dBi
Antenna Gain Numeric (G)	1
Antenna Type	integral
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm ²	Power mW (P)	Numeric Gain (G)	Distance (r) cm
0.0000060083	0.0302	1	20

Power Density (S) =0.0000060083
Limit =(from above table) = 1.0

END OF TEST REPORT