

**FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 Issue 4**

TEST REPORT

For

PDA

MODEL NUMBER: N5510L

FCC ID: 2ADINN5510L

IC: 20782-N5510L

REPORT NUMBER: 4791928708-1-RF-4

ISSUE DATE: November 27, 2025

Prepared for

FCC: Sun Cupid Technology (HK) Ltd.

16/F, CEO Tower, 77 Wing Hong Street, Cheung Sha Wan, Kowloon, Hong Kong

IC: Sun Cupid (Shenzhen) Electronic Ltd.

**Baolong Industrial City, Longgang District, Shenzhen Hi-Tech Road, Building 1, A7
Shenzhen N/A China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

**Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	November 27, 2025	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2020, Clause 11.9.1.2	FCC Part 15.247 (b)(3) RSS-247 Clause 6.3.2	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2020, Clause 11.8.1	FCC Part 15.247 (a)(2) RSS-247 Clause 6.3.1 (a) RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2020, Clause 11.10.2	FCC Part 15.247 (e) RSS-247 Clause 6.3.1 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2020, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 6.6	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2020, Clause 11.12	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 6.6 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2020, Clause 11.6	None; for reporting purposes only.	Pass

Note: For ISED, this report is also performed according to ANSI C63.10-2020+Cor.1-2023 standards.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <FCC 47 CFR PART 15 SUBPART C, ISED RSS-247 Issue 4> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY</i>	<i>8</i>
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	<i>9</i>
5.2. <i>CHANNEL LIST</i>	<i>9</i>
5.3. <i>MAXIMUM POWER</i>	<i>10</i>
5.4. <i>TEST CHANNEL CONFIGURATION</i>	<i>10</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	<i>10</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>10</i>
5.7. <i>SETUP DIAGRAM</i>	<i>11</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	12
7. ANTENNA PORT TEST RESULTS	15
7.1. <i>CONDUCTED OUTPUT POWER</i>	<i>15</i>
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i>	<i>16</i>
7.3. <i>POWER SPECTRAL DENSITY</i>	<i>18</i>
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION</i>	<i>20</i>
7.5. <i>DUTY CYCLE</i>	<i>22</i>
8. RADIATED TEST RESULTS	23
8.1. <i>RESTRICTED BANDEDGE</i>	<i>31</i>
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ)</i>	<i>36</i>
8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ)</i>	<i>42</i>
8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i>	<i>54</i>
8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i>	<i>57</i>
8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)</i>	<i>59</i>
9. ANTENNA REQUIREMENT	61
10. AC POWER LINE CONDUCTED EMISSION	62
11. TEST DATA.....	65

11.1.	<i>APPENDIX A: DTS BANDWIDTH</i>	65
11.1.1.	Test Result.....	65
11.1.2.	Test Graphs	66
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i>	68
11.2.1.	Test Result.....	68
11.2.2.	Test Graphs	69
11.3.	<i>APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER</i>	71
11.3.1.	Test Result.....	71
11.4.	<i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY</i>	72
11.4.1.	Test Result.....	72
11.4.2.	Test Graphs	73
11.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS</i>	75
11.5.1.	Test Result.....	75
11.5.2.	Test Graphs	76
11.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i>	78
11.6.1.	Test Result.....	78
11.6.2.	Test Graphs	79
11.7.	<i>APPENDIX G: DUTY CYCLE</i>	85
11.7.1.	Test Result.....	85
11.7.2.	Test Graphs	86

1. ATTESTATION OF TEST RESULTS

Applicant Information

FCC Company Name: Sun Cupid Technology (HK) Ltd.
FCC Address: 16/F, CEO Tower, 77 Wing Hong Street, Cheung Sha Wan,
Kowloon, Hong Kong

IC Company Name: Sun Cupid (Shenzhen) Electronic Ltd.
IC Address: Baolong Industrial City, Longgang District, Shenzhen Hi-Tech
Road, Building 1, A7
Shenzhen N/A China

Manufacturer Information


Company Name: Sun Cupid Technology (HK) Ltd.
Address: 16/F, CEO Tower, 77 Wing Hong Street, Cheung Sha Wan,
Kowloon, Hong Kong

EUT Information

EUT Name: PDA
Model: N5510L
Brand: NUU
Sample Received Date: September 1, 2025
Sample Status: Normal
Sample ID: 8874415
Date of Tested: September 2, 2025 to September 30, 2025


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR PART 15 SUBPART C ISED RSS-247 Issue 4	Pass

Prepared By:



James Qin
Project Engineer

Checked By:



Kebo Zhang
Operations Leader

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard FCC 47 CFR PART 15 SUBPART C ISSED RSS-247 Issue 4, KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, FCC 47 CFR Part 2, ANSI C63.10-2020 and ISSED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch has been assessed and proved to be in compliance with VCCI, the membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	--

Note:

1. All measurement facilities that used to collect the measurement data are located at Room 101, Building 2, No. 4, Information Road, Songshan Lake, Dongguan, Guangdong, China.
2. The anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field site (OFS), the anechoic chamber is proved to be equivalent to the worst case from the open field site (OFS).
3. Radiation measurements below 30 MHz have been performed in anechoic chamber, the measurement result is compared to the result that obtained on an open field site (OFS) and have been correlated to measurements result collected on an open field site (OFS).

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	PDA
Model	N5510L
Series Model	\
Model Difference	\
Battery	Nominal Voltage: DC 3.82 V Rated capacity: 3060 mAh

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Support Standards:	FCC 47 CFR PART 15 SUBPART C, ISM RSS-247 ISSUE 4
Type of Modulation:	GFSK
Data Rates:	1Mbps/2Mbps
Antenna Type:	FPC Antenna
Antenna Gain:	0.9 dBi
Normal Test Voltage:	DC 3.82 V
EUT Test software:	MTK

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2466	/	/

5.3. MAXIMUM POWER

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
LE 1M	2402 ~ 2480	0-39[40]	-2.63	-1.73
LE 2M	2402 ~ 2480	0-39[40]	-2.68	-1.78

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER


The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 0	CH 19	CH 39
GFSK(1Mbps)	3	default	default	default
GFSK(2Mbps)	3	default	default	default

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
3	2402-2480	FPC	0.9

Test Mode	Transmit and Receive Mode	Description
LE 1M	☒ 1TX, 1RX	Antenna 3 can be used as transmitting/receiving antenna.
LE 2M	☒ 1TX, 1RX	Antenna 3 can be used as transmitting/receiving antenna.

5.7. SETUP DIAGRAM



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.27,2024	Dec.26,2025
Vector Signal Generator	R&S	SMBV100A	261637	Sep.28, 2024	Sep.27, 2025
Signal Generator	R&S	SMB100A	178553	Sep.28, 2024	Sep.27, 2025
Signal Analyzer	R&S	FSV40	101118	Sep.28, 2024	Sep.27, 2025
Software					
Description	Manufacturer		Name	Version	
For R&S TS 8997 Test System	Rohde & Schwarz		EMC 32	10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.13, 2024	Sep.12, 2025
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.28, 2024	Sep.27, 2025
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.28, 2024	Sep.27, 2025
DC power supply	Keysight	E3642A	MY55159130	Sep.28, 2024	Sep.27, 2025
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.28, 2024	Sep.27, 2025
Attenuator	Aglient	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.27,2024	Dec.26,2025
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.28, 2024	Sep.27, 2025
Two-Line V-Network	R&S	ENV216	101983	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.28, 2024	Sep.27, 2025
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.28, 2024	Sep.27, 2025
EMI Measurement Receiver	R&S	ESR26	101377	Sep.28, 2024	Sep.27, 2025
Horn Antenna	TDK	HRN-0118	130940	Dec.10, 2024	Dec.11, 2027
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.28, 2024	Sep.27, 2025
Horn Antenna	Schwarzbeck	BBHA9170	697	Jun 30, 2024	Jun 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep.28, 2024	Sep.27, 2025
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.28, 2024	Sep.27, 2025
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Sep.28, 2024	Sep.27, 2025
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Sep.28, 2024	Sep.27, 2025
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.8, 2024	Oct.7, 2025
Barometer	Yiyi	Baro	N/A	Oct.10, 2024	Oct.9, 2025
Attenuator	Agilent	8495B	2814a12853	Sep.28, 2024	Sep.27, 2025

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS


FCC 47 CFR Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(b)(3) ISED RSS-247 6.3.2	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.9°C	Relative Humidity	61.7%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.82V

TEST DATE / ENGINEER

Test Date	September 11, 2025	Test By	Bairong Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(a)(2) ISED RSS-247 6.3.1(a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 1 % to 5 % of the OBW but not less than 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP**TEST ENVIRONMENT**

Temperature	23.9℃	Relative Humidity	61.7%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.82V

TEST DATE / ENGINEER

Test Date	September 11, 2025	Test By	Bairong Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. POWER SPECTRAL DENSITY

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR §15.247 (e) ISED RSS-247 6.3.1 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.10.2.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$> 1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.9°C	Relative Humidity	61.7%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.82V

TEST DATE / ENGINEER

Test Date	September 11, 2025	Test By	Bairong Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4		
Section	Test Item	Limit
FCC 47 CFR §15.247 (d) ISED RSS-247 6.6	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.11.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	$\geq 1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span/RBW}$
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP**TEST ENVIRONMENT**

Temperature	23.9℃	Relative Humidity	61.7%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.82V

TEST DATE / ENGINEER

Test Date	September 11, 2025	Test By	Bairong Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix E&F

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.9°C	Relative Humidity	61.7%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.82V

TEST DATE / ENGINEER

Test Date	September 11, 2025	Test By	Bairong Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix G

8. RADIATED TEST RESULTS

LIMITS

Please refer to FCC 47 CFR §15.205 and §15.209.

Please refer to ISSED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz



TEST ENVIRONMENT

Temperature	22.9 °C	Relative Humidity	58 %
Atmosphere Pressure	101kPa	Test Voltage	DC 3.82 V


TEST DATE / ENGINEER

Test Date	September 23, 2025	Test By	Leslie Xie
-----------	--------------------	---------	------------

TEST RESULTS

8.1. RESTRICTED BANDEDGE


TX Radiated Test Result



PEAK Data List									
NO	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2388.44	40.74	49.65	8.91	74.00	24.35	PK	Horizontal	PASS
2	2390.00	39.29	48.23	8.94	74.00	25.77	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2389.89	41.02	49.95	8.93	74.00	24.05	PK	Vertical	PASS
2	2390.00	39.96	48.90	8.94	74.00	25.10	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List


NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2483.50	42.98	53.26	10.28	74.00	20.74	PK	Horizontal	PASS
2	2486.46	46.02	56.34	10.32	74.00	17.66	PK	Horizontal	PASS

AVG Data List

NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	2483.51	10.28	29.13	39.41	54.00	14.59	Horizontal	PASS
2	2486.47	10.32	29.68	40.00	54.00	14.00	Horizontal	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2373.48	41.30	50.00	8.70	74.00	24.00	PK	Horizontal	PASS
2	2390.00	39.08	48.02	8.94	74.00	25.98	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List

NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	2483.50	39.12	49.40	10.28	74.00	24.60	PK	Horizontal	PASS
2	2486.57	45.11	55.43	10.32	74.00	18.57	PK	Horizontal	PASS

AVG Data List


NO.	Frequency [MHz]	Factor [dB/m]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Polarity	Verdict
1	2483.50	10.28	29.10	39.38	54.00	14.62	Horizontal	PASS
2	2486.56	10.32	29.74	40.06	54.00	13.94	Horizontal	PASS

Note: (1) Level = Reading + Factor

(2) Margin = Limit - Level

8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1078.08	50.07	39.47	-10.60	74.00	34.53	PK	Horizontal	PASS
2	1608.61	48.72	38.87	-9.85	74.00	35.13	PK	Horizontal	PASS
3	1964.96	48.79	42.46	-6.33	74.00	31.54	PK	Horizontal	PASS
4	2401.40	53.99	49.15	-4.84	74.00	24.85	PK	Horizontal	PASS
5	2557.56	50.44	45.78	-4.66	74.00	28.22	PK	Horizontal	PASS
6	2959.96	48.59	45.52	-3.07	74.00	28.48	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1200.20	50.13	39.90	-10.23	74.00	34.10	PK	Vertical	PASS
2	1668.67	50.92	41.57	-9.35	74.00	32.43	PK	Vertical	PASS
3	2189.19	49.12	44.20	-4.92	74.00	29.80	PK	Vertical	PASS
4	2401.40	50.74	45.90	-4.84	74.00	28.10	PK	Vertical	PASS
5	2575.58	50.37	45.75	-4.62	74.00	28.25	PK	Vertical	PASS
6	2809.81	47.85	44.17	-3.68	74.00	29.83	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1202.20	50.00	39.76	-10.24	74.00	34.24	PK	Horizontal	PASS
2	1788.79	48.22	39.64	-8.58	74.00	34.36	PK	Horizontal	PASS
3	2029.03	49.01	43.14	-5.87	74.00	30.86	PK	Horizontal	PASS
4	2429.43	49.78	44.96	-4.82	74.00	29.04	PK	Horizontal	PASS
5	2625.63	49.07	44.52	-4.55	74.00	29.48	PK	Horizontal	PASS
6	2955.96	48.00	44.90	-3.10	74.00	29.10	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1172.17	49.68	39.33	-10.35	74.00	34.67	PK	Vertical	PASS
2	1554.55	50.29	40.12	-10.17	74.00	33.88	PK	Vertical	PASS
3	2035.04	48.26	42.38	-5.88	74.00	31.62	PK	Vertical	PASS
4	2521.52	50.78	46.04	-4.74	74.00	27.96	PK	Vertical	PASS
5	2789.79	47.84	44.07	-3.77	74.00	29.93	PK	Vertical	PASS
6	2967.97	47.46	44.45	-3.01	74.00	29.55	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1310.31	49.78	39.12	-10.66	74.00	34.88	PK	Horizontal	PASS
2	1806.81	48.24	39.80	-8.44	74.00	34.20	PK	Horizontal	PASS
3	2025.03	48.56	42.69	-5.87	74.00	31.31	PK	Horizontal	PASS
4	2333.33	49.04	44.17	-4.87	74.00	29.83	PK	Horizontal	PASS
5	2597.60	49.90	45.32	-4.58	74.00	28.68	PK	Horizontal	PASS
6	2945.95	47.82	44.63	-3.19	74.00	29.37	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	1308.31	51.41	40.76	-10.65	74.00	33.24	PK	Vertical	PASS
2	1668.67	49.56	40.21	-9.35	74.00	33.79	PK	Vertical	PASS
3	2179.18	48.54	43.51	-5.03	74.00	30.49	PK	Vertical	PASS
4	2401.40	49.55	44.71	-4.84	74.00	29.29	PK	Vertical	PASS
5	2541.54	50.04	45.34	-4.70	74.00	28.66	PK	Vertical	PASS
6	2789.79	47.86	44.09	-3.77	74.00	29.91	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

TX Radiated Test Result




PEAK Data List

NO	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4223.11	45.61	46.00	0.39	74.00	28.00	PK	Horizontal	PASS
2	7014.51	41.63	46.89	5.26	74.00	27.11	PK	Horizontal	PASS
3	10541.27	40.30	48.38	8.08	74.00	25.62	PK	Horizontal	PASS
4	13107.55	36.59	48.26	11.67	74.00	25.74	PK	Horizontal	PASS
5	15013.51	35.27	48.92	13.65	74.00	25.08	PK	Horizontal	PASS
6	17924.96	30.75	49.17	18.42	74.00	24.83	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4530.77	46.42	45.79	-0.63	74.00	28.21	PK	Vertical	PASS
2	7134.57	41.66	46.35	4.69	74.00	27.65	PK	Vertical	PASS
3	9573.29	39.62	46.63	7.01	74.00	27.37	PK	Vertical	PASS
4	10481.24	41.47	49.55	8.08	74.00	24.45	PK	Vertical	PASS
5	15013.51	36.24	49.89	13.65	74.00	24.11	PK	Vertical	PASS
6	17827.41	30.96	49.36	18.40	74.00	24.64	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4200.60	45.59	46.10	0.51	74.00	27.90	PK	Horizontal	PASS
2	5881.44	44.29	46.70	2.41	74.00	27.30	PK	Horizontal	PASS
3	10166.08	40.74	48.10	7.36	74.00	25.90	PK	Horizontal	PASS
4	12259.63	38.19	48.63	10.44	74.00	25.37	PK	Horizontal	PASS
5	15366.18	34.62	49.18	14.56	74.00	24.82	PK	Horizontal	PASS
6	17894.95	30.83	49.24	18.41	74.00	24.76	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level

TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4658.33	45.96	45.79	-0.17	74.00	28.21	PK	Vertical	PASS
2	7854.93	41.67	47.14	5.47	74.00	26.86	PK	Vertical	PASS
3	10571.29	40.49	48.58	8.09	74.00	25.42	PK	Vertical	PASS
4	13190.10	37.28	48.82	11.54	74.00	25.18	PK	Vertical	PASS
5	15013.51	35.29	48.94	13.65	74.00	25.06	PK	Vertical	PASS
6	17834.92	31.20	49.60	18.40	74.00	24.40	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4230.62	45.55	45.90	0.35	74.00	28.10	PK	Horizontal	PASS
2	6714.36	42.62	46.98	4.36	74.00	27.02	PK	Horizontal	PASS
3	9505.75	39.92	47.36	7.44	74.00	26.64	PK	Horizontal	PASS
4	13055.03	36.93	48.69	11.76	74.00	25.31	PK	Horizontal	PASS
5	15373.69	34.11	48.70	14.59	74.00	25.30	PK	Horizontal	PASS
6	17437.22	31.55	49.26	17.71	74.00	24.74	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4193.10	46.87	47.24	0.37	74.00	26.76	PK	Vertical	PASS
2	7014.51	41.79	47.05	5.26	74.00	26.95	PK	Vertical	PASS
3	10548.77	39.56	47.65	8.09	74.00	26.35	PK	Vertical	PASS
4	11659.33	38.73	48.72	9.99	74.00	25.28	PK	Vertical	PASS
5	13445.22	37.26	48.85	11.59	74.00	25.15	PK	Vertical	PASS
6	17422.21	30.58	48.31	17.73	74.00	25.69	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4230.62	46.36	46.71	0.35	74.00	27.29	PK	Horizontal	PASS
2	6804.40	43.29	47.18	3.89	74.00	26.82	PK	Horizontal	PASS
3	10466.23	39.18	47.25	8.07	74.00	26.75	PK	Horizontal	PASS
4	13265.13	37.52	49.09	11.57	74.00	24.91	PK	Horizontal	PASS
5	15351.18	33.95	48.44	14.49	74.00	25.56	PK	Horizontal	PASS
6	17617.31	31.49	48.80	17.31	74.00	25.20	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4230.62	45.67	46.02	0.35	74.00	27.98	PK	Vertical	PASS
2	7944.97	41.12	47.06	5.94	74.00	26.94	PK	Vertical	PASS
3	10413.71	39.68	47.72	8.04	74.00	26.28	PK	Vertical	PASS
4	12372.19	38.38	48.86	10.48	74.00	25.14	PK	Vertical	PASS
5	15373.69	34.56	49.15	14.59	74.00	24.85	PK	Vertical	PASS
6	17902.45	31.49	49.91	18.42	74.00	24.09	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5371.19	45.43	46.27	0.84	74.00	27.73	PK	Horizontal	PASS
2	6286.64	43.74	47.61	3.87	74.00	26.39	PK	Horizontal	PASS
3	10518.76	41.95	50.03	8.08	74.00	23.97	PK	Horizontal	PASS
4	13100.05	36.99	48.67	11.68	74.00	25.33	PK	Horizontal	PASS
5	15358.68	34.35	48.88	14.53	74.00	25.12	PK	Horizontal	PASS
6	17939.97	30.07	48.50	18.43	74.00	25.50	PK	Horizontal	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	4230.62	46.01	46.36	0.35	74.00	27.64	PK	Vertical	PASS
2	7007.00	41.38	46.68	5.30	74.00	27.32	PK	Vertical	PASS
3	10773.89	39.50	47.85	8.35	74.00	26.15	PK	Vertical	PASS
4	14210.61	35.84	48.58	12.74	74.00	25.42	PK	Vertical	PASS
5	15793.90	32.95	47.95	15.00	74.00	26.05	PK	Vertical	PASS
6	17894.95	30.27	48.68	18.41	74.00	25.32	PK	Vertical	PASS

Note: (1) Level = Reading + Factor
 (2) Margin = Limit - Level


TX Radiated Test Result



PEAK Data List									
NO	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	3900.45	48.83	47.59	-1.24	74.00	26.41	PK	Horizontal	PASS
2	6286.64	42.70	46.57	3.87	74.00	27.43	PK	Horizontal	PASS
3	9753.38	40.72	47.75	7.03	74.00	26.25	PK	Horizontal	PASS
4	13190.10	36.74	48.28	11.54	74.00	25.72	PK	Horizontal	PASS
5	15321.16	34.35	48.68	14.33	74.00	25.32	PK	Horizontal	PASS
6	17444.72	30.31	48.00	17.69	74.00	26.00	PK	Horizontal	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

TX Radiated Test Result




PEAK Data List									
NO.	Frequency [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Verdict
1	5303.65	47.09	47.81	0.72	74.00	26.19	PK	Vertical	PASS
2	7464.73	41.77	46.40	4.63	74.00	27.60	PK	Vertical	PASS
3	10541.27	40.97	49.05	8.08	74.00	24.95	PK	Vertical	PASS
4	13265.13	36.67	48.24	11.57	74.00	25.76	PK	Vertical	PASS
5	14930.97	35.32	49.01	13.69	74.00	24.99	PK	Vertical	PASS
6	17399.70	31.10	48.87	17.77	74.00	25.13	PK	Vertical	PASS

Note:(1)Level=Reading+Factor
 (2)Margin=Limit-Level


8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.82 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0094	76.16	-101.35	-25.19	48.05	-76.69	-3.45	-73.24	peak
2	0.0165	71.84	-101.37	-29.53	43.25	-81.03	-8.25	-72.78	peak
3	0.0269	69.35	-101.38	-32.03	39.01	-83.53	-12.49	-71.04	peak
4	0.0417	64.58	-101.44	-36.86	35.20	-88.36	-16.30	-72.06	peak
5	0.0674	62.78	-101.56	-38.78	31.03	-90.28	-20.47	-69.81	peak
6	0.1073	59.30	-101.77	-42.47	26.99	-93.97	-24.51	-69.46	peak

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.82 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1617	77.09	-101.65	-24.56	23.43	-76.06	-28.07	-47.99	peak
2	0.1827	74.67	-101.69	-27.02	22.37	-78.52	-29.13	-49.39	peak
3	0.2346	70.35	-101.77	-31.42	20.19	-82.92	-31.31	-51.61	peak
4	0.2983	67.18	-101.85	-34.67	18.11	-86.17	-33.39	-52.78	peak
5	0.3659	64.71	-101.93	-37.22	16.33	-88.72	-35.17	-53.55	peak
6	0.4349	62.10	-101.99	-39.89	14.83	-91.39	-36.67	-54.72	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.82 V



No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.7861	64.33	-62.14	2.19	29.69	-49.31	-21.81	-27.50	peak
2	1.7036	59.94	-61.96	-2.02	22.98	-53.52	-28.52	-25.00	peak
3	2.7136	58.69	-61.65	-2.96	29.54	-54.46	-21.96	-32.50	peak
4	5.4477	57.91	-61.42	-3.51	29.54	-55.01	-21.96	-33.05	peak
5	12.6775	57.46	-60.92	-3.46	29.54	-54.96	-21.96	-33.00	peak
6	20.6748	57.31	-60.79	-3.48	29.54	-54.98	-21.96	-33.02	peak


8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.82 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18752.000	49.70	-5.42	44.28	74.00	-29.72	peak
2	19504.000	49.97	-5.54	44.43	74.00	-29.57	peak
3	21248.000	50.29	-4.77	45.52	74.00	-28.48	peak
4	23768.000	49.06	-3.16	45.90	74.00	-28.10	peak
5	25072.000	48.17	-1.97	46.20	74.00	-27.80	peak
6	25736.000	47.49	-0.68	46.81	74.00	-27.19	peak


Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.82 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18328.000	50.49	-5.46	45.03	74.00	-28.97	peak
2	19712.000	50.51	-5.29	45.22	74.00	-28.78	peak
3	20472.000	50.57	-5.39	45.18	74.00	-28.82	peak
4	21432.000	49.74	-4.71	45.03	74.00	-28.97	peak
5	22696.000	49.30	-3.73	45.57	74.00	-28.43	peak
6	24584.000	48.87	-2.31	46.56	74.00	-27.44	peak


8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.82 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	59.1000	29.41	-14.93	14.48	40.00	-25.52	peak
2	136.7000	26.26	-14.11	12.15	43.50	-31.35	peak
3	284.1400	33.44	-12.49	20.95	46.00	-25.05	peak
4	523.7300	24.26	-7.38	16.88	46.00	-29.12	peak
5	739.0700	24.58	-3.69	20.89	46.00	-25.11	peak
6	947.6200	27.23	-0.81	26.42	46.00	-19.58	peak

Test Mode:	BLE 1M	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.82 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.7000	41.79	-14.74	27.05	40.00	-12.95	peak
2	78.5000	36.98	-15.91	21.07	40.00	-18.93	peak
3	114.3900	36.12	-15.11	21.01	43.50	-22.49	peak
4	263.7700	30.47	-13.73	16.74	46.00	-29.26	peak
5	635.2800	24.40	-5.63	18.77	46.00	-27.23	peak
6	913.6700	28.15	-0.54	27.61	46.00	-18.39	peak

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to FCC 47 CFR §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2020. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	23.5°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V_60Hz

TEST DATE / ENGINEER

Test Date	September 16, 2025	Test By	Deacon Tan
-----------	--------------------	---------	------------

TEST RESULTS

Test Mode:	GFSK	Frequency(MHz):	2402
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1504	20.25	9.74	29.99	65.98	-35.99	QP
2	0.1504	7.17	9.74	16.91	55.98	-39.07	AVG
3	0.3970	21.70	9.64	31.34	57.92	-26.58	QP
4	0.3970	11.04	9.64	20.68	47.92	-27.24	AVG
5	0.5557	29.27	9.64	38.91	56.00	-17.09	QP
6	0.5557	13.09	9.64	22.73	46.00	-23.27	AVG
7	1.0739	21.63	9.64	31.27	56.00	-24.73	QP
8	1.0739	10.65	9.64	20.29	46.00	-25.71	AVG
9	3.0722	18.06	9.73	27.79	56.00	-28.21	QP
10	3.0722	10.20	9.73	19.93	46.00	-26.07	AVG
11	17.4075	20.86	9.74	30.60	60.00	-29.40	QP
12	17.4075	8.99	9.74	18.73	50.00	-31.27	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	GFSK	Frequency(MHz):	2402
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1707	23.44	9.64	33.08	64.93	-31.85	QP
2	0.1707	10.41	9.64	20.05	54.93	-34.88	AVG
3	0.4953	28.40	9.64	38.04	56.08	-18.04	QP
4	0.4953	15.76	9.64	25.40	46.08	-20.68	AVG
5	0.5627	26.97	9.64	36.61	56.00	-19.39	QP
6	0.5627	17.80	9.64	27.44	46.00	-18.56	AVG
7	0.9020	20.86	9.63	30.49	56.00	-25.51	QP
8	0.9020	10.32	9.63	19.95	46.00	-26.05	AVG
9	2.0684	13.93	9.64	23.57	56.00	-32.43	QP
10	2.0684	6.57	9.64	16.21	46.00	-29.79	AVG
11	17.1112	18.80	9.74	28.54	60.00	-31.46	QP
12	17.1112	6.02	9.74	15.76	50.00	-34.24	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.


11. TEST DATA


11.1. APPENDIX A: DTS BANDWIDTH

11.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.68	2401.66	2402.34	≥ 0.5	PASS
		2440	0.68	2439.66	2440.34	≥ 0.5	PASS
		2480	0.68	2479.66	2480.34	≥ 0.5	PASS
BLE_2M	Ant1	2404	1.16	2403.42	2404.58	≥ 0.5	PASS
		2440	1.16	2439.43	2440.58	≥ 0.5	PASS
		2478	1.16	2477.42	2478.58	≥ 0.5	PASS

11.1.2. Test Graphs






BLE_2M_Ant1_2404



BLE_2M_Ant1_2440




BLE_2M_Ant1_2478


11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

11.2.1. Test Result


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
BLE_1M	Ant1	2402	1.047	2401.4845	2402.5315	PASS
		2440	1.047	2439.4845	2440.5315	PASS
		2480	1.047	2479.4845	2480.5315	PASS
BLE_2M	Ant1	2404	2.074	2402.9770	2405.0509	PASS
		2440	2.074	2438.9770	2441.0509	PASS
		2478	2.074	2476.9730	2479.0470	PASS

11.2.2. Test Graphs






BLE_2M_Ant1_2404



BLE_2M_Ant1_2440



BLE_2M_Ant1_2478

11.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER

11.3.1. Test Result


Test Mode	Antenna	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-3.89	≤30	PASS
		2440	-2.63	≤30	PASS
		2480	-3.58	≤30	PASS
BLE_2M	Ant1	2404	-3.84	≤30	PASS
		2440	-2.68	≤30	PASS
		2478	-3.42	≤30	PASS


11.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY

11.4.1. Test Result


Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-19.25	≤8.00	PASS
		2440	-18.02	≤8.00	PASS
		2480	-19.13	≤8.00	PASS
BLE_2M	Ant1	2404	-22.87	≤8.00	PASS
		2440	-21.63	≤8.00	PASS
		2478	-22.56	≤8.00	PASS

11.4.2. Test Graphs






BLE_2M_Ant1_2404



BLE_2M_Ant1_2440




BLE_2M_Ant1_2478


11.5. APPENDIX E: BAND EDGE MEASUREMENTS

11.5.1. Test Result

Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-4.81	-46.03	≤ -24.81	PASS
		High	2480	-4.64	-45.45	≤ -24.64	PASS
BLE_2M	Ant1	Low	2404	-5.76	-46.77	≤ -25.76	PASS
		High	2478	-4.56	-44.7	≤ -24.56	PASS

11.5.2. Test Graphs







11.6. APPENDIX F: CONDUCTED SPURIOUS EMISSION


11.6.1. Test Result


Test Mode	Antenna	Frequency[MHz]	FreqRange [MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-4.70	---	PASS
			30~1000	-45.41	≤ -24.7	PASS
			1000~26500	-39.68	≤ -24.7	PASS
		2440	Reference	-3.49	---	PASS
			30~1000	-45.72	≤ -23.49	PASS
			1000~26500	-39.75	≤ -23.49	PASS
		2480	Reference	-4.60	---	PASS
			30~1000	-45.02	≤ -24.6	PASS
			1000~26500	-38.98	≤ -24.6	PASS
BLE_2M	Ant1	2404	Reference	-4.69	---	PASS
			30~1000	-45.38	≤ -24.69	PASS
			1000~26500	-39.04	≤ -24.69	PASS
		2440	Reference	-3.52	---	PASS
			30~1000	-45.01	≤ -23.52	PASS
			1000~26500	-39.32	≤ -23.52	PASS
		2478	Reference	-4.44	---	PASS
			30~1000	-45.11	≤ -24.44	PASS
			1000~26500	-39.87	≤ -24.44	PASS

11.6.2. Test Graphs












BLE_2M_Ant1_2404_0~Reference




BLE_2M_Ant1_2404_30~1000




BLE_2M_Ant1_2404_1000~26500






BLE_2M_Ant1_2478_0~Reference



BLE_2M_Ant1_2478_30~1000



BLE_2M_Ant1_2478_1000~26500

11.7. APPENDIX G: DUTY CYCLE

11.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
BLE_1M	0.39	0.63	0.6190	61.90	2.08	2.56	3
BLE_2M	1.06	1.86	0.5699	56.99	2.44	0.94	1

Note:


Duty Cycle Correction Factor= $10\log(1/x)$.

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

11.7.2. Test Graphs



END OF REPORT