



FCC RADIO TEST REPORT

FCC ID: 2ADJW-FI-3A2W

Product : Fault Indicator

Trade Name : N/A

Model Name : FI-3A2W

Serial Model : N/A

Report No. : NTEK-2014NT0918442F

Prepared for

Creative Distribution Automation Co., Ltd.
The 4th floor, Building No.3, No.8 Chuangye Road, Shangdi, Haidian,
Beijing, 100085 China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name : Creative Distribution Automation Co., Ltd.
Address : The 4th floor, Building No.3, No.8 Chuangye Road, Shangdi
Haidian, Beijing, 100085 China
Manufacture's Name : Creative Distribution Automation Co., Ltd.
Address : The 4th floor, Building No.3, No.8 Chuangye Road, Shangdi
Haidian, Beijing, 100085 China

Product description

Product name : Fault Indicator
Model and/or type reference : FI-3A2W
Serial Model : N/A
Rating(s) : DC 7.2V

Standards : FCC Part15.249: 01 Oct. 2013

Test procedure ANSI C63.4-2003

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.


Date of Test

Date (s) of performance of tests : 18 Sep. 2014 ~22 Oct. 2014

Date of Issue : 22 Oct. 2014


Test Result : **Pass**

Testing Engineer :



Denny Huang

Technical Manager :



(Brown Lu)

Authorized Signatory :



(Bill Yao)

Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . ANTENNA REQUIREMENT	12
3.1 STANDARD REQUIREMENT	12
3.2 EUT ANTENNA	12
3.3 CONDUCTED EMISSION MEASUREMENT	13
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.3.2 TEST PROCEDURE	14
3.3.3 DEVIATION FROM TEST STANDARD	14
3.3.4 TEST SETUP	14
3.2.5 TEST RESULT	15
3.4 RADIATED EMISSION MEASUREMENT	16
3.4.1 RADIATED EMISSION LIMITS	16
3.4.2 TEST PROCEDURE	17
3.4.3 DEVIATION FROM TEST STANDARD	17
3.4.4 TEST SETUP	18
3.4.5 TEST RESULTS (BLOW 30MHZ)	20
3.4.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)	21
3.4.7 TEST RESULTS (ABOVE 1000 MHZ)	23
3.4.8 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	26
4 . BANDWIDTH TEST	30
4.1 TEST PROCEDURE	30
4.2 DEVIATION FROM STANDARD	30
4.3 TEST SETUP	30
4.4 TEST RESULTS	31
5 . EUT TEST PHOTO	33
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.249)			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.203	Antenna Requirement	Pass	
15.249	Radiated Spurious Emission	Pass	
15.205	Band Edge Emission	Pass	
15.249	Occupied Bandwidth	Pass	

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC FRN Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Fault Indicator
Trade Name	N/A
Model Name	FI-3A2W
Serial Model	N/A
Model Difference	N/A
Product Description	The EUT is a Fault Indicator
	Operation Frequency: 2403.375MHz-2479.750MHz
	Modulation Type: 2-FSK
	Antenna Designation: Ceramic chip Antenna
	Antenna Gain(Peak) 1.5 dBi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.
Channel List	Please refer to the Note 2.
Adapter	N/A
Battery	DC 3.6V*2 cell "AA" alkaline battery

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2403.375	16	2429.375	31	2455.375
02	2405.500	17	2431.000	32	2457.000
03	2406.625	18	2432.625	33	2458.625
04	2408.250	19	2434.250	34	2460.250
05	2409.875	20	2435.875	35	2461.875
06	2411.500	21	2437.500	36	2463.500
07	2413.125	22	2439.125	37	2465.125
08	2414.750	23	2440.750	38	2466.750
09	2416.375	24	2442.375	39	2468.375
10	2419.625	25	2445.625	40	2471.625
11	2421.250	26	2447.250	41	2473.250
12	2422.875	27	2448.875	42	2474.875
13	2424.500	28	2450.500	43	2476.500
14	2426.125	29	2452.125	44	2478.125
15	2427.750	30	2453.750	45	2479.750

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Ceramic chip Antenna	N/A	1.5	Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Link Mode
Mode 2	TX CH 01
Mode 3	TX CH 23
Mode 4	TX CH 45


For Radiated Emission	
Final Test Mode	Description
Mode 1	Link Mode
Mode 2	TX CH 01
Mode 3	TX CH 23
Mode 4	TX CH 45

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Fault Indicator	N/A	FI-3A2W	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	E4407B	160400005	Jul. 06. 2015
2	Test Receiver	R&S	ESPI	101318	Jul. 06. 2015
3	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06. 2015
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	Jul. 06. 2015
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	Jul. 06. 2015
6	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06. 2015
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	Jul. 06. 2015
8	Amplifier	EM	EM-30180	060538	Jul. 06. 2015
9	Loop Antenna	ARA	PLA-1030/B	1029	Jul. 06. 2015
10	Power Meter	R&S	NRVS	100696	Jul. 06. 2015

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Test Receiver	R&S	ESCI	101160	Jul. 06. 2015
2	LISN	R&S	ENV216	101313	Jul. 06. 2015
3	LISN	EMCO	3816/2	00042990	Jul. 06. 2015
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	Jul. 06. 2015
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	Jul. 06. 2015
6	Absorbing clamp	R&S	MOS-21	100423	Jul. 06. 2015

3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is Ceramic chip Antenna. It comply with the standard requirement.

3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR
0.50 -5.0			56.00	46.00	CISPR
5.0 -30.0			60.00	50.00	CISPR

0.15 -0.5			66 - 56 *	56 - 46 *	LP002.
0.50 -5.0			56.00	46.00	LP002.
5.0 -30.0			60.00	50.00	LP002.

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.3.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.2.5 TEST RESULT

EUT :	Fault Indicator	Model Name. :	FI-3A2W
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N/A
Test Voltage :	N/A	Test Mode :	N/A

3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
Frequency (MHz)	Limit (dBuV)	
30~88	40	3
88~216	43.5	3
216~960	46	3
960 -10000	54.00	3
*902 - 928	94.00	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).
- (3) *Note: This is the limit for the fundamental frequency.

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.249)

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Peak	1 MHz	10 Hz

3.4.3 DEVIATION FROM TEST STANDARD


No deviation

3.4.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.4.5 TEST RESULTS (BLOW 30MHz)

EUT :	Fault Indicator	Model Name. :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	--
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.4.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)

EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
31.1798	6.59	18.78	25.37	40.00	-14.63	QP
64.6594	10.34	6.78	17.12	40.00	-22.88	QP
128.5629	9.39	11.92	21.31	43.50	-22.19	QP
185.1379	7.99	10.67	18.66	43.50	-24.84	QP
323.3204	15.15	15.12	30.27	46.00	-15.73	QP
903.3093	8.17	27.03	35.20	46.00	-10.80	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
30.8535	6.22	18.97	25.19	40.00	-14.81	QP
47.6584	6.07	11.27	17.34	40.00	-22.66	QP
138.3873	7.51	11.48	18.99	43.50	-24.51	QP
410.3824	7.53	18.52	26.05	46.00	-19.95	QP
533.8318	5.70	21.00	26.70	46.00	-19.30	QP
801.7862	7.23	27.40	34.63	46.00	-11.37	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



3.4.7 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2403.375MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2403.562	101.51	-7.74	93.77	114.00	-20.23	peak
2403.562	91.58	-7.74	83.84	94.00	-10.16	AVG
4806.921	54.95	1.79	56.74	74.00	-17.26	peak
4806.921	44.35	1.79	46.14	54.00	-7.86	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2403.375MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2403.458	101.34	-7.74	93.60	114.00	-20.40	peak
2403.458	91.97	-7.74	84.23	94.00	-9.77	AVG
4806.894	54.33	1.79	56.12	74.00	-17.88	peak
4806.894	44.76	1.79	46.55	54.00	-7.45	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2440.750MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2440.728	103.52	-7.68	95.84	114.00	-18.16	peak
2440.728	93.04	-7.68	85.36	94.00	-8.64	AVG
4881.632	54.76	1.82	56.58	74.00	-17.42	peak
4881.632	44.06	1.82	45.88	54.00	-8.12	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2440.750MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2440.728	102.40	-7.68	94.72	114.00	-19.28	peak
2440.728	92.84	-7.68	85.16	94.00	-8.86	AVG
4881.633	55.27	1.82	57.09	74.00	-16.91	peak
4881.633	45.03	1.82	46.85	54.00	-7.15	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2479.750MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2479.912	101.65	-7.54	94.11	114.00	-19.89	peak
2479.912	92.57	-7.54	85.03	94.00	-8.97	AVG
4959.623	55.82	2.00	57.82	74.00	-16.18	peak
4959.623	44.85	2.00	46.85	54.00	-7.15	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2479.750MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2479.821	101.26	-7.54	93.72	114.00	-20.28	peak
2479.821	91.79	-7.54	84.25	94.00	-9.75	AVG
4959.633	54.40	2.00	56.40	74.00	-17.60	peak
4959.633	43.98	2.00	45.98	54.00	-8.02	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.


3.4.8 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2403.375MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2337.830	48.32	-8.01	40.31	74.00	-33.69	peak
2337.830	38.23	-8.01	30.22	54.00	-23.78	AVG
2400.000	65.65	-7.74	57.91	74.00	-16.09	peak
2400.000	55.76	-7.74	48.02	54.00	-5.98	AVG
2403.940	96.99	-7.74	89.25	114.00	-24.75	peak
2403.940	87.07	-7.74	79.33	94.00	-14.67	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2403.375MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2388.760	49.99	-7.83	42.16	74.00	-31.84	peak
2388.760	40.28	-7.83	32.45	54.00	-21.55	AVG
2400.000	66.33	-7.74	58.59	74.00	-15.41	peak
2400.000	56.69	-7.74	48.95	54.00	-5.05	AVG
2403.940	95.89	-7.74	88.15	114.00	-28.85	peak
2403.940	86.26	-7.74	78.52	94.00	-15.48	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2479.750MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480.140	101.24	-7.54	93.70	114.00	-20.30	peak
2480.140	91.45	-7.54	83.91	94.00	-10.09	AVG
2483.500	66.00	-7.53	58.47	74.00	-15.53	peak
2483.500	56.12	-7.53	48.59	54.00	-5.41	AVG
2489.620	51.49	-7.5	43.99	74.00	-30.01	peak
2489.620	41.42	-7.5	33.92	54.00	-20.08	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 7.2V
Test Mode :	TX-2479.750MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2480.14	100.84	-7.54	93.30	114.00	-20.70	peak
2480.14	90.92	-7.54	83.38	94.00	-10.62	AVG
2483.50	68.20	-7.53	60.67	74.00	-13.33	peak
2483.50	58.48	-7.53	50.95	54.00	-3.05	AVG
2489.62	46.70	-7.50	39.20	74.00	-34.80	peak
2489.62	36.89	-7.50	29.39	54.00	-24.61	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



4. BANDWIDTH TEST

4.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW $\geq$ RBW, Sweep time = Auto.

4.2 DEVIATION FROM STANDARD

No deviation.

4.3 TEST SETUP




4.4 TEST RESULTS


EUT :	Fault Indicator	Model Name :	FI-3A2W
Temperature :	26 °C	Relative Humidity :	53%
Pressure :	1020 hPa	Test Power :	DC 7.2V
Test Mode :	TX		

Frequency (MHz)	20 dBc Bandwidth (MHz)	99% Bandwidth (MHz)
2403.375	0.494	0.526
2440.750	0.659	0.669
2479.750	0.562	0.558


The Lowest Channel:2403.375MHz



The Middle Channel: 2440.750MHz



The HIGH Channel: 2479.750MHz



5. EUT TEST PHOTO

Radiated Measurement Photos

