



Test report No. : 10532071S
Page : 1 of 19
Issued date : December 3, 2014
Revised date : December 18, 2014
FCC ID : 2ADKKDSF214

RADIO TEST REPORT

Test Report No. : 10532071S

Applicant : Ueda Japan Radio Co., Ltd.
Type of Equipment : Secure Tag
Model No. : DSF-214P
FCC ID : 2ADKKDSF214
Test regulation : FCC Part15 Subpart C: 2014
Test result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test:

November 6 to 7, 2014

Representative test engineer:

Akio Hayashi
Engineer
Consumer Technology Division

Approved by:

Toyokazu Imamura
Leader
Consumer Technology Division



- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
☒ There is no testing item of "Non-accreditation".

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

13-EM-F0429

REVISION HISTORY

Original Test Report No.: 10532071S

[illegible]

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Contents

	<u>Page</u>
SECTION 1: Customer information.....	4
SECTION 2: Equipment under test (E.U.T.).....	4
SECTION 3: Test specification, procedures & results.....	5
SECTION 4: Operation of E.U.T. during testing	7
SECTION 5: Radiated emission	8
SECTION 6: 20dB bandwidth & Occupied bandwidth (99%)	10
Contents of APPENDIXES	11
APPENDIX 1: Data of radio tests	12
APPENDIX 2: Test instruments.....	17
APPENDIX 3: Photographs of test setup	18

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 1: Customer information

Company Name : Ueda Japan Radio Co., Ltd.
Address : 2-10-19 Fumiiri, Ueda-shi, Nagano, 386-8608 Japan
Telephone Number : +81-268-26-2059
Facsimile Number : +81-268-26-2072
Contact Person : Kiyoharu Yamadera

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Secure Tag
Model No. : DSF-214P
Serial No. : Refer to 4.2 of this report.
Rating : DC3V (2.3 to 3.3V)
Receipt Date of Sample : November 6, 2014
Country of Mass-production : Japan
Condition of EUT : Production model
Modification of EUT : No modification by the test lab.

2.2 Product description

Model: DSF-214P (referred to as the EUT in this report) is a Secure Tag.

Clock frequency(ies) in the system : CPU: 32.768kHz, RF: 26MHz

Radio specification:

Equipment type : Transmitter
Frequency of operation : 923.6-927.4MHz
Type of modulation : FSK
Antenna type : Loop
Antenna connector type : Soldering
Antenna gain : -17 dBi
Operation temperature range : -10 to +50 deg.C.
ITU code : F1D

Equipment type : Receiver
Frequency of operation : 125kHz

FCC 15.31 (e)

The test was performed with new battery. Therefore, the EUT complies with the requirement.

FCC 15.203

The antenna is not removable from the EUT. Therefore, the EUT complies with the requirement

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 3: Test specification, procedures & results

3.1 Test specification

Test specification : FCC Part 15 Subpart C: 2014, final revised on August 15, 2014 and effective October 14, 2014
Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.209 Radiated emission limits, general requirements
Section 15.249 Operation within the bands 902-928MHz, 2400-2483.5MHz, 5725-5875MHz, and 24.0-24.25GHz

3.2 Procedures & Results

Item	Test Procedure	Specification	Remarks	Deviation	Worst Margin	Results
Conducted emission	ANSI C63.4:2009 7. AC powerline conducted emission measurements	FCC 15.207	-	N/A *1)	N/A	N/A
20dB bandwidth	ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.215	Radiated	N/A	-	Complied
Electric field strength of fundamental emission	ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.249 (a)(e), 15.209	Radiated	N/A	8.3dB Freq.: 927.400 MHz Detector: Quasi-Peak Polarization: Horizontal	Complied
Electric field strength of spurious emission	ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.205 (a)(b), 15.209, 15.249 (a)(d)(e)	Radiated	N/A	1.6dB Freq.: 928.000 MHz Detector: Quasi-Peak Polarization: Horizontal Mode: Tx 927.4MHz	Complied
Frequency tolerance	ANSI C63.4:2009 13. Measurement of intentional radiators	FCC 15.249 (b)	-	N/A *2)	N/A	N/A

Note: UL Japan's EMI Work Procedures No.13-EM-W0420 and 13-EM-W0422

*1) The test is not applicable since the EUT has no AC mains.

*2) The test is not applicable since the EUT does not operate in the 24.05-24.25GHz band.

3.3 Addition to standard

Item	Test Procedure	Specification	Remarks	Worst Margin	Results
Occupied bandwidth (99%)	ANSI C63.4:2009 13. Measurement of intentional radiators, RSS-Gen 4.6.1	-	Radiated	-	Complied

Note: UL Japan's EMI Work Procedures No.13-EM-W0420 and 13-EM-W0422

* Other than above, no addition, exclusion nor deviation has been made from the standard.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Item	Frequency range	No.1 SAC ^{*1} /SR ^{*2} (±)	No.2 SAC/SR (±)	No.3 SAC/SR (±)
Radiated emission (Measurement distance: 3m)	9kHz-30MHz	3.7 dB	3.5 dB	3.5 dB
	30MHz-300MHz	4.8 dB	4.9 dB	4.7 dB
	300MHz-1GHz	5.0 dB	5.0 dB	4.8 dB
	1GHz-18GHz	4.9 dB	4.9 dB	4.9 dB
	18GHz-26.5GHz	4.5 dB	4.3 dB	4.3 dB

*1: SAC=Semi-Anechoic Chamber

*2: SR= Shielded Room is applied besides radiated emission

The data listed in this report meets the limits unless the uncertainty is taken into consideration.

Antenna port conducted test

Bandwidth Measurement uncertainty for this test was: (±) 0.66%

3.5 Test location

UL Japan, Inc. Shonan EMC Lab.

1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number : +81 463 50 6400

Facsimile number : +81 463 50 6401

JAB Accreditation No. : RTL02610

	IC Registration No.	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
☐ No.1 semi-anechoic chamber	2973D-1	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
☐ No.2 semi-anechoic chamber	2973D-2	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
☒ No.3 semi-anechoic chamber	2973D-3	12.7 x 7.7 x 5.35	12.7 x 7.7	5m
☐ No.4 semi-anechoic chamber	-	8.1 x 5.1 x 3.55	8.1 x 5.1	-
☐ No.1 shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
☐ No.2 shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
☐ No.3 shielded room	-	6.3 x 4.7 x 2.7	6.3 x 4.7	-
☐ No.4 shielded room	-	4.4 x 4.7 x 2.7	4.4 x 4.7	-
☐ No.5 shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
☐ No.6 shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-

3.6 Test setup, Data of test & Test instruments

Refer to APPENDIX 1 to 3.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 4: Operation of E.U.T. during testing

4.1 Operating mode


The EUT exercise program used during testing was designed to exercise the various system components in a manner similar to typical use.

Test item	Operating mode	Tested frequency
All items	Transmitting	923.6MHz, 925.4MHz, 927.4MHz

Software: WR-900

Justification: The system was configured in typical fashion (as customer would normally use it) for testing.

4.2 Configuration and peripherals



* Test data was taken under worse case conditions.

Description of EUT and support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Secure Tag	DSF-214P	0089 0002	Ueda Japan Radio Co., Ltd.	EUT

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 5: Radiated emission

5.1 Operating environment

Test place : See test data (APPENDIX 1)
Temperature : See test data (APPENDIX 1)
Humidity : See test data (APPENDIX 1)

5.2 Test configuration

EUT was placed on a polystyrene platform of nominal size, 0.5m by 0.5m, raised 0.8m above the conducting ground plane. Photographs of the set up are shown in APPENDIX 3.

5.3 Test conditions

Frequency range : 9kHz to 10GHz
EUT position : Table top

5.4 Test procedure

The Radiated Electric Field Strength intensity has been measured on a semi-anechoic chamber with a ground plane at a distance of 3m.

Measurement was performed additionally on open area at a 3m distance to confirm no noise was detected.

<9kHz to 30MHz>

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for vertical polarization (antenna angle: 0deg.to 360deg.) and horizontal polarization.

* FCC 15.31 (f)(2) (9kHz-30MHz)

9kHz – 490kHz [Limit at 3m]= [Limit at 300m]-40log (3[m]/300[m])

490kHz – 30MHz [Limit at 3m]= [Limit at 30m]-40log (3[m]/30[m])

<30MHz to 10GHz>

The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detection of the test receiver and spectrum analyzer.

	9kHz to 90kHz & 110kHz to 150kHz	90kHz to 110kHz	150kHz to 490kHz	490kHz to 30MHz	30MHz to 1GHz	1GHz to 10GHz	
Detector type	PK/AV	QP	PK/AV	QP	QP	PK	AV *1)
IF Bandwidth	200Hz	200Hz	10kHz	9kHz	120kHz	RBW: 1MHz /VBW: 3MHz	RBW:1MHz /VBW:10Hz

*1) When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.


Antenna polarization	Frequency	Carrier	Spurious		
			9kHz-30MHz	30-1000MHz	1-10GHz
Horizontal		X	X	X	Z
Vertical		Z	Z	Z	Y

Horizontal (Top View)




Antenna was not rotated.

Vertical (Side View)



(Top View)



Front side: 0 deg.
Forward direction: clockwise

Figure 1. Direction of the Loop Antenna




Figure 2. Antenna angle (except Loop antenna)

5.5 Results

Summary of the test results : Pass
* No noise was detected below 30MHz.

Refer to APPENDIX 1

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 6: 20dB bandwidth & Occupied bandwidth (99%)

Test procedure

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

Results

Summary of the test results : Pass
Refer to APPENDIX 1

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Contents of APPENDIXES

APPENDIX 1: Test data

20dB bandwidth
Radiated emission
99% Occupied bandwidth

APPENDIX 2: Test instruments

Test instruments

APPENDIX 3: Photographs of test setup

Radiated emission
Pre-check of the worst position

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400


Facsimile : +81 463 50 6401

APPENDIX 1: Data of Radio tests

20dB Bandwidth

Test place	UL Japan, Inc. Shonan EMC Lab.	No.3 Semi Anechoic Chamber
Date	November 7, 2014	
Temperature / Humidity	23deg.C , 50%RH	
Engineer	Akio Hayashi	
Mode	Tx,	

Freq. [MHz]	20dB Bandwidth [MHz]
923.6000	0.477
925.4000	0.437
927.4000	0.436



Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date November 6, 2014 November 7, 2014
 Temperature / Humidity 23 deg.C, 35 %RH 23 deg.C, 50 %RH
 Engineer Akio Hayashi Akio Hayashi
 Mode Tx, 923.6 MHz

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	902.000	QP	21.4	21.6	20.7	31.0	32.7	46.0	13.3	100	16	
Hori.	923.600	QP	72.8	21.8	20.8	30.9	84.5	93.9	9.4	100	16	
Hori.	928.000	QP	21.5	21.8	20.8	30.8	33.3	46.0	12.7	100	16	
Hori.	1847.200	PK	46.9	25.4	3.7	41.2	34.8	73.9	39.1	100	0	
Hori.	3694.400	PK	43.7	28.5	5.2	40.8	36.6	73.9	37.3	100	23	
Hori.	5541.600	PK	50.7	31.7	6.1	38.8	49.7	73.9	24.2	100	23	
Hori.	7388.800	PK	46.9	36.9	6.9	40.4	50.3	73.9	23.6	100	0	
Hori.	9236.000	PK	41.3	38.2	8.0	40.4	47.1	73.9	26.8	100	22	
Hori.	1847.200	AV	36.6	25.4	3.7	41.2	24.5	53.9	29.4	100	0	
Hori.	3694.400	AV	34.2	28.5	5.2	40.8	27.1	53.9	26.8	100	23	
Hori.	5541.600	AV	43.3	31.7	6.1	38.8	42.3	53.9	11.6	100	23	
Hori.	7388.800	AV	36.9	36.9	6.9	40.4	40.3	53.9	13.6	100	0	
Hori.	9236.000	AV	33.7	38.2	8.0	40.4	39.5	53.9	14.4	100	22	
Vert.	902.000	QP	21.4	21.6	20.7	31.0	32.7	46.0	13.3	116	241	
Vert.	923.600	QP	69.9	21.8	20.8	30.9	81.6	93.9	12.3	116	241	
Vert.	928.000	QP	21.4	21.8	20.8	30.8	33.2	46.0	12.8	116	241	
Vert.	1847.200	PK	46.7	25.4	3.7	41.2	34.6	73.9	39.3	100	332	
Vert.	3694.400	PK	48.0	28.5	5.2	40.8	40.9	73.9	33.0	100	280	
Vert.	5541.600	PK	51.5	31.7	6.1	38.8	50.5	73.9	23.4	100	334	
Vert.	7388.800	PK	46.2	36.9	6.9	40.4	49.6	73.9	24.3	100	51	
Vert.	9236.000	PK	42.8	38.2	8.0	40.4	48.6	73.9	25.3	100	334	
Vert.	1847.200	AV	36.4	25.4	3.7	41.2	24.3	53.9	29.6	100	332	
Vert.	3694.400	AV	38.0	28.5	5.2	40.8	30.9	53.9	23.0	100	280	
Vert.	5541.600	AV	42.7	31.7	6.1	38.8	41.7	53.9	12.2	100	334	
Vert.	7388.800	AV	36.3	36.9	6.9	40.4	39.7	53.9	14.2	100	51	
Vert.	9236.000	AV	32.9	38.2	8.0	40.4	38.7	53.9	15.2	100	334	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)) - Gain(Amplifier)

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date November 6, 2014 November 7, 2014
 Temperature / Humidity 23 deg.C, 35 %RH 23 deg.C, 50 %RH
 Engineer Akio Hayashi Akio Hayashi
 Mode Tx, 925.4 MHz

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	902.000	QP	21.6	21.6	20.7	31.0	32.9	46.0	13.1	100	24	
Hori.	925.400	QP	72.8	21.8	20.8	30.8	84.6	93.9	9.3	100	24	
Hori.	928.000	QP	22.0	21.8	20.8	30.8	33.8	46.0	12.2	100	24	
Hori.	1850.800	PK	45.7	25.5	3.7	41.2	33.7	73.9	40.2	100	13	
Hori.	3701.600	PK	45.3	28.6	5.2	40.8	38.3	73.9	35.6	100	13	
Hori.	5552.400	PK	52.5	31.8	6.1	38.8	51.6	73.9	22.3	100	13	
Hori.	7403.200	PK	47.1	36.9	6.9	40.4	50.5	73.9	23.4	100	13	
Hori.	9254.000	PK	42.0	38.2	8.0	40.4	47.8	73.9	26.1	100	13	
Hori.	1850.800	AV	40.5	25.5	3.7	41.2	28.5	53.9	25.4	100	13	
Hori.	3701.600	AV	34.0	28.6	5.2	40.8	27.0	53.9	26.9	100	13	
Hori.	5552.400	AV	42.2	31.8	6.1	38.8	41.3	53.9	12.6	100	13	
Hori.	7403.200	AV	37.3	36.9	6.9	40.4	40.7	53.9	13.2	100	13	
Hori.	9254.000	AV	33.0	38.2	8.0	40.4	38.8	53.9	15.1	100	13	
Vert.	902.000	QP	21.5	21.6	20.7	31.0	32.8	46.0	13.2	115	255	
Vert.	925.400	QP	70.8	21.8	20.8	30.8	82.6	93.9	11.3	115	255	
Vert.	928.000	QP	21.8	21.8	20.8	30.8	33.6	46.0	12.4	115	255	
Vert.	1850.800	PK	51.9	25.5	3.7	41.2	39.9	73.9	34.0	100	350	
Vert.	3701.600	PK	48.4	28.6	5.2	40.8	41.4	73.9	32.5	100	315	
Vert.	5552.400	PK	47.0	31.8	6.1	38.8	46.1	73.9	27.8	100	350	
Vert.	7403.200	PK	46.6	36.9	6.9	40.4	50.0	73.9	23.9	100	350	
Vert.	9254.000	PK	40.4	38.2	8.0	40.4	46.2	73.9	27.7	100	350	
Vert.	1850.800	AV	47.0	25.5	3.7	41.2	35.0	53.9	18.9	100	350	
Vert.	3701.600	AV	36.9	28.6	5.2	40.8	29.9	53.9	24.0	100	315	
Vert.	5552.400	AV	36.8	31.8	6.1	38.8	35.9	53.9	18.0	100	350	
Vert.	7403.200	AV	34.4	36.9	6.9	40.4	37.8	53.9	16.1	100	350	
Vert.	9254.000	AV	33.0	38.2	8.0	40.4	38.8	53.9	15.1	100	350	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)) - Gain(Amplifier)

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Radiated Emission

Test place No.3 Semi Anechoic Chamber
 Date November 6, 2014 November 7, 2014
 Temperature / Humidity 23 deg.C, 35 %RH 23 deg.C, 50 %RH
 Engineer Akio Hayashi Akio Hayashi
 Mode Tx, 927.4 MHz

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	902.000	QP	21.5	21.6	20.7	31.0	32.8	46.0	13.2	100	16	
Hori.	927.400	QP	73.8	21.8	20.8	30.8	85.6	93.9	8.3	100	16	
Hori.	928.000	QP	32.6	21.8	20.8	30.8	44.4	46.0	1.6	100	16	
Hori.	1854.800	PK	44.5	25.5	3.7	41.2	32.5	73.9	41.4	100	179	
Hori.	3709.600	PK	45.7	28.6	5.2	40.8	38.7	73.9	35.2	100	46	
Hori.	5564.400	PK	50.3	31.8	6.1	38.8	49.4	73.9	24.5	100	48	
Hori.	7419.200	PK	46.2	37.0	6.9	40.4	49.7	73.9	24.2	100	2	
Hori.	9274.000	PK	41.0	38.2	8.0	40.3	46.9	73.9	27.0	100	48	
Hori.	1854.800	AV	36.8	25.5	3.7	41.2	24.8	53.9	29.1	100	179	
Hori.	3709.600	AV	34.4	28.6	5.2	40.8	27.4	53.9	26.5	100	46	
Hori.	5564.400	AV	45.0	31.8	6.1	38.8	44.1	53.9	9.8	100	48	
Hori.	7419.200	AV	35.4	37.0	6.9	40.4	38.9	53.9	15.0	100	2	
Hori.	9274.000	AV	32.6	38.2	8.0	40.3	38.5	53.9	15.4	100	48	
Vert.	902.000	QP	21.5	21.6	20.7	31.0	32.8	46.0	13.2	115	250	
Vert.	927.400	QP	71.7	21.8	20.8	30.8	83.5	93.9	10.4	115	250	
Vert.	928.000	QP	30.6	21.8	20.8	30.8	42.4	46.0	3.6	115	250	
Vert.	1854.800	PK	46.7	25.5	3.7	41.2	34.7	73.9	39.2	100	0	
Vert.	3709.600	PK	46.5	28.6	5.2	40.8	39.5	73.9	34.4	100	321	
Vert.	5564.400	PK	50.5	31.8	6.1	38.8	49.6	73.9	24.3	100	330	
Vert.	7419.200	PK	50.7	37.0	6.9	40.4	54.2	73.9	19.7	100	333	
Vert.	9274.000	PK	41.5	38.2	8.0	40.3	47.4	73.9	26.5	100	333	
Vert.	1854.800	AV	36.2	25.5	3.7	41.2	24.2	53.9	29.7	100	0	
Vert.	3709.600	AV	37.1	28.6	5.2	40.8	30.1	53.9	23.8	100	321	
Vert.	5564.400	AV	40.8	31.8	6.1	38.8	39.9	53.9	14.0	100	330	
Vert.	7419.200	AV	42.0	37.0	6.9	40.4	45.5	53.9	8.4	100	333	
Vert.	9274.000	AV	32.5	38.2	8.0	40.3	38.4	53.9	15.5	100	333	

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)) - Gain(Amplifier)

UL Japan, Inc.


Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

99% Occupied Bandwidth



APPENDIX 2

Test Instruments

EMI test equipment

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
SAF-03	Pre Amplifier	SONOMA	310N	290213	RE	2014/02/14 * 12
SAT6-06	Attenuator	JFW	50HF-006N	-	RE	2014/02/17 * 12
SBA-03	Biconical Antenna	Schwarzbeck	BBA9106	91032666	RE	2014/10/18 * 12
SCC-C1/C2/C3/C4/C5/C10/SRSE-03	Coaxial Cable&RF Selector	Fujikura/Fujikura/Suhner/Suhner/Suhner/Suhner/TOYO	8D2W/12DSFA/141PE/141PE/141PE/141PE/NS4906	-/0901-271 (RF Selector)	RE	2014/04/25 * 12
SLA-03	Logperiodic Antenna	Schwarzbeck	UHALP9108A	UHALP 9108-A 0901	RE	2014/10/18 * 12
SOS-05	Humidity Indicator	A&D	AD-5681	4062518	RE	2014/10/30 * 12
STR-06	Test Receiver	Rohde & Schwarz	ESCI	101259	RE	2014/03/04 * 12
SJM-15	Measure	ASKUL	-	-	RE	-
SAEC-03(NSA)	Semi-Anechoic Chamber	TDK	SAEC-03(NSA)	3	RE	2014/07/14 * 12
COTS-SEMI-1	EMI Software	TSJ	TEPTO-DV(RE,CE, RFL,MF)	-	RE	-
SAF-06	Pre Amplifier	TOYO Corporation	TPA0118-36	1440491	RE	2014/05/23 * 12
SCC-G04	Coaxial Cable	Junkosha	J12J102207-00	JUN-12-14-018	RE	2014/06/24 * 12
SCC-G23	Coaxial Cable	Suhner	SUCOFLEX 104	297342/4	RE	2014/05/15 * 12
SHA-03	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-739	RE	2014/08/12 * 12
KSA-08	Spectrum Analyzer	Agilent	E4446A	MY46180525	RE	2014/03/04 * 12
SFL-01	Highpass Filter	MICRO-TRONICS	HPM50115	001	RE	2013/11/22 * 12
SAT10-02	Attenuator	JFW	50HF-010N	-	RE	2014/02/17 * 12
SLP-02	Loop Antenna	Rohde & Schwarz	HFH2-Z2	100218	RE	2013/11/08 * 12
SAT6-07	Attenuator	JFW	50HF-006N	-	RE	2014/02/17 * 12

The expiration date of the calibration is the end of the expired month .
 As for some calibrations performed after the tested dates , those test equipment have been controlled by means of an unbroken chains of calibrations .

All equipment is calibrated with valid calibrations . Each measurement data is traceable to the national or international standards .

Test Item :

RE: Radiated emission