

RF Exposure Evaluation

FCC ID: 2ADKSGBTY-6A

1. Client Information

Applicant : MEET Studio CO.,LTD.
Address : Room 204, Hanhai Building, NO.2 North Construction Road,
Chenghua District, Chengdu, Sichuan, China
Manufacturer : MEET Studio CO.,LTD.
Address : Room 204, Hanhai Building, NO.2 North Construction Road,
Chenghua District, Chengdu, Sichuan, China

2. General Description of EUT

EUT Name	:	Cool Gym	
Models No.	:	GBTY-6A	
Brand Name	:	Cool Gym	
Model Difference	:	N/A	
Product Description	:	Operation Frequency: Bluetooth:2402~2480MHz	
	:	Number of Channel:	BLE:40 Channels
	:	Max Peak Output Power:	GFSK:-0.97 dBm
	:	Antenna Gain:	-2 dBi Chip Antenna
	:	Modulation Type:	1Mbps(GFSK)
Power Supply	:	DC power by USB cable form Host System DC power by Li-ion battery	
Power Rating	:	DC 5V by USB Cable from PC system. DC 3.7V by 60 mAh Li-ion Battery.	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:

More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v05r02.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] \cdot [\sqrt{f_{(\text{GHz})}}]}{\leq 3.0 \text{ for 1-g SAR}}$$

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] \cdot [\sqrt{f_{(\text{GHz})}}]}{\leq 7.5.0 \text{ for 10-g SAR}}$$

2.

Calculation:

Test separation: 5mm						
BLE Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Ant Gain (dBi)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-0.970	-2	± 1	0.635	0.197	3.0
2.442	-1.230	-2	± 1	0.598	0.187	3.0
2.480	-2.206	-2	± 1	0.478	0.151	3.0

So standalone SAR measurements are not required.