

FCC Part 22H & 24E Measurement and Test Report For

Insane Enterprises. Inc.

22631 Pacific Coast HWY, Suite 469, Malibu, CA 90265 USA

FCC ID: 2ADMI-SMT1

FCC Rules: FCC Part 22H, FCC Part 24E

Product Description: Waterproof rugged phone

Tested Model: SMT1

Report No.: STR14118070I-1

Tested Date: 2014-11-12 to 2014-12-06

Issued Date: 2014-12-08

Tested By: Silin Chen / Engineer

Reviewed By: Lahm Peng / EMC Manager

Approved & Authorized By: Jandy So / PSQ Manager

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
2. SUMMARY OF TEST RESULTS	7
3. RF EXPOSURE	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. RF OUTPUT POWER.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 TEST EQUIPMENT LIST AND DETAILS	9
4.3 TEST PROCEDURE.....	9
4.4 ENVIRONMENTAL CONDITIONS	10
4.5 SUMMARY OF TEST RESULTS/PLOTS	10
5. PEAK-TO-AVERAGE RADIO (PAR) OF TRANSMITTER.....	17
5.1 STANDARD APPLICABLE.....	17
5.2 TEST EQUIPMENT LIST AND DETAILS	17
5.3 TEST PROCEDURE.....	17
5.4 ENVIRONMENTAL CONDITIONS	17
5.5 SUMMARY OF TEST RESULTS	18
6. EMISSION BANDWIDTH.....	20
6.1 STANDARD APPLICABLE.....	20
6.2 TEST EQUIPMENT LIST AND DETAILS	20
6.3 TEST PROCEDURE.....	20
6.4 ENVIRONMENTAL CONDITIONS	20
6.5 SUMMARY OF TEST RESULTS/PLOTS	21
7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL.....	35
7.1 STANDARD APPLICABLE.....	35
7.2 TEST EQUIPMENT LIST AND DETAILS	35
7.3 TEST PROCEDURE.....	35
7.4 ENVIRONMENTAL CONDITIONS	35
7.5 SUMMARY OF TEST RESULTS/PLOTS	36
8. SPURIOUS RADIATED EMISSIONS.....	68
8.1 MEASUREMENT UNCERTAINTY	68
8.2 STANDARD APPLICABLE.....	68
8.3 TEST EQUIPMENT LIST AND DETAILS	68
8.4 TEST PROCEDURE.....	68
8.5 ENVIRONMENTAL CONDITIONS	68
8.6 SUMMARY OF TEST RESULTS/PLOTS	69
9. FREQUENCY STABILITY	89
9.1 STANDARD APPLICABLE.....	89
9.2 TEST EQUIPMENT LIST AND DETAILS	89
9.3 TEST PROCEDURE.....	89
9.4 ENVIRONMENTAL CONDITIONS	90
9.5 SUMMARY OF TEST RESULTS/PLOTS	90

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Insane Enterprises. Inc.
Address of applicant: 22631 Pacific Coast HWY, Suite 469, Malibu, CA 90265
USA

Manufacturer: Insane Enterprises. Inc.
Address of manufacturer: 22631 Pacific Coast HWY, Suite 469, Malibu, CA 90265
USA

General Description of EUT	
Product Name:	Waterproof rugged phone
Brand Name:	Sierra Mountain Technology
Model No.:	SMT1
Hardware Version:	F034_V1.3
Software Version:	F034_ENGLISH_26_V0.1_EMMC_V45_20141101
IMEI:	358903321097928/358903321080536
Rated Voltage:	DC 3.7V Battery
Battery:	Capacitance: 3000mAh
Device Category:	Portable Device
<i>The EUT is dual band GSM850/GSM900/DCS1800/PCS1900, WCDMA Band I/V, Waterproof rugged phone. The Waterproof rugged phone is intended for speech and Multimedia Message Service (MMS) transmission. It is equipped with GPRS/EDGE class 12 for GSM850/PCS1900 and Wi-Fi, Bluetooth, GPS, and camera functions. For more information see the following datasheet.</i> <i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
2G	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS 850: 824~849MHz GSM/GPRS 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS 850: 869~894MHz GSM/GPRS 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 32.57dBm, GSM1900: 28.93dBm
Type of Modulation:	GMSK, 8PSK
Type of Emission:	GSM850: 258KGXW, GSM1900: 259KGXW EDGE850: 262KG7W, EDGE1900: 263KG7W
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: -3.37dBi, GSM1900: -2.43dBi
GPRS/EDGE Class:	Class 12
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band V
Uplink Frequency:	WCDMA Band V: 824~849MHz
Downlink Frequency:	WCDMA Band V: 869~894MHz
Max RF Output Power:	WCDMA850: 22.16dBm
Type of Modulation:	BPSK
Type of Emission:	WCDMA850: 4M30F9W
Type of Antenna:	Integral Antenna
Antenna Gain:	WCDMA850: 1.14dBi

1.2 Test Standards

The following report is prepared on behalf of the Insane Enterprises. Inc. in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603-C: 2004 and ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	EDGE 850	Low, Middle, High Channels
TM4	GSM 1900	Low, Middle, High Channels
TM5	GPRS 1900	Low, Middle, High Channels
TM6	EDGE 1900	Low, Middle, High Channels
TM7	WCDMA Band V	Low, Middle, High Channels
TM8	HSDPA Band V	Low, Middle, High Channels
TM9	HSUPA Band V	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.4 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band V	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.4 MHz	4182
		846.6 MHz	4233
Note: the transmitter has been tested on the communications mode of GSM, GPRS, WCDMA, HSDPA, HSUPA compliance test and record the worst case.			

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	0.6	Shielded	Without Core
Earphone	1.1	Unshielded	Without Ferrite

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R
Adapter	/	ETA-U90JWS	/

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 22.917 (b), § 24.238 (b)	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a)	Out of Band Emissions	Compliant
§ 22.355, § 24.235	Frequency Stability	Compliant

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR report.

4. RF Output Power

4.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.


According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-334	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086198	2014-05-24	2015-05-23
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	112012	2014-05-28	2015-05-27
Signal Generator	R&S	SMR20	100047	2014-05-28	2015-05-27

4.3 Test Procedure

Conducted output power test method:



Radiated power test method:

1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2003 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.

4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

4.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.5 Summary of Test Results/Plots

Radiated Power

ERP For GSM Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	27.95	1.5	0	H	1.5	0	26.45	38.45
824.2	30.30	1.5	0	V	1.5	0	28.80	38.45
Middle Channel								
836.4	28.25	1.5	0	H	1.5	0	26.75	38.45
836.4	30.84	1.5	0	V	1.5	0	29.34	38.45
High Channel								
848.8	27.92	1.5	0	H	1.5	0	26.42	38.45
848.8	30.21	1.5	0	V	1.5	0	28.71	38.45

EIRP For GSM Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	17.45	1.5	0	H	1.9	7.7	23.25	33
1850.2	19.54	1.5	0	V	1.9	7.7	25.34	33
Middle Channel								
1880.0	17.54	1.5	0	H	1.9	7.7	23.34	33
1880.0	20.21	1.5	0	V	1.9	7.7	26.01	33
High Channel								
1909.8	17.50	1.5	0	H	1.9	7.7	23.30	33
1909.8	20.11	1.5	0	V	1.9	7.7	25.91	33

ERP For GPRS Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	27.84	1.5	0	H	1.5	0	26.34	38.45
824.2	30.39	1.5	0	V	1.5	0	28.89	38.45
Middle Channel								
836.4	28.28	1.5	0	H	1.5	0	26.78	38.45
836.4	30.98	1.5	0	V	1.5	0	29.48	38.45
High Channel								
848.8	27.90	1.5	0	H	1.5	0	26.40	38.45
848.8	30.52	1.5	0	V	1.5	0	29.02	38.45

EIRP For GPRS Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	17.22	1.5	0	H	1.9	7.7	23.02	33
1850.2	19.56	1.5	0	V	1.9	7.7	25.36	33
Middle Channel								
1880.0	17.32	1.5	0	H	1.9	7.7	23.12	33
1880.0	20.12	1.5	0	V	1.9	7.7	25.92	33
High Channel								
1909.8	18.05	1.5	0	H	1.9	7.7	23.85	33
1909.8	19.71	1.5	0	V	1.9	7.7	25.51	33

ERP For EDGE Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	24.14	1.5	0	H	1.5	0	22.64	38.45
824.2	25.75	1.5	0	V	1.5	0	24.25	38.45
Middle Channel								
836.6	23.19	1.5	0	H	1.5	0	21.69	38.45
836.6	25.25	1.5	0	V	1.5	0	23.75	38.45
High Channel								
848.8	23.55	1.5	0	H	1.5	0	22.05	38.45
848.8	25.46	1.5	0	V	1.5	0	23.96	38.45

EIRP For EDGE Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	13.11	1.5	0	H	1.9	7.7	18.91	33
1850.2	14.87	1.5	0	V	1.9	7.7	20.67	33
Middle Channel								
1880.0	13.22	1.5	0	H	1.9	7.7	19.02	33
1880.0	15.44	1.5	0	V	1.9	7.7	21.24	33
High Channel								
1909.8	12.57	1.5	0	H	1.9	7.7	18.37	33
1909.8	15.14	1.5	0	V	1.9	7.7	20.94	33

ERP For WCDMA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	21.81	1.5	0	H	1.5	0	20.31	38.45
826.4	23.81	1.5	0	V	1.5	0	22.31	38.45
Middle Channel								
836.4	21.81	1.5	0	H	1.5	0	20.31	38.45
836.4	24.08	1.5	0	V	1.5	0	22.58	38.45
High Channel								
846.6	21.62	1.5	0	H	1.5	0	20.12	38.45
846.6	23.58	1.5	0	V	1.5	0	22.08	38.45

ERP For HSDPA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	20.86	1.5	0	H	1.5	0	19.36	38.45
826.4	22.75	1.5	0	V	1.5	0	21.25	38.45
Middle Channel								
836.4	20.52	1.5	0	H	1.5	0	19.02	38.45
836.4	22.74	1.5	0	V	1.5	0	21.24	38.45
High Channel								
846.6	21.71	1.5	0	H	1.5	0	20.21	38.45
846.6	22.86	1.5	0	V	1.5	0	21.36	38.45

ERP For HSUPA Mode Band V

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	21.51	1.5	0	H	1.5	0	20.01	38.45
826.4	22.88	1.5	0	V	1.5	0	21.38	38.45
Middle Channel								
836.4	21.77	1.5	0	H	1.5	0	20.27	38.45
836.4	22.89	1.5	0	V	1.5	0	21.39	38.45
High Channel								
846.6	21.75	1.5	0	H	1.5	0	20.25	38.45
846.6	22.84	1.5	0	V	1.5	0	21.34	38.45

Note: Result = Substitute - Cable loss + Antenna Gain

Max. Conducted Output Power

For Cellular Band (GSM850)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
GSM	Low Channel	824.2	32.54	38.45
	Middle Channel	836.4	32.27	38.45
	High Channel	848.8	32.33	38.45
GPRS(1 Slot)	Low Channel	824.2	32.57	38.45
	Middle Channel	836.4	32.35	38.45
	High Channel	848.8	32.40	38.45
EDGE(1 Slot)	Low Channel	824.2	26.65	38.45
	Middle Channel	836.6	26.72	38.45
	High Channel	848.8	26.64	38.45

For PCS Band (GSM1900)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
GSM	Low Channel	1850.2	28.88	33.0
	Middle Channel	1880.0	28.77	33.0
	High Channel	1909.8	28.64	33.0
GPRS(1 Slot)	Low Channel	1850.2	28.93	33.0
	Middle Channel	1880.0	28.80	33.0
	High Channel	1909.8	28.66	33.0
EDGE(1 Slot)	Low Channel	1850.2	25.27	33.0
	Middle Channel	1880.0	25.09	33.0
	High Channel	1909.8	24.98	33.0

For WCDMA Band V

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	826.4	22.08	38.45
	Middle Channel	836.4	21.68	38.45
	High Channel	846.6	22.16	38.45
HSDPA	Low Channel	826.4	21.14	38.45
	Middle Channel	836.4	20.79	38.45
	High Channel	846.6	21.18	38.45
HSUPA	Low Channel	826.4	21.18	38.45
	Middle Channel	836.4	20.91	38.45
	High Channel	846.6	21.21	38.45

5. Peak-to-average Radio (PAR) of Transmitter

5.1 Standard Applicable

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


5.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-28	2015-05-27
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-28	2015-05-27

5.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.

Test Configuration for the emission bandwidth testing:



5.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.5 Summary of Test Results

For Cellular Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
GSM	128	824.2	34.82	32.54	2.28	13
	190	836.4	35.16	32.27	2.89	13
	251	848.8	34.45	32.33	2.12	13
GPRS (1 Slot)	128	824.2	34.92	32.57	2.35	13
	190	836.4	35.24	32.35	2.89	13
	251	848.8	35.05	32.40	2.65	13
EDGE (1 Slot)	128	824.2	28.92	26.65	2.27	13
	190	836.6	28.99	26.72	2.27	13
	251	848.8	28.74	26.64	2.10	13

For PCS Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR	Limit
GSM	512	1850.2	31.65	28.88	2.77	13
	661	1880.0	31.52	28.77	2.75	13
	810	1909.8	31.42	28.64	2.78	13
GPRS (1 Slot)	512	1850.2	31.36	28.93	2.43	13
	661	1880.0	31.21	28.80	2.41	13
	810	1909.8	31.22	28.66	2.56	13
EDGE (1 Slot)	512	1850.2	27.54	25.27	2.27	13
	661	1880.0	26.51	25.09	1.42	13
	810	1909.8	26.21	24.98	1.23	13

For WCDMA Band V

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR	Limit
WCDMA	4132	826.4	24.84	22.08	2.76	13
	4182	836.4	23.45	21.68	1.77	13
	4233	846.6	24.82	22.16	2.66	13
HSDPA	4132	826.4	24.71	21.14	3.57	13
	4182	836.4	23.56	20.79	2.77	13
	4233	846.6	24.71	21.18	3.53	13
HSUPA	4132	826.4	24.81	21.18	3.63	13
	4182	836.4	23.58	20.91	2.67	13
	4233	846.6	24.81	21.21	3.60	13

6. Emission Bandwidth

6.1 Standard Applicable

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


6.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-28	2015-05-27
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-28	2015-05-27

6.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



6.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

6.5 Summary of Test Results/Plots

For Cellular Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	128	824.2	253.7375	342.344
	190	836.6	255.2512	338.522
	251	848.8	256.0920	341.023
GPRS	128	824.2	253.1758	340.044
	190	836.6	258.4504	341.073
	251	848.8	252.1136	335.819
EDGE	128	824.2	247.6843	323.226
	190	836.6	246.0503	315.292
	251	848.8	261.9255	336.458

For PCS Band


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	512	1850.2	256.0870	341.868
	661	1880.0	252.1882	338.955
	810	1909.8	252.9565	342.187
GPRS	512	1850.2	259.1027	327.348
	661	1880.0	251.8733	332.258
	810	1909.8	258.3257	335.367
EDGE	512	1850.2	263.2238	340.824
	661	1880.0	259.0096	343.847
	810	1909.8	262.9644	351.781

For Band V


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	4132	826.4	4.1467	4.696
	4182	836.4	4.2992	6.536
	4233	846.6	4.1726	4.735
HSDPA	4132	826.4	4.1620	4.678
	4182	836.4	4.2468	5.730
	4233	846.6	4.1970	4.686

Please refer to the following test plots:


For Cellular Band
GSM Low Channel




GSM Middle Channel




GSM High channel




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




EDGE Low Channel




EDGE Middle Channel



EDGE High channel

For PCS Band
GSM Low Channel


GSM Middle Channel




GSM High channel




GPRS Low Channel




GPRS Middle Channel



GPRS High Channel



EDGE Low Channel



EDGE Middle Channel




EDGE High channel




For Band V


WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




HSDPA Low Channel



HSDPA Middle Channel



HSDPA High Channel



7. Out of Band Emissions at Antenna Terminal

7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


7.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2014-05-28	2015-05-27
Rohde & Schwarz	Spectrum Analyzer	FSP	836079/035	2014-05-28	2015-05-27
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2014-05-28	2015-05-27

7.3 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic.

Test Configuration for the out of band emissions testing:




7.4 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

7.5 Summary of Test Results/Plots

Please refer to the following test plots For Cellular Band
GSM Low Channel 30MHz to 1GHz




Above 1GHz




GSM Middle Channel


30MHz to 1GHz




Above 1GHz




GSM High Channel
30MHz to 1GHz




Above 1GHz




GSM Low Band Emission




GSM High Band Emission



GPRS Low Channel
30MHz to 1GHz




Above 1GHz




GPRS Middle Channel


30MHz to 1GHz




Above 1GHz




GPRS High Channel
30MHz to 1GHz




Above 1GHz




GPRS Low Band Emission




GPRS High Band Emission



EDGE Low Channel
30MHz to 1GHz




Above 1GHz




EDGE Middle Channel


30MHz to 1GHz




Above 1GHz




EDGE High Channel
30MHz to 1GHz




Above 1GHz




EDGE Low Band Emission




EDGE High Band Emission



For PCS Band
GSM Low Channel
30MHz to 1GHz




Above 1GHz




GSM Middle Channel


30MHz to 1GHz




Above 1GHz




GSM High Channel
30MHz to 1GHz




Above 1GHz




GSM Low Band Emission




GSM High Band Emission




GPRS Low Channel
30MHz to 1GHz




Above 1GHz




GPRS Middle Channel
30MHz to 1GHz




Above 1GHz




GPRS High Channel
30MHz to 1GHz




Above 1GHz




GPRS Low Band Emission




GPRS High Band Emission




EDGE Low Channel
30MHz to 1GHz




Above 1GHz




EDGE Middle Channel
30MHz to 1GHz




Above 1GHz




EDGE High Channel
30MHz to 1GHz




Above 1GHz



EDGE Low Band Emission




EDGE High Band Emission




For Band V

WCDMA Low Channel


30MHz to 1GHz




Above 1GHz




WCDMA Middle Channel
30MHz to 1GHz




Above 1GHz




WCDMA High Channel
30MHz to 1GHz




Above 1GHz




WCDMA Low Band Spurious Emission




WCDMA High Band Spurious Emission




HSDPA Low Channel
30MHz to 1GHz




Above 1GHz




HSDPA Middle Channel
30MHz to 1GHz




Above 1GHz




HSDPA High Channel 30MHz to 1GHz




Above 1GHz



HSDPA Low Band Spurious Emission



HSDPA High Band Spurious Emission



8. Spurious Radiated Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.20 dB.

8.2 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

8.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Horn Antenna	EMCO	3116	9203-2178	2014-05-24	2015-05-23
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	112012	2014-05-28	2015-05-27
Signal Generator	R&S	SMR20	100047	2014-05-28	2015-05-27

8.4 Test Procedure

1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2003 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB = $43 + 10 \log_{10}$ (power out in Watts)

8.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.6 Summary of Test Results/Plots

According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:


-36.34 dB at 989.5355 MHz in the Horizontal polarization, PCS Band GSM Mode, 9 kHz to 20 GHz, 3Meters

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Spurious Emission From 30MHz to 1GHz


For Cellular Band_ GSM850 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	40.5591	-70.51	20.41	-50.10	-13.00	-37.10	ERP
2	100.2286	-70.61	17.60	-53.01	-13.00	-40.01	ERP
3	321.0608	-69.77	20.80	-48.97	-13.00	-35.97	ERP
4	739.6605	-69.98	27.51	-42.47	-13.00	-29.47	ERP


Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.9942	-70.32	20.66	-49.66	-13.00	-36.66	ERP
2	100.2286	-69.95	17.92	-52.03	-13.00	-39.03	ERP
3	293.0842	-69.95	20.66	-49.29	-13.00	-36.29	ERP
4	744.8661	-69.34	27.10	-42.24	-13.00	-29.24	ERP
5	1000.0000	-69.49	29.05	-40.44	-13.00	-27.44	ERP


For Cellular Band_GPRS Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	39.4372	-70.80	20.50	-50.30	-13.00	-37.30	ERP
2	100.9340	-70.83	17.53	-53.30	-13.00	-40.30	ERP
3	396.2415	-68.67	21.58	-47.09	-13.00	-34.09	ERP
4	893.8567	-69.07	28.96	-40.11	-13.00	-27.11	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	39.7147	-70.13	20.62	-49.51	-13.00	-36.51	ERP
2	100.2286	-69.82	17.92	-51.90	-13.00	-38.90	ERP
3	297.2241	-68.87	20.82	-48.05	-13.00	-35.05	ERP
4	582.7425	-69.49	24.40	-45.09	-13.00	-32.09	ERP
5	739.6605	-70.17	27.29	-42.88	-13.00	-29.88	ERP
6	887.6099	-69.26	28.54	-40.72	-13.00	-27.72	ERP


For Cellular Band_EDGE Mode

Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	41.4215	-69.79	20.15	-49.64	-13.00	-36.64	ERP
2	99.5281	-70.15	17.50	-52.65	-13.00	-39.65	ERP
3	316.5890	-69.78	20.81	-48.97	-13.00	-35.97	ERP
4	875.2470	-68.92	28.80	-40.12	-13.00	-27.12	ERP


Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	40.8446	-70.49	20.42	-50.07	-13.00	-37.07	ERP
2	100.9340	-70.39	17.85	-52.54	-13.00	-39.54	ERP
3	301.4224	-70.37	20.95	-49.42	-13.00	-36.42	ERP
4	599.3213	-69.53	25.00	-44.53	-13.00	-31.53	ERP
5	734.4913	-69.72	26.98	-42.74	-13.00	-29.74	ERP
6	881.4067	-70.06	28.53	-41.53	-13.00	-28.53	ERP


For PCS Band_GSM Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	39.4372	-69.57	20.50	-49.07	-13.00	-36.07	ERP
2	130.8369	-68.02	14.67	-53.35	-13.00	-40.35	ERP
3	279.0436	-68.83	19.80	-49.03	-13.00	-36.03	ERP
4	739.6605	-70.07	27.51	-42.56	-13.00	-29.56	ERP


Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	34.5173	-69.26	19.79	-49.47	-13.00	-36.47	ERP
2	100.2286	-70.19	17.92	-52.27	-13.00	-39.27	ERP
3	301.4224	-69.33	20.95	-48.38	-13.00	-35.38	ERP
4	734.4913	-69.48	26.98	-42.50	-13.00	-29.50	ERP
5	900.1474	-68.72	28.55	-40.17	-13.00	-27.17	ERP


For PCS Band_GPRS Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	100.9340	-69.38	17.85	-51.53	-13.00	-38.53	ERP
2	642.8613	-68.39	24.27	-44.12	-13.00	-31.12	ERP
3	744.8661	-69.31	27.10	-42.21	-13.00	-29.21	ERP
4	869.1302	-68.71	28.26	-40.45	-13.00	-27.45	ERP


Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.7147	-70.20	20.62	-49.58	-13.00	-36.58	ERP
2	99.5281	-70.25	17.83	-52.42	-13.00	-39.42	ERP
3	303.5437	-69.77	20.97	-48.80	-13.00	-35.80	ERP
4	607.7867	-68.21	24.47	-43.74	-13.00	-30.74	ERP
5	739.6605	-69.46	27.29	-42.17	-13.00	-29.17	ERP
6	919.2866	-68.64	28.19	-40.45	-13.00	-27.45	ERP


For PCS Band_EDGE Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	312.1794	-69.16	21.02	-48.14	-13.00	-35.14	ERP
2	595.1329	-69.56	24.84	-44.72	-13.00	-31.72	ERP
3	719.1995	-68.88	26.08	-42.80	-13.00	-29.80	ERP
4	958.7943	-69.09	28.00	-41.09	-13.00	-28.09	ERP

Vertical:




No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	39.4372	-70.83	20.58	-50.25	-13.00	-37.25	ERP
2	100.9340	-70.37	17.85	-52.52	-13.00	-39.52	ERP
3	323.3204	-69.51	20.99	-48.52	-13.00	-35.52	ERP
4	734.4913	-69.67	26.98	-42.69	-13.00	-29.69	ERP
5	893.8567	-69.79	28.55	-41.24	-13.00	-28.24	ERP
6	1000.0000	-68.99	29.05	-39.94	-13.00	-26.94	ERP

Spurious Emission From 30MHz to 1GHz


For band V WCDMA Mode

Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	295.1469	-69.76	20.75	-49.01	-13.00	-36.01	ERP
2	607.7867	-68.19	24.47	-43.72	-13.00	-30.72	ERP
3	766.0572	-68.82	26.08	-42.74	-13.00	-29.74	ERP
4	906.4824	-69.62	28.43	-41.19	-13.00	-28.19	ERP


Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.9942	-71.08	20.66	-50.42	-13.00	-37.42	ERP
2	103.8055	-70.03	17.55	-52.48	-13.00	-39.48	ERP
3	295.1469	-68.77	20.75	-48.02	-13.00	-35.02	ERP
4	603.5392	-69.16	24.77	-44.39	-13.00	-31.39	ERP
5	739.6605	-69.84	27.29	-42.55	-13.00	-29.55	ERP
6	857.0247	-69.62	27.91	-41.71	-13.00	-28.71	ERP
7	993.0114	-70.00	28.80	-41.20	-13.00	-28.20	ERP


For band V HSDPA Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	100.2286	-70.98	17.92	-53.06	-13.00	-40.06	ERP
2	586.8437	-69.11	24.55	-44.56	-13.00	-31.56	ERP
3	739.6605	-69.95	27.29	-42.66	-13.00	-29.66	ERP
4	875.2470	-69.51	28.42	-41.09	-13.00	-28.09	ERP


Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.9942	-69.58	20.66	-48.92	-13.00	-35.92	ERP
2	98.8326	-70.38	17.65	-52.73	-13.00	-39.73	ERP
3	459.1144	-68.29	22.33	-45.96	-13.00	-32.96	ERP
4	755.3873	-68.99	26.64	-42.35	-13.00	-29.35	ERP
5	979.1804	-69.48	28.32	-41.16	-13.00	-28.16	ERP


For band V HSDPA Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	40.8446	-70.10	20.42	-49.68	-13.00	-36.68	ERP
2	112.1305	-68.39	16.69	-51.70	-13.00	-38.70	ERP
3	739.6605	-70.07	27.29	-42.78	-13.00	-29.78	ERP
4	912.8620	-68.60	28.31	-40.29	-13.00	-27.29	ERP

Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	38.6161	-71.05	20.44	-50.61	-13.00	-37.61	ERP
2	98.8326	-70.05	17.65	-52.40	-13.00	-39.40	ERP
3	286.9823	-68.83	20.42	-48.41	-13.00	-35.41	ERP
4	595.1329	-69.51	24.84	-44.67	-13.00	-31.67	ERP
5	755.3873	-69.22	26.64	-42.58	-13.00	-29.58	ERP
6	958.7943	-67.63	28.00	-39.63	-13.00	-26.63	ERP

Note: $\text{Margin} = (\text{Reading} + \text{Correct}) - \text{Limit}$

Spurious Emissions Above 1GHz
For Cellular Band_GSM850 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.2MHz)						
1648.4	-49.46	4.94	-44.52	-13	-31.52	H
2472.6	-51.46	8.46	-43.00	-13	-30.00	H
1648.4	-50.06	4.94	-45.12	-13	-32.12	V
2472.6	-53.71	8.46	-45.25	-13	-32.25	V
Middle Channel (836.6MHz)						
1673.2	-48.47	5.11	-43.36	-13	-30.36	H
2509.8	-50.79	8.54	-42.25	-13	-29.25	H
1673.2	-48.36	5.11	-43.25	-13	-30.25	V
2509.8	-50.69	8.54	-42.15	-13	-29.15	V
High Channel (848.8MHz)						
1697.6	-50.43	5.29	-45.14	-13	-32.14	H
2546.4	-52.80	8.59	-44.21	-13	-31.21	H
1697.6	-50.30	5.29	-45.01	-13	-32.01	V
2546.4	-52.73	8.59	-44.14	-13	-31.14	V

For PCS Band_GSM1900 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-54.90	10.54	-44.36	-13	-31.36	H
5550.6	-57.62	13.37	-44.25	-13	-31.25	H
3700.4	-53.90	10.54	-43.36	-13	-30.36	V
5550.6	-57.62	13.37	-44.25	-13	-31.25	V
Middle Channel (1880MHz)						
3760.0	-53.00	10.64	-42.36	-13	-29.36	H
5640.0	-57.79	13.54	-44.25	-13	-31.25	H
3760.0	-53.00	10.64	-42.36	-13	-29.36	V
5640.0	-57.79	13.54	-44.25	-13	-31.25	V
High Channel (1909.8MHz)						
3819.6	-54.43	10.74	-43.69	-13	-30.69	H
5729.4	-57.96	13.71	-44.25	-13	-31.25	H
3819.6	-55.13	10.74	-44.39	-13	-31.39	V
5729.4	-57.46	13.71	-43.75	-13	-30.75	V

For Band V Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (826.4MHz)						
1652.8	-50.33	4.97	-45.36	-13	-32.36	H
2479.2	-51.69	8.47	-43.22	-13	-30.22	H
1652.8	-51.33	4.97	-46.36	-13	-33.36	V
2479.2	-50.72	8.47	-42.25	-13	-29.25	V
Middle Channel (836.4MHz)						
1672.8	-50.47	5.11	-45.36	-13	-32.36	H
2509.2	-52.23	8.54	-43.69	-13	-30.69	H
1672.8	-47.47	5.11	-42.36	-13	-29.36	V
2509.2	-51.45	8.54	-42.91	-13	-29.91	V
High Channel (846.6MHz)						
1693.2	-47.61	5.25	-42.36	-13	-29.36	H
2539.8	-52.19	8.57	-43.62	-13	-30.62	H
1693.2	-48.61	5.25	-43.36	-13	-30.36	V
2539.8	-52.51	8.57	-43.94	-13	-30.94	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so the data is not display.

9. Frequency Stability

9.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

9.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B-ESA	US41192821	2014-05-28	2015-05-27
Rohde & Schwarz	Universal Radio Communication	CMU200	112012	2014-05-28	2015-05-27
GONGWEN	Moisture Test Chamber	GDS-150	SEMT-0013	2014-05-28	2015-05-27

9.3 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	85-115% of declared nominal voltage
-30°C to +50°C	Normal

9.4 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.5 Summary of Test Results/Plots

For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-65	-0.0681
40	3.7	-45	-0.0538
30	3.7	-17	-0.0418
20	3.7	-54	-0.0323
10	3.7	-30	-0.0359
0	3.7	-35	-0.0418
-10	3.7	-27	-0.0502
-20	3.7	-29	-0.0478
-30	3.7	-34	-0.0514

For PCS Band GSM Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	61	0.0303
40	3.7	59	0.0340
30	3.7	55	0.0293
20	3.7	46	0.0191
10	3.7	48	0.0202
0	3.7	39	0.0154
-10	3.7	32	0.0223
-20	3.7	36	0.0245
-30	3.7	30	0.0266

For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	63	0.0753
40	3.7	67	0.0681
30	3.7	56	0.0550
20	3.7	49	0.0430
10	3.7	47	0.0335
0	3.7	37	0.0442
-10	3.7	42	0.0502
-20	3.7	35	0.0538
-30	3.7	38	0.0574

For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	71	0.0388
40	3.7	72	0.0319
30	3.7	66	0.0245
20	3.7	58	0.0202
10	3.7	53	0.0223
0	3.7	47	0.0197
-10	3.7	50	0.0266
-20	3.7	42	0.0255
-30	3.7	35	0.0293

For Cellular Band EDGE Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-59	-0.0598
40	3.7	-47	-0.0645
30	3.7	-51	-0.0394
20	3.7	-56	-0.0335
10	3.7	-43	-0.0359
0	3.7	-45	-0.0418
-10	3.7	-34	-0.0359
-20	3.7	-34	-0.0454
-30	3.7	-37	-0.0478

For PCS Band EDGE Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	62	0.0330
40	3.7	53	0.0282
30	3.7	48	0.0255
20	3.7	45	0.0239
10	3.7	48	0.0255
0	3.7	52	0.0277
-10	3.7	58	0.0309
-20	3.7	63	0.0335
-30	3.7	70	0.0372

For WCDMA Band V Mode

Reference Frequency(Middle Channel): 836.4 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-50	-0.0598
40	3.7	-45	-0.0538
30	3.7	-38	-0.0454
20	3.7	-33	-0.0395
10	3.7	-38	-0.0454
0	3.7	-40	-0.0478
-10	3.7	-45	-0.0538
-20	3.7	-56	-0.0670
-30	3.7	-63	-0.0753

For HSDPA Band V Mode

Reference Frequency(Middle Channel): 836.4 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	-36	-0.0383
40	3.7	-32	-0.0263
30	3.7	-12	-0.0215
20	3.7	-19	-0.0191
10	3.7	-21	-0.0251
0	3.7	-21	-0.0347
-10	3.7	-39	-0.0394
-20	3.7	-48	-0.0454
-30	3.7	-45	-0.0538

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-23	-0.0394
	3.7	-36	-0.0323
	4.2	-45	-0.0359
Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	34	0.0202
	3.7	48	0.0191
	4.2	56	0.0213
Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	18	0.0478
	3.7	24	0.0430
	4.2	31	0.0466
Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	28	0.0213
	3.7	47	0.0202
	4.2	62	0.0218

Reference Frequency(Middle Channel): EDGE 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-28	-0.0359
	3.7	-32	-0.0335
	4.2	-42	-0.0371
Reference Frequency(Middle Channel): EDGE 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	39	0.0255
	3.7	45	0.0239
	4.2	57	0.0245
Reference Frequency(Middle Channel): WCDMA 836.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-35	-0.0418
	3.7	-33	-0.0395
	4.2	-33	-0.0395
Reference Frequency(Middle Channel): HSDPA 836.4MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	-35	-0.0186
	3.7	-26	-0.0138
	4.2	-33	-0.0176

***** END OF REPORT *****