FCC Test Report

Report No.: AGC01665141102FE04

FCC ID	:	2ADN6S42
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	3G Smart Phone
BRAND NAME	:	TIGER
MODEL NAME	:	S42
CLIENT	:	Tiger International Electronic Company
DATE OF ISSUE	:	Nov.25, 2014
STANDARD(S) **TEST PROCEDURE(S)**	:	FCC Part 15.247 KDB 558074 v03r02
REPORT VERSION	:	V1.0

Attestation of ***G***lobal ***C***ompliance (Shenzhen) Co., Ltd

CAUTION:
This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov.25, 2014	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY 5
2. GENERAL INFORMATION 6
2.1. PRODUCT DESCRIPTION 6
2.2. TABLE OF CARRIER FREQUENCYS 6
2.3. IEEE 802.11N MODULATION SCHEME 7
2.4. RELATED SUBMITTAL(S) / GRANT (S) 7
2.5. TEST METHODOLOGY 7
2.6. SPECIAL ACCESSORIES 7
2.7. EQUIPMENT MODIFICATIONS 7
3. MEASUREMENT UNCERTAINTY 8
4. DESCRIPTION OF TEST MODES 8
5. SYSTEM TEST CONFIGURATION 9
5.1. CONFIGURATION OF EUT SYSTEM 9
5.2. EQUIPMENT USED IN EUT SYSTEM 9
5.3. SUMMARY OF TEST RESULTS 9
6. TEST FACILITY 10
7. PEAK OUTPUT POWER 11
7.1. MEASUREMENT PROCEDURE 11
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 12
7.3. LIMITS AND MEASUREMENT RESULT 13
8. 6DB BANDWIDTH 15
8.1. MEASUREMENT PROCEDURE 15
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 15
8.3. LIMITS AND MEASUREMENT RESULTS 15
9. CONDUCTED SPURIOUS EMISSION 20
9.1. MEASUREMENT PROCEDURE 20
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 20
9.3. MEASUREMENT EQUIPMENT USED 20
9.4. LIMITS AND MEASUREMENT RESULT 20
10. MAXIMUM CONDUCTED OUTPUT PEAK POWER SPECTRAL DENSITY 49
10.1 MEASUREMENT PROCEDURE 49
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 49
10.3 MEASUREMENT EQUIPMENT USED 49
10.4 LIMITS AND MEASUREMENT RESULT 49

11. RADIATED EMISSION 54
11.1. MEASUREMENT PROCEDURE 54
11.2. TEST SETUP 55
11.3. LIMITS AND MEASUREMENT RESULT 56
11.4. TEST RESULT 56
12. BAND EDGE EMISSION 65
12.1. MEASUREMENT PROCEDURE 65
12.2. TEST SET-UP 65
12.3. Radiated Test Result 66
12.4. Conducted Test Result 70
13. FCC LINE CONDUCTED EMISSION TEST 74
13.1. LIMITS OF LINE CONDUCTED EMISSION TEST 74
13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 74
13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 75
13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 75
13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 76
APPENDIX A: PHOTOGRAPHS OF TEST SETUP 78
APPENDIX B: PHOTOGRAPHS OF EUT 79

1. VERIFICATION OF CONFORMITY

Applicant	Tiger International Electronic Company
Address	Dera, Naïf Satellite Market, Nakhil Road, Dubai, UAE
Manufacturer	SHENZHEN ELECTRONICAL TECHNOLOGY CO., LTD.
Address	C028 Third Floor, Foreign Trade Wholesale Market, Huaqiangbei, Futian District, Shenzhen, China
Product Designation	3G Smart Phone
Brand Name	TIGER
Test Model	S42
Date of test	Nov.18, 2014 to Nov.24, 2014
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BGN/RF

We hereby certify that:
The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with requirement of FCC Part 15 Rules requirement.

Prepared By	Matt Zhang	
	Matt Zhang	Nov.25, 2014
Checked By	Kidd Yang	
	Kidd Yang	Nov.25, 2014
Authorized By	Solger Zhang	
	Solger Zhang	Nov.25, 2014

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as “3G Smart Phone”. It is designed by way of utilizing the DSSS and OFDM technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.412 GHz～2.462GHz
Output Power	IEEE 802.11b:11.45dBm; IEEE 802.11g:9.56dBm; IEEE 802.11n(20):9.46dBm; IEEE 802.11n(40):6.59dBm
Modulation	DSSS(DBPSK/DQPSK/CCK);OFDM(BPSK/QPSK/16-QAM/64-QAM)
Number of channels	11
Hardware Version	S135_MB_V1.5
Software Version	N/A
Antenna Designation	Integrated Antenna
Antenna Gain	0.8dBi
Power Supply	DC3.7V by Built-in Li-ion Battery

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	1	2412 MHZ
	2	2417 MHZ
	3	2422 MHZ
	4	2427 MHZ
	5	2432 MHZ
	6	2437 MHZ
	7	2442 MHZ
	8	2447 MHZ
	9	2452 MHZ
	10	2457 MHZ
	11	2462 MHZ

Note: For 20MHZ bandwidth system use Channel 1 to Channel 11
For 40MHZ bandwidth system use Channel 3 to Channel 9

2.3. IEEE 802.11N MODULATION SCHEME

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Data rate(Mbps)	
									800nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval

2.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ADN6S42** filing to comply with the FCC Part 15 requirements.

2.5. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4 (2003).
Radiated testing was performed at an antenna to EUT distance 3 meters.
Others testing (listed at item 5.3) was performed according to the procedures in FCC Part 15.247 rules KDB 558074 D01 DTS Meas Guidance v03r02.

2.6. SPECIAL ACCESSORIES

Refer to section 5.2.

2.7. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 2.75dB
Radiated measurement: +/- 3.2dB

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal operating
Note: Transmit by 802.11b with Date rate (1/2/5.5/11) Transmit by 802.11g with Date rate (6/9/12/18/24/36/48/54) Transmit by 802.11n (20MHz) with Date rate (6.5/13/19.5/26/39/52/58.5/65) Transmit by 802.11n (40MHz) with Date rate (13.5/27/40.5/54/81/108/121.5/135)	

Note:

1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency Individually, and the eut is operating at its maximum duty cycle>or equal 98%
2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure:



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	3G Smart Phone	S42	FCCID:2ADN6S42	EUT
2	Adapter	GMT-050120A	DC5V / 1200mA	Accessory
3	Battery	S42	DC3.7V / 1400 mAh	Accessory
4	Earphone	S42	N/A	Accessory
5	USB Cable	S42	N/A	Accessory

Note: All the accessories have been used during the test in conduction emission test.

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Peak Output Power	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247	Conducted Spurious Emission	Compliant
§15.247	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Line Conduction Emission	Compliant

Note: The EUT received power from DC3.7V lithium battery.

6. TEST FACILITY

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.

ALL TEST EQUIPMENT LIST

Description	Manufacturer	Model	Cal. Date	Cal. Due
Power Probe	R&S	NRP-Z23	07/25/2014	07/24/2015
Power Meter	Agilent	N1911A	04/20/2014	04/20/2015
RF attenuator	N/A	RFA20db	N/A	N/A
Spectrum Analyzer	Agilent	E4440A	02/17/2014	02/16/2015
Amplifier	EM	EM30180	02/17/2014	02/16/2015
Horn Antenna	EM	EM-AH-10180	02/17/2014	02/16/2015
Horn Antenna	A.H. Systems Inc.	SAS-574	07/25/2014	07/24/2015
EMI Test Receiver	Rohde & Schwarz	ESCI	07/25/2014	07/24/2015
WIDEBAND REQUENCY ANTENNA	SCHWARZBECK	VULB9168	08/16/2014	08/15/2015
Loop Antenna	A.H.	SAS-526B	05/10/2014	05/09/2015
LISN	R&S	ESH3-Z5	07/25/2014	07/24/2015
Radiation Cable 1	Sat	RE1	06/04/2014	06/03/2015
Radiation Cable 2	Sat	RE2	06/04/2014	06/03/2015
Conduction Cable	Sat	CE1	06/04/2014	06/03/2015

7. PEAK OUTPUT POWER

7.1. MEASUREMENT PROCEDURE

For peak power test:

1. Use a direct connection between the antenna port of the transmitter and the power meter, through suitable attenuation
2. Set the bandwidth of the power meter is 40MHz
3. Record the peak value

For average power test:

1. Connect EUT RF output port to power probe through an RF attenuator.
2. Connect the power probe to the PC.
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Record the maximum power from the software.
5. The maximum peak power shall be less 1 Watt (30dBm).

Note：The EUT was tested according to KDB 558074v03r02 for compliance to FCC 47CFR 15.247 requirements.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

PEAK POWER TEST SETUP



AVERAGE POWER SETUP



7.3. LIMITS AND MEASUREMENT RESULT

TEST ITEM	PEAK POWER
TEST MODE	802.11b with data rate 1

LIMITS AND MEASUREMENT RESULT				
Frequency (GHz)	Average Power (dBm)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	9.47	11.45	30	Pass
2.437	9.4	11.38	30	Pass
2.462	9.36	11.34	30	Pass

TEST ITEM	PEAK POWER
TEST MODE	802.11g with data rate 6

LIMITS AND MEASUREMENT RESULT				
Frequency (GHz)	Average Power (dBm)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	7.58	9.56	30	Pass
2.437	7.5	9.48	30	Pass
2.462	7.39	9.37	30	Pass

TEST ITEM	PEAK POWER
TEST MODE	802.11n 20 with data rate 6.5

LIMITS AND MEASUREMENT RESULT				
Frequency (GHz)	Average Power (dBm)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	7.48	9.46	30	Pass
2.437	7.44	9.42	30	Pass
2.462	7.36	9.34	30	Pass

TEST ITEM	PEAK POWER
TEST MODE	802.11n 40 with data rate 13.5

LIMITS AND MEASUREMENT RESULT				
Frequency (GHz)	**Average Power (dBm)**	**Peak Power (dBm)**	**Applicable Limits (dBm)**	**Pass or Fail**
2.422	4.61	6.59	30	Pass
2.437	4.5	6.48	30	Pass
2.452	4.41	6.39	30	Pass

8. 6DB BANDWIDTH

8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW≥3×RBW.
4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



8.3. LIMITS AND MEASUREMENT RESULTS

`	Channel	6dB Bandwidth [MHz]	OBW [MHz]	Verdict
11B	LCH	9.59	12.88	PASS
11B	MCH	9.58	12.85	PASS
11B	HCH	9.13	12.85	PASS
11G	LCH	15.49	16.36	PASS
11G	MCH	15.66	16.40	PASS
11G	HCH	13.83	16.37	PASS
11N20SISO	LCH	15.83	17.52	PASS
11N20SISO	MCH	16.95	17.55	PASS
11N20SISO	HCH	13.92	17.54	PASS
11N40SISO	LCH	34.72	35.76	PASS
11N40SISO	MCH	33.93	35.79	PASS
11N40SISO	HCH	35.28	35.79	PASS

Test Graph

Graphs	
11B/LCH	
11B/MCH	
11B/HCH	

11G/LCH	
11G/MCH	
11G/HCH	

11N20SISO/LCH	
11N20SISO/MCH	
11N20SISO/HCH	

11N40SISO/LCH	
11N40SISO/MCH	
11N40SISO/HCH	

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW＞RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW＞RBW) are conform to the requirement.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2.

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	**Measurement Result**	
	Test Data	**Criteria**
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS
	At least -20dBc than the limit Specified on the TOP Channel	PASS

Test Graph

11B_LCH_Graphs	
Pref/11B/LCH	
Puw/11B/LCH	


Agilent
R L
Freq/Channel
Mkr1 7.235 GHz
Ref 10 dBm
#Atten 30 dB
-43.10 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-3.2
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
File name error
Agilent
R L
Freq/Channel
Mkr1 14.402 GHz
Ref 10 dBm
#Atten 30 dB
-42.94 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-3.2
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
File name error
Agilent
R L
Freq/Channel
Mkr1 18.326 GHz
Ref 10 dBm
#Atten 32 dB
-40.85 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-3.2
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 15.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 20.000 GHz
Sweep 12.8 ms (8001 pts)
Center Freq
17.5000000 GHz
Start Freq
15.0000000 GHz
Stop Freq
20.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
File name error

	

11B_MCH_Graphs	
Pref/11B/MCH	
Puw/11B/MCH	


Agilent
R L
Freq/Channel
Mkr1 2.382 GHz
Ref 10 dBm
#Atten 30 dB
-53.42 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-11.5
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.400 GHz
Sweep 133.9 ms (8001 pts)
Center Freq
1.70000000 GHz
Start Freq
1.00000000 GHz
Stop Freq
2.40000000 GHz
CF Step
140.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error
Agilent
R L
Freq/Channel
Mkr1 7.311 GHz
Ref 10 dBm
#Atten 30 dB
-43.21 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-1.5
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error
Agilent
R L
Freq/Channel
Mkr1 13.990 GHz
Ref 10 dBm
#Atten 30 dB
-43.39 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-1.5
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error



11B_HCH_Graphs	
Pref/11B/HCH	

Puw/11B/HCH	

Agilent
R L
Freq/Channel
Mkr1 501.3 MHz
Ref 10 dBm
#Atten 30 dB
-54.05 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-11.0
dBm
LgAv
W1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
515.000000 MHz
Start Freq
30.0000000 MHz
Stop Freq
1.00000000 GHz
CF Step
97.0000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.000 0 GHz
Sweep 92.8 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 2.400 GHz
Ref 10 dBm
#Atten 30 dB
-55.64 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-11.0
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
1.70000000 GHz
Start Freq
1.00000000 GHz
Stop Freq
2.40000000 GHz
CF Step
140.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.400 GHz
Sweep 133.9 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 2.485 GHz
Ref 10 dBm
#Atten 30 dB
-41.33 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-1.0
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
File name error


Agilent
R L
Freq/Channel
Mkr1 13.354 GHz
Ref 10 dBm
#Atten 30 dB
-43.32 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-1.0
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
File name error
Agilent
R T
Freq/Channel
Mkr1 16.077 GHz
Ref 10 dBm
#Atten 32 dB
-40.40 dBm
Center Freq
17.5000000 GHz
Start Freq
15.0000000 GHz
Stop Freq
20.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 15.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 20.000 GHz
Sweep 12.8 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 24.509 GHz
Ref 10 dBm
#Atten 32 dB
-37.28 dBm
Center Freq
22.5000000 GHz
Start Freq
20.0000000 GHz
Stop Freq
25.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 20.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 25.000 GHz
Sweep 12.8 ms (8001 pts)
File name error

11G_LCH_Graphs	
Pref/11G/LCH	
Puw/11G/LCH	 


Agilent
R L
Freq/Channel
Mkr1 6.795 GHz
Ref 10 dBm
#Atten 30 dB
-45.35 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-9.1
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 14.122 GHz
Ref 10 dBm
#Atten 30 dB
-43.56 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-9.1
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 19.711 GHz
Ref 10 dBm
#Atten 32 dB
-39.70 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-9.1
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
17.5000000 GHz
Start Freq
15.0000000 GHz
Stop Freq
20.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 15.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 20.000 GHz
Sweep 12.8 ms (8001 pts)
File name error



11G_MCH_Graphs	
Pref/11G/MCH	
Puw/11G/MCH	


Agilent
R L
Freq/Channel
Mkr1 2.394 GHz
Ref 10 dBm
#Atten 30 dB
-50.04 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-15.4
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
1.70000000 GHz
Start Freq
1.00000000 GHz
Stop Freq
2.40000000 GHz
CF Step
140.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.400 GHz
Sweep 133.9 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 2.492 GHz
Ref 10 dBm
#Atten 30 dB
-41.14 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-5.4
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 14.708 GHz
Ref 10 dBm
#Atten 30 dB
-42.70 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-5.4
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
File name error



11G_HCH_Graphs	
Pref/11G/HCH	

Puw/11G/HCH	

Agilent
R L
Freq/Channel
Mkr1 466.5 MHz
Ref 10 dBm
#Atten 30 dB
-61.15 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-17.9
dBm
LgAv
W1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
515.000000 MHz
Start Freq
30.0000000 MHz
Stop Freq
1.00000000 GHz
CF Step
97.0000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.000 0 GHz
Sweep 92.8 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 2.382 GHz
Ref 10 dBm
#Atten 30 dB
-53.60 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-17.9
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
1.70000000 GHz
Start Freq
1.00000000 GHz
Stop Freq
2.40000000 GHz
CF Step
140.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.400 GHz
Sweep 133.9 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 2.485 GHz
Ref 10 dBm
#Atten 30 dB
-26.81 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-7.9
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
File name error


Agilent
R L
Freq/Channel
Mkr1 14.383 GHz
Ref 10 dBm
#Atten 30 dB
-42.11 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-7.9
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 18.839 GHz
Ref 10 dBm
#Atten 32 dB
-40.46 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-7.9
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
17.5000000 GHz
Start Freq
15.0000000 GHz
Stop Freq
20.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 15.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 20.000 GHz
Sweep 12.8 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 24.876 GHz
Ref 10 dBm
#Atten 32 dB
-36.75 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-7.9
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
22.5000000 GHz
Start Freq
20.0000000 GHz
Stop Freq
25.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 20.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 25.000 GHz
Sweep 12.8 ms (8001 pts)
File name error

11N20SISO_LCH_Graphs	
Pref/11N20SISO/LCH	
/11N20SISO/LCH	 


Agilent
R L
Freq/Channel
Mkr1 7.143 GHz
Ref 10 dBm
#Atten 30 dB
-45.08 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-8.7
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 14.507 GHz
Ref 10 dBm
#Atten 30 dB
-43.17 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-8.7
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 15.574 GHz
Ref 10 dBm
#Atten 32 dB
-40.35 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-8.7
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
17.5000000 GHz
Start Freq
15.0000000 GHz
Stop Freq
20.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 15.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 20.000 GHz
Sweep 12.8 ms (8001 pts)
File name error

	

11N20SISO_MCH_Graphs	
Pref/11N20SISO/MCH	
Puw/11N20SISO/MCH	


Agilent
R L
Freq/Channel
Mkr1 2.395 GHz
Ref 10 dBm
#Atten 30 dB
-49.76 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-16.8
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.400 GHz
Sweep 133.9 ms (8001 pts)
Center Freq
1.70000000 GHz
Start Freq
1.00000000 GHz
Stop Freq
2.40000000 GHz
CF Step
140.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error
Agilent
R L
Freq/Channel
Mkr1 2.487 GHz
Ref 10 dBm
#Atten 30 dB
-42.79 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-6.8
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error
Agilent
R L
Freq/Channel
Mkr1 13.845 GHz
Ref 10 dBm
#Atten 30 dB
-43.38 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-6.8
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error



11N20SISO_HCH_Graphs	
Pref/11N20SISO/HCH	

Puw/11N20SISO/HCH	


Agilent
R L
Freq/Channel
Mkr1 13.554 GHz
Ref 10 dBm
#Atten 30 dB
-42.73 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-7.0
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error
Agilent
R L
Freq/Channel
Mkr1 17.253 GHz
Ref 10 dBm
#Atten 32 dB
-41.08 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-7.0
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 15.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 20.000 GHz
Sweep 12.8 ms (8001 pts)
Center Freq
17.5000000 GHz
Start Freq
15.0000000 GHz
Stop Freq
20.0000000 GHz
CF Step
500.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error
Agilent
R L
Freq/Channel
Mkr1 24.859 GHz
Ref 10 dBm
#Atten 32 dB
-35.98 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-7.0
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 20.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 25.000 GHz
Sweep 12.8 ms (8001 pts)
Center Freq
22.5000000 GHz
Start Freq
20.0000000 GHz
Stop Freq
25.0000000 GHz
CF Step
500.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error

11N40SISO_LCH_Graphs	
Pref/11N40SISO/LCH	
Puw/11N40SISO/LCH	 


Agilent
R L
Freq/Channel
Mkr1 2.492 GHz
Ref 10 dBm
#Atten 30 dB
-38.25 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-12.8
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
File name error
Agilent
R L
Freq/Channel
Mkr1 14.512 GHz
Ref 10 dBm
#Atten 30 dB
-42.85 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-12.8
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
File name error
Agilent
R L
Freq/Channel
Mkr1 15.146 GHz
Ref 10 dBm
#Atten 32 dB
-40.70 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-12.8
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 15.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 20.000 GHz
Sweep 12.8 ms (8001 pts)
Center Freq
17.5000000 GHz
Start Freq
15.0000000 GHz
Stop Freq
20.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
File name error

	

11N40SISO_MCH_Graphs	
Pref/11N40SISO/MCH	
Puw/11N40SISO/MCH	


Agilent
R T
Freq/Channel
Mkr1 2.398 GHz
Ref 10 dBm
#Atten 30 dB
-38.34 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-20.5
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 1.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.400 GHz
Sweep 133.9 ms (8001 pts)
Center Freq
1.70000000 GHz
Start Freq
1.00000000 GHz
Stop Freq
2.40000000 GHz
CF Step
140.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error
Agilent
R L
Freq/Channel
Mkr1 2.485 GHz
Ref 10 dBm
#Atten 30 dB
-27.49 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-10.5
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 2.484 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 7.500 GHz
Sweep 8.533 ms (8001 pts)
Center Freq
4.99175000 GHz
Start Freq
2.48350000 GHz
Stop Freq
7.50000000 GHz
CF Step
501.650000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error
Agilent
R L
Freq/Channel
Mkr1 14.513 GHz
Ref 10 dBm
#Atten 30 dB
-41.96 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-10.5
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File name error

	

11N40SISO_HCH_Graphs	
Pref/11N40SISO/HCH	

Puw/11N40SISO/HCH	


Agilent
R L
Freq/Channel
Mkr1 13.789 GHz
Ref 10 dBm
#Atten 30 dB
-43.54 dBm
#Peak
Log
10
dB/
Offst
1.4
dB
Dl
-11.9
dBm
LgAv
M1 S2
S3 FS
£(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
7.50000000 GHz
Stop Freq
15.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 7.500 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 15.000 GHz
Sweep 15.47 ms (8001 pts)
File name error
Agilent
R T
Freq/Channel
Mkr1 16.308 GHz
Ref 10 dBm
#Atten 32 dB
-40.69 dBm
Center Freq
17.5000000 GHz
Start Freq
15.0000000 GHz
Stop Freq
20.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 15.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 20.000 GHz
Sweep 12.8 ms (8001 pts)
File name error
Agilent
R L
Freq/Channel
Mkr1 24.859 GHz
Ref 10 dBm
#Atten 32 dB
-36.01 dBm
Center Freq
22.5000000 GHz
Start Freq
20.0000000 GHz
Stop Freq
25.0000000 GHz
CF Step
500.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 20.000 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 25.000 GHz
Sweep 12.8 ms (8001 pts)
File name error

10. MAXIMUM CONDUCTED OUTPUT PEAK POWER SPECTRAL DENSITY

10.1 MEASUREMENT PROCEDURE

(1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator

(2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.

(3). Set SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 10.2 was used in this testing.

10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 8.2.

10.3 MEASUREMENT EQUIPMENT USED

Refer To Section 6.

10.4 LIMITS AND MEASUREMENT RESULT

Mode	Channel	Meas.Level [dBm]	Av.PSD [dBm]	Verdict
11B	LCH	6.79	6.877	PASS
11B	MCH	8.49	8.576	PASS
11B	HCH	8.64	8.727	PASS
11G	LCH	1.14	1.655	PASS
11G	MCH	4.15	4.665	PASS
11G	HCH	1.6	2.123	PASS
11N20SISO	LCH	1.1	1.658	PASS
11N20SISO	MCH	3.63	4.188	PASS
11N20SISO	HCH	2.93	3.488	PASS
11N40SISO	LCH	-3.18	-2.133	PASS
11N40SISO	MCH	-0.47	0.574	PASS
11N40SISO	HCH	-2.07	-1.026	PASS

Test Graph

Graphs	
11B/LCH	
11B/MCH	
11B/HCH	

11G/LCH	
11G/MCH	
11G/HCH	

11N20SISO/LCH	
11N20SISO/MCH	
11N20SISO/HCH	

11N40SISO/LCH	
11N40SISO/MCH	
11N40SISO/HCH	

11. RADIATED EMISSION

11.1. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

11.2. TEST SETUP

RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,
the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: 3G Smart Phone
M/N: S42
Mode: Low Channel TX
Note:

Polarization: *Horizontal*
Power: AC 120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		30.0000	21.12	-1.00	20.12	40.00	-19.88	peak			
2		114.0667	16.26	11.45	27.71	43.50	-15.79	peak			
3	*	169.0333	15.77	13.41	29.18	43.50	-14.32	peak			
4		382.4333	3.69	18.95	22.64	46.00	-23.36	peak			
5		569.9667	0.32	22.98	23.30	46.00	-22.70	peak			
6		718.7000	1.91	25.73	27.64	46.00	-18.36	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Vertical



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: 3G Smart Phone
M/N: S42
Mode: Low Channel TX
Note:

Polarization: *Vertical*
Power: AC 120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	41.3167	24.70	8.81	33.51	40.00	-6.49	peak			
2		151.2500	7.09	15.27	22.36	43.50	-21.14	peak			
3		190.0500	13.38	11.52	24.90	43.50	-18.60	peak			
4		227.2333	5.28	11.67	16.95	46.00	-29.05	peak			
5		537.6332	-0.68	22.15	21.47	46.00	-24.53	peak			
6		797.9167	0.92	27.29	28.21	46.00	-17.79	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHZ	Antenna	Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: 3G Smart Phone
M/N: S42
Mode: Middle Channel TX
Note:

Polarization: *Horizontal*
Power: AC 120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		114.0667	15.31	11.45	26.76	43.50	-16.74	peak			
2	*	170.6500	16.78	13.06	29.84	43.50	-13.66	peak			
3		338.7833	1.18	17.99	19.17	46.00	-26.83	peak			
4		468.1167	1.34	20.79	22.13	46.00	-23.87	peak			
5		689.6000	0.38	24.91	25.29	46.00	-20.71	peak			
6		899.7667	2.31	28.60	30.91	46.00	-15.09	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHZ	Antenna	Vertical



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: 3G Smart Phone
M/N: S42
Mode: Middle Channel TX
Note:

Polarization: *Vertical*
Power: AC 120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	41.3167	24.62	8.81	33.43	40.00	-6.57	peak			
2		154.4832	8.66	15.29	23.95	43.50	-19.55	peak			
3		264.4166	5.71	14.34	20.05	46.00	-25.95	peak			
4		346.8667	3.29	18.53	21.82	46.00	-24.18	peak			
5		742.9500	-0.86	26.43	25.57	46.00	-20.43	peak			
6		891.6833	2.30	28.39	30.69	46.00	-15.31	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHZ	Antenna	Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: 3G Smart Phone
M/N: S42
Mode: High Channel TX
Note:

Polarization: *Horizontal*
Power: AC 120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		114.0667	15.74	11.45	27.19	43.50	-16.31	peak			
2	*	170.6500	16.39	13.06	29.45	43.50	-14.05	peak			
3		186.8167	14.08	11.39	25.47	43.50	-18.03	peak			
4		350.1000	1.90	18.74	20.64	46.00	-25.36	peak			
5		518.2333	1.65	21.62	23.27	46.00	-22.73	peak			
6		773.6667	1.19	26.96	28.15	46.00	-17.85	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHZ	Antenna	Vertical



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: 3G Smart Phone
M/N: S42
Mode: High Channel TX
Note:

Polarization: *Vertical*
Power: AC 120V/60Hz
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	41.3167	24.70	8.81	33.51	40.00	-6.49	peak			
2		94.6667	19.12	1.42	20.54	43.50	-22.96	peak			
3		190.0500	12.67	11.52	24.19	43.50	-19.31	peak			
4		264.4166	5.28	14.34	19.62	46.00	-26.38	peak			
5		586.1332	0.63	22.66	23.29	46.00	-22.71	peak			
6		772.0500	0.79	26.93	27.72	46.00	-18.28	peak			

RESULT: PASS
Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHZ

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: 3G Smart Phone
M/N: S42
Mode: 802.11b Low Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1283.333	58.88	-15.47	43.41	74.00	-30.59	peak			
2	*	2412.000	114.28	-9.67	104.61	74.00	30.61	peak			
3		4008.333	48.06	-4.78	43.28	74.00	-30.72	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Vertical



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: 3G Smart Phone
M/N: S42
Mode: 802.11b Low Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1658.333	56.08	-13.71	42.37	74.00	-31.63	peak			
2	*	2412.000	114.57	-9.67	104.90	74.00	30.90	peak			
3		4625.000	45.18	-2.78	42.40	74.00	-31.60	peak			

RESULT: PASS

Note: The other modes radiation emissions have more than 20dB margin.

All modes radiation emission from 6GHz to 25GHz at least have 20dB margin.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

12. BAND EDGE EMISSION

12.1. MEASUREMENT PROCEDURE

1)Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting

2)Conducted Emissions at the bang edge

a)The transmitter output was connected to the spectrum analyzer

b)Set RBW=100kHz,VBW=300kHz

c)Suitable frequency span including 100kHz bandwidth from band edge

12.2. TEST SET-UP

Radiated same as 11.2

Conducted set up



12.3. Radiated Test Result

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: 3G Smart Phone
M/N: S42
Mode: 802.11b Low Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2352.733	52.38	-9.73	42.65	74.00	-31.35	peak			
2		2390.000	52.90	-9.69	43.21	74.00	-30.79	peak			
3	*	2412.000	114.36	-9.67	104.69	74.00	30.69	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Vertical



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: 3G Smart Phone
M/N: S42
Mode: 802.11b Low Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2373.267	53.16	-9.71	43.45	74.00	-30.55	peak			
2		2390.000	53.27	-9.69	43.58	74.00	-30.42	peak			
3	*	2412.000	114.58	-9.67	104.91	74.00	30.91	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: 3G Smart Phone
M/N: S42
Mode: 802.11b High Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2462.000	114.39	-9.61	104.78	74.00	30.78	peak			
2		2483.500	55.81	-9.59	46.22	74.00	-27.78	peak			
3		2561.600	53.30	-9.42	43.88	74.00	-30.12	peak			

RESULT: PASS

EUT	3G Smart Phone	Model Name	S42
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Vertical



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: 3G Smart Phone
M/N: S42
Mode: 802.11b High Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2462.000	114.42	-9.61	104.81	74.00	30.81	peak			
2		2483.500	57.72	-9.59	48.13	74.00	-25.87	peak			
3		2543.733	52.41	-9.46	42.95	74.00	-31.05	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

12.4. Conducted Test Result

Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
11B	LCH	7.06	-29.78	-12.94	PASS
11B	HCH	9.55	-46.23	-10.45	PASS
11G	LCH	1.02	-34.94	-18.98	PASS
11G	HCH	2.41	-39.29	-17.59	PASS
11N20SISO	LCH	-0.07	-35.75	-20.07	PASS
11N20SISO	HCH	1.83	-37.42	-18.17	PASS
11N40SISO	LCH	-2.62	-39.01	-22.62	PASS
11N40SISO	HCH	-1.49	-35.92	-21.49	PASS

Test Graph

Graphs	
11B/LCH	
11B/HCH	
11G/LCH	

11G/HCH	
11N20SISO/LCH	
11N20SISO/HCH	

11N40SISO/LCH	
11N40SISO/HCH	

13. FCC LINE CONDUCTED EMISSION TEST

13.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION TEST LINE 1-L



Site: Conduction
Limit: FCC Class B Conduction(QP)
EUT: 3G Smart Phone
M/N: S42
Mode: Normal Operating(WIFI)
Note:

Phase: *L1*
Power: AC 120V/60Hz

Temperature: 26
Humidity: 60 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1860	30.19		10.07	10.20	40.39		20.27	64.21	54.21	-23.82	-33.94	P	
2	0.2420	25.08		12.59	10.26	35.34		22.85	62.02	52.02	-26.68	-29.17	P	
3	0.4500	25.88		10.86	10.37	36.25		21.23	56.87	46.87	-20.62	-25.64	P	
4	1.0859	20.37		6.43	10.37	30.74		16.80	56.00	46.00	-25.26	-29.20	P	
5	4.0620	25.49		10.80	10.40	35.89		21.20	56.00	46.00	-20.11	-24.80	P	
6	17.0020	30.63		16.94	10.13	40.76		27.07	60.00	50.00	-19.24	-22.93	P	

Line Conducted Emission Test Line 2-N



Site: Conduction
Limit: FCC Class B Conduction(QP)
EUT: 3G Smart Phone
M/N: S42
Mode: Normal Operating(WIFI)
Note:

Phase: *N*
Power: AC 120V/60Hz

Temperature: 26
Humidity: 60 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1660	33.81		16.29	10.18	43.99		26.47	65.15	55.15	-21.16	-28.68	P	
2	0.2100	26.66		12.08	10.23	36.89		22.31	63.20	53.20	-26.31	-30.89	P	
3	0.9060	24.97		11.44	10.41	35.38		21.85	56.00	46.00	-20.62	-24.15	P	
4	3.7620	25.56		8.23	10.47	36.03		18.70	56.00	46.00	-19.97	-27.30	P	
5	4.7780	25.49		9.72	10.23	35.72		19.95	56.00	46.00	-20.28	-26.05	P	
6	16.6860	29.35		13.24	10.12	39.47		23.36	60.00	50.00	-20.53	-26.64	P	

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP

FCC RADIATED EMISSION TEST SETUP



APPENDIX B: PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT

TOP VIEW OF EUT

BOTTOM VIEW OF EUT

FRONT VIEW OF EUT

BACK VIEW OF EUT

LEFT VIEW OF EUT

RIGHT VIEW OF EUT

BT&WIF Antenna

OPEN VIEW OF EUT-1

GSM & WCDMA Antenna

OPEN VIEW OF EUT-2

OPEN VIEW OF EUT-3

INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



----END OF REPORT----