RF TEST REPORT

SIEMIC
GLOBAL TESTING & CERTIFICATIONS
YOUR CHOICE FOR- TCB FCB CB NB CAB RCB

Report No.: 15070121-FCC-R3 Rev2

Supersede Report No.: 15070121-FCC-R3 Rev1

Applicant	Worldlinks Communications, L.L.C.
Product Name	PHONE
Model No.	R50S
Serial No.	N/A
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2009
Test Date	March 02 to March 13, 2015
Issue Date	March 21, 2015
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Winnie.Zhang	Alex.Liu	
Winne Zhang **Test Engineer**	**Alex Liu** **Checked By**	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 5

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 6

5. TEST SUMMARY 8

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 9

6.1 ANTENNA REQUIREMENT 9

6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH 10

6.3 MAXIMUM OUTPUT POWER 16

6.4 POWER SPECTRAL DENSITY 20

6.5 BAND-EDGE & UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS 24

6.6 AC POWER LINE CONDUCTED EMISSIONS 30

6.7 RADIATED SPURIOUS EMISSIONS 34

ANNEX A. TEST INSTRUMENT 38

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 39

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 45

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 48

ANNEX E. DECLARATION OF SIMILARITY 49

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070121-FCC-R3	Original	NONE	March 13, 2015
15070121-FCC-R3 Rev1	Version 1	Update Battery Information	March 17, 2015
15070121-FCC-R3 Rev2	Version 2	Added LTE Band 7 Information	March 21, 2015

2. Customer information

Applicant Name	Worldlinks Communications, L.L.C.
Applicant Add	270 Center Drive Suite 230, Vernon Hills, IL. 60061
Manufacturer	Shenzhen VSDREAM Technology Co., Ltd
Manufacturer Add	4F, Headquarters Building, zhonghaixin Science&Technology Park, Bulan Road, Buji Ave, Longgang Dist., Shenzhen, Guangdong, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	PHONE
Main Model:	R50S
Serial Model:	N/A
Date EUT received:	February 12, 2015
Test Date(s):	March 02 to March 13, 2015
Equipment Category :	DTS
Antenna Gain:	GSM850: 0.13 dBi PCS1900: 0.77 dBi UMTS-FDD Band 5: 0.11 dBi UMTS-FDD Band 2: 0.73 dBi UMTS-FDD Band 4: 0.52 dBi LTE Band 2: 0.81 dBi LTE Band 4: 0.55 dBi LTE Band 5: 0.27 dBi LTE Band 7: 1.01 dBi LTE Band 17: -1.23 dBi Bluetooth/BLE/WIFI: 1.15 dBi
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band 5 TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band 2 TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz

	UMTS-FDD Band 4 TX :1712.4 ~ 1752.6 MHz; RX : 2112.4 ~ 2152.6 MHz LTE Band 2 TX: 1852.5 ~ 1907.5 MHz; RX : 1932.5 ~ 1987.5 MHz LTE Band 4 TX: 1712.5 ~ 1752.5 MHz; RX : 2112.5 ~ 2152.5 MHz LTE Band 5 TX: 826.5 ~ 846.5 MHz; RX : 871.5 ~ 891.5 MHz LTE Band 7 TX: 2502.5 ~ 2567.5 MHz; RX : 2622.5 ~ 2687.5 MHz LTE Band 17 TX: 706.5 ~ 713.5 MHz; RX : 736.5 ~ 743.5 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz
Max. Output Power:	802.11b: 9.35 dBm 802.11g: 9.38 dBm 802.11n(20M): 8.72 dBm 802.11n(40M): 7.72 dBm
Port:	Power Port, Earphone Port, USB Port
Input Power:	Battery: Model: 5MQ2 Spec: 3.7V 2000mAh Limited charger voltage: 4.2V Adapter: Model: KA25-0501000US Input: AC 100-240V; 50/60Hz 0.25A Output: DC 5.0V; 1000mA
Trade Name :	REDDOTMOBILE
GPRS/EGPRS Multi-slot class	8/10/12
FCC ID:	2ADNIR50S

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	**Description**	**Uncertainty**
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.
The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:
A permanently attached PIFA antenna for Bluetooth/BLE/WIFI, the gain is 1.15 dBi.
A permanently attached PIFA antenna for GSM/UMTS/LTE, the gain is 0.13 dBi for GSM850, 0.77 dBi for PCS1900;
0.11 dBi for UMTS-FDD Band 5, 0.73 dBi for UMTS-FDD Band 2, 0.52 dBi for UMTS-FDD Band 4;
0.81 dBi for LTE Band 2, 0.55 dBi for LTE Band 4, 0.27 dBi for LTE Band 5, 1.01 dBi for LTE Band 7, -1.23 dBi for LTE Band 17.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	23°C
Relative Humidity	60%
Atmospheric Pressure	1005mbar
Test date :	March 02, 2015
Tested By :	Winne Zhang

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW≥ 500kHz; 20dB BW≥ 500kHz;	☑
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	☑
Test Setup			
Test Procedure	558074 D01 DTS MEAS Guidance v03r02, 8.1 DTS bandwidth 6dB bandwidth a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) ≥ 3 × RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the freq uencies associated with the two outermost amplitude points (upper and lower fr equencies) that are attenuated by 6 dB relative to the maximum level measure d in the fundamental emission. 20dB bandwidth C63.10 Occupied Bandwidth (OBW=20dB bandwidth) 1. Set RBW = 1%-5% OBW. 2. Set the video bandwidth (VBW) ≥ 3 x RBW. 3. Set the span range between 2 times and 5 times of the OBW. 4. Sweep time=Auto, Detector=PK, Trace=Max hold. 5. Once the reference level is established, the equipment is conditioned with t ypical modulating signals to produce the worst-		

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.580	14.287	≥ 0.5
	Mid	2437	9.174	14.325	≥ 0.5
	High	2462	9.551	13.945	≥ 0.5
802.11g	Low	2412	15.546	18.883	≥ 0.5
	Mid	2437	15.654	19.166	≥ 0.5
	High	2462	15.686	18.874	≥ 0.5
802.11n (20M)	Low	2412	16.113	19.373	≥ 0.5
	Mid	2437	17.348	19.421	≥ 0.5
	High	2462	16.134	19.179	≥ 0.5
802.11n (40M)	Low	2422	35.337	38.068	≥ 0.5
	Mid	2437	35.428	38.457	≥ 0.5
	High	2452	35.298	37.906	≥ 0.5

Test Plots

6dB Bandwidth measurement result



802.11b 6dB Bandwidth - Low CH 2412



802.11b 6dB Bandwidth - Mid CH 2437



802.11b 6dB Bandwidth - High CH 2462



802.11g 6dB Bandwidth - Low CH 2412



802.11g 6dB Bandwidth - Mid CH 2437



802.11g 6dB Bandwidth - High CH 2462



802.11n20 6dB Bandwidth - Low CH 2412



802.11n20 6dB Bandwidth - Mid CH 2437



802.11n20 6dB Bandwidth - High CH 2462



802.11n40 6dB Bandwidth - Low CH 2422



802.11n40 6dB Bandwidth - Mid CH 2437



802.11n40 6dB Bandwidth - High CH 2452

20 dB Bandwidth measurement result



802.11b 20dB Bandwidth - Low CH 2412



802.11b 20dB Bandwidth - Mid CH 2437



802.11b 20dB Bandwidth - High CH 2462



802.11g 20dB Bandwidth - Low CH 2412



802.11g 20dB Bandwidth - Mid CH 2437



802.11g 20dB Bandwidth - High CH 2462



802.11n20 20dB Bandwidth - Low CH 2412



802.11n20 20dB Bandwidth - Mid CH 2437



802.11n20 20dB Bandwidth - High CH 2462



802.11n40 20dB Bandwidth - Low CH 2422



802.11n40 20dB Bandwidth - Mid CH 2437



802.11n40 20dB Bandwidth - High CH 2452

6.3 Maximum Output Power

Temperature	23°C
Relative Humidity	60%
Atmospheric Pressure	1005mbar
Test date :	March 02, 2015
Tested By :	Winne Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b)(2),RSS210(A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☐
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☐
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: ≤ 1 Watt	☑
Test Setup			
Test Procedure	558074 D01 DTS MEAS Guidance v03r02, 9.1.2 Integrated band power method Maximum output power measurement procedure - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW ≥ 3 x RBW. - d) Number of points in sweep ≥ 2 × span / RBW. (This gives bin-to-bin spacing ≤ RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable		

	triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to " free run" . - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument' s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Output Power measurement result

Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	8.22	30	Pass
		Mid	2437	**9.35**	30	Pass
		High	2462	9.02	30	Pass
	802.11g	Low	2412	8.25	30	Pass
		Mid	2437	8.83	30	Pass
		High	2462	**9.38**	30	Pass
	802.11n (20M)	Low	2412	7.61	30	Pass
		Mid	2437	7.55	30	Pass
		High	2462	**8.72**	30	Pass
	802.11n (40M)	Low	2422	5.07	30	Pass
		Mid	2437	**7.72**	30	Pass
		High	2452	6.27	30	Pass

Test Plots

The Average Power



802.11b - AV Output power - Low CH 2412



802.11b - AV Output power - Mid CH 2437



802.11b - AV Output power - High CH 2462



802.11g - AV Output power - Low CH 2412



802.11g - AV Output power - Mid CH 2437



802.11g - AV Output power - High CH 2462



Channel Power 7.61 dBm / 19.3730 MHz

Power Spectral Density -65.26 dBm/Hz

802.11n20 - AV Output power - Low CH 2412



Channel Power 8.72 dBm / 19.4210 MHz

Power Spectral Density -64.16 dBm/Hz

802.11n20 - AV Output power - Mid CH 2437



Channel Power 9.10 dBm / 19.1790 MHz

Power Spectral Density -63.73 dBm/Hz

802.11n20 - AV Output power - High CH 2462



Channel Power 5.07 dBm / 38.0680 MHz

Power Spectral Density -70.42 dBm/Hz

802.11n40 - AV Output power - Low CH 2422



Channel Power 7.72 dBm / 38.4570 MHz

Power Spectral Density -68.13 dBm/Hz

802.11n40 - AV Output power - Mid CH 2437



Channel Power 6.27 dBm / 37.9060 MHz

Power Spectral Density -69.63 dBm/Hz

802.11n40 - AV Output power - High CH 2452

6.4 Power Spectral Density

Temperature	23°C
Relative Humidity	60%
Atmospheric Pressure	1005mbar
Test date :	March 02, 2015
Tested By :	Winne Zhang

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	☑
Test Setup			
Test Procedure	558074 D01 DTS MEAS Guidance v03r02, 10.2 power spectral density method power spectral density measurement procedure - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz. - d) Set the VBW ≥ 3 × RBW. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD (dBm)	Limit (dBm)	Result
PSD	802.11b	Low	2412	-1.198	8	Pass
		Mid	2437	0.927	8	Pass
		High	2462	-1.357	8	Pass
	802.11g	Low	2412	-5.767	8	Pass
		Mid	2437	-4.897	8	Pass
		High	2462	-3.888	8	Pass
	802.11n (20M)	Low	2412	-5.904	8	Pass
		Mid	2437	-4.458	8	Pass
		High	2462	-3.896	8	Pass
	802.11n (40M)	Low	2422	-6.043	8	Pass
		Mid	2437	-3.858	8	Pass
		High	2452	-5.07	8	Pass

Test Plots

Power Spectral Density measurement result



PSD - Low CH 2412 - 802.11b



PSD - Mid CH 2437 – 802.11b



PSD - High CH 2462 - 802.11b



PSD - Low CH 2412 -802.11g



PSD - Mid CH 2437 – 802.11g



PSD - High CH 2462 - 802.11g



PSD - Low CH 2412 - 802.11n20



PSD - Mid CH 2437 – 802.11n20



PSD - High CH 2462 - 802.11n20



PSD - Low CH 2422 - 802.11n40



PSD - Mid CH 2437 – 802.11n40



PSD - High CH 2452 - 802.11n40

6.5 Band-Edge & Unwanted Emissions into Non-Restricted Frequency Bands

Temperature	21°C
Relative Humidity	68%
Atmospheric Pressure	1009mbar
Test date :	March 04 to March 13, 2015
Tested By :	Winne Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☑
Test Setup			
Test Procedure	Radiated Method Only - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge,		

	check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Plots

Band Edge measurement result



Band Edge, Left Side (Peak) - 802.11b

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11b

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11b



Band Edge, Right Side (Average) - 802.11b



Band Edge, Left Side (Peak) - 802.11g

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Peak) - 802.11g

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Average) - 802.11g

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Average) - 802.11g

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Peak) - 802.11n20

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n20

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Average) - 802.11n20

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Average) - 802.11n20

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Peak) - 802.11n40

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n40

Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Average) - 802.11n40

Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Average) - 802.11n40

Note: F1 is frequency 2483.5MHz

6.6 AC Power Line Conducted Emissions

Temperature	24°C
Relative Humidity	66%
Atmospheric Pressure	1007mbar
Test date :	March 03, 2015
Tested By :	Winne Zhang

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.207, RSS210 (A8.1)</td><td>a)</td><td>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.
<table>
<tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBμV)</th></tr>
<tr><th>QP</th><th>Average</th></tr>
<tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr>
<tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr>
<tr><td>5 ~ 30</td><td>60</td><td>50</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 

Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.
2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</td></tr>
</table>

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode:	Transmitting Mode



Test Data

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Factors (dB)
0.54	44.20	56.00	-11.80	40.28	46.00	-5.72	10.54
0.75	39.61	56.00	-16.39	35.57	46.00	-10.43	10.42
1.14	39.65	56.00	-16.35	37.78	46.00	-8.22	10.29
0.17	43.80	64.96	-21.16	38.80	54.96	-16.16	12.35
2.06	37.47	56.00	-18.53	32.39	46.00	-13.61	10.45
2.54	38.44	56.00	-17.56	35.37	46.00	-10.63	10.54

Test Mode:	Transmitting Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Factors (dB)
0.51	40.31	56.00	-15.69	31.79	46.00	-14.21	10.57
1.17	30.78	56.00	-25.22	17.61	46.00	-28.39	10.29
0.15	58.94	66.00	-7.06	35.33	56.00	-20.67	12.49
3.02	38.37	56.00	-17.63	28.33	46.00	-17.67	10.63
3.50	36.44	56.00	-19.56	26.59	46.00	-19.41	10.71
3.98	35.69	56.00	-20.31	24.90	46.00	-21.10	10.81

6.7 Radiated Spurious Emissions

Temperature	24°C
Relative Humidity	66%
Atmospheric Pressure	1007mbar
Test date :	March 03, 2015
Tested By :	Winne Zhang

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td rowspan="3">47CFR§15.247(d), RSS210 (A8.5)</td><td>a)</td><td>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges
<table>
<tr><th>Frequency range (MHz)</th><th>Field Strength (μV/m)</th></tr>
<tr><td>30 – 88</td><td>100</td></tr>
<tr><td>88 – 216</td><td>150</td></tr>
<tr><td>216 960</td><td>200</td></tr>
<tr><td>Above 960</td><td>500</td></tr>
</table></td><td>☑</td></tr>
<tr><td>b)</td><td>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required
☒ 20 dB down ☐ 30 dB down</td><td>☑</td></tr>
<tr><td>c)</td><td>or restricted band, emission must also comply with the radiated emission limits specified in 15.209</td><td>☑</td></tr>
</table>

Test Setup	
Procedure	1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode:	Transmitting Mode

(Below 1GHz)



Test Data

Vertical & Horizontal Polarity Plot @3m

Frequency (MHz)	Quasi Peak (dBµV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBµV/m)	Margin (dB)
46.92	33.99	0.00	V	145.00	-12.45	40.00	-6.01
50.68	35.22	195.00	V	111.00	-14.00	40.00	-4.78
207.24	27.96	109.00	H	102.00	-8.01	43.52	-15.56
203.86	27.00	249.00	H	138.00	-8.06	43.52	-16.52
214.70	24.42	245.00	H	158.00	-7.90	43.52	-19.10
59.39	23.64	202.00	V	110.00	-13.98	40.00	-16.36

Test Mode:	Transmitting Mode

(Above 1GHz)

Note: Other modes were verified, only the result of worst case basic rate mode was presented.

Mode: 802.11b

Low Channel (2412 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4824	28	AV	V	33.82	4.86	27.22	39.46	54	-14.54
4824	27.65	AV	H	33.82	4.86	27.22	39.11	54	-14.89
4824	42.71	PK	V	33.82	4.86	27.22	54.17	74	-19.83
4824	42.55	PK	H	33.82	4.86	27.22	54.01	74	-19.99

Middle Channel (2437 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4874	30.87	AV	V	33.86	4.86	26.52	43.07	54	-10.93
4874	31.37	AV	H	33.86	4.86	26.52	43.57	54	-10.43
4874	45.23	PK	V	33.86	4.86	26.52	57.43	74	-16.57
4874	45.02	PK	H	33.86	4.86	26.52	57.22	74	-16.78

High Channel (2462 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4924	39.26	AV	V	33.9	4.86	26.42	51.6	54	-2.4
4924	37.72	AV	H	33.9	4.86	26.42	50.06	54	-3.94
4924	50.49	PK	V	33.9	4.86	26.42	62.83	74	-11.17
4924	46.79	PK	H	33.9	4.86	26.42	59.13	74	-14.87

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/18/2014	09/17/2015	☑
Line Impedance	LI-125A	191106	09/26/2014	09/25/2015	☑
Line Impedance	LI-125A	191107	09/26/2014	09/25/2015	☑
LISN	ISN T800	34373	09/26/2014	09/25/2015	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☑
Transient Limiter	LIT-153	531118	09/02/2014	09/01/2015	☑
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/18/2014	09/17/2015	☑
Power Splitter	1#	1#	09/02/2014	09/01/2015	☑
DC Power Supply	E3640A	MY40004013	09/18/2014	09/17/2015	☑
Radiated Emissions					
EMI test receiver	ESL6	100262	09/18/2014	09/17/2015	☑
Positioning Controller	UC3000	MF780208282	11/20/2014	11/19/2015	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/02/2014	09/01/2015	☑
Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	09/02/2014	09/01/2015	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/22/2014	09/21/2015	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	☑
Universal Radio Communication Tester	CMU200	121393	09/26/2014	09/25/2015	☑

Annex B. EUT and Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package - Top View



Adapter - Front View

EUT - Front View



EUT - Rear View

EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1

Cover Off - Top View 2



Battery - Top View



Battery - Bottom View

LCD - Front View

LCD - Rear View



Mainborad With Shielding - Front View



Mainborad Without Shielding - Front View



Mainborad - Rear View



Connect borad - Front View



Connect borad - Rear View

GSM/PCS/UMTS-FDD/LTE Antenna View	BT/BLE/WIFI Antenna View

Annex B.iii. Photograph: Test Setup Photo

Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz



Radiated Spurious Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Annex C. iI. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
N/A	N/A	N/A	N/A	N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Annex E. DECLARATION OF SIMILARITY

N/A