S T S LAB

FCC TEST REPORT

Report No: STS1411077F04

Issued for

Genuis Partners Group Limited

Unit 04, 7/F Bright Way Tower No.33 Mong Kok Rd Kl,Hong Kong

Product Name:	**mobile phone**
Brand Name:	**N/A**
Model No.:	**G5006**
Series Model:	**N/A**
FCC ID:	**2ADO5G5006**
Test Standard:	**FCC Part 15.247**

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.
1/F A, Building 2, Zhuoke Science Park, Chongqing Road, Fuyong, Baoan District, Shenzhen, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com

TEST RESULT CERTIFICATION

Applicant's name ..... : Genuis Partners Group Limited

Address..... : Unit 04, 7/F Bright Way Tower No.33 Mong Kok Rd Kl,Hong Kong

Manufacture's Name..... : HengDaChuangXin Technology Limited

Address..... : Rm1910 South Block Futian Building,No.7,Tairan Rd,.Che Gongmiao Futian Dist.,Shenzhen ,China

Product description

Product name.....: mobile phone

Model and/or type reference : N/A

Serial Model .....: N/A

Standards ..... : FCC Part15.247

Test procedure ..... ANSI C63.10：2009

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of STS, thidocument may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test .....:

Date (s) of performance of tests.....: 22 Nov. 2014 ~30 Nov. 2014

Date of Issue .....: 02 Dec. 2014

Test Result.....: **Pass**

Testing Engineer : (Tony Liu)

Technical Manager : (Vita Li)

Authorized Signatory : (Bovey Yang)

TESTING CONSULING SOLUTION CERTIFICATION STS APPROVAL

Table of Contents Page

1. SUMMARY OF TEST RESULTS 5
1.1 TEST FACILITY 5
1.2 MEASUREMENT UNCERTAINTY 5
2. GENERAL INFORMATION 6
2.1 GENERAL DESCRIPTION OF EUT 6
2.2 DESCRIPTION OF TEST MODES 8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 11
3. EMC EMISSION TEST 12
3.1 CONDUCTED EMISSION MEASUREMENT 12
3.2 TEST PROCEDURE 13
3.3 TEST SETUP 13
3.4 EUT OPERATING CONDITIONS 13
3.5 TEST RESULTS 14
4. RADIATED EMISSION MEASUREMENT 16
4.1 RADIATED EMISSION LIMITS 16
4.2 TEST PROCEDURE 17
4.3 TEST SETUP 18
4.4 EUT OPERATING CONDITIONS 19
4.5 TEST RESULTS 20
4.6 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS) 26
5. CONDUCTED SPURIOUS EMISSIONS 27
5.1 REQUIREMENT 27
5.2 TEST PROCEDURE 27
5.3 TEST SETUP 27
5.4 EUT OPERATION CONDITIONS 27
5.5 TEST RESULTS 28
6. POWER SPECTRAL DENSITY TEST 31
6.1 APPLIED PROCEDURES / LIMIT 31
6.2 TEST PROCEDURE 31
6.3 TEST SETUP 31

Table of Contents Page

6.4 EUT OPERATION CONDITIONS 31
6.5 TEST RESULTS 32
7. BANDWIDTH TEST 34
7.1 APPLIED PROCEDURES / LIMIT 34
7.2 TEST PROCEDURE 34
7.3 TEST SETUP 34
7.4 EUT OPERATION CONDITIONS 34
7.5 TEST RESULTS 35
8. PEAK OUTPUT POWER TEST 37
8.1 APPLIED PROCEDURES / LIMIT 37
8.2 TEST PROCEDURE 37
8.3 TEST SETUP 37
8.4 EUT OPERATION CONDITIONS 37
8.5 TEST RESULTS 38
9. ANTENNA REQUIREMENT 40
9.1 STANDARD REQUIREMENT 40
9.2 EUT ANTENNA 40
10. EUT TEST PHOTO 41

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F, Building 2, Zhuoke Science Park, Chongqing Road, Fuyong, Baoan District, Shenzhen, China.

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y ± U**，where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	mobile phone
Trade Name	N/A
Model Name	G5006
Serial Model	N/A
Model Difference	N/A
Product Description	The EUT is a mobile phone Operation Frequency: 2402~2480 MHz Modulation Type: GFSK Radio Technology Bluetooth 4.0 Number Of Channel 40 Antenna Designation: Please see Note 3. Antenna Gain (dBi) 0 dbi
Frequency Bands	☒GSM 850 ☒PCS 1900 (U.S. Bands) ☒GSM 900 ☒DCS 1800 (Non-U.S. Bands) U.S. Bands: ☒UMTS FDD Band II ☒UMTS FDD Band V Non-U.S. Bands: ☐UMTS FDD Band I ☐UMTS FDD Band VIII
Channel List	Please refer to the Note 2.
Adapter	Adapter Input:AC 100-240V,50/60Hz,0.4A Output:DC 5V,1000mA
Battery	Rated Voltage: 3.8V Charge Limit: 4.2V capacity :1800mAh
Hardware version number	F1Q-V1.3
Software versioning number	--
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	11	2422	21	2442	31	2462
01	2404	12	2424	22	2444	32	2464
02	2406	13	2426	23	2446	33	2466
03	2408	14	2428	24	2448	34	2468
05	2410	15	2430	25	2450	35	2470
06	2412	16	2432	26	2452	36	2472
07	2414	17	2434	27	2454	37	2474
08	2416	18	2436	28	2456	38	2476
09	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	Chip Antenna	N/A	0	BT 4.0 ANT

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX CH1/CH20/CH40
Mode 2	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 2	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX CH1/CH20/CH40
Mode 2	Link Mode

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	mobile phone	N/A	G5006	N/A	EUT
E-2	Adapter	N/A	GFP121-0520BX-1	N/A	
E-3	Earphone	N/A	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	YES	1.5m	
C-2	NO	NO	1.2m	

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2014.10.25	2015.10.24
Test Receiver	R&S	ESCI	101427	2014.10.25	2015.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2014.10.27	2015.10.26
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.06	2015.06.06
Horn Antenna	R&S	9120D	152265	2014.10.27	2015.10.26
Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05
Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21
Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07
Power Meter	Anritsu	ML2495A	1204003	2014.10.25	2015.10.24
Power Sensor	Anritsu	MA2411B	100309	2014.10.25	2015.10.24

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	102086	2014.10.25	2015.10.24	102086
LISN	R&S	ENV216	101242	2014.10.25	2015.10.24
LISN	EMCO	3810/2NM	000-23625	2014.10.25	2015.10.24
50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.06	2015.06.06
Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.06	2015.06.06
Absorbing clamp	R&S	MDS-21	100668	2014.10.27	2015.10.26

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.5 TEST RESULTS

EUT：	Mobile phone	Model Name. ：	G5006
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 5V from Adapter with AC 120V/60Hz	Test Mode：	Mode 2

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1495	24.53	11.85	36.38	66.03	-29.65	QP
2	0.1495	20.85	11.85	32.70	56.03	-23.33	AVG
3	0.1775	37.17	10.44	47.61	64.60	-16.99	QP
4	0.1775	23.72	10.44	34.16	54.60	-20.44	AVG
5	0.6746	18.13	10.41	28.54	56.00	-27.46	QP
6	0.6746	12.36	10.41	22.77	46.00	-23.23	AVG
7	1.2290	18.23	10.41	28.64	56.00	-27.36	QP
8	1.2290	10.71	10.41	21.12	46.00	-24.88	AVG
9	3.5197	25.09	10.61	35.70	56.00	-20.30	QP
10	3.5197	14.55	10.61	25.16	46.00	-20.84	AVG
11	4.1106	29.23	10.62	39.85	56.00	-16.15	QP
12	4.1106	18.80	10.62	29.42	46.00	-16.58	AVG

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT：	Mobile phone	Model Name. ：	G5006
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 5V from Adapter with AC 120V/60Hz	Test Mode：	Mode 2

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1491	18.99	11.86	30.85	66.05	-35.20	QP
2	0.1491	15.33	11.86	27.19	56.05	-28.86	AVG
3	0.1723	35.97	10.36	46.33	64.85	-18.52	QP
4	0.1723	20.92	10.36	31.28	54.85	-23.57	AVG
5	0.1998	34.73	10.43	45.16	63.62	-18.46	QP
6	0.1998	23.43	10.43	33.86	53.62	-19.76	AVG
7	0.3695	26.95	10.42	37.37	58.51	-21.14	QP
8	0.3695	19.69	10.42	30.11	48.51	-18.40	AVG
9	1.5105	16.66	10.44	27.10	56.00	-28.90	QP
10	1.5105	8.32	10.44	18.76	46.00	-27.24	AVG
11	4.2316	30.91	10.65	41.56	56.00	-14.44	QP
12	4.2316	21.90	10.65	32.55	46.00	-13.45	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

6dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&205(a), then the Part15.247&209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (Frequency Range 9kHz-1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / *10Hz* for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.3 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.5 TEST RESULTS

(Between 9KHz – 30 MHz)

EUT：	Mobile phone	Model Name. ：	G5006
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	Link mode	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

Between 30MHz – 1GHz

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	Link mode	Polarization :	Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	180.0165	25.19	10.52	35.71	43.50	-7.79	QP
2	239.9873	27.85	12.15	40.00	46.00	-6.00	QP
3	314.3765	23.48	15.82	39.30	46.00	-6.70	QP
4	374.6225	23.20	17.60	40.80	46.00	-5.20	QP
5	480.5276	20.90	20.40	41.30	46.00	-4.70	QP
6	962.1622	15.77	29.32	45.09	54.00	-8.91	QP

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT：	Waterproof WCDMA Tablet	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	Link mode	Polarization :	Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	63.7588	17.77	5.81	23.58	40.00	-16.42	QP
2	124.5690	15.39	12.75	28.14	43.50	-15.36	QP
3	180.0165	21.79	10.52	32.31	43.50	-11.19	QP
4	239.9873	28.85	12.15	41.00	46.00	-5.00	QP
5	480.5276	19.20	20.40	39.60	46.00	-6.40	QP
6	962.1623	17.95	29.32	47.27	54.00	-6.73	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Above 1000 MHz

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH1:2402MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804	43.37	10.44	53.81	74	-20.19	peak
4804	32.18	10.44	42.62	54	-11.38	AVG
7206	41.15	12.39	53.54	74	-20.46	peak
7206	31.58	12.39	43.97	54	-10.03	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH1:2402MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804	41.34	10.4	51.74	74	-22.26	peak
4804	29.33	10.4	39.73	54	-14.27	AVG
7206	31.48	12.75	44.23	74	-29.77	peak
7206	25.29	12.75	38.04	54	-15.96	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH20:2440MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4884	43.25	10.4	53.65	74	-20.35	peak
4884	32.36	10.4	42.76	54	-11.24	AVG
7326	41.92	12.75	54.67	74	-19.33	peak
7326	32.52	12.75	45.27	54	-8.73	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH20:2440MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4884	45.32	10.39	55.71	74	-18.29	peak
4884	32.47	10.44	42.91	54	-11.09	AVG
7326	32.56	12.68	45.24	74	-28.76	peak
7326	32.22	12.68	44.9	54	-9.1	AVG

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. No emission detected above 18GHz

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH40:2480MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960	36.93	10.39	47.32	74	-26.68	peak
4960	25.36	10.39	35.75	54	-18.25	AVG
7440	42.42	12.68	55.1	74	-18.9	peak
7440	31.68	12.68	44.36	54	-9.64	AVG

Remark:
1 Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2 No emission detected above 18GHz

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH40:2480MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960	45.28	10.39	55.67	74	-18.33	peak
4960	34.42	10.39	44.81	54	-9.19	AVG
7440	44.72	12.68	57.4	74	-16.6	peak
7440	25.22	12.68	37.9	54	-16.1	AVG

Remark:
1 Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2 No emission detected above 18GHz

4.6 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH00: 2402	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
GFSK							
2399.9	77.22	-13	64.22	74	-9.78	peak	Vertical
2399.9	55.52	-13	42.52	54	-11.48	AVG	Vertical
2400	78.83	-12.99	65.84	74	-8.16	peak	Vertical
2400	56.86	-12.99	43.87	54	-10.13	AVG	Vertical

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH40: 2480	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
GFSK							
2483.5	78.25	-12.78	65.47	74	-8.53	peak	Vertical
2483.5	56.52	-12.78	43.74	54	-10.26	AVG	Vertical
2483.6	78.85	-12.77	66.08	74	-7.92	peak	Vertical
2483.6	55.54	-12.77	42.77	54	-11.23	AVG	Vertical

5. CONDUCTED SPURIOUS EMISSIONS

5.1 REQUIREMENT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2 TEST PROCEDURE

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

.

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 – 2404 MHz Upper Band Edge: 2478 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.5 TEST RESULTS

EUT：	mobile phone	Model Name ：	G5006
Temperature：	25 ℃	Relative Humidity：	50%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX Mode /CH02, CH20, CH40		

00 CH



20 CH



40 CH


Agilent
R T
Marker
Mkr1 2.481 GHz
Ref 10 dBm
Atten 20 dB
-6.464 dBm
Peak
Log
10
dB/
Offst
0.6
dB
Dl
-26.5
dBm
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2
Start 30 MHz
Stop 25 GHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 2.587 s (8192 pts)
Marker Trace Type X Axis Amplitude
1 (1) Freq 2.481 GHz -6.464 dBm
2 (1) Freq 13.150 GHz -54.54 dBm

For Band edge

00 Channel



40 Channel



6. POWER SPECTRAL DENSITY TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.5 TEST RESULTS

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH02, CH20, CH40		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2402 MHz	-20.64	8	**PASS**
2440 MHz	-20.83	8	**PASS**
2480 MHz	-20.42	8	**PASS**

TX CH01



TX CH20



TX CH40



7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 ´ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7.Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 d B relative to the maximum level measured in the fundamental emission.

7.3 TEST SETUP

7.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

7.5 TEST RESULTS

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH01, CH20, CH40		

Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2402 MHz	0.663	>=500KHz	**PASS**
2440 MHz	0.664	>=500KHz	**PASS**
2480 MHz	0.665	>=500KHz	**PASS**

TX CH 01



TX CH 20



TX CH 40



8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

8.3 TEST SETUP

8.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

8.5 TEST RESULTS

EUT：	Mobile phone	Model Name ：	G5006
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 5V From Adapter AC 120/60Hz
Test Mode ：	TX Mode /CH01, CH20, CH40		

TX Mode			
Test Channe	Frequency (MHz)	Peak Conducted Output Power (dBm)	LIMIT dBm
CH01	2402	-6.994	30
CH20	2440	-6.462	30
CH40	2480	-6.745	30

TX CH 01



TX CH 20



TX CH 40



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is Chip antenna. It comply with the standard requirement.

10. EUT TEST PHOTO

Radiated Measurement Photos





Conducted Measurement Photos