

## **RF Exposure Evaluation For FCC ID: 2ADPF-GCP-200;**

Refer user manual this device is a GHOSTDRONE that the minimum distance between human's body is **20cm**. Based on the 47CFR 2.1091, this device belongs to Mobile device. The definition of the category as following:

### **Mobile Derives:**

CFR Title 47 § 2.1091(b)

(b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

### **FCC KDB 447498 D01 General RF Exposure Guidance v05r02 Limit**

Devices operating in standalone mobile exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance  $\geq 20$  cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When the categorical exclusion provision of § 2.1091(c) applies, the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

## RF Exposure Evaluation Result:

### FCC (Worst case)

According to FCC Part 1.1307, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidelines.

| Limits for General Population/ Uncontrolled Exposure |                                    |                                     |                                           |
|------------------------------------------------------|------------------------------------|-------------------------------------|-------------------------------------------|
| Frequency Range<br>(MHz)                             | Electric Field<br>Strength(E)(V/m) | Magnetic Field Strength<br>(H)(A/m) | Power Density<br>(S)(mW/cm <sup>2</sup> ) |
| 0.3-1.34                                             | 614                                | 1.63                                | (100)*                                    |
| 1.34-30                                              | 824/f                              | 2.19/f                              | (180/f <sup>2</sup> )*                    |
| 30-300                                               | 27.5                               | 0.073                               | 0.2                                       |
| 300-1500                                             |                                    |                                     | f/1500                                    |
| 1500-100,000                                         |                                    |                                     | 1.0                                       |

### MPE calculation formula

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density

P = output power (W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Separation distance between radiator and human body (m)

### Test result

|                                                                         |               |
|-------------------------------------------------------------------------|---------------|
| Maximum peak output power at antenna input terminal(dBm):               | <b>15.55</b>  |
| Maximum peak output power at antenna input terminal(mW):                | <b>35.89</b>  |
| Prediction distance(cm):                                                | <b>20</b>     |
| Predication frequency(MHz):                                             | <b>2402</b>   |
| Antenna Gain (typical) (dBi):                                           | <b>2</b>      |
| Power density at predication frequency at 20 cm(mW/cm <sup>2</sup> ):   | <b>0.0113</b> |
| MPE limit for RF exposure at prediction frequency(mW/cm <sup>2</sup> ): | <b>1</b>      |

### FCC Verdict: PASS

Note:

1. More power list please refer to RF test report.