



EMI – TEST REPORT

- Human Exposure -

Type / Model Name : EasyLogger

Product Description : Temperature and Humidity Sensor with BLE module

Applicant : fp floor protector GmbH

Address : Waldgasse 2

2700 WIENER NEUSTADT, AUSTRIA

Manufacturer : fp floor protector GmbH

Address : Waldgasse 2

2700 WIENER NEUSTADT, AUSTRIA

Test Result according to the standards
listed in clause 1 test standards:

POSITIVE

Test Report No. : **T46146-00-04FX**

28. April 2020

Date of issue



Deutsche
Akkreditierungsstelle
D-PL-12030-01-01
D-PL-12030-01-02

FCC ID: 2ADQTV1EL

IC: 12568A-V1EL

Contents

1	<u>TEST STANDARDS</u>	<u>3</u>
2	<u>EQUIPMENT UNDER TEST</u>	<u>4</u>
2.1	Information provided by the Client	4
2.2	Sampling	4
2.3	Photo documentation of the EUT – See ATTACHMENT A	4
2.4	Equipment type, category	4
2.5	Short description of the equipment under test (EUT)	4
2.6	Variants of the EUT	4
2.7	Operation frequency and channel plan	5
2.8	Transmit operating modes	5
2.9	Antennas	5
2.10	Power supply system utilised	5
3	<u>TEST RESULT SUMMARY</u>	<u>6</u>
3.1	Final assessment	6
4	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1	Address of the test laboratory	7
4.2	Environmental conditions	7
4.3	Statement of the measurement uncertainty	7
5	<u>HUMAN EXPOSURE</u>	<u>8</u>
5.1	Maximum permissible exposure (MPE)	8
5.2	Co-location and Co-transmission	10

ATTACHMENT A as separate supplement

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2ADQTV1EL

IC: 12568A-V1EL

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules and Regulations Part 1, Subpart I - Procedures Implementing the National Environmental Policy Act of 1969

Part 1, Subpart I, Section 1.1310	Radiofrequency radiation exposure limits
Part 1, Subpart 2, Section 2.1091	Radiofrequency radiation exposure evaluation: mobile devices .
Part 1, Subpart 2, Section 2.1093	Radiofrequency radiation exposure evaluation: portable devices .
KDB 447498 D01 v06	RF Exposure procedures and equipment authorisation policies for mobile and portable devices, October 23, 2015.
KDB 865664 D01 v01r04	SAR Measurement Requirements for 100 MHz to 6 GHz, August 7, 2015.
ANSI C95.1: 2005	IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
ETSI TR 100 028 V1.3.1: 2001-03,	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); Uncertainties in the Measurement of Mobile Radio Equipment Characteristics—Part 1 and Part 2

FCC ID: 2ADQTV1EL

IC: 12568A-V1EL

2 EQUIPMENT UNDER TEST

2.1 Information provided by the Client

Please note, we do not take any responsibility for information provided by the client or his representative which may have an influence on the validity of the test results.

2.2 Sampling

The customer is responsible for the choice of sample. Sample configuration, start-up and operation is carried out by the customer or according his/her instructions.

2.3 Photo documentation of the EUT – See ATTACHMENT A

2.4 Equipment type, category

BLE device, mobile equipment.

2.5 Short description of the equipment under test (EUT)

Number of tested samples: 2
Serial number: 300268 (conducted), 300269 (radiated)
Firmware version: 0120007048

EUT configuration:

(The CDF filled by the applicant can be viewed at the test laboratory.)

2.6 Variants of the EUT

There are no variants.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2ADQTV1EL
IC: 12568A-V1EL

2.7 Operation frequency and channel plan

The operating frequency is 2400 MHz to 2483.5 MHz.

Channel plan BT-Standard 802.15.1:

Channel	Frequency	Channel	Frequency
37	2402	18	2442
0	2404	19	2444
1	2406	20	2446
2	2408	21	2448
3	2410	22	2450
4	2412	23	2452
5	2414	24	2454
6	2416	25	2456
7	2418	26	2458
8	2420	27	2460
9	2422	28	2462
10	2424	29	2464
38	2426	30	2466
11	2428	31	2468
12	2430	32	2470
13	2432	33	2472
14	2434	34	2474
15	2436	35	2476
16	2438	36	2478
17	2440	39	2480

Note: the marked frequencies are determined for final testing.

2.8 Transmit operating modes

The EUT uses GFSK modulation and may provide following data rates:

- 1000 kbps

(kbps = kilobits per second)

2.9 Antennas

The following antenna shall be used with the EUT:

Number	Characteristic	Model number	Plug	Frequency range (GHz)	Gain (dBi)	Cable loss (dB)	Effective gain (dBi)
1	Omni-Directional	ANT3216LL00R2400A	solder	2.4	5.05	0	5.05

2.10 Power supply system utilised

Power supply voltage, V_{nom} : 3 VDC (battery)

Power supply voltage (alternative) : ---

FCC ID: 2ADQTV1EL
IC: 12568A-V1EL

3 TEST RESULT SUMMARY

BLE device using digital modulation:

Operating in the 2400 MHz – 2483.5 MHz:

FCC Rule Part	RSS Rule Part	Description	Result
KDB 447498, 7.1	RSS 102, 2.5.2	MPE	passed
KDB 447498, 4.3.1	RSS 102, 2.5.1	SAR exclusion consideration	not applicable
KDB 447498, 7.2	RSS102, 3.2	Co-location, Co-transmission	not applicable

The mentioned RSS Rule Parts in the above table are related to:
RSS 102, Issue 5, March 2015

3.1 Final assessment

The equipment under test fulfills the EMI requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 06 March 2020

Testing concluded on : 20 March 2020

Checked by:



Klaus Gegenfurtner
I confirm the correctness
and integrity of this
document
2020.04.28 09:13:33
+02'00'

Klaus Gegenfurtner
Teamleader Radio

Tested by:



I am the author of
this document
2020.04.28 07:18:18
+02'00'

Franz-Xaver Schrettenbrunner
Radio Team

FCC ID: 2ADQTV1EL

IC: 12568A-V1EL

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

**CSA Group Bayern GmbH
Ohmstrasse 1-4
94342 STRASSKIRCHEN
GERMANY**

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 °C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

4.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. It is noted that the expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor $k = 2$. The true value is located in the corresponding interval with a probability of 95 %. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4-2 / 2011 + A1 / 2014 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements“ and is documented in the quality system acc. to DIN EN ISO/IEC 17025. For all measurements shown in this report, the measurement uncertainty of the test laboratory, CSA Group Bayern GmbH, is below the measurement uncertainty as defined by CISPR. Therefore, no special measures must be taken into consideration with regard to the limits according to CISPR. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

4.4 Conformity Decision Rule

The conformity decision rule is based on the ILAC G8 published at the time of reporting.

FCC ID: 2ADQTV1EL

IC: 12568A-V1EL

5 HUMAN EXPOSURE

5.1 Maximum permissible exposure (MPE)

For test instruments and accessories used see section 6 Part **CPC 3**.

5.1.1 Description of the test location

Test location: NONE

5.1.2 Applicable standard

According to FCC Part 15, Section 15.247(i):

Systems operating under the provisions of this section shall be operated in a manner that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

The test methods used comply with ANSI/IEEE C95.1, "IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz".

This test report shows the compliance with the limits for Maximum Permissible Exposure (MPE) specified in FCC Part 1, Section 1.1310 and the criteria to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in FCC Part 1, Section 1.1307(b).

5.1.3 Description of Determination

The maximum rated output power conducted included the tune up tolerance is used to calculate the EIRP. Through the Friis transmission formula, the known maximum gain of the antenna and the maximum power, can be calculated the MPE in a defined distance away from the product.

Friis transmission formula:

$$P_d = \frac{P_{out} * G}{4 * \pi * r^2}$$

Where:

P_d = power density (mW/cm²)

P_{out} = output power to antenna (mW)

G = gain of antenna (linear scale)

r = distance between antenna and observation point (cm)

According to FCC Rules 47CFR 2.1093(b) the EUT is not a portable device. The EUT is designed to be used that radiating structures are 20 cm outside of the body of the user. ($r = 20$ cm)

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2ADQTV1EL
IC: 12568A-V1EL
5.1.4 Determination of MPE according FCC

Rated output power:	2.3 dBm	1.7 mW
Tune-up tolerance:	2.00 dB	
Maximum output power:	4.3 dBm	2.7 mW
Antenna gain max:	5.05 dBi	
Maximum EIRP:	9.4 dBm	8.6 mW
Minimum distance r:	20.0 cm	

EIRP	Antgain	EIRP	G	EIRP	S	Limit S_{eq}	Margin	Exposure ratio
(dBm)	(dBi)	(mW)	linear	(W)	(mW/cm ²)	(mW/cm ²)	(mW/cm ²)	(%)
9.4	5.1	8.62	3.20	0.0086	0.0017	1.0	-0.9983	0.17

Limits for maximum permissible exposure (MPE):

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	100	30
1.34 – 30	824/f	2.19/f	180/f ²	30
30 - 300	27.5	0.073	0.2	30
300-1500	---	---	f/1500	30
1500-100000	---	---	1.0	30

 f = Frequency in MHz

5.1.5 Determination of MPE according ISD:

EIRP	Antgain	Factor	$f^{0.6834}$	Limit	Margin
(mW)	(dBi)		(W)	(W)	(W/m ²)
8.6	5.1	0.0131	204.3072	2.6764	-2.6678

Exemption limits for routine Evaluation – RF exposure evaluation according RSS102, 2.5.2:

At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

At or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance)

The requirements are **FULFILLED**.

Remarks: None.

FCC ID: 2ADQTV1EL

IC: 12568A-V1EL

5.2 Co-location and Co-transmission

Applicable standard:

OET Bulletin 65, Edition 97-01, Section 2: Multiple-transmitter sites and Complex Environments

The FCC's MPE limits vary with frequency. Therefore, in mixed or broadband RF fields where several sources and frequencies are involved, the fraction of the recommended limit (in terms of power density or square of the electric or magnetic field strength) incurred within each frequency interval should be determined, and the sum of all fractional contributions should not exceed 1.0, or 100 % in terms of percentage.

The requirements are **FULFILLED**.

Remarks: The EUT is a single transmitter.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.