



# SAR Test Report

## For


**Applicant Name:** UNNECTO HOLDING LIMITED  
**Address:** 13/F HARBOUR COMMERCIAL BUILDING 122-124 CONNAUGHT ROAD CENTRAL SHEUNG WAN HK  
**EUT Name:** Mobile Phone  
**Brand name:** unnecto™  
**Model Name:** BOLT 1U

## Issued By

**Company Name:** BTF Testing Lab (Shenzhen) Co., Ltd.  
**Address:** 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

**Report Number:** BTF250630R00501  
**Test Standards:** FCC 47 CFR§2.1093 IEEE Std. 1528-2013  
IEEE C95.1-2019  
**FCC ID:** 2ADR3UB01U

**Test Conclusion:** Pass  
**Test Date:** 2025-08-15 to 2025-09-19  
**Date of Issue:** 2025-09-22

**Tested By:**   
Kris Li / Tester

**Date:** 2025-09-22


**Prepared By:** 

Amenda Zhong / Project Engineer

**Date:** 2025-09-22

**Approved By:**   
Ryan.CJ / EMC Manager

**Date:** 2025-09-22



*Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.*

| Revision History |                                                                              |                   |
|------------------|------------------------------------------------------------------------------|-------------------|
| Version          | Issue Date                                                                   | Revisions Content |
| R_V0             | 2025-09-20                                                                   | Original          |
|                  |                                                                              |                   |
| Note:            | Once the revision has been made, then previous versions reports are invalid. |                   |

## Table of Contents

|                                                              |     |
|--------------------------------------------------------------|-----|
| 1. Introduction .....                                        | 4   |
| 1.1 Identification of Testing Laboratory .....               | 4   |
| 1.2 Identification of the Responsible Testing Location ..... | 4   |
| 1.3 Laboratory Condition .....                               | 4   |
| 1.4 Announcement .....                                       | 4   |
| 2. Product Information .....                                 | 4   |
| 2.1 Application Information .....                            | 5   |
| 2.2 Manufacturer Information .....                           | 5   |
| 2.3 Factory Information .....                                | 5   |
| 2.4 General Description of Equipment under Test (EUT) .....  | 5   |
| 2.5 Equipment under Test Ancillary Equipment .....           | 5   |
| 2.6 Technical Information .....                              | 5   |
| 3. Summary of Test Results .....                             | 6   |
| 3.1 Test Standards .....                                     | 6   |
| 3.2 Device Category and SAR Limit .....                      | 7   |
| 3.3 Test Result Summary .....                                | 7   |
| 3.4 Test Uncertainty .....                                   | 8   |
| 4. Measurement System .....                                  | 10  |
| 4.1 Specific Absorption Rate (SAR) Definition .....          | 10  |
| 4.2 MVG SAR System .....                                     | 11  |
| 5. System Verification .....                                 | 15  |
| 5.1 Purpose of System Check .....                            | 15  |
| 5.2 System Check Setup .....                                 | 16  |
| 6. TEST POSITION CONFIGURATIONS .....                        | 16  |
| 6.1 Head Exposure Conditions .....                           | 16  |
| 6.2 Body-worn Position Conditions .....                      | 18  |
| 6.3 Hotspot Mode Exposure Position Conditions .....          | 19  |
| 6.4 Product Specific 10g Exposure Consideration .....        | 20  |
| 7. Measurement Procedure .....                               | 20  |
| 7.1 Measurement Process Diagram .....                        | 20  |
| 7.2 SAR Scan General Requirement .....                       | 21  |
| 7.3 Measurement Procedure .....                              | 22  |
| 7.4 Area & Zoom Scan Procedure .....                         | 23  |
| 8. Conducted RF Output Power .....                           | 23  |
| 8.1 GSM .....                                                | 23  |
| 8.2 WCDMA .....                                              | 24  |
| 8.3 LTE .....                                                | 25  |
| 8.4 Wi-Fi .....                                              | 43  |
| 8.5 Bluetooth .....                                          | 45  |
| 9. Test Exclusion Consideration .....                        | 45  |
| 9.1 SAR Test Exclusion Consideration Table .....             | 46  |
| 10. SAR Measurement Variability .....                        | 53  |
| 11. Simultaneous Transmission .....                          | 54  |
| 12. 1 Simultaneous Transmission Mode Considerations .....    | 54  |
| 12.2 Sum SAR of Simultaneous Transmission .....              | 55  |
| 12. Test Equipment List .....                                | 55  |
| ANNEX A Simulating Liquid Verification Result .....          | 56  |
| ANNEX B System Check Result .....                            | 57  |
| ANNEX C Test Data .....                                      | 78  |
| ANNEX D SAR Test Setup Photos .....                          | 174 |
| ANNEX E EUT External and Internal Photos .....               | 174 |
| ANNEX F Calibration Information .....                        | 174 |

## 1. Introduction

### 1.1 Identification of Testing Laboratory

|               |                                                                                                                                    |
|---------------|------------------------------------------------------------------------------------------------------------------------------------|
| Company Name: | BTF Testing Lab (Shenzhen) Co., Ltd.                                                                                               |
| Address:      | 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China |
| Phone Number: | +86-0755-23146130                                                                                                                  |
| Fax Number:   | +86-0755-23146130                                                                                                                  |

### 1.2 Identification of the Responsible Testing Location

|                         |                                                                                                                                                                                                                   |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Location:          | BTF Testing Lab (Shenzhen) Co., Ltd.                                                                                                                                                                              |
| Address:                | 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China                                                                                |
| Description:            | All measurement facilities used to collect the measurement data are located at 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China |
| FCC Registration Number | 518915                                                                                                                                                                                                            |
| Designation Number      | CN1409                                                                                                                                                                                                            |

### 1.3 Laboratory Condition

|                            |                    |
|----------------------------|--------------------|
| Ambient Temperature:       | 21°C to 25°C       |
| Ambient Relative Humidity: | 48% to 59%         |
| Ambient Pressure:          | 100 kPa to 102 kPa |

### 1.4 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

## 2. Product Information

## 2.1 Application Information

|               |                                                                               |
|---------------|-------------------------------------------------------------------------------|
| Company Name: | UNNECTO HOLDING LIMITED                                                       |
| Address:      | 13/F HARBOUR COMMERCIAL BUILDING 122-124 CONNAUGHT ROAD CENTRAL SHEUNG WAN HK |

## 2.2 Manufacturer Information

|               |                                                                                                                                              |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Company Name: | Shenzhen Water World Information Co., LTD                                                                                                    |
| Address:      | 3rd Floor, Building 3, Dexinchang Smart Park, No. 23, Heping Road, Qinghua Community, Longhua Sub-district, Longhua District, Shenzhen City. |

## 2.3 Factory Information

|               |                                                                                                                                              |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Company Name: | Shenzhen Water World Information Co., LTD                                                                                                    |
| Address:      | 3rd Floor, Building 3, Dexinchang Smart Park, No. 23, Heping Road, Qinghua Community, Longhua Sub-district, Longhua District, Shenzhen City. |

## 2.4 General Description of Equipment under Test (EUT)

|                       |                |
|-----------------------|----------------|
| EUT Name              | Mobile Phone   |
| Under Test Model Name | BOLT 1U        |
| Sample No.            | BTFSN250630008 |
| Hardware Version      | YK583-MB-V0.2A |

## 2.5 Equipment under Test Ancillary Equipment

|                       |                      |         |
|-----------------------|----------------------|---------|
| Ancillary Equipment 1 | Rechargeable Battery |         |
|                       | Capacity             | 4000mAh |
|                       | Rated Voltage        | 3.85V   |

## 2.6 Technical Information

|                                   |                                                                                                                                                                                                                                                                                    |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network and Wireless connectivity | 2G Network GSM/GPRS/EGPRS 850/1900<br>3G Network WCDMA/HSDPA/HSUPA Band 2/4/5<br>4G Network FDD LTE Band 2/4/5/12/13/17/25/26/66/71 TDD LTE Band 38/41<br>2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40)<br>5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80)<br>BT (EDR+BLE) |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

The requirement for the following technical information of the EUT was tested in this report:

|                |                                  |
|----------------|----------------------------------|
| Operating Mode | GSM, WCDMA, LTE, WLAN, Bluetooth |
|----------------|----------------------------------|

|                   |                                                              |                                                                                                                                   |                       |
|-------------------|--------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| Frequency Range   | GSM 850                                                      | TX: 824 ~ 849 MHz                                                                                                                 | RX: 869 ~ 894 MHz     |
|                   | GSM 1900                                                     | TX: 1850 ~ 1910 MHz                                                                                                               | RX: 1930 ~ 1990 MHz   |
|                   | WCDMA Band 2                                                 | TX: 1850 ~ 1910 MHz                                                                                                               | RX: 1930 ~ 1990 MHz   |
|                   | WCDMA Band 4                                                 | TX: 1710 ~ 1755 MHz                                                                                                               | RX: 2110 ~ 2155 MHz   |
|                   | WCDMA Band 5                                                 | TX: 824 ~ 849 MHz                                                                                                                 | RX: 869 ~ 894 MHz     |
|                   | LTE Band 2                                                   | TX: 1850 ~ 1910 MHz                                                                                                               | RX: 1930 ~ 1990 MHz   |
|                   | LTE Band 4                                                   | TX: 1710 ~ 1755 MHz                                                                                                               | RX: 2110 ~ 2155 MHz   |
|                   | LTE Band 5                                                   | TX: 824 ~ 849 MHz                                                                                                                 | RX: 869 ~ 894 MHz     |
|                   | LTE Band 12                                                  | TX: 698 ~ 716 MHz                                                                                                                 | RX: 728 ~ 746 MHz     |
|                   | LTE Band 13                                                  | TX: 777 ~ 787 MHz                                                                                                                 | RX: 746 ~ 756 MHz     |
|                   | LTE Band 17                                                  | TX: 704 ~ 716 MHz                                                                                                                 | RX: 734 ~ 746 MHz     |
|                   | LTE Band 25                                                  | TX: 1850 ~ 1915 MHz                                                                                                               | RX: 1930 ~ 1995 MHz   |
|                   | LTE Band 26 part 90                                          | TX: 814.7 ~ 823.3 MHz                                                                                                             | RX: 859.7 ~ 868.3 MHz |
|                   | LTE Band 26 part 22                                          | TX: 824.7 ~ 848.3 MHz                                                                                                             | RX: 869.7 ~ 893.3 MHz |
|                   | LTE Band 38                                                  | 2570 ~ 2620 MHz                                                                                                                   |                       |
|                   | LTE Band 41                                                  | 2496 ~ 2690 MHz                                                                                                                   |                       |
|                   | LTE Band 66                                                  | TX: 1710 ~ 1780 MHz                                                                                                               | RX: 2110 ~ 2200 MHz   |
|                   | LTE Band 71                                                  | TX: 663 ~ 698 MHz                                                                                                                 | RX: 617 ~ 652 MHz     |
|                   | 802.11b/g/n(HT20)                                            | 2412 ~ 2462 MHz                                                                                                                   |                       |
|                   | 802.11n(HT40)                                                | 2422 ~ 2452 MHz                                                                                                                   |                       |
|                   | 802.11a<br>/802.11n(HT20/40)<br>/802.11ac(HT20/40/80)        | U-NII-1: 5180 MHz ~ 5240 MHz,<br>U-NII-2A: 5260 MHz ~ 5320 MHz,<br>U-NII-2C: 5500 MHz ~ 5700 MHz,<br>U-NII-3: 5745 MHz ~ 5825 MHz |                       |
|                   | Bluetooth                                                    | 2402 ~ 2480 MHz                                                                                                                   |                       |
| Antenna Type      | WWAN: PIFA Antenna<br>WLAN: PIFA Antenna<br>BT: PIFA Antenna |                                                                                                                                   |                       |
| Hotspot Function  | Support                                                      |                                                                                                                                   |                       |
| Power Reduction   | Not Support                                                  |                                                                                                                                   |                       |
| Exposure Category | General Population/Uncontrolled exposure                     |                                                                                                                                   |                       |
| EUT Stage         | Portable Device                                              |                                                                                                                                   |                       |
| Product           | Type                                                         |                                                                                                                                   |                       |
|                   | <input type="checkbox"/> Production unit                     | <input checked="" type="checkbox"/> Identical prototype                                                                           |                       |

### 3. Summary of Test Results

#### 3.1 Test Standards

| No. | Identity            | Document Title                                                                                                                                                              |
|-----|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | 47 CFR Part 2.1093  | Radiofrequency radiation exposure evaluation: portable devices                                                                                                              |
| 2   | IEEE Std. 1528-2013 | Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques |
| 3   | IEEE C95.1-2019     | IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz                                           |
| 4   | KDB447498 D04       | Interim General RF Exposure Guidance v01                                                                                                                                    |
| 5   | KDB865664 D01       | SAR measurement 100MHz to 6GHz v01r04                                                                                                                                       |
| 6   | KDB865664 D02       | RF Exposure Reporting v01r02                                                                                                                                                |
| 7   | KDB941225 D01       | 3G SAR Procedures v03r01                                                                                                                                                    |
| 8   | KDB941225 D05       | SAR for LTE Devices v02r05                                                                                                                                                  |
| 9   | KDB248227 D01       | 802.11 Wi-Fi SAR v02r02                                                                                                                                                     |
| 10  | KDB941225 D06       | Hotspot Mode v02r01                                                                                                                                                         |
| 11  | KDB648474 D04       | Handset SAR v01r03                                                                                                                                                          |
| 12  | KDB690783 D01       | SAR Listings on Grant v01r03                                                                                                                                                |

### 3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

| Body Position                                                                    | SAR Value (W/Kg)                             |                                      |
|----------------------------------------------------------------------------------|----------------------------------------------|--------------------------------------|
|                                                                                  | General Population/<br>Uncontrolled Exposure | Occupational/<br>Controlled Exposure |
| Whole-Body SAR<br>(averaged over the entire body)                                | 0.08                                         | 0.4                                  |
| Partial-Body SAR<br>(averaged over any 1 gram of tissue)                         | 1.60                                         | 8.0                                  |
| SAR for hands, wrists, feet and ankles<br>(averaged over any 10 grams of tissue) | 4.0                                          | 20.0                                 |

NOTE:  
**General Population/Uncontrolled Exposure:** Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment- related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.  
**Occupational/Controlled Exposure:** Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

### 3.3 Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as bellows:

<Highest Reported standalone SAR Summary>

| Exposure Position | Frequency Band | Reported SAR<br>(W/kg) | Equipment Class | Highest Reported SAR<br>(W/kg) |
|-------------------|----------------|------------------------|-----------------|--------------------------------|
| Head              | GSM 850        | 0.051                  | PCE             | 0.672                          |

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 59 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

|                                         |                     |                |                     |                 |
|-----------------------------------------|---------------------|----------------|---------------------|-----------------|
| 1-g SAR<br>(0 mm Gap)                   | GSM 1900            | 0.227          |                     |                 |
|                                         | WCDMA Band II       | 0.530          |                     |                 |
|                                         | WCDMA Band IV       | 0.571          |                     |                 |
|                                         | WCDMA Band V        | 0.148          |                     |                 |
|                                         | LTE Band 2          | 0.672          |                     |                 |
|                                         | LTE Band 4          | 0.531          |                     |                 |
|                                         | LTE Band 5          | 0.191          |                     |                 |
|                                         | LTE Band 12         | 0.134          |                     |                 |
|                                         | LTE Band 13         | 0.110          |                     |                 |
|                                         | LTE Band 17         | 0.150          |                     |                 |
|                                         | LTE Band 25         | 0.643          |                     |                 |
|                                         | LTE Band 26 part 90 | 0.246          |                     |                 |
|                                         | LTE Band 26 part 22 | 0.255          |                     |                 |
|                                         | LTE Band 38         | 0.095          |                     |                 |
|                                         | LTE Band 41         | 0.149          |                     |                 |
|                                         | LTE Band 66         | 0.645          |                     |                 |
|                                         | LTE Band 71         | 0.074          |                     |                 |
|                                         | WLAN 2.4 GHz        | 0.235          |                     |                 |
|                                         | WLAN 5.2 GHz        | 0.655          |                     |                 |
|                                         | WLAN 5.4 GHz        | 0.237          |                     |                 |
|                                         | WLAN 5.6 GHz        | 0.092          |                     |                 |
|                                         | WLAN 5.8 GHz        | 0.212          |                     |                 |
|                                         | Bluetooth           | 0.004          |                     |                 |
| Exposure Position                       |                     | Frequency Band | Reported SAR (W/kg) | Equipment Class |
| Hotspot(Body)<br>1-g SAR<br>(10 mm Gap) | GSM 850             | 0.040          | PCE                 | 0.361           |
|                                         | GSM 1900            | 0.045          |                     |                 |
|                                         | WCDMA Band II       | 0.206          |                     |                 |
|                                         | WCDMA Band IV       | 0.189          |                     |                 |
|                                         | WCDMA Band V        | 0.121          |                     |                 |
|                                         | LTE Band 2          | 0.286          |                     |                 |
|                                         | LTE Band 4          | 0.201          |                     |                 |
|                                         | LTE Band 5          | 0.222          |                     |                 |
|                                         | LTE Band 12         | 0.141          |                     |                 |
|                                         | LTE Band 13         | 0.122          |                     |                 |
|                                         | LTE Band 17         | 0.144          |                     |                 |
|                                         | LTE Band 25         | 0.269          |                     |                 |
|                                         | LTE Band 26 part 90 | 0.180          |                     |                 |
|                                         | LTE Band 26 part 22 | 0.162          |                     |                 |
|                                         | LTE Band 38         | 0.138          |                     |                 |
|                                         | LTE Band 41         | 0.081          |                     |                 |
|                                         | LTE Band 66         | 0.222          |                     |                 |
|                                         | LTE Band 71         | 0.104          |                     |                 |
|                                         | WLAN 2.4 GHz        | 0.361          |                     |                 |
|                                         | WLAN 5.2 GHz        | 0.281          |                     |                 |
|                                         | WLAN 5.4 GHz        | 0.311          |                     |                 |
|                                         | WLAN 5.6 GHz        | 0.007          |                     |                 |
|                                         | WLAN 5.8 GHz        | 0.102          |                     |                 |
|                                         | Bluetooth           | 0.003          |                     |                 |

This device is in compliance with Specific Absorption Rate(SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC47 CFR part 2(2.1093) and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std. 1528-2013.

#### <Highest Reported Simultaneous SAR>

| Exposure Position                    | Simultaneous Configuration | Highest Reported Simultaneous Transmission SAR (W/kg) | Limit (W/kg) | Verdict |
|--------------------------------------|----------------------------|-------------------------------------------------------|--------------|---------|
| Head<br>1-g SAR (0 mm Gap)           | LTE Band 2 + 5.2G WIFI     | 1.327                                                 | 1.6          | Pass    |
| Hotspot(Body)<br>1-g SAR (10 mm Gap) | LTE Band 2 + 2.4G WIFI     | 0.647                                                 | 1.6          | Pass    |

## 3.4 Test Uncertainty

### 3.4.1 Measurement uncertainty evaluation for SAR test

#### Measurement uncertainty evaluation for SAR test (450MHz to 6GHz)

| Uncertainty Component | Tol (+-%) | Prob. Dist. | Div. | Unc. u(xi)=a(xi)/qi | Ci (1g) | Ci (10g) | 1g Ui (+-%) | 10 g Ui (+-%) | Vi veff |
|-----------------------|-----------|-------------|------|---------------------|---------|----------|-------------|---------------|---------|
|-----------------------|-----------|-------------|------|---------------------|---------|----------|-------------|---------------|---------|

| Measurement System                                                 |      |           |      |      |      |      |       |       |   |
|--------------------------------------------------------------------|------|-----------|------|------|------|------|-------|-------|---|
| Probe calibration                                                  | 14   | N (k = 2) | 2    | 7.00 | 1    | 1    | 7.00  | 7.00  | ∞ |
| Probe calibration drift                                            | 4    | R         | √3   | 2.31 | 1    | 1    | 2.31  | 2.31  | ∞ |
| Probe linearity                                                    | 4.7  | R         | √3   | 2.71 | 1    | 1    | 2.71  | 2.71  | ∞ |
| detection limit                                                    | 1    | R         | √3   | 0.58 | 1    | 1    | 0.58  | 0.58  | ∞ |
| Probe isotropy                                                     | 3.5  | R         | √3   | 2.02 | 0.71 | 0.71 | 1.43  | 1.43  | ∞ |
| Hemispherical Isotropy                                             | 5.9  | N         | 1    | 5.90 | 0.71 | 0.71 | 4.19  | 4.19  | ∞ |
| Boundary effect                                                    | 1    | R         | 1.73 | 0.58 | 1    | 1    | 0.58  | 0.58  | ∞ |
| Integration time                                                   | 1.4  | R         | 1.73 | 0.81 | 1    | 1    | 0.81  | 0.81  | ∞ |
| Response time                                                      | 0    | R         | 1.73 | 0.00 | 1    | 1    | 0.00  | 0.00  | ∞ |
| Readout electronics                                                | 0.5  | N         | 1    | 0.50 | 1    | 1    | 0.50  | 0.50  | ∞ |
| RF ambient and noise                                               | 3    | R         | √3   | 1.73 | 1    | 1    | 1.73  | 1.73  | ∞ |
| Probe positioning errors                                           | 3.28 | N         | 1    | 3.28 | 0.33 | 0.33 | 1.08  | 1.08  | ∞ |
| Data processing errors                                             | 2.3  | R         | 1    | 1.33 | 1    | 1    | 1.33  | 1.33  | ∞ |
| Conductivity measurement                                           | 4.07 | N         | 1    | 2.35 | 0.79 | 0.77 | 1.86  | 1.81  | ∞ |
| Permittivity measurement                                           | 5.06 | N         | 1    | 2.92 | 0.23 | 0.26 | 0.67  | 0.76  | ∞ |
| Liquid Conductivity - Temperature Uncertainty                      | 2.5  | R         | 1    | 1.44 | 0.79 | 0.77 | 1.14  | 1.11  | ∞ |
| Liquid Permittivity - Temperature Uncertainty                      | 2.5  | R         | √3   | 1.44 | 0.23 | 0.26 | 0.33  | 0.38  | ∞ |
| Shell permittivity                                                 | 2.9  | R         | √3   | 1.67 | 0.25 | 0.25 | 0.42  | 0.42  | ∞ |
| Repeatability of positioning the DUT or source against the phantom | 2.7  | N         | 1    | 2.70 | 2    | 2    | 5.40  | 5.40  | ∞ |
| Uncertainty in accepted power                                      | 3    | R         | 1    | 3.00 | 1    | 1    | 3.00  | 3.00  | ∞ |
| Effect of operating mode on probe sensitivity                      | 2.3  | R         | √3   | 1.33 | 1    | 1    | 1.33  | 1.33  | ∞ |
| Variation in SAR due to drift in output of DUT                     | 2.2  | N         | 1    | 2.20 | 1    | 1    | 2.20  | 2.20  | ∞ |
| Phantom deviation from target ( $\epsilon'$ , $\sigma$ )           | 1.9  | N         | 1    | 1.90 | 1    | 1    | 1.90  | 1.90  | ∞ |
| SAR scaling                                                        | 0    | R         | √3   | 0.00 | 1    | 1    | 0.00  | 0.00  | ∞ |
| Probe calibration                                                  | 14   | N (k = 2) | 2    | 7.00 | 1    | 1    | 7.00  | 7.00  | ∞ |
| Combined uncertainty                                               | /    |           |      |      |      |      | 11.94 | 11.94 |   |
| Expanded Uncertainty (95% Confidence interval)                     | /    |           |      |      |      |      | 23.89 | 23.88 |   |

\* This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3.4.2 Measurement uncertainty evaluation for system check

| Uncertainty Component   | Tol (+ - %) | Prob. Dist. | Div. | Unc. $u(x_i)=a(x_i)/q_i$ | Ci (1g) | Ci (10 g) | 1g Ui (+ - %) | 10 g Ui (+ - %) | Vi veff |
|-------------------------|-------------|-------------|------|--------------------------|---------|-----------|---------------|-----------------|---------|
| Measurement System      |             |             |      |                          |         |           |               |                 |         |
| Probe calibration       | 14          | N (k = 2)   | 2    | 7.00                     | 1       | 1         | 7.00          | 7.00            | ∞       |
| Probe calibration drift | 4           | R           | 1.73 | 2.31                     | 1       | 1         | 2.31          | 2.31            | ∞       |
| Probe linearity         | 4.7         | R           | 1.73 | 2.72                     | 1       | 1         | 2.72          | 2.72            | ∞       |

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 59 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

|                                                                          |      |   |      |      |      |      |       |       |          |
|--------------------------------------------------------------------------|------|---|------|------|------|------|-------|-------|----------|
| Detection limit                                                          | 1    | R | 1.73 | 0.58 | 1    | 1    | 0.58  | 0.58  | $\infty$ |
| Axial Isotropy                                                           | 3.5  | R | 1.73 | 2.02 | 1    | 1    | 2.02  | 2.02  | $\infty$ |
| Hemispherical Isotropy                                                   | 5.9  | R | 1.73 | 3.41 | 0.71 | 0.71 | 2.42  | 2.42  | $\infty$ |
| Boundary effect                                                          | 1    | R | 1.73 | 0.58 | 0.71 | 0.71 | 0.41  | 0.41  | $\infty$ |
| Integration time                                                         | 1.4  | R | 1.73 | 0.81 | 1    | 1    | 0.81  | 0.81  | $\infty$ |
| Response time                                                            | 0    | R | 1.73 | 0.00 | 1    | 1    | 0.00  | 0.00  | $\infty$ |
| Readout electronics                                                      | 0.5  | N | 1    | 0.50 | 1    | 1    | 0.50  | 0.50  | $\infty$ |
| Noise                                                                    | 3    | R | 1.73 | 1.73 | 1    | 1    | 1.73  | 1.73  | $\infty$ |
| Reflections                                                              | 3    | R | 1.73 | 1.73 | 1    | 1    | 1.73  | 1.73  | $\infty$ |
| Positioner Mechanical Tolerance                                          | 3.28 | R | 1.73 | 1.90 | 0.33 | 0.33 | 0.63  | 0.63  | $\infty$ |
| Positioning with respect to Phantom Shell                                | 3.28 | R | 1.73 | 1.90 | 0.33 | 0.33 | 0.63  | 0.63  | $\infty$ |
| Data processing errors                                                   | 2.3  | R | 1.73 | 1.33 | 1    | 1    | 1.33  | 1.33  | $\infty$ |
| Conductivity measurement                                                 | 4.07 | N | 1    | 4.07 | 0.79 | 0.77 | 3.22  | 3.13  | $\infty$ |
| Permittivity measurement                                                 | 5.06 | N | 1    | 5.06 | 0.23 | 0.26 | 1.16  | 1.32  | $\infty$ |
| Liquid Conductivity - Temperature Uncertainty                            | 2.5  | R | 1.73 | 1.45 | 0.79 | 0.77 | 1.14  | 1.11  | $\infty$ |
| Liquid Permittivity - Temperature Uncertainty                            | 2.5  | R | 1.73 | 1.45 | 0.23 | 0.26 | 0.33  | 0.38  | $\infty$ |
| Shell permittivity                                                       | 2.9  | R | 1.73 | 1.68 | 0.25 | 0.25 | 0.42  | 0.42  | $\infty$ |
| Distance between the radiating element of the DUT and the phantom medium | 2.7  | N | 1    | 2.70 | 2    | 2    | 5.40  | 5.40  | $\infty$ |
| Deviation of experimental antennas                                       | 4.5  | N | 1.73 | 2.60 | 1    | 1    | 2.60  | 2.60  | $\infty$ |
| Other uncertainty contributions                                          | 2    | R | 1    | 2.00 | 1    | 1    | 2.00  | 2.00  | $\infty$ |
| Uncertainty in accepted power                                            | 3    | R | 1.73 | 1.73 | 1    | 1    | 1.73  | 1.73  | $\infty$ |
| Phantom deviation from target ( $\epsilon'$ , $\sigma$ )                 | 1.9  | N | 1    | 1.90 | 1    | 0.87 | 1.90  | 1.65  | $\infty$ |
| $u(\Delta\text{SAR})$                                                    | /    |   |      |      |      |      | 11.89 | 11.85 |          |
| Expanded uncertainty (95% confidence interval)                           | /    |   |      |      |      |      | 23.79 | 23.70 |          |

## 4. Measurement System

### 4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  
 $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

## 4.2 MVG SAR System

### 4.2.1 SAR system diagram



### 4.2.2 Robot



A standard high precision 6-axis robot (Denso) with teaches pendant with Scanning System

- It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- Must be able to set the probe orthogonal of the surface of the phantom ( $\pm 30^\circ$ ).
- Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.

#### 4.2.3 E-Field Probe

For the measurements, the Specific Dosimetric SSE2 E-Field Probe with following specifications is used:

- Dynamic range: 0.01-100 W/kg
- Tip diameter: 2mm for SSE2
- Distance between probe tip and sensor centre: 1mm for SSE2
- Distance between sensor centre and the inner phantom surface: 2mm for  $f \geq 4\text{GHz}$ .
- Probe linearity:  $< 0.25\text{dB}$ .
- Axial Isotropy:  $< 0.25\text{dB}$ .
- Spherical Isotropy:  $< 0.50\text{dB}$ .
- Calibration range: 150 to 6000 MHz for head & body simulating liquid
- Angle between probe axis (evaluation axis) and surface normal line: less than  $20^\circ$ .



#### 4.2.4 Phantoms

##### **SAM Phantom**

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The probe scanning of the E-Field is done in the 2 halves of the normalized head. The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size. It enables the dosimetric evaluation of left and right-hand phone usage and includes an additional flat phantom part for the simplified body performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



**SAM Phantom**

The thickness of the phantom amounts to  $2\text{ mm} \pm 0.2\text{ mm}$ . The materials for the phantom do not affect the radiation of the device under test (DUT) :  $\epsilon_r' < 5$   
The head is filled with tissue simulating liquid. The hand do not have to be modeled.

| TWIN SAM phantom  |                                         |                       |      |
|-------------------|-----------------------------------------|-----------------------|------|
|                   | Mechanical                              | Electrical            |      |
| Overall thickness | $2 \pm 0.2\text{ mm}$ (except ear area) | Relative permittivity | 3.4  |
| Dimensions        | 1000 mm(L) x 500 mm(W) x 200 mm(H)      | Loss tangent          | 0.02 |
| Maximum volume    | 27 L                                    |                       |      |
| Material          | Fiberglass based                        |                       |      |

#### ELLIPTICAL Phantom

The phantom is for Body performance check filled with tissue-equivalent liquid to a depth of at least 150 mm, whose shell material is resistant to damage or reaction with tissue-equivalent liquid chemicals.




**ELLI Phantom**

The shape of the phantom is an ellipse with length  $600\text{ mm} \pm 5\text{ mm}$  and width  $400\text{ mm} \pm 5\text{ mm}$ .  
The phantom shell is made of low-loss and low-permittivity material, having loss tangent  $\tan \delta \leq 0.05$  and relative permittivity:  
 $\epsilon_r' \leq 5$  for  $f \leq 3\text{ GHz}$   
 $3 \leq \epsilon_r' \leq 5$  for  $f > 3\text{ GHz}$   
The thickness of the bottom-wall of the flat phantom is 2.0 mm with a tolerance of  $\pm 0.2\text{ mm}$ .

| Technical & mechanical characteristics |                                 |
|----------------------------------------|---------------------------------|
| Shell thickness                        | $2\text{ mm} \pm 0.2\text{ mm}$ |
| Filling volume                         | 25 L                            |
| Dimensions                             | 600 mm x 400 mm x 200 mm        |
| Permittivity                           | 4.4                             |
| Loss tangent                           | 0.017                           |

#### 4.2.5 Device Holder



| System Material | Permittivity | Loss tangent |
|-----------------|--------------|--------------|
| Delrin          | 3.7          | 0.005        |

(The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.)

| System Material | Permittivity | Loss tangent |
|-----------------|--------------|--------------|
| PMMA            | 2.9          | 0.028        |


#### 4.2.6 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)


| Frequency<br>(MHz)                  | Water<br>(%) | Sugar<br>(%)          | Cellulose<br>(%) | Salt<br>(%) | Preventol<br>(%)    | DGBE<br>(%) | Conductivity<br>σ (S/m) | Permittivity<br>ε |
|-------------------------------------|--------------|-----------------------|------------------|-------------|---------------------|-------------|-------------------------|-------------------|
| 750                                 | 41.1         | 57.0                  | 0.2              | 1.4         | 0.2                 | 0           | 0.89                    | 41.9              |
| 835                                 | 40.3         | 57.9                  | 0.2              | 1.4         | 0.2                 | 0           | 0.90                    | 41.5              |
| 900                                 | 40.3         | 57.9                  | 0.2              | 1.4         | 0.2                 | 0           | 0.97                    | 41.5              |
| 1800, 1900, 2000                    | 55.2         | 0                     | 0                | 0.3         | 0                   | 44.5        | 1.4                     | 40.0              |
| 2450                                | 55.0         | 0                     | 0                | 0.1         | 0                   | 44.9        | 1.80                    | 39.2              |
| 2600                                | 54.9         | 0                     | 0                | 0.1         | 0                   | 45.0        | 1.96                    | 39.0              |
| Frequency<br>(MHz)                  | Water<br>(%) | Hexyl Carbitol<br>(%) |                  |             | Triton X-100<br>(%) |             | Conductivity<br>σ (S/m) | Permittivity<br>ε |
| 5200                                | 62.52        | 17.24                 |                  |             | 17.24               |             | 4.66                    | 36.0              |
| 5800                                | 62.52        | 17.24                 |                  |             | 17.24               |             | 5.27                    | 35.3              |
| Body (From instrument manufacturer) |              |                       |                  |             |                     |             |                         |                   |
| Frequency<br>(MHz)                  | Water<br>(%) | Sugar<br>(%)          | Cellulose<br>(%) | Salt<br>(%) | Preventol<br>(%)    | DGBE<br>(%) | Conductivity<br>σ (S/m) | Permittivity<br>ε |
| 750                                 | 51.7         | 47.2                  | 0                | 0.9         | 0.1                 | 0           | 0.96                    | 55.5              |
| 835                                 | 50.8         | 48.2                  | 0                | 0.9         | 0.1                 | 0           | 0.97                    | 55.2              |
| 900                                 | 50.8         | 48.2                  | 0                | 0.9         | 0.1                 | 0           | 1.05                    | 55.0              |
| 1800, 1900, 2000                    | 70.2         | 0                     | 0                | 0.4         | 0                   | 29.4        | 1.52                    | 53.3              |
| 2450                                | 68.6         | 0                     | 0                | 0.1         | 0                   | 31.3        | 1.95                    | 52.7              |
| 2600                                | 68.2         | 0                     | 0                | 0.1         | 0                   | 31.7        | 2.16                    | 52.5              |
| Frequency(MHz)                      | Water        | DGBE<br>(%)           |                  |             | Salt<br>(%)         |             | Conductivity<br>σ (S/m) | Permittivity<br>ε |
| 5200                                | 78.60        | 21.40                 |                  |             | /                   |             | 5.30                    | 49.00             |
| 5800                                | 78.50        | 21.40                 |                  |             | 0.1                 |             | 6.00                    | 48.20             |

## 5. System Verification

### 5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. The setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

## 5.2 System Check Setup



## 6. TEST POSITION CONFIGURATIONS


According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

## 6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

### 6.1.1 Two Imaginary Lines on the Handset

- The vertical center line passes through two points on the front side of the handset - the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the bottom of the handset.
- The horizontal line is perpendicular to the vertical center line and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical center line is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



### 6.1.2 Two Imaginary Lines on the Handset


- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with

the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.



### 6.1.3 Titled Position

- (a) To position the device in the “cheek” position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.




## 6.2 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of


body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance  $\leq 5$  mm to support compliance.



### 6.3 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing



functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).

## 6.4 Product Specific 10g Exposure Consideration


According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at  $\leq 25$  mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

## 7. Measurement Procedure

### 7.1 Measurement Process Diagram

Body SAR



IEC

## 7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-

processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

|                                                                                                                                                          |                           |                                                                   | ≤3GHz                                                                                                                                                                                                                                                             | >3GHz                                              |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| Maximum distance from closest measurement point<br>(geometric center of probe sensors) to phantom surface                                                |                           |                                                                   | 5±1 mm                                                                                                                                                                                                                                                            | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm |
| Maximum probe angle from probe axis to phantom surface<br>normal at the measurement location                                                             |                           |                                                                   | 30°±1°                                                                                                                                                                                                                                                            | 20°±1°                                             |
| Maximum area scan spatial resolution: Δx Area , Δy Area                                                                                                  |                           |                                                                   | ≤ 2 GHz: ≤ 15 mm<br>2 – 3 GHz: ≤ 12 mm                                                                                                                                                                                                                            | 3–4 GHz: ≤ 12 mm<br>4 – 6 GHz: ≤ 10 mm             |
|                                                                                                                                                          |                           |                                                                   | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                    |
| Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom                                                                                                  |                           |                                                                   | ≤ 2 GHz: ≤ 8 mm<br>2 – 3 GHz: ≤ 5 mm*                                                                                                                                                                                                                             | 3–4 GHz: ≤ 5 mm*<br>4 – 6 GHz: ≤ 4 mm*             |
| Maximum zoom scan spatial resolution, normal to phantom surface                                                                                          | uniform grid: Δz Zoom (n) |                                                                   | ≤ 5 mm                                                                                                                                                                                                                                                            | 3–4 GHz: ≤ 4 mm                                    |
|                                                                                                                                                          | 4–5 GHz: ≤ 3 mm           |                                                                   |                                                                                                                                                                                                                                                                   |                                                    |
|                                                                                                                                                          | graded grid               | Δz Zoom (1):<br>between 1st two points closest to phantom surface | ≤ 4 mm                                                                                                                                                                                                                                                            | 5–6 GHz: ≤ 2 mm                                    |
|                                                                                                                                                          |                           |                                                                   |                                                                                                                                                                                                                                                                   | 3–4 GHz: ≤ 3 mm                                    |
|                                                                                                                                                          |                           |                                                                   |                                                                                                                                                                                                                                                                   | 4–5 GHz: ≤ 2.5 mm                                  |
|                                                                                                                                                          |                           |                                                                   |                                                                                                                                                                                                                                                                   | 5–6 GHz: ≤ 2 mm                                    |
|                                                                                                                                                          |                           |                                                                   |                                                                                                                                                                                                                                                                   | Δz Zoom (n>1):<br>between subsequent points        |
| Minimum zoom scan volume                                                                                                                                 | x, y, z                   |                                                                   | ≥30 mm                                                                                                                                                                                                                                                            | 3–4 GHz: ≥ 28 mm                                   |
|                                                                                                                                                          |                           |                                                                   |                                                                                                                                                                                                                                                                   | 4–5 GHz: ≥ 25 mm                                   |
|                                                                                                                                                          |                           |                                                                   |                                                                                                                                                                                                                                                                   | 5–6 GHz: ≥ 22 mm                                   |
| Note:                                                                                                                                                    |                           |                                                                   |                                                                                                                                                                                                                                                                   |                                                    |
| 1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528- 2011 for details.                 |                           |                                                                   |                                                                                                                                                                                                                                                                   |                                                    |
| 2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB                                       |                           |                                                                   |                                                                                                                                                                                                                                                                   |                                                    |
| 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                           |                                                                   |                                                                                                                                                                                                                                                                   |                                                    |

## 7.3 Measurement Procedure

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.

- c. Measurement of the SAR distribution with a grid of 8 to 16mm \* 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 \* 30 \* 30 mm or 32 \* 32 \* 32 mm is assessed by measuring 5 or 8 \* 5 or 8 \* 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

## 7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

## 8. Conducted RF Output Power

### 8.1 GSM

| Mode: GSM850 | Maximum Tune-up(dBm) | Burst Average Power (dBm) |          |          | Division Factors | Frame-Average Power (dBm) |          |          |
|--------------|----------------------|---------------------------|----------|----------|------------------|---------------------------|----------|----------|
|              |                      | CH128                     | CH190    | CH251    |                  | CH128                     | CH190    | CH251    |
|              |                      | 824.2MHz                  | 836.6MHz | 848.8MHz |                  | 824.2MHz                  | 836.6MHz | 848.8MHz |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |           |                      |                           |           |           |                  |                           |           |           |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----------------------|---------------------------|-----------|-----------|------------------|---------------------------|-----------|-----------|
| GSM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |           | 33.00                | 32.63                     | 32.68     | 32.81     | -9.03            | 23.60                     | 23.65     | 23.78     |
| GPRS<br>(GMSK)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 1Tx slot  | 33.00                | 32.53                     | 32.39     | 32.49     | -9.03            | 23.50                     | 23.36     | 23.46     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 2Tx slots | 31.50                | 31.37                     | 31.33     | 31.47     | -6.02            | 25.35                     | 25.31     | 25.45     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 3Tx slots | 29.50                | 28.95                     | 28.91     | 29.15     | -4.26            | 24.69                     | 24.65     | 24.89     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 4Tx slots | 28.00                | 27.71                     | 27.72     | 27.95     | -3.01            | 24.70                     | 24.71     | 24.94     |
| EGPRS<br>(8PSK)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 1Tx slot  | 27.50                | 27.08                     | 27.16     | 27.12     | -9.03            | 18.05                     | 18.13     | 18.09     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 2Tx slots | 26.50                | 26.15                     | 26.17     | 26.18     | -6.02            | 20.13                     | 20.15     | 20.16     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 3Tx slots | 24.50                | 24.04                     | 24.19     | 24.15     | -4.26            | 19.78                     | 19.93     | 19.89     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 4Tx slots | 23.00                | 22.72                     | 22.73     | 22.77     | -3.01            | 19.71                     | 19.72     | 19.76     |
| Mode: GSM1900                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |           | Maximum Tune-up(dBm) | Burst Average Power (dBm) |           |           | Division Factors | Frame-Average Power (dBm) |           |           |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |           |                      | CH512                     | CH661     | CH810     |                  | CH512                     | CH661     | CH810     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |           |                      | 1850.2MHz                 | 1880.0MHz | 1909.8MHz |                  | 1850.2MHz                 | 1880.0MHz | 1909.8MHz |
| GSM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |           | 29.50                | 29.22                     | 28.85     | 28.64     | -9.03            | 20.19                     | 19.82     | 19.61     |
| GPRS<br>(GMSK)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 1Tx slot  | 29.50                | 29.36                     | 28.85     | 28.60     | -9.03            | 20.33                     | 19.82     | 19.57     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 2Tx slots | 28.50                | 28.37                     | 27.88     | 27.60     | -6.02            | 22.35                     | 21.86     | 21.58     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 3Tx slots | 26.50                | 26.06                     | 25.61     | 25.33     | -4.26            | 21.80                     | 21.35     | 21.07     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 4Tx slots | 25.00                | 24.87                     | 24.45     | 24.22     | -3.01            | 21.86                     | 21.44     | 21.21     |
| EGPRS<br>(8PSK)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 1Tx slot  | 26.00                | 25.12                     | 25.99     | 24.66     | -9.03            | 16.09                     | 16.96     | 15.63     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 2Tx slots | 25.00                | 24.06                     | 23.88     | 24.65     | -6.02            | 18.04                     | 17.86     | 18.63     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 3Tx slots | 22.50                | 22.16                     | 21.87     | 21.66     | -4.26            | 17.90                     | 17.61     | 17.40     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 4Tx slots | 21.50                | 21.04                     | 20.78     | 20.54     | -3.01            | 18.03                     | 17.77     | 17.53     |
| Note:<br>1) Division Factors<br>To average the power, the division factor is as follows:<br>1Tx-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB<br>2Tx-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB<br>3Tx-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB<br>4Tx-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB |           |                      |                           |           |           |                  |                           |           |           |

## 8.2 WCDMA

| Mode      |           | Maximum Tune-up(dBm) | WCDMA Band II         |        |        |
|-----------|-----------|----------------------|-----------------------|--------|--------|
|           |           |                      | Conducted Power (dBm) |        |        |
|           |           |                      | CH9262                | CH9400 | CH9538 |
| RMC 12.2K |           | 21.00                | 20.94                 | 20.46  | 20.74  |
| HSDPA     | Subtest-1 | 19.00                | 18.68                 | 18.18  | 18.50  |
|           | Subtest-2 | 19.00                | 18.68                 | 18.19  | 18.47  |
|           | Subtest-3 | 19.00                | 18.67                 | 18.14  | 18.50  |
|           | Subtest-4 | 19.00                | 18.66                 | 18.15  | 18.53  |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |                      |                       |        |        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----------------------|-----------------------|--------|--------|
| HSUPA                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Subtest-1 | 16.50                | 16.42                 | 15.63  | 16.23  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-2 | 16.50                | 16.14                 | 15.43  | 15.95  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-3 | 16.50                | 16.42                 | 15.90  | 16.26  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-4 | 16.50                | 16.11                 | 15.46  | 16.23  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-5 | 16.50                | 16.31                 | 15.82  | 16.17  |
| Mode                                                                                                                                                                                                                                                                                                                                                                                                                                                     |           | Maximum Tune-up(dBm) | WCDMA Band IV         |        |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |                      | Conducted Power (dBm) |        |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |                      | CH1312                | CH1413 | CH1513 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |                      | 1712.4                | 1732.6 | 1752.6 |
| RMC 12.2K                                                                                                                                                                                                                                                                                                                                                                                                                                                |           | 21.50                | 20.68                 | 20.50  | 21.26  |
| HSDPA                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Subtest-1 | 19.00                | 18.27                 | 18.13  | 18.81  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-2 | 19.00                | 18.27                 | 18.10  | 18.83  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-3 | 19.00                | 18.26                 | 18.12  | 18.81  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-4 | 19.00                | 18.25                 | 18.12  | 18.80  |
| HSUPA                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Subtest-1 | 17.00                | 16.14                 | 15.92  | 16.69  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-2 | 16.50                | 16.09                 | 15.94  | 16.35  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-3 | 16.50                | 16.13                 | 15.47  | 16.36  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-4 | 17.00                | 15.81                 | 15.93  | 16.69  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-5 | 18.00                | 16.96                 | 15.84  | 17.56  |
| Mode                                                                                                                                                                                                                                                                                                                                                                                                                                                     |           | Maximum Tune-up(dBm) | WCDMA Band V          |        |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |                      | Conducted Power (dBm) |        |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |                      | CH4132                | CH4183 | CH4233 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |                      | 826.4                 | 836.6  | 846.6  |
| RMC 12.2K                                                                                                                                                                                                                                                                                                                                                                                                                                                |           | 21.50                | 20.50                 | 21.21  | 21.07  |
| HSDPA                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Subtest-1 | 19.00                | 18.05                 | 18.78  | 18.61  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-2 | 19.00                | 18.04                 | 18.79  | 18.59  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-3 | 19.00                | 18.06                 | 18.79  | 18.60  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-4 | 19.00                | 18.07                 | 18.77  | 18.61  |
| HSUPA                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Subtest-1 | 17.00                | 15.92                 | 16.61  | 16.48  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-2 | 16.50                | 15.62                 | 16.33  | 16.00  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-3 | 16.50                | 15.91                 | 16.34  | 16.02  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-4 | 17.00                | 16.08                 | 16.57  | 16.49  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Subtest-5 | 17.50                | 16.84                 | 17.46  | 16.47  |
| Per KDB 941225 D01, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/2$ dB higher than the primary mode (RMC12.2kbps) or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is $\leq 1.2$ W/kg, SAR measurement is not required for the secondary mode. |           |                      |                       |        |        |

## 8.3 LTE

### Band 2

| LTE-FDD Band 2 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |           |           |
|----------------|------------|---------------|-----------|----------------------|----------------------|-----------|-----------|
| Bandwidth      | Modulation | RB allocation | RB offset |                      | 18607                | 18900     | 19193     |
|                |            |               |           |                      | 1850.7MHz            | 1880.0MHz | 1909.3MHz |
| 1.4MHz         | QPSK       | 1             | 0         | 21.50                | 21.18                | 21.11     | 20.95     |
|                |            |               | 2         | 21.50                | 21.32                | 21.26     | 21.04     |
|                |            |               | 5         | 21.50                | 21.21                | 21.12     | 20.94     |
|                |            | 3             | 0         | 21.50                | 21.36                | 21.21     | 21.02     |
|                |            |               | 2         | 21.50                | 21.35                | 21.23     | 21.04     |

|           |            |               |           |                      |           |           |           |
|-----------|------------|---------------|-----------|----------------------|-----------|-----------|-----------|
|           | 16QAM      | 6             | 3         | 21.50                | 21.37     | 21.21     | 21.01     |
|           |            |               | 0         | 20.50                | 20.30     | 20.16     | 20.02     |
|           |            | 1             | 0         | 20.50                | 20.24     | 20.14     | 20.07     |
|           |            |               | 2         | 20.50                | 20.34     | 20.22     | 20.19     |
|           |            |               | 5         | 20.50                | 20.24     | 20.17     | 20.06     |
|           |            | 3             | 0         | 21.00                | 20.52     | 20.25     | 19.93     |
|           |            |               | 2         | 21.00                | 20.55     | 20.23     | 19.98     |
|           |            |               | 3         | 21.00                | 20.52     | 20.21     | 19.96     |
|           |            | 6             | 0         | 19.50                | 19.38     | 19.13     | 19.02     |
|           |            |               |           |                      |           |           |           |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 18615     | 18900     | 19185     |
|           |            |               |           |                      | 1851.5MHz | 1880.0MHz | 1908.5MHz |
| 3MHz      | QPSK       | 1             | 0         | 21.50                | 21.31     | 21.20     | 20.99     |
|           |            |               | 7         | 21.50                | 21.42     | 21.30     | 21.13     |
|           |            |               | 14        | 21.50                | 21.30     | 21.17     | 20.98     |
|           |            | 8             | 0         | 20.50                | 20.30     | 20.17     | 19.99     |
|           |            |               | 4         | 20.50                | 20.32     | 20.19     | 20.00     |
|           |            |               | 7         | 20.50                | 20.30     | 20.18     | 19.97     |
|           | 16QAM      | 15            | 0         | 20.50                | 20.28     | 20.15     | 19.98     |
|           |            |               | 0         | 20.50                | 20.36     | 20.34     | 20.49     |
|           |            |               | 7         | 21.00                | 20.47     | 20.46     | 20.62     |
|           |            | 1             | 14        | 20.50                | 20.31     | 20.33     | 20.48     |
|           |            |               | 0         | 19.50                | 19.41     | 19.20     | 19.15     |
|           |            |               | 4         | 19.50                | 19.46     | 19.26     | 19.20     |
|           |            | 8             | 7         | 19.50                | 19.42     | 19.20     | 19.12     |
|           |            |               | 0         | 19.50                | 19.38     | 19.18     | 19.06     |
|           |            |               |           |                      |           |           |           |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 18625     | 18900     | 19175     |
|           |            |               |           |                      | 1852.5MHz | 1880.0MHz | 1907.5MHz |
| 5MHz      | QPSK       | 1             | 0         | 21.50                | 21.28     | 21.15     | 20.99     |
|           |            |               | 13        | 21.50                | 21.36     | 21.22     | 21.12     |
|           |            |               | 24        | 21.50                | 21.25     | 21.12     | 21.00     |
|           |            | 12            | 0         | 20.50                | 20.26     | 20.15     | 19.99     |
|           |            |               | 6         | 20.50                | 20.35     | 20.21     | 20.10     |
|           |            |               | 13        | 20.50                | 20.25     | 20.17     | 19.98     |
|           | 16QAM      | 25            | 0         | 20.50                | 20.25     | 20.14     | 19.98     |
|           |            |               | 0         | 20.50                | 20.34     | 20.43     | 19.85     |
|           |            |               | 13        | 20.50                | 20.46     | 20.48     | 19.95     |
|           |            | 1             | 24        | 20.50                | 20.36     | 20.33     | 19.84     |
|           |            |               | 0         | 19.50                | 19.29     | 19.19     | 19.00     |
|           |            |               | 6         | 19.50                | 19.37     | 19.31     | 19.05     |
|           |            | 12            | 13        | 19.50                | 19.31     | 19.27     | 18.94     |
|           |            |               | 0         | 19.50                | 19.35     | 19.19     | 19.03     |
|           |            |               |           |                      |           |           |           |

| LTE-FDD Band 2 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |           |           |       |
|----------------|------------|---------------|-----------|----------------------|----------------------|-----------|-----------|-------|
| Bandwidth      | Modulation | RB allocation | RB offset |                      | 18650                | 18900     | 19150     |       |
|                |            |               |           |                      | 1855.0MHz            | 1880.0MHz | 1905.0MHz |       |
| 10MHz          | QPSK       | 1             | 0         | 21.50                | 21.34                | 21.21     | 21.09     |       |
|                |            |               | 25        | 22.00                | 21.54                | 21.36     | 21.25     |       |
|                |            |               | 49        | 21.50                | 21.32                | 21.14     | 21.05     |       |
|                |            | 25            | 0         | 20.50                | 20.28                | 20.22     | 20.05     |       |
|                |            |               | 13        | 20.50                | 20.36                | 20.23     | 20.10     |       |
|                |            |               | 25        | 20.50                | 20.27                | 20.23     | 20.06     |       |
|                | 16QAM      | 50            | 0         | 20.50                | 20.28                | 20.19     | 20.06     |       |
|                |            |               | 1         | 0                    | 21.00                | 20.35     | 20.37     | 20.65 |
|                |            |               |           | 25                   | 21.00                | 20.54     | 20.55     | 20.76 |
|                |            | 49            |           | 21.00                | 20.35                | 20.29     | 20.54     |       |
|                |            | 12            | 0         | 20.50                | 20.37                | 20.23     | 20.13     |       |

|           |            |               |           |                      |           |           |           |
|-----------|------------|---------------|-----------|----------------------|-----------|-----------|-----------|
|           |            |               | 19        | 20.50                | 20.46     | 20.28     | 20.19     |
|           |            |               | 38        | 20.50                | 20.35     | 20.19     | 20.08     |
|           |            | 27            | 0         | 19.50                | 19.40     | 19.36     | 19.04     |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 18675     | 18900     | 19125     |
|           |            |               |           |                      | 1857.5MHz | 1880.0MHz | 1902.5MHz |
| 15MHz     | QPSK       | 1             | 0         | 21.50                | 21.24     | 21.13     | 20.99     |
|           |            |               | 38        | 21.50                | 21.38     | 21.24     | 21.08     |
|           |            |               | 74        | 21.50                | 21.23     | 21.06     | 20.97     |
|           |            | 36            | 0         | 20.50                | 20.34     | 20.20     | 20.15     |
|           |            |               | 18        | 20.50                | 20.38     | 20.26     | 20.14     |
|           |            |               | 39        | 20.50                | 20.31     | 20.23     | 20.16     |
|           | 16QAM      | 75            | 0         | 20.50                | 20.32     | 20.26     | 20.15     |
|           |            |               | 0         | 21.00                | 20.63     | 20.34     | 20.55     |
|           |            |               | 38        | 21.00                | 20.72     | 20.41     | 20.64     |
|           |            | 12            | 74        | 21.00                | 20.60     | 20.22     | 20.45     |
|           |            |               | 0         | 20.50                | 20.21     | 20.21     | 20.14     |
|           |            |               | 31        | 20.50                | 20.31     | 20.25     | 20.16     |
|           |            |               | 63        | 20.50                | 20.22     | 20.15     | 20.02     |
|           |            | 27            | 48        | 19.50                | 19.32     | 19.30     | 18.98     |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 18700     | 18900     | 19100     |
|           |            |               |           |                      | 1860.0MHz | 1880.0MHz | 1900.0MHz |
| 20MHz     | QPSK       | 1             | 0         | 21.50                | 21.04     | 21.05     | 20.89     |
|           |            |               | 50        | 21.50                | 21.47     | 21.42     | 21.26     |
|           |            |               | 99        | 21.50                | 21.02     | 20.90     | 20.81     |
|           |            | 50            | 0         | 20.50                | 20.33     | 20.14     | 20.26     |
|           |            |               | 25        | 20.50                | 20.31     | 20.22     | 20.16     |
|           |            |               | 50        | 20.50                | 20.21     | 20.25     | 20.16     |
|           | 16QAM      | 100           | 0         | 20.50                | 20.26     | 20.20     | 20.23     |
|           |            |               | 0         | 21.00                | 20.57     | 20.25     | 20.17     |
|           |            |               | 50        | 21.00                | 20.98     | 20.57     | 20.54     |
|           |            | 12            | 99        | 21.00                | 20.61     | 20.06     | 20.04     |
|           |            |               | 0         | 20.50                | 20.13     | 20.02     | 19.99     |
|           |            |               | 44        | 20.50                | 20.39     | 20.21     | 20.18     |
|           |            |               | 88        | 20.50                | 20.15     | 19.92     | 19.88     |
|           |            | 27            | 0         | 19.50                | 19.33     | 19.21     | 18.98     |

## Band 4

| LTE-FDD Band 4 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |           |           |
|----------------|------------|---------------|-----------|----------------------|----------------------|-----------|-----------|
| Bandwidth      | Modulation | RB allocation | RB offset |                      | 19957                | 20175     | 20393     |
|                |            |               |           |                      | 1710.7MHz            | 1732.5MHz | 1754.3MHz |
| 1.4MHz         | QPSK       | 1             | 0         | 21.50                | 20.80                | 20.96     | 21.20     |
|                |            |               | 2         | 21.50                | 20.91                | 21.00     | 21.32     |
|                |            |               | 5         | 21.50                | 20.78                | 20.96     | 21.19     |
|                |            | 3             | 0         | 21.50                | 20.92                | 21.09     | 21.26     |
|                |            |               | 2         | 21.50                | 20.96                | 21.09     | 21.10     |
|                |            |               | 3         | 21.50                | 20.95                | 21.05     | 20.80     |
|                |            | 6             | 0         | 20.50                | 19.86                | 20.01     | 20.22     |
|                | 16QAM      | 1             | 0         | 20.00                | 19.98                | 19.96     | 19.78     |
|                |            |               | 2         | 20.50                | 20.14                | 20.05     | 20.14     |
|                |            |               | 5         | 20.50                | 19.97                | 20.00     | 20.04     |
|                |            | 3             | 0         | 20.50                | 19.86                | 20.24     | 20.04     |

|           |            |               |           |                      |           |           |           |
|-----------|------------|---------------|-----------|----------------------|-----------|-----------|-----------|
|           |            |               | 2         | 20.50                | 19.89     | 20.26     | 19.89     |
|           |            |               | 3         | 20.50                | 19.90     | 20.27     | 19.93     |
|           |            | 6             | 0         | 19.50                | 18.95     | 19.10     | 19.24     |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 19965     | 20175     | 20385     |
|           |            |               |           |                      | 1711.5MHz | 1732.5MHz | 1753.5MHz |
| 3MHz      | QPSK       | 1             | 0         | 21.50                | 20.90     | 20.95     | 21.20     |
|           |            |               | 7         | 21.50                | 20.91     | 21.06     | 21.33     |
|           |            |               | 14        | 21.50                | 20.84     | 20.91     | 21.06     |
|           |            | 8             | 0         | 20.50                | 19.69     | 19.95     | 20.24     |
|           |            |               | 4         | 20.50                | 19.80     | 19.98     | 20.24     |
|           |            |               | 7         | 20.50                | 19.78     | 19.94     | 20.21     |
|           |            | 15            | 0         | 20.50                | 19.80     | 19.95     | 20.21     |
|           | 16QAM      | 1             | 0         | 20.50                | 19.83     | 20.16     | 20.30     |
|           |            |               | 7         | 20.50                | 19.76     | 20.27     | 20.40     |
|           |            |               | 14        | 20.50                | 19.63     | 20.18     | 20.26     |
|           |            | 8             | 0         | 19.50                | 18.77     | 18.99     | 19.44     |
|           |            |               | 4         | 19.50                | 18.89     | 19.01     | 19.47     |
|           |            |               | 7         | 19.50                | 18.96     | 19.00     | 19.41     |
|           |            | 15            | 0         | 19.50                | 18.87     | 18.96     | 19.32     |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 19976     | 20175     | 20375     |
|           |            |               |           |                      | 1712.5MHz | 1732.5MHz | 1752.5MHz |
| 5MHz      | QPSK       | 1             | 0         | 21.50                | 20.77     | 20.85     | 21.07     |
|           |            |               | 13        | 21.50                | 20.88     | 20.94     | 21.17     |
|           |            |               | 24        | 21.00                | 20.75     | 20.80     | 20.78     |
|           |            | 12            | 0         | 20.00                | 19.70     | 19.93     | 19.94     |
|           |            |               | 6         | 20.50                | 19.78     | 19.99     | 20.02     |
|           |            |               | 13        | 20.50                | 19.45     | 20.01     | 19.99     |
|           |            | 25            | 0         | 20.00                | 19.42     | 19.94     | 19.97     |
|           | 16QAM      | 1             | 0         | 20.50                | 19.64     | 20.16     | 19.44     |
|           |            |               | 13        | 20.50                | 19.59     | 20.28     | 19.60     |
|           |            |               | 24        | 20.50                | 19.44     | 20.18     | 19.48     |
|           |            | 12            | 0         | 19.50                | 18.59     | 19.10     | 18.99     |
|           |            |               | 6         | 19.50                | 18.68     | 19.09     | 19.06     |
|           |            |               | 13        | 19.50                | 18.71     | 19.05     | 19.05     |
|           |            | 25            | 0         | 19.50                | 18.74     | 18.99     | 19.09     |

| LTE-FDD Band 4 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |           |           |
|----------------|------------|---------------|-----------|----------------------|----------------------|-----------|-----------|
| Bandwidth      | Modulation | RB allocation | RB offset |                      | 20000                | 20175     | 20350     |
|                |            |               |           |                      | 1715.0MHz            | 1732.5MHz | 1750.0MHz |
| 10MHz          | QPSK       | 1             | 0         | 21.50                | 20.81                | 20.89     | 21.06     |
|                |            |               | 25        | 21.50                | 21.06                | 21.10     | 21.01     |
|                |            |               | 49        | 21.00                | 20.84                | 20.68     | 20.59     |
|                |            | 25            | 0         | 20.50                | 19.76                | 20.04     | 19.65     |
|                |            |               | 13        | 20.50                | 19.83                | 20.00     | 19.68     |
|                |            |               | 25        | 20.00                | 19.98                | 19.99     | 19.72     |
|                |            | 50            | 0         | 20.00                | 19.83                | 19.99     | 19.68     |
|                | 16QAM      | 1             | 1         | 20.50                | 19.78                | 20.04     | 20.10     |
|                |            | 12            | 12        | 20.50                | 19.79                | 20.31     | 20.36     |
|                |            | 27            | 27        | 20.50                | 19.78                | 20.18     | 20.13     |
|                |            | 1             | 1         | 20.00                | 19.69                | 19.95     | 19.66     |
|                |            | 12            | 12        | 20.50                | 19.77                | 20.01     | 19.75     |
|                |            | 27            | 27        | 20.00                | 19.86                | 19.96     | 19.69     |
|                |            | 1             | 1         | 19.50                | 18.85                | 19.17     | 18.75     |
| Bandwidth      | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 20025                | 20175     | 20325     |
|                |            |               |           |                      | 1717.5MHz            | 1732.5MHz | 1747.5MHz |

|           |            |               |           |                      |           |           |           |
|-----------|------------|---------------|-----------|----------------------|-----------|-----------|-----------|
| 15MHz     | QPSK       | 1             | 0         | 21.00                | 20.69     | 20.69     | 20.88     |
|           |            |               | 38        | 21.00                | 20.86     | 20.93     | 20.83     |
|           |            |               | 74        | 21.00                | 20.78     | 20.84     | 20.52     |
|           |            | 36            | 0         | 20.00                | 19.70     | 19.98     | 19.59     |
|           |            |               | 18        | 20.00                | 19.85     | 19.98     | 19.73     |
|           |            |               | 39        | 20.00                | 19.95     | 19.96     | 19.66     |
|           |            | 75            | 0         | 20.50                | 19.85     | 20.02     | 19.70     |
|           | 16QAM      | 1             | 0         | 20.50                | 20.06     | 19.96     | 20.04     |
|           |            |               | 38        | 20.50                | 20.15     | 20.15     | 20.21     |
|           |            |               | 74        | 20.50                | 20.14     | 20.08     | 20.10     |
|           |            | 12            | 0         | 20.00                | 19.67     | 19.83     | 19.56     |
|           |            |               | 31        | 20.00                | 19.79     | 19.95     | 19.71     |
|           |            |               | 63        | 20.00                | 19.78     | 19.92     | 19.67     |
|           |            | 27            | 0         | 19.50                | 18.72     | 19.01     | 18.77     |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 20050     | 20175     | 20300     |
|           |            |               |           |                      | 1720.0MHz | 1732.5MHz | 1745.0MHz |
| 20MHz     | QPSK       | 1             | 0         | 21.00                | 20.48     | 20.24     | 20.70     |
|           |            |               | 50        | 21.50                | 20.95     | 21.12     | 21.05     |
|           |            |               | 99        | 21.00                | 20.63     | 20.60     | 20.37     |
|           |            | 50            | 0         | 20.50                | 19.55     | 20.00     | 19.58     |
|           |            |               | 25        | 20.00                | 19.85     | 19.96     | 19.61     |
|           |            |               | 50        | 20.00                | 19.89     | 19.85     | 19.64     |
|           |            | 100           | 0         | 20.00                | 19.75     | 19.97     | 19.60     |
|           | 16QAM      | 1             | 0         | 20.50                | 20.05     | 19.79     | 19.59     |
|           |            |               | 50        | 20.50                | 20.49     | 20.26     | 20.02     |
|           |            |               | 99        | 20.50                | 20.21     | 19.83     | 19.66     |
|           |            | 12            | 0         | 20.00                | 19.60     | 19.60     | 19.37     |
|           |            |               | 44        | 20.00                | 19.86     | 19.93     | 19.66     |
|           |            |               | 88        | 20.00                | 19.80     | 19.71     | 19.46     |
|           |            | 27            | 0         | 19.00                | 18.70     | 18.86     | 18.60     |

## Band 5

| LTE-FDD Band 5 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |          |          |
|----------------|------------|---------------|-----------|----------------------|----------------------|----------|----------|
| Bandwidth      | Modulation | RB allocation | RB offset |                      | 20407                | 20525    | 20643    |
| 1.4MHz         | QPSK       | 1             | 0         | 21.50                | 21.34                | 21.21    | 21.27    |
|                |            |               | 2         | 21.50                | 21.43                | 21.33    | 21.41    |
|                |            |               | 5         | 21.50                | 21.36                | 21.23    | 21.31    |
|                |            | 3             | 0         | 21.50                | 21.38                | 21.34    | 21.35    |
|                |            |               | 2         | 21.50                | 21.45                | 21.36    | 21.35    |
|                |            |               | 3         | 21.50                | 21.42                | 21.31    | 21.28    |
|                |            | 6             | 0         | 20.50                | 20.40                | 20.30    | 20.34    |
|                | 16QAM      | 1             | 0         | 20.50                | 20.42                | 20.24    | 20.21    |
|                |            |               | 2         | 21.00                | 20.57                | 20.31    | 20.37    |
|                |            |               | 5         | 20.50                | 20.45                | 20.23    | 20.29    |
|                |            | 3             | 0         | 20.50                | 20.38                | 20.46    | 20.34    |
|                |            |               | 2         | 21.00                | 20.42                | 20.52    | 20.38    |
|                |            |               | 3         | 20.50                | 20.38                | 20.48    | 20.28    |
|                |            | 6             | 0         | 19.50                | 19.44                | 19.36    | 19.32    |
| Bandwidth      | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 20415                | 20525    | 20635    |
|                |            |               |           |                      | 825.5MHz             | 836.5MHz | 847.5MHz |
| 3MHz           | QPSK       | 1             | 0         | 21.50                | 21.41                | 21.29    | 21.32    |

|  |       |    |    |       |       |       |       |
|--|-------|----|----|-------|-------|-------|-------|
|  |       | 8  | 7  | 22.00 | 21.57 | 21.41 | 21.46 |
|  |       |    | 14 | 21.50 | 21.44 | 21.30 | 21.31 |
|  |       |    | 0  | 20.50 | 20.38 | 20.32 | 20.33 |
|  |       |    | 4  | 20.50 | 20.44 | 20.35 | 20.36 |
|  |       |    | 7  | 20.50 | 20.40 | 20.31 | 20.31 |
|  |       | 15 | 0  | 20.50 | 20.34 | 20.32 | 20.32 |
|  | 16QAM | 1  | 0  | 21.00 | 20.38 | 20.46 | 20.81 |
|  |       |    | 7  | 21.00 | 20.56 | 20.57 | 20.95 |
|  |       |    | 14 | 21.00 | 20.40 | 20.42 | 20.79 |
|  |       | 8  | 0  | 20.00 | 19.50 | 19.36 | 19.54 |
|  |       |    | 4  | 20.00 | 19.56 | 19.43 | 19.59 |
|  |       |    | 7  | 20.00 | 19.52 | 19.35 | 19.52 |
|  |       | 15 | 0  | 19.50 | 19.45 | 19.34 | 19.47 |

| LTE-FDD Band 5 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |          |          |       |
|----------------|------------|---------------|-----------|----------------------|----------------------|----------|----------|-------|
| Bandwidth      | Modulation | RB allocation | RB offset |                      | 20425                | 20525    | 20625    |       |
|                |            |               |           |                      | 826.5MHz             | 836.5MHz | 846.5MHz |       |
| 5MHz           | QPSK       | 1             | 0         | 21.50                | 21.27                | 21.24    | 21.18    |       |
|                |            |               | 13        | 21.50                | 21.43                | 21.30    | 21.38    |       |
|                |            |               | 24        | 21.50                | 21.31                | 21.26    | 21.23    |       |
|                |            | 12            | 0         | 20.50                | 20.30                | 20.34    | 20.33    |       |
|                |            |               | 6         | 20.50                | 20.41                | 20.37    | 20.37    |       |
|                |            |               | 13        | 20.50                | 20.41                | 20.28    | 20.27    |       |
|                |            | 25            | 0         | 20.50                | 20.38                | 20.34    | 20.27    |       |
|                |            | 16QAM         | 1         | 0                    | 20.50                | 20.37    | 20.45    | 20.06 |
|                |            |               |           | 13                   | 21.00                | 20.55    | 20.58    | 20.22 |
|                | 24         |               |           | 20.50                | 20.37                | 20.48    | 20.09    |       |
|                | 12         |               | 0         | 19.50                | 19.40                | 19.37    | 19.40    |       |
|                |            |               | 6         | 19.50                | 19.47                | 19.46    | 19.40    |       |
|                |            |               | 13        | 19.50                | 19.42                | 19.36    | 19.28    |       |
|                | 25         | 0             | 19.50     | 19.48                | 19.40                | 19.37    |          |       |
| Bandwidth      | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 20450                | 20525    | 20600    |       |
|                |            |               |           |                      | 829.0MHz             | 836.5MHz | 844.0MHz |       |
| 10MHz          | QPSK       | 1             | 0         | 21.50                | 21.39                | 21.30    | 21.29    |       |
|                |            |               | 25        | 22.00                | 21.58                | 21.36    | 21.36    |       |
|                |            |               | 49        | 21.50                | 21.33                | 21.29    | 21.31    |       |
|                |            | 25            | 0         | 20.50                | 20.32                | 20.43    | 20.26    |       |
|                |            |               | 13        | 20.50                | 20.38                | 20.37    | 20.31    |       |
|                |            |               | 25        | 20.50                | 20.32                | 20.33    | 20.18    |       |
|                | 50         | 0             | 20.50     | 20.32                | 20.34                | 20.22    |          |       |
|                | 16QAM      | 1             | 0         | 21.00                | 20.34                | 20.44    | 20.81    |       |
|                |            |               | 25        | 21.00                | 20.51                | 20.57    | 20.90    |       |
|                |            |               | 49        | 21.00                | 20.31                | 20.46    | 20.77    |       |
|                |            | 12            | 0         | 20.50                | 20.32                | 20.38    | 20.30    |       |
|                |            |               | 19        | 20.50                | 20.42                | 20.36    | 20.35    |       |
|                |            |               | 38        | 20.50                | 20.33                | 20.29    | 20.28    |       |
|                |            | 27            | 23        | 20.00                | 19.42                | 19.53    | 19.22    |       |

## Band 12

| LTE-FDD Band 12 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |          |          |
|-----------------|------------|---------------|-----------|----------------------|----------------------|----------|----------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 23017                | 23095    | 23173    |
|                 |            |               |           |                      | 699.7MHz             | 707.5MHz | 715.3MHz |

|           |            |               |           |                      |          |          |          |
|-----------|------------|---------------|-----------|----------------------|----------|----------|----------|
| 1.4MHz    | QPSK       | 1             | 0         | 21.50                | 21.00    | 21.10    | 20.97    |
|           |            |               | 2         | 21.50                | 21.06    | 21.16    | 21.06    |
|           |            |               | 5         | 21.50                | 21.03    | 21.05    | 20.97    |
|           |            | 3             | 0         | 21.50                | 21.06    | 21.17    | 21.04    |
|           |            |               | 2         | 21.50                | 21.08    | 21.18    | 21.04    |
|           |            |               | 3         | 21.50                | 21.07    | 21.14    | 21.03    |
|           | 16QAM      | 6             | 0         | 20.50                | 20.14    | 20.20    | 20.02    |
|           |            |               | 0         | 20.50                | 20.05    | 20.11    | 20.01    |
|           |            |               | 2         | 20.50                | 20.14    | 20.21    | 20.13    |
|           |            | 1             | 5         | 20.50                | 20.10    | 20.13    | 20.03    |
|           |            |               | 0         | 20.50                | 20.22    | 20.35    | 20.14    |
|           |            |               | 2         | 20.50                | 20.16    | 20.39    | 20.13    |
|           |            | 3             | 3         | 20.50                | 20.15    | 20.37    | 20.09    |
|           |            |               | 0         | 19.50                | 19.02    | 19.17    | 19.00    |
|           |            | 6             | 0         | 19.50                | 19.02    | 19.17    | 19.00    |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 23025    | 23095    | 23165    |
|           |            |               |           |                      | 700.5MHz | 707.5MHz | 714.5MHz |
| 3MHz      | QPSK       | 1             | 0         | 21.50                | 21.19    | 21.10    | 21.03    |
|           |            |               | 7         | 21.50                | 21.32    | 21.27    | 21.15    |
|           |            |               | 14        | 21.50                | 21.13    | 21.08    | 20.97    |
|           |            | 8             | 0         | 20.50                | 20.23    | 20.18    | 20.09    |
|           |            |               | 4         | 20.50                | 20.27    | 20.22    | 20.12    |
|           |            |               | 7         | 20.50                | 20.20    | 20.19    | 20.06    |
|           |            | 15            | 0         | 20.50                | 20.18    | 20.15    | 20.09    |
|           |            |               | 0         | 21.00                | 20.24    | 20.31    | 20.64    |
|           |            |               | 7         | 21.00                | 20.37    | 20.47    | 20.75    |
|           | 16QAM      | 1             | 14        | 21.00                | 20.18    | 20.29    | 20.56    |
|           |            |               | 0         | 19.50                | 19.28    | 19.16    | 19.23    |
|           |            |               | 4         | 19.50                | 19.29    | 19.17    | 19.28    |
|           |            | 8             | 7         | 19.50                | 19.20    | 19.15    | 19.21    |
|           |            |               | 0         | 19.50                | 19.23    | 19.14    | 19.12    |
|           |            |               | 0         | 19.50                | 19.23    | 19.14    | 19.12    |
|           |            | 15            | 0         | 19.50                | 19.23    | 19.14    | 19.12    |
|           |            |               | 0         | 19.50                | 19.23    | 19.14    | 19.12    |
|           |            |               | 0         | 19.50                | 19.23    | 19.14    | 19.12    |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 23035    | 23095    | 23155    |
|           |            |               |           |                      | 701.5MHz | 707.5MHz | 713.5MHz |
| 5MHz      | QPSK       | 1             | 0         | 21.50                | 21.05    | 20.99    | 20.90    |
|           |            |               | 13        | 21.50                | 21.21    | 21.15    | 21.05    |
|           |            |               | 24        | 21.50                | 21.03    | 21.04    | 20.89    |
|           |            | 12            | 0         | 20.50                | 20.22    | 20.16    | 20.06    |
|           |            |               | 6         | 20.50                | 20.19    | 20.18    | 20.14    |
|           |            |               | 13        | 20.50                | 20.16    | 20.21    | 20.00    |
|           |            | 25            | 0         | 20.50                | 20.16    | 20.19    | 20.05    |
|           |            |               | 0         | 20.50                | 20.18    | 20.32    | 19.81    |
|           |            |               | 13        | 20.50                | 20.27    | 20.47    | 19.98    |
|           | 16QAM      | 1             | 24        | 20.50                | 20.21    | 20.35    | 19.83    |
|           |            |               | 0         | 19.50                | 19.18    | 19.15    | 18.99    |
|           |            |               | 6         | 19.50                | 19.17    | 19.20    | 19.10    |
|           |            | 12            | 13        | 19.50                | 19.15    | 19.20    | 19.01    |
|           |            |               | 0         | 19.50                | 19.19    | 19.16    | 19.07    |
|           |            |               | 0         | 19.50                | 19.19    | 19.16    | 19.07    |
|           |            | 25            | 0         | 19.50                | 19.19    | 19.16    | 19.07    |
|           |            |               | 0         | 19.50                | 19.19    | 19.16    | 19.07    |
|           |            |               | 0         | 19.50                | 19.19    | 19.16    | 19.07    |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 23060    | 23095    | 23130    |
|           |            |               |           |                      | 704.0MHz | 707.5MHz | 711.0MHz |
| 10MHz     | QPSK       | 1             | 0         | 21.50                | 21.06    | 20.99    | 20.99    |
|           |            |               | 25        | 21.50                | 21.30    | 21.25    | 21.17    |
|           |            |               | 49        | 21.50                | 21.09    | 21.00    | 20.95    |
|           |            | 25            | 0         | 20.50                | 20.15    | 20.13    | 20.17    |
|           |            |               | 13        | 20.50                | 20.20    | 20.19    | 20.13    |
|           |            |               | 25        | 20.50                | 20.18    | 20.15    | 20.06    |
|           |            | 50            | 0         | 20.50                | 20.19    | 20.15    | 20.13    |
|           |            |               | 0         | 20.50                | 20.19    | 20.15    | 20.13    |
|           |            |               | 0         | 20.50                | 20.19    | 20.15    | 20.13    |
|           | 16QAM      | 1             | 0         | 20.50                | 20.09    | 20.20    | 20.22    |
|           |            |               | 25        | 20.50                | 20.32    | 20.44    | 20.37    |
|           |            |               | 49        | 20.50                | 20.13    | 20.21    | 20.14    |

|  |  |    |    |       |       |       |       |
|--|--|----|----|-------|-------|-------|-------|
|  |  | 12 | 0  | 20.50 | 20.19 | 20.10 | 20.07 |
|  |  |    | 19 | 20.50 | 20.24 | 20.15 | 20.13 |
|  |  |    | 38 | 20.50 | 20.15 | 20.05 | 20.02 |
|  |  | 27 | 0  | 19.50 | 19.18 | 19.20 | 19.06 |

### Band 13

| LTE-FDD Band 13 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |                   |                   |
|-----------------|------------|---------------|-----------|----------------------|----------------------|-------------------|-------------------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 23205<br>779.5MHz    | 23230<br>782.0MHz | 23255<br>784.5MHz |
| 5MHz            | QPSK       | 1             | 0         | 21.50                | 21.16                | 21.18             | 21.19             |
|                 |            |               | 13        | 21.50                | 21.31                | 21.38             | 21.34             |
|                 |            |               | 24        | 21.50                | 21.22                | 21.23             | 21.19             |
|                 |            | 12            | 0         | 20.50                | 20.29                | 20.38             | 20.36             |
|                 |            |               | 6         | 20.50                | 20.37                | 20.44             | 20.41             |
|                 |            |               | 13        | 20.50                | 20.27                | 20.37             | 20.36             |
|                 |            | 25            | 0         | 20.50                | 20.27                | 20.37             | 20.41             |
|                 |            |               | 0         | 21.00                | 20.03                | 20.33             | 20.53             |
|                 |            |               | 13        | 21.00                | 20.24                | 20.54             | 20.68             |
|                 | 16QAM      | 1             | 24        | 21.00                | 20.13                | 20.37             | 20.52             |
|                 |            |               | 0         | 19.50                | 19.30                | 19.37             | 19.42             |
|                 |            |               | 6         | 19.50                | 19.35                | 19.41             | 19.44             |
|                 |            | 12            | 13        | 19.50                | 19.29                | 19.35             | 19.44             |
|                 |            |               | 0         | 19.50                | 19.32                | 19.40             | 19.40             |
|                 |            |               | 0         | 21.50                | 21.24                | 21.29             | 21.29             |
|                 |            | 25            | 25        | 21.50                | 21.46                | 21.46             | 21.46             |
|                 |            |               | 49        | 21.50                | 21.29                | 21.29             | 21.29             |
|                 |            |               | 0         | 20.50                | 20.45                | 20.45             | 20.45             |
| 10MHz           | QPSK       | 1             | 13        | 20.50                | 20.42                | 20.42             | 20.42             |
|                 |            |               | 25        | 20.50                | 20.47                | 20.47             | 20.47             |
|                 |            |               | 0         | 20.50                | 20.48                | 20.48             | 20.48             |
|                 |            | 25            | 0         | 20.50                | 20.45                | 20.45             | 20.45             |
|                 |            |               | 25        | 21.00                | 20.68                | 20.68             | 20.68             |
|                 |            |               | 49        | 20.50                | 20.42                | 20.42             | 20.42             |
|                 |            | 50            | 0         | 20.50                | 20.33                | 20.33             | 20.33             |
|                 |            |               | 19        | 20.50                | 20.42                | 20.42             | 20.42             |
|                 |            |               | 38        | 20.50                | 20.45                | 20.45             | 20.45             |
|                 | 16QAM      | 1             | 0         | 20.00                | 19.52                | 19.52             | 19.52             |
|                 |            |               | 0         | 20.50                | 20.45                | 20.45             | 20.45             |
|                 |            |               | 25        | 21.00                | 20.68                | 20.68             | 20.68             |
|                 |            | 12            | 49        | 20.50                | 20.42                | 20.42             | 20.42             |
|                 |            |               | 0         | 20.50                | 20.33                | 20.33             | 20.33             |
|                 |            |               | 19        | 20.50                | 20.42                | 20.42             | 20.42             |
|                 |            |               | 38        | 20.50                | 20.45                | 20.45             | 20.45             |
|                 |            | 27            | 0         | 20.00                | 19.52                | 19.52             | 19.52             |

### Band 17

| LTE-FDD Band 17 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |                 |                   |
|-----------------|------------|---------------|-----------|----------------------|----------------------|-----------------|-------------------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 23755<br>706.5MHz    | 23790<br>710MHz | 23825<br>713.5MHz |
| 5MHz            | QPSK       | 1             | 0         | 21.00                | 20.98                | 20.99           | 20.86             |
|                 |            |               | 13        | 21.50                | 21.10                | 21.03           | 20.98             |
|                 |            |               | 24        | 21.50                | 21.03                | 20.93           | 20.88             |
|                 |            | 12            | 0         | 20.50                | 20.10                | 20.09           | 20.05             |
|                 |            |               | 6         | 20.50                | 20.16                | 20.12           | 20.04             |
|                 |            |               | 0         | 20.50                | 20.16                | 20.12           | 20.04             |

|           |            |               |           |                      |        |        |        |
|-----------|------------|---------------|-----------|----------------------|--------|--------|--------|
|           | 16QAM      | 25            | 13        | 20.50                | 20.18  | 20.03  | 19.97  |
|           |            |               | 0         | 20.50                | 20.13  | 20.06  | 20.00  |
|           |            | 1             | 0         | 20.50                | 19.88  | 20.12  | 20.20  |
|           |            |               | 13        | 20.50                | 20.03  | 20.18  | 20.31  |
|           |            |               | 24        | 20.50                | 19.93  | 20.09  | 20.16  |
|           |            | 12            | 0         | 19.50                | 19.12  | 19.02  | 19.04  |
|           |            |               | 6         | 19.50                | 19.18  | 19.08  | 19.08  |
|           |            |               | 13        | 19.50                | 19.18  | 19.00  | 18.97  |
|           |            | 25            | 0         | 19.50                | 19.13  | 19.10  | 18.98  |
|           |            |               |           |                      |        |        |        |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 23780  | 23790  | 23800  |
|           |            |               |           |                      | 709MHz | 710MHz | 711MHz |
| 10MHz     | QPSK       | 1             | 0         | 21.50                | 20.99  | 21.01  | 20.98  |
|           |            |               | 25        | 21.50                | 21.25  | 21.11  | 21.10  |
|           |            |               | 49        | 21.00                | 20.96  | 20.94  | 20.92  |
|           |            | 25            | 0         | 20.50                | 20.13  | 20.12  | 20.08  |
|           |            |               | 13        | 20.50                | 20.11  | 20.09  | 20.08  |
|           |            |               | 25        | 20.50                | 20.10  | 20.04  | 20.01  |
|           |            | 50            | 0         | 20.50                | 20.13  | 20.09  | 20.03  |
|           |            |               |           |                      |        |        |        |
|           |            |               |           |                      |        |        |        |
|           | 16QAM      | 1             | 0         | 21.00                | 20.05  | 20.21  | 20.58  |
|           |            |               | 25        | 21.00                | 20.27  | 20.32  | 20.67  |
|           |            |               | 49        | 21.00                | 20.00  | 20.17  | 20.50  |
|           |            | 12            | 0         | 20.50                | 20.15  | 20.14  | 20.13  |
|           |            |               | 19        | 20.50                | 20.12  | 20.09  | 20.08  |
|           |            |               | 38        | 20.50                | 20.07  | 19.99  | 20.04  |
|           |            | 27            | 23        | 19.50                | 19.19  | 19.18  | 18.98  |
|           |            |               |           |                      |        |        |        |
|           |            |               |           |                      |        |        |        |

## Band 25

| LTE-FDD Band 25 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |                      |           |           |           |
|-----------------|------------|---------------|-----------|----------------------|----------------------|----------------------|-----------|-----------|-----------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 26047                | 26365                | 26683     |           |           |
|                 |            |               |           |                      | 1850.7MHz            | 1882.5MHz            | 1914.3MHz |           |           |
| 1.4MHz          | QPSK       | 1             | 0         | 22.50                | 22.26                | 22.12                | 21.92     |           |           |
|                 |            |               | 2         | 22.50                | 22.43                | 22.24                | 21.88     |           |           |
|                 |            |               | 5         | 22.50                | 22.27                | 22.11                | 21.48     |           |           |
|                 |            | 3             | 0         | 22.50                | 22.31                | 22.20                | 21.53     |           |           |
|                 |            |               | 2         | 22.50                | 22.33                | 22.21                | 21.47     |           |           |
|                 |            |               | 3         | 22.50                | 22.31                | 22.14                | 21.43     |           |           |
|                 |            | 6             | 0         | 21.50                | 21.30                | 21.19                | 20.92     |           |           |
|                 |            |               | 16QAM     | 1                    | 0                    | 21.50                | 21.23     | 21.27     | 20.59     |
|                 |            |               |           |                      | 2                    | 21.50                | 21.35     | 21.38     | 20.62     |
|                 | 5          | 21.50         |           |                      | 21.28                | 21.25                | 20.53     |           |           |
|                 | 3          | 0             |           | 21.50                | 21.35                | 21.11                | 20.83     |           |           |
|                 |            | 2             |           | 21.50                | 21.32                | 21.15                | 20.74     |           |           |
|                 |            | 3             |           | 21.50                | 21.32                | 21.12                | 20.73     |           |           |
|                 | 6          | 0             |           | 20.50                | 20.21                | 20.16                | 19.89     |           |           |
|                 | Bandwidth  | Modulation    |           | RB allocation        | RB offset            | Maximum Tune-up(dBm) | 26055     | 26365     | 26675     |
|                 |            |               |           |                      |                      |                      | 1851.5MHz | 1882.5MHz | 1913.5MHz |
|                 | 3MHz       | QPSK          | 1         | 0                    | 22.50                | 22.36                | 22.21     | 22.00     |           |
|                 |            |               |           | 7                    | 22.50                | 22.48                | 22.30     | 21.89     |           |
| 14              |            |               |           | 22.50                | 22.35                | 22.15                | 21.43     |           |           |
| 8               |            |               | 0         | 21.50                | 21.30                | 21.17                | 20.93     |           |           |
|                 |            |               | 4         | 21.50                | 21.33                | 21.18                | 20.96     |           |           |
|                 |            |               | 7         | 21.50                | 21.30                | 21.19                | 20.92     |           |           |
| 15              |            |               | 0         | 21.50                | 21.28                | 21.16                | 20.90     |           |           |
|                 |            |               | 16QAM     | 1                    | 0                    | 21.50                | 21.31     | 21.34     | 21.19     |
|                 |            |               |           |                      | 7                    | 21.50                | 21.46     | 21.44     | 21.29     |
| 14              |            | 21.50         |           |                      | 21.29                | 21.32                | 20.94     |           |           |
| 8               |            | 0             |           | 20.50                | 20.33                | 20.14                | 20.07     |           |           |
|                 |            | 4             |           | 20.50                | 20.39                | 20.18                | 20.08     |           |           |

|           |            |               |           |                      |           |           |           |
|-----------|------------|---------------|-----------|----------------------|-----------|-----------|-----------|
|           |            |               | 7         | 20.50                | 20.36     | 20.12     | 20.05     |
|           |            | 15            | 0         | 20.50                | 20.32     | 20.10     | 19.94     |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 26065     | 26365     | 26665     |
|           |            |               |           |                      | 1852.5MHz | 1882.5MHz | 1912.5MHz |
| 5MHz      | QPSK       | 1             | 0         | 22.50                | 22.29     | 22.13     | 21.92     |
|           |            |               | 13        | 22.50                | 22.41     | 22.23     | 21.84     |
|           |            |               | 24        | 22.50                | 22.26     | 22.07     | 21.47     |
|           |            | 12            | 0         | 21.50                | 21.26     | 21.19     | 21.03     |
|           |            |               | 6         | 21.50                | 21.38     | 21.25     | 21.00     |
|           |            |               | 13        | 21.50                | 21.35     | 21.17     | 20.91     |
|           |            | 25            | 0         | 21.50                | 21.30     | 21.16     | 20.95     |
|           |            |               | 0         | 21.50                | 21.35     | 21.37     | 20.62     |
|           |            |               | 13        | 21.50                | 21.45     | 21.46     | 20.67     |
|           | 16QAM      | 1             | 24        | 21.50                | 21.34     | 21.30     | 20.39     |
|           |            |               | 0         | 20.50                | 20.27     | 20.18     | 20.00     |
|           |            |               | 6         | 20.50                | 20.34     | 20.24     | 19.95     |
|           |            | 12            | 13        | 20.50                | 20.31     | 20.20     | 19.86     |
|           |            |               | 0         | 20.50                | 20.33     | 20.16     | 19.96     |
|           |            |               | 0         | 20.50                | 20.33     | 20.16     | 19.96     |

| LTE-FDD Band 25 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |           |           |
|-----------------|------------|---------------|-----------|----------------------|----------------------|-----------|-----------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 26090                | 26365     | 26640     |
|                 |            |               |           |                      | 1855.0MHz            | 1882.5MHz | 1910.0MHz |
| 10MHz           | QPSK       | 1             | 0         | 22.50                | 22.35                | 22.25     | 22.00     |
|                 |            |               | 25        | 23.00                | 22.57                | 22.35     | 22.08     |
|                 |            |               | 49        | 22.50                | 22.35                | 22.14     | 21.45     |
|                 |            | 25            | 0         | 21.50                | 21.30                | 21.16     | 21.01     |
|                 |            |               | 13        | 21.50                | 21.36                | 21.24     | 21.00     |
|                 |            |               | 25        | 21.50                | 21.31                | 21.24     | 20.86     |
|                 |            | 50            | 0         | 21.50                | 21.32                | 21.19     | 20.96     |
|                 |            |               | 0         | 21.50                | 21.32                | 20.97     | 21.26     |
|                 |            |               | 25        | 22.00                | 21.49                | 21.53     | 21.47     |
|                 | 16QAM      | 1             | 49        | 21.50                | 21.32                | 21.29     | 20.97     |
|                 |            |               | 0         | 21.50                | 21.32                | 21.08     | 20.99     |
|                 |            |               | 19        | 21.50                | 21.38                | 21.22     | 21.01     |
|                 |            | 12            | 38        | 21.50                | 21.31                | 21.12     | 20.50     |
|                 |            |               | 0         | 20.50                | 20.36                | 20.25     | 19.85     |
|                 |            |               | 0         | 20.50                | 20.36                | 20.25     | 19.85     |
|                 |            | 27            | 0         | 20.50                | 20.36                | 20.25     | 19.85     |
|                 |            |               | 0         | 20.50                | 20.36                | 20.25     | 19.85     |
|                 |            |               | 0         | 20.50                | 20.36                | 20.25     | 19.85     |
| Bandwidth       | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 26115                | 26365     | 26615     |
|                 |            |               |           |                      | 1857.5MHz            | 1882.5MHz | 1907.5MHz |
| 15MHz           | QPSK       | 1             | 0         | 22.50                | 22.22                | 22.18     | 21.65     |
|                 |            |               | 38        | 22.50                | 22.36                | 22.22     | 22.02     |
|                 |            |               | 74        | 22.50                | 22.25                | 22.09     | 21.37     |
|                 |            | 36            | 0         | 21.50                | 21.34                | 21.22     | 20.82     |
|                 |            |               | 18        | 21.50                | 21.38                | 21.28     | 20.94     |
|                 |            |               | 39        | 21.50                | 21.31                | 21.24     | 20.96     |
|                 |            | 75            | 0         | 21.50                | 21.37                | 21.22     | 20.94     |
|                 |            |               | 0         | 22.00                | 21.54                | 20.82     | 21.16     |
|                 |            |               | 38        | 22.00                | 21.64                | 21.37     | 21.46     |
|                 | 16QAM      | 1             | 74        | 22.00                | 21.59                | 21.22     | 20.88     |
|                 |            |               | 0         | 21.50                | 21.16                | 20.89     | 20.73     |
|                 |            |               | 31        | 21.50                | 21.24                | 21.19     | 20.98     |
|                 |            | 12            | 63        | 21.50                | 21.20                | 21.05     | 20.42     |
|                 |            |               | 0         | 20.50                | 20.26                | 20.24     | 19.85     |
|                 |            |               | 48        | 20.50                | 20.26                | 20.24     | 19.85     |
|                 |            | 27            | 0         | 20.50                | 20.26                | 20.24     | 19.85     |
|                 |            |               | 0         | 20.50                | 20.26                | 20.24     | 19.85     |
|                 |            |               | 0         | 20.50                | 20.26                | 20.24     | 19.85     |
| Bandwidth       | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 26140                | 26365     | 26590     |
|                 |            |               |           |                      | 1860.0MHz            | 1882.5MHz | 1905.0MHz |
| 20MHz           | QPSK       | 1             | 0         | 22.50                | 22.04                | 21.93     | 21.40     |

|  |       |     |    |       |       |       |       |
|--|-------|-----|----|-------|-------|-------|-------|
|  |       |     | 50 | 22.50 | 22.47 | 22.37 | 21.85 |
|  |       |     | 99 | 22.50 | 22.00 | 21.38 | 21.21 |
|  |       |     | 0  | 21.50 | 21.31 | 21.08 | 20.68 |
|  |       | 50  | 25 | 21.50 | 21.31 | 21.03 | 20.71 |
|  |       |     | 50 | 21.50 | 21.19 | 21.07 | 20.75 |
|  |       | 100 | 0  | 21.50 | 21.27 | 20.98 | 20.88 |
|  | 16QAM | 1   | 0  | 22.00 | 21.53 | 20.70 | 20.60 |
|  |       |     | 50 | 22.00 | 21.92 | 21.34 | 21.19 |
|  |       |     | 99 | 21.50 | 21.18 | 20.56 | 20.42 |
|  |       | 12  | 0  | 21.00 | 20.93 | 20.58 | 20.38 |
|  |       |     | 44 | 21.50 | 21.32 | 21.01 | 20.94 |
|  |       |     | 88 | 21.00 | 20.64 | 20.60 | 20.25 |
|  |       | 27  | 73 | 20.50 | 20.27 | 20.08 | 19.70 |

## Band 26 Part90

| LTE-FDD Band 26 Part90 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |       |       |
|------------------------|------------|---------------|-----------|----------------------|----------------------|-------|-------|
| Bandwidth              | Modulation | RB allocation | RB offset |                      | 26697                | 26740 | 26783 |
| 1.4MHz                 | QPSK       | 1             | 0         | 23.00                | 22.77                | 22.29 | 22.74 |
|                        |            |               | 2         | 23.00                | 22.85                | 22.38 | 22.82 |
|                        |            |               | 5         | 23.00                | 22.61                | 22.27 | 22.31 |
|                        |            | 3             | 0         | 22.50                | 22.34                | 22.33 | 22.35 |
|                        |            |               | 2         | 22.50                | 22.36                | 22.35 | 22.38 |
|                        |            |               | 3         | 22.50                | 22.34                | 22.35 | 22.34 |
|                        |            | 6             | 0         | 21.50                | 21.34                | 21.32 | 21.33 |
|                        | 16QAM      | 1             | 0         | 21.50                | 21.25                | 21.25 | 21.43 |
|                        |            |               | 2         | 22.00                | 21.33                | 21.35 | 21.52 |
|                        |            |               | 5         | 21.50                | 21.26                | 21.28 | 21.39 |
|                        |            | 3             | 0         | 21.50                | 21.49                | 21.34 | 21.28 |
|                        |            |               | 2         | 22.00                | 21.52                | 21.35 | 21.32 |
|                        |            |               | 3         | 21.50                | 21.48                | 21.34 | 21.32 |
|                        |            | 6             | 0         | 20.50                | 20.31                | 20.23 | 20.34 |
|                        |            | 15            | 0         | 21.50                | 21.28                | 21.28 | 21.27 |
|                        |            |               | 7         | 22.00                | 21.44                | 21.56 | 21.95 |
|                        |            |               | 14        | 22.00                | 21.29                | 21.42 | 21.78 |
|                        |            | 8             | 0         | 20.50                | 20.33                | 20.25 | 20.41 |
|                        |            |               | 4         | 20.50                | 20.40                | 20.30 | 20.48 |
|                        |            |               | 7         | 20.50                | 20.35                | 20.26 | 20.45 |
|                        |            | 15            | 0         | 20.50                | 20.32                | 20.25 | 20.34 |

| LTE-FDD Band 26 Part90 |            |    |    | Maximum Tune-up(dBm) | Conducted Power(dBm) |       |       |
|------------------------|------------|----|----|----------------------|----------------------|-------|-------|
| Bandwidth              | Modulation | RB | RB |                      | 26715                | 26740 | 26765 |

|      |       | allocation | offset |       | 816.5MHz | 819.0MHz | 821.5MHz |
|------|-------|------------|--------|-------|----------|----------|----------|
| 5MHz | QPSK  | 1          | 0      | 22.50 | 22.41    | 22.19    | 22.21    |
|      |       |            | 13     | 22.50 | 22.33    | 22.34    | 22.37    |
|      |       |            | 24     | 22.50 | 22.25    | 22.23    | 22.27    |
|      |       | 12         | 0      | 21.50 | 21.17    | 21.29    | 21.32    |
|      |       |            | 6      | 21.50 | 21.30    | 21.31    | 21.32    |
|      |       |            | 13     | 21.50 | 21.23    | 21.22    | 21.24    |
|      |       | 25         | 0      | 21.50 | 21.25    | 21.26    | 21.32    |
|      | 16QAM | 1          | 0      | 21.50 | 21.33    | 21.40    | 21.08    |
|      |       |            | 13     | 22.00 | 21.39    | 21.55    | 21.18    |
|      |       |            | 24     | 21.50 | 21.31    | 21.48    | 21.12    |
|      |       | 12         | 0      | 20.50 | 20.09    | 20.26    | 20.26    |
|      |       |            | 6      | 20.50 | 20.25    | 20.35    | 20.30    |
|      |       |            | 13     | 20.50 | 20.27    | 20.21    | 20.24    |
|      |       | 25         | 0      | 20.50 | 20.24    | 20.26    | 20.34    |

| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 26740        |
|-----------|------------|---------------|-----------|----------------------|--------------|
| 10MHz     | QPSK       | 1             | 0         | 23.00                | 22.78        |
|           |            |               | 25        | <b>23.00</b>         | <b>22.98</b> |
|           |            |               | 49        | 23.00                | 22.76        |
|           |            | 25            | 0         | 22.00                | 21.72        |
|           |            |               | 13        | 22.00                | <b>21.81</b> |
|           |            |               | 25        | 22.00                | 21.77        |
|           |            | 50            | 0         | 22.00                | 21.75        |
|           | 16QAM      | 1             | 0         | 22.00                | 21.81        |
|           |            |               | 25        | 22.00                | 21.73        |
|           |            |               | 49        | 22.00                | 21.60        |
|           |            | 12            | 0         | 21.50                | 21.16        |
|           |            |               | 19        | 21.50                | 21.33        |
|           |            |               | 38        | 21.50                | 21.33        |
|           |            | 27            | 0         | 20.50                | 20.34        |

## Band 26 Part22

| LTE-FDD Band 26 Part22 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |       |       |
|------------------------|------------|---------------|-----------|----------------------|----------------------|-------|-------|
| Bandwidth              | Modulation | RB allocation | RB offset |                      | 26797                | 26915 | 27033 |
| 1.4MHz                 | QPSK       | 1             | 0         | 23.00                | 22.81                | 16.45 | 17.37 |
|                        |            |               | 2         | 23.00                | 22.93                | 16.56 | 17.58 |
|                        |            |               | 5         | 23.00                | 22.80                | 16.51 | 17.52 |
|                        |            | 3             | 0         | 23.00                | 22.86                | 16.55 | 17.38 |
|                        |            |               | 2         | 23.00                | 22.88                | 16.58 | 17.47 |
|                        |            |               | 3         | 23.00                | 22.85                | 16.59 | 17.43 |
|                        |            | 6             | 0         | 22.00                | 21.77                | 15.60 | 16.53 |
|                        | 16QAM      | 1             | 0         | 22.00                | 21.54                | 15.49 | 16.28 |
|                        |            |               | 2         | 22.00                | 21.54                | 15.54 | 16.48 |
|                        |            |               | 5         | 21.50                | 21.42                | 15.48 | 16.50 |
|                        |            | 3             | 0         | 21.50                | 21.48                | 15.70 | 16.42 |
|                        |            |               | 2         | 21.50                | 21.42                | 15.74 | 16.45 |
|                        |            |               | 3         | 21.50                | 21.41                | 15.72 | 16.43 |
|                        |            | 6             | 0         | 20.50                | 20.28                | 14.57 | 15.38 |
| Bandwidth              | Modulation | RB            | RB offset | Maximum Tune-up(dBm) | 26805                | 26915 | 27025 |

|                        |            | allocation    |           |                      | 825.5MHz             | 836.5MHz | 847.5MHz |       |
|------------------------|------------|---------------|-----------|----------------------|----------------------|----------|----------|-------|
| 3MHz                   | QPSK       | 1             | 0         | 17.00                | 16.98                | 16.51    | 16.89    |       |
|                        |            |               | 7         | 17.50                | 16.96                | 16.66    | 17.02    |       |
|                        |            |               | 14        | 17.50                | 16.75                | 16.61    | 17.05    |       |
|                        |            | 8             | 0         | 16.00                | 15.90                | 15.56    | 15.82    |       |
|                        |            |               | 4         | 16.00                | 15.86                | 15.61    | 15.94    |       |
|                        |            |               | 7         | 16.00                | 15.75                | 15.61    | 15.98    |       |
|                        |            | 15            | 0         | 16.00                | 15.81                | 15.54    | 15.86    |       |
|                        |            | 16QAM         | 1         | 0                    | 16.50                | 15.92    | 15.56    | 16.25 |
|                        |            |               |           | 7                    | 16.50                | 15.96    | 15.62    | 16.44 |
|                        | 14         |               |           | 16.50                | 15.73                | 15.49    | 16.42    |       |
|                        | 8          |               | 0         | 15.00                | 14.92                | 14.44    | 14.96    |       |
|                        |            |               | 4         | 15.50                | 14.90                | 14.52    | 15.06    |       |
|                        |            |               | 7         | 15.50                | 14.82                | 14.53    | 15.08    |       |
|                        | 15         |               | 0         | 15.00                | 14.84                | 14.51    | 14.90    |       |
| LTE-FDD Band 26 Part22 |            |               |           |                      | Conducted Power(dBm) |          |          |       |
| Bandwidth              | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 26815                | 26915    | 27015    |       |
|                        |            |               |           |                      | 826.5MHz             | 836.5MHz | 846.5MHz |       |
| 5MHz                   | QPSK       | 1             | 0         | 17.00                | 16.86                | 15.97    | 16.51    |       |
|                        |            |               | 13        | 17.00                | 16.27                | 16.12    | 16.84    |       |
|                        |            |               | 24        | 17.00                | 16.09                | 16.14    | 16.97    |       |
|                        |            | 12            | 0         | 16.00                | 15.41                | 14.99    | 15.64    |       |
|                        |            |               | 6         | 16.00                | 15.31                | 15.15    | 15.80    |       |
|                        |            |               | 13        | 16.00                | 15.18                | 15.14    | 15.91    |       |
|                        |            | 25            | 0         | 16.00                | 15.28                | 15.09    | 15.79    |       |
|                        |            | 16QAM         | 1         | 0                    | 15.50                | 15.41    | 15.20    | 15.36 |
|                        |            |               |           | 13                   | 16.00                | 15.35    | 15.34    | 15.68 |
|                        | 24         |               |           | 16.00                | 15.21                | 15.29    | 15.76    |       |
|                        | 12         |               | 0         | 15.00                | 14.28                | 13.99    | 14.65    |       |
|                        |            |               | 6         | 15.00                | 14.27                | 14.13    | 14.78    |       |
|                        |            |               | 13        | 15.00                | 14.15                | 14.14    | 14.85    |       |
|                        | 25         | 0             | 15.00     | 14.30                | 14.06                | 14.85    |          |       |
| Bandwidth              | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 26840                | 26915    | 26990    |       |
|                        |            |               |           |                      | 829.0MHz             | 836.5MHz | 844.0MHz |       |
| 10MHz                  | QPSK       | 1             | 0         | 16.50                | 16.43                | 16.03    | 16.23    |       |
|                        |            |               | 25        | 17.00                | 16.34                | 16.25    | 16.68    |       |
|                        |            |               | 49        | 17.50                | 16.05                | 16.31    | 17.02    |       |
|                        |            | 25            | 0         | 16.00                | 15.47                | 14.97    | 15.61    |       |
|                        |            |               | 13        | 16.00                | 15.21                | 15.17    | 15.65    |       |
|                        |            |               | 25        | 16.00                | 15.19                | 15.20    | 15.89    |       |
|                        |            | 50            | 0         | 16.00                | 15.31                | 15.10    | 15.77    |       |
|                        |            | 16QAM         | 1         | 0                    | 16.00                | 15.34    | 15.19    | 15.70 |
|                        |            |               |           | 25                   | 16.50                | 15.32    | 15.38    | 16.23 |
|                        | 49         |               |           | 16.50                | 15.04                | 15.45    | 16.43    |       |
|                        | 12         |               | 0         | 15.50                | 15.38                | 15.00    | 15.40    |       |
|                        |            |               | 19        | 16.00                | 15.24                | 15.16    | 15.66    |       |
|                        |            |               | 38        | 16.00                | 15.11                | 15.27    | 15.92    |       |
|                        | 27         | 0             | 15.00     | 14.50                | 14.05                | 14.86    |          |       |
| Bandwidth              | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 26865                | 26915    | 26965    |       |
|                        |            |               |           |                      | 831.5MHz             | 836.5MHz | 841.5MHz |       |
| 15MHz                  | QPSK       | 1             | 0         | 16.50                | 16.31                | 15.96    | 15.91    |       |
|                        |            |               | 38        | 16.50                | 16.07                | 16.11    | 16.37    |       |
|                        |            |               | 74        | 17.00                | 16.17                | 16.43    | 16.93    |       |
|                        |            | 36            | 0         | 15.50                | 15.38                | 15.05    | 15.24    |       |
|                        |            |               | 18        | 15.50                | 15.18                | 15.15    | 15.47    |       |
|                        |            |               | 39        | 16.00                | 15.24                | 15.25    | 15.77    |       |
|                        |            | 75            | 0         | 16.00                | 15.32                | 15.16    | 15.51    |       |

|  |       |    |    |       |       |       |       |
|--|-------|----|----|-------|-------|-------|-------|
|  | 16QAM | 1  | 0  | 16.00 | 15.59 | 15.12 | 15.47 |
|  |       |    | 38 | 16.00 | 15.48 | 15.24 | 15.87 |
|  |       |    | 74 | 16.50 | 15.41 | 15.58 | 16.34 |
|  |       | 12 | 0  | 15.50 | 15.25 | 15.02 | 14.97 |
|  |       |    | 31 | 15.50 | 15.05 | 15.11 | 15.42 |
|  |       |    | 63 | 16.00 | 15.06 | 15.33 | 15.86 |
|  |       | 27 | 48 | 20.50 | 14.40 | 14.06 | 20.27 |
|  |       |    |    |       |       |       |       |

## Band 38

| LTE-TDD Band 38 |            |               |            | Maximum Tune-up(dBm) | Conducted Power(dBm) |                      |            |            |            |
|-----------------|------------|---------------|------------|----------------------|----------------------|----------------------|------------|------------|------------|
| Bandwidth       | Modulation | RB allocation | RB offset  |                      | 37775                | 38000                | 38225      |            |            |
|                 |            |               |            |                      | 2572.5MHz            | 2595.0MHz            | 2617.5MHz  |            |            |
| 5MHz            | QPSK       | 1             | 0          | 21.50                | 21.11                | 16.53                | 17.84      |            |            |
|                 |            |               | 12         | 21.50                | 21.21                | 17.05                | 18.18      |            |            |
|                 |            |               | 24         | 18.50                | 18.05                | 16.56                | 18.11      |            |            |
|                 |            | 12            | 0          | 18.50                | 18.31                | 16.97                | 18.15      |            |            |
|                 |            |               | 6          | 18.50                | 18.39                | 17.04                | 18.29      |            |            |
|                 |            |               | 13         | 18.50                | 18.27                | 16.75                | 18.16      |            |            |
|                 |            | 25            | 0          | 18.50                | 18.13                | 16.78                | 18.06      |            |            |
|                 | 16QAM      | 1             | 0          | 18.50                | 18.16                | 16.99                | 18.08      |            |            |
|                 |            |               | 12         | 18.50                | 18.18                | 17.09                | 18.21      |            |            |
|                 |            |               | 24         | 18.50                | 18.05                | 17.02                | 18.16      |            |            |
|                 |            | 12            | 0          | 18.50                | 18.32                | 16.93                | 17.92      |            |            |
|                 |            |               | 6          | 18.50                | 18.28                | 16.99                | 18.01      |            |            |
|                 |            |               | 13         | 18.50                | 18.28                | 16.90                | 18.20      |            |            |
|                 |            | 25            | 0          | 18.50                | 18.12                | 16.81                | 18.05      |            |            |
|                 |            | Bandwidth     | Modulation | RB allocation        | RB offset            | Maximum Tune-up(dBm) | 37800      | 38000      | 38200      |
|                 |            |               |            |                      |                      |                      | 2575.00MHz | 2595.00MHz | 2615.00MHz |
|                 | 10MHz      | QPSK          | 1          | 0                    | 18.50                | 18.49                | 17.02      | 17.81      |            |
| 24              |            |               |            | 18.50                | 18.36                | 17.23                | 18.35      |            |            |
| 49              |            |               |            | 18.50                | 17.95                | 16.95                | 18.11      |            |            |
| 25              |            |               | 0          | 18.50                | 18.36                | 17.16                | 18.13      |            |            |
|                 |            |               | 12         | 18.50                | 18.17                | 17.02                | 18.11      |            |            |
|                 |            |               | 25         | 18.50                | 18.05                | 16.99                | 18.08      |            |            |
| 50              |            |               | 0          | 18.50                | 18.12                | 17.05                | 18.03      |            |            |
| 16QAM           |            | 1             | 0          | 18.50                | 18.26                | 16.93                | 17.76      |            |            |
|                 |            |               | 25         | 18.50                | 18.06                | 16.92                | 18.31      |            |            |
|                 |            |               | 49         | 18.50                | 17.92                | 16.84                | 18.26      |            |            |
|                 |            | 12            | 0          | 18.50                | 18.42                | 16.94                | 18.03      |            |            |
|                 |            |               | 19         | 18.50                | 18.21                | 16.95                | 18.23      |            |            |
|                 |            |               | 38         | 18.50                | 17.97                | 16.98                | 18.17      |            |            |
|                 |            | 27            | 0          | 18.50                | 18.44                | 16.88                | 18.05      |            |            |

| LTE-TDD Band 38 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |           |           |
|-----------------|------------|---------------|-----------|----------------------|----------------------|-----------|-----------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 37825                | 38000     | 38175     |
|                 |            |               |           |                      | 2577.5MHz            | 2595.0MHz | 2612.5MHz |
| 15MHz           | QPSK       | 1             | 0         | 18.50                | 18.25                | 16.92     | 17.48     |
|                 |            |               | 38        | 18.50                | 18.06                | 16.88     | 18.10     |
|                 |            |               | 74        | 18.50                | 17.42                | 17.20     | 18.16     |
|                 |            | 36            | 0         | 18.50                | 18.23                | 16.97     | 17.89     |
|                 |            |               | 18        | 18.50                | 18.27                | 17.04     | 18.10     |
|                 |            |               | 39        | 18.50                | 17.84                | 16.93     | 18.09     |

|  |       |    |    |       |       |       |       |
|--|-------|----|----|-------|-------|-------|-------|
|  | 16QAM | 75 | 0  | 18.50 | 18.19 | 16.93 | 18.06 |
|  |       | 1  | 0  | 18.50 | 18.42 | 16.98 | 17.43 |
|  |       |    | 38 | 18.50 | 18.31 | 16.76 | 18.03 |
|  |       |    | 74 | 18.50 | 17.68 | 16.98 | 18.15 |
|  |       | 12 | 0  | 18.50 | 18.19 | 17.18 | 17.49 |
|  |       |    | 31 | 18.50 | 18.30 | 17.00 | 17.91 |
|  |       |    | 63 | 18.00 | 17.72 | 16.92 | 17.99 |
|  |       | 27 | 0  | 18.50 | 18.34 | 17.11 | 18.20 |

| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 37850     | 38000     | 38150     |
|-----------|------------|---------------|-----------|----------------------|-----------|-----------|-----------|
|           |            |               |           |                      | 2580.0MHz | 2595.0MHz | 2610.0MHz |
| 20MHz     | QPSK       | 1             | 0         | 18.00                | 17.95     | 17.13     | 16.94     |
|           |            |               | 50        | 18.50                | 18.23     | 16.99     | 18.14     |
|           |            |               | 99        | 18.00                | 16.82     | 17.04     | 17.88     |
|           |            | 50            | 0         | 18.50                | 18.27     | 17.04     | 17.54     |
|           |            |               | 25        | 18.00                | 17.88     | 17.04     | 17.75     |
|           |            |               | 50        | 18.50                | 17.67     | 16.97     | 18.06     |
|           |            | 100           | 0         | 18.00                | 17.99     | 16.99     | 17.79     |
|           | 16QAM      | 1             | 0         | 18.50                | 18.25     | 17.29     | 16.82     |
|           |            |               | 49        | 18.50                | 18.20     | 17.23     | 18.02     |
|           |            |               | 99        | 18.50                | 17.02     | 16.76     | 18.27     |
|           |            | 50            | 0         | 18.50                | 18.02     | 17.11     | 16.86     |
|           |            |               | 25        | 18.00                | 17.99     | 17.07     | 17.68     |
|           |            |               | 50        | 18.00                | 17.07     | 17.17     | 17.83     |
|           |            | 100           | 0         | 18.50                | 18.10     | 17.17     | 17.96     |

## Band 41

| LTE-TDD Band 41 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |           |           |
|-----------------|------------|---------------|-----------|----------------------|----------------------|-----------|-----------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 39675                | 40620     | 41565     |
|                 |            |               |           |                      | 2498.5MHz            | 2593.0MHz | 2687.5MHz |
| 5MHz            | QPSK       | 1             | 0         | 21.50                | 21.04                | 20.69     | 21.18     |
|                 |            |               | 13        | 21.50                | 21.15                | 20.75     | 21.28     |
|                 |            |               | 24        | 21.50                | 20.97                | 20.56     | 21.20     |
|                 |            | 12            | 0         | 20.50                | 20.30                | 19.91     | 20.04     |
|                 |            |               | 6         | 20.50                | 20.37                | 19.82     | 20.08     |
|                 |            |               | 13        | 20.50                | 20.11                | 19.89     | 20.15     |
|                 |            | 25            | 0         | 20.50                | 20.14                | 19.91     | 20.11     |
|                 | 16QAM      | 1             | 0         | 20.50                | 20.05                | 19.60     | 19.97     |
|                 |            |               | 13        | 20.50                | 20.17                | 19.70     | 20.13     |
|                 |            |               | 24        | 20.50                | 20.15                | 19.78     | 20.04     |
|                 |            | 12            | 0         | 19.50                | 19.08                | 18.90     | 18.98     |
|                 |            |               | 6         | 19.50                | 19.20                | 18.67     | 19.17     |
|                 |            |               | 13        | 19.50                | 19.25                | 18.88     | 18.99     |
| 25              | 0          | 19.50         | 19.14     | 18.74                | 19.04                |           |           |
| Bandwidth       | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 39700                | 40620     | 41540     |
|                 |            |               |           |                      | 2501.0MHz            | 2593.0MHz | 2685.0MHz |
| 10MHz           | QPSK       | 1             | 0         | 21.50                | 21.08                | 20.76     | 21.08     |
|                 |            |               | 25        | 22.00                | 21.54                | 21.02     | 21.60     |
|                 |            |               | 49        | 21.50                | 21.27                | 20.72     | 21.16     |
|                 |            | 25            | 0         | 20.50                | 20.20                | 19.73     | 20.06     |
|                 |            |               | 13        | 20.50                | 20.15                | 19.93     | 20.05     |
|                 |            |               | 25        | 20.50                | 20.13                | 19.92     | 20.20     |
|                 |            | 50            | 0         | 20.50                | 20.33                | 19.72     | 20.05     |

|  |       |    |    |       |       |       |       |
|--|-------|----|----|-------|-------|-------|-------|
|  | 16QAM | 1  | 0  | 20.50 | 20.05 | 19.57 | 19.95 |
|  |       |    | 25 | 21.00 | 20.67 | 19.83 | 20.27 |
|  |       |    | 49 | 20.50 | 20.43 | 19.56 | 20.07 |
|  |       | 12 | 0  | 20.50 | 20.32 | 19.82 | 19.83 |
|  |       |    | 19 | 20.50 | 20.36 | 19.88 | 20.11 |
|  |       |    | 38 | 20.50 | 20.29 | 19.80 | 19.93 |
|  |       | 27 | 23 | 19.50 | 19.38 | 18.93 | 19.22 |
|  |       |    |    |       |       |       |       |

| LTE-TDD Band 41 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |                    |                    |
|-----------------|------------|---------------|-----------|----------------------|----------------------|--------------------|--------------------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 39725<br>2503.5MHz   | 40620<br>2593.0MHz | 41515<br>2682.5MHz |
| 15MHz           | QPSK       | 1             | 0         | 21.50                | 21.10                | 20.68              | 21.05              |
|                 |            |               | 38        | 21.50                | 21.22                | 21.02              | 21.33              |
|                 |            |               | 74        | 21.50                | 21.05                | 20.65              | 21.24              |
|                 |            | 36            | 0         | 20.50                | 20.33                | 19.95              | 20.16              |
|                 |            |               | 18        | 20.50                | 20.15                | 19.98              | 20.20              |
|                 |            |               | 39        | 20.50                | 20.15                | 19.96              | 20.19              |
|                 |            | 75            | 0         | 20.50                | 20.34                | 19.98              | 20.17              |
|                 |            |               |           |                      |                      |                    |                    |
|                 |            |               |           |                      |                      |                    |                    |
|                 | 16QAM      | 1             | 0         | 20.50                | 20.32                | 19.53              | 19.89              |
|                 |            |               | 38        | 20.50                | 20.45                | 19.77              | 20.07              |
|                 |            |               | 74        | 20.50                | 19.88                | 19.48              | 20.06              |
|                 |            | 12            | 0         | 20.50                | 20.06                | 19.79              | 19.93              |
|                 |            |               | 31        | 20.50                | 20.29                | 19.91              | 20.07              |
|                 |            |               | 63        | 20.50                | 20.25                | 19.75              | 20.10              |
|                 |            | 27            | 48        | 19.50                | 19.25                | 18.89              | 19.22              |
|                 |            |               |           |                      |                      |                    |                    |
|                 |            |               |           |                      |                      |                    |                    |
| Bandwidth       | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 39750<br>2506.0MHz   | 40620<br>2593.0MHz | 41490<br>2680.0MHz |
| 20MHz           | QPSK       | 1             | 0         | 21.00                | 20.77                | 20.71              | 20.73              |
|                 |            |               | 50        | 21.50                | 21.14                | 20.93              | 21.41              |
|                 |            |               | 99        | 21.00                | 20.73                | 20.39              | 20.99              |
|                 |            | 50            | 0         | 20.50                | 20.09                | 19.69              | 20.05              |
|                 |            |               | 25        | 20.50                | 20.09                | 19.90              | 19.98              |
|                 |            |               | 50        | 20.50                | 20.05                | 19.74              | 20.12              |
|                 |            | 100           | 0         | 20.50                | 20.24                | 19.71              | 20.08              |
|                 |            |               |           |                      |                      |                    |                    |
|                 |            |               |           |                      |                      |                    |                    |
|                 | 16QAM      | 1             | 0         | 20.50                | 20.03                | 19.49              | 19.94              |
|                 |            |               | 50        | 20.50                | 20.34                | 19.82              | 20.22              |
|                 |            |               | 99        | 20.50                | 19.36                | 19.42              | 20.13              |
|                 |            | 12            | 0         | 20.00                | 19.87                | 19.54              | 19.70              |
|                 |            |               | 44        | 20.50                | 20.25                | 19.74              | 20.01              |
|                 |            |               | 88        | 20.00                | 19.96                | 19.64              | 19.77              |
|                 |            | 27            | 73        | 19.50                | 18.99                | 18.63              | 19.13              |
|                 |            |               |           |                      |                      |                    |                    |
|                 |            |               |           |                      |                      |                    |                    |

## Band 66

| LTE-FDD Band 66 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |                     |                     |
|-----------------|------------|---------------|-----------|----------------------|----------------------|---------------------|---------------------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 131979<br>1710.7MHz  | 132322<br>1745.0MHz | 132665<br>1779.3MHz |
| 1.4MHz          | QPSK       | 1             | 0         | 21.50                | 21.10                | 21.34               | 21.43               |
|                 |            |               | 2         | 22.00                | 21.33                | 21.58               | 21.46               |
|                 |            |               | 5         | 21.50                | 21.14                | 21.34               | 21.03               |
|                 |            | 3             | 0         | 21.50                | 21.19                | 21.33               | 21.17               |
|                 |            |               | 2         | 21.50                | 21.17                | 21.22               | 21.13               |
|                 |            |               | 3         | 21.50                | 21.25                | 21.07               | 21.20               |
|                 |            | 6             | 0         | 20.50                | 20.12                | 18.06               | 20.17               |
|                 |            |               |           |                      |                      |                     |                     |
|                 |            |               |           |                      |                      |                     |                     |
|                 | 16QAM      | 1             | 0         | 20.50                | 20.44                | 20.23               | 20.04               |
|                 |            |               | 2         | 21.00                | 20.64                | 20.48               | 20.22               |

|  |  |   |   |       |       |       |       |
|--|--|---|---|-------|-------|-------|-------|
|  |  | 3 | 5 | 20.50 | 20.40 | 20.25 | 20.02 |
|  |  |   | 0 | 20.50 | 20.20 | 20.30 | 20.21 |
|  |  |   | 2 | 20.50 | 20.15 | 20.23 | 20.15 |
|  |  |   | 3 | 20.50 | 20.21 | 20.29 | 20.23 |
|  |  | 6 | 0 | 20.00 | 19.17 | 19.47 | 19.51 |
|  |  |   |   |       |       |       |       |

| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 131987    | 132322    | 132657    |
|-----------|------------|---------------|-----------|----------------------|-----------|-----------|-----------|
|           |            |               |           |                      | 1711.5MHz | 1745.0MHz | 1778.5MHz |
| 3MHz      | QPSK       | 1             | 0         | 19.50                | 18.78     | 19.24     | 19.08     |
|           |            |               | 7         | 19.50                | 18.68     | 19.20     | 18.97     |
|           |            |               | 14        | 19.50                | 18.81     | 19.16     | 19.06     |
|           |            | 8             | 0         | 18.50                | 17.77     | 17.75     | 18.08     |
|           |            |               | 4         | 18.50                | 17.73     | 17.86     | 18.09     |
|           |            |               | 7         | 18.50                | 17.73     | 17.72     | 18.05     |
|           |            | 15            | 0         | 18.50                | 17.70     | 17.69     | 18.07     |
|           |            |               | 0         | 18.50                | 18.15     | 17.69     | 18.13     |
|           |            |               | 7         | 18.50                | 18.04     | 17.62     | 17.99     |
|           | 16QAM      | 1             | 14        | 18.50                | 18.19     | 17.74     | 18.12     |
|           |            |               | 0         | 17.50                | 16.86     | 16.78     | 17.17     |
|           |            |               | 4         | 17.50                | 16.89     | 16.83     | 17.19     |
|           |            | 8             | 7         | 17.50                | 16.86     | 16.75     | 17.10     |
|           |            |               | 0         | 17.50                | 16.83     | 16.80     | 17.08     |
|           |            |               | 0         | 17.50                | 16.83     | 16.80     | 17.08     |
|           |            | 15            | 0         | 17.50                | 16.83     | 16.80     | 17.08     |
|           |            |               | 0         | 17.50                | 16.83     | 16.80     | 17.08     |
|           |            |               | 0         | 17.50                | 16.83     | 16.80     | 17.08     |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 131997    | 132322    | 132647    |
|           |            |               |           |                      | 1712.5MHz | 1745.0MHz | 1777.5MHz |
| 5MHz      | QPSK       | 1             | 0         | 21.50                | 20.93     | 21.17     | 21.37     |
|           |            |               | 13        | 22.00                | 21.02     | 21.30     | 21.55     |
|           |            |               | 24        | 21.50                | 20.90     | 21.21     | 21.43     |
|           |            | 12            | 0         | 21.00                | 19.99     | 20.27     | 20.56     |
|           |            |               | 6         | 21.00                | 20.09     | 20.32     | 20.59     |
|           |            |               | 13        | 21.00                | 20.06     | 20.29     | 20.50     |
|           |            | 25            | 0         | 21.00                | 20.04     | 20.29     | 20.56     |
|           |            |               | 0         | 20.50                | 20.41     | 20.31     | 20.37     |
|           |            |               | 13        | 21.00                | 20.50     | 20.47     | 20.54     |
|           | 16QAM      | 1             | 24        | 20.50                | 20.35     | 20.35     | 20.41     |
|           |            |               | 0         | 20.00                | 18.98     | 19.28     | 19.66     |
|           |            |               | 6         | 20.00                | 19.11     | 19.38     | 19.67     |
|           |            | 12            | 13        | 20.00                | 19.12     | 19.34     | 19.60     |
|           |            |               | 0         | 20.00                | 19.08     | 19.32     | 19.70     |
|           |            |               | 0         | 20.00                | 19.08     | 19.32     | 19.70     |
|           |            | 25            | 0         | 20.00                | 19.08     | 19.32     | 19.70     |
|           |            |               | 0         | 20.00                | 19.08     | 19.32     | 19.70     |
|           |            |               | 0         | 20.00                | 19.08     | 19.32     | 19.70     |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 132022    | 132322    | 132622    |
|           |            |               |           |                      | 1715.0MHz | 1745.0MHz | 1775.0MHz |
| 10MHz     | QPSK       | 1             | 0         | 19.50                | 18.74     | 19.09     | 19.34     |
|           |            |               | 25        | 20.00                | 18.88     | 19.27     | 19.51     |
|           |            |               | 49        | 19.50                | 18.83     | 19.17     | 19.49     |
|           |            | 25            | 0         | 19.00                | 17.62     | 18.27     | 18.57     |
|           |            |               | 13        | 18.50                | 17.81     | 18.23     | 18.44     |
|           |            |               | 25        | 18.50                | 17.94     | 18.25     | 18.37     |
|           |            | 50            | 0         | 18.50                | 17.80     | 18.23     | 18.46     |
|           |            |               | 0         | 19.00                | 17.69     | 18.16     | 18.66     |
|           |            |               | 25        | 19.00                | 17.73     | 18.28     | 18.83     |
|           | 16QAM      | 1             | 49        | 19.00                | 17.75     | 18.12     | 18.85     |
|           |            |               | 0         | 18.50                | 17.65     | 17.87     | 18.41     |
|           |            |               | 19        | 18.50                | 17.74     | 17.96     | 18.42     |
|           |            | 12            | 38        | 18.50                | 17.84     | 17.76     | 18.42     |
|           |            |               | 0         | 17.50                | 16.68     | 16.93     | 17.45     |
|           |            |               | 23        | 17.50                | 16.68     | 16.93     | 17.45     |
|           |            | 27            | 0         | 17.50                | 16.68     | 16.93     | 17.45     |
|           |            |               | 0         | 17.50                | 16.68     | 16.93     | 17.45     |
|           |            |               | 0         | 17.50                | 16.68     | 16.93     | 17.45     |

| LTE-FDD Band 66 |            |               |            | Maximum Tune-up(dBm) | Conducted Power(dBm) |                      |           |           |           |
|-----------------|------------|---------------|------------|----------------------|----------------------|----------------------|-----------|-----------|-----------|
| Bandwidth       | Modulation | RB allocation | RB offset  |                      | 132047               | 132322               | 132597    |           |           |
|                 |            |               |            |                      | 1717.5MHz            | 1745.0MHz            | 1772.5MHz |           |           |
| 15MHz           | QPSK       | 1             | 0          | 19.50                | 18.55                | 18.96                | 19.26     |           |           |
|                 |            |               | 38         | 19.50                | 18.75                | 19.23                | 19.28     |           |           |
|                 |            |               | 74         | 19.50                | 18.76                | 19.10                | 19.07     |           |           |
|                 |            | 36            | 0          | 18.50                | 17.60                | 18.16                | 18.42     |           |           |
|                 |            |               | 18         | 18.50                | 17.77                | 18.19                | 18.42     |           |           |
|                 |            |               | 39         | 18.50                | 17.85                | 18.28                | 18.34     |           |           |
|                 |            | 75            | 0          | 18.50                | 17.77                | 18.12                | 18.43     |           |           |
|                 |            | 16QAM         | 1          | 0                    | 18.50                | 17.65                | 17.72     | 18.14     |           |
|                 |            |               |            | 38                   | 18.50                | 17.81                | 17.97     | 18.34     |           |
|                 | 74         |               |            | 18.50                | 17.82                | 17.59                | 18.23     |           |           |
|                 | 12         |               | 0          | 18.50                | 17.60                | 17.57                | 18.23     |           |           |
|                 |            |               | 31         | 18.50                | 17.70                | 17.75                | 18.41     |           |           |
|                 |            |               | 63         | 18.50                | 17.74                | 17.70                | 18.23     |           |           |
|                 | 27         |               | 48         | 17.50                | 16.64                | 16.70                | 17.25     |           |           |
|                 | Bandwidth  |               | Modulation | RB allocation        | RB offset            | Maximum Tune-up(dBm) | 132072    | 132322    | 132572    |
|                 |            |               |            |                      |                      |                      | 1720.0MHz | 1745.0MHz | 1770.0MHz |
|                 | 20MHz      | QPSK          | 1          | 0                    | 21.50                | 20.69                | 20.82     | 21.08     |           |
|                 |            |               |            | 50                   | 22.00                | 21.07                | 21.37     | 21.52     |           |
| 99              |            |               |            | 21.50                | 20.86                | 21.06                | 21.27     |           |           |
| 50              |            |               | 0          | 20.50                | 19.84                | 20.29                | 20.37     |           |           |
|                 |            |               | 25         | 20.50                | 20.06                | 20.29                | 20.48     |           |           |
|                 |            |               | 50         | 20.50                | 20.13                | 20.35                | 20.34     |           |           |
| 100             |            |               | 0          | 20.50                | 19.94                | 20.29                | 20.30     |           |           |
| 16QAM           |            |               | 1          | 0                    | 20.50                | 20.19                | 19.95     | 19.95     |           |
|                 |            |               |            | 50                   | 21.00                | 20.51                | 20.42     | 20.35     |           |
|                 |            | 99            |            | 20.50                | 20.28                | 20.06                | 20.17     |           |           |
|                 |            | 12            | 0          | 20.50                | 19.81                | 19.92                | 20.23     |           |           |
|                 |            |               | 44         | 20.50                | 20.04                | 20.23                | 20.48     |           |           |
|                 |            |               | 88         | 20.50                | 19.94                | 20.11                | 20.39     |           |           |
|                 |            | 27            | 73         | 19.50                | 18.92                | 19.16                | 19.36     |           |           |

## Band 71

| LTE-FDD Band 71 |            |               |           | Maximum Tune-up(dBm) | Conducted Power(dBm) |          |          |       |       |
|-----------------|------------|---------------|-----------|----------------------|----------------------|----------|----------|-------|-------|
| Bandwidth       | Modulation | RB allocation | RB offset |                      | 133147               | 133297   | 133447   |       |       |
|                 |            |               |           |                      | 665.5MHz             | 680.5MHz | 695.5MHz |       |       |
| 5MHz            | QPSK       | 1             | 0         | 21.50                | 21.31                | 21.26    | 21.15    |       |       |
|                 |            |               | 13        | 21.50                | 21.39                | 21.40    | 21.23    |       |       |
|                 |            |               | 24        | 21.50                | 21.29                | 21.27    | 21.06    |       |       |
|                 |            | 12            | 0         | 20.50                | 20.21                | 20.36    | 20.19    |       |       |
|                 |            |               | 6         | 20.50                | 20.43                | 20.42    | 20.32    |       |       |
|                 |            |               | 13        | 20.50                | 20.31                | 20.32    | 20.29    |       |       |
|                 |            | 25            | 0         | 20.50                | 20.27                | 20.33    | 20.27    |       |       |
|                 |            |               | 16QAM     | 1                    | 0                    | 21.00    | 20.41    | 20.24 | 20.53 |
|                 |            |               |           |                      | 13                   | 21.00    | 20.51    | 20.33 | 20.67 |
|                 | 24         | 21.00         |           |                      | 20.38                | 20.23    | 20.52    |       |       |
|                 | 12         | 0             |           | 19.50                | 19.20                | 19.32    | 19.20    |       |       |
|                 |            | 6             |           | 19.50                | 19.40                | 19.41    | 19.28    |       |       |
|                 |            | 13            | 19.50     | 19.30                | 19.33                | 19.28    |          |       |       |
|                 | 25         | 0             | 19.50     | 19.23                | 19.41                | 19.23    |          |       |       |

| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 133172   | 133297   | 133422   |
|-----------|------------|---------------|-----------|----------------------|----------|----------|----------|
|           |            |               |           |                      | 668.0MHz | 680.5MHz | 693.0MHz |
| 10MHz     | QPSK       | 1             | 0         | 21.50                | 21.45    | 21.41    | 21.27    |
|           |            |               | 25        | 22.00                | 21.59    | 21.54    | 21.41    |
|           |            |               | 49        | 22.00                | 21.50    | 21.39    | 21.15    |
|           |            | 25            | 0         | 20.50                | 20.37    | 20.35    | 20.39    |
|           |            |               | 13        | 20.50                | 20.43    | 20.37    | 20.35    |
|           |            |               | 25        | 20.50                | 20.37    | 20.32    | 20.47    |
|           |            | 50            | 0         | 20.50                | 20.28    | 20.27    | 20.42    |
|           |            |               | 0         | 21.00                | 20.75    | 20.29    | 20.27    |
|           |            |               | 25        | 21.00                | 20.84    | 20.41    | 20.40    |
|           | 16QAM      | 1             | 49        | 21.00                | 20.74    | 20.33    | 20.27    |
|           |            |               | 0         | 20.50                | 20.25    | 20.27    | 20.25    |
|           |            |               | 19        | 20.50                | 20.41    | 20.39    | 20.27    |
|           |            | 12            | 38        | 20.50                | 20.42    | 20.32    | 20.25    |
|           |            |               | 0         | 19.50                | 19.41    | 19.35    | 19.44    |
|           |            |               | 0         | 21.00                | 20.75    | 20.29    | 20.27    |
|           |            |               | 25        | 21.00                | 20.84    | 20.41    | 20.40    |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 133197   | 133297   | 133397   |
|           |            |               |           |                      | 670.5MHz | 680.5MHz | 690.5MHz |
| 15MHz     | QPSK       | 1             | 0         | 21.50                | 21.30    | 21.27    | 21.18    |
|           |            |               | 38        | 21.50                | 21.43    | 21.46    | 21.28    |
|           |            |               | 74        | 21.50                | 21.33    | 21.37    | 21.10    |
|           |            | 36            | 0         | 20.50                | 20.45    | 20.27    | 20.47    |
|           |            |               | 18        | 20.50                | 20.45    | 20.39    | 20.39    |
|           |            |               | 39        | 21.00                | 20.53    | 20.31    | 20.43    |
|           |            | 75            | 0         | 20.50                | 20.46    | 20.30    | 20.48    |
|           |            |               | 0         | 20.50                | 20.23    | 20.20    | 20.19    |
|           |            |               | 38        | 20.50                | 20.37    | 20.36    | 20.35    |
|           | 16QAM      | 1             | 74        | 20.50                | 20.28    | 20.24    | 20.21    |
|           |            |               | 0         | 20.50                | 20.22    | 20.23    | 20.23    |
|           |            |               | 31        | 20.50                | 20.44    | 20.38    | 20.31    |
|           |            | 12            | 63        | 20.50                | 20.29    | 20.28    | 20.25    |
|           |            |               | 0         | 19.50                | 19.28    | 19.29    | 19.37    |
|           |            |               | 0         | 20.50                | 20.23    | 20.20    | 20.19    |
|           |            |               | 38        | 20.50                | 20.37    | 20.36    | 20.35    |
| Bandwidth | Modulation | RB allocation | RB offset | Maximum Tune-up(dBm) | 133222   | 133322   | 133372   |
|           |            |               |           |                      | 673.0MHz | 683.0MHz | 688.0MHz |
| 20MHz     | QPSK       | 1             | 0         | 21.50                | 21.09    | 21.06    | 21.08    |
|           |            |               | 50        | 21.50                | 21.45    | 21.47    | 21.46    |
|           |            |               | 99        | 21.50                | 21.13    | 21.06    | 20.98    |
|           |            | 50            | 0         | 21.00                | 20.48    | 20.28    | 20.57    |
|           |            |               | 25        | 20.50                | 20.39    | 20.33    | 20.39    |
|           |            |               | 50        | 21.00                | 20.56    | 20.20    | 20.43    |
|           |            | 100           | 0         | 20.50                | 20.41    | 20.19    | 20.49    |
|           |            |               | 0         | 20.50                | 20.46    | 20.09    | 19.92    |
|           |            |               | 50        | 21.00                | 20.83    | 20.47    | 20.31    |
|           | 16QAM      | 1             | 99        | 21.00                | 20.53    | 20.09    | 19.92    |
|           |            |               | 0         | 20.50                | 20.12    | 20.05    | 20.14    |
|           |            |               | 44        | 20.50                | 20.34    | 20.34    | 20.44    |
|           |            | 12            | 88        | 20.50                | 20.18    | 20.05    | 20.22    |
|           |            |               | 0         | 19.50                | 19.28    | 19.10    | 19.31    |
|           |            |               | 0         | 20.50                | 20.46    | 20.09    | 19.92    |
|           |            |               | 50        | 21.00                | 20.83    | 20.47    | 20.31    |

## 8.4 Wi-Fi

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 59 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

## 2.4G

| Band (GHz)                | Mode          | Channel | Freq. (MHz) | Average Power (dBm) | Maximum Tune-up(dBm) | SAR Test Require. |
|---------------------------|---------------|---------|-------------|---------------------|----------------------|-------------------|
| 2.4g Wifi<br>(2.4~2.4835) | 802.11b       | 1       | 2412        | 14.94               | 15.00                | No                |
|                           |               | 6       | 2437        | <b>15.29</b>        | <b>15.50</b>         | Yes               |
|                           |               | 11      | 2462        | 14.88               | 15.00                | No                |
|                           | 802.11g       | 1       | 2412        | 14.24               | 14.50                | No                |
|                           |               | 6       | 2437        | 14.72               | 15.00                | No                |
|                           |               | 11      | 2462        | 14.12               | 14.50                | No                |
|                           | 802.11n(HT20) | 1       | 2412        | 14.26               | 14.50                | No                |
|                           |               | 6       | 2437        | 14.79               | 15.00                | No                |
|                           |               | 11      | 2462        | 14.19               | 14.50                | No                |
|                           | 802.11n(HT40) | 3       | 2422        | 14.96               | 15.00                | No                |
|                           |               | 6       | 2437        | 14.77               | 15.00                | No                |
|                           |               | 9       | 2452        | 14.44               | 14.50                | No                |

Note: SAR is not required for the following 2.4 GHz OFDM conditions as the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2\text{W/kg}$ .

## 5G

| Band (GHz)                | Mode            | Channel | Freq. (MHz) | Average Power (dBm) | Maximum Tune-up(dBm) | SAR Test Require. |
|---------------------------|-----------------|---------|-------------|---------------------|----------------------|-------------------|
| U-NII-1<br>(5.150~5.250)  | 802.11a         | 36      | 5180        | 12.23               | 12.50                | No                |
|                           |                 | 40      | 5200        | 11.88               | 12.00                | No                |
|                           |                 | 48      | 5240        | 11.99               | 12.00                | No                |
|                           | 802.11n(HT20)   | 36      | 5180        | 12.10               | 12.50                | No                |
|                           |                 | 40      | 5200        | 11.83               | 12.00                | No                |
|                           |                 | 48      | 5240        | 12.07               | 12.50                | No                |
|                           | 802.11ac(VHT20) | 36      | 5180        | 11.71               | 12.00                | No                |
|                           |                 | 40      | 5200        | 11.52               | 12.00                | No                |
|                           |                 | 48      | 5240        | 11.40               | 11.50                | No                |
|                           | 802.11n(HT40)   | 38      | 5190        | 11.59               | 12.00                | No                |
|                           |                 | 46      | 5230        | 11.32               | 11.50                | No                |
|                           | 802.11ac(VHT40) | 38      | 5190        | 12.22               | 12.50                | No                |
|                           |                 | 46      | 5230        | 11.70               | 12.00                | No                |
|                           | 802.11ac(VHT80) | 42      | 5210        | <b>12.43</b>        | <b>12.50</b>         | Yes               |
| Band (GHz)                | Mode            | Channel | Freq. (MHz) | Average Power (dBm) | Maximum Tune-up(dBm) | SAR Test Require. |
| U-NII-2a<br>(5.250~5.350) | 802.11a         | 52      | 5260        | <b>12.01</b>        | <b>12.50</b>         | Yes               |
|                           |                 | 60      | 5300        | 11.32               | 11.50                | No                |
|                           |                 | 64      | 5320        | 11.68               | 12.00                | No                |
|                           | 802.11n(HT20)   | 52      | 5260        | 11.78               | 12.00                | No                |
|                           |                 | 60      | 5300        | 11.25               | 11.50                | No                |
|                           |                 | 64      | 5320        | 11.40               | 11.50                | No                |
|                           | 802.11ac(VHT20) | 52      | 5260        | 11.58               | 12.00                | No                |
|                           |                 | 60      | 5300        | 10.98               | 11.00                | No                |
|                           |                 | 64      | 5320        | 11.17               | 11.50                | No                |
|                           | 802.11n(HT40)   | 54      | 5270        | 11.47               | 11.50                | No                |
|                           |                 | 62      | 5310        | 10.93               | 11.00                | No                |
|                           | 802.11ac(VHT40) | 54      | 5270        | 11.83               | 12.00                | No                |
|                           |                 | 62      | 5310        | 11.28               | 11.50                | No                |
|                           | 802.11ac(VHT80) | 58      | 5290        | 11.90               | 12.00                | No                |
| Band (GHz)                | Mode            | Channel | Freq. (MHz) | Average Power (dBm) | Maximum Tune-up(dBm) | SAR Test Require. |
| U-NII-2c<br>(5.470~5.725) | 802.11a         | 100     | 5500        | <b>11.05</b>        | <b>11.50</b>         | Yes               |
|                           |                 | 116     | 5580        | 10.04               | 10.50                | No                |
|                           |                 | 140     | 5700        | 10.09               | 10.50                | No                |
|                           | 802.11n(HT20)   | 100     | 5500        | 10.14               | 10.50                | No                |

|                          | 802.11ac(VHT20) | 116     | 5580        | 9.82                | 10.00                | No                |
|--------------------------|-----------------|---------|-------------|---------------------|----------------------|-------------------|
|                          |                 | 140     | 5700        | 10.04               | 10.50                | No                |
|                          |                 | 100     | 5500        | 10.07               | 10.50                | No                |
|                          |                 | 116     | 5580        | 9.99                | 10.00                | No                |
|                          |                 | 140     | 5700        | 9.96                | 10.00                | No                |
|                          |                 | 102     | 5510        | 10.25               | 10.50                | No                |
|                          | 802.11n(HT40)   | 110     | 5550        | 10.22               | 10.50                | No                |
|                          |                 | 134     | 5670        | 10.39               | 10.50                | No                |
|                          |                 | 102     | 5510        | 10.27               | 10.50                | No                |
|                          | 802.11ac(VHT40) | 110     | 5550        | 10.05               | 10.50                | No                |
|                          |                 | 134     | 5670        | 10.28               | 10.50                | No                |
|                          |                 | 106     | 5530        | 10.45               | 10.50                | No                |
|                          | 802.11ac(VHT80) | 122     | 5610        | 10.20               | 10.50                | No                |
| Band (GHz)               | Mode            | Channel | Freq. (MHz) | Average Power (dBm) | Maximum Tune-up(dBm) | SAR Test Require. |
| U-NII-3<br>(5.725~5.850) | 802.11a         | 149     | 5745        | 10.76               | 11.00                | No                |
|                          |                 | 157     | 5785        | 10.81               | 11.00                | No                |
|                          |                 | 165     | 5825        | 11.11               | 11.50                | No                |
|                          | 802.11n(HT20)   | 149     | 5745        | 10.64               | 11.00                | No                |
|                          |                 | 157     | 5785        | 10.57               | 11.00                | No                |
|                          |                 | 165     | 5825        | 10.96               | 11.00                | No                |
|                          | 802.11ac(VHT20) | 149     | 5745        | 10.40               | 10.50                | No                |
|                          |                 | 157     | 5785        | 10.37               | 10.50                | No                |
|                          |                 | 165     | 5825        | 10.78               | 11.00                | No                |
|                          | 802.11n(HT40)   | 151     | 5755        | 10.13               | 10.50                | No                |
|                          |                 | 159     | 5795        | 10.63               | 11.00                | No                |
|                          | 802.11ac(VHT40) | 151     | 5755        | 10.39               | 10.50                | No                |
|                          |                 | 159     | 5795        | 10.90               | 11.00                | No                |
|                          | 802.11ac(VHT80) | 155     | 5775        | <b>11.33</b>        | <b>11.50</b>         | Yes               |

## 8.5 Bluetooth

| EDR | Mode | Maximum Tune-up(dBm) | Average Conducted Output Power(dBm) |             |         |
|-----|------|----------------------|-------------------------------------|-------------|---------|
|     |      |                      | 0                                   | 39          | 78      |
|     |      |                      | 2402MHz                             | 2441MHz     | 2480MHz |
|     |      |                      | 2.83                                | <b>4.61</b> | 3.94    |
| BLE | Mode | Maximum Tune-up(dBm) | Average Conducted Output Power(dBm) |             |         |
|     |      |                      | 0                                   | 20          | 39      |
|     |      |                      | 2402MHz                             | 2440MHz     | 2480MHz |
|     |      |                      | -3.89                               | -2.04       | -2.56   |

### Note

- Per KDB 447498 D04 Interim General RF Exposure Guidance v01, the 1-g SAR test exclusion thresholds for 300 MHz to 6 GHz at *test separation distances*  $\leq 40$  cm are determined by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$


and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1).

\*When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine estimated SAR.

- Per KDB 248227 D01 v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
- The output power of all data rate were prescan, just the worst case (the lowest data rate) of all mode were shown in report.

## 9. Test Exclusion Consideration

Antenna information:



|                                                                                                                                             |                    |
|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| WWAN Antenna                                                                                                                                | GSM/CDMA/LTE TX/RX |
| WLAN/BT Antenna                                                                                                                             | WLAN/BT TX/RX      |
| Note:                                                                                                                                       |                    |
| 1. KDB 447498 D04v01, particular DUT edges were not required to be evaluated for SAR if the antenna-to-edge distance is greater than 2.5cm. |                    |
| 2. Per KDB648474 D04, 10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR < 1.2W/Kg.                                    |                    |

| Distance of The Antenna to the EUT surface and edge (mm) |                 |                |                |                 |               |                  |
|----------------------------------------------------------|-----------------|----------------|----------------|-----------------|---------------|------------------|
| Antenna                                                  | Front Side (mm) | Back Side (mm) | Left Edge (mm) | Right Edge (mm) | Top Edge (mm) | Bottom Edge (mm) |
| WWAN                                                     | <25             | <25            | 28             | 31              | 160           | <25              |
| BT/Wifi                                                  | <25             | <25            | 60             | <25             | <25           | 160              |
| Positions for SAR tests: Hotspot mode                    |                 |                |                |                 |               |                  |
| Antenna                                                  | Front Side (mm) | Back Side (mm) | Left Edge (mm) | Right Edge (mm) | Top Edge (mm) | Bottom Edge (mm) |
| WWAN                                                     | Yes             | Yes            | No             | No              | No            | Yes              |
| BT/Wifi                                                  | Yes             | Yes            | No             | Yes             | Yes           | No               |

## 9.1 SAR Test Exclusion Consideration Table

Per KDB 447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following format to determine simultaneous transmission SAR test exclusion:

(max.power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f(GHz) / x]

W/kg for test separation distances ≤ 50 mm;

where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.

0.4 W/Kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

## Test Result

| Head(0mm gap)   |            |     |             |                 |                     |                |                   |                   |                          |                |                      |           |
|-----------------|------------|-----|-------------|-----------------|---------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode            | Position   | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| GSM 850 (voice) | Left Cheek | 251 | 848.8       | 1.010           | 0.041               | 100.00         | 1.000             | 32.81             | 33.00                    | 1.045          | 0.043                | /         |
|                 | Left Tilt  | 251 | 848.8       | 1.230           | 0.019               | 100.00         | 1.000             | 32.81             | 33.00                    | 1.045          | 0.020                | /         |

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 59 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

|                              | Right Cheek | 251 | 848.8       | -0.660          | 0.049               | 100.00         | 1.000             | 32.81             | 33.00                    | 1.045          | <b>0.051</b>         | 1#        |
|------------------------------|-------------|-----|-------------|-----------------|---------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
|                              | Right Tilt  | 251 | 848.8       | 1.740           | 0.023               | 100.00         | 1.000             | 32.81             | 33.00                    | 1.045          | 0.024                | /         |
| Body(10mm Gap)               |             |     |             |                 |                     |                |                   |                   |                          |                |                      |           |
| Mode                         | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| GSM 850 (voice)              | Front       | 251 | 848.8       | 2.550           | 0.031               | 100.00         | 1.000             | 32.81             | 33.00                    | 1.045          | 0.032                | /         |
|                              | Back        | 251 | 848.8       | -0.490          | 0.038               | 100.00         | 1.000             | 32.81             | 33.00                    | 1.045          | 0.040                | /         |
|                              | Bottom      | 251 | 848.8       | -1.160          | 0.022               | 100.00         | 1.000             | 32.81             | 33.00                    | 1.045          | 0.023                | /         |
| Body(hotspot open, 10mm Gap) |             |     |             |                 |                     |                |                   |                   |                          |                |                      |           |
| Mode                         | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| GPRS 850+2slots              | Front       | 251 | 848.8       | -2.270          | 0.033               | 100.00         | 1.000             | 31.47             | 31.50                    | 1.007          | 0.033                | /         |
|                              | Back        | 251 | 848.8       | -0.270          | 0.040               | 100.00         | 1.000             | 31.47             | 31.50                    | 1.007          | <b>0.040</b>         | 2#        |
|                              | Bottom      | 251 | 848.8       | -3.940          | 0.026               | 100.00         | 1.000             | 31.47             | 31.50                    | 1.007          | 0.026                | /         |

| Head(0mm gap)                |             |     |             |                 |                     |                |                   |                   |                          |                |                      |           |
|------------------------------|-------------|-----|-------------|-----------------|---------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| GSM 1900 (voice)             | Left Cheek  | 512 | 1850.2      | 0.430           | 0.201               | 100.00         | 1.000             | 29.22             | 29.50                    | 1.067          | 0.214                | /         |
|                              | Left Tilt   | 512 | 1850.2      | 3.070           | 0.094               | 100.00         | 1.000             | 29.22             | 29.50                    | 1.067          | 0.100                | /         |
|                              | Right Cheek | 512 | 1850.2      | -3.470          | 0.213               | 100.00         | 1.000             | 29.22             | 29.50                    | 1.067          | <b>0.227</b>         | 3#        |
|                              | Right Tilt  | 512 | 1850.2      | -4.660          | 0.102               | 100.00         | 1.000             | 29.22             | 29.50                    | 1.067          | 0.109                | /         |
| Body(hotspot open, 10mm Gap) |             |     |             |                 |                     |                |                   |                   |                          |                |                      |           |
| Mode                         | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| GSM 1900 (voice)             | Front       | 512 | 1850.2      | -4.100          | 0.038               | 100.00         | 1.000             | 29.22             | 29.50                    | 1.067          | 0.041                | /         |
|                              | Back        | 512 | 1850.2      | 0.110           | 0.041               | 100.00         | 1.000             | 29.22             | 29.50                    | 1.067          | 0.044                | /         |
|                              | Bottom      | 512 | 1850.2      | 1.230           | 0.026               | 100.00         | 1.000             | 29.22             | 29.50                    | 1.067          | 0.028                | /         |
| Body(hotspot open, 10mm Gap) |             |     |             |                 |                     |                |                   |                   |                          |                |                      |           |
| Mode                         | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| GPRS 1900+2slots             | Front       | 512 | 1850.2      | -4.040          | 0.031               | 100.00         | 1.000             | 28.37             | 28.50                    | 1.030          | 0.032                | /         |
|                              | Back        | 512 | 1850.2      | -2.490          | 0.044               | 100.00         | 1.000             | 28.37             | 28.50                    | 1.030          | <b>0.045</b>         | 4#        |
|                              | Bottom      | 512 | 1850.2      | 1.660           | 0.024               | 100.00         | 1.000             | 28.37             | 28.50                    | 1.030          | 0.025                | /         |

| Head(0mm gap)                |             |      |             |                 |                     |                |                   |                   |                          |                |                      |           |
|------------------------------|-------------|------|-------------|-----------------|---------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Position    | Ch.  | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| WCDMA Band 2 (RMC*)          | Left Cheek  | 9262 | 1852.4      | -3.570          | 0.496               | 100.00         | 1.000             | 20.94             | 21.00                    | 1.014          | 0.503                | /         |
|                              | Left Tilt   | 9262 | 1852.4      | 1.990           | 0.211               | 100.00         | 1.000             | 20.94             | 21.00                    | 1.014          | 0.214                | /         |
|                              | Right Cheek | 9262 | 1852.4      | -2.880          | 0.523               | 100.00         | 1.000             | 20.94             | 21.00                    | 1.014          | <b>0.530</b>         | 5#        |
|                              | Right Tilt  | 9262 | 1852.4      | 2.220           | 0.249               | 100.00         | 1.000             | 20.94             | 21.00                    | 1.014          | 0.252                | /         |
| Body(hotspot open, 10mm Gap) |             |      |             |                 |                     |                |                   |                   |                          |                |                      |           |
| Mode                         | Position    | Ch.  | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| WCDMA Band 2 (RMC*)          | Front       | 9262 | 1852.4      | 3.840           | 0.200               | 100.00         | 1.000             | 20.94             | 21.00                    | 1.014          | 0.203                | /         |
|                              | Back        | 9262 | 1852.4      | -2.970          | 0.203               | 100.00         | 1.000             | 20.94             | 21.00                    | 1.014          | <b>0.206</b>         | 6#        |
|                              | Bottom      | 9262 | 1852.4      | -1.170          | 0.155               | 100.00         | 1.000             | 20.94             | 21.00                    | 1.014          | 0.157                | /         |

| Head(0mm gap)                |             |      |             |                 |                     |                |                   |                   |                          |                |                      |           |
|------------------------------|-------------|------|-------------|-----------------|---------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Position    | Ch.  | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| WCDMA Band 4 (RMC*)          | Left Cheek  | 1513 | 1752.6      | -0.110          | 0.495               | 100.00         | 1.000             | 21.26             | 21.50                    | 1.057          | 0.523                | /         |
|                              | Left Tilt   | 1513 | 1752.6      | 0.560           | 0.233               | 100.00         | 1.000             | 21.26             | 21.50                    | 1.057          | 0.246                | /         |
|                              | Right Cheek | 1513 | 1752.6      | -2.030          | 0.540               | 100.00         | 1.000             | 21.26             | 21.50                    | 1.057          | <b>0.571</b>         | 7#        |
|                              | Right Tilt  | 1513 | 1752.6      | -2.430          | 0.279               | 100.00         | 1.000             | 21.26             | 21.50                    | 1.057          | 0.295                | /         |
| Body(hotspot open, 10mm Gap) |             |      |             |                 |                     |                |                   |                   |                          |                |                      |           |
| Mode                         | Position    | Ch.  | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| WCDMA Band 4 (RMC*)          | Front       | 1513 | 1752.6      | -1.730          | 0.164               | 100.00         | 1.000             | 21.26             | 21.50                    | 1.057          | 0.173                | /         |
|                              | Back        | 1513 | 1752.6      | -3.330          | 0.179               | 100.00         | 1.000             | 21.26             | 21.50                    | 1.057          | <b>0.189</b>         | 8#        |
|                              | Bottom      | 1513 | 1752.6      | -1.430          | 0.146               | 100.00         | 1.000             | 21.26             | 21.50                    | 1.057          | 0.154                | /         |

| Head(0mm gap) |          |     |             |                 |                     |                |                   |                   |                          |                |                      |           |
|---------------|----------|-----|-------------|-----------------|---------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode          | Position | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas. SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |

|                              |             |      |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|-------------|------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| WCDMA Band 5<br>(RMC*)       | Left Cheek  | 4183 | 836.6       | -3.760          | 0.129              | 100.00         | 1.000             | 21.21             | 21.50                    | 1.069          | 0.138                | /         |
|                              | Left Tilt   | 4183 | 836.6       | -0.930          | 0.052              | 100.00         | 1.000             | 21.21             | 21.50                    | 1.069          | 0.056                | /         |
|                              | Right Cheek | 4183 | 836.6       | -2.390          | 0.138              | 100.00         | 1.000             | 21.21             | 21.50                    | 1.069          | <b>0.148</b>         | 9#        |
|                              | Right Tilt  | 4183 | 836.6       | -1.170          | 0.095              | 100.00         | 1.000             | 21.21             | 21.50                    | 1.069          | 0.102                | /         |
| Body(hotspot open, 10mm Gap) |             |      |             |                 |                    |                |                   |                   |                          |                |                      |           |
| Mode                         | Position    | Ch.  | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| WCDMA Band 5<br>(RMC*)       | Front       | 4183 | 836.6       | -1.240          | 0.102              | 100.00         | 1.000             | 21.21             | 21.50                    | 1.069          | 0.109                | /         |
|                              | Back        | 4183 | 836.6       | -0.940          | 0.161              | 100.00         | 1.000             | 21.21             | 21.50                    | 1.069          | <b>0.121</b>         | 10#       |
|                              | Bottom      | 4183 | 836.6       | 0.270           | 0.076              | 100.00         | 1.000             | 21.21             | 21.50                    | 1.069          | 0.081                | /         |

| Head(0mm gap)         |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|-----------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                  | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 2<br>(BW: 20MHz) | 1RB          | Left Cheek  | 18700 | 1860.0      | -0.890          | 0.606              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.610                | /         |
|                       |              | Left Tilt   | 18700 | 1860.0      | 2.510           | 0.298              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.300                | /         |
|                       |              | Right Cheek | 18700 | 1860.0      | -0.230          | 0.667              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | <b>0.672</b>         | 11#       |
|                       |              | Right Tilt  | 18700 | 1860.0      | 3.020           | 0.325              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.327                | /         |
|                       | 50%RB        | Left Cheek  | 18700 | 1860.0      | -3.380          | 0.511              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.531                | /         |
|                       |              | Left Tilt   | 18700 | 1860.0      | -4.050          | 0.202              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.210                | /         |
|                       |              | Right Cheek | 18700 | 1860.0      | 3.640           | 0.543              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.565                | /         |
|                       |              | Right Tilt  | 18700 | 1860.0      | 3.330           | 0.231              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.240                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 2<br>(BW: 20MHz)        | 1RB          | Front    | 18700 | 1860.0      | 0.270           | 0.210              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.211                | /         |
|                              |              | Back     | 18700 | 1860.0      | -1.710          | 0.284              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | <b>0.286</b>         | 12#       |
|                              |              | Bottom   | 18700 | 1860.0      | 3.790           | 0.188              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.189                | /         |
|                              | 50%RB        | Front    | 18700 | 1860.0      | 1.150           | 0.189              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.197                | /         |
|                              |              | Back     | 18700 | 1860.0      | 3.530           | 0.244              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.254                | /         |
|                              |              | Bottom   | 18700 | 1860.0      | 2.890           | 0.132              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.137                | /         |

| Head(0mm gap)         |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|-----------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                  | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 4<br>(BW: 20MHz) | 1RB          | Left Cheek  | 20175 | 1732.5      | 1.030           | 0.421              | 100.00         | 1.000             | 21.12             | 21.50                    | 1.091          | 0.459                | /         |
|                       |              | Left Tilt   | 20175 | 1732.5      | 2.060           | 0.172              | 100.00         | 1.000             | 21.12             | 21.50                    | 1.091          | 0.188                | /         |
|                       |              | Right Cheek | 20175 | 1732.5      | -3.550          | 0.487              | 100.00         | 1.000             | 21.12             | 21.50                    | 1.091          | <b>0.531</b>         | 13#       |
|                       |              | Right Tilt  | 20175 | 1732.5      | 2.960           | 0.221              | 100.00         | 1.000             | 21.12             | 21.50                    | 1.091          | 0.241                | /         |
|                       | 50%RB        | Left Cheek  | 20175 | 1732.5      | 2.480           | 0.248              | 100.00         | 1.000             | 20.00             | 20.50                    | 1.122          | 0.278                | /         |
|                       |              | Left Tilt   | 20175 | 1732.5      | 0.830           | 0.095              | 100.00         | 1.000             | 20.00             | 20.50                    | 1.122          | 0.107                | /         |
|                       |              | Right Cheek | 20175 | 1732.5      | 2.570           | 0.354              | 100.00         | 1.000             | 20.00             | 20.50                    | 1.122          | 0.397                | /         |
|                       |              | Right Tilt  | 20175 | 1732.5      | -3.040          | 0.131              | 100.00         | 1.000             | 20.00             | 20.50                    | 1.122          | 0.147                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 4<br>(BW: 20MHz)        | 1RB          | Front    | 20175 | 1732.5      | -2.090          | 0.137              | 100.00         | 1.000             | 21.12             | 21.50                    | 1.091          | 0.149                | /         |
|                              |              | Back     | 20175 | 1732.5      | 3.520           | 0.184              | 100.00         | 1.000             | 21.12             | 21.50                    | 1.091          | <b>0.201</b>         | 14#       |
|                              |              | Bottom   | 20175 | 1732.5      | -0.150          | 0.092              | 100.00         | 1.000             | 21.12             | 21.50                    | 1.091          | 0.100                | /         |
|                              | 50%RB        | Front    | 20175 | 1732.5      | 3.320           | 0.088              | 100.00         | 1.000             | 20.00             | 20.50                    | 1.122          | 0.099                | /         |
|                              |              | Back     | 20175 | 1732.5      | -4.540          | 0.107              | 100.00         | 1.000             | 20.00             | 20.50                    | 1.122          | 0.120                | /         |
|                              |              | Bottom   | 20175 | 1732.5      | 3.320           | 0.048              | 100.00         | 1.000             | 20.00             | 20.50                    | 1.122          | 0.054                | /         |

| Head(0mm gap)                |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 5<br>(BW: 10MHz)        | 1RB          | Left Cheek  | 20450 | 829.0       | 1.240           | 0.156              | 100.00         | 1.000             | 21.58             | 22.00                    | 1.102          | 0.172                | /         |
|                              |              | Left Tilt   | 20450 | 829.0       | -0.500          | 0.042              | 100.00         | 1.000             | 21.58             | 22.00                    | 1.102          | 0.046                | /         |
|                              |              | Right Cheek | 20450 | 829.0       | 0.850           | 0.173              | 100.00         | 1.000             | 21.58             | 22.00                    | 1.102          | <b>0.191</b>         | 15#       |
|                              |              | Right Tilt  | 20450 | 829.0       | 3.270           | 0.074              | 100.00         | 1.000             | 21.58             | 22.00                    | 1.102          | 0.082                | /         |
|                              | 50%RB        | Left Cheek  | 20450 | 829.0       | 4.430           | 0.094              | 100.00         | 1.000             | 20.38             | 20.50                    | 1.028          | 0.097                | /         |
|                              |              | Left Tilt   | 20450 | 829.0       | -3.130          | 0.032              | 100.00         | 1.000             | 20.38             | 20.50                    | 1.028          | 0.033                | /         |
|                              |              | Right Cheek | 20450 | 829.0       | -4.530          | 0.111              | 100.00         | 1.000             | 20.38             | 20.50                    | 1.028          | 0.114                | /         |
|                              |              | Right Tilt  | 20450 | 829.0       | 3.750           | 0.051              | 100.00         | 1.000             | 20.38             | 20.50                    | 1.028          | 0.052                | /         |
| Body(hotspot open, 10mm Gap) |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |

| Mode                  | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
|-----------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Band 5<br>(BW: 10MHz) | 1RB          | Front    | 20450 | 829.0       | -2.170          | 0.113              | 100.00         | 1.000             | 21.58             | 22.00                    | 1.102          | 0.125                | /         |
|                       |              | Back     | 20450 | 829.0       | -3.900          | 0.201              | 100.00         | 1.000             | 21.58             | 22.00                    | 1.102          | <b>0.222</b>         | 16#       |
|                       |              | Bottom   | 20450 | 829.0       | 3.990           | 0.076              | 100.00         | 1.000             | 21.58             | 22.00                    | 1.102          | 0.084                | /         |
|                       | 50%RB        | Front    | 20450 | 829.0       | 3.050           | 0.096              | 100.00         | 1.000             | 20.38             | 20.50                    | 1.028          | 0.099                | /         |
|                       |              | Back     | 20450 | 829.0       | 2.240           | 0.185              | 100.00         | 1.000             | 20.38             | 20.50                    | 1.028          | 0.190                | /         |
|                       |              | Bottom   | 20450 | 829.0       | 0.040           | 0.065              | 100.00         | 1.000             | 20.38             | 20.50                    | 1.028          | 0.067                | /         |

| Head(0mm gap)          |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                   | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 12<br>(BW: 10MHz) | 1RB          | Left Cheek  | 23060 | 704.0       | 2.820           | 0.105              | 100.00         | 1.000             | 21.30             | 21.50                    | 1.047          | 0.110                | /         |
|                        |              | Left Tilt   | 23060 | 704.0       | -0.010          | 0.048              | 100.00         | 1.000             | 21.30             | 21.50                    | 1.047          | 0.050                | /         |
|                        |              | Right Cheek | 23060 | 704.0       | -1.980          | 0.128              | 100.00         | 1.000             | 21.30             | 21.50                    | 1.047          | <b>0.134</b>         | 17#       |
|                        |              | Right Tilt  | 23060 | 704.0       | 1.030           | 0.061              | 100.00         | 1.000             | 21.30             | 21.50                    | 1.047          | 0.064                | /         |
|                        | 50%RB        | Left Cheek  | 23060 | 704.0       | -3.490          | 0.094              | 100.00         | 1.000             | 20.20             | 20.50                    | 1.072          | 0.101                | /         |
|                        |              | Left Tilt   | 23060 | 704.0       | -0.380          | 0.043              | 100.00         | 1.000             | 20.20             | 20.50                    | 1.072          | 0.046                | /         |
|                        |              | Right Cheek | 23060 | 704.0       | 4.900           | 0.118              | 100.00         | 1.000             | 20.20             | 20.50                    | 1.072          | 0.126                | /         |
|                        |              | Right Tilt  | 23060 | 704.0       | 4.320           | 0.055              | 100.00         | 1.000             | 20.20             | 20.50                    | 1.072          | 0.059                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 12<br>(BW: 10MHz)       | 1RB          | Front    | 23060 | 704.0       | -3.210          | 0.126              | 100.00         | 1.000             | 21.30             | 21.50                    | 1.047          | 0.132                | /         |
|                              |              | Back     | 23060 | 704.0       | -2.000          | 0.135              | 100.00         | 1.000             | 21.30             | 21.50                    | 1.047          | <b>0.141</b>         | 18#       |
|                              |              | Bottom   | 23060 | 704.0       | -0.300          | 0.088              | 100.00         | 1.000             | 21.30             | 21.50                    | 1.047          | 0.092                | /         |
|                              | 50%RB        | Front    | 23060 | 704.0       | -3.760          | 0.110              | 100.00         | 1.000             | 20.20             | 20.50                    | 1.072          | 0.118                | /         |
|                              |              | Back     | 23060 | 704.0       | 1.500           | 0.130              | 100.00         | 1.000             | 20.20             | 20.50                    | 1.072          | 0.139                | /         |
|                              |              | Bottom   | 23060 | 704.0       | 4.520           | 0.072              | 100.00         | 1.000             | 20.20             | 20.50                    | 1.072          | 0.077                | /         |

| Head(0mm gap)          |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                   | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 13<br>(BW: 10MHz) | 1RB          | Left Cheek  | 23230 | 782.0       | -4.710          | 0.101              | 100.00         | 1.000             | 21.46             | 21.50                    | 1.009          | 0.102                | /         |
|                        |              | Left Tilt   | 23230 | 782.0       | -3.330          | 0.047              | 100.00         | 1.000             | 21.46             | 21.50                    | 1.009          | 0.047                | /         |
|                        |              | Right Cheek | 23230 | 782.0       | -0.510          | 0.109              | 100.00         | 1.000             | 21.46             | 21.50                    | 1.009          | <b>0.110</b>         | 19#       |
|                        |              | Right Tilt  | 23230 | 782.0       | 0.670           | 0.055              | 100.00         | 1.000             | 21.46             | 21.50                    | 1.009          | 0.055                | /         |
|                        | 50%RB        | Left Cheek  | 23230 | 782.0       | -2.860          | 0.082              | 100.00         | 1.000             | 20.47             | 20.50                    | 1.007          | 0.083                | /         |
|                        |              | Left Tilt   | 23230 | 782.0       | -4.480          | 0.042              | 100.00         | 1.000             | 20.47             | 20.50                    | 1.007          | 0.042                | /         |
|                        |              | Right Cheek | 23230 | 782.0       | 3.860           | 0.097              | 100.00         | 1.000             | 20.47             | 20.50                    | 1.007          | 0.098                | /         |
|                        |              | Right Tilt  | 23230 | 782.0       | -1.050          | 0.051              | 100.00         | 1.000             | 20.47             | 20.50                    | 1.007          | 0.051                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 13<br>(BW: 10MHz)       | 1RB          | Front    | 23230 | 782.0       | -3.130          | 0.099              | 100.00         | 1.000             | 21.46             | 21.50                    | 1.009          | 0.100                | /         |
|                              |              | Back     | 23230 | 782.0       | 2.810           | 0.121              | 100.00         | 1.000             | 21.46             | 21.50                    | 1.009          | <b>0.122</b>         | 20#       |
|                              |              | Bottom   | 23230 | 782.0       | -4.010          | 0.077              | 100.00         | 1.000             | 21.46             | 21.50                    | 1.009          | 0.078                | /         |
|                              | 50%RB        | Front    | 23230 | 782.0       | 2.510           | 0.085              | 100.00         | 1.000             | 20.47             | 20.50                    | 1.007          | 0.086                | /         |
|                              |              | Back     | 23230 | 782.0       | 0.740           | 0.112              | 100.00         | 1.000             | 20.47             | 20.50                    | 1.007          | 0.113                | /         |
|                              |              | Bottom   | 23230 | 782.0       | 4.360           | 0.074              | 100.00         | 1.000             | 20.47             | 20.50                    | 1.007          | 0.075                | /         |

| Head(0mm gap)          |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                   | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 17<br>(BW: 10MHz) | 1RB          | Left Cheek  | 23780 | 709.0       | -1.990          | 0.133              | 100.00         | 1.000             | 21.25             | 21.50                    | 1.059          | 0.141                | /         |
|                        |              | Left Tilt   | 23780 | 709.0       | 4.730           | 0.062              | 100.00         | 1.000             | 21.25             | 21.50                    | 1.059          | 0.066                | /         |
|                        |              | Right Cheek | 23780 | 709.0       | -3.990          | 0.142              | 100.00         | 1.000             | 21.25             | 21.50                    | 1.059          | <b>0.150</b>         | 21#       |
|                        |              | Right Tilt  | 23780 | 709.0       | 4.220           | 0.088              | 100.00         | 1.000             | 21.25             | 21.50                    | 1.059          | 0.093                | /         |
|                        | 50%RB        | Left Cheek  | 23780 | 709.0       | -2.230          | 0.119              | 100.00         | 1.000             | 20.13             | 20.50                    | 1.089          | 0.130                | /         |
|                        |              | Left Tilt   | 23780 | 709.0       | -3.300          | 0.042              | 100.00         | 1.000             | 20.13             | 20.50                    | 1.089          | 0.046                | /         |
|                        |              | Right Cheek | 23780 | 709.0       | 1.860           | 0.138              | 100.00         | 1.000             | 20.13             | 20.50                    | 1.089          | 0.150                | /         |
|                        |              | Right Tilt  | 23780 | 709.0       | -4.420          | 0.071              | 100.00         | 1.000             | 20.13             | 20.50                    | 1.089          | 0.077                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 17                      | 1RB          | Front    | 23780 | 709.0       | -2.600          | 0.107              | 100.00         | 1.000             | 21.25             | 21.50                    | 1.059          | 0.113                | /         |

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 59 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

|             |       |        |       |       |        |       |        |       |       |       |       |       |     |
|-------------|-------|--------|-------|-------|--------|-------|--------|-------|-------|-------|-------|-------|-----|
| (BW: 10MHz) | 50%RB | Back   | 23780 | 709.0 | 2.370  | 0.136 | 100.00 | 1.000 | 21.25 | 21.50 | 1.059 | 0.144 | 22# |
|             |       | Bottom | 23780 | 709.0 | -2.260 | 0.099 | 100.00 | 1.000 | 21.25 | 21.50 | 1.059 | 0.105 | /   |
|             |       | Front  | 23780 | 709.0 | 0.550  | 0.098 | 100.00 | 1.000 | 20.13 | 20.50 | 1.089 | 0.107 | /   |
|             |       | Back   | 23780 | 709.0 | -2.760 | 0.128 | 100.00 | 1.000 | 20.13 | 20.50 | 1.089 | 0.139 | /   |
|             |       | Bottom | 23780 | 709.0 | 0.970  | 0.082 | 100.00 | 1.000 | 20.13 | 20.50 | 1.089 | 0.089 | /   |

| Head(0mm gap)         |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|-----------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                  | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 25<br>(BW:20MHz) | 1RB          | Left Cheek  | 26140 | 1860.0      | 1.350           | 0.573              | 100.00         | 1.000             | 22.47             | 22.50                    | 1.007          | 0.577                | /         |
|                       |              | Left Tilt   | 26140 | 1860.0      | -2.690          | 0.243              | 100.00         | 1.000             | 22.47             | 22.50                    | 1.007          | 0.245                | /         |
|                       |              | Right Cheek | 26140 | 1860.0      | -1.910          | 0.639              | 100.00         | 1.000             | 22.47             | 22.50                    | 1.007          | 0.643                | 23#       |
|                       |              | Right Tilt  | 26140 | 1860.0      | 1.570           | 0.361              | 100.00         | 1.000             | 22.47             | 22.50                    | 1.007          | 0.364                | /         |
|                       | 50%RB        | Left Cheek  | 26140 | 1860.0      | 1.020           | 0.438              | 100.00         | 1.000             | 21.31             | 21.50                    | 1.045          | 0.458                | /         |
|                       |              | Left Tilt   | 26140 | 1860.0      | -1.870          | 0.251              | 100.00         | 1.000             | 21.31             | 21.50                    | 1.045          | 0.262                | /         |
|                       |              | Right Cheek | 26140 | 1860.0      | -1.270          | 0.554              | 100.00         | 1.000             | 21.31             | 21.50                    | 1.045          | 0.579                | /         |
|                       |              | Right Tilt  | 26140 | 1860.0      | -3.110          | 0.337              | 100.00         | 1.000             | 21.31             | 21.50                    | 1.045          | 0.352                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 25<br>(BW: 20MHz)       | 1RB          | Front    | 26140 | 1860.0      | -4.500          | 0.228              | 100.00         | 1.000             | 22.47             | 22.50                    | 1.007          | 0.230                | /         |
|                              |              | Back     | 26140 | 1860.0      | -4.030          | 0.267              | 100.00         | 1.000             | 22.47             | 22.50                    | 1.007          | 0.269                | 24#       |
|                              |              | Bottom   | 26140 | 1860.0      | -1.910          | 0.123              | 100.00         | 1.000             | 22.47             | 22.50                    | 1.007          | 0.124                | /         |
|                              | 50%RB        | Front    | 26140 | 1860.0      | -4.010          | 0.184              | 100.00         | 1.000             | 21.31             | 21.50                    | 1.045          | 0.192                | /         |
|                              |              | Back     | 26140 | 1860.0      | -2.560          | 0.231              | 100.00         | 1.000             | 21.31             | 21.50                    | 1.045          | 0.241                | /         |
|                              |              | Bottom   | 26140 | 1860.0      | -3.330          | 0.134              | 100.00         | 1.000             | 21.31             | 21.50                    | 1.045          | 0.140                | /         |

| Head(0mm gap)                |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 26 Part90<br>(BW:10MHz) | 1RB          | Left Cheek  | 26740 | 819.0       | -0.450          | 0.221              | 100.00         | 1.000             | 22.98             | 23.00                    | 1.005          | 0.222                | /         |
|                              |              | Left Tilt   | 26740 | 819.0       | -0.290          | 0.097              | 100.00         | 1.000             | 22.98             | 23.00                    | 1.005          | 0.097                | /         |
|                              |              | Right Cheek | 26740 | 819.0       | 2.720           | 0.245              | 100.00         | 1.000             | 22.98             | 23.00                    | 1.005          | 0.246                | 25#       |
|                              |              | Right Tilt  | 26740 | 819.0       | -2.190          | 0.113              | 100.00         | 1.000             | 22.98             | 23.00                    | 1.005          | 0.114                | /         |
|                              | 50%RB        | Left Cheek  | 26740 | 819.0       | -2.370          | 0.175              | 100.00         | 1.000             | 21.81             | 22.00                    | 1.045          | 0.183                | /         |
|                              |              | Left Tilt   | 26740 | 819.0       | 0.990           | 0.063              | 100.00         | 1.000             | 21.81             | 22.00                    | 1.045          | 0.066                | /         |
|                              |              | Right Cheek | 26740 | 819.0       | 1.340           | 0.208              | 100.00         | 1.000             | 21.81             | 22.00                    | 1.045          | 0.217                | /         |
|                              |              | Right Tilt  | 26740 | 819.0       | -4.720          | 0.104              | 100.00         | 1.000             | 21.81             | 22.00                    | 1.045          | 0.109                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 26 Part90<br>(BW:10MHz) | 1RB          | Front    | 26740 | 819.0       | -2.400          | 0.172              | 100.00         | 1.000             | 22.98             | 23.00                    | 1.005          | 0.173                | /         |
|                              |              | Back     | 26740 | 819.0       | -3.300          | 0.179              | 100.00         | 1.000             | 22.98             | 23.00                    | 1.005          | 0.180                | 26#       |
|                              |              | Bottom   | 26740 | 819.0       | -4.670          | 0.134              | 100.00         | 1.000             | 22.98             | 23.00                    | 1.005          | 0.135                | /         |
|                              | 50%RB        | Front    | 26740 | 819.0       | -4.340          | 0.155              | 100.00         | 1.000             | 21.81             | 22.00                    | 1.045          | 0.162                | /         |
|                              |              | Back     | 26740 | 819.0       | 3.880           | 0.158              | 100.00         | 1.000             | 21.81             | 22.00                    | 1.045          | 0.165                | /         |
|                              |              | Bottom   | 26740 | 819.0       | -4.870          | 0.125              | 100.00         | 1.000             | 21.81             | 22.00                    | 1.045          | 0.131                | /         |

| Head(0mm gap)                |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 26 Part22<br>(BW:15MHz) | 1RB          | Left Cheek  | 26965 | 841.5       | 1.850           | 0.242              | 100.00         | 1.000             | 16.93             | 17.00                    | 1.016          | 0.246                | /         |
|                              |              | Left Tilt   | 26965 | 841.5       | 0.260           | 0.144              | 100.00         | 1.000             | 16.93             | 17.00                    | 1.016          | 0.146                | /         |
|                              |              | Right Cheek | 26965 | 841.5       | 2.420           | 0.251              | 100.00         | 1.000             | 16.93             | 17.00                    | 1.016          | 0.255                | 27#       |
|                              |              | Right Tilt  | 26965 | 841.5       | -2.100          | 0.156              | 100.00         | 1.000             | 16.93             | 17.00                    | 1.016          | 0.158                | /         |
|                              | 50%RB        | Left Cheek  | 26965 | 841.5       | -1.780          | 0.231              | 100.00         | 1.000             | 15.77             | 16.00                    | 1.054          | 0.244                | /         |
|                              |              | Left Tilt   | 26965 | 841.5       | 0.910           | 0.097              | 100.00         | 1.000             | 15.77             | 16.00                    | 1.054          | 0.102                | /         |
|                              |              | Right Cheek | 26965 | 841.5       | 1.650           | 0.243              | 100.00         | 1.000             | 15.77             | 16.00                    | 1.054          | 0.256                | /         |
|                              |              | Right Tilt  | 26965 | 841.5       | -2.690          | 0.102              | 100.00         | 1.000             | 15.77             | 16.00                    | 1.054          | 0.108                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 26 Part22<br>(BW:15MHz) | 1RB          | Front    | 26965 | 841.5       | 1.970           | 0.106              | 100.00         | 1.000             | 16.93             | 17.00                    | 1.016          | 0.108                | /         |
|                              |              | Back     | 26965 | 841.5       | -2.290          | 0.159              | 100.00         | 1.000             | 16.93             | 17.00                    | 1.016          | 0.162                | 28#       |
|                              |              | Bottom   | 26965 | 841.5       | 1.710           | 0.087              | 100.00         | 1.000             | 16.93             | 17.00                    | 1.016          | 0.088                | /         |

|  |       |        |       |       |        |       |        |       |       |       |       |       |   |
|--|-------|--------|-------|-------|--------|-------|--------|-------|-------|-------|-------|-------|---|
|  | 50%RB | Front  | 26965 | 841.5 | -2.850 | 0.101 | 100.00 | 1.000 | 15.77 | 16.00 | 1.016 | 0.106 | / |
|  |       | Back   | 26965 | 841.5 | -1.210 | 0.121 | 100.00 | 1.000 | 15.77 | 16.00 | 1.016 | 0.128 | / |
|  |       | Bottom | 26965 | 841.5 | 4.450  | 0.045 | 100.00 | 1.000 | 15.77 | 16.00 | 1.016 | 0.047 | / |

| Head(0mm gap)         |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|-----------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                  | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 38<br>(BW:20MHz) | 1RB          | Left Cheek  | 37850 | 2580.5      | -0.610          | 0.073              | 100.00         | 1.000             | 18.23             | 18.50                    | 1.064          | 0.078                | /         |
|                       |              | Left Tilt   | 37850 | 2580.5      | -1.710          | 0.026              | 100.00         | 1.000             | 18.23             | 18.50                    | 1.064          | 0.028                | /         |
|                       |              | Right Cheek | 37850 | 2580.5      | -3.350          | 0.089              | 100.00         | 1.000             | 18.23             | 18.50                    | 1.064          | <b>0.095</b>         | 29#       |
|                       |              | Right Tilt  | 37850 | 2580.5      | 2.180           | 0.055              | 100.00         | 1.000             | 18.23             | 18.50                    | 1.064          | 0.059                | /         |
|                       | 50%RB        | Left Cheek  | 37850 | 2580.5      | 2.200           | 0.063              | 100.00         | 1.000             | 18.27             | 18.50                    | 1.054          | 0.066                | /         |
|                       |              | Left Tilt   | 37850 | 2580.5      | 0.060           | 0.021              | 100.00         | 1.000             | 18.27             | 18.50                    | 1.054          | 0.022                | /         |
|                       |              | Right Cheek | 37850 | 2580.5      | -1.290          | 0.077              | 100.00         | 1.000             | 18.27             | 18.50                    | 1.054          | 0.081                | /         |
|                       |              | Right Tilt  | 37850 | 2580.5      | 0.520           | 0.031              | 100.00         | 1.000             | 18.27             | 18.50                    | 1.054          | 0.033                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 38<br>(BW:20MHz)        | 1RB          | Front    | 37850 | 2580.5      | -3.930          | 0.094              | 100.00         | 1.000             | 18.23             | 18.50                    | 1.064          | 0.100                | /         |
|                              |              | Back     | 37850 | 2580.5      | -4.100          | 0.130              | 100.00         | 1.000             | 18.23             | 18.50                    | 1.064          | <b>0.138</b>         | 30#       |
|                              |              | Bottom   | 37850 | 2580.5      | -1.460          | 0.085              | 100.00         | 1.000             | 18.23             | 18.50                    | 1.064          | 0.090                | /         |
|                              | 50%RB        | Front    | 37850 | 2580.5      | 0.180           | 0.064              | 100.00         | 1.000             | 18.27             | 18.50                    | 1.054          | 0.067                | /         |
|                              |              | Back     | 37850 | 2580.5      | 4.660           | 0.107              | 100.00         | 1.000             | 18.27             | 18.50                    | 1.054          | 0.113                | /         |
|                              |              | Bottom   | 37850 | 2580.5      | -4.750          | 0.052              | 100.00         | 1.000             | 18.27             | 18.50                    | 1.054          | 0.055                | /         |

| Head(0mm gap)         |              |             |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|-----------------------|--------------|-------------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                  | Channel Type | Position    | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 41<br>(BW:20MHz) | 1RB          | Left Cheek  | 41490 | 2680.0      | 0.960           | 0.127              | 100.00         | 1.000             | 21.41             | 21.50                    | 1.021          | 0.130                | /         |
|                       |              | Left Tilt   | 41490 | 2680.0      | -1.410          | 0.051              | 100.00         | 1.000             | 21.41             | 21.50                    | 1.021          | 0.052                | /         |
|                       |              | Right Cheek | 41490 | 2680.0      | -1.420          | 0.146              | 100.00         | 1.000             | 21.41             | 21.50                    | 1.021          | <b>0.149</b>         | 31#       |
|                       |              | Right Tilt  | 41490 | 2680.0      | 2.210           | 0.087              | 100.00         | 1.000             | 21.41             | 21.50                    | 1.021          | 0.089                | /         |
|                       | 50%RB        | Left Cheek  | 41490 | 2680.0      | 3.640           | 0.118              | 100.00         | 1.000             | 20.12             | 20.50                    | 1.091          | 0.129                | /         |
|                       |              | Left Tilt   | 41490 | 2680.0      | -1.860          | 0.042              | 100.00         | 1.000             | 20.12             | 20.50                    | 1.091          | 0.046                | /         |
|                       |              | Right Cheek | 41490 | 2680.0      | -1.570          | 0.135              | 100.00         | 1.000             | 20.12             | 20.50                    | 1.091          | 0.147                | /         |
|                       |              | Right Tilt  | 41490 | 2680.0      | 3.600           | 0.069              | 100.00         | 1.000             | 20.12             | 20.50                    | 1.091          | 0.075                | /         |

| Body(hotspot open, 10mm Gap) |              |          |       |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|-------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.   | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 41<br>(BW: 20MHz)       | 1RB          | Front    | 41490 | 2680.0      | 3.860           | 0.064              | 100.00         | 1.000             | 21.41             | 21.50                    | 1.021          | 0.065                | /         |
|                              |              | Back     | 41490 | 2680.0      | 3.460           | 0.079              | 100.00         | 1.000             | 21.41             | 21.50                    | 1.021          | <b>0.081</b>         | 32#       |
|                              |              | Bottom   | 41490 | 2680.0      | 1.690           | 0.052              | 100.00         | 1.000             | 21.41             | 21.50                    | 1.021          | 0.053                | /         |
|                              | 50%RB        | Front    | 41490 | 2680.0      | 1.330           | 0.051              | 100.00         | 1.000             | 20.12             | 20.50                    | 1.091          | 0.056                | /         |
|                              |              | Back     | 41490 | 2680.0      | -3.090          | 0.066              | 100.00         | 1.000             | 20.12             | 20.50                    | 1.091          | 0.072                | /         |
|                              |              | Bottom   | 41490 | 2680.0      | -0.520          | 0.048              | 100.00         | 1.000             | 20.12             | 20.50                    | 1.091          | 0.052                | /         |

| Head(0mm gap)          |              |             |        |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------|--------------|-------------|--------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                   | Channel Type | Position    | Ch.    | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 66<br>(BW: 20MHz) | 1RB          | Left Cheek  | 132322 | 1770.0      | 3.520           | 0.543              | 100.00         | 1.000             | 21.37             | 21.50                    | 1.030          | 0.559                | /         |
|                        |              | Left Tilt   | 132322 | 1770.0      | -0.940          | 0.241              | 100.00         | 1.000             | 21.37             | 21.50                    | 1.030          | 0.248                | /         |
|                        |              | Right Cheek | 132322 | 1770.0      | -2.470          | 0.626              | 100.00         | 1.000             | 21.37             | 21.50                    | 1.030          | <b>0.645</b>         | 33#       |
|                        |              | Right Tilt  | 132322 | 1770.0      | -1.070          | 0.358              | 100.00         | 1.000             | 21.37             | 21.50                    | 1.030          | 0.369                | /         |
|                        | 50%RB        | Left Cheek  | 132322 | 1770.0      | -1.030          | 0.502              | 100.00         | 1.000             | 20.35             | 20.50                    | 1.035          | 0.520                | /         |
|                        |              | Left Tilt   | 132322 | 1770.0      | 3.050           | 0.219              | 100.00         | 1.000             | 20.35             | 20.50                    | 1.035          | 0.227                | /         |
|                        |              | Right Cheek | 132322 | 1770.0      | 4.360           | 0.598              | 100.00         | 1.000             | 20.35             | 20.50                    | 1.035          | 0.619                | /         |
|                        |              | Right Tilt  | 132322 | 1770.0      | -2.160          | 0.288              | 100.00         | 1.000             | 20.35             | 20.50                    | 1.035          | 0.298                | /         |

| Body(hotspot open, 10mm Gap) |              |          |        |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|----------|--------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position | Ch.    | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 66<br>(BW: 20MHz)       | 1RB          | Front    | 132322 | 1770.0      | -2.360          | 0.207              | 100.00         | 1.000             | 21.37             | 21.50                    | 1.030          | 0.213                | /         |
|                              |              | Back     | 132322 | 1770.0      | 2.390           | 0.216              | 100.00         | 1.000             | 21.37             | 21.50                    | 1.030          | <b>0.222</b>         | 34#       |
|                              |              | Bottom   | 132322 | 1770.0      | 2.090           | 0.143              | 100.00         | 1.000             | 21.37             | 21.50                    | 1.030          | 0.147                | /         |
|                              | 50%RB        | Front    | 132322 | 1770.0      | -2.850          | 0.177              | 100.00         | 1.000             | 20.35             | 20.50                    | 1.035          | 0.183                | /         |
|                              |              | Back     | 132322 | 1770.0      | 4.110           | 0.206              | 100.00         | 1.000             | 20.35             | 20.50                    | 1.035          | 0.213                | /         |

|  |  |        |        |        |        |       |        |       |       |       |       |       |   |
|--|--|--------|--------|--------|--------|-------|--------|-------|-------|-------|-------|-------|---|
|  |  | Bottom | 132322 | 1770.0 | -3.870 | 0.098 | 100.00 | 1.000 | 20.35 | 20.50 | 1.035 | 0.101 | / |
|--|--|--------|--------|--------|--------|-------|--------|-------|-------|-------|-------|-------|---|

| Head(0mm gap)                |              |             |        |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|--------------|-------------|--------|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Channel Type | Position    | Ch.    | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 71<br>(BW: 20MHz)       | 1RB          | Left Cheek  | 133322 | 683.0       | -0.960          | 0.064              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.064                | /         |
|                              |              | Left Tilt   | 133322 | 683.0       | 3.370           | 0.028              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.028                | /         |
|                              |              | Right Cheek | 133322 | 683.0       | -3.200          | 0.073              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.074                | 35#       |
|                              |              | Right Tilt  | 133322 | 683.0       | -1.070          | 0.032              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.032                | /         |
|                              | 50%RB        | Left Cheek  | 133322 | 683.0       | 4.260           | 0.051              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.053                | /         |
|                              |              | Left Tilt   | 133322 | 683.0       | 1.560           | 0.017              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.018                | /         |
|                              |              | Right Cheek | 133322 | 683.0       | -0.890          | 0.065              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.068                | /         |
|                              |              | Right Tilt  | 133322 | 683.0       | 1.660           | 0.026              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.027                | /         |
| Body(hotspot open, 10mm Gap) |              |             |        |             |                 |                    |                |                   |                   |                          |                |                      |           |
| Mode                         | Channel Type | Position    | Ch.    | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Band 71<br>(BW: 20MHz)       | 1RB          | Front       | 133322 | 683.0       | 1.650           | 0.098              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.099                | /         |
|                              |              | Back        | 133322 | 683.0       | 1.480           | 0.103              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.104                | 36#       |
|                              |              | Bottom      | 133322 | 683.0       | 0.120           | 0.062              | 100.00         | 1.000             | 21.47             | 21.50                    | 1.007          | 0.062                | /         |
|                              | 50%RB        | Front       | 133322 | 683.0       | 0.890           | 0.076              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.079                | /         |
|                              |              | Back        | 133322 | 683.0       | -1.530          | 0.094              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.098                | /         |
|                              |              | Bottom      | 133322 | 683.0       | 3.020           | 0.051              | 100.00         | 1.000             | 20.33             | 20.50                    | 1.040          | 0.053                | /         |

| Head(0mm gap)                               |             |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
|---------------------------------------------|-------------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                                        | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| 2.4g<br>(2.4~2.4835)<br>802.11b             | Left Cheek  | 6   | 2437        | -1.760          | 0.207              | 100.00         | 1.000             | 15.29             | 15.50                    | 1.050          | 0.217                | /         |
|                                             | Left Tilt   | 6   | 2437        | -1.970          | 0.095              | 100.00         | 1.000             | 15.29             | 15.50                    | 1.050          | 0.100                | /         |
|                                             | Right Cheek | 6   | 2437        | -0.960          | 0.224              | 100.00         | 1.000             | 15.29             | 15.50                    | 1.050          | <b>0.235</b>         | 37#       |
|                                             | Right Tilt  | 6   | 2437        | -2.780          | 0.113              | 100.00         | 1.000             | 15.29             | 15.50                    | 1.050          | 0.119                | /         |
| Body(hotspot open, 10mm Gap)                |             |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
| Mode                                        | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| 2.4g<br>(2.4~2.4835)<br>802.11b             | Front       | 6   | 2437        | 2.940           | 0.328              | 100.00         | 1.000             | 15.29             | 15.50                    | 1.050          | 0.344                | /         |
|                                             | Back        | 6   | 2437        | -4.920          | 0.344              | 100.00         | 1.000             | 15.29             | 15.50                    | 1.050          | <b>0.361</b>         | 38#       |
|                                             | Right       | 6   | 2437        | -3.970          | 0.082              | 100.00         | 1.000             | 15.29             | 15.50                    | 1.050          | 0.086                | /         |
|                                             | Top         | 6   | 2437        | -0.410          | 0.143              | 100.00         | 1.000             | 15.29             | 15.50                    | 1.050          | 0.150                | /         |
| Head(0mm gap)                               |             |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
| Mode                                        | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| U-NII-1<br>(5.150~5.250)<br>802.11ac(VHT80) | Left Cheek  | 42  | 5210        | 3.750           | 0.571              | 100.00         | 1.000             | 12.43             | 12.50                    | 1.016          | 0.580                | /         |
|                                             | Left Tilt   | 42  | 5210        | -3.590          | 0.239              | 100.00         | 1.000             | 12.43             | 12.50                    | 1.016          | 0.243                | /         |
|                                             | Right Cheek | 42  | 5210        | -2.300          | 0.645              | 100.00         | 1.000             | 12.43             | 12.50                    | 1.016          | <b>0.655</b>         | 39#       |
|                                             | Right Tilt  | 42  | 5210        | 4.440           | 0.357              | 100.00         | 1.000             | 12.43             | 12.50                    | 1.016          | 0.363                | /         |
| Body(hotspot open, 10mm Gap)                |             |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
| Mode                                        | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| U-NII-1<br>(5.150~5.250)<br>802.11ac(VHT80) | Front       | 42  | 5210        | 3.370           | 0.178              | 100.00         | 1.000             | 12.43             | 12.50                    | 1.016          | 0.181                | /         |
|                                             | Back        | 42  | 5210        | -2.260          | 0.277              | 100.00         | 1.000             | 12.43             | 12.50                    | 1.016          | <b>0.281</b>         | 40#       |
|                                             | Right       | 42  | 5210        | -3.960          | 0.074              | 100.00         | 1.000             | 12.43             | 12.50                    | 1.016          | 0.075                | /         |
|                                             | Top         | 42  | 5210        | 0.380           | 0.121              | 100.00         | 1.000             | 12.43             | 12.50                    | 1.016          | 0.123                | /         |

| Head(0mm gap)                        |             |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
|--------------------------------------|-------------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                                 | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| U-NII-2a<br>(5.250~5.350)<br>802.11a | Left Cheek  | 52  | 5260        | 2.820           | 0.173              | 100.00         | 1.000             | 12.01             | 12.50                    | 1.119          | 0.194                | /         |
|                                      | Left Tilt   | 52  | 5260        | 1.550           | 0.062              | 100.00         | 1.000             | 12.01             | 12.50                    | 1.119          | 0.069                | /         |
|                                      | Right Cheek | 52  | 5260        | 1.490           | 0.212              | 100.00         | 1.000             | 12.01             | 12.50                    | 1.119          | <b>0.237</b>         | 41#       |
|                                      | Right Tilt  | 52  | 5260        | -1.830          | 0.086              | 100.00         | 1.000             | 12.01             | 12.50                    | 1.119          | 0.096                | /         |

| Body(hotspot open, 10mm Gap)         |          |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
|--------------------------------------|----------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                                 | Position | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| U-NII-2a<br>(5.250~5.350)<br>802.11a | Front    | 52  | 5260        | -0.740          | 0.182              | 100.00         | 1.000             | 12.01             | 12.50                    | 1.119          | 0.204                | /         |
|                                      | Back     | 52  | 5260        | -4.870          | 0.278              | 100.00         | 1.000             | 12.01             | 12.50                    | 1.119          | 0.311                | 42#       |
|                                      | Right    | 52  | 5260        | 3.970           | 0.052              | 100.00         | 1.000             | 12.01             | 12.50                    | 1.119          | 0.058                | /         |

|                                              | Top         | 52  | 5260        | -1.850          | 0.146              | 100.00         | 1.000             | 12.01             | 12.50                    | 1.119          | 0.163                | /         |
|----------------------------------------------|-------------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Head(0mm gap)                                |             |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
| Mode                                         | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| U-NII-2c<br>(5.470~5.725)<br>802.11ac(VHT80) | Left Cheek  | 122 | 5610        | -2.170          | 0.066              | 100.00         | 1.000             | 11.05             | 11.50                    | 1.109          | 0.073                | /         |
|                                              | Left Tilt   | 122 | 5610        | 0.480           | 0.031              | 100.00         | 1.000             | 11.05             | 11.50                    | 1.109          | 0.034                | /         |
|                                              | Right Cheek | 122 | 5610        | -1.880          | 0.083              | 100.00         | 1.000             | 11.05             | 11.50                    | 1.109          | <b>0.092</b>         | 43#       |
|                                              | Right Tilt  | 122 | 5610        | 3.640           | 0.052              | 100.00         | 1.000             | 11.05             | 11.50                    | 1.109          | 0.058                | /         |

| Body(hotspot open, 10mm Gap)                 |          |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
|----------------------------------------------|----------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                                         | Position | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| U-NII-2c<br>(5.470~5.725)<br>802.11ac(VHT80) | Front    | 122 | 5610        | 3.660           | 0.005              | 100.00         | 1.000             | 11.05             | 11.50                    | 1.109          | 0.006                | /         |
|                                              | Back     | 122 | 5610        | -4.200          | 0.006              | 100.00         | 1.000             | 11.05             | 11.50                    | 1.109          | <b>0.007</b>         | 44#       |
|                                              | Right    | 122 | 5610        | 3.450           | 0.004              | 100.00         | 1.000             | 11.05             | 11.50                    | 1.109          | 0.004                | /         |
|                                              | Top      | 122 | 5610        | -1.970          | 0.003              | 100.00         | 1.000             | 11.05             | 11.50                    | 1.109          | 0.003                | /         |

| Head(0mm gap)                               |             |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
|---------------------------------------------|-------------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                                        | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| U-NII-3<br>(5.725~5.850)<br>802.11ac(VHT80) | Left Cheek  | 155 | 5775        | 4.160           | 0.179              | 100.00         | 1.000             | 11.33             | 11.50                    | 1.040          | 0.186                | /         |
|                                             | Left Tilt   | 155 | 5775        | -2.830          | 0.087              | 100.00         | 1.000             | 11.33             | 11.50                    | 1.040          | 0.090                | /         |
|                                             | Right Cheek | 155 | 5775        | -3.690          | 0.204              | 100.00         | 1.000             | 11.33             | 11.50                    | 1.040          | <b>0.212</b>         | 45#       |
|                                             | Right Tilt  | 155 | 5775        | -3.200          | 0.142              | 100.00         | 1.000             | 11.33             | 11.50                    | 1.040          | 0.148                | /         |

| Body(hotspot open, 10mm Gap)                |          |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
|---------------------------------------------|----------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                                        | Position | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| U-NII-3<br>(5.725~5.850)<br>802.11ac(VHT80) | Front    | 155 | 5775        | 3.300           | 0.072              | 100.00         | 1.000             | 11.33             | 11.50                    | 1.040          | 0.075                | /         |
|                                             | Back     | 155 | 5775        | 1.940           | 0.098              | 100.00         | 1.000             | 11.33             | 11.50                    | 1.040          | <b>0.102</b>         | 46#       |
|                                             | Right    | 155 | 5775        | -3.150          | 0.021              | 100.00         | 1.000             | 11.33             | 11.50                    | 1.040          | 0.022                | /         |
|                                             | Top      | 155 | 5775        | -2.630          | 0.054              | 100.00         | 1.000             | 11.33             | 11.50                    | 1.040          | 0.056                | /         |

| Head(0mm gap) |             |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
|---------------|-------------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode          | Position    | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Bluetooth     | Left Cheek  | 39  | 2441        | 0.850           | 0.003              | 100.00         | 1.000             | 4.61              | 5.00                     | 1.094          | 0.003                | /         |
|               | Left Tilt   | 39  | 2441        | -3.350          | 0.001              | 100.00         | 1.000             | 4.61              | 5.00                     | 1.094          | 0.001                | /         |
|               | Right Cheek | 39  | 2441        | 1.090           | 0.004              | 100.00         | 1.000             | 4.61              | 5.00                     | 1.094          | <b>0.004</b>         | 47#       |
|               | Right Tilt  | 39  | 2441        | 2.520           | 0.002              | 100.00         | 1.000             | 4.61              | 5.00                     | 1.094          | 0.002                | /         |

| Body(hotspot open, 10mm Gap) |          |     |             |                 |                    |                |                   |                   |                          |                |                      |           |
|------------------------------|----------|-----|-------------|-----------------|--------------------|----------------|-------------------|-------------------|--------------------------|----------------|----------------------|-----------|
| Mode                         | Position | Ch. | Freq. (MHz) | Power Drift (%) | 1g Meas SAR (W/kg) | Duty cycle (%) | Duty cycle Factor | Meas. Power (dBm) | Max. tune-up power (dBm) | Scaling Factor | 1g Scaled SAR (W/kg) | Meas. No. |
| Bluetooth                    | Front    | 39  | 2441        | 3.320           | 0.002              | 100.00         | 1.000             | 4.61              | 5.00                     | 1.094          | 0.002                | /         |
|                              | Back     | 39  | 2441        | 2.840           | 0.003              | 100.00         | 1.000             | 4.61              | 5.00                     | 1.094          | <b>0.003</b>         | 48#       |
|                              | Right    | 39  | 2441        | 0.800           | 0.001              | 100.00         | 1.000             | 4.61              | 5.00                     | 1.094          | 0.001                | /         |
|                              | Top      | 39  | 2441        | -3.380          | 0.001              | 100.00         | 1.000             | 4.61              | 5.00                     | 1.094          | 0.001                | /         |

#### Note:

- The maximum SAR Value of each test band is marked bold.
- SAR plot is provided only for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.
- Per KDB 447498 D04 v01, for each exposure position, if the highest output power channel Reported SAR  $\leq 0.8\text{W/kg}$ , other channels SAR testing is not necessary.
- Per KDB 447498 D04 v01, head/body-worn use is evaluated with the device positioned at 0mm/10 mm from a head/flat phantom respectively filled with head tissue-equivalent medium.
- Per KDB Publication 941225 D06 where SAR test considerations for handsets ( $L \times W \geq 9\text{ cm} \times 5\text{ cm}$ ) are based on a composite test separation distance of 10 mm from the front, back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.
- Per KDB 447498 D04 v01, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor =  $10^{[(\text{tune-up limit power (dBm)} - \text{Ave. power power (dBm)})/10]}$ , where tune-up limit is the maximum rated power among all production units.  
Reported SAR(W/kg)=Measured SAR (W/kg)\*Scaling Factor.

## 10. SAR Measurement Variability

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 59 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is  $< 0.80$  W/kg, repeated measurement is not required.
2. When the highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$ , or when the original or repeated measurement is  $\geq 1.45$  W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ , and the original, first or second repeated measurement is  $\geq 1.5$  W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is  $0.667 < 0.80$  W/kg, repeated measurement is not necessary.

## 11. Simultaneous Transmission

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

### 12. 1 Simultaneous Transmission Mode Considerations

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. The device has 2 Tx antennas, WWAN main antenna, Wifi/BT antenna supports 2.4G&5G WIFI and BT. The 2 antennas can always transmit simultaneously. The work mode combination is showed as below table.

Application Simultaneous Transmission information:

| NO. | Configuration   | Head | Body-worn |
|-----|-----------------|------|-----------|
| 1   | WWAN+WIFI(2.4g) | Yes  | Yes       |
| 2   | WWAN+WIFI(5g)   | Yes  | Yes       |
| 3   | WWAN+BT         | Yes  | Yes       |

## 12.2 Sum SAR of Simultaneous Transmission

Head

| Band       | Channel Type | Test Position | Scaled       |              |              |              | $\Sigma$ SAR (W/kg) WWAN + WIFI 2.4G | $\Sigma$ SAR (W/kg) WWAN + WIFI 5G | $\Sigma$ SAR (W/kg) WWAN + BT | SPLSR | Remark |
|------------|--------------|---------------|--------------|--------------|--------------|--------------|--------------------------------------|------------------------------------|-------------------------------|-------|--------|
|            |              |               | WWAN         | WIFI 2.4G    | WIFI 5G      | Bluetooth    |                                      |                                    |                               |       |        |
| LTE Band 2 | 1RB          | Left Cheek    | 0.610        | 0.217        | 0.580        | 0.003        | 0.827                                | 1.190                              | 0.613                         | N/A   | N/A    |
|            |              | Left Tilt     | 0.300        | 0.100        | 0.243        | 0.001        | 0.400                                | 0.543                              | 0.301                         | N/A   | N/A    |
|            |              | Right Cheek   | <b>0.672</b> | <b>0.235</b> | <b>0.655</b> | <b>0.004</b> | <b>0.907</b>                         | <b>1.327</b>                       | <b>0.676</b>                  | N/A   | N/A    |
|            |              | Right Tilt    | 0.327        | 0.119        | 0.363        | 0.002        | 0.446                                | 0.690                              | 0.329                         | N/A   | N/A    |
|            | 50%RB        | Left Cheek    | 0.531        | 0.217        | 0.580        | 0.003        | 0.748                                | 1.111                              | 0.534                         | N/A   | N/A    |
|            |              | Left Tilt     | 0.210        | 0.100        | 0.243        | 0.001        | 0.310                                | 0.453                              | 0.211                         | N/A   | N/A    |
|            |              | Right Cheek   | 0.565        | 0.235        | 0.655        | 0.004        | 0.800                                | 1.220                              | 0.569                         | N/A   | N/A    |
|            |              | Right Tilt    | 0.240        | 0.119        | 0.363        | 0.002        | 0.359                                | 0.603                              | 0.242                         | N/A   | N/A    |

Hotspot(body-worn)

| Band       | Test Position | Scaled |           |         |           | $\Sigma$ SAR (W/kg) WWAN + WIFI 2.4G | $\Sigma$ SAR (W/kg) WWAN + WIFI 5G | $\Sigma$ SAR (W/kg) WWAN + BT | SPLSR | Remark |
|------------|---------------|--------|-----------|---------|-----------|--------------------------------------|------------------------------------|-------------------------------|-------|--------|
|            |               | WWAN   | WIFI 2.4G | WIFI 5G | Bluetooth |                                      |                                    |                               |       |        |
| LTE Band 2 | Front         | 0.211  | 0.344     | 0.181   | 0.002     | 0.555                                | 0.392                              | 0.213                         | N/A   | N/A    |
|            | Back          | 0.286  | 0.361     | 0.281   | 0.003     | <b>0.647</b>                         | 0.567                              | 0.289                         | N/A   | N/A    |
|            | Left          | /      | /         | /       | /         | /                                    | /                                  | /                             | N/A   | N/A    |
|            | Right         | /      | 0.086     | 0.075   | 0.001     | 0.086                                | 0.075                              | 0.001                         | N/A   | N/A    |
|            | Top           | /      | 0.150     | 0.123   | 0.001     | 0.150                                | 0.123                              | 0.001                         | N/A   | N/A    |
|            | Bottom        | 0.189  | /         | /       | /         | 0.189                                | 0.189                              | 0.189                         | N/A   | N/A    |

## 12. Test Equipment List

| Description                         | Manufacturer    | Model         | Serial No./Version  | Cal. Date  | Cal. Due   |
|-------------------------------------|-----------------|---------------|---------------------|------------|------------|
| E-Field Probe                       | MVG             | SSE2          | 0125-EPGO-445       | 2025/02/01 | 2026/01/31 |
| 6 1/2 Digital Multimeter            | Keithley        | DMM6500       | 4527164             | 2024/10/25 | 2025/10/24 |
| Wideband Radio Communication Tester | ROHDE & SCHWARZ | CMW500        | 161997              | 2024/10/25 | 2025/10/24 |
| MXG Vector Signal Generator         | Agilent         | N5182A        | MY46240163          | 2024/10/25 | 2025/10/24 |
| E-Series Avg. Power Sensor          | KEYSIGHT        | E9300A        | MY55050017          | 2025/04/02 | 2026/04/01 |
| EPM Series Power Meter              | KEYSIGHT        | E4418B        | MY41293435          | 2025/04/02 | 2026/04/01 |
| MXA Signal Analyzer                 | KEYSIGHT        | N9020A        | MY54410409          | 2024/10/25 | 2025/10/24 |
| Broadband Preamplifier              | Schwarzbeck     | BBV9718D      | 00008               | 2024/09/24 | 2025/09/23 |
| Coupler                             | MERRIMAC        | CWM-10R-10.8G | LOT-83391           | N/A        | N/A        |
| 750MHz Validation Dipole            | MVG             | SID750        | 07/22 DIP 0G750-655 | 2025/05/26 | 2028/05/25 |
| 835MHz Validation Dipole            | MVG             | SID835        | 07/22 DIP 0G835-656 | 2025/05/26 | 2028/05/25 |
| 1800MHz Validation Dipole           | MVG             | SID1800       | 07/22 DIP 1G800-657 | 2025/05/26 | 2028/05/25 |
| 1900MHz Validation Dipole           | MVG             | SID1900       | 07/22 DIP 1G900-658 | 2025/05/26 | 2028/05/25 |

|                                   |         |         |                     |            |            |
|-----------------------------------|---------|---------|---------------------|------------|------------|
| 2450MHz Validation Dipole         | MVG     | SID2450 | 07/22 DIP 2G450-662 | 2025/05/26 | 2028/05/25 |
| 2600MHz Validation Dipole         | MVG     | SID2600 | 07/22 DIP 2G600-663 | 2025/05/26 | 2028/05/25 |
| 5200MHz-5800MHz Validation Dipole | MVG     | SID5000 | 07/22 DIP5G000-670  | 2025/05/26 | 2028/05/25 |
| LIMESAR Dielectric Probe          | MVG     | SCLMP   | 06/22 OCPG88        | 2025/02/05 | 2026/02/04 |
| ENA Series Network Analyzer       | Agilent | E5071B  | MY42301221          | 2024/10/25 | 2025/10/24 |
| Thermometer                       | Riters  | DT-232  | 21A11               | 2025/04/02 | 2026/04/01 |
| Antenna network emulator          | MVG     | ANTA 74 | 07/22 ANTA 74       | N/A        | N/A        |
| SAM Phantom                       | MVG     | SAM     | 07/22 SAM149        | N/A        | N/A        |
| Mobile Phone Positioning System   | MVG     | MSH 118 | 07/22 MSH 118       | N/A        | N/A        |
| Mechanical Calibration Kit        | PNA     | N/A     | N/A                 | 2024/10/25 | 2025/10/24 |
| Open SAR test software            | MVG     | N/A     | V5.3.5              | N/A        | N/A        |

Note: For dipole antennas, BTF has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

## ANNEX A Simulating Liquid Verification Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

| Dielectric performance of tissue simulating liquid |              |          |               |          |                        |                    |       |           |           |
|----------------------------------------------------|--------------|----------|---------------|----------|------------------------|--------------------|-------|-----------|-----------|
| Frequency (MHz)                                    | $\epsilon_r$ |          | $\sigma(s/m)$ |          | Delta ( $\epsilon_r$ ) | Delta ( $\sigma$ ) | Limit | Temp (°C) | Date      |
|                                                    | Target       | Measured | Target        | Measured |                        |                    |       |           |           |
| 750                                                | 41.90        | 41.46    | 0.89          | 0.88     | -1.05%                 | -1.12%             | ±5%   | 22.1      | 09/9/2025 |
| 835                                                | 41.50        | 41.21    | 0.90          | 0.91     | -0.70%                 | 1.11%              | ±5%   | 21.4      | 11/9/2025 |
| 1800                                               | 40.00        | 40.17    | 1.40          | 1.35     | 0.43%                  | -3.57%             | ±5%   | 21.7      | 13/9/2025 |
| 1900                                               | 40.00        | 40.16    | 1.40          | 1.38     | 0.40%                  | -1.43%             | ±5%   | 20.9      | 15/9/2025 |
| 2450                                               | 39.20        | 38.82    | 1.80          | 1.78     | -0.97%                 | -1.11%             | ±5%   | 21.8      | 16/9/2025 |
| 2600                                               | 39.00        | 38.42    | 1.96          | 1.92     | -1.49%                 | -2.04%             | ±5%   | 21.5      | 17/9/2025 |
| 5200                                               | 36.00        | 36.84    | 4.66          | 4.58     | 2.33%                  | -1.72%             | ±5%   | 21.7      | 18/9/2025 |
| 5400                                               | 35.80        | 35.95    | 4.86          | 4.73     | 0.42%                  | -2.67%             | ±5%   | 21.7      | 18/9/2025 |
| 5600                                               | 35.50        | 35.76    | 5.07          | 5.24     | 0.73%                  | 3.35%              | ±5%   | 21.6      | 19/9/2025 |
| 5800                                               | 35.30        | 35.61    | 5.27          | 5.38     | 0.88%                  | 2.09%              | ±5%   | 21.6      | 19/9/2025 |

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

## ANNEX B System Check Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 % (for 10 g).

| Frequency (MHz) | Input Power (mW) | 10g SAR (W/Kg) | 1g SAR (W/Kg) | 10g SAR 1W input power normalized (W/Kg) | 1g SAR 1W input power normalized (W/Kg) | 10g SAR Standard target (1W) (W/Kg) | 1g SAR Standard target (1W) (W/Kg) | 10g SAR Deviation | 1g SAR Deviation |
|-----------------|------------------|----------------|---------------|------------------------------------------|-----------------------------------------|-------------------------------------|------------------------------------|-------------------|------------------|
| 750             | 100              | 0.565          | 0.854         | 5.65                                     | 8.54                                    | 5.55                                | 8.41                               | 1.80%             | 1.55%            |
| 835             | 100              | 0.660          | 1.000         | 6.60                                     | 10.00                                   | 6.12                                | 9.46                               | 7.84%             | 5.71%            |
| 1800            | 100              | 2.027          | 3.848         | 20.27                                    | 38.48                                   | 19.83                               | 37.93                              | 2.22%             | 1.45%            |
| 1900            | 100              | 2.191          | 4.152         | 21.91                                    | 41.52                                   | 20.82                               | 40.29                              | 5.24%             | 3.05%            |
| 2450            | 100              | 2.338          | 4.951         | 23.38                                    | 49.51                                   | 24.55                               | 52.72                              | -4.77%            | -6.09%           |
| 2600            | 100              | 2.611          | 5.589         | 26.11                                    | 55.89                                   | 24.43                               | 53.76                              | 6.88%             | 3.96%            |
| 5200            | 100              | 2.483          | 8.315         | 24.83                                    | 83.15                                   | 22.78                               | 78.16                              | 9.00%             | 6.38%            |
| 5400            | 100              | 2.408          | 7.975         | 24.08                                    | 79.75                                   | 22.55                               | 78.64                              | 6.78%             | 1.41%            |
| 5600            | 100              | 2.336          | 7.895         | 23.36                                    | 78.95                                   | 23.95                               | 82.72                              | -2.46%            | -4.56%           |
| 5800            | 100              | 2.262          | 7.696         | 22.62                                    | 76.96                                   | 22.71                               | 78.32                              | -0.40%            | -1.74%           |

### System Performance Check Data (750 MHz)

#### System check at 750 MHz

Date of measurement: 9/9/2025

#### A. Experimental conditions.


|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | CW750                                   |
| Channels/Frequency | Higher                                  |
| Signal             | CW                                      |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 750.000 |
| Relative permittivity (real part)      | 41.461  |
| Relative permittivity (imaginary part) | 21.342  |
| Conductivity (S/m)                     | 0.882   |

#### C. SAR Surface and Volume

|             |            |
|-------------|------------|
| SURFACE SAR | VOLUME SAR |
|-------------|------------|




Maximum location: X=-1.00, Y=0.00 ; SAR Peak: 1.20 W/kg

### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.565     |
| SAR 1g (W/Kg)                                         | 0.854     |
| Variation (%)                                         | 3.190     |
| Horizontal validation criteria: minimum distance (mm) | 22.627417 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 68.958728 |

### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 1.207 | 0.887 | 0.612 | 0.430 | 0.311 | 0.222 | 0.162 |



### E. 3D Image



## System Performance Check Data (835 MHz)

### System check at 835 MHz

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Dipole                                  |
| Band               | CW835                                   |
| Channels/Frequency | Middle                                  |
| Signal             | CW                                      |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 835.000 |
| Relative permittivity (real part)      | 41.213  |
| Relative permittivity (imaginary part) | 19.432  |
| Conductivity (S/m)                     | 0.912   |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.39 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.660     |
| SAR 1g (W/Kg)                                         | 1.000     |
| Variation (%)                                         | -1.670    |
| Horizontal validation criteria: minimum distance (mm) | 22.627417 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 69.263296 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 1.389 | 1.028 | 0.712 | 0.503 | 0.362 | 0.261 | 0.190 |



## E. 3D Image



## System Performance Check Data (1800 MHz)

### System check at 1800 MHz

Date of measurement: 13/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.20                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Dipole                                  |
| Band               | CW1800                                  |
| Channels/Frequency | Middle                                  |
| Signal             | CW                                      |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1800.000 |
| Relative permittivity (real part)      | 40.173   |
| Relative permittivity (imaginary part) | 14.642   |
| Conductivity (S/m)                     | 1.354    |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 6.36 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 2.027     |
| SAR 1g (W/Kg)                                         | 3.848     |
| Variation (%)                                         | -1.320    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 56.827614 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 6.423 | 4.133 | 2.348 | 1.396 | 0.842 | 0.518 | 0.321 |



## E. 3D Image



## System Performance Check Data (1900 MHz)

### System check at 1900 MHz

Date of measurement: 15/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Dipole                                  |
| Band               | CW1900                                  |
| Channels/Frequency | Middle                                  |
| Signal             | CW                                      |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1900.000 |
| Relative permittivity (real part)      | 40.162   |
| Relative permittivity (imaginary part) | 13.645   |
| Conductivity (S/m)                     | 1.384    |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 6.68 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 2.191     |
| SAR 1g (W/Kg)                                         | 4.152     |
| Variation (%)                                         | -2.980    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 57.902583 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 6.742 | 4.396 | 2.545 | 1.545 | 0.937 | 0.573 | 0.353 |



## E. 3D Image



## System Performance Check Data (2450 MHz)

### System check at 2450 MHz

Date of measurement: 16/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.40                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Dipole                                  |
| Band               | CW2450                                  |
| Channels/Frequency | Higher                                  |
| Signal             | CW                                      |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2450.000 |
| Relative permittivity (real part)      | 38.823   |
| Relative permittivity (imaginary part) | 13.645   |
| Conductivity (S/m)                     | 1.782    |

#### C. SAR Surface and Volume




Maximum location: X=-1.00, Y=0.00 ; SAR Peak: 8.52 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 2.338     |
| SAR 1g (W/Kg)                                         | 4.951     |
| Variation (%)                                         | -1.040    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 53.023333 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 8.575 | 5.321 | 2.821 | 1.521 | 0.823 | 0.447 | 0.247 |



## F. 3D Image



## System Performance Check Data (2600 MHz)

### System check at 2600 MHz

Date of measurement: 17/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.27                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Dipole                                  |
| Band               | CW2600                                  |
| Channels/Frequency | Higher                                  |
| Signal             | CW                                      |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2600.000 |
| Relative permittivity (real part)      | 38.423   |
| Relative permittivity (imaginary part) | 12.352   |
| Conductivity (S/m)                     | 1.921    |

#### C. SAR Surface and Volume




Maximum location: X=-2.00, Y=1.00 ; SAR Peak: 9.81 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 2.611     |
| SAR 1g (W/Kg)                                         | 5.589     |
| Variation (%)                                         | -2.070    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 52.138434 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 9.885 | 6.084 | 3.172 | 1.655 | 0.869 | 0.460 | 0.247 |



## F. 3D Image



## System Performance Check Data (5200 MHz)

### System check at 5200 MHz

Date of measurement: 18/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.18                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Validation plane                         |
| Device Position    | Dipole                                   |
| Band               | CW5200                                   |
| Channels/Frequency | Middle                                   |
| Signal             | CW                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5200.000 |
| Relative permittivity (real part)      | 36.843   |
| Relative permittivity (imaginary part) | 16.422   |
| Conductivity (S/m)                     | 4.584    |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 25.70 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 2.483     |
| SAR 1g (W/Kg)                                         | 8.315     |
| Variation (%)                                         | 1.060     |
| Horizontal validation criteria: minimum distance (mm) | 8.000000  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 54.746732 |

#### E. Z Axis Scan

|            |        |        |       |       |       |       |       |       |       |       |       |       |
|------------|--------|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00   | 2.00   | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 24.047 | 14.812 | 8.109 | 4.552 | 2.533 | 1.422 | 0.787 | 0.426 | 0.240 | 0.135 | 0.067 | 0.041 |



## E. 3D Image



## System Performance Check Data (5400 MHz)

### System check at 5400 MHz

Date of measurement: 18/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.14                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Validation plane                         |
| Device Position    | Dipole                                   |
| Band               | CW5400                                   |
| Channels/Frequency | Middle                                   |
| Signal             | CW                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5400.000 |
| Relative permittivity (real part)      | 35.954   |
| Relative permittivity (imaginary part) | 16.521   |
| Conductivity (S/m)                     | 4.733    |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 24.75 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 2.408     |
| SAR 1g (W/Kg)                                         | 7.975     |
| Variation (%)                                         | -3.540    |
| Horizontal validation criteria: minimum distance (mm) | 8.000000  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 53.730409 |

#### E. Z Axis Scan

|            |        |        |       |       |       |       |       |       |       |       |       |       |
|------------|--------|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00   | 2.00   | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 23.620 | 14.402 | 7.738 | 4.235 | 2.299 | 1.275 | 0.694 | 0.361 | 0.205 | 0.105 | 0.064 | 0.065 |



## E. 3D Image



## System Performance Check Data (5600 MHz)

### System check at 5600 MHz

Date of measurement: 19/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.12                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Validation plane                         |
| Device Position    | Dipole                                   |
| Band               | CW5600                                   |
| Channels/Frequency | Middle                                   |
| Signal             | CW                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5600.000 |
| Relative permittivity (real part)      | 35.763   |
| Relative permittivity (imaginary part) | 16.845   |
| Conductivity (S/m)                     | 5.244    |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 25.79 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 2.336     |
| SAR 1g (W/Kg)                                         | 7.895     |
| Variation (%)                                         | -2.390    |
| Horizontal validation criteria: minimum distance (mm) | 8.000000  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 51.802819 |

#### E. Z Axis Scan

|            |        |        |       |       |       |       |       |       |       |       |       |       |
|------------|--------|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00   | 2.00   | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 24.385 | 14.617 | 7.572 | 3.993 | 2.095 | 1.095 | 0.564 | 0.284 | 0.145 | 0.062 | 0.041 | 0.020 |



## E. 3D Image



## System Performance Check Data (5800 MHz)

### System check at 5800 MHz

Date of measurement: 19/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.11                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Validation plane                         |
| Device Position    | Dipole                                   |
| Band               | CW5800                                   |
| Channels/Frequency | Middle                                   |
| Signal             | CW                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5800.000 |
| Relative permittivity (real part)      | 35.613   |
| Relative permittivity (imaginary part) | 16.347   |
| Conductivity (S/m)                     | 5.381    |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 25.40 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 2.262     |
| SAR 1g (W/Kg)                                         | 7.696     |
| Variation (%)                                         | -4.380    |
| Horizontal validation criteria: minimum distance (mm) | 8.000000  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 50.696099 |

#### E. Z Axis Scan

|            |        |        |       |       |       |       |       |       |       |       |       |       |
|------------|--------|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00   | 2.00   | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 24.141 | 14.252 | 7.225 | 3.626 | 1.848 | 0.939 | 0.490 | 0.245 | 0.108 | 0.065 | 0.027 | 0.016 |



## E. 3D Image



## ANNEX C Test Data

1-Head with front position in dist. 0mm on Channel 251 in GSM850 voice

### SAR Measurement at GSM850 (Cheek, Right)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | GSM850                                  |
| Channels/Frequency | Higher (251)/ frequency 848.800 Mhz     |
| Signal             | TDMA (GSM)                              |
| Modulation         | GMSK                                    |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 848.800 |
| Relative permittivity (real part)      | 41.198  |
| Relative permittivity (imaginary part) | 19.364  |
| Conductivity (S/m)                     | 0.918   |

#### C. SAR Surface and Volume




Maximum location: X=-48.00, Y=-47.00 ; SAR Peak: 0.06 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.034     |
| SAR 1g (W/Kg)                                         | 0.049     |
| Variation (%)                                         | -0.660    |
| Horizontal validation criteria: minimum distance (mm) | 19.140795 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 65.384615 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.076 | 0.052 | 0.034 | 0.038 | 0.021 | 0.020 | 0.012 |



## F. 3D Image



## 2-Body with back position in dist. 10mm on Channel 251 in GPRS850+2slots

### SAR Measurement at GSM850 (Body, Validation Plane)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | GSM850                                  |
| Channels/Frequency | Higher (251)/ frequency 848.800 Mhz     |
| Signal             | TDMA (GSM)                              |
| Modulation         | GMSK                                    |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 848.800 |
| Relative permittivity (real part)      | 41.198  |
| Relative permittivity (imaginary part) | 19.364  |
| Conductivity (S/m)                     | 0.918   |

#### C. SAR Surface and Volume




#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.025     |
| SAR 1g (W/Kg)                                         | 0.040     |
| Variation (%)                                         | -0.270    |
| Horizontal validation criteria: minimum distance (mm) | 28.844410 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 66.514332 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.059 | 0.042 | 0.028 | 0.020 | 0.014 | 0.012 | 0.007 |



## F. 3D Image



### 3-Head with front position in dist. 0mm on Channel 512 in GSM1900 voice

#### SAR Measurement at GSM1900 (Cheek, Right)

Date of measurement: 15/9/2025


##### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | GSM1900                                 |
| Channels/Frequency | Lower (512)/ frequency 1850.200 Mhz     |
| Signal             | TDMA (GSM)                              |
| Modulation         | GMSK                                    |

##### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1850.200 |
| Relative permittivity (real part)      | 40.168   |
| Relative permittivity (imaginary part) | 14.144   |
| Conductivity (S/m)                     | 1.369    |

##### C. SAR Surface and Volume




Maximum location: X=-38.00, Y=1.00 ; SAR Peak: 0.35 W/kg

##### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.117     |
| SAR 1g (W/Kg)                                         | 0.213     |
| Variation (%)                                         | -3.470    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 62.538723 |

##### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.327 | 0.227 | 0.142 | 0.083 | 0.050 | 0.029 | 0.014 |



## E. 3D Image



## 4-Body with front position in dist. 10mm on Channel 512 in GPRS1900+2slots

### SAR Measurement at GSM1900 (Body, Validation Plane)

Date of measurement: 15/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | GSM1900                                 |
| Channels/Frequency | Lower (512)/ frequency 1850.200 Mhz     |
| Signal             | TDMA (GSM)                              |
| Modulation         | GMSK                                    |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1850.200 |
| Relative permittivity (real part)      | 40.168   |
| Relative permittivity (imaginary part) | 14.144   |
| Conductivity (S/m)                     | 1.369    |

#### C. SAR Surface and Volume




Maximum location: X=31.00, Y=2.00 ; SAR Peak: 0.07 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.025     |
| SAR 1g (W/Kg)                                         | 0.044     |
| Variation (%)                                         | -2.490    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 61.601819 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.066 | 0.048 | 0.030 | 0.019 | 0.008 | 0.005 | 0.002 |



## E. 3D Image



## 5-Head with front position in dist. 0mm on Channel 9262 in WCDMA Band 2

### SAR Measurement at Band 2 (1900) (Cheek, Right)

Date of measurement: 15/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | Band 2 (1900)                           |
| Channels/Frequency | Lower (9262)/ frequency 1852.400 Mhz    |
| Signal             | WCDMA                                   |
| Mode               | Release 99                              |
| Connection Type    | RMC, 12.2 kbps                          |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1852.400 |
| Relative permittivity (real part)      | 40.167   |
| Relative permittivity (imaginary part) | 14.120   |
| Conductivity (S/m)                     | 1.370    |

#### C. SAR Surface and Volume




Maximum location: X=-23.00, Y=11.00 ; SAR Peak: 0.81 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.304     |
| SAR 1g (W/Kg)                                         | 0.523     |
| Variation (%)                                         | -2.880    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 63.709213 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.776 | 0.548 | 0.349 | 0.219 | 0.136 | 0.085 | 0.051 |



## E. 3D Image



## 6-Body with front position in dist. 10mm on Channel 9262 in WCDMA Band 2

### SAR Measurement at Band 2 (1900) (Body, Validation Plane)

Date of measurement: 15/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | Band 2 (1900)                           |
| Channels/Frequency | Lower (9262)/ frequency 1852.400 Mhz    |
| Signal             | WCDMA                                   |
| Mode               | Release 99                              |
| Connection Type    | RMC, 12.2 kbps                          |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1852.400 |
| Relative permittivity (real part)      | 40.167   |
| Relative permittivity (imaginary part) | 14.120   |
| Conductivity (S/m)                     | 1.370    |

#### C. SAR Surface and Volume




Maximum location: X=26.00, Y=5.00 ; SAR Peak: 0.32 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.115     |
| SAR 1g (W/Kg)                                         | 0.203     |
| Variation (%)                                         | -2.970    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 60.135698 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.313 | 0.214 | 0.129 | 0.082 | 0.045 | 0.026 | 0.015 |



## F. 3D Image



## 7-Head with front position in dist. 0mm on Channel 1513 in WCDMA Band 4

### SAR Measurement at Band 4 (1700) (Cheek, Right)

Date of measurement: 13/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.20                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | Band 4 (1700)                           |
| Channels/Frequency | Higher (1513)/ frequency 1752.600 Mhz   |
| Signal             | WCDMA                                   |
| Mode               | Release 99                              |
| Connection Type    | RMC, 12.2 kbps                          |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1752.600 |
| Relative permittivity (real part)      | 40.178   |
| Relative permittivity (imaginary part) | 15.115   |
| Conductivity (S/m)                     | 1.340    |

#### C. SAR Surface and Volume




Maximum location: X=-22.00, Y=2.00 ; SAR Peak: 0.86 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.305     |
| SAR 1g (W/Kg)                                         | 0.540     |
| Variation (%)                                         | -2.030    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 62.411831 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.817 | 0.571 | 0.357 | 0.218 | 0.134 | 0.079 | 0.050 |



## E. 3D Image



## 8-Body with back position in dist. 10mm on Channel 1513 in WCDMA Band 4

### SAR Measurement at Band 4 (1700) (Body, Validation Plane)

Date of measurement: 13/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.20                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | Band 4 (1700)                           |
| Channels/Frequency | Higher (1513)/ frequency 1752.600 Mhz   |
| Signal             | WCDMA                                   |
| Mode               | Release 99                              |
| Connection Type    | RMC, 12.2 kbps                          |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1752.600 |
| Relative permittivity (real part)      | 40.178   |
| Relative permittivity (imaginary part) | 15.115   |
| Conductivity (S/m)                     | 1.340    |

#### C. SAR Surface and Volume




Maximum location: X=25.00, Y=1.00 ; SAR Peak: 0.27 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.104     |
| SAR 1g (W/Kg)                                         | 0.179     |
| Variation (%)                                         | -3.330    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 64.949318 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.257 | 0.190 | 0.124 | 0.077 | 0.044 | 0.027 | 0.017 |



## E. 3D Image



## 9-Head with front position in dist. 0mm on Channel 4183 in WCDMA Band 5

### SAR Measurement at Band 5 (850) (Cheek, Right)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | Band 5 (850)                            |
| Channels/Frequency | Middle (4183)/ frequency 836.600 Mhz    |
| Signal             | WCDMA                                   |
| Mode               | Release 99                              |
| Connection Type    | RMC, 12.2 kbps                          |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 836.600 |
| Relative permittivity (real part)      | 41.211  |
| Relative permittivity (imaginary part) | 19.424  |
| Conductivity (S/m)                     | 0.913   |

#### C. SAR Surface and Volume




Maximum location: X=-49.00, Y=-47.00 ; SAR Peak: 0.17 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.106     |
| SAR 1g (W/Kg)                                         | 0.138     |
| Variation (%)                                         | -2.390    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 83.754698 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.166 | 0.140 | 0.117 | 0.098 | 0.083 | 0.070 | 0.054 |



## E. 3D Image



## 10-Body with back position in dist. 10mm on Channel 4183 in WCDMA Band 5

### SAR Measurement at Band 5 (850) (Body, Validation Plane)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | Band 5 (850)                            |
| Channels/Frequency | Middle (4183)/ frequency 836.600 Mhz    |
| Signal             | WCDMA                                   |
| Mode               | Release 99                              |
| Connection Type    | RMC, 12.2 kbps                          |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 836.600 |
| Relative permittivity (real part)      | 41.211  |
| Relative permittivity (imaginary part) | 19.424  |
| Conductivity (S/m)                     | 0.913   |

#### C. SAR Surface and Volume




#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.112     |
| SAR 1g (W/Kg)                                         | 0.161     |
| Variation (%)                                         | -0.940    |
| Horizontal validation criteria: minimum distance (mm) | 22.627417 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 71.895384 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.218 | 0.167 | 0.120 | 0.089 | 0.067 | 0.048 | 0.037 |



## F. 3D Image



## 11-Head with front position in dist. 10mm on Channel 18700 in LTE band 2

### SAR Measurement at LTE band 2 (Cheek, Right)

Date of measurement: 15/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 2                              |
| Channels/Frequency | Lower (18700)/ frequency 1860.000 Mhz   |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1860.090 |
| Relative permittivity (real part)      | 40.166   |
| Relative permittivity (imaginary part) | 14.043   |
| Conductivity (S/m)                     | 1.372    |

#### C. SAR Surface and Volume




Maximum location: X=-25.00, Y=-7.00 ; SAR Peak: 1.06 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.378     |
| SAR 1g (W/Kg)                                         | 0.667     |
| Variation (%)                                         | -0.230    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 62.178669 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 1.015 | 0.704 | 0.438 | 0.264 | 0.163 | 0.096 | 0.058 |



## E. 3D Image



## 12-Body with front position in dist. 10mm on Channel 18700 in LTE band 2

### SAR Measurement at LTE band 2 (Body, Validation Plane)

Date of measurement: 15/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 2                              |
| Channels/Frequency | Lower (18700)/ frequency 1860.000 Mhz   |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1860.090 |
| Relative permittivity (real part)      | 40.166   |
| Relative permittivity (imaginary part) | 14.043   |
| Conductivity (S/m)                     | 1.372    |

#### C. SAR Surface and Volume




#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.166     |
| SAR 1g (W/Kg)                                         | 0.284     |
| Variation (%)                                         | -1.710    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 61.300251 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.434 | 0.299 | 0.183 | 0.115 | 0.066 | 0.043 | 0.024 |



## E. 3D Image



## 13-Head with front position in dist. 0mm on Channel 20175 in LTE band 4

### SAR Measurement at LTE band 4 (Cheek, Right)

Date of measurement: 13/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.20                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 4                              |
| Channels/Frequency | Middle (20175)/ frequency 1732.500 Mhz  |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1732.590 |
| Relative permittivity (real part)      | 40.180   |
| Relative permittivity (imaginary part) | 15.314   |
| Conductivity (S/m)                     | 1.334    |

#### C. SAR Surface and Volume



Maximum location: X=-24.00, Y=-7.00 ; SAR Peak: 0.78 W/kg

#### D. SAR 1g & 10g

|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.278     |
| SAR 1g (W/Kg)                                         | 0.487     |
| Variation (%)                                         | -3.550    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 62.619941 |

#### E. Z Axis Scan


|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.737 | 0.513 | 0.321 | 0.197 | 0.125 | 0.074 | 0.047 |

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


Page 103 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China



## F. 3D Image



## 14-Body with front position in dist. 10mm on Channel 20175 in LTE band 4

### SAR Measurement at LTE band 4 (Body, Validation Plane)

Date of measurement: 13/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.20                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 4                              |
| Channels/Frequency | Middle (20175)/ frequency 1732.500 Mhz  |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1732.590 |
| Relative permittivity (real part)      | 40.180   |
| Relative permittivity (imaginary part) | 15.314   |
| Conductivity (S/m)                     | 1.334    |

#### C. SAR Surface and Volume




Maximum location: X=25.00, Y=9.00 ; SAR Peak: 0.29 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.112     |
| SAR 1g (W/Kg)                                         | 0.184     |
| Variation (%)                                         | 3.520     |
| Horizontal validation criteria: minimum distance (mm) | 22.627417 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 64.584383 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.262 | 0.189 | 0.122 | 0.082 | 0.050 | 0.030 | 0.020 |



## E. 3D Image



## 15-Head with front position in dist. 0mm on Channel 20450 in LTE band 5

### SAR Measurement at LTE band 5 (Cheek, Right)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 5                              |
| Channels/Frequency | Lower (20450)/ frequency 829.000 Mhz    |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 829.090 |
| Relative permittivity (real part)      | 41.219  |
| Relative permittivity (imaginary part) | 19.461  |
| Conductivity (S/m)                     | 0.909   |

#### C. SAR Surface and Volume




Maximum location: X=-48.00, Y=-62.00 ; SAR Peak: 0.21 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.134     |
| SAR 1g (W/Kg)                                         | 0.173     |
| Variation (%)                                         | 0.850     |
| Horizontal validation criteria: minimum distance (mm) | 22.627417 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 84.595711 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.203 | 0.180 | 0.153 | 0.129 | 0.105 | 0.086 | 0.069 |



## F. 3D Image



## 16-Body with back position in dist. 10mm on Channel 20450 in LTE band 5

### SAR Measurement at LTE band 5 (Body, Validation Plane)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 5                              |
| Channels/Frequency | Lower (20450)/ frequency 829.000 Mhz    |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 829.090 |
| Relative permittivity (real part)      | 41.219  |
| Relative permittivity (imaginary part) | 19.461  |
| Conductivity (S/m)                     | 0.909   |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=-33.00 ; SAR Peak: 0.27 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.139     |
| SAR 1g (W/Kg)                                         | 0.201     |
| Variation (%)                                         | -3.900    |
| Horizontal validation criteria: minimum distance (mm) | 22.627417 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 72.154862 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.272 | 0.207 | 0.149 | 0.110 | 0.082 | 0.058 | 0.043 |



## F. 3D Image



## 17-Head with front position in dist. 0mm on Channel 23060 in LTE band 12

### SAR Measurement at LTE band 12 (Cheek, Right)

Date of measurement: 9/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 12                             |
| Channels/Frequency | Lower (23060)/ frequency 704.000 Mhz    |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |            |
|----------------------------------------|------------|
| Middle TX Frequency (MHz)              | 704.090    |
| Relative permittivity (real part)      | 79.577465% |
| Relative permittivity (imaginary part) | 79.577465% |
| Conductivity (S/m)                     | 79.577465% |

#### C. SAR Surface and Volume




Maximum location: X=-48.00, Y=-56.00 ; SAR Peak: 0.16 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.096     |
| SAR 1g (W/Kg)                                         | 0.128     |
| Variation (%)                                         | -1.980    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 79.577465 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.149 | 0.142 | 0.113 | 0.097 | 0.082 | 0.065 | 0.053 |



## E. 3D Image



## 18-Body with back position in dist. 10mm on Channel 23060 in LTE band 12

### SAR Measurement at LTE band 12 (Body, Validation Plane)

Date of measurement: 9/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 12                             |
| Channels/Frequency | Lower (23060)/ frequency 704.000 Mhz    |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 704.090 |
| Relative permittivity (real part)      | 41.595  |
| Relative permittivity (imaginary part) | 22.374  |
| Conductivity (S/m)                     | 0.866   |

#### C. SAR Surface and Volume




Maximum location: X=0.00, Y=-48.00 ; SAR Peak: 0.18 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.096     |
| SAR 1g (W/Kg)                                         | 0.135     |
| Variation (%)                                         | -2.000    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 74.577307 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.177 | 0.140 | 0.105 | 0.077 | 0.057 | 0.043 | 0.032 |



## E. 3D Image



## 19-Head with front position in dist. 0mm on Channel 23230 in LTE band 13

### SAR Measurement at LTE band 13 (Cheek, Right)

Date of measurement: 9/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 13                             |
| Channels/Frequency | Middle (23230)/ frequency 782.000 Mhz   |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 782.090 |
| Relative permittivity (real part)      | 41.367  |
| Relative permittivity (imaginary part) | 20.621  |
| Conductivity (S/m)                     | 0.893   |

#### C. SAR Surface and Volume




Maximum location: X=-48.00, Y=-55.00 ; SAR Peak: 0.13 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.085     |
| SAR 1g (W/Kg)                                         | 0.109     |
| Variation (%)                                         | -0.510    |
| Horizontal validation criteria: minimum distance (mm) | 22.627417 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 78.048780 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.125 | 0.123 | 0.096 | 0.078 | 0.064 | 0.050 | 0.043 |



## E. 3D Image



## 20-Body with back position in dist. 10mm on Channel 23230 in LTE band 13

### SAR Measurement at LTE band 13 (Body, Validation Plane)

Date of measurement: 9/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 13                             |
| Channels/Frequency | Middle (23230)/ frequency 782.000 Mhz   |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 782.090 |
| Relative permittivity (real part)      | 41.367  |
| Relative permittivity (imaginary part) | 20.621  |
| Conductivity (S/m)                     | 0.893   |

#### C. SAR Surface and Volume




#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.084     |
| SAR 1g (W/Kg)                                         | 0.121     |
| Variation (%)                                         | 2.810     |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 73.525979 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.160 | 0.125 | 0.092 | 0.068 | 0.050 | 0.037 | 0.028 |



## E. 3D Image



## 21-Head with front position in dist. 0mm on Channel 23780 in LTE band 17

### SAR Measurement at LTE band 17 (Cheek, Right)

Date of measurement: 9/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 17                             |
| Channels/Frequency | Lower (23780)/ frequency 709.000 Mhz    |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 709.090 |
| Relative permittivity (real part)      | 41.580  |
| Relative permittivity (imaginary part) | 22.261  |
| Conductivity (S/m)                     | 0.868   |

#### C. SAR Surface and Volume




Maximum location: X=-49.00, Y=-48.00 ; SAR Peak: 0.18 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.111     |
| SAR 1g (W/Kg)                                         | 0.142     |
| Variation (%)                                         | -3.990    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 72.535211 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.178 | 0.142 | 0.103 | 0.106 | 0.100 | 0.070 | 0.055 |



## E. 3D Image



## 22-Body with front position in dist. 10mm on Channel 23780 in LTE band 17

### SAR Measurement at LTE band 17 (Body, Validation Plane)

Date of measurement: 9/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 17                             |
| Channels/Frequency | Lower (23780)/ frequency 709.000 Mhz    |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 709.090 |
| Relative permittivity (real part)      | 41.580  |
| Relative permittivity (imaginary part) | 22.261  |
| Conductivity (S/m)                     | 0.868   |

#### C. SAR Surface and Volume



Maximum location: X=1.00, Y=-51.00 ; SAR Peak: 0.18 W/kg

#### D. SAR 1g & 10g

|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.095     |
| SAR 1g (W/Kg)                                         | 0.136     |
| Variation (%)                                         | 2.370     |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 73.745181 |

#### E. Z Axis Scan


|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.179 | 0.142 | 0.104 | 0.078 | 0.058 | 0.042 | 0.033 |

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


Page 121 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China



## F. 3D Image



## 23-Head with front position in dist. 0mm on Channel 26140 in LTE band 25

### SAR Measurement at LTE band 25 (Cheek, Right)

Date of measurement: 15/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 25                             |
| Channels/Frequency | Lower (26140)/ frequency 1860.000 Mhz   |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1860.090 |
| Relative permittivity (real part)      | 40.166   |
| Relative permittivity (imaginary part) | 14.043   |
| Conductivity (S/m)                     | 1.372    |

#### C. SAR Surface and Volume




Maximum location: X=-31.00, Y=0.00 ; SAR Peak: 0.98 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.372     |
| SAR 1g (W/Kg)                                         | 0.639     |
| Variation (%)                                         | -1.910    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 63.767020 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.951 | 0.674 | 0.430 | 0.272 | 0.170 | 0.107 | 0.068 |



## E. 3D Image



## 24-Body with front position in dist. 10mm on Channel 26140 in LTE band 25

### SAR Measurement at LTE band 25 (Body, Validation Plane)

Date of measurement: 15/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.31                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 25                             |
| Channels/Frequency | Lower (26140)/ frequency 1860.000 Mhz   |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1860.090 |
| Relative permittivity (real part)      | 40.166   |
| Relative permittivity (imaginary part) | 14.043   |
| Conductivity (S/m)                     | 1.372    |

#### C. SAR Surface and Volume




#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.156     |
| SAR 1g (W/Kg)                                         | 0.267     |
| Variation (%)                                         | -4.030    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 61.697612 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.406 | 0.280 | 0.173 | 0.109 | 0.064 | 0.037 | 0.021 |



## F. 3D Image



## 25-Head with front position in dist. 0mm on Channel 26740 in LTE band 26 Part 90

### SAR Measurement at LTE band 26 (Cheek, Right)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 26                             |
| Channels/Frequency | Lower (26740)/ frequency 819.000 Mhz    |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 819.090 |
| Relative permittivity (real part)      | 41.230  |
| Relative permittivity (imaginary part) | 19.511  |
| Conductivity (S/m)                     | 0.905   |

#### C. SAR Surface and Volume




Maximum location: X=-54.00, Y=-43.00 ; SAR Peak: 0.31 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.185     |
| SAR 1g (W/Kg)                                         | 0.245     |
| Variation (%)                                         | 2.720     |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 75.272727 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.290 | 0.275 | 0.207 | 0.165 | 0.130 | 0.103 | 0.086 |



## E. 3D Image



## 26-Body with front position in dist. 10mm on Channel 26740 in LTE band 26

### Part 90

### SAR Measurement at LTE band 26 (Body, Validation Plane)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 26                             |
| Channels/Frequency | Lower (26740)/ frequency 819.000 Mhz    |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 10 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 25                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 819.090 |
| Relative permittivity (real part)      | 41.230  |
| Relative permittivity (imaginary part) | 19.511  |
| Conductivity (S/m)                     | 0.905   |

#### C. SAR Surface and Volume




Maximum location: X=7.00, Y=-23.00 ; SAR Peak: 0.24 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.124     |
| SAR 1g (W/Kg)                                         | 0.179     |
| Variation (%)                                         | -3.300    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 72.687650 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.241 | 0.185 | 0.135 | 0.098 | 0.073 | 0.053 | 0.038 |



## F. 3D Image



## 27-Head with front position in dist. 0mm on Channel 26965 in LTE band 26 Part 22

### SAR Measurement at LTE band 26 (Cheek, Right)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 26                             |
| Channels/Frequency | Higher (26965)/ frequency 841.500 Mhz   |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 15 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 74                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 848.160 |
| Relative permittivity (real part)      | 41.199  |
| Relative permittivity (imaginary part) | 19.367  |
| Conductivity (S/m)                     | 0.918   |

#### C. SAR Surface and Volume



Maximum location: X=-53.00, Y=-45.00 ; SAR Peak: 0.32 W/kg

#### D. SAR 1g & 10g

|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.187     |
| SAR 1g (W/Kg)                                         | 0.251     |
| Variation (%)                                         | 2.420     |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 79.595898 |

#### E. Z Axis Scan


|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.309 | 0.260 | 0.207 | 0.170 | 0.131 | 0.106 | 0.084 |

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


Page 131 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China



## F. 3D Image



## 28-Body with back position in dist. 10mm on Channel 26965 in LTE band 26

### Part 22

### SAR Measurement at LTE band 26 (Body, Validation Plane)

Date of measurement: 11/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.15                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 26                             |
| Channels/Frequency | Higher (26965)/ frequency 841.500 Mhz   |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 15 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 74                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 848.160 |
| Relative permittivity (real part)      | 41.199  |
| Relative permittivity (imaginary part) | 19.367  |
| Conductivity (S/m)                     | 0.918   |

#### C. SAR Surface and Volume



Maximum location: X=9.00, Y=-47.00 ; SAR Peak: 0.21 W/kg

#### D. SAR 1g & 10g

|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.121     |
| SAR 1g (W/Kg)                                         | 0.159     |
| Variation (%)                                         | -2.290    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 79.241578 |

#### E. Z Axis Scan


|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.199 | 0.164 | 0.130 | 0.105 | 0.084 | 0.066 | 0.052 |

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


Page 133 of 177

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China



## F. 3D Image



## 29-Head with front position in dist. 0mm on Channel 37850 in LTE band 38

### SAR Measurement at LTE band 38 (Cheek, Right)

Date of measurement: 17/9/2025


#### A. Experimental conditions.

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Probe                          | 0125-EPGO-445                           |
| ConvF                          | 1.27                                    |
| Area Scan                      | dx=8mm dy=8mm, Complete                 |
| Zoom Scan                      | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom                        | Right head                              |
| Device Position                | Cheek                                   |
| Band                           | LTE band 38                             |
| Channels/Frequency             | Lower (37850)/ frequency 2580.000 Mhz   |
| Signal                         | LTE TDD                                 |
| Cell Bandwidth                 | 20 Mhz                                  |
| Modulation                     | SC-OFDM - QPSK                          |
| RB offset                      | 50                                      |
| RB size                        | 1                                       |
| Subframe configuration         | 0                                       |
| Special subframe configuration | 0                                       |
| Cyclic prefix                  | Normal                                  |
| Duty Cycle (%)                 | 0.61                                    |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2580.090 |
| Relative permittivity (real part)      | 38.476   |
| Relative permittivity (imaginary part) | 12.524   |
| Conductivity (S/m)                     | 1.903    |

#### C. SAR Surface and Volume




Maximum location: X=-40.00, Y=-7.00 ; SAR Peak: 0.16 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.045     |
| SAR 1g (W/Kg)                                         | 0.089     |
| Variation (%)                                         | -3.350    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 49.042441 |

### E. Z Axis Scan

| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|
| SAR (W/Kg) | 0.152 | 0.090 | 0.044 | 0.028 | 0.019 | 0.005 | 0.009 |



### F. 3D Image



## 30-Body with front position in dist. 10mm on Channel 37850 in LTE band 38

### SAR Measurement at LTE band 38 (Body, Validation Plane)

Date of measurement: 17/9/2025


#### A. Experimental conditions.

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Probe                          | 0125-EPGO-445                           |
| ConvF                          | 1.27                                    |
| Area Scan                      | dx=8mm dy=8mm, Complete                 |
| Zoom Scan                      | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom                        | Validation plane                        |
| Device Position                | Body                                    |
| Band                           | LTE band 38                             |
| Channels/Frequency             | Lower (37850)/ frequency 2580.000 Mhz   |
| Signal                         | LTE TDD                                 |
| Cell Bandwidth                 | 20 Mhz                                  |
| Modulation                     | SC-OFDM - QPSK                          |
| RB offset                      | 50                                      |
| RB size                        | 1                                       |
| Subframe configuration         | 0                                       |
| Special subframe configuration | 0                                       |
| Cyclic prefix                  | Normal                                  |
| Duty Cycle (%)                 | 0.61                                    |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2580.090 |
| Relative permittivity (real part)      | 38.476   |
| Relative permittivity (imaginary part) | 12.524   |
| Conductivity (S/m)                     | 1.903    |

#### C. SAR Surface and Volume




Maximum location: X=23.00, Y=15.00 ; SAR Peak: 0.23 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.063     |
| SAR 1g (W/Kg)                                         | 0.130     |
| Variation (%)                                         | -4.100    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 49.046270 |

### E. Z Axis Scan

| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|
| SAR (W/Kg) | 0.230 | 0.142 | 0.070 | 0.042 | 0.017 | 0.011 | 0.009 |



### F. 3D Image



## 31-Head with front position in dist. 0mm on Channel 41490 in LTE band 41

### SAR Measurement at LTE band 41 (Cheek, Right)

Date of measurement: 17/9/2025


#### A. Experimental conditions.

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Probe                          | 0125-EPGO-445                           |
| ConvF                          | 1.27                                    |
| Area Scan                      | dx=8mm dy=8mm, Complete                 |
| Zoom Scan                      | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom                        | Right head                              |
| Device Position                | Cheek                                   |
| Band                           | LTE band 41                             |
| Channels/Frequency             | Higher (41490)/ frequency 2680.000 Mhz  |
| Signal                         | LTE TDD                                 |
| Cell Bandwidth                 | 20 Mhz                                  |
| Modulation                     | SC-OFDM - QPSK                          |
| RB offset                      | 50                                      |
| RB size                        | 1                                       |
| Subframe configuration         | 0                                       |
| Special subframe configuration | 0                                       |
| Cyclic prefix                  | Normal                                  |
| Duty Cycle (%)                 | 0.61                                    |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2680.090 |
| Relative permittivity (real part)      | 38.209   |
| Relative permittivity (imaginary part) | 11.662   |
| Conductivity (S/m)                     | 1.995    |

#### C. SAR Surface and Volume




Maximum location: X=-41.00, Y=-6.00 ; SAR Peak: 0.27 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.070     |
| SAR 1g (W/Kg)                                         | 0.146     |
| Variation (%)                                         | -1.420    |
| Horizontal validation criteria: minimum distance (mm) | 17.313708 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 55.788694 |

### E. Z Axis Scan

| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|
| SAR (W/Kg) | 0.239 | 0.157 | 0.087 | 0.040 | 0.020 | 0.013 | 0.006 |



### F. 3D Image



## 32-Body with front position in dist. 10mm on Channel 41490 in LTE band 41

### SAR Measurement at LTE band 41 (Body, Validation Plane)

Date of measurement: 17/9/2025


#### A. Experimental conditions.

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Probe                          | 0125-EPGO-445                           |
| ConvF                          | 1.27                                    |
| Area Scan                      | dx=8mm dy=8mm, Complete                 |
| Zoom Scan                      | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom                        | Validation plane                        |
| Device Position                | Body                                    |
| Band                           | LTE band 41                             |
| Channels/Frequency             | Higher (41490)/ frequency 2680.000 Mhz  |
| Signal                         | LTE TDD                                 |
| Cell Bandwidth                 | 20 Mhz                                  |
| Modulation                     | SC-OFDM - QPSK                          |
| RB offset                      | 50                                      |
| RB size                        | 1                                       |
| Subframe configuration         | 0                                       |
| Special subframe configuration | 0                                       |
| Cyclic prefix                  | Normal                                  |
| Duty Cycle (%)                 | 0.61                                    |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2680.090 |
| Relative permittivity (real part)      | 38.209   |
| Relative permittivity (imaginary part) | 11.662   |
| Conductivity (S/m)                     | 1.995    |

#### C. SAR Surface and Volume




Maximum location: X=31.00, Y=9.00 ; SAR Peak: 0.14 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.041     |
| SAR 1g (W/Kg)                                         | 0.079     |
| Variation (%)                                         | 3.460     |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 49.605339 |

### E. Z Axis Scan

| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|
| SAR (W/Kg) | 0.137 | 0.082 | 0.041 | 0.021 | 0.009 | 0.007 | 0.003 |



### F. 3D Image



### 33-Head with front position in dist. 0mm on Channel 132322 in LTE band 66

#### SAR Measurement at LTE band 66 (Cheek, Right)

Date of measurement: 13/9/2025


##### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.20                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 66                             |
| Channels/Frequency | Middle (132322)/ frequency 1745.000 Mhz |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

##### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1745.090 |
| Relative permittivity (real part)      | 40.179   |
| Relative permittivity (imaginary part) | 15.189   |
| Conductivity (S/m)                     | 1.338    |

##### C. SAR Surface and Volume




Maximum location: X=-38.00, Y=2.00 ; SAR Peak: 0.98 W/kg

##### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.357     |
| SAR 1g (W/Kg)                                         | 0.626     |
| Variation (%)                                         | -2.470    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 64.240741 |

##### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.927 | 0.665 | 0.427 | 0.267 | 0.164 | 0.102 | 0.063 |



## E. 3D Image



## 34-Body with front position in dist. 10mm on Channel 132322 in LTE band 66

### SAR Measurement at LTE band 66 (Body, Validation Plane)

Date of measurement: 13/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.20                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 66                             |
| Channels/Frequency | Middle (132322)/ frequency 1745.000 Mhz |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 1745.090 |
| Relative permittivity (real part)      | 40.179   |
| Relative permittivity (imaginary part) | 15.189   |
| Conductivity (S/m)                     | 1.338    |

#### C. SAR Surface and Volume




Maximum location: X=23.00, Y=15.00 ; SAR Peak: 0.32 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.129     |
| SAR 1g (W/Kg)                                         | 0.216     |
| Variation (%)                                         | 2.390     |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 63.198420 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.320 | 0.229 | 0.145 | 0.090 | 0.052 | 0.029 | 0.018 |



## E. 3D Image



## 35-Head with front position in dist. 0mm on Channel 133322 in LTE band 71

### SAR Measurement at LTE band 71 (Cheek, Right)

Date of measurement: 9/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | LTE band 71                             |
| Channels/Frequency | Middle (133322)/ frequency 683.000 Mhz  |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 683.090 |
| Relative permittivity (real part)      | 41.656  |
| Relative permittivity (imaginary part) | 22.846  |
| Conductivity (S/m)                     | 0.858   |

#### C. SAR Surface and Volume




Maximum location: X=-49.00, Y=-39.00 ; SAR Peak: 0.10 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.050     |
| SAR 1g (W/Kg)                                         | 0.073     |
| Variation (%)                                         | -3.200    |
| Horizontal validation criteria: minimum distance (mm) | 17.888544 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 70.930233 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.090 | 0.086 | 0.061 | 0.051 | 0.041 | 0.034 | 0.027 |



## E. 3D Image



## 36-Body with front position in dist. 10mm on Channel 133322 in LTE band 71

### SAR Measurement at LTE band 71 (Body, Validation Plane)

Date of measurement: 9/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.24                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | LTE band 71                             |
| Channels/Frequency | Middle (133322)/ frequency 683.000 Mhz  |
| Signal             | LTE FDD                                 |
| Cell Bandwidth     | 20 Mhz                                  |
| Modulation         | SC-OFDM - QPSK                          |
| RB offset          | 50                                      |
| RB size            | 1                                       |

#### B. Permittivity

|                                        |         |
|----------------------------------------|---------|
| Middle TX Frequency (MHz)              | 683.090 |
| Relative permittivity (real part)      | 41.656  |
| Relative permittivity (imaginary part) | 22.846  |
| Conductivity (S/m)                     | 0.858   |

#### C. SAR Surface and Volume




#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.079     |
| SAR 1g (W/Kg)                                         | 0.103     |
| Variation (%)                                         | 1.480     |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 73.333333 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.141 | 0.105 | 0.077 | 0.065 | 0.048 | 0.044 | 0.033 |



## F. 3D Image



## 37-Head with front position in dist. 0mm on Channel 6 in IEEE 802.11b ISM

### SAR Measurement at ISM (Cheek, Right)

Date of measurement: 16/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.40                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | ISM                                     |
| Channels/Frequency | Middle (6)/ frequency 2437.000 Mhz      |
| Signal             | IEEE 802.11 b                           |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2437.000 |
| Relative permittivity (real part)      | 38.855   |
| Relative permittivity (imaginary part) | 13.645   |
| Conductivity (S/m)                     | 1.773    |

#### C. SAR Surface and Volume




Maximum location: X=-2.00, Y=-22.00 ; SAR Peak: 0.41 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.104     |
| SAR 1g (W/Kg)                                         | 0.224     |
| Variation (%)                                         | -0.960    |
| Horizontal validation criteria: minimum distance (mm) | 17.313708 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 51.712196 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.402 | 0.242 | 0.125 | 0.066 | 0.036 | 0.023 | 0.009 |



## E. 3D Image



## 38-Body with back position in dist. 10mm on Channel 6 in IEEE 802.11b ISM

### SAR Measurement at ISM (Body, Validation Plane)

Date of measurement: 16/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.40                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | ISM                                     |
| Channels/Frequency | Middle (6)/ frequency 2437.000 Mhz      |
| Signal             | IEEE 802.11 b                           |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2437.000 |
| Relative permittivity (real part)      | 38.855   |
| Relative permittivity (imaginary part) | 13.645   |
| Conductivity (S/m)                     | 1.773    |

#### C. SAR Surface and Volume




Maximum location: X=-2.00, Y=16.00 ; SAR Peak: 0.60 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.165     |
| SAR 1g (W/Kg)                                         | 0.344     |
| Variation (%)                                         | -4.920    |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 52.777708 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.597 | 0.371 | 0.196 | 0.107 | 0.055 | 0.029 | 0.014 |



## E. 3D Image



## 39-Head with front position in dist. 0mm on Channel 42 in IEEE 802.11ac U-NII

### SAR Measurement at U-NII-1 (Cheek, Right)

Date of measurement: 18/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.18                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Right head                               |
| Device Position    | Cheek                                    |
| Band               | U-NII-1                                  |
| Channels/Frequency | Higher (42)/ frequency 5210.000 Mhz      |
| Signal             | IEEE 802.11 ac                           |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5210.000 |
| Relative permittivity (real part)      | 36.837   |
| Relative permittivity (imaginary part) | 16.438   |
| Conductivity (S/m)                     | 4.594    |

#### C. SAR Surface and Volume




Maximum location: X=-12.00, Y=-11.00 ; SAR Peak: 1.76 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.213     |
| SAR 1g (W/Kg)                                         | 0.645     |
| Variation (%)                                         | -2.300    |
| Horizontal validation criteria: minimum distance (mm) | 18.944272 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 55.504434 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 2.00  | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 1.156 | 0.701 | 0.389 | 0.191 | 0.110 | 0.058 | 0.032 | 0.009 | 0.006 | 0.003 | 0.004 | 0.004 |



## E. 3D Image



## 40-Body with back position in dist. 10mm on Channel 42 in IEEE 802.11ac U-NII

### SAR Measurement at U-NII-1 (Body, Validation Plane)

Date of measurement: 18/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.18                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Validation plane                         |
| Device Position    | Body                                     |
| Band               | U-NII-1                                  |
| Channels/Frequency | Higher (42)/ frequency 5210.000 Mhz      |
| Signal             | IEEE 802.11 ac                           |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5210.000 |
| Relative permittivity (real part)      | 36.837   |
| Relative permittivity (imaginary part) | 16.438   |
| Conductivity (S/m)                     | 4.594    |

#### C. SAR Surface and Volume




Maximum location: X=-33.00, Y=26.00 ; SAR Peak: 0.78 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.095     |
| SAR 1g (W/Kg)                                         | 0.277     |
| Variation (%)                                         | -2.260    |
| Horizontal validation criteria: minimum distance (mm) | 17.313708 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 58.006424 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 2.00  | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 0.736 | 0.461 | 0.268 | 0.155 | 0.078 | 0.035 | 0.028 | 0.011 | 0.007 | 0.004 | 0.005 | 0.004 |



## E. 3D Image



## 41-Head with front position in dist. 0mm on Channel 52 in IEEE 802.11a U-NII

### SAR Measurement at U-NII-2a (Cheek, Right)

Date of measurement: 18/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.14                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Right head                               |
| Device Position    | Cheek                                    |
| Band               | U-NII-2a                                 |
| Channels/Frequency | Higher (64)/ frequency 5260.000 Mhz      |
| Signal             | IEEE 802.11 a                            |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5260.000 |
| Relative permittivity (real part)      | 36.807   |
| Relative permittivity (imaginary part) | 16.516   |
| Conductivity (S/m)                     | 4.645    |

#### C. SAR Surface and Volume




Maximum location: X=-9.00, Y=-17.00 ; SAR Peak: 1.03 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.077     |
| SAR 1g (W/Kg)                                         | 0.212     |
| Variation (%)                                         | 1.490     |
| Horizontal validation criteria: minimum distance (mm) | 8.944272  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 55.470188 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 2.00  | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 0.470 | 0.271 | 0.049 | 0.077 | 0.042 | 0.033 | 0.054 | 0.014 | 0.026 | 0.042 | 0.024 | 0.028 |



## E. 3D Image



## 42-Body with back position in dist. 10mm on Channel 52 in IEEE 802.11a U-NII

### SAR Measurement at U-NII-2a (Body, Validation Plane)

Date of measurement: 18/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.18                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Validation plane                         |
| Device Position    | Body                                     |
| Band               | U-NII-2a                                 |
| Channels/Frequency | Lower (52)/ frequency 5260.000 Mhz       |
| Signal             | IEEE 802.11 a                            |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5260.000 |
| Relative permittivity (real part)      | 36.807   |
| Relative permittivity (imaginary part) | 16.516   |
| Conductivity (S/m)                     | 4.645    |

#### C. SAR Surface and Volume




Maximum location: X=-27.00, Y=33.00 ; SAR Peak: 0.82 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.100     |
| SAR 1g (W/Kg)                                         | 0.278     |
| Variation (%)                                         | -4.870    |
| Horizontal validation criteria: minimum distance (mm) | 10.313708 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 55.538242 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 2.00  | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 0.767 | 0.469 | 0.261 | 0.134 | 0.082 | 0.043 | 0.025 | 0.011 | 0.011 | 0.006 | 0.004 | 0.004 |



## F. 3D Image



## 43-Head with front position in dist. 0mm on Channel 122 in IEEE 802.11ac U-NII

### SAR Measurement at U-NII-2c (Cheek, Right)

Date of measurement: 19/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.14                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Right head                               |
| Device Position    | Cheek                                    |
| Band               | U-NII-2c                                 |
| Channels/Frequency | Lower (100)/ frequency 5500.000 Mhz      |
| Signal             | IEEE 802.11 a                            |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5500.000 |
| Relative permittivity (real part)      | 35.859   |
| Relative permittivity (imaginary part) | 16.599   |
| Conductivity (S/m)                     | 4.988    |

#### C. SAR Surface and Volume




Maximum location: X=-6.00, Y=-32.00 ; SAR Peak: 0.28 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.032     |
| SAR 1g (W/Kg)                                         | 0.083     |
| Variation (%)                                         | -1.880    |
| Horizontal validation criteria: minimum distance (mm) | 8.000000  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 49.594793 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 2.00  | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 0.158 | 0.086 | 0.028 | 0.023 | 0.008 | 0.004 | 0.008 | 0.016 | 0.013 | 0.011 | 0.011 | 0.008 |



## E. 3D Image



## 44-Body with back position in dist. 10mm on Channel 122 in IEEE 802.11ac U-NII

### SAR Measurement at U-NII-2c (Body, Validation Plane)

Date of measurement: 19/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.14                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Validation plane                         |
| Device Position    | Body                                     |
| Band               | U-NII-2c                                 |
| Channels/Frequency | Lower (100)/ frequency 5500.000 Mhz      |
| Signal             | IEEE 802.11 a                            |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5500.000 |
| Relative permittivity (real part)      | 35.859   |
| Relative permittivity (imaginary part) | 16.599   |
| Conductivity (S/m)                     | 4.988    |

#### C. SAR Surface and Volume




Maximum location: X=24.00, Y=39.00 ; SAR Peak: 0.07 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.006     |
| SAR 1g (W/Kg)                                         | 0.012     |
| Variation (%)                                         | -4.200    |
| Horizontal validation criteria: minimum distance (mm) | 8.000000  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 22.159250 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 2.00  | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 0.033 | 0.022 | 0.012 | 0.008 | 0.011 | 0.008 | 0.007 | 0.008 | 0.012 | 0.016 | 0.008 | 0.008 |



## E. 3D Image



## 45-Head with front position in dist. 0mm on Channel 155 in IEEE 802.11ac U-NII

### SAR Measurement at U-NII-2 (Cheek, Right)

Date of measurement: 19/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.11                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Right head                               |
| Device Position    | Cheek                                    |
| Band               | U-NII-2                                  |
| Channels/Frequency | Middle (155) frequency 5775.000 Mhz      |
| Signal             | IEEE 802.11 ac                           |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5775.000 |
| Relative permittivity (real part)      | 35.632   |
| Relative permittivity (imaginary part) | 16.409   |
| Conductivity (S/m)                     | 5.364    |

#### C. SAR Surface and Volume




Maximum location: X=-9.00, Y=-16.00 ; SAR Peak: 0.62 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.065     |
| SAR 1g (W/Kg)                                         | 0.204     |
| Variation (%)                                         | -3.690    |
| Horizontal validation criteria: minimum distance (mm) | 8.944272  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 52.233927 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 2.00  | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 0.359 | 0.203 | 0.082 | 0.047 | 0.017 | 0.018 | 0.013 | 0.005 | 0.012 | 0.032 | 0.009 | 0.005 |



## E. 3D Image



## 46-Body with back position in dist. 10mm on Channel 155 in IEEE 802.11ac U-NII

### SAR Measurement at U-NII-2 (Body, Validation Plane)

Date of measurement: 19/9/2025


#### A. Experimental conditions.

|                    |                                          |
|--------------------|------------------------------------------|
| Probe              | 0125-EPGO-445                            |
| ConvF              | 1.11                                     |
| Area Scan          | dx=8mm dy=8mm, Complete                  |
| Zoom Scan          | 7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete |
| Phantom            | Validation plane                         |
| Device Position    | Body                                     |
| Band               | U-NII-2                                  |
| Channels/Frequency | Middle (155)/ frequency 5775.000 Mhz     |
| Signal             | IEEE 802.11 ac                           |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 5775.000 |
| Relative permittivity (real part)      | 35.632   |
| Relative permittivity (imaginary part) | 16.409   |
| Conductivity (S/m)                     | 5.364    |

#### C. SAR Surface and Volume




#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.032     |
| SAR 1g (W/Kg)                                         | 0.098     |
| Variation (%)                                         | 1.940     |
| Horizontal validation criteria: minimum distance (mm) | 8.944272  |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 46.025838 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 2.00  | 4.00  | 6.00  | 8.00  | 10.00 | 12.00 | 14.00 | 16.00 | 18.00 | 20.00 | 22.00 |
| SAR (W/Kg) | 0.314 | 0.169 | 0.037 | 0.040 | 0.005 | 0.015 | 0.008 | 0.012 | 0.009 | 0.012 | 0.008 | 0.008 |



## E. 3D Image



## 47-Head with front position in dist. 0mm on Channel 39 in Bluetooth

### SAR Measurement at Bluetooth (Cheek, Right)

Date of measurement: 16/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.40                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Right head                              |
| Device Position    | Cheek                                   |
| Band               | Bluetooth                               |
| Channels/Frequency | Middle (39)/ frequency 2441.000 Mhz     |
| Signal             | Bluetooth                               |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2441.000 |
| Relative permittivity (real part)      | 38.845   |
| Relative permittivity (imaginary part) | 13.645   |
| Conductivity (S/m)                     | 1.775    |

#### C. SAR Surface and Volume




Maximum location: X=-2.00, Y=-8.00 ; SAR Peak: 0.01 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.003     |
| SAR 1g (W/Kg)                                         | 0.004     |
| Variation (%)                                         | 1.090     |
| Horizontal validation criteria: minimum distance (mm) | 11.313708 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 75.785396 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.002 | 0.005 | 0.005 | 0.002 | 0.002 | 0.004 | 0.002 |



## E. 3D Image



## 48-Body with back position in dist. 10mm on Channel 39 in Bluetooth

### SAR Measurement at Bluetooth (Body, Validation Plane)

Date of measurement: 16/9/2025


#### A. Experimental conditions.

|                    |                                         |
|--------------------|-----------------------------------------|
| Probe              | 0125-EPGO-445                           |
| ConvF              | 1.40                                    |
| Area Scan          | dx=8mm dy=8mm, Complete                 |
| Zoom Scan          | 5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete |
| Phantom            | Validation plane                        |
| Device Position    | Body                                    |
| Band               | Bluetooth                               |
| Channels/Frequency | Middle (39)/ frequency 2441.000 Mhz     |
| Signal             | Bluetooth                               |

#### B. Permittivity

|                                        |          |
|----------------------------------------|----------|
| Middle TX Frequency (MHz)              | 2441.000 |
| Relative permittivity (real part)      | 38.845   |
| Relative permittivity (imaginary part) | 13.645   |
| Conductivity (S/m)                     | 1.775    |

#### C. SAR Surface and Volume




Maximum location: X=-8.00, Y=16.00 ; SAR Peak: 0.01 W/kg

#### D. SAR 1g & 10g


|                                                       |           |
|-------------------------------------------------------|-----------|
| SAR 10g (W/Kg)                                        | 0.002     |
| SAR 1g (W/Kg)                                         | 0.003     |
| Variation (%)                                         | 2.840     |
| Horizontal validation criteria: minimum distance (mm) | 16.000000 |
| Vertical validation criteria: SAR ratio M2/M1 (%)     | 70.985810 |

#### E. Z Axis Scan

|            |       |       |       |       |       |       |       |
|------------|-------|-------|-------|-------|-------|-------|-------|
| Z (mm)     | 0.00  | 4.00  | 9.00  | 14.00 | 19.00 | 24.00 | 29.00 |
| SAR (W/Kg) | 0.006 | 0.004 | 0.001 | 0.003 | 0.002 | 0.002 | 0.003 |




### F. 3D Image



## ANNEX D SAR Test Setup Photos

Reference Photo: simulation liquid depth 15cm



Please refer to the Appendix Test Setup Photos

## ANNEX E EUT External and Internal Photos

Please refer to RF Report.

## ANNEX F Calibration Information

Please refer to the document "Calibration.pdf".



BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict,  
Bao'an District, Shenzhen, China

[www.btf-lab.com](http://www.btf-lab.com)

**--END OF REPORT--**