



FCC Test Report (Bluetooth)

FCC ID : 2ADRK-X7

Applicant : Xiamen Maxa Engineering Co., Ltd
RM 804, No. 619#, Sishui Road, Huli, Xiamen, 361009, China

Sample Description

Product Name : Bluetooth Headset

Model No. : X7

Trademark : N/A

Receipt Date : 2014-12-02

Test Date : 2014-12-03 to 2014-12-04

Issue Date : 2014-12-05

Test Standard(s) : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Conclusions : PASSED*

*In the configuration tested, the EUT complied with the standards specified above.

Test/Witness Engineer : Jason Deng

Approved & Authorized : Frank Zhang

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



Contents

CONTENTS.....	2
1. GENERAL INFORMATION.....	4
1.1. Client Information.....	4
1.2. General Description of EUT (Equipment Under Test).....	4
1.3. Block Diagram Showing The Configuration of System Tested.....	5
1.4. Description of Support Units.....	5
1.5. External I/O Cable.....	5
1.6. Description of Test Mode.....	5
1.7. Test Instruments List.....	6
1.8. Laboratory Location.....	7
2. TEST SUMMARY.....	8
3. ANTENNA REQUIREMENT.....	9
3.1. Standard Requirement.....	9
3.2. Antenna Connected Construction.....	9
4. CONDUCTED EMISSION TEST.....	10
4.1. Test Standard and Limit.....	10
4.2. Test Setup.....	10
4.3. Test Procedure.....	10
4.4. Test Data.....	11
5. CONDUCTED PEAK OUTPUT POWER TEST.....	14
5.1. Test Standard and Limit.....	14
5.2. Test Setup.....	14
5.3. Test Procedure.....	14
5.4. Test Data.....	14
6. PEAK POWER SPECTRAL DENSITY.....	17
6.1. Test Standard and Limit.....	17
6.2. Test Setup.....	17
6.3. Test Procedure.....	17
6.4. Test Data.....	17
7. BANDWIDTH.....	20
7.1. Test Standard and Limit.....	20
7.2. Test Setup.....	20
7.3. Test Procedure.....	20
7.4. Test Data.....	20
8. BAND EDGE REQUIREMENT (CONDUCTED EMISSION METHOD).....	24
11.1. Test Standard and Limit.....	24
11.2. Test Setup.....	24



ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 3 of 35

11.3.	Test Procedure.....	24
11.4.	Test Data.....	24
9.	BAND EDGE REQUIREMENT (RADIATED EMISSION METHOD).....	27
12.1.	Test Standard and Limit.....	27
12.2.	Test Setup.....	27
12.3.	Test Procedure.....	27
12.4.	Test Data.....	28
10.	SPURIOUS EMISSION.....	29
14.1.	Test Standard and Limit.....	29
14.2.	Test Setup.....	29
14.3.	Test Procedure.....	29
14.4.	Test Data.....	30



1. General Information

1.1. Client Information

Applicant	:	Xiamen Maxa Engineering Co., Ltd
Address	:	RM 804, No. 619#, Sishui Road, Huli, Xiamen, 361009, China
Manufacturer	:	Xiamen Maxa Engineering Co., Ltd
Address	:	RM 804, No. 619#, Sishui Road, Huli, Xiamen, 361009, China

1.2. General Description of EUT (Equipment Under Test)

Product Name	:	Bluetooth Headset	
Models No.	:	X7	
Trademark	:	N/A	
Product Description	:	Operation Frequency:	2402MHz~2480MHz
		Number of Channel:	40 Channels
		Modulation Type:	GFSK
		Modulation Technology:	BT4.0
		Antenna Type:	Integral PCB Antenna
		Antenna Gain:	2 dBi
Power Supply	:	DC 3.7V From battery or DC 5V From USB For Charge	

Note:

(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.


(2) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474



09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	40	2456
13	2428	27	2456		
Remark: Channel 0, 39 &78 selected for GFSK, $\pi/4$ -DQPSK and 8DPSK.					

1.3. Block Diagram Showing The Configuration of System Tested



1.4. Description of Support Units

Name	Model	Serial Number	Manufacturer
Printer	HP1020	CNCJ410726	HP
LCD Monitor	G205HV	10306738385	ACER
PC	ASPIREM1830	PTSF90C00305005CAC3000	ACER
Keyboard	SK-9625	KBUSB1580500037E0100	ACER
Mouse	MS.11200.014	M-UAY-ACR2	ACER

1.5. External I/O Cable

N/A

1.6. Description of Test Mode

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned followed was evaluated respectively.

Test Mode	Description
Transmitting mode	Keep the EUT in Transmitting mode with worst case data rate



Remark	N/A
--------	-----

Remark: The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

1.7. Test Instruments List

Item	Test Equipment	Manufacturer	Model No.	Cal. Date	Cal. Due date
1	Bilog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	Mar. 28, 2014	Mar. 27, 2015
2	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	Mar. 28, 2014	Mar. 27, 2015
3	Coaxial Cable	N/A	N/A	Mar. 28, 2014	Mar. 27, 2015
4	Coaxial Cable	N/A	N/A	Mar. 28, 2014	Mar. 27, 2015
5	Coaxial cable	N/A	N/A	Mar. 28, 2014	Mar. 27, 2015
6	Coaxial Cable	N/A	N/A	Mar. 28, 2014	Mar. 27, 2015
7	Coaxial Cable	N/A	N/A	Mar. 28, 2014	Mar. 27, 2015
8	Amplifier (10kHz-1.3GHz)	HP	8447D	Mar. 28, 2014	Mar. 27, 2015
9	Amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	Mar. 28, 2014	Mar. 27, 2015
10	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	Mar. 28, 2014	Mar. 27, 2015
11	Horn Antenna	ETS-LINDGREN	3160	Mar. 28, 2014	Mar. 27, 2015
12	Positioning Controller	UC	UC3000	N/A	N/A
13	Spectrum analyzer 9kHz-30GHz	Rohde & Schwarz	FSP	Mar. 28, 2014	Mar. 27, 2015
14	EMI Test Receiver	Rohde & Schwarz	ESPI	Mar. 28, 2014	Mar. 27, 2015
15	Loop antenna	Laplace instrument	RF300	Mar. 28, 2014	Mar. 27, 2015
16	Universal radio communication tester	Rhode & Schwarz	CMU200	Mar. 28, 2014	Mar. 27, 2015
17	Signal Analyzer	Rohde & Schwarz	FSIQ3	Mar. 28, 2014	Mar. 27, 2015
18	EMI Test Receiver	Rohde & Schwarz ESCI	ESCI	Mar. 28, 2014	Mar. 27, 2015
19	LISN	CHASE	MN2050D	Mar. 28, 2014	Mar. 27, 2015



1.8. Laboratory Location

Shenzhen TOBY technology Co., Ltd

Address: 1 A/F., Bldg.6, Yusheng Industrial Zone The National Road No.107 Xixiang Section 467,
Xixiang, Bao'an, Shenzhen, Guangdong, 518057, China

At the time of testing, the Laboratory is accredited. It is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562 7.

Tel:0086-755-26509301 Fax: 0086-755-26509195



2. Test Summary

Standard Section	Test Item	Judgment
Section 15.247&15.209	Spurious Emission	PASSED
Section 15.207	Conduction Emission	PASSED
Section 15.247	Bandwidth Test	PASSED
Section 15.247	Peak Power	PASSED
Section 15.247	Power Density	PASSED
Section 15.247	Band Edge	PASSED
Section 15.203	Antenna Requirement	PASSED
Remark: "N/A" is an abbreviation for Not Applicable.		



3. Antenna Requirement

3.1. Standard Requirement

3.1.1 Test standard

FCC Part15 Section 15.203 /247(c)

3.1.2 Requirement

1) 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

2) 15.247(c) (1)(i) requirement:

Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2. Antenna Connected Construction

The bluetooth antenna is an integral antenna which permanently attached, and the best case gain of the antenna is 2 dBi. It complies with the standard requirement.

4. Conducted Emission Test

4.1. Test Standard and Limit

4.1.1 Test Standard

FCC Part15 Section 15.207


4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequencies.

4.2. Test Setup



4.3. Test Procedure

- 1) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50 \Omega / 50 \mu\text{H} + 5 \Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 2) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.

The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal



ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

The Test Receiver setup: RBW=9kHz, VBW=30kHz, Sweep time= auto

4.4. Test Data

PASS.




ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 12 of 35

EUT: Bluetooth Headset M/N: X7
Operating Condition: Bluetooth TX mode
Test Site: Conduction Room
Operator: Jason
Test Specification: DC 5V from USB port with AC120V/60HZ
Polarization: Line
Note: Tem:23°C Hum:50%






ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 13 of 35

EUT: Bluetooth Headset M/N: X7
Operating Condition: Bluetooth TX mode
Test Site: Conduction Room
Operator: Jason
Test Specification: DC 5V from USB port with AC120V/60HZ
Polarization: Neutral
Note Tem:23℃ Hum:50%



Item	Freq MHz	Read dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.182	25.61	0.03	-9.72	0.10	35.46	54.42	-18.96	Average
2	0.223	38.63	0.03	-9.72	0.10	48.48	62.70	-14.22	QP
3	0.223	20.33	0.03	-9.72	0.10	30.18	52.70	-22.52	Average
4	0.456	28.93	0.03	-9.72	0.10	38.78	56.76	-17.98	QP
5	0.456	15.26	0.03	-9.72	0.10	25.11	46.76	-21.65	Average
6	1.464	25.86	0.05	-9.71	0.10	35.72	56.00	-20.28	QP
7	1.464	12.22	0.05	-9.71	0.10	22.08	46.00	-23.92	Average
8	5.058	25.85	0.10	-9.68	0.12	35.75	60.00	-24.25	QP
9	5.058	10.21	0.10	-9.68	0.12	20.11	50.00	-29.89	Average
10	23.636	22.15	0.43	-9.56	0.44	32.58	60.00	-27.42	QP
11	23.636	11.78	0.43	-9.56	0.44	22.21	50.00	-27.79	Average

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss



5. Conducted Peak Output Power Test

5.1. Test Standard and Limit


5.1.1 Test Standard

FCC Part15 C Section 15.247 (b)(3)

5.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

5.2. Test Setup



5.3. Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW $\leq$ 1 MHz)
RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.4. Test Data


GFSK mode				
Channel Number	Channel Frequency (MHz)	Test Result (dBm)	Limit (30dBm)	Judgment
CH 00	2402	2.41	21	PASSED
CH 19	2440	2.57	21	PASSED
CH 39	2480	2.19	21	PASSED




ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 15 of 35







6. PEAK POWER SPECTRAL DENSITY

6.1. Test Standard and Limit


6.1.1 Test Standard

FCC Part15 C Section 15.247

6.1.2 Test Limit

FCC Part 15 Subpart C(15.247)	
Test Item	Limit
Power Density	8dBm

6.2. Test Setup



6.3. Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:

Bandwidth: RBW=3kHz, VBW=1 kHz, detector= Peak

6.4. Test Data


Channel Number	Channel Frequency	Power Density
		GFSK
CH 00	2402(MHz)	-13.09
CH 19	2440MHz)	-12.88
CH 39	2480(MHz)	-13.24
Remark: Test plot as follows		



ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 18 of 35






ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 19 of 35





7. Bandwidth

7.1. Test Standard and Limit


7.1.1 Test Standard

FCC Part15 C Section 15.247 \

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
6dB Bandwidth	500KHz	2400~2483.5

7.2. Test Setup



7.3. Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=100 kHz, VBW=300 kHz, detector= Peak, Sweep Time =auto.
- (3) The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Test.

7.4. Test Data


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
CH0	2402	0.739	1.189	0.5	PASS
CH19	2440	0.750	1.188	0.5	PASS
CH39	2480	0.774	1.194	0.5	PASS



ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 21 of 35






ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 22 of 35






ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 23 of 35





8. Band Edge Requirement (Conducted Emission Method)

11.1. Test Standard and Limit


11.1.1 Test Standard

FCC Part15 C Section 15.247 (d)

11.1.2 Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

11.2. Test Setup



11.3. Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 kHz, VBW=300 kHz, Detector=Peak

11.4. Test Data


Test plot as follows



ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 25 of 35






ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 26 of 35



9. Band Edge Requirement (Radiated Emission Method)

12.1. Test Standard and Limit

12.1.1 Test Standard


FCC Part15 C Section 15.209 and 15.205

12.1.2 Test Limit

Radiated Emission Test Limit

Frequency	Limit (dB μ V/m @3m)	Remark
Above 1GHz	54.00	Average value
	74.00	Peak value

12.2. Test Setup



12.3. Test Procedure

- 1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum



ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 28 of 35

Hold Mode. Peak Value: RBW=1MHz, VBW=3MHz; Average value: RBW=1MHz, VBW=10Hz

- 6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

12.4. Test Data

Remark:

1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8DPSK, and all data were shown in the report.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.

Test mode: GFSK					Test channel: Lowest				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Level
2400.00	14.57	27.58	5.67	0	47.82	74	26.18	H	PEAK
2400.00	15.27	27.58	5.67	0	48.52	74	25.48	V	PEAK
2400.00	4.12	27.58	5.67	0	37.37	54	16.63	H	AVG.
2400.00	6.43	27.58	5.67	0	39.68	54	14.32	V	AVG.
Test mode: GFSK					Test channel: Highest				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Level
2483.50	15.13	27.52	5.7	0	48.35	74	25.65	H	PEAK
2483.50	13.62	27.52	5.7	0	46.84	74	27.16	V	PEAK
2483.50	4.77	27.52	5.7	0	37.99	54	16.01	H	AVG.
2483.50	3.62	27.52	5.7	0	36.84	54	17.16	V	AVG.

Remark:

1. Final Level = Read Level + Antenna Factor + Cable Loss - Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

10. Spurious Emission

14.1. Test Standard and Limit

14.1.1 Test Standard

FCC Part15 C Section 15.209


14.1.2 Test Limit

Frequency (MHz)	Limit (dB μ V/m)	
	At 3m Distance	
30MHz~88MHz	40	Quasi-peak
88MHz~216MHz	43.5	Quasi-peak
216MHz~960MHz	46	Quasi-peak
960MHz~1000MHz	54	Quasi-peak
Above 1000MHz	54	Average
	74	Peak


Remark: 1. The lower limit shall apply at the transition frequency.

14.2. Test Setup

Below 1GHz



Above 1GHz



14.3. Test Procedure

- 1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set



to make the measurement.

- 4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
Peak value: RBW=1MHz, VBW=3MHz;
Average value: RBW=1MHz, VBW=10Hz;
QP Value: RBW=120kHz, VBW=300kHz
- 6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

14.4. Test Data

Remark:

1. During the test, pre-scan the GFSK.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.
3. 9 kHz to 30 MHz is noise floor, so only shows the data of above 30MHz in this report.




ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 31 of 35

Radiated Emission Test Data (Below 1GHz)

EUT: Bluetooth Headset M/N: X7
Operating Condition: Bluetooth TX mode
Test Site: 3m chamber
Operator: Jason
Test Specification: DC 5V From USB Port with AC120V/60Hz
Polarization: Horizontal
Note: Tem:23°C Hum:50%



Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss




ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 32 of 35

Radiated Emission Test Data (Below 1GHz)

EUT: Bluetooth Headset M/N: X7
Operating Condition: Bluetooth TX mode
Test Site: 3m chamber
Operator: Jason
Test Specification: DC 5V From USB Port with AC120V/60Hz
Polarization: Vertical
Note Tem:23°C Hum:50%



Condition : FCC PART 15 B 3m POL: VERTICAL

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	39.30	41.29	14.07	25.81	0.17	29.72	40.00	-10.28	QP
2	69.11	48.34	10.82	26.76	0.30	32.70	40.00	-7.30	QP
3	104.17	40.50	10.74	26.85	0.32	24.71	43.50	-18.79	QP
4	156.46	49.97	14.15	26.91	0.38	37.59	43.50	-5.91	QP
5	287.99	40.97	12.54	24.17	0.66	30.00	46.00	-16.00	QP
6	570.61	42.23	17.74	27.33	1.41	34.05	46.00	-11.95	QP

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 33 of 35

Radiated Emission Test Data (Above 1GHz)

Test mode: GFSK					Test channel: Lowest				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Level
4804.00	37.58	31.53	8.90	40.24	37.77	74.00	36.23	V	PEAK
7206.00	35.12	36.47	10.59	41.24	40.94	74.00	33.06	V	PEAK
9608.00	*					74.00		V	PEAK
12010.00	*					74.00		V	PEAK
14412.00	*					74.00		V	PEAK
16814.00	*					74.00		V	PEAK
4804.00	35.73	31.53	8.90	40.24	35.92	74.00	38.08	H	PEAK
7206.00	35.49	36.47	10.59	41.24	41.31	74.00	32.69	H	PEAK
9608.00	*					74.00		H	PEAK
12010.00	*					74.00		H	PEAK
14412.00	*					74.00		H	PEAK
16814.00	*					74.00		H	PEAK
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Level
4804.00	37.66	31.53	8.90	40.24	37.85	74.00	36.15	V	AVG.
7206.00	35.89	36.47	10.59	41.24	41.71	74.00	32.29	V	AVG.
9608.00	*					54.00		V	AVG.
12010.00	*					54.00		V	AVG.
14412.00	*					54.00		V	AVG.
16814.00	*					54.00		V	AVG.
4804.00	36.65	31.53	8.90	40.24	36.84	74.00	37.16	H	AVG.
7206.00	35.62	36.47	10.59	41.24	41.44	74.00	32.56	H	AVG.
9608.00	*					54.00		H	AVG.
12010.00	*					54.00		H	AVG.
14412.00	*					54.00		H	AVG.
16814.00	*					54.00		H	AVG.

Remark:

1. Final Level = Read Level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.



ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 34 of 35

Radiated Emission Test Data (Above 1GHz)

Test mode: GFSK					Test channel: Middle				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Level
488000	36.13	31.58	8.98	40.15	36.54	74.00	37.46	V	PEAK
732000	37.09	36.48	10.69	41.15	43.11	74.00	30.89	V	PEAK
9764.00	*					74.00		V	PEAK
12205.00	*					74.00		V	PEAK
14646.00	*					74.00		V	PEAK
17087.00	*					74.00		V	PEAK
488000	35.89	31.58	8.98	40.15	36.30	74.00	37.7	H	PEAK
732000	36.15	36.48	10.69	41.15	42.17	74.00	31.83	H	PEAK
9764.00	*					74.00		H	PEAK
12205.00	*					74.00		H	PEAK
14646.00	*					74.00		H	PEAK
17087.00	*					74.00		H	PEAK
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Level
4882.00	36.13	31.58	8.98	40.15	36.54	74.00	37.46	V	AVG.
7323.00	36.47	36.47	10.69	41.15	42.48	74.00	31.52	V	AVG.
9764.00	*					54.00		V	AVG.
12205.00	*					54.00		V	AVG.
14646.00	*					54.00		V	AVG.
17087.00	*					54.00		V	AVG.
4882.00	32.01	31.58	8.98	40.15	32.42	74.00	41.58	H	AVG.
7323.00	33.09	36.47	10.69	41.15	39.10	74.00	34.9	H	AVG.
9764.00	*					54.00		H	AVG.
12205.00	*					54.00		H	AVG.
14646.00	*					54.00		H	AVG.
17087.00	*					54.00		H	AVG.

Remark:

1. Final Level = Read Level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.



ATA Testing Technology Service Co., Ltd.

Report No.:ATA141203016F

Page: 35 of 35

Radiated Emission Test Data (Above 1GHz)

Test mode: GFSK					Test channel: Highest				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Level
4960.00	35.17	31.69	9.08	40.03	35.91	74.00	38.09	V	PEAK
7440.00	35.43	36.6	10.8	41.05	41.78	74.00	32.22	V	PEAK
9920.00	*					74.00		V	PEAK
12400.00	*					74.00		V	PEAK
14880.00	*					74.00		V	PEAK
17360.00	*					74.00		V	PEAK
4960.00	35.49	31.69	9.08	40.03	36.23	74.00	37.77	H	PEAK
7440.00	35.78	36.6	10.8	41.05	42.13	74.00	31.87	H	PEAK
9920.00						74.00		H	PEAK
12400.00	*					74.00		H	PEAK
14880.00	*					74.00		H	PEAK
17360.00	*					74.00		H	PEAK
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Level
4960.00	32.82	31.69	9.08	40.03	33.56	74.00	40.44	V	AVG.
7440.00	35.93	36.6	10.8	41.05	42.28	74.00	31.72	V	AVG.
9920.00	*					54.00		V	AVG.
12400.00	*					54.00		V	AVG.
14880.00	*					54.00		V	AVG.
17360.00	*					54.00		V	AVG.
4960.00	35.67	31.69	9.08	40.03	36.41	74.00	37.59	H	AVG.
7440.00	35.15	36.6	10.8	41.05	41.5	74.00	32.5	H	AVG.
9920.00	*					54.00		H	AVG.
12400.00	*					54.00		H	AVG.
14880.00	*					54.00		H	AVG.
17360.00	*					54.00		H	AVG.

Remark:

1. Final Level = Read Level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.