



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM150200080102
Page: 1 of 9

SAR Evaluation Report

Application No.: SZEM1502000801HR
Applicant: Aspenta International FZ-LLC
Product Name: GPS Tracker
Model No.(EUT): CIT-002
Trade Mark:



FCC ID: 2ADTO-CIT-001
Standards: 47 CFR Part 2.1093 (2014)
KDB447498D01 General RF Exposure Guidance v05
Tracking Number: 340466
Date of Receipt: 2014-11-06 (for original report SZEM141100609003)
Date of Test: 2014-12-16 to 2015-01-08 (for original report SZEM141100609003)
Date of Issue: 2015-04-23 (for original report SZEM141100609003)
2015-07-07 (for new report SZEM150200080102)

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-07-07		Original

Authorized for issue by:			
Tested By			2015-01-08
		(Chris Zhong) /Project Engineer	Date
Prepared By			2015-07-07
		(Jade Chen) /Clerk	Date
Checked By			2015-07-07
		(Emen Li) /Reviewer	Date



3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST LOCATION.....	4
4.4 TEST FACILITY	5
4.5 DEVIATION FROM STANDARDS	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 SAR EVALUATION	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
5.1.1 <i>Standard Requirement</i>	6
5.1.2 <i>Limits</i>	6
5.1.3 <i>Duty Cycle Measurement</i>	7
5.1.4 <i>Conducted power measurement and calculation</i>	9
5.1.5 <i>Stand-alone SAR test evaluation</i>	9



4 General Information

4.1 Client Information

Applicant:	Aspenta International FZ-LLC
Address of Applicant:	Premises:155 Floor:01 building:17 Dubai, United Arab Emirates

4.2 General Description of EUT

Product Name:	GPS Tracker
Model No.:	CIT-001
Trade Mark:	
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	Bluetooth:3.4dBi GSM850:2.5dBi GSM1900:2.5dBi
Battery:	Li recharge battery 3.7V 300mAh
Power Supply:	DC 12V

Remark:

Original model No. in report SZEM141100609003: CIT-001

New model No. in report SZEM150200080101: CIT-002

Only the model CIT-001 was tested in report SZEM141100609003.

This report was an additional report copied from the report SZEM141100609003, just changed the model information. Since the electrical circuit design, layout, components used and internal wiring for the model in the report SZEM141100609003 was exactly the same as the model in this report, with difference being of the model No. and information as below:

Only GSM and GPS antenna and enclosure is different. CIT-001(2ADTO-CIT-001) has internal antenna, and CIT-002(2ADTO-CIT-002) has external antenna.

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.



5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v05

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation


The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion




5.1.3 Duty Cycle Measurement

GSM 850:





GSM 1900:



For GSM 850 , it supports GSM only,contains 1 time slot. The time of a frame for GSM network is 4.615ms, every frame contains 8 timeslots, so the maximum transmission time is $4.615/8=0.576875$ ms,and the minimum time (shortest interval) between transmissions is 33.1175s

So the **Duty Factor**= $10\log(0.576875/33117.5) = -47.59\text{dB}$

For GSM GSM1900 , it supports GSM only,contains 1 time slot. The time of a frame for GSM network is 4.615ms, every frame contains 8 timeslots, so the maximum transmission time is $4.615/8=0.576875$ ms,and the minimum time (shortest interval) between transmissions is 33.173077s

So the **Duty Factor**= $10\log(0.576875/33173.077) = -47.60\text{dB}$



5.1.4 Conducted power measurement and calculation

Frequency band	Test ch./Freq.	Coducted Output Power(dBm)	Tune Up Max. Power(dBm)	Duty Cycle(dB)	Max. Average Output Power(dBm)	Max. Average Output Power(mW)
GSM850 (GSM only)	128/824.2	32.38	33	-47.59	-14.59	0.035
	190/836.6	32.37				
	251/848.8	32.31				
GSM1900 (GSM only)	512/1850.2	30.14	31	-47.60	-16.6	0.022
	661/1880	29.36				
	810/1909.8	29.28				
BT	0/2402	-0.12	0	0	0	1
	19/2440	-0.96				
	39/2480	-1.6				

5.1.5 Stand-alone SAR test evaluation

Per FCC KDB 447498 D01 v05r02, the SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel(mW)}}{\text{Test Separation Dist(mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Note:

When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- 1) Based on the Max. Average Output Power of GSM 850 and the antenna to use separation distance 5mm, Stand-alone SAR evaluation is not required for GSM 850; $[(0.035/5) * \sqrt{0.8488}] = 0.006 < 3.0$.
- 2) Based on the Max. Average Output Power of GSM 1900 and the antenna to use separation distance 5mm, Stand-alone SAR evaluation is not required for GSM 1900; $[(0.022/5) * \sqrt{1.9098}] = 0.006 < 3.0$
- 3) Based on the Max. Average Output Power of BT and the antenna to use separation distance 5mm, Stand-alone SAR evaluation is not required for BT; $[(1.0/5) * \sqrt{2.480}] = 0.31 < 3.0$