



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

FCC PART 15 SUBPART C 15.247

Report Reference No.: CTL1805287041-WF

Compiled by:
(position+printed name+signature)

Allen Wang
(File administrators)

Allen Wang

Tested by:
(position+printed name+signature)

Nice Nong
(Test Engineer)

Nice Nong

Approved by:
(position+printed name+signature)

Ivan Xie
(Manager)

Ivan Xie

Product Name.....: G1 Ultra 4K Action Camera

Model/Type reference: G1

Trade Mark.....: NEEWER

FCC ID.....: 2ADUJ-G1

Applicant's name: Shenzhen Neewer Technology Co., Ltd

Address of applicant: Room 3603, Shenfang Plaza No.3005, Renmin South Road,
Shenzhen, Guangdong, China

Test Firm: Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm: Floor 1-A, Baisha Technology Park, No.3011, Shahehexi Road,
Nanshan District, Shenzhen, China 518055

Test specification.....:

Standard.....: 47 CFR FCC Part 15 Subpart C 15.247

TRF Originator: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF: Dated 2011-01

Date of Receipt.....: June. 05, 2018

Date of Test Date.....: June. 05, 2018–July 05, 2018

Data of Issue.....: July 05, 2018

Result.....: Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL1805287041-WF	July 05, 2018 Date of issue
--------------------------	-------------------------	--------------------------------

Equipment under Test : G1 Ultra 4K Action Camera

Model /Type : G1

Applicant : **Shenzhen Neewer Technology Co., Ltd**

Address : Room 3603, Shenfang Plaza No.3005, Renmin South Road, Shenzhen, Guangdong, China

Manufacturer : **Shenzhen XingYingDa Industry Co., Ltd**

Address : Floor 2, Building A, Longshan Industrial Zone No. 6 Nanling Village, South Bay Street, Longgang District, Shenzhen, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

**** Modified History ****

Revisions	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2018-07-05	CTL1805287041-WF	Tracy Qi



Table of Contents

Page

1. SUMMARY.....	5
1.1. TEST STANDARDS.....	5
1.2. TEST DESCRIPTION.....	5
1.3. TEST FACILITY	6
FCC-REGISTRATION NO.: 399832	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
2. GENERAL INFORMATION.....	7
2.1. ENVIRONMENTAL CONDITIONS	7
2.2. GENERAL DESCRIPTION OF EUT	7
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	7
2.4. EQUIPMENTS USED DURING THE TEST	8
2.5. RELATED SUBMITTAL(S) / GRANT (S).....	9
2.6. MODIFICATIONS.....	9
3. TEST CONDITIONS AND RESULTS	10
3.1. CONDUCTED EMISSIONS TEST	10
3.2. RADIATED EMISSIONS AND BAND EDGE	13
3.3. MAXIMUM CONDUCTED OUTPUT POWER.....	22
3.4. POWER SPECTRAL DENSITY	23
3.5. 6dB AND 99%BANDWIDTH	26
3.6. OUT-OF-BAND EMISSIONS	29
3.7. ANTENNA REQUIREMENT.....	38
4. TEST SETUP PHOTOS OF THE EUT	39
5. PHOTOS OF THE EUT.....	40

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10:2013](#) : American National Standard for Testing Unlicensed Wireless Devices

1.2. Test Description

FCC Requirements		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Conducted Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge	PASS

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 399832

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	± 0.57 dB	(1)
Transmitter power Radiated	± 2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	± 2.20 dB	(1)
Occupied Bandwidth	± 0.01 ppm	(1)
Radiated Emission 30~1000MHz	± 4.10 dB	(1)
Radiated Emission Above 1GHz	± 4.32 dB	(1)
Conducted Disturbance 0.15~30MHz	± 3.20 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	G1 Ultra 4K Action Camera
Model/Type reference:	G1
Power supply:	DC 3.7V from battery
WIFI :	
Supported type:	802.11b/802.11g/802.11n(H20)/802.11n(H40)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20)/802.11n(H40): OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz 802.11n(H40): 2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n(H20): 11 802.11n(H40): 7
Channel separation:	5MHz
Antenna type:	Internal antenna
Antenna gain:	0dBi

Note: For more details, please refer to the user's manual of the EUT.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing.

There are 11 channels provided to the EUT and Channel 01/06/11 were selected for WIFI test.

Operation Frequency WIFI :

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

Note: The line display in grey were the channel selected for testing

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9kHz~1GHz& Radiated Emission 1GHz~10th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
	11n(40MHz)/OFDM	13.5Mbps	3/6/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11
	11n(40MHz)/OFDM	13.5Mbps	3/9

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.1 2	2018/05/19	2019/05/18
LISN	R&S	ESH2-Z5	860014/010	2018/05/19	2019/05/18
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2018/05/19	2019/05/18
EMI Test Receiver	R&S	ESCI	103710	2018/05/19	2019/05/18
Spectrum Analyzer	Agilent	E4407B	MY41440676	2018/05/19	2019/05/18
Spectrum Analyzer	Agilent	N9020	US46220290	2018/05/19	2019/05/18
Power Meter	Anritsu	ML2487B	110553	2018/05/19	2019/05/18
Power Sensor	Anritsu	MA2411B	100345	2018/05/19	2019/05/18
Controller	EM Electronics	Controller EM 1000	N/A	2018/05/19	2019/05/18
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2018/05/19	2019/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2018/05/19	2019/05/18
Amplifier	Agilent	8349B	3008A02306	2018/05/19	2019/05/18
Amplifier	Agilent	8447D	2944A10176	2018/05/19	2019/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2018/05/19	2019/05/18
High-Pass Filter	K&L	9SH10-2700/X1 2750-O/O	N/A	2018/05/19	2019/05/18

High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2018/05/19	2019/05/18
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-10M	10m	2018/05/19	2019/05/18
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-3M	3m	2018/05/19	2019/05/18
Coaxial Cables	HUBER+SUHN ER	SUCOFLEX 104PEA-3M	3m	2018/05/19	2019/05/18
RF Cable	Megalon	RF-A303	N/A	2018/05/19	2019/05/18


The calibration interval was one year

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.



3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION




TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Remark: 802.11b/802.11g/802.11n(H20)/802.11n(H40) mode all have been tested ,only worse case of 802.11b High Channel was reported.

**MEASUREMENT RESULT: "CTL180307627_fin"**


6/6/2018 9:42AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.518000	42.00	10.0	56	14.0	QP	L1	GND
0.734000	33.90	10.0	56	22.1	QP	L1	GND
0.848000	35.40	10.0	56	20.6	QP	L1	GND
0.938000	34.20	10.0	56	21.8	QP	L1	GND
1.304000	33.50	10.1	56	22.5	QP	L1	GND
1.400000	33.60	10.1	56	22.4	QP	L1	GND

MEASUREMENT RESULT: "CTL180307627_fin2"

6/6/2018 9:42AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.512000	32.40	10.0	46	13.6	AV	L1	GND
0.770000	24.40	10.0	46	21.6	AV	L1	GND
0.854000	25.00	10.0	46	21.0	AV	L1	GND
0.944000	24.20	10.0	46	21.8	AV	L1	GND
1.016000	23.10	10.1	46	22.9	AV	L1	GND
1.298000	22.40	10.1	46	23.6	AV	L1	GND



MEASUREMENT RESULT: "CTL180307626_fin"

6/6/2018 9:36AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.518000	39.80	10.0	56	16.2	QP	N	GND
0.758000	31.00	10.0	56	25.0	QP	N	GND
0.872000	30.00	10.0	56	26.0	QP	N	GND
0.944000	30.50	10.0	56	25.5	QP	N	GND
1.022000	32.40	10.1	56	23.6	QP	N	GND

MEASUREMENT RESULT: "CTL180307626_fin2"

6/6/2018 9:36AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.330000	22.80	10.0	50	26.7	AV	N	GND
0.434000	22.90	10.0	47	24.3	AV	N	GND
0.518000	31.40	10.0	46	14.6	AV	N	GND
0.758000	23.40	10.0	46	22.6	AV	N	GND
0.860000	23.40	10.0	46	22.6	AV	N	GND
1.448000	22.20	10.1	46	23.8	AV	N	GND

3.2. Radiated Emissions and Band Edge

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure


1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.


TEST RESULTS

Remark:

1. All three channels (lowest/middle/highest) of each mode were measured below 1GHz and recorded worst case at 802.11b low channel.
2. All three channels (lowest/middle/highest) of each mode were measured above 1GHz and recorded worst case at 802.11b mode.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
4. Battery is full during all test

For 30MHz-1GHz

Test mode:	WIFI	Polarization:	Horizontal
SWEEP TABLE: "test (30M-1G)"			
Short Description: Field Strength			
Start	Stop	Detector	Meas. IF Transducer
Frequency	Frequency	Time	Bandw.
30.0 MHz	1.0 GHz	MaxPeak	200.0 ms 120 kHz VULB 9168
			
x x x MES CTL180531576_red			
MEASUREMENT RESULT: "CTL180531576_red"			
2018-6-7 16:18			
Frequency	Level	Transd	Limit Margin Det. Height Azimuth Polarization
MHz	dBµV/m	dB	dBµV/m dB dB cm deg
305.480000	32.40	14.6	46.0 13.6 --- 0.0 0.00 HORIZONTAL
342.340000	32.70	15.6	46.0 13.3 --- 0.0 0.00 HORIZONTAL
377.260000	32.40	16.4	46.0 13.6 --- 0.0 0.00 HORIZONTAL
414.120000	32.30	17.3	46.0 13.7 --- 0.0 0.00 HORIZONTAL
485.900000	32.90	18.7	46.0 13.1 --- 0.0 0.00 HORIZONTAL
901.060000	34.30	25.2	46.0 11.7 --- 0.0 0.00 HORIZONTAL

Test mode:	WIFI	Polarization:	Vertical
SWEEP TABLE: "test (30M-1G)"			
Short Description: Field Strength			
Start	Stop	Detector	Meas. IF Transducer
Frequency	Frequency	Time	Bandw.
30.0 MHz	1.0 GHz	MaxPeak	200.0 ms 120 kHz VULB 9168
			
x x x MES CTL180531577_red			
MEASUREMENT RESULT: "CTL180531577_red"			
2018-6-7 16:21			
Frequency	Level	Transd	Limit Margin Det. Height Azimuth Polarization
MHz	dBµV/m	dB	dBµV/m dB dB cm deg
53.280000	18.70	13.5	40.0 21.3 --- 0.0 0.00 VERTICAL
59.100000	20.40	13.1	40.0 19.6 --- 0.0 0.00 VERTICAL
169.680000	26.20	14.3	43.5 17.3 --- 0.0 0.00 VERTICAL
175.500000	24.30	13.5	43.5 19.2 --- 0.0 0.00 VERTICAL
344.280000	27.30	15.7	46.0 18.7 --- 0.0 0.00 VERTICAL
914.640000	30.20	25.4	46.0 15.8 --- 0.0 0.00 VERTICAL

For 1GHz to 25GHz**802.11b Mode (above 1GHz)**

Note: 802.11b/802.11g/802.11n (H20) /802.11n(H40) all have been tested, only worse case 802.11b is reported

Frequency(MHz):			2412		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	58.06	PK	74	15.94	53.51	33.52	6.92	35.89	4.55
4824.00	51.42	AV	54	2.58	46.87	33.52	6.92	35.89	4.55
5125.75	42.96	PK	74	31.04	35.76	34.38	7.10	34.28	7.20
5125.75	--	AV	54	--	--	--	--	--	--
7236.00	48.21	PK	74	25.79	36.94	37.1	9.19	35.02	11.27
7236.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2412		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	58.61	PK	74	15.39	54.06	33.52	6.92	35.89	4.55
4824.00	51.92	AV	54	2.08	47.37	33.52	6.92	35.89	4.55
5125.75	42.65	PK	74	31.35	35.45	34.38	7.10	34.28	7.20
5125.75	--	AV	54	--	--	--	--	--	--
7236.00	47.33	PK	74	26.67	36.06	37.1	9.19	35.02	11.27
7236.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2437		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	58.08	PK	74	15.92	51.84	33.59	6.95	34.3	6.24
4874.00	51.69	AV	54	2.31	45.45	33.59	6.95	34.3	6.24
5215.50	43.05	PK	74	30.95	35.45	34.56	7.15	34.11	7.60
5215.50	--	AV	54	--	--	--	--	--	--
7311.00	47.92	PK	74	26.08	36.26	37.44	9.22	35	11.66
7311.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2437		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	57.84	PK	74	16.16	51.5	33.59	6.95	34.2	6.34
4874.00	51.07	AV	54	2.93	44.73	33.59	6.95	34.2	6.34
5215.50	42.61	PK	74	31.39	35.71	34.07	7.05	34.22	6.90
5215.50	--	AV	54	--	--	--	--	--	--
7311.00	48.05	PK	74	25.95	36.39	37.44	9.22	35	11.66
7311.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2462		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)
4924.00	57.17	PK	74	16.83	52.39	33.71	6.98	35.91	4.78
4924.00	50.64	AV	54	3.36	45.86	33.71	6.98	35.91	4.78
5105.50	44.58	PK	74	29.42	37.41	34.34	7.09	34.27	7.17
5105.50	--	AV	54	--	--	--	--	--	--
7386.00	47.34	PK	74	26.66	35.46	37.61	9.25	34.98	11.88
7386.00	--	AV	54	--	--	--	--	--	--


Frequency(MHz):			2462		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)
4924.00	58.18	PK	74	15.82	53.4	33.71	6.98	35.91	4.78
4924.00	51.86	AV	54	2.14	47.08	33.71	6.98	35.91	4.78
5105.50	43.23	PK	74	30.77	36.06	34.34	7.09	34.27	7.17
5105.50	--	AV	54	--	--	--	--	--	--
7386.00	47.04	PK	74	26.96	35.16	37.61	9.25	34.98	11.88
7386.00	--	AV	54	--	--	--	--	--	--

REMARKS:


1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RMS detector is for AV value.

Results of Band Edges Test (Radiated)


Note: 802.11b/802.11g/802.11n(H20)/802.11n(H40) all have been tested, only worse case 802.11b is reported




Mark	Frequency MHz	Level dBuV	Factor dB	Reading dBuV	Limit dB	Margin dB	Det.	Polarization
1	2353.20	51.70	33.14	18.56	74.00	22.30	Peak	HORIZONTAL
2	2390.04	51.68	33.39	18.29	74.00	22.32	Peak	HORIZONTAL
3	2400.00	51.65	33.39	18.26	74.00	22.35	Peak	HORIZONTAL
4	2411.52	86.34	33.44	52.90	74.00	-12.34	Peak	HORIZONTAL





Mark	Frequency MHz	Level dBuV	Factor dB	Reading dBuV	Limit dB	Margin dB	Det.	Polarization
1	2363.16	52.96	33.14	19.82	74.00	21.04	Peak	VERTICAL
2	2390.04	52.46	33.39	19.07	74.00	21.54	Peak	VERTICAL
3	2400.00	52.53	33.39	19.14	74.00	21.47	Peak	VERTICAL
4	2412.60	85.34	33.44	51.90	74.00	-11.34	Peak	VERTICAL





Mark	Frequency MHz	Level dBuV	Factor dB	Reading dBuV	Limit dB	Margin dB	Det.	Polarization
1	2364.36	33.73	33.14	0.59	54.00	20.27	Average	HORIZONTAL
2	2390.04	33.53	33.39	0.14	54.00	20.47	Average	HORIZONTAL
3	2400.00	33.64	33.39	0.25	54.00	20.36	Average	HORIZONTAL
4	2412.96	68.78	33.44	35.34	54.00	-14.78	Average	HORIZONTAL



Mark	Frequency MHz	Level dBuV	Factor dB	Reading dBuV	Limit dB	Margin dB	Det.	Polarization
1	2363.16	33.40	33.14	0.26	54.00	20.60	Average	VERTICAL
2	2390.04	33.35	33.39	-0.04	54.00	20.65	Average	VERTICAL
3	2400.00	34.00	33.39	0.61	54.00	20.00	Average	VERTICAL
4	2411.16	68.11	33.44	34.67	54.00	-14.11	Average	VERTICAL





3.3. Maximum Conducted Output Power


Limit

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

WIFI				
Type	Channel	Output power PK (dBm)	Limit (dBm)	Result
802.11b	01	8.31	30.00	Pass
	06	9.02		
	11	9.46		
802.11g	01	8.27	30.00	Pass
	06	9.12		
	11	9.50		
802.11n(HT20)	01	7.64	30.00	Pass
	06	9.58		
	11	9.44		
802.11n(HT40)	03	7.77	30.00	Pass
	06	7.86		
	09	8.68		

Note: 1.The test results including the cable lose.

3.4. Power Spectral Density

Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW ≥ 3 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

Test Configuration




Test Results


WIFI				
Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-23.527	8.00	Pass
	06	-22.998		
	11	-22.540		
802.11g	01	-28.035	8.00	Pass
	06	-27.340		
	11	-26.732		
802.11n(HT20)	01	-27.945	8.00	Pass
	06	-26.979		
	11	-26.039		
802.11n(HT40)	03	-29.561	8.00	Pass
	06	-30.319		
	09	-31.922		

Test plot as follows:


802.11b




802.11g




CH01




CH01



CH06



CH06




CH11




CH11




802.11n(HT20)




802.11n(HT40)




CH01




CH03



CH06



CH06



CH11



CH09



3.5. 6dB Bandwidth

Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

Test Configuration




Test Results


WIFI					
Type	Channel	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit (KHz)	Result
802.11b	01	9.960	14.298	≥500	Pass
	06	9.957	14.242		
	11	9.557	14.292		
802.11g	01	16.59	16.538	≥500	Pass
	06	16.57	16.477		
	11	16.57	16.489		
802.11n(HT20)	01	17.82	17.667	≥500	Pass
	06	17.79	17.661		
	11	17.76	17.653		
802.11n(HT40)	03	36.46	36.051	≥500	Pass
	06	36.44	36.050		
	09	36.43	36.100		

Test plot as follows:


802.11b




802.11g




CH01




CH01



CH06



CH06




CH11




CH11




802.11n(HT20)




802.11n(HT40)




CH01




CH03




CH06




CH06



CH11



CH09



3.6. Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section (b)(3) of §15.247, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in §15.209(a) are not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector , and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration




Test Results


Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandage measurement data.

Test plot as follows:



802.11b CH01



802.11b CH06




Reference



30MHz-3GHz




30MHz-3GHz




3GHz-25GHz

3GHz-25GHz


802.11b CH11




802.11g CH01




Reference




Reference



30MHz-3GHz




30MHz-3GHz




3GHz-25GHz

3GHz-25GHz


802.11g CH06




802.11g CH11




Reference




Reference



30MHz-3GHz




30MHz-3GHz




3GHz-25GHz

3GHz-25GHz



802.11n(HT20) CH01





802.11n(HT20) CH06



Reference




30MHz-3GHz




3GHz-25GHz

3GHz-25GHz


802.11n(HT20) CH11




802.11n(HT40) CH03




Reference




Reference



30MHz-3GHz




30MHz-3GHz




3GHz-25GHz

3GHz-25GHz


802.11n(HT40) CH06




802.11n(HT40) CH09




Reference




Reference



30MHz-3GHz




30MHz-3GHz




3GHz-25GHz


3GHz-25GHz

Band-edge Measurements for RF Conducted Emissions:**802.11b**


Left bandedge




Right bandedge

802.11g


Left bandedge



Right bandedge


802.11n(HT20)

Left bandedge



Right bandedge

802.11n(HT40)



Left bandedge



Right bandedge



3.7. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result:

The maximum gain of antenna was 0dBi.





4. Test Setup Photos of the EUT




5. Photos of the EUT


External Photos of EUT












Internal Photos of EUT







***** End of Report *****

