



FCC Part 15C Test Report

FCC ID: 2ADW6KS-18A

Product Name:	Balance of electric car
Trademark:	N/A
Model Name :	KS-18A
Prepared For :	Shenzhen King Song Sports Equipment Co., Ltd
Address :	5th Floor, Bld.A, Taiyufeng Industry Park, Queshan Road, Dalang Street, Longhua, Shenzhen,China
Prepared By :	Shenzhen BCTC Technology Co., Ltd.
Address :	No.101,Yousong Road,Longhua New District, Shenzhen,China
Test Date:	Nov. 2 – Nov. 12, 2015
Date of Report :	Nov. 14, 2015
Report No.:	BCTC-151012455



VERIFICATION OF COMPLIANCE

Applicant's name : **Shenzhen King Song Sports Equipment Co., Ltd**
Address : 5th Floor, Bld.A, Taiyufeng Industry Park, Queshan Road, Dalang Street, Longhua, Shenzhen, China
Manufacture's Name : **Shenzhen King Song Sports Equipment Co., Ltd**
Address : 5th Floor, Bld.A, Taiyufeng Industry Park, Queshan Road, Dalang Street, Longhua, Shenzhen, China

Product description

Product name : Balance of electric car
Trademark: N/A
Model Name: KS-18A
Test procedure FCC Part15.249
Standards ANSI C63.10-2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Test Result.....: **Pass**

Testing Engineer :

Eric Yang

(Eric Yang)

Technical Manager :

Sophie Lee

(Sophia Lee)

Authorized Signatory :

Carson. Zhang



(Carson. Zhang)



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	8
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3 . EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	10
3.1.2 TEST PROCEDURE	11
3.1.3 DEVIATION FROM TEST STANDARD	11
3.1.4 TEST SETUP	11
3.1.5 EUT OPERATING CONDITIONS	11
3.1.6 TEST RESULTS	12
3.2 RADIATED EMISSION MEASUREMENT	14
3.2.1 RADIATED EMISSION LIMITS	14
3.2.2 TEST PROCEDURE	15
3.2.3 DEVIATION FROM TEST STANDARD	15
3.2.4 TEST SETUP	16
3.2.5 EUT OPERATING CONDITIONS	17
3.2.6 TEST RESULTS	18
4 . BANDWIDTH TEST	27
4.1 APPLIED PROCEDURES / LIMIT	27
4.1.1 TEST PROCEDURE	27
4.1.2 DEVIATION FROM STANDARD	27
4.1.3 TEST SETUP	27
4.1.4 EUT OPERATION CONDITIONS	27
4.1.5 TEST RESULTS	28
5 . OUTSIDE OF THE SPECIFIED FREQUENCY BANDS	35
5.1 DEVIATION FROM STANDARD	35
5.2 TEST SETUP	35
5.3 EUT OPERATION CONDITIONS	35
5.4 TEST RESULTS	36



Table of Contents

Page

6 . ANTENNA REQUIREMENT	40
6.1 STANDARD REQUIREMENT	40
6.2 EUT ANTENNA	40
7 . EUT TEST PHOTO	41
8 . PHOTO OF THE EUT	43



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.249	Radiated Spurious Emission	PASS	
15.249	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add.:No.101,Yousong Road,Longhua New District, Shenzhen,China

FCC Registration No.:187086

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Balance of electric car
Trade Name	N/A
Model Name	KS-18A
Product Description	Operation Frequency: 2402~2480 MHz
	Modulation Type: GFSK,PI/4 DPSK,8DPSK
	Bit Rate of Transmitter 1M/2M/3Mbps
	Number Of Channel 79 CH
	Antenna Designation: Please see Note 3.
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.
Channel List	Please refer to the Note 2.
Adapter	DC 67.2V from adapter
Battery	DC 59.2V
Connecting I/O Port(s)	Please refer to the User's Manual
hardware version	--
Software version	--
Serial number	--

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468



13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Internal Antenna	N/A	0	
2	N/A	N/A	Internal Antenna	N/A	0.5	

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

For Conducted & Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Fully-charged battery is used during the test




2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS


Frequency	2402 MHz	2441 MHz	2480 MHz
Channel	Low	Middle	High

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Balance of electric car	N/A	KS-18A	01	EUT
E-2	Adapter	N/A	GJS-672200	N/A	I/P: AC 100~240V 50/60Hz O/P: DC 67.2V/2A

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	1.0M	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESCI	1166.5950K03-101165-ha	2015.06.06	2016.06.05
2	LISN	R&S	NSLK8126	8126466	2015.08.24	2016.08.23
3	LISN	R&S	NSLK8126	8126487	2015.08.24	2016.08.23
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.06	2016.06.05
5	RF cables	R&S	R204	R20X	2015.06.06	2016.06.05

Radiation test, Band-edge test and 20db bandwidth test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.06.06	2016.06.05
2	Test Receiver	R&S	ESPI	101318	2015.06.06	2016.06.05
3	Bilog Antenna	R&S	VULB 9168	VULB91 68-438	2015.06.06	2016.06.05
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.06	2016.06.05
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.06	2016.06.05
6	Horn Antenna	R&S	HF906	10027	2015.06.06	2016.06.05
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.06.06	2016.06.05
8	Amplifier	R&S	BBV9743	9743-019	2014.12.22	2015.12.21
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.06	2016.06.05
10	RF cables	R&S	R203	R20X	2015.06.06	2016.06.05
11	Antenna connector	Florida RFLabs	Lab-Fle	RF 01#	2015.06.06	2016.06.05



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quas -peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The data only show the worst mode.




3.1.6 TEST RESULTS

EUT :	Balance of electric car	Model Name :	KS-18A
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 67.2V from PC input AC 120V/60Hz	Test Mode :	Link Mode(Worst Mode)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector Comment
1		0.1580	44.39	10.05	54.44	65.56	-11.12	QP
2		0.1580	36.50	10.05	46.55	55.56	-9.01	AVG
3		0.4740	35.39	10.11	45.50	56.44	-10.94	QP
4	*	0.4740	31.47	10.11	41.58	46.44	-4.86	AVG
5		1.1100	30.79	10.17	40.96	56.00	-15.04	QP
6		1.1100	28.71	10.17	38.88	46.00	-7.12	AVG
7		3.4940	30.61	10.18	40.79	56.00	-15.21	QP
8		3.4940	25.34	10.18	35.52	46.00	-10.48	AVG
9		10.6380	29.04	10.13	39.17	60.00	-20.83	QP
10		10.6380	21.82	10.13	31.95	50.00	-18.05	AVG
11		15.1340	35.11	10.15	45.26	60.00	-14.74	QP
12		15.1340	27.22	10.15	37.37	50.00	-12.63	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.






EUT :	Balance of electric car	Model Name :	KS-18A
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 67.2V from PC input AC 120V/60Hz	Test Mode :	Link Mode(Worst Mode)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1620	52.79	10.05	62.84	65.36	-2.52	QP	
2	*	0.1620	44.70	10.05	54.75	55.36	-0.61	AVG	
3		0.7980	38.22	10.14	48.36	56.00	-7.64	QP	
4		0.7980	34.86	10.14	45.00	46.00	-1.00	AVG	
5		2.3380	34.12	10.18	44.30	56.00	-11.70	QP	
6		2.3380	30.14	10.18	40.32	46.00	-5.68	AVG	
7		7.2820	33.92	10.10	44.02	60.00	-15.98	QP	
8		7.2820	28.56	10.10	38.66	50.00	-11.34	AVG	
9		15.8500	44.55	10.15	54.70	60.00	-5.30	QP	
10		15.8500	37.80	10.15	47.95	50.00	-2.05	AVG	
11		19.4619	42.51	10.17	52.68	60.00	-7.32	QP	
12		19.4619	35.98	10.17	46.15	50.00	-3.85	AVG	

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
--------------------	---------



Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 1.5 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.
- For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.6 TEST RESULTS

Radiated Spurious Emission (Below 30MHz)

EUT :	Balance of electric car	Model Name :	KS-18A
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Polarization :	---
Test Voltage :	DC 59.2V		
Test Mode :	TX		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



Radiated Spurious Emission (Between 30MHz – 1GHz)

EUT :	Balance of electric car	Model Name :	KS-18A
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 59.2V		
Test Mode : (Worst)	Link Mode		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	33.0950	45.64	-8.39	37.25	40.00	-2.75	QP		
2	!	42.8998	44.31	-9.21	35.10	40.00	-4.90	QP		
3	!	82.9385	54.08	-18.12	35.96	40.00	-4.04	QP		
4		119.8556	50.80	-14.72	36.08	43.50	-7.42	QP		
5		336.0352	47.52	-11.66	35.86	46.00	-10.14	QP		
6		601.4265	43.66	-5.66	38.00	46.00	-8.00	QP		

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Pretest all mode, the data only show the worst mode.

If peak level comply with Quasi-Peak limit, then the Quasi-Peak level is deemed to comply with Quasi-Peak limit.





EUT :	Balance of electric car	Model Name :	KS-18A
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 59.2V		
Test Mode : (Worst)	Link Mode		


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		83.8156	45.61	-18.13	27.48	40.00	-12.52	QP		
2		119.8556	48.05	-14.72	33.33	43.50	-10.17	QP		
3		239.9874	49.18	-14.49	34.69	46.00	-11.31	QP		
4		300.3672	46.29	-12.57	33.72	46.00	-12.28	QP		
5	*	801.7863	42.11	-2.49	39.62	46.00	-6.38	QP		
6		962.1623	42.49	-0.42	42.07	54.00	-11.93	QP		

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Pretest all mode, the data only show the worst mode.

If peak level comply with Quasi-Peak limit, then the Quasi-Peak level is deemed to comply with Quasi-Peak limit.





Radiated Spurious Emission (1GHz to 25GHz)

Module 1

GFSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	103.24	PK	H	1.31	104.55	114.00	Pass
	2402.00	89.00	Ave	H	1.31	90.31	94.00	Pass
	4804.00	57.76	PK	H	-1.06	56.70	74.00	Pass
	4804.00	48.77	Ave	H	-1.06	47.71	54.00	Pass
	2402.00	102.16	PK	V	1.31	103.47	114.00	Pass
	2402.00	88.28	Ave	V	1.31	89.59	94.00	Pass
	4804.00	58.77	PK	V	-1.06	57.71	74.00	Pass
	4804.00	47.28	Ave	V	-1.06	46.22	54.00	Pass
	2441.00	103.09	PK	H	0.85	103.94	114.00	Pass
	2441.00	88.53	Ave	H	0.85	89.38	94.00	Pass
Middle Channel 2441MHz	4882.00	54.59	PK	H	-0.62	53.97	74.00	Pass
	4882.00	43.74	Ave	H	-0.62	43.12	54.00	Pass
	2441.00	101.89	PK	V	0.85	102.74	114.00	Pass
	2441.00	86.96	Ave	V	0.85	87.81	94.00	Pass
	4882.00	54.91	PK	V	-0.62	54.29	74.00	Pass
	4882.00	44.33	Ave	V	-0.62	43.71	54.00	Pass
	2480.00	102.20	PK	H	0.53	102.73	114.00	Pass
	2480.00	87.65	Ave	H	0.53	88.18	94.00	Pass
Upper Channel 2480MHz	4960.00	52.14	PK	H	-0.24	51.90	74.00	Pass
	4960.00	43.17	Ave	H	-0.24	42.93	54.00	Pass
	2480.00	101.34	PK	V	0.53	101.87	114.00	Pass
	2480.00	86.93	Ave	V	0.53	87.46	94.00	Pass
	4960.00	54.30	PK	V	-0.24	54.06	74.00	Pass
	4960.00	43.38	Ave	V	-0.24	43.14	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.



PI/4 DPSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	102.06	PK	H	1.31	103.37	114.00	Pass
	2402.00	88.00	Ave	H	1.31	89.31	94.00	Pass
	4804.00	57.10	PK	H	-1.06	56.04	74.00	Pass
	4804.00	48.23	Ave	H	-1.06	47.17	54.00	Pass
	2402.00	101.00	PK	V	1.31	102.31	114.00	Pass
	2402.00	87.29	Ave	V	1.31	88.60	94.00	Pass
	4804.00	58.12	PK	V	-1.06	57.06	74.00	Pass
	4804.00	46.74	Ave	V	-1.06	45.68	54.00	Pass
	2441.00	101.93	PK	H	0.85	102.78	114.00	Pass
	2441.00	87.54	Ave	H	0.85	88.39	94.00	Pass
Middle Channel 2441MHz	4882.00	53.98	PK	H	-0.62	53.36	74.00	Pass
	4882.00	43.26	Ave	H	-0.62	42.64	54.00	Pass
	2441.00	100.75	PK	V	0.85	101.60	114.00	Pass
	2441.00	85.99	Ave	V	0.85	86.84	94.00	Pass
	4882.00	54.29	PK	V	-0.62	53.67	74.00	Pass
	4882.00	43.83	Ave	V	-0.62	43.21	54.00	Pass
	2480.00	101.03	PK	H	0.53	101.56	114.00	Pass
	2480.00	86.67	Ave	H	0.53	87.20	94.00	Pass
Upper Channel 2480MHz	4960.00	51.55	PK	H	-0.24	51.31	74.00	Pass
	4960.00	42.69	Ave	H	-0.24	42.45	54.00	Pass
	2480.00	100.20	PK	V	0.53	100.73	114.00	Pass
	2480.00	85.96	Ave	V	0.53	86.49	94.00	Pass
	4960.00	53.69	PK	V	-0.24	53.45	74.00	Pass
	4960.00	42.89	Ave	V	-0.24	42.65	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.



8DPSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	102.62	PK	H	1.31	103.93	114.00	Pass
	2402.00	88.48	Ave	H	1.31	89.79	94.00	Pass
	4804.00	57.41	PK	H	-1.06	56.35	74.00	Pass
	4804.00	48.49	Ave	H	-1.06	47.43	54.00	Pass
	2402.00	101.55	PK	V	1.31	102.86	114.00	Pass
	2402.00	87.77	Ave	V	1.31	89.08	94.00	Pass
	4804.00	58.43	PK	V	-1.06	57.37	74.00	Pass
	4804.00	47.00	Ave	V	-1.06	45.94	54.00	Pass
	2441.00	102.49	PK	H	0.85	103.34	114.00	Pass
	2441.00	88.01	Ave	H	0.85	88.86	94.00	Pass
Middle Channel 2441MHz	4882.00	54.27	PK	H	-0.62	53.65	74.00	Pass
	4882.00	43.49	Ave	H	-0.62	42.87	54.00	Pass
	2441.00	101.29	PK	V	0.85	102.14	114.00	Pass
	2441.00	86.45	Ave	V	0.85	87.30	94.00	Pass
	4882.00	54.58	PK	V	-0.62	53.96	74.00	Pass
	4882.00	44.07	Ave	V	-0.62	43.45	54.00	Pass
	2480.00	101.58	PK	H	0.53	102.11	114.00	Pass
	2480.00	87.14	Ave	H	0.53	87.67	94.00	Pass
Upper Channel 2480MHz	4960.00	51.83	PK	H	-0.24	51.59	74.00	Pass
	4960.00	42.92	Ave	H	-0.24	42.68	54.00	Pass
	2480.00	100.75	PK	V	0.53	101.28	114.00	Pass
	2480.00	86.42	Ave	V	0.53	86.95	94.00	Pass
	4960.00	53.99	PK	V	-0.24	53.75	74.00	Pass
	4960.00	43.12	Ave	V	-0.24	42.88	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.


Module 2
GFSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	103.12	PK	H	1.31	104.43	114.00	Pass
	2402.00	88.90	Ave	H	1.31	90.21	94.00	Pass
	4804.00	57.69	PK	H	-1.06	56.63	74.00	Pass
	4804.00	48.72	Ave	H	-1.06	47.66	54.00	Pass
	2402.00	102.04	PK	V	1.31	103.35	114.00	Pass
	2402.00	88.18	Ave	V	1.31	89.49	94.00	Pass
	4804.00	58.70	PK	V	-1.06	57.64	74.00	Pass
	4804.00	47.23	Ave	V	-1.06	46.17	54.00	Pass
	2441.00	102.97	PK	H	0.85	103.82	114.00	Pass
	2441.00	88.43	Ave	H	0.85	89.28	94.00	Pass
Middle Channel 2441MHz	4882.00	54.53	PK	H	-0.62	53.91	74.00	Pass
	4882.00	43.69	Ave	H	-0.62	43.07	54.00	Pass
	2441.00	102.88	PK	V	0.85	103.73	114.00	Pass
	2441.00	87.81	Ave	V	0.85	88.66	94.00	Pass
	4882.00	55.45	PK	V	-0.62	54.83	74.00	Pass
	4882.00	44.76	Ave	V	-0.62	44.14	54.00	Pass
	2480.00	103.19	PK	H	0.53	103.72	114.00	Pass
	2480.00	88.51	Ave	H	0.53	89.04	94.00	Pass
Upper Channel 2480MHz	4960.00	52.65	PK	H	-0.24	52.41	74.00	Pass
	4960.00	43.59	Ave	H	-0.24	43.35	54.00	Pass
	2480.00	102.33	PK	V	0.53	102.86	114.00	Pass
	2480.00	87.78	Ave	V	0.53	88.31	94.00	Pass
	4960.00	54.83	PK	V	-0.24	54.59	74.00	Pass
	4960.00	43.80	Ave	V	-0.24	43.56	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.



PI/4 DPSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	103.26	PK	H	1.31	104.57	114.00	Pass
	2402.00	89.21	Ave	H	1.31	90.52	94.00	Pass
	4804.00	55.98	PK	H	-1.06	54.92	74.00	Pass
	4804.00	47.12	Ave	H	-1.06	46.06	54.00	Pass
	2402.00	102.20	PK	V	1.31	103.51	114.00	Pass
	2402.00	88.50	Ave	V	1.31	89.81	94.00	Pass
	4804.00	56.99	PK	V	-1.06	55.93	74.00	Pass
	4804.00	45.62	Ave	V	-1.06	44.56	54.00	Pass
Middle Channel 2441MHz	2441.00	102.67	PK	H	0.85	103.52	114.00	Pass
	2441.00	88.29	Ave	H	0.85	89.14	94.00	Pass
	4882.00	53.30	PK	H	-0.62	52.68	74.00	Pass
	4882.00	42.59	Ave	H	-0.62	41.97	54.00	Pass
	2441.00	102.58	PK	V	0.85	103.43	114.00	Pass
	2441.00	87.68	Ave	V	0.85	88.53	94.00	Pass
	4882.00	54.20	PK	V	-0.62	53.58	74.00	Pass
	4882.00	43.64	Ave	V	-0.62	43.02	54.00	Pass
Upper Channel 2480MHz	2480.00	102.55	PK	H	0.53	103.08	114.00	Pass
	2480.00	88.05	Ave	H	0.53	88.58	94.00	Pass
	4960.00	51.81	PK	H	-0.24	51.57	74.00	Pass
	4960.00	42.87	Ave	H	-0.24	42.63	54.00	Pass
	2480.00	101.71	PK	V	0.53	102.24	114.00	Pass
	2480.00	87.33	Ave	V	0.53	87.86	94.00	Pass
	4960.00	53.98	PK	V	-0.24	53.74	74.00	Pass
	4960.00	43.07	Ave	V	-0.24	42.83	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.



8DPSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	102.50	PK	H	1.31	103.81	114.00	Pass
	2402.00	88.38	Ave	H	1.31	89.69	94.00	Pass
	4804.00	57.35	PK	H	-1.06	56.29	74.00	Pass
	4804.00	48.44	Ave	H	-1.06	47.38	54.00	Pass
	2402.00	101.44	PK	V	1.31	102.75	114.00	Pass
	2402.00	87.67	Ave	V	1.31	88.98	94.00	Pass
	4804.00	58.36	PK	V	-1.06	57.30	74.00	Pass
	4804.00	46.94	Ave	V	-1.06	45.88	54.00	Pass
	2441.00	102.37	PK	H	0.85	103.22	114.00	Pass
	2441.00	87.91	Ave	H	0.85	88.76	94.00	Pass
Middle Channel 2441MHz	4882.00	54.21	PK	H	-0.62	53.59	74.00	Pass
	4882.00	43.44	Ave	H	-0.62	42.82	54.00	Pass
	2441.00	102.28	PK	V	0.85	103.13	114.00	Pass
	2441.00	87.30	Ave	V	0.85	88.15	94.00	Pass
	4882.00	55.12	PK	V	-0.62	54.50	74.00	Pass
	4882.00	44.50	Ave	V	-0.62	43.88	54.00	Pass
	2480.00	102.57	PK	H	0.53	103.10	114.00	Pass
	2480.00	87.99	Ave	H	0.53	88.52	94.00	Pass
Upper Channel 2480MHz	4960.00	52.33	PK	H	-0.24	52.09	74.00	Pass
	4960.00	43.34	Ave	H	-0.24	43.10	54.00	Pass
	2480.00	101.73	PK	V	0.53	102.26	114.00	Pass
	2480.00	87.27	Ave	V	0.53	87.80	94.00	Pass
	4960.00	54.52	PK	V	-0.24	54.28	74.00	Pass
	4960.00	43.54	Ave	V	-0.24	43.30	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.



4. BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.249	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30KHz
VB	$\geq$ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW $\geq$ RBW, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



4.1.5 TEST RESULTS


EUT :	Balance of electric car	Model Name :	KS-18A
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	By Battery
Test Mode :	CH00 / CH39 / C78		


		Frequency	20dB Bandwidth (MHz)	Result
Module 1	GFSK	2402 MHz	0.831	PASS
		2441 MHz	0.841	PASS
		2480 MHz	0.839	PASS
	PI/4 DPSK	2402 MHz	1.036	PASS
		2441 MHz	1.034	PASS
		2480 MHz	1.032	PASS
	8DPSK	2402 MHz	1.129	PASS
		2441 MHz	1.120	PASS
		2480 MHz	1.128	PASS
Module 2	GFSK	2402 MHz	0.836	PASS
		2441 MHz	0.836	PASS
		2480 MHz	0.839	PASS
	PI/4 DPSK	2402 MHz	1.042	PASS
		2441 MHz	1.041	PASS
		2480 MHz	1.040	PASS
	8DPSK	2402 MHz	1.134	PASS
		2441 MHz	1.139	PASS
		2480 MHz	1.140	PASS




Module 1



GFSK





8DPSK










Module 2



GFSK





8DPSK







5. OUTSIDE OF THE SPECIFIED FREQUENCY BANDS

APPLICABLE STANDARD

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1.5 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- e. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

The bandwidth of the Spectrum's setting.

For the radiated test of band-edge above 1GHz:

Restricted band: RBW=1MHz, VBW=3MHz

Non-restricted band: RBW=100kHz, VBW=300kHz

For all tests, it used peak detector.

Note:

Both horizontal and vertical antenna polarities were tested

and performed pretest to three orthogonal axis. The worst case emissions were reported

5.1 DEVIATION FROM STANDARD

No deviation.

5.2 TEST SETUP

5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



5.4 TEST RESULTS

EUT :	Balance of electric car	Model Name :	KS-18A
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 59.2V
Test Mode :	CH00/ CH78		

Module 1

		Frequency (MHz)	Antenna polarization (H/V)	Test Frequency (MHz)	Emission (dBuV/m)	Band edge Limit (dBuV/m)		Result
					PK	PK	AV	
GFSK	Hopping	<2400	H	2397.94	50.08	74.00	54.00	Pass
		<2400	V	2398.06	49.34	74.00	54.00	Pass
		>2483.5	H	2487.62	49.22	74.00	54.00	Pass
		>2483.5	V	2488.06	49.78	74.00	54.00	Pass
	Unhopping	<2400	H	2397.61	49.40	74.00	54.00	Pass
		<2400	V	2397.29	49.15	74.00	54.00	Pass
		>2483.5	H	2486.95	49.44	74.00	54.00	Pass
		>2483.5	V	2487.27	49.87	74.00	54.00	Pass
8DPSK	Hopping	<2400	H	2397.68	49.92	74.00	54.00	Pass
		<2400	V	2398.35	49.42	74.00	54.00	Pass
		>2483.5	H	2487.42	49.29	74.00	54.00	Pass
		>2483.5	V	2488.74	49.93	74.00	54.00	Pass
	Unhopping	<2400	H	2397.26	49.72	74.00	54.00	Pass
		<2400	V	2397.38	49.36	74.00	54.00	Pass
		>2483.5	H	2486.46	49.26	74.00	54.00	Pass
		>2483.5	V	2487.45	49.83	74.00	54.00	Pass

If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



Module 2

		Frequency (MHz)	Antenna polarization (H/V)	Test Frequency (MHz)	Emission (dBuV/m)	Band edge Limit (dBuV/m)		Result
					PK	PK	AV	
GFSK	Hopping	<2400	H	2397.62	50.08	74.00	54.00	Pass
		<2400	V	2398.74	49.34	74.00	54.00	Pass
		>2483.5	H	2487.27	49.22	74.00	54.00	Pass
		>2483.5	V	2488.30	49.78	74.00	54.00	Pass
	Unhopping	<2400	H	2397.69	49.40	74.00	54.00	Pass
		<2400	V	2397.35	49.15	74.00	54.00	Pass
		>2483.5	H	2486.47	49.44	74.00	54.00	Pass
		>2483.5	V	2487.62	49.87	74.00	54.00	Pass
8DPSK	Hopping	<2400	H	2397.31	49.92	74.00	54.00	Pass
		<2400	V	2398.22	49.42	74.00	54.00	Pass
		>2483.5	H	2487.67	49.29	74.00	54.00	Pass
		>2483.5	V	2488.61	49.93	74.00	54.00	Pass
	Unhopping	<2400	H	2397.38	49.72	74.00	54.00	Pass
		<2400	V	2397.76	49.36	74.00	54.00	Pass
		>2483.5	H	2486.45	49.26	74.00	54.00	Pass
		>2483.5	V	2487.64	49.83	74.00	54.00	Pass

If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.





For Conducted:

We pretest all mode, the worst mode was Module 1 GFSK mode.



Unhopping

GFSK





Hopping





6. ANTENNA REQUIREMENT

6.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 EUT ANTENNA

The EUT antenna is PCB antenna. It complies with the standard requirement.

7. EUT TEST PHOTO

Radiated Measurement Photos





Conducted Emission



8. PHOTO OF THE EUT



