

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
MODULAR ROBOTICS INCORPORATED

BTLE and Battery blocks
Model No.: mo-bk-BTLE-1, mo-bk-battery 1X-1, mo-kt-z1600-1
FCC ID: 2ADWM-BTLE

Prepared for : MODULAR ROBOTICS INCORPORATED
Address : 3085 BLUFF ST BOULDER COLORADO 80301
USA
Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Chan Yuan New Material Port, Keyuan
Rd. Science & Industry Park, Nan Shan, Shenzhen,
Guangdong P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20142409
Date of Test : Dec 04-12,2014
Date of Report : Dec 15,2014

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	5
1.2. Carrier Frequency of Channels	6
1.3. Special Accessory and Auxiliary Equipment	6
1.4. Description of Test Facility	7
1.5. Measurement Uncertainty	7
2. MEASURING DEVICE AND TEST EQUIPMENT	8
3. OPERATION OF EUT DURING TESTING	9
3.1. Operating Mode	9
3.2. Configuration and peripherals	9
4. TEST PROCEDURES AND RESULTS	10
5. 6DB BANDWIDTH MEASUREMENT	11
5.1. Block Diagram of Test Setup.....	11
5.2. The Requirement For Section 15.247(a)(2).....	11
5.3. EUT Configuration on Measurement	11
5.4. Operating Condition of EUT	11
5.5. Test Procedure	12
5.6. Test Result	12
6. MAXIMUM PEAK OUTPUT POWER	14
6.1. Block Diagram of Test Setup.....	14
6.2. The Requirement For Section 15.247(b)(3).....	14
6.3. EUT Configuration on Measurement	14
6.4. Operating Condition of EUT	14
6.5. Test Procedure	15
6.6. Test Result	15
7. POWER SPECTRAL DENSITY MEASUREMENT	17
7.1. Block Diagram of Test Setup.....	17
7.2. The Requirement For Section 15.247(e).....	17
7.3. EUT Configuration on Measurement	17
7.4. Operating Condition of EUT	17
7.5. Test Procedure	18
7.6. Test Result	19
8. BAND EDGE COMPLIANCE TEST	21
8.1. Block Diagram of Test Setup.....	21
8.2. The Requirement For Section 15.247(d)	21
8.3. EUT Configuration on Measurement	21
8.4. Operating Condition of EUT	22
8.5. Test Procedure	22
8.6. Test Result	22
9. RADIATED SPURIOUS EMISSION TEST	28
9.1. Block Diagram of Test Setup.....	28
9.2. The Limit For Section 15.247(d)	29
9.3. Restricted bands of operation	29
9.4. Configuration of EUT on Measurement	30

9.5.	Operating Condition of EUT	30
9.6.	Test Procedure	30
9.7.	The Field Strength of Radiation Emission Measurement Results	31
10.	CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST	43
10.1.	Block Diagram of Test Setup.....	43
10.2.	The Requirement of Section 15.247(d).....	43
10.3.	EUT Configuration on Measurement	43
10.4.	Operating Condition of EUT	44
10.5.	Test Procedure	44
10.6.	Test Result	44
11.	POWER LINE CONDUCTED MEASUREMENT	47
11.1.	Block Diagram of Test Setup.....	47
11.2.	Power Line Conducted Emission Measurement Limits.....	47
11.3.	Configuration of EUT on Measurement	47
11.4.	Operating Condition of EUT	47
11.5.	Test Procedure	48
11.6.	Power Line Conducted Emission Measurement Results	48
12.	ANTENNA REQUIREMENT.....	51
12.1.	The Requirement	51
12.2.	Antenna Construction	51

Test Report Certification

Applicant : MODULAR ROBOTICS INCORPORATED

Manufacturer : MODULAR ROBOTICS INCORPORATED

EUT Description : BTLE and Battery blocks

(A) MODEL NO.: mo-bk-BTLE-1, mo-bk-battery 1X-1, mo-kt-z1600-1

(B) Trade Name.: N/A

(C) POWER SUPPLY: DC 5V (USB Port) or DC 3.7V(Battery)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.4: 2009

The EUT was tested according to DTS test procedure of Jun 05, 2014 KDB558074 D01 DTS Meas Guidance v03r02 for compliance to FCC 47CFR 15.247 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Dec 04-12,2014

Date of Report : Dec 15,2014

Prepared by :


(Eric Zhang , Engineer)

Approved & Authorized Signer :


(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	BTLE and Battery blocks
Model Number	:	mo-bk-BTLE-1, mo-bk-battery 1X-1, mo-kt-z1600-1 (Note: These samples are same except for the model number and colors are different. So we prepare the mo-bk-BTLE-1 for test.)
Frequency Range	:	2402-2480MHz
Number of Channels	:	40
BT Version	:	4.0
Antenna Gain	:	0dBi
Power Supply	:	DC 5V (USB Port) or DC 3.7V(Battery)
Modulation mode	:	GFSK
Applicant	:	MODULAR ROBOTICS INCORPORATED
Address	:	3085 BLUFF ST BOULDER COLORADO 80301 USA
Manufacturer	:	MODULAR ROBOTICS INCORPORATED
Address	:	3085 BLUFF ST BOULDER COLORADO 80301 USA
Date of sample received	:	Dec 04,2014
Date of Test	:	Dec 04-12,2014

1.2.Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

1.3.Special Accessory and Auxiliary Equipment

N/A

1.4. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee
for Laboratories
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

1.5. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 11, 2014	Jan. 10, 2015
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 11, 2014	Jan. 10, 2015
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2014	Jan. 10, 2015
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 11, 2014	Jan. 10, 2015
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2014	Jan. 14, 2015
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 15, 2014	Jan. 14, 2015
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 11, 2014	Jan. 10, 2015
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 11, 2014	Jan. 10, 2015
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 11, 2014	Jan. 10, 2015
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 11, 2014	Jan. 10, 2015

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode


The mode is used: **BLE Transmitting mode**

Low Channel: 2402MHz

Middle Channel: 2440MHz

High Channel: 2480MHz

3.2.Configuration and peripherals



4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Power Line Conducted Emission	Compliant
Section 15.247(a)(2)	6dB Bandwidth Test	Compliant
Section 15.247(e)	Power Spectral Density Test	Compliant
Section 15.247(b)(3)	Maximum Peak Output Power Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.247(d) Section 15.209	Radiated Spurious Emission Test	Compliant
Section 15.247(d)	Conducted Spurious Emission Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 6DB BANDWIDTH MEASUREMENT

5.1. Block Diagram of Test Setup



(EUT: BTLE and Battery blocks)

5.2. The Requirement For Section 15.247(a)(2)

Section 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.3. EUT Configuration on Measurement

The equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.


5.5.3. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

5.6. Test Result


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit(MHz)	PASS/FAIL
0	2402	0.692	0.5	PASS
19	2440	0.692	0.5	PASS
39	2480	0.696	0.5	PASS

The spectrum analyzer plots are attached as below.


channel 0



channel 19



channel 39



6. MAXIMUM PEAK OUTPUT POWER

6.1. Block Diagram of Test Setup



(EUT: BTLE and Battery blocks)

6.2. The Requirement For Section 15.247(b)(3)

Section 15.247(b)(3): For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: 1 Watt.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. Set the RBW $\geq$ DTS bandwidth. VBW $\geq 3 \times$ RBW.

6.5.2. Set span $\geq 3 \times$ RBW

6.5.3. Sweep time = auto couple.

6.5.4. Detector = peak.

6.5.5. Trace mode = max hold.

6.5.6. Allow trace to fully stabilize.


6.5.7. Use peak marker function to determine the peak amplitude level.

6.6. Test Result


Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
0	2402	-3.83	30	PASS
19	2440	-0.10	30	PASS
39	2480	-0.93	30	PASS

The spectrum analyzer plots are attached as below.


channel 0



channel 19



channel 39



7. POWER SPECTRAL DENSITY MEASUREMENT

7.1. Block Diagram of Test Setup



(EUT: BTLE and Battery blocks)

7.2. The Requirement For Section 15.247(e)

Section 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. EUT Configuration on Measurement

The equipment is installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 8.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The EUT was tested according to DTS test procedure of KDB558074 D01 DTS Meas Guidance v03r02 for compliance to FCC 47CFR 15.247 requirements.

7.5.2. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.3. Measurement Procedure PKPSD:

This procedure must be used if maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit, and is optional if the maximum (average) conducted output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


7.5.4. Measurement the maximum power spectral density.

7.6. Test Result


CHANNEL NUMBER	FREQUENCY (MHz)	PSD (dBm/3KHz)	LIMIT (dBm/3KHz)	PASS/FAIL
0	2402	-20.10	8	PASS
19	2440	-16.17	8	PASS
39	2480	-16.90	8	PASS

The spectrum analyzer plots are attached as below.


channel 0



channel 19



channel 39



8. BAND EDGE COMPLIANCE TEST

8.1. Block Diagram of Test Setup



(EUT: BTLE and Battery blocks)

8.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

8.3. EUT Configuration on Measurement

The equipment is installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4.Operating Condition of EUT

8.4.1.Setup the EUT and simulator as shown as Section 9.1.

8.4.2.Turn on the power of all equipment.

8.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

8.5.Test Procedure

Conducted Band Edge:

8.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

8.5.2.Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.

Radiate Band Edge:

8.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

8.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

8.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

8.5.6.Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz


8.5.7.The band edges was measured and recorded.

8.6.Test Result


Pass

Channel	Frequency	Delta peak to band emission	Limit(dBc)
0	2400MHz	49.89	20
39	2483.5MHz	53.32	20

channel 0



channel 39



Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2877

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2402MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS INCORPORATED

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/31/33

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2385.140	45.01	-7.61	37.40	74.00	-36.60	peak			
2	2385.140	39.87	-7.61	32.26	54.00	-21.74	AVG			
3	2390.000	43.70	-7.57	36.13	74.00	-37.87	peak			
4	2390.000	38.27	-7.57	30.70	54.00	-23.30	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2876

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2402MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/29/24

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2370.190	45.02	-7.71	37.31	74.00	-36.69	peak			
2	2370.190	39.82	-7.71	32.11	54.00	-21.89	AVG			
3	2390.000	43.74	-7.57	36.17	74.00	-37.83	peak			
4	2390.000	38.34	-7.57	30.77	54.00	-23.23	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2875

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2480MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/26/20

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	49.21	-7.38	41.83	74.00	-32.17	peak			
2	2483.500	44.09	-7.38	36.71	54.00	-17.29	AVG			
3	2484.220	49.32	-7.39	41.93	74.00	-32.07	peak			
4	2484.220	44.12	-7.39	36.73	54.00	-17.27	AVG			

Job No.: ricky #2874

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2480MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS INCORPORATED

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/24/15

Engineer Signature:

Distance: 3m

Note: Report No:ATE20142409




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	47.90	-7.38	40.52	74.00	-33.48	peak			
2	2483.500	42.35	-7.38	34.97	54.00	-19.03	AVG			
3	2483.950	49.17	-7.39	41.78	74.00	-32.22	peak			
4	2483.950	43.97	-7.39	36.58	54.00	-17.42	AVG			

9. RADIATED SPURIOUS EMISSION TEST

9.1. Block Diagram of Test Setup


9.1.1. Block diagram of connection between the EUT and peripherals



Setup: Transmitting mode

(EUT: BTLE and Battery blocks)

9.1.2. Semi-Anechoic Chamber Test Setup Diagram



9.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

9.3.Restricted bands of operation

9.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

9.4. Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.5. Operating Condition of EUT

9.5.1. Setup the EUT and simulator as shown as Section 10.1.

9.5.2. Turn on the power of all equipment.

9.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

9.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector. When average radiated emissions measurements are specified there is also a limit on the peak emissions level which is 20 dB above the applicable maximum permitted average emission limit

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz

Peak detector above 1GHz

RBW (1 MHz), VBW (3MHz) for Peak measurement

RBW (1 MHz), VBW (10Hz) for AV measurement

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

9.7.The Field Strength of Radiation Emission Measurement Results

- Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The EUT is tested radiation emission at Low, Middle, High channel in three axes. The worst emissions are reported in all channels. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.
3. The radiation emissions from 18-25GHz are not reported, because the test values lower than the limits of 20dB.
4. The average measurement was not performed when peak measured data under the limit of average detection.



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2862

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2402MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS INCORPORATED

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/05/02

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



Job No.: ricky #2863

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2402MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/06/28

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	110.8580	49.77	-22.19	27.58	43.50	-15.92	QP			
2	191.1114	49.54	-20.87	28.67	43.50	-14.83	QP			
3	209.3924	46.35	-20.02	26.33	43.50	-17.17	QP			

Job No.: ricky #2864

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2440MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/07/31

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	110.8581	49.39	-22.19	27.20	43.50	-16.30	peak			
2	190.4411	49.40	-20.93	28.47	43.50	-15.03	peak			
3	209.3924	46.23	-20.02	26.21	43.50	-17.29	peak			

**ACCURATE TECHNOLOGY CO., LTD.**F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2865

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2440MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/08/26

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	110.8581	53.25	-22.19	31.06	43.50	-12.44	QP			
2	190.4411	61.67	-20.93	40.74	43.50	-2.76	QP			
3	208.6580	55.93	-20.03	35.90	43.50	-7.60	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2866

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2480MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/09/51

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	110.8581	54.11	-22.19	31.92	43.50	-11.58	QP			
2	190.4411	61.62	-20.93	40.69	43.50	-2.81	QP			
3	208.6580	57.40	-20.03	37.37	43.50	-6.13	QP			

**ACCURATE TECHNOLOGY CO., LTD.**F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2867

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2480MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/10/56

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	110.8581	49.38	-22.19	27.19	43.50	-16.31	QP			
2	190.4411	50.04	-20.93	29.11	43.50	-14.39	QP			
3	208.6580	46.46	-20.03	26.43	43.50	-17.07	QP			

Job No.: ricky #2873

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2402MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Horizontal

Power Source: DC 3.7V

Date: 14/12/08/

Time: 9/22/41

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	8494.331	39.43	8.91	48.34	54.00	-5.66	peak			
2	12222.059	4.76	45.01	49.77	54.00	-4.23	peak			
3	15882.369	1.88	48.57	50.45	54.00	-3.55	peak			

Job No.: ricky #2872

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2402MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS INCORPORATED

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/21/01

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	9082.470	39.59	9.04	48.63	54.00	-5.37	peak			
2	11768.220	36.86	13.13	49.99	54.00	-4.01	peak			
3	17331.611	-2.09	52.36	50.27	54.00	-3.73	peak			

**ACCURATE TECHNOLOGY CO., LTD.**F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: ricky #2871

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2440MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS INCORPORATED

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/19/15

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	10815.616	38.54	10.34	48.88	54.00	-5.12	peak			
2	13892.030	2.40	47.70	50.10	54.00	-3.90	peak			
3	18000.000	-5.39	55.70	50.31	54.00	-3.69	peak			

Job No.: ricky #2870

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2440MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS INCORPORATED

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/17/21

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	9460.230	37.69	10.55	48.24	54.00	-5.76	peak			
2	11768.220	35.90	13.13	49.03	54.00	-4.97	peak			
3	16591.174	1.13	49.51	50.64	54.00	-3.36	peak			

Job No.: ricky #2869

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2480MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS IMCORPORATED

Polarization: Horizontal

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/15/25

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	9796.504	37.02	10.87	47.89	54.00	-6.11	peak			
2	14219.315	0.50	49.01	49.51	54.00	-4.49	peak			
3	15292.613	0.69	48.83	49.52	54.00	-4.48	peak			

Job No.: ricky #2868

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: BTLE and Battery blocks

Mode: TX 2480MHz

Model: mo-bk-BTLE-1

Manufacturer: MODULAR ROBOTICS INCORPORATED

Polarization: Vertical

Power Source: DC 3.7V


Date: 14/12/08/

Time: 9/13/43

Engineer Signature:

Distance: 3m


Note: Report NO.:ATE20142409



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	6690.695	40.72	4.80	45.52	54.00	-8.48	peak			
2	8323.009	38.49	8.91	47.40	54.00	-6.60	peak			
3	16021.665	1.08	48.62	49.70	54.00	-4.30	peak			

10.CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST

10.1.Block Diagram of Test Setup



(EUT: BTLE and Battery blocks)

10.2.The Requirement of Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.EUT Configuration on Measurement

The equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.4. Operating Condition of EUT

10.4.1. Setup the EUT and simulator as shown as Section 11.1.

10.4.2. Turn on the power of all equipment.

10.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480 MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

10.5. Test Procedure

10.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

10.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz


10.5.3. The Conducted Spurious Emission was measured and recorded.

10.6. Test Result


Pass.

The spectrum analyzer plots are attached as below.


BLE Channel Low 2402MHz



BLE Channel Middle 2440MHz




BLE Channel High 2480MHz



11. POWER LINE CONDUCTED MEASUREMENT

11.1. Block Diagram of Test Setup



(EUT: BTLE and Battery blocks)

11.2. Power Line Conducted Emission Measurement Limits

Frequency (MHz)	Limit dB(μV)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0
NOTE1: The lower limit shall apply at the transition frequencies.		
NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.		

11.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

11.4. Operating Condition of EUT

11.4.1. Setup the EUT and simulator as shown as Section 5.1.

11.4.2. Turn on the power of all equipment.

11.4.3. Let the EUT work in test mode and measure it.

11.5. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

11.6. Power Line Conducted Emission Measurement Results

PASS.

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART15 B

EUT: BTLE and Battery blocks M/N:mo-bk-BTLE-1
 Manufacturer: MODULAR ROBOTICS IMCORPORATED
 Operating Condition: Operation
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: N 120V/60Hz
 Comment: Report NO.:ATE20142409
 Start of Test: 12/10/2014 / 8:58:08AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "RY1210-1_fin"

12/10/2014 9:02AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	54.30	10.5	66	11.7	QP	N	GND
0.175000	51.70	10.5	65	13.0	QP	N	GND
3.040000	37.40	11.1	56	18.6	QP	N	GND

MEASUREMENT RESULT: "RY1210-1_fin2"

12/10/2014 9:02AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.410000	33.90	10.7	48	13.7	AV	N	GND
2.930000	31.40	11.1	46	14.6	AV	N	GND
5.210000	28.70	11.2	50	21.3	AV	N	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART15 B

EUT: BTLE and Battery blocks M/N:mo-bk-BTLE-1
 Manufacturer: MODULAR ROBOTICS IMCORPORATED
 Operating Condition: Operation
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: L 120V/60Hz
 Comment: Report NO.:ATE20142409
 Start of Test: 12/10/2014 / 9:03:27AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "RY1210-2_fin"

12/10/2014 9:06AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.155000	53.00	10.5	66	12.7	QP	L1	GND
3.020000	36.30	11.1	56	19.7	QP	L1	GND
5.130000	35.40	11.2	60	24.6	QP	L1	GND

MEASUREMENT RESULT: "RY1210-2_fin2"

12/10/2014 9:06AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.410000	28.50	10.7	48	19.1	AV	L1	GND
2.940000	30.70	11.1	46	15.3	AV	L1	GND
5.140000	25.50	11.2	50	24.5	AV	L1	GND


12.ANTENNA REQUIREMENT

12.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

12.2.Antenna Construction

Device is equipped with a permanent attached antenna, which isn't displaced by other antenna. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna