



REPORT No.: SZ15110072W02

FCC RF TEST REPORT

APPLICANT : Shenzhen Renqing Technology Co.,Ltd.

PRODUCT NAME : Autobot eye smart dashcam

MODEL NAME : RSD0602

TRADE NAME : ROCK

BRAND NAME : ROCK

FCC ID : 2ADYI-RSD0602

STANDARD(S) : 47 CFR Part 15 Subpart C

ISSUE DATE : 2016-01-05



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.com

Fax: 86-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION.....4

1. TECHNICAL INFORMATION5

1.1 APPLICANT INFORMATION5

1.2 EQUIPMENT UNDER TEST (EUT) DESCRIPTION5

1.2.1 IDENTIFICATION OF ALL USED EUTS6

1.3 TEST STANDARDS AND RESULTS6

1.3.1 TEST ENVIRONMENT CONDITIONS6

2. 47 CFR PART 15C REQUIREMENTS.....7

2.1 ANTENNA REQUIREMENT7

2.1.1 APPLICABLE STANDARD7

2.1.2 RESULT: COMPLIANT7

2.2 PEAK OUTPUT POWER.....7

2.2.1 REQUIREMENT7

2.2.2 TEST DESCRIPTION7

2.2.3 TEST RESULT.....8

2.3 BANDWIDTH9

2.3.1 REQUIREMENT9

2.3.2 TEST DESCRIPTION9

2.3.3 TEST RESULT.....9

2.4 CONDUCTED SPURIOUS EMISSIONS AND BAND EDGE18

2.4.1 REQUIREMENT..... 18

2.4.2 TEST DESCRIPTION 18

2.4.3 TEST RESULT..... 18

2.5 POWER SPECTRAL DENSITY (PSD)31

2.5.1 REQUIREMENT..... 31

2.5.2 TEST DESCRIPTION 31

2.5.3 TEST RESULT..... 32

2.6 RESTRICTED FREQUENCY BANDS40

2.6.1 REQUIREMENT..... 40

2.6.2 TEST DESCRIPTION 40

2.6.3 TEST RESULT..... 41



REPORT No.: SZ15110072W02

2.7	RADIATED EMISSION	52
2.7.1	REQUIREMENT	52
2.7.2	TEST DESCRIPTION	53
2.7.3	TEST RESULT	55
ANNEX A GENERAL INFORMATION		68

Change History		
Issue	Date	Reason for change
1.0	2016-01-05	First edition



REPORT No.: SZ15110072W02

TEST REPORT DECLARATION

Applicant	Shenzhen Renqing Technology Co.,Ltd.
Applicant Address	3/F,Block A7 Nanshan iPark,NO.1001 Xueyuan Road,Nanshan District, Shenzhen
Manufacturer	Shenzhen Renqing Technology Co.,Ltd.
Manufacturer Address	3/F,Block A7 Nanshan iPark,NO.1001 Xueyuan Road,Nanshan District, Shenzhen
Product Name	Autobot eye smart dashcam
Model Name	RSD0602
Brand Name	ROCK
HW Version	V2.0
SW Version	WK01_1116
Test Standards	47 CFR Part 15 Subpart C
Test Date	2015-12-15 to 2015-12-30
Test Result	PASS

Tested by : Zou Jian
Zou Jian(Test Engineer)

Reviewed by : Peng Huarui
Peng Huarui(RF Manager)

Approved by : Zeng Dexin
Zeng Dexin(Chief Engineer)



1. TECHNICAL INFORMATION

Note: Provide by applicant.

1.1 Applicant Information

Company:	Shenzhen Renqing Technology Co.,Ltd.
Address:	3/F,Block A7 Nanshan iPark,NO.1001 Xueyuan Road,Nanshan District, Shenzhen

1.2 Equipment under Test (EUT) Description

Brand Name:	ROCK
Trade Name:	ROCK
Model Name:	RSD0602
Frequency Range:	802.11b/g/n-20MHz: 2.412GHz - 2.462GHz 802.11n-40MHz: 2.422GHz - 2.452GHz
Channel Number:	802.11b/g/n-20MHz: 11 802.11n-40MHz: 7
Modulation Type:	DSSS, OFDM
Antenna Type:	FPC Antenna
Antenna Gain:	-1.2dBi

NOTE:

The EUT is a Autobot eye smart dashcam, it contains WIFI EUT operating at 2.4GHz ISM; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.

For 802.11b/g/n-20MHz (2.4GHz band), the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 \times (n-1)$ ($1 \leq n \leq 11$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).

For 802.11n-40MHz, the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 \times (n-1)$ ($3 \leq n \leq 9$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 3 (2422MHz), 6 (2437MHz) and 9 (2452MHz).

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

The antenna connector of EUT is designed with permanent attachment and no consideration of replacement.



1.2.1 Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	V2.0	WK01_1116

1.3 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-13 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Result
1	15.203	Antenna Requirement	N.A	<u>PASS</u>
2	15.247(b)	Peak Output Power	Dec 24, 2015	<u>PASS</u>
3	15.247(a)	Bandwidth	Dec 24, 2015	<u>PASS</u>
4	15.247(d)	Conducted Spurious Emission and Band Edge	Dec 24, 2015	<u>PASS</u>
5	15.247(d)	Restricted Frequency Bands	Dec 25, 2015	<u>PASS</u>
6	15.209 ,15.247(d)	Radiated Emission	Dec 25, 2015	<u>PASS</u>
7	15.247(e)	Power spectral density (PSD)	Dec 24, 2015	<u>PASS</u>

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10 2013.

1.3.1 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR PART 15C REQUIREMENTS

2.1 Antenna requirement

2.1.1 Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2 Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2 Peak Output Power


2.2.1 Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.2.2 Test Description

The measured output power was calculated by the reading of the Power Meter and calibration.

A. Test Setup:



The EUT (Equipment under the test) which is coupled to the Power Meter; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading, all test result in power meter.

**B. Equipments List:**

Please reference ANNEX A(1.4).

2.2.3 Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the EUT.

2.2.3.1 802.11b Test Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	17.37	0.05458	30	1	PASS
6	2437	17.62	0.05781			PASS
11	2462	17.9	0.06166			PASS

2.2.3.2 802.11g Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	18.55	0.07161	30	1	PASS
6	2437	19.12	0.08166			PASS
11	2462	19.46	0.08831			PASS

2.2.3.3 802.11n-20MHz Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	18.11	0.06471	30	1	PASS
6	2437	18.78	0.07551			PASS
11	2462	19.02	0.07980			PASS

2.2.3.4 802.11n-40MHz Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
3	2422	16.54	0.04508	30	1	PASS
6	2437	16.96	0.04966			PASS
9	2452	17.23	0.05284			PASS


2.3 Bandwidth

2.3.1 Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2 Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Please reference ANNEX A(1.4).

2.3.3 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the EUT.




REPORT No.: SZ15110072W02

2.3.3.1 802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	10.08	≥ 500	PASS
6	2437	10.09	≥ 500	PASS
11	2462	10.08	≥ 500	PASS


B. Test Plots




(Channel 1: 2412MHz @ 802.11b)



REPORT No.: SZ15110072W02



(Channel 6: 2437 MHz @ 802.11b)



(Channel 11: 2462MHz @ 802.11b)




REPORT No.: SZ15110072W02

2.3.3.2 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.57	≥ 500	PASS
6	2437	16.57	≥ 500	PASS
11	2462	16.55	≥ 500	PASS


B. Test Plots:




(Channel 1: 2412MHz @ 802.11g)



REPORT No.: SZ15110072W02



(Channel 6: 2437MHz @ 802.11g)



(Channel 11: 2462MHz @ 802.11g)




REPORT No.: SZ15110072W02

2.3.3.3 802.11n-20 Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	17.84	≥500	PASS
6	2437	17.83	≥500	PASS
11	2462	17.83	≥500	PASS


B. Test Plots:




(Channel 1: 2412MHz @ 802.11n-20)



REPORT No.: SZ15110072W02



(Channel 6: 2437MHz @ 802.11n-20)



(Channel 11: 2462MHz @ 802.11n-20)




REPORT No.: SZ15110072W02

2.3.3.4 802.11n-40 Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
3	2422	36.37	≥500	PASS
6	2437	36.35	≥500	PASS
9	2452	36.38	≥500	PASS


B. Test Plots:




(Channel 3: 2422MHz @ 802.11n-40)



REPORT No.: SZ15110072W02



(Channel 6: 2437MHz @ 802.11n-40)



(Channel 9: 2452MHz @ 802.11n-40)


2.4 Conducted Spurious Emissions and Band Edge

2.4.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.4.2 Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

B. Equipments List:

Please reference ANNEX A(1.4).

2.4.3 Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

**2.4.3.1 802.11b Test mode****A. Test Verdict:**

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-41.11	4.70	-15.30	PASS
6	2437	-40.84	5.35	-14.65	PASS
11	2462	-40.82	4.77	-15.23	PASS

B. Test Plots:


Note: the power of the EUT transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No.: SZ15110072W02




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No.: SZ15110072W02



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)



REPORT No.: SZ15110072W02


2.4.3.2 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-49.85	-4.64	-24.64	PASS
6	2437	-50.88	-3.92	-23.92	PASS
11	2462	-51.41	-3.89	-23.89	PASS

B. Test Plots:


Note: the power of the EUT transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No.: SZ15110072W02




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No.: SZ15110072W02



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)




REPORT No.: SZ15110072W02

2.4.3.3 802.11n -20MHz Test mode**A. Test Verdict:**

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-51.27	-4.79	-24.79	PASS
6	2437	-50.86	-4.78	-24.78	PASS
11	2462	-51.15	-4.28	-24.28	PASS

B. Test Plots:


Note: the power of the EUT transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No.: SZ15110072W02




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No.: SZ15110072W02



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)




REPORT No.: SZ15110072W02

2.4.3.4 802.11n -40MHz Test mode**A. Test Verdict:**

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
3	2422	-50.34	-7.93	-27.93	PASS
6	2437	-51.22	-8.40	-28.40	PASS
9	2452	-51.1	-7.94	-27.94	PASS

B. Test Plots:


Note: the power of the EUT transmitting frequency should be ignored.




(Channel = 3, 30MHz to 25GHz)



REPORT No.: SZ15110072W02




(Band Edge @ Channel = 3)




(Channel = 6, 30MHz to 25GHz)



REPORT No.: SZ15110072W02



(Channel = 9, 30MHz to 25GHz)



(Band Edge @ Channel = 9)


2.5 Power spectral density (PSD)

2.5.1 Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.5.2 Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Please reference ANNEX A(1.4).



REPORT No.: SZ15110072W02


2.5.3 Test Result

2.5.3.1 802.11b Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-14	8	PASS
6	2437	-13.56	8	PASS
11	2462	-13.24	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 1 @ 802.11b)



REPORT No.: SZ15110072W02



(Channel = 6 @ 802.11b)



(Channel = 11 @ 802.11b)




REPORT No.: SZ15110072W02

2.5.3.2 802.11g Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-18.32	8	PASS
6	2437	-17.84	8	PASS
11	2462	-17.48	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 1 @ 802.11g)



REPORT No.: SZ15110072W02



(Channel = 6 @ 802.11g)



(Channel = 11 @ 802.11g)




REPORT No.: SZ15110072W02

2.5.3.3 802.11n-20MHz Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-18.03	8	PASS
6	2437	-17.3	8	PASS
11	2462	-17.51	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 1 @ 802.11n-20MHz)



REPORT No.: SZ15110072W02



(Channel = 6 @ 802.11n-20MHz)



(Channel = 11 @ 802.11n-20MHz)




REPORT No.: SZ15110072W02

2.5.3.4 802.11n-40MHz Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
3	2422	-18.77	8	PASS
6	2437	-20.33	8	PASS
9	2452	-18.58	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 3 @ 802.11n-40MHz)



REPORT No.: SZ15110072W02



(Channel = 6 @ 802.11n-40MHz)



(Channel = 9 @ 802.11n-40MHz)


2.6 Restricted Frequency Bands

2.6.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.6.2 Test Description

A. Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

B. Equipments List:

Please reference ANNEX A(1.4).



2.6.3 Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

2.6.3.1 802.11b Test mode

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2368.03	PK	46.71	-33.63	32.56	45.64	74	Pass
1	2373.28	AV	33.98	-33.63	32.56	32.91	54	Pass
11	2485.26	PK	46.48	-33.18	32.5	45.80	74	Pass
11	2488.79	AV	34.59	-33.18	32.5	33.91	54	Pass


B. Test Plots:



REPORT No.: SZ15110072W02




(Plot A1: Channel = 1 PEAK @ 802.11b)



(Plot A2: Channel = 1 AVG @ 802.11b)



REPORT No.: SZ15110072W02



(Plot B1: Channel = 11 PEAK @ 802.11b)



(Plot B2: Channel = 11 AVG @ 802.11b)



REPORT No.: SZ15110072W02


2.6.3.2 802.11g Test mode

The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2383.87	PK	46.43	-33.63	32.56	45.36	74	Pass
1	2375.58	AV	33.94	-33.63	32.56	32.87	54	Pass
11	2483.96	PK	47.68	-33.18	32.5	47.00	74	Pass
11	2485.73	AV	34.39	-33.18	32.5	33.71	54	Pass


B. Test Plots:



(Plot C1: Channel = 1 PEAK @ 802.11g)




REPORT No.: SZ15110072W02



(Plot C2: Channel = 1 AVG @ 802.11g)



(Plot D1: Channel = 11 PEAK @ 802.11g)



(Plot D2: Channel = 11 AVG @ 802.11g)

2.6.3.3 802.11n-20MHz Test mode

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBμV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2368.19	PK	47.02	-33.63	32.56	45.95	74	Pass
1	2368.19	AV	33.89	-33.63	32.56	32.82	54	Pass
11	2483.95	PK	51.39	-33.18	32.5	50.71	74	Pass
11	2485.86	AV	34.61	-33.18	32.5	33.93	54	Pass


B. Test Plots:



REPORT No.: SZ15110072W02




(Plot E1: Channel = 1 PEAK @ 802.11n-20)




(Plot E2: Channel = 1 AVG @ 802.11n-20)



REPORT No.: SZ15110072W02



(Plot F1: Channel = 11 PEAK @ 802.11n-20)



(Plot F2: Channel = 11 AVG @ 802.11n-20)




2.6.3.4 802.11n-40MHz Test mode

The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
3	2385.18	PK	47.44	-33.63	32.56	46.37	74	Pass
3	2383.95	AV	36.24	-33.63	32.56	35.17	54	Pass
9	2485.57	PK	48.65	-33.18	32.5	47.97	74	Pass
9	2486.37	AV	35.22	-33.18	32.5	34.54	54	Pass


B. Test Plots:



(Plot E1: Channel = 3 PEAK @ 802.11n-40)



REPORT No.: SZ15110072W02




(Plot E2: Channel = 3 AVG @ 802.11n-40)



(Plot F1: Channel = 9 PEAK @ 802.11n-40)



REPORT No.: SZ15110072W02



(Plot F2: Channel = 9 AVG @ 802.11n-40)



2.7 Radiated Emission

2.7.1 Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.


For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.7.2 Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10.

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Please reference ANNEX A(1.4).



2.7.3 Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


**2.7.3.1 802.11b Test mode****A. Test Plots for the Whole Measurement Frequency Range:**

Plots for Channel = 1



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
220.601	39.55	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
371.139	38.74	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
719.562	37.68	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2252.981	45.95	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4824.113	51.21	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12119.694	49.76	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
32.428	31.51	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
63.992	28.12	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
440.338	40.74	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2254.902	48.56	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
4824.113	51.86	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12152.282	49.66	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




REPORT No.: SZ15110072W02

Plot for Channel = 6




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.025	37.27	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
445.194	38.84	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
720.776	38.95	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2239.536	49.12	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
8380.251	49.12	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12172.650	49.74	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
63.992	28.26	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
220.601	29.79	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
440.338	40.66	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2196.639	47.44	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
4872.995	49.57	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
8962.757	48.38	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11


Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	40.04	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
371.139	41.68	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
815.469	41.36	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2258.743	48.37	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4925.950	48.77	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
11732.715	49.94	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
63.992	27.19	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
440.338	36.15	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
815.469	40.43	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
1392.477	45.96	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
4925.950	48.42	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12193.017	48.74	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**2.7.3.2 802.11g Test mode****A. Test Plots for the Whole Measurement Frequency Range:**Plots for Channel = 1

Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	39.65	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
371.139	38.74	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
815.469	39.74	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
4563.412	46.32	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
11288.707	49.03	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
22612.948	49.52	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
161.114	24.28	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
440.338	33.91	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
719.562	39.45	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2323.409	43.33	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5687.689	47.42	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
9084.961	47.78	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




REPORT No.: SZ15110072W02

Plot for Channel = 6



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
220.601	40.76	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
371.139	42.13	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
816.683	40.98	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
1392.477	44.99	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5626.587	47.13	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
9015.712	49.31	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
32.428	29.66	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
440.338	33.29	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
719.562	39.16	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2201.120	43.47	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5712.129	46.58	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
16800.109	49.43	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




REPORT No.: SZ15110072W02

Plot for Channel = 11




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
220.601	37.80	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
440.338	43.41	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
815.469	37.09	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
1296.439	42.74	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4714.130	46.97	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
9011.638	47.85	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
63.992	27.87	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
223.029	29.76	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
815.469	40.23	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2190.236	47.17	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
4925.950	48.92	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18857.210	50.23	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**2.7.3.3 802.11n-20MHz Test mode****A. Test Plots for the Whole Measurement Frequency Range:**Plots for Channel = 1

Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	34.37	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
371.139	38.08	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
719.562	40.35	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2689.616	43.98	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5683.615	46.71	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12213.384	47.86	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	29.55	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
440.338	35.70	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
719.562	42.76	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2224.170	43.71	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
8380.251	47.86	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
16168.722	50.16	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




REPORT No.: SZ15110072W02

Plot for Channel = 6



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	33.31	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
371.139	38.92	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
719.562	41.74	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2258.743	44.48	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
6555.337	48.26	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
15443.644	48.90	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	29.73	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
623.655	37.76	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
815.469	38.12	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2999.200	44.70	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7915.876	47.37	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
14445.645	48.80	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




REPORT No.: SZ15110072W02

Plot for Channel = 11




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	40.19	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
440.338	43.65	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
815.469	43.82	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
1296.439	46.93	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
2236.335	46.54	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
9048.300	48.24	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
63.992	28.05	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
440.338	37.41	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
719.562	39.07	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
1392.477	44.66	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
4490.089	46.68	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
10311.075	48.47	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**2.7.3.4 802.11n-40MHz Test mode****A. Test Plots for the Whole Measurement Frequency Range:**Plots for Channel = 3

Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	40.88	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
371.139	42.27	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
1296.439	45.66	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4526.750	47.57	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5691.762	49.15	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
9015.712	48.84	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot A.2: Antenna Horizontal, 30MHz to 25GHz)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	28.10	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
527.747	34.35	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
719.562	39.28	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2350.940	45.13	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5374.032	47.01	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
16144.281	49.07	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot A.3: Antenna Vertical, 30MHz to 25GHz)




Plots for Channel = 6



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
155.044	30.08	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
440.338	43.73	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
815.469	40.45	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2222.889	44.03	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
7097.109	47.39	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12522.968	49.31	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot B.2: Antenna Horizontal, 30MHz to 25GHz)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
162.328	25.18	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
440.338	33.04	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
719.562	38.35	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2276.671	44.28	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
3903.510	46.20	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
10184.797	49.91	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot B.3: Antenna Vertical, 30MHz to 25GHz)




Plots for Channel = 9



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
223.029	39.93	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
440.338	43.89	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
815.469	40.27	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
1392.477	43.17	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
7011.566	47.89	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12543.335	48.52	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot C.2: Antenna Horizontal, 30MHz to 25GHz)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
32.428	30.45	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
223.029	28.71	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
623.655	35.55	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
1296.439	44.44	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5056.301	46.61	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
15325.514	49.21	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot C.3: Antenna Vertical, 30MHz to 25GHz)



ANNEX A GENERAL INFORMATION

1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2013 and CISPR Publication 22; the FCC registration number is 695796.

1.4 Maximum measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Measurements	Frequency	Uncertainty
Conducted emissions	9KHz~30MHz	2.44dB
Radiated emissions	30MHz~200MHz	2.93
	200MHz~1000MHz	2.95
	1GHz~18GHz	2.26
	18GHz~40GHz	1.94



REPORT No.: SZ15110072W02

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$

1.5 Test Equipments Utilized

1.5.1 Conducted Test Equipments

Conducted Test Equipment

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Spectrum Analyzer	MY45101810	E4407B	Agilent	2015.03.28	2016.03.27
2	USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2015.03.28	2016.03.27
3	EXA Signal Analyzer	MY53470838	N9010A	Agilent	2015.08.26	2016.08.25
4	RF cable	CB01	RF01	Morlab	N/A	N/A
5	Attenuator	(n.a.)	10dB	Resnet	N/A	N/A
6	SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.5.2 Conducted Emission Test Equipments

Conducted Emission Test Equipments

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Receiver	595WX11007	PMM9010	Narda S.T.S/PMM	2015.05.07	2016.05.06
2	LISN	812744	NSLK 8127	Schwarzbeck	2015.06.18	2016.06.17
3	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2015.05.07	2016.05.06
4	Coaxial cable(BNC)	CB01	EMC01	Morlab	N/A	N/A

1.5.3 Auxiliary Test Equipment

Auxiliary Test Equipment

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Computer	N.A	N.A	Asus	N.A	N.A



REPORT No.: SZ15110072W02

1.5.4 Radiated Test Equipments

Radiated Test Equipments						
No	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
1	System Simulator	GB45360846	8960-E5515C	Agilent	2015.05.07	2016.05.06
2	Receiver	MY54130016	N9038A	Agilent	2015.05.07	2016.05.06
3	Test Antenna - Bi-Log	N/A	VULB9163	Schwarzbeck	2015.05.14	2016.05.13
4	Test Antenna - Horn	9170C-531	BBHA9170	Schwarzbeck	2015.03.31	2016.03.30
5	Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2015.02.26	2016.02.25
6	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2015.02.26	2016.02.25
7	Coaxial cable(N male)	CB02	EMC02	Morlab	N/A	N/A
8	Coaxial cable(N male)	CB03	EMC03	Morlab	N/A	N/A
9	1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde&Schwarz	2015.02.26	2016.02.25
10	18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde&Schwarz	2015.02.26	2016.02.25

1.5.5 Climate Chamber

Climate Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Climate Chamber	2004012	HL4003T	Yinhe	2015.02.26	2016.02.25

1.5.6 Vibration Table

Vibration Table						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2015.02.26	2016.02.25

1.5.7 Anechoic Chamber

Anechoic Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Anechoic Chamber	N/A	9m*6m*6m	Changning	2015.05.14	2016.05.13

***** END OF REPORT *****