

Appendix B

LTE Cat M1 Band 13
LTE Cat M1 Band 25
LTE Cat M1 Band 26
LTE Cat M1 Band 66
LTE Cat M1 Band 85
NB-IOT Band 5
NB-IOT Band 13
NB-IOT Band 25
NB-IOT Band 66
NB-IOT Band 71
NB-IOT Band 85

Test Laboratory: TOWE Lab

Measurement Report for JPD-700A, FRONT, Band 13, LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK) RBPosition:Low AntennaCfg:SISO, Channel 23230 (782.000 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 13	LTE-FDD, 10175-CAH	782.000, 23230	9.65	0.902	42.3

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL750	EX3DV4 - SN7812, 2024-06-25	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	180.0 x 210.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-02, 06:27	2025-06-02, 06:31
psSAR1g [W/Kg]	0.157	0.167
psSAR10g [W/Kg]	0.106	0.107
Power Drift [dB]	0.09	-0.06
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		58.8
Dist 3dB Peak [mm]		16.8



Test Laboratory: TOWE Lab

Measurement Report for JPD-700A, FRONT, Band 25, LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK) RBPosition:Low AntennaCfg:SISO, Channel 26590 (1905.000 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 25	LTE-FDD, 10169-CAF	1905.000, 26590	7.79	1.38	39.9

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL1900	EX3DV4 - SN7858, 2025-01-15	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 90.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	Unknown method	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-01, 15:42	2025-06-01, 15:46
psSAR1g [W/Kg]	0.569	0.579
psSAR10g [W/Kg]	0.281	0.292
Power Drift [dB]	-0.08	0.06
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		54.4
Dist 3dB Peak [mm]		10.8



Test Laboratory: TOWE Lab

Measurement Report for JPD-700A, FRONT, Band 26, LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK) RBPosition:Low AntennaCfg:SISO, Channel 26865 (831.500 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 26	LTE-FDD, 10181-CAF	831.500, 26865	9.52	0.898	42.1

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL835	EX3DV4 - SN7858, 2025-01-15	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	180.0 x 210.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	Unknown method	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-01, 10:18	2025-06-01, 10:24
psSAR1g [W/Kg]	0.143	0.120
psSAR10g [W/Kg]	0.088	0.056
Power Drift [dB]	-0.05	0.07
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		56.8
Dist 3dB Peak [mm]		14.8



Measurement Report for JPD-700A, FRONT, Band 66, LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK) RBPosition:Low AntennaCfg:SISO, Channel 132072 (1720.000 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 66	LTE-FDD, 10169-CAF	1720.000, 132072	8.09	1.36	40.2

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL1750	EX3DV4 - SN7858, 2025-01-15	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 90.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-01, 13:07	2025-06-01, 13:12
psSAR1g [W/Kg]	0.492	0.536
psSAR10g [W/Kg]	0.267	0.301
Power Drift [dB]	-0.04	0.06
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		59.5
Dist 3dB Peak [mm]		11.2



Test Laboratory: TOWE Lab

Measurement Report for JPD-700A, FRONT, Band 85, LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK) RBPosition:Low AntennaCfg:SISO, Channel 134092 (707.000 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 85	LTE-FDD, 10175-CAH	707.000, 134092	9.65	0.878	42.6

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL750	EX3DV4 - SN7812, 2024-06-25	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	210.0 x 240.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-02, 07:09	2025-06-02, 07:12
psSAR1g [W/Kg]	0.134	0.140
psSAR10g [W/Kg]	0.086	0.081
Power Drift [dB]	-0.11	0.09
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		48.5
Dist 3dB Peak [mm]		13.7



Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 5	LTE-FDD, 10177-CAJ	836.500, 20525	9.52	0.901	42.0

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL835	EX3DV4 - SN7858, 2025-01-15	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	210.0 x 240.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	Y	Y
Surface Detection	Unknown method	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-01, 11:27	2025-06-01, 11:32
psSAR1g [W/Kg]	0.088	0.089
psSAR10g [W/Kg]	0.057	0.053
Power Drift [dB]	-0.05	0.06
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		56.9
Dist 3dB Peak [mm]		15.2



Test Laboratory: TOWE Lab

Measurement Report for JPD-700A, FRONT, Band 13, LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK) RBPosition:Mid AntennaCfg:SISO, Channel 23230 (782.000 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 13	LTE-FDD, 10177-CAJ	782.000, 23230	9.65	0.902	42.3

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL750	EX3DV4 - SN7812, 2024-06-25	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	210.0 x 240.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	Y	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-02, 10:46	2025-06-02, 10:51
psSAR1g [W/Kg]	0.073	0.075
psSAR10g [W/Kg]	0.047	0.045
Power Drift [dB]	0.01	0.04
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		49.2
Dist 3dB Peak [mm]		12.8



Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 25	LTE-FDD, 10177-CAJ	1882.500, 26365	7.79	1.38	39.9

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL1900	EX3DV4 - SN7858, 2025-01-15	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-01, 16:39	2025-06-01, 16:42
psSAR1g [W/Kg]	0.479	0.506
psSAR10g [W/Kg]	0.241	0.253
Power Drift [dB]	-0.01	-0.01
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		55.6
Dist 3dB Peak [mm]		10.8



Test Laboratory: TOWE Lab

Measurement Report for JPD-700A, FRONT, Band 66, LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK) RBPosition:Mid AntennaCfg:SISO, Channel 132322 (1745.000 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 66	LTE-FDD, 10177-CAJ	1745.000, 132322	8.09	1.37	40.2

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL1750	EX3DV4 - SN7858, 2025-01-15	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-01, 14:10	2025-06-01, 14:14
psSAR1g [W/Kg]	0.465	0.497
psSAR10g [W/Kg]	0.245	0.271
Power Drift [dB]	-0.01	0.09
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		55.2
Dist 3dB Peak [mm]		9.6



Test Laboratory: TOWE Lab

Measurement Report for JPD-700A, FRONT, Band 71, LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK) RBPosition:Mid AntennaCfg:SISO, Channel 133297 (680.500 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 71	LTE-FDD, 10177-CAJ	680.500, 133297	9.65	0.870	42.7

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL750	EX3DV4 - SN7812, 2024-06-25	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	210.0 x 240.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-02, 09:50	2025-06-02, 09:54
psSAR1g [W/Kg]	0.109	0.116
psSAR10g [W/Kg]	0.070	0.072
Power Drift [dB]	0.07	-0.10
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		60.2
Dist 3dB Peak [mm]		13.7



Measurement Report for JPD-700A, FRONT, Band 85, LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK) RBPosition:Mid AntennaCfg:SISO, Channel 134092 (707.000 MHz)

Device Under Test Properties

Model	Dimensions [mm]
JPD-700A	375.0 x 300.0 x 29.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	Band 85	LTE-FDD, 10175-CAH	707.000, 134092	9.65	0.878	42.6

Hardware Setup

Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2227	HSL750	EX3DV4 - SN7812, 2024-06-25	DAE4ip Sn1847, 2024-12-31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	210.0 x 240.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-06-02, 08:48	2025-06-02, 08:52
psSAR1g [W/Kg]	0.10	0.109
psSAR10g [W/Kg]	0.065	0.064
Power Drift [dB]	-0.18	0.08
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		51.3
Dist 3dB Peak [mm]		14.4

