

TEST REPORT

FCC ID: 2ADYY-K15SDA

Product: Laptop Computer

Model No.: K15SDA

Trade Mark: TECNO

Report No.: WSCT-ANAB-R&E250100005A-15B

Issued Date: 12 February 2025

Issued for:

TECNO MOBILE LIMITED
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN
NT HONGKONG

Issued By:

World Standardization Certification & Testing Group(Shenzhen) Co.,Ltd.
Building A-B,Baoli'an Industrial Park,No.58 and 60,Tangtou Avenue, Shiyan Street, Bao'an
District, Shenzhen City, Guangdong Province, China
TEL: +86-755-26996192
FAX: +86-755-86376605

Note: This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. This document may be altered or revised by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. Test Certification	3
2. GENERAL DESCRIPTION OF EUT	4
3. Test Result Summary	5
4. TEST METHODOLOGY	6
4.1. CONFIGURATION OF SYSTEM UNDER TEST	7
4.2. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	8
5. MEASUREMENT INSTRUMENTS	9
6. Facilities and Accreditations	10
6.1. FACILITIES	10
6.2. ACCREDITATIONS	10
6.3. MEASUREMENT UNCERTAINTY	11
7. EMC EMISSION TEST	12
7.1. CONDUCTED EMISSION MEASUREMENT	12
7.2. RADIATED EMISSION MEASUREMENT	16
8. Test Setup Photographs	23

Report No.: WSCT-ANAB-R&E250100005A-15B

1. Test Certification

Product: Laptop Computer**Model No.:** K15SDA**Trade Mark:** TECNO**Applicant:** TECNO MOBILE LIMITED**Address:** FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG**Manufacturer:** TECNO MOBILE LIMITED**Address:** FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG**Date of Test:** 02 January 2025 to 11 February 2025**Applicable Standards:** FCC CFR Title 47 Part 15 Subpart B

The above equipment has been tested by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Jiang Guanliang
(Jiang Guanliang)**Checked By:** Qin Shuiquan
(Qin Shuiquan)**Approved By:** Li Huaibi
(Li Huaibi)**Date:** 12 February 2025

Report No.: WSCT-ANAB-R&E250100005A-15B

2. GENERAL DESCRIPTION OF EUT

Equipment Type:	Laptop Computer
Test Model:	K15SDA
Trade Mark	TECNO
Software version:	Windows 11
Hardware version:	N156ERB01_MB_V11
EUT Power Rating	Adapter1: E065-1R200325VU INPUT: 100-240V~50/60Hz 1.5A OUTPUT: 20.0V---3.25A 65.0W Rechargeable Li-ion Polymer Battery: K15S Nominal Voltage: 11.55V Rated Capacity: 6060mAh Rated Energy: 70.00Wh Limited Charge Voltage: 13.2V
Remark:	N/A.

Configuration differences

Configuration/ Processor	CPU
K15SDA (AMD Lucienne)	LuB R5-5625U 5600U 5600H:LuC 5800U TDP 15W(5600H TDP with 30w)
K15SDA (AMD Barcelo-R)	R5-7430U/R7-7730U
Note: All models were tested, with the main test model being the K15SDA (R5-7430U)	

Report No.: WSCT-ANAB-R&E250100005A-15B

3. Test Result Summary

Requirement	CFR 47 Section	Result
CONDUCTED EMISSION	§15.107	PASS
RADIATED EMISSION	§15.109	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

Report No.: WSCT-ANAB-R&E250100005A-15B

4. TEST METHODOLOGY


To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Video Recording
Model 2	Video Playing
Mode 3	Transferring with USB Disk (the worst case)
Mode 4	TF Card Playing

Report No.: WSCT-ANAB-R&E250100005A-15B

4.1. CONFIGURATION OF SYSTEM UNDER TEST

Mode 1&2&3&4



(EUT: Laptop Computer)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
Power	1	2.4m cable, unshielded	1
USB cable	1	1.8m USB cable, unshielded	1

Report No.: WSCT-ANAB-R&E250100005A-15B

4.2. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	TF	Kingston	DTX/64GB	/	/
2	Adapter	/	E065-1R200325VU	/	/
3	USB Disk	Kingston	/	/	/

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in [Length] column.

Report No.: WSCT-ANAB-R&E250100005A-15B

5. MEASUREMENT INSTRUMENTS

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibrated	Calibrated until
Test software	--	EZ-EMC	CON-03A	--	--
ESCI Test Receiver	R&S	ESCI	100005	11/05/2024	11/04/2025
LISN	AFJ	LS16	16010222119	11/05/2024	11/04/2025
LISN(EUT)	Mastic	AN3016	04/10040	11/05/2024	11/04/2025
pre-amplifier	CDSI	PAP-1G18-38	--	11/05/2024	11/04/2025
System Controller	CT	SC100	-	11/05/2024	11/04/2025
Bi-log Antenna	Chase	CBL6111C	2576	11/05/2024	11/04/2025
Spectrum analyzer	R&S	FSU26	200409	11/05/2024	11/04/2025
Horn Antenna	SCHWARZBECK	9120D	1141	11/05/2024	11/04/2025
Bi-log Antenna	SCHWARZBECK	VULB9168	01488	11/05/2024	11/04/2025
Pre Amplifier	H.P.	HP8447E	2945A02715	11/05/2024	11/04/2025
9*6*6 Anechoic	--	--	--	11/05/2024	11/04/2025

Report No.: WSCT-ANAB-R&E250100005A-15B

6. Facilities and Accreditations

6.1. Facilities

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtuo Avenue, Shiyan Street, Bao'an District, Shenzhen City, Guangdong Province, China of the World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 32. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

CNAS - Registration Number: L3732

China National Accreditation Service for Conformity Assessment, The test firm Registration Number: L3732

FCC - Designation Number: CN1303

World Standardization Certification & Testing Group (Shenzhen) CO., LTD. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The test firm Designation Number: CN1303.

ANAB - Certificate Number: AT-3951

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (ANAB). Certification Number: AT-3951

6.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission Test	$\pm 3.2\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1GHz)	$\pm 4.7\text{dB}$
5	All emissions, radiated(>1GHz)	$\pm 4.7\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2.0\%$

Report No.: WSCT-ANAB-R&E250100005A-15B

7. EMC EMISSION TEST

7.1. CONDUCTED EMISSION MEASUREMENT

7.1.1. POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of "*" marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

Report No.: WSCT-ANAB-R&E250100005A-15B

TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

TEST SETUP




Report No.: WSCT-ANAB-R&E250100005A-15B

7.1.2. Test Results

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Adapter: Mode 3(the worst case)


Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1 *	0.1725	32.72	20.71	53.43	64.84	-11.41	QP
2	0.1725	11.88	20.71	32.59	54.84	-22.25	AVG
3	0.2580	25.50	20.66	46.16	61.50	-15.34	QP
4	0.2580	7.23	20.66	27.89	51.50	-23.61	AVG
5	0.2985	16.30	20.63	36.93	60.28	-23.35	QP
6	0.2985	-2.71	20.63	17.92	50.28	-32.36	AVG
7	0.5910	15.07	20.52	35.59	56.00	-20.41	QP
8	0.5910	-5.05	20.52	15.47	46.00	-30.53	AVG
9	0.8160	17.00	20.59	37.59	56.00	-18.41	QP
10	0.8160	12.72	20.59	33.31	46.00	-12.69	AVG
11	20.9670	15.42	20.33	35.75	60.00	-24.25	QP
12	20.9670	1.90	20.33	22.23	50.00	-27.77	AVG

Report No.: WSCT-ANAB-R&E250100005A-15B

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1860	23.04	20.70	43.74	64.21	-20.47	QP
2	0.1860	-0.87	20.70	19.83	54.21	-34.38	AVG
3	0.2400	26.03	20.67	46.70	62.10	-15.40	QP
4	0.2400	8.04	20.67	28.71	52.10	-23.39	AVG
5	0.5055	13.30	20.51	33.81	56.00	-22.19	QP
6	0.5055	-1.94	20.51	18.57	46.00	-27.43	AVG
7	0.8160	15.01	20.59	35.60	56.00	-20.40	QP
8 *	0.8160	11.92	20.59	32.51	46.00	-13.49	AVG
9	16.2959	11.40	20.19	31.59	60.00	-28.41	QP
10	16.2959	0.20	20.19	20.39	50.00	-29.61	AVG
11	20.5935	15.33	20.30	35.63	60.00	-24.37	QP
12	20.5935	3.36	20.30	23.66	50.00	-26.34	AVG

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)

Q.P. = Quasi-Peak AVG = average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

7.2. RADIATED EMISSION MEASUREMENT

7.2.1. Radiated Emission Limits

The field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

Report No.: WSCT-ANAB-R&E250100005A-15B


TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Report No.: WSCT-ANAB-R&E250100005A-15B

TEST SETUP

(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



Report No.: WSCT-ANAB-R&E250100005A-15B


7.2.2 Test Results

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Adapter: Mode 3(the worst case)

Please refer to following diagram for individual

Below 1GHz


Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	34.8670	37.58	-19.48	18.10	40.00	-21.90	QP
2	53.2245	37.21	-19.00	18.21	40.00	-21.79	QP
3	106.0126	47.24	-22.99	24.25	43.50	-19.25	QP
4 *	260.8294	58.26	-21.57	36.69	46.00	-9.31	QP
5	466.0078	42.21	-16.10	26.11	46.00	-19.89	QP
6	902.1223	37.32	-9.80	27.52	46.00	-18.48	QP

Report No.: WSCT-ANAB-R&E250100005A-15B

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	33.5330	45.37	-19.53	25.84	40.00	-14.16	QP
2	52.9453	44.05	-18.94	25.11	40.00	-14.89	QP
3	104.9033	40.50	-23.09	17.41	43.50	-26.09	QP
4	209.7722	46.33	-24.00	22.33	43.50	-21.17	QP
5	318.9568	51.38	-19.59	31.79	46.00	-14.21	QP
6 *	833.3171	47.21	-10.55	36.66	46.00	-9.34	QP

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)


Report No.: WSCT-ANAB-R&E250100005A-15B

TEST RESULTS

Above 1GHz(1~6GHz) :(Mode 1)

Note: The spurious above 6G is noise only, do not show on the report.


Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1388.750	39.83	-7.47	32.36	74.00	-41.64	peak
2	1388.750	29.83	-7.47	22.36	54.00	-31.64	AVG
3	2145.000	39.77	-1.26	38.51	74.00	-35.49	peak
4	2145.000	29.69	-1.26	28.43	54.00	-25.57	AVG
5	3232.500	38.95	-1.75	37.20	74.00	-36.80	peak
6	3232.500	29.01	-1.75	27.26	54.00	-26.74	AVG
7	4128.750	39.17	1.51	40.68	74.00	-33.32	peak
8	4128.750	28.81	1.51	30.32	54.00	-23.68	AVG
9	5165.000	38.47	5.78	44.25	74.00	-29.75	peak
10	5165.000	29.08	5.78	34.86	54.00	-19.14	AVG
11	5870.000	39.88	8.94	48.82	74.00	-25.18	peak
12 *	5870.000	31.15	8.94	40.09	54.00	-13.91	AVG

Report No.: WSCT-ANAB-R&E250100005A-15B

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2179.375	38.94	-1.50	37.44	74.00	-36.56	peak
2	2179.375	28.55	-1.50	27.05	54.00	-26.95	AVG
3	2937.500	38.20	-2.44	35.76	74.00	-38.24	peak
4	2937.500	28.71	-2.44	26.27	54.00	-27.73	AVG
5	3914.375	38.53	0.61	39.14	74.00	-34.86	peak
6	3914.375	29.21	0.61	29.82	54.00	-24.18	AVG
7	4834.375	38.54	4.49	43.03	74.00	-30.97	peak
8	4834.375	28.65	4.49	33.14	54.00	-20.86	AVG
9	5506.875	39.18	6.92	46.10	74.00	-27.90	peak
10	5506.875	29.79	6.92	36.71	54.00	-17.29	AVG
11	5809.375	41.00	8.52	49.52	74.00	-24.48	peak
12 *	5809.375	29.84	8.52	38.36	54.00	-15.64	AVG

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Freq. = Emission frequency in MHz

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Over = Emission Level - Limit.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Report No.: WSCT-ANAB-R&E250100005A-15B

8. Test Setup Photographs

Please refer to Annex "Set Up Photos-15B" for test setup photos

*******END OF REPORT*******