

Appendix A: Effective (Isotropic) Radiated Power Output Data

Test Result

Band	Channel	PCL	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	33.54	26.89	38.45	PASS
GSM850	190	5	33.70	27.05	38.45	PASS
GSM850	251	5	33.44	26.79	38.45	PASS
GSM1900	512	0	30.45	25.85	33.00	PASS
GSM1900	661	0	30.85	26.25	33.00	PASS
GSM1900	810	0	30.63	26.03	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	33.54	26.89	38.45	PASS
GPRS850	128	5	2	32.57	25.92	38.45	PASS
GPRS850	128	5	3	30.55	23.9	38.45	PASS
GPRS850	128	5	4	29.44	22.79	38.45	PASS
GPRS850	190	5	1	33.69	27.04	38.45	PASS
GPRS850	190	5	2	32.72	26.07	38.45	PASS
GPRS850	190	5	3	30.71	24.06	38.45	PASS
GPRS850	190	5	4	29.62	22.97	38.45	PASS
GPRS850	251	5	1	33.42	26.77	38.45	PASS
GPRS850	251	5	2	32.47	25.82	38.45	PASS
GPRS850	251	5	3	30.49	23.84	38.45	PASS
GPRS850	251	5	4	29.42	22.77	38.45	PASS
GPRS1900	512	0	1	30.45	25.85	33.00	PASS
GPRS1900	512	0	2	29.63	25.03	33.00	PASS
GPRS1900	512	0	3	27.74	23.14	33.00	PASS
GPRS1900	512	0	4	26.49	21.89	33.00	PASS
GPRS1900	661	0	1	30.82	26.22	33.00	PASS
GPRS1900	661	0	2	30.06	25.46	33.00	PASS
GPRS1900	661	0	3	28.25	23.65	33.00	PASS
GPRS1900	661	0	4	27.05	22.45	33.00	PASS
GPRS1900	810	0	1	30.62	26.02	33.00	PASS
GPRS1900	810	0	2	29.88	25.28	33.00	PASS
GPRS1900	810	0	3	28.15	23.55	33.00	PASS
GPRS1900	810	0	4	27.04	22.44	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
EGPRS850	128	8	1	27.83	21.18	38.45	PASS
EGPRS850	128	8	2	26.53	19.88	38.45	PASS
EGPRS850	128	8	3	24.12	17.47	38.45	PASS
EGPRS850	128	8	4	24.09	17.44	38.45	PASS
EGPRS850	190	8	1	27.76	21.11	38.45	PASS
EGPRS850	190	8	2	26.48	19.83	38.45	PASS
EGPRS850	190	8	3	24.14	17.49	38.45	PASS
EGPRS850	190	8	4	24.12	17.47	38.45	PASS
EGPRS850	251	8	1	27.95	21.3	38.45	PASS
EGPRS850	251	8	2	26.69	20.04	38.45	PASS
EGPRS850	251	8	3	24.31	17.66	38.45	PASS
EGPRS850	251	8	4	24.34	17.69	38.45	PASS
EGPRS1900	512	2	1	26.55	21.95	33.00	PASS
EGPRS1900	512	2	2	25.34	20.74	33.00	PASS
EGPRS1900	512	2	3	23.12	18.52	33.00	PASS
EGPRS1900	512	2	4	23.57	18.97	33.00	PASS
EGPRS1900	661	2	1	26.85	22.25	33.00	PASS
EGPRS1900	661	2	2	25.73	21.13	33.00	PASS
EGPRS1900	661	2	3	23.46	18.86	33.00	PASS
EGPRS1900	661	2	4	23.90	19.30	33.00	PASS
EGPRS1900	810	2	1	26.79	22.19	33.00	PASS
EGPRS1900	810	2	2	25.64	21.04	33.00	PASS
EGPRS1900	810	2	3	23.37	18.77	33.00	PASS
EGPRS1900	810	2	4	23.90	19.30	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)


Appendix B: Peak-to-Average Ratio(CCDF)

Test Result

Band	Channel	PCL	Result(dB)	Limit(dB)	Verdict
GSM850	190	5	2.62	13	PASS
EGPRS850	190	8	5.65	13	PASS
GSM1900	661	0	2.65	13	PASS
EGPRS1900	661	2	5.6	13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test Result

Band	Channel	PCL	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM850	128	5	0.24652	0.3189	---	PASS
GSM850	190	5	0.24430	0.3070	---	PASS
GSM850	251	5	0.24229	0.3119	---	PASS
EGPRS850	128	8	0.24871	0.3116	---	PASS
EGPRS850	190	8	0.25324	0.3149	---	PASS
EGPRS850	251	8	0.24977	0.3218	---	PASS
GSM1900	512	0	0.24742	0.3170	---	PASS
GSM1900	661	0	0.24581	0.3127	---	PASS
GSM1900	810	0	0.24581	0.3172	---	PASS
EGPRS1900	512	2	0.25033	0.3128	---	PASS
EGPRS1900	661	2	0.24986	0.3166	---	PASS
EGPRS1900	810	2	0.25098	0.3051	---	PASS

Test Graphs







Appendix D: Band Edge

Test Result

Band	Channel	PCL	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM850	128	5	823.99	-23.64	-13	PASS
GSM850	251	5	849.02	-23.20	-13	PASS
EGPRS850	128	8	823.96	-32.92	-13	PASS
EGPRS850	251	8	849.03	-34.55	-13	PASS
GSM1900	512	0	1849.98	-28.24	-13	PASS
GSM1900	810	0	1910.01	-27.44	-13	PASS
EGPRS1900	512	2	1849.99	-21.48	-13	PASS
EGPRS1900	810	2	1910.01	-19.62	-13	PASS

Test Graphs






Appendix E: Conducted Spurious Emission

Test Result

Band	Channel	PCL	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM850	128	5	0.009~0.15MHz	0.01	-55.58	-33	PASS
GSM850	128	5	0.15~30MHz	0.15	-44.5	-13	PASS
GSM850	128	5	30~1000MHz	958.26	-44.27	-13	PASS
GSM850	128	5	1000~10000MHz	1648	-28.97	-13	PASS
GSM850	190	5	0.009~0.15MHz	0.01	-53.07	-33	PASS
GSM850	190	5	0.15~30MHz	0.15	-42.54	-13	PASS
GSM850	190	5	30~1000MHz	989.07	-44.92	-13	PASS
GSM850	190	5	1000~10000MHz	1673.2	-29.83	-13	PASS
GSM850	251	5	0.009~0.15MHz	0.01	-57.14	-33	PASS
GSM850	251	5	0.15~30MHz	0.15	-42.16	-13	PASS
GSM850	251	5	30~1000MHz	365.17	-45.02	-13	PASS
GSM850	251	5	1000~10000MHz	2546.5	-29.55	-13	PASS
GSM1900	512	0	0.009~0.15MHz	0.01	-53.81	-43	PASS
GSM1900	512	0	0.15~30MHz	0.15	-41.01	-23	PASS
GSM1900	512	0	30~1000MHz	824.43	-45.71	-13	PASS
GSM1900	512	0	1000~18000MHz	16894.43	-21.95	-13	PASS
GSM1900	661	0	0.009~0.15MHz	0.01	-56.56	-43	PASS
GSM1900	661	0	0.15~30MHz	0.15	-40.05	-23	PASS
GSM1900	661	0	30~1000MHz	486.13	-46.47	-13	PASS
GSM1900	661	0	1000~18000MHz	16057.47	-22.06	-13	PASS
GSM1900	810	0	0.009~0.15MHz	0.01	-56.62	-43	PASS
GSM1900	810	0	0.15~30MHz	0.15	-44.29	-23	PASS
GSM1900	810	0	30~1000MHz	888.71	-46.34	-13	PASS
GSM1900	810	0	1000~18000MHz	17012.87	-22	-13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





JianYan Testing Group Shenzhen Co., Ltd.


No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2406054







Appendix F: Frequency Stability

Test Result

Reference Frequency: GSM850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	3.52	0.004208	±2.5	Pass
	-20	6.01	0.007184		
	-10	9.07	0.010842		
	0	7.26	0.008678		
	10	5.65	0.006754		
	20	10.65	0.012730		
	30	10.85	0.012969		
	40	7.04	0.008415		
	50	8.81	0.010531		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-4.13	-0.004937	±2.5	Pass
	3.87	6.20	0.007411		
	4.45	5.55	0.006634		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	3.91	0.004674	±2.5	Pass
	-20	0.06	0.000072		
	-10	1.26	0.001506		
	0	1.58	0.001889		
	10	4.00	0.004781		
	20	1.74	0.002080		
	30	4.42	0.005283		
	40	7.49	0.008953		
	50	8.75	0.010459		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	1.16	0.001387	±2.5	Pass
	3.87	0.42	0.000502		
	4.45	0.45	0.000538		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: PCS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	11.59	0.006165	Within authorized band for PCS 1900	Pass
	-20	13.01	0.006920		
	-10	13.66	0.007266		
	0	15.50	0.008245		
	10	11.49	0.006112		
	20	17.21	0.009154		
	30	18.60	0.009894		
	40	15.76	0.008383		
	50	10.01	0.005324		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	3.03	0.001612	Within authorized band for PCS 1900	Pass
	3.87	4.39	0.002335		
	4.45	-2.45	-0.001303		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.87	-30	-2.62	-0.001394	Within authorized band for PCS 1900	Pass
	-20	-5.81	-0.003090		
	-10	-7.81	-0.004154		
	0	-8.49	-0.004516		
	10	-8.94	-0.004755		
	20	-9.52	-0.005064		
	30	-7.23	-0.003846		
	40	-6.13	-0.003261		
	50	-0.90	-0.000479		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-6.72	-0.003574	Within authorized band for PCS 1900	Pass
	3.87	-5.04	-0.002681		
	4.45	-7.04	-0.003745		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
GSM850	190	PASS	PASS
EGPRS850	190	PASS	PASS
GSM1900	661	PASS	PASS
EGPRS1900	661	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

