

SAR TEST REPORT

Reference No. : WTS19S12087926W001 V1
FCC ID : 2ADYY-LC7
Applicant : TECNO MOBILE LIMITED
Address : ROOM 604 6/F SOUTH TOWER WORLD, FINANCE CTR HARBOUR
CITY 17 CANTON ROAD TST KL, Hong Kong
Manufacturer : SHENZHEN TECNO TECHNOLOGY CO.,LTD.
Address : 101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng
Street, Longhua District, Shenzhen City, P.R. China
Product : Mobile Phone
Model(s) : LC7
Brand Name : TECNO
Standards : FCC 47 CFR Part2(2.1093)
ANSI/IEEE C95.1-2006
IEEE 1528-2013 & Published RF Exposure KDB Procedures
Date of Receipt sample : 2019-12-17
Date of Test : 2019-12-23 to 2020-01-02
Date of Issue : 2020-01-13
Test Result : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Approved by:

Ford Wang

Ford Wang / Project Engineer



Philo Zhong

Philo Zhong / Manager

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 REVISION HISTORY	3
4 GENERAL INFORMATION	4
4.1 GENERAL DESCRIPTION OF E.U.T.	4
4.2 DETAILS OF E.U.T.	4
5 EQUIPMENT USED DURING TEST	7
5.1 EQUIPMENT LIST	7
5.2 TEST EQUIPMENT CALIBRATION	7
6 SAR INTRODUCTION.....	8
6.1 INTRODUCTION	8
6.2 SAR DEFINITION.....	8
7 SAR MEASUREMENT SETUP.....	9
8 EXPOSURE LIMIT	18
9 SYSTEM AND LIQUID VALIDATION	19
9.1 SYSTEM VALIDATION	19
9.2 LIQUID VALIDATION	21
10 TYPE A MEASUREMENT UNCERTAINTY	35
11 OUTPUT POWER VERIFICATION	38
12 EXPOSURE CONDITIONS CONSIDERATION	65
13 SAR TEST RESULTS	67
14 SAR MEASUREMENT REFERENCE	87
MAXIMUM SAR MEASUREMENT PLOTS.....	88
15 CALIBRATION REPORTS-PROBE AND DIPOLE	112
16 RE-CALIBRATION FOR DIPOLE	176

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS19S12087 926W001	2019-12-17	2019-12-23 to 2020-01-02	2020-01-08	original	-	Replaced
WTS19S12087 926W001 V1	2019-12-17	2019-12-23 to 2020-01-02	2020-01-13	Version 1	Updated	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	Mobile Phone
Model(s):	LC7
Model Description:	N/A
GSM Band(s):	GSM 850/900/1800/1900MHz
GPRS/EGPRS Class:	12
WCDMA Band(s):	FDD Band II/IV/V
LTE Band(s):	FDD Band 2/4/5/7
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40 5G-802.11a/ n(HT20/40)/ac(HT20/40/80)
Bluetooth Version:	Bluetooth v4.0 with BLE
GPS:	Support
NFC:	N/A
Hardware Version:	V1.2
Software Version:	LC7-H6116BCF-Q-191206V72

Note: This EUT has two SIM card slots, and use same one RF module. We found that RF parameters are the same, when we insert the card 1 and card 2. So we usually performed the test under main card slot 1.

4.2 Details of E.U.T.

Operation Frequency:	GSM/GPRS/EDGE 850: 824~849MHz PCS/GPRS/EDGE 1900: 1850~1910MHz WCDMA Band II: 1850~1910MHz WCDMA Band V: 824~849MHz WCDMA Band IV: 1710~1755MHz LTE Band 2: 1850~1910MHz LTE Band 4: 1710~1755MHz LTE Band 5: 842~849MHz LTE Band 7: 2500-2570MHz WiFi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz 802.11a/ n(HT20/40)/ac(HT20/40/80): 5150MHz to 5250MHz 802.11a/ n(HT20/40)/ac(HT20/40/80): 5725MHz to 5850MHz Bluetooth: 2402~2480MHz BLE: 2402-2480MHz
----------------------	--

Max. RF output power:	GSM 850: 33.54dBm PCS1900: 30.00dBm WCDMA Band II: 22.88dBm WCDMA Band V: 23.19dBm WCDMA Band IV: 22.85dBm LTE Band 2: 22.44dBm LTE Band 4: 22.93dBm LTE Band 5: 22.96dBm LTE Band 7: 22.92dBm WiFi(2.4G): 19.12dBm U-NII-1: 18.29dBm U-NII-3: 9.67dBm Bluetooth: 6.99dBm BLE: -3.31dBm
Max.SAR:	0.66 W/Kg 1g Head Tissue 0.20 W/Kg 1g Body Tissue 0.20 W/Kg 1g Hotspot
Max Simultaneous SAR	1.03 W/Kg
Type of Modulation:	GSM,GPRS: GMSK EDGE: GMSK, 8PSK WCDMA: BPSK LTE: QPSK, 16QAM WiFi: CCK, OFDM Bluetooth: GFSK, Pi/4 DQPSK,8DPSK
Antenna installation	GSM/WCDMA/LTE: internal permanent antenna WiFi/Bluetooth: internal permanent antenna
Antenna Gain:	GSM 850: -1.9dBi PCS1900: -0.6dBi WCDMA Band II: -0.6dBi WCDMA Band V: -1.9dBi WCDMA Band IV: -0.8dBi LTE Band 2: -0.6dBi LTE Band 4: -0.8dBi LTE Band 5: -1.9dBi LTE Band 7: -0.5dBi WiFi(2.4G): 1.2dBi U-NII-1: 1.2dBi U-NII-3: 1.2dBi Bluetooth: 1.2dBi
Ratings:	Battery DC 3.85V, 5850mAh

Adapter: DC 5V, 2.0A, charging from adapter
(Adapter Input: 100-240V~50/60Hz 0.35A)
Manufacturer: Dongguan Aohai Power Technology CO.,LTD
Model No.: A8A-050200U-US1

5 Equipment Used during Test

5.1 Equipment List

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Calibration Due
6 AXIS ROBOT	KUKA	KR6 R900 SIXX	502635	N/A	N/A
SATIMO Test Software	MVG	OPENSAR	OPENSAR V_4_02_27	N/A	N/A
PHANTOM TABLE	MVG	N/A	SAR_1215_01	N/A	N/A
SAM PHANTOM	MVG	SAM118	SN 11/15 SAM118	N/A	N/A
MultiMeter	Keithley	MiltiMeter 2000	4073942	2019-02-27	2020-02-26
Data Acquisition Electronics	MVG	DAE4	915	2019-02-27	2020-02-26
S-Parameter Network Analyzer	Agilent	8753E	JP38160684	2019-09-17	2020-09-16
Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	114798	2019-09-17	2020-09-16
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	/	2019-09-17	2020-09-16
E-Field Probe	MVG	SSE5	SN 07/15 EP247	2019-08-20	2020-08-19
DIPOLE 835	MVG	SID835	SN 09/15 DIP 0G835-358	2018-02-28	2020-02-27
DIPOLE 1800	MVG	SID1800	SN 09/15 DIP 1G800-360	2018-02-28	2020-02-27
DIPOLE 1900	MVG	SID1900	SN 09/15 DIP 1G900-361	2018-02-28	2020-02-27
DIPOLE 2450	MVG	SID2450	SN 09/15 DIP 2G450-363	2018-02-28	2020-02-27
DIPOLE 2600	MVG	SID2600	SN 16/15 DIP 2G600-376	2018-02-28	2020-02-27
Limesar Dielectric Probe	MVG	SCLMP	SN 11/15 OCPG 69	2019-02-28	2020-02-27
Power Amplifier	BONN	BLWA 0830 -160/100/40D	128740	2019-09-17	2020-09-16
Signal Generator	R&S	SMB100A	105942	2019-09-17	2020-09-16
Power Meter	R&S	NRP2	102031	2019-09-17	2020-09-16
Power Meter	R&S	NRVD	102284	2019-09-17	2020-09-16
USB Wideband Power Sensor	Malaysia Keysight	U2021XA	MY54340009	2019-04-19	2020-04-18
USB Wideband Power Sensor	Malaysia Keysight	U2021XA	MY54340010	2019-04-19	2020-04-18

5.2 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 SAR Introduction

6.1 Introduction

This measurement report shows compliance of the EUT with ANSI/IEEE C95.1-2006 and FCC 47 CFR Part2 (2.1093). The test procedures, as described in IEEE 1528-2013 Standard for IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques(300MHz~6GHz) and Published RF Exposure KDB Procedures

6.2 SAR Definition

- ✎ SAR : Specific Absorption Rate
- ✎ The SAR characterize the absorption of energy by a quantity of tissue
- ✎ This is related to a increase of the temperature of these tissues during a time period.

$$DAS = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

$$DAS = \frac{\sigma E^2}{\rho}$$

$$DAS = c_h \left. \frac{dT}{dt} \right|_{t=0}$$

SAR definition

$$SAR = \frac{\sigma E^2}{\rho}$$

✎ SAR : Specific Absorption Rate

- σ : Liquid conductivity

$$\circ \epsilon_r = \epsilon' - j\epsilon'' \text{ (complex permittivity of liquid)}$$

$$\circ \sigma = \frac{\epsilon'' \omega}{\epsilon_0}$$

- ρ : Liquid density


$$\circ \rho = 1000 \text{ g/L} = 1000 \text{ Kg/m}^3$$

where:

σ = conductivity of the tissue (S/m)
 ρ = mass density of the tissue (kg/m³)
 E = rms electric field strength (V/m)

7 SAR Measurement Setup

SAR bench sub-systems





Scanning System (robot)

- ✎ It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- ✎ Must be able to set the probe orthogonal of the surface of the phantom ($\pm 30^\circ$).
- ✎ Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.




SAM Phantom (Specific Anthropomorphic Mannequin)

- ▶ The probe scanning of the E-Field is done in the 2 half of the normalized head.
- ▶ The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size.
- ▶ The materials for the phantom should not affect the radiation of the device under test (DUT)
 - Permittivity < 5
- ▶ The head is filled with tissue simulating liquid.
- ▶ The hand holding the DUT does not have to be modeled.



Bi-section sagittale du fantôme avec périmètre étendu (montrée sur le côté comme lors des essais de DAS de l'appareil)



The OPENSAR system for performing compliance tests consist of the following items:

1. A standard high precision 6-axis robot (KUKA) with controller and software.
2. KUKA Control Panel (KCP).
3. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
4. The functions of the PC plug-in card are to perform the time critical task such as signal filtering, surveillance of the robot operation fast movement interrupts.
5. A computer operating Windows 7.
6. OPENSAR software.
7. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
8. The SAM phantom enabling testing left-hand right-hand and body usage.
9. The Position device for handheld EUT.
10. Tissue simulating liquid mixed according to the given recipes (see Application Note).
11. System validation dipoles to validate the proper functioning of the system.

Data Evaluation

The OPENSAR software automatically executes the following procedure to calculate the field units from the microvolt readings at the probe connector. The parameters used in the valuation are stored in the configuration modules of the software:

Probe Parameters	- Sensitivity	Norm _i
	- Conversion factor	ConvFi
	- Diode compression point Dcpi	
Device Parameter	- Frequency	f
	- Crest factor	cf
Media Parametrs	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can either be found in the component documents or be imported into the software from the configuration files issued for the OPENSAR components.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Where V_i = Compensated signal of channel i ($i = x, y, z$)

U_i = Input signal of channel i ($i = x, y, z$)

cf = Crest factor of exciting field (DASY parameter)

dcp_i = Diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

Where V_i = Compensated signal of channel i ($i = x, y, z$)

Norm_i = Sensor sensitivity of channel i ($i = x, y, z$)
μV/(V/m)² for E0field Probes

ConvF = Sensitivity enhancement in solution

a_{ij} = Sensor sensitivity factors for H-field probes

$$\begin{aligned}
 f &= \text{Carrier frequency (GHz)} \\
 E_i &= \text{Electric field strength of channel } i \text{ in V/m} \\
 H_i &= \text{Magnetic field strength of channel } i \text{ in A/m}
 \end{aligned}$$

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

$$\begin{aligned}
 \text{where } SAR &= \text{local specific absorption rate in mW/g} \\
 E_{\text{tot}} &= \text{total field strength in V/m} \\
 \sigma &= \text{conductivity in [mho/m] or [siemens/m]} \\
 \rho &= \text{equivalent tissue density in g/cm}^3
 \end{aligned}$$

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{\text{pwe}} = \frac{E_{\text{tot}}^2}{3770} \quad \text{or} \quad P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

$$\begin{aligned}
 \text{where } P_{\text{pwe}} &= \text{Equivalent power density of a plane wave in mW/cm}^2 \\
 E_{\text{tot}} &= \text{total electric field strength in V/m} \\
 H_{\text{tot}} &= \text{total magnetic field strength in A/m}
 \end{aligned}$$

SAR Evaluation – Peak Spatial - Average

The procedure for assessing the peak spatial-average SAR value consists of the following steps

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in OPENSAR software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom.

When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

- **Power Drift measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have OPENSAR software stop the measurements if this limit is exceeded.

SAR Evaluation – Peak SAR

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1528 standard. It can be conducted for 1 g and 10 g. The OPENSAR system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the fourth order least square polynomial method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

Definition of Reference Points

Ear Reference Point

Figure 6.2 shows the front, back and side views of the SAM Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERPs are 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 6.1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 6.1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 6.1 Close-up side view of ERP's



Figure 6.2 Front, back and side view of SAM

Device Reference Points

Two imaginary lines on the device need to be established: the vertical centerline and the horizontal line. The test device is placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Fig. 6.3). The “test device reference point” is then located at the same level as the center of the ear reference point. The test device is positioned so that the “vertical centerline” is bisecting the front surface of the device at it's top and bottom edges, positioning the “ear reference point” on the outer surface of both the left and right head phantoms on the ear reference point [5].




Figure 6.3 Handset Vertical Center & Horizontal Line Reference Points

Test Configuration – Positioning for Cheek / Touch

1. Position the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure below), such that the plane defined by the vertical center line and the horizontal line of the device is approximately parallel to the sagittal plane of the phantom




Figure 7.1 Front, Side and Top View of Cheek/Touch Position

2. Translate the device towards the phantom along the line passing through RE and LE until the device touches the ear.
3. While maintaining the device in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).
4. Rotate the device around the vertical centerline until the device (horizontal line) is symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the device contact with the ear, rotate the device about the line NF until any point on the device is in contact with a phantom point below the ear (cheek). See Figure below.




Figure 7.2 Side view w/ relevant markings

Test Configuration – Positioning for Ear / 15° Tilt

With the test device aligned in the Cheek/Touch Position”:

1. While maintaining the orientation of the device, retract the device parallel to the reference plane far enough to enable a rotation of the device by 15 degrees.
2. Rotate the device around the horizontal line by 15 degrees.
3. While maintaining the orientation of the device, move the device parallel to the reference plane until any part of the device touches the head. (In this position, point A is located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, the angle of the device shall be reduced. The tilted position is obtained when any part of the device is in contact with the ear as well as a second part of the device is in contact with the head (see Figure below).





Figure 7.3 Front, Side and Top View of Ear/15° Tilt Position

Test Position – Body Configurations

Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.0 cm or holster surface and the flat phantom to 0 cm.



8 Exposure limit

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements are included in the user's manual.

Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 8.1 Human Exposure Limits

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Brain	1.60	8.00
SPATIAL AVERAGE SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00


¹ The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

² The Spatial Average value of the SAR averaged over the whole body.

³ The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

9 System and liquid validation

9.1 System validation



The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

The output power on dipole port must be calibrated to 30 dBm (1000 mW) before dipole is connected.

Numerical reference SAR values (W/kg) for reference dipole and flat phantom

Frequency (MHz)	1g SAR	10g SAR	Local SAR at surface(above feed-point)	Local SAR at surface(y = 2 cm offset from feedpoint)
300	3.02	2.04	4.40	2.10
450	4.92	3.28	7.20	3.20
750	8.49	5.55	12.6	4.59
835	9.56	6.22	14.1	4.90
900	10.9	6.99	16.4	5.40
1450	29.0	16.0	50.2	6.50
1800	38.4	20.1	69.5	6.80
1900	39.7	20.5	72.1	6.60
2000	41.1	21.1	74.6	6.50
2450	52.4	24.0	104	7.70
2600	55.3	24.6	113	8.29
3000	63.8	25.7	140	9.50

Table 1: system validation (1g)

Measurement Date	Frequency (MHz)	Liquid Type (head/body)	1W Target SAR1g (W/kg)	Measured SAR1g (W/kg)	1W Normalized SAR1g (W/kg)	Deviation (±10%)
2019-12-23	835	head	9.58	0.957	9.57	-0.1
2019-12-23	835	body	9.78	1.029	10.29	5.2
2019-12-24	1800	head	38.76	4.112	41.12	6.1
2019-12-24	1800	body	38.90	3.712	37.12	-4.6
2020-01-02	1900	head	39.49	3.987	39.87	1.0
2020-01-02	1900	body	40.01	3.896	38.96	-2.6
2019-12-31	2450	head	54.31	5.548	55.48	2.2
2019-12-31	2450	body	53.67	5.265	52.65	-1.9
2020-01-02	2600	head	56.32	5.201	52.01	-7.7
2020-01-02	2600	body	55.20	5.341	53.41	-3.2

Note: system check input power: 100mW

9.2 liquid validation

The dielectric parameters were checked prior to assessment using the HP85070C dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

KDB 865664 recommended Tissue Dielectric Parameters

The head and body tissue parameters given in this below table should be used to measure the SAR of transmitters operating in 100 MHz to 6 GHz frequency range. The tissue dielectric parameters of the tissue medium at the test frequency should be within the tolerance required in this document. The dielectric parameters should be linearly interpolated between the closest pair of target frequencies to determine the applicable dielectric parameters corresponding to the device test frequency.

The head tissue dielectric parameters recommended by IEEE Std 1528-2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in 1528 are derived from tissue dielectric parameters computed from the 4-Cole-Cole equations described above and extrapolated according to the head parameters specified in 1528.

Target Frequency	Head Tissue		Body Tissue	
MHz	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
2600	39.0	1.96	52.5	2.16
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness Power drifts in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Table 2: Recommended Dielectric Performance of Tissue


Recommended Dielectric Performance of Tissue												
Ingredients (% by weight)	Frequency (MHz)											
	750		835		1800		1900		2450		2600	
Tissue	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	40.52	51.83	41.45	52.4	55.2	70.2	54.9	40.4	62.7	73.2	54.8	68.1
Salt (Nacl)	1.61	1.52	1.45	1.4	0.3	0.4	0.18	0.5	0.5	0.04	0.1	0.01
Sugar	57.67	46.45	56.0	45.0	0.0	0.0	0.0	58.0	0.0	0.0	0.0	0.0
HEC	0.1	0.1	1.0	1.0	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0
Bactericide	0.1	0.1	0.1	0.1	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.0
Triton x-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0	0.0	0.0
DGBE	0.0	0.0	0.0	0.0	44.5	29.4	44.92	0.0	0.0	26.7	45.1	31.8
Dielectric	40.93	54.32	42.54	56.1	40.0	53.3	39.9	54.0	39.8	52.5	39.0	52.5
Conductivity	0.87	0.95	0.91	0.95	1.40	1.52	1.42	1.45	1.88	1.78	1.96	2.15


Table 3: Dielectric Performance of Head Tissue Simulating Liquid


Temperature: 21°C , Relative humidity: 57%				
Frequency(MHz)	Measured Date	Description	Dielectric Parameters	
			ϵ_r	$\sigma(\text{s/m})$
835	2019-12-23	Target Value $\pm 5\%$ window	41.50 39.43 — 43.58	0.90 0.855 — 0.945
		Measurement Value	41.79	0.92
1700	2019-12-24	Target Value $\pm 5\%$ window	40.00 38.00 — 42.00	1.40 1.33 — 1.47
		Measurement Value	41.99	1.37
1800	2019-12-24	Target Value $\pm 5\%$ window	40.00 38.00 — 42.00	1.40 1.33 — 1.47
		Measurement Value	40.59	1.38
1900	2020-01-02	Target Value $\pm 5\%$ window	40.00 38.00 — 42.00	1.40 1.33 — 1.47
		Measurement Value	40.91	1.45
2450	2019-12-31	Target Value $\pm 5\%$ window	39.2 37.24 — 41.16	1.80 1.71 — 1.89
		Measurement Value	39.16	1.86
2500	2020-01-02	Target Value $\pm 5\%$ window	39.0 37.05 — 40.95	1.96 1.87 — 2.05
		Measurement Value	39.49	1.97
2600	2020-01-02	Target Value $\pm 5\%$ window	39.0 37.05 — 40.95	1.96 1.87 — 2.05
		Measurement Value	39.84	1.98


Table 4: Dielectric Performance of Body Tissue Simulating Liquid


Temperature: 21°C , Relative humidity: 57% , Measured Date: 2019-12-23				
Frequency(MHz)	Measured Date	Description	Dielectric Parameters	
			ϵ_r	$\sigma(\text{s/m})$
835	2019-12-23	Target Value $\pm 5\%$ window	55.2 52.63 — 57.75	0.97 0.922 — 1.018
		Measurement Value	55.59	0.99
1700	2019-12-24	Target Value $\pm 5\%$ window	53.30 50.64 — 55.97	1.52 1.44 — 1.60
		Measurement Value	53.61	1.51
1800	2019-12-24	Target Value $\pm 5\%$ window	53.30 50.64 — 55.97	1.52 1.44 — 1.60
		Measurement Value	53.60	1.57
1900	2020-01-02	Target Value $\pm 5\%$ window	53.30 50.64 — 55.97	1.52 1.44 — 1.60
		Measurement Value	53.15	1.53
2450	2019-12-31	Target Value $\pm 5\%$ window	52.84 50.07 — 55.34	1.95 1.86 — 2.05
		Measurement Value	53.20	1.90
2500	2020-01-02	Target Value $\pm 5\%$ window	52.50 49.88 — 55.12	2.16 2.06 — 2.26
		Measurement Value	52.03	2.15
2600	2020-01-02	Target Value $\pm 5\%$ window	52.50 49.88 — 55.12	2.16 2.06 — 2.26
		Measurement Value	52.84	2.18


System Verification Plots**Product Description:** Dipole**Model:** SID835**Test Date:** 2019-12-23


Product Description: Dipole**Model: SID835****Test Date: 2019-12-23**

Product Description: Dipole**Model: SID1800****Test Date: 2019-12-24**

Product Description: Dipole**Model: SID1800****Test Date: 2019-12-24**




Product Description: Dipole**Model: SID1900****Test Date: 2020-01-02**


Product Description: Dipole**Model: SID1900****Test Date: 2020-01-02**


Product Description: Dipole**Model: SID2450****Test Date: 2019-12-31**

Product Description: Dipole**Model: SID2450****Test Date: 2019-12-31**

Medium(liquid type)	MSL_2450
Frequency (MHz)	2450.000
Relative permittivity (real part)	53.20
Conductivity (S/m)	1.90
Input power	100mW
E-Field Probe	SN 07/15 EP247
Duty cycle	1:1
Conversion Factor	4.61
Sensor-surface	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.69
SAR 10g (W/Kg)	2.542104
SAR 1g (W/Kg)	5.265269
SURFACE SAR	VOLUME SAR



Product Description: Dipole**Model: SID2600****Test Date: 2020-01-02**

Product Description: Dipole**Model: SID2600****Test Date: 2020-01-02**

10 Type a Measurement Uncertainty

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table below :

Uncertainty Distribution	Normal	Rectangle	Triangular	U Shape
Multi-plying Factor(a)	$1/k(b)$	$1 / \sqrt{3}$	$1 / \sqrt{6}$	$1 / \sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type -sum- by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %.

The COMOSAR Uncertainty Budget is show in below table:

UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK								
a	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$(1_{-Cp})^{1/2}$	$(1_{-Cp})^{1/2}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	2.41	2.41	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0.00	N	1	1	1	0.00	0.00	∞
Readout Electronics	0.50	N	1	1	1	0.50	0.50	∞
Reponse Time	0.0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.40	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of experimental source from numerical source	4.00	N	1	1	1	4.00	4.00	∞
Input power and SAR drift measurement	5.00	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid Distance	2.00	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and thickness tolerances)	4.00	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2.00	N	1	1	1	2.00	1.68	∞
Liquid conductivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid conductivity - measurement uncertainty	4.00	N	1	0.23	0.26	0.92	1.04	M
Liquid permittivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid permittivity - measurement uncertainty	5.00	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				10.21	10.12	
Expanded Uncertainty (95% Confidence interval)		k				19.91	19.73	

UNCERTAINTY EVALUATION FOR HANDSET SAR TEST								
a	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$(1_{-Cp})^{1/2}$	$(1_{-Cp})^{1/2}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	2.41	2.41	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3.00	N	1	1	1	3.00	3.00	∞
Readout Electronics	0.50	N	1	1	1	0.50	0.50	∞
Reponse Time	0.0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.40	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.60	N	1	1	1	2.60	2.60	N-1
Device Holder Uncertainty	3.00	N	1	1	1	3.00	3.00	N-1
Output power Variation - SAR drift measurement	5.00	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2.00	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and thickness tolerances)	4.00	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2.00	N	1	1	1	2.00	1.68	∞
Liquid conductivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid conductivity - measurement uncertainty	4.00	N	1	0.23	0.26	0.92	1.04	M
Liquid permittivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid permittivity - measurement uncertainty	5.00	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				10.63	10.54	
Expanded Uncertainty (95% Confidence interval)		k				20.73	20.56	

11 Output Power Verification

Test Condition:

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The base station simulator was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ± 1.5 dB.
3. Environmental Conditions

Temperature	23°C
Relative Humidity	53%
Atmospheric Pressure	1019mbar
4. Test Date : 2019-12-23
Tested By : Andy Feng

Test Procedures:

Mobile Phone radio output power measurement

1. The transmitter output port was connected to base station emulator.
2. Establish communication link between emulator and EUT and set EUT to operate at maximum output power all the time.
3. Select lowest, middle, and highest channels for each band and different possible test mode.
4. Measure the conducted peak burst power and conducted average burst power from EUT antenna port.

Other radio output power measurement:

The output power was measured using power meter at low, mid, and hi channels.

Source-based Time Averaged Burst Power Calculation:

For TDMA, the following duty cycle factor was used to calculate the source-based time average power

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Duty cycle factor	-9.03 dB	-6.02 dB	-4.26 dB	-3.01 dB
Crest Factor	8	4	2.66	2

Remark: Time slot duty cycle factor = $10 * \log(\text{Time Slot Duty Cycle})$

Source based time averaged power = Maximum burst averaged power (1 Uplink) – 9.03 dB

Source based time averaged power = Maximum burst averaged power (2 Uplink) – 6.02 dB

Source based time averaged power = Maximum burst averaged power (3 Uplink) – 4.26 dB

Source based time averaged power = Maximum burst averaged power (4 Uplink) – 3.01 dB

Test Result:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice	33.45	33.52	33.53	33±1	29.94	29.91	29.94	29±1
GPRS 1 slots	33.44	33.49	33.54	33±1	29.96	29.96	30.00	29±1
GPRS 2 slots	32.52	32.64	32.68	32±1	29.15	29.16	29.16	29±1
GPRS 3 slots	31.69	31.81	31.81	31±1	28.35	28.34	28.33	28±1
GPRS 4 slots	30.84	30.92	30.95	30±1	27.51	27.52	27.56	27±1
EGPRS 1 slots	25.90	25.78	25.71	25±1	26.20	26.09	25.93	26±1
EGPRS 2 slots	25.05	24.91	24.92	25±1	25.36	25.25	25.14	25±1
EGPRS 3 slots	24.21	24.03	24.05	24±1	24.54	24.41	24.32	24±1
EGPRS 4 slots	23.40	23.21	23.19	23±1	23.66	23.61	23.51	23±1
Remark : GPRS, CS1 coding scheme. EGPRS, MCS5 coding scheme. Multi 1 Slot , Support Max 4 downlink, 1 uplink , 5 working link Multi 2 Slots , Support Max 4 downlink, 2 uplink , 5 working link Multi 3 Slots , Support Max 4 downlink, 3 uplink , 5 working link Multi 4 Slots , Support Max 4 downlink, 4 uplink , 5 working link								

Source Based time Average Power (dBm)								
Band	GSM850				PCS1900			
Channel	128	190	251	Time Average factor	512	661	810	Time Average factor
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice	24.42	24.49	24.50	-9.03	20.91	20.88	20.91	-9.03
GPRS 1 slots	24.41	24.46	24.51	-9.03	20.93	20.93	20.97	-9.03
GPRS 2 slots	26.50	26.62	26.66	-6.02	23.13	23.14	23.14	-6.02
GPRS 3 slots	27.43	27.55	27.55	-4.26	24.09	24.08	24.07	-4.26
GPRS 4 slots	27.83	27.91	27.94	-3.01	24.50	24.51	24.55	-3.01
EGPRS 1 slots	16.87	16.75	16.68	-9.03	17.17	17.06	16.90	-9.03
EGPRS 2 slots	19.03	18.89	18.90	-6.02	19.34	19.23	19.12	-6.02
EGPRS 3 slots	19.95	19.77	19.79	-4.26	20.28	20.15	20.06	-4.26
EGPRS 4 slots	20.39	20.20	20.18	-3.01	20.65	20.60	20.50	-3.01
Remark : Time average factor = 1 uplink , $10 \cdot \log(1/8) = -9.03\text{dB}$, 2 uplink , $10 \cdot \log(2/8) = -6.02\text{dB}$, 3 uplink , $10 \cdot \log(3/8) = -4.26\text{dB}$, 4 uplink , $10 \cdot \log(4/8) = -3.01\text{dB}$ Source based time average power = Burst Average power + Time Average factor								

Note: DUT was set in GPRS(4Tx slots) due to the Maximum source-base time average output power for body SAR.

WCDMA - Average Power (dBm)								
Band	WCDMA Band II				WCDMA Band V			
Channel	9262	9400	9538	Tune up Power tolerant	4132	4183	4233	Tune up Power tolerant
Frequency (MHz)	1852.4	1880	1907.6	/	826.4	836.6	846.6	/
RMC 12.2k	22.88	22.84	22.84	22±1	23.10	23.17	23.19	23.0±1
HSDPA Subtest-1	21.81	21.76	21.75	21±1	22.01	22.07	22.07	22±1
HSDPA Subtest-2	21.78	21.74	21.71	21±1	21.98	22.04	22.03	22±1
HSDPA Subtest-3	21.75	21.71	21.68	21±1	21.95	22.01	22.00	22±1
HSDPA Subtest-4	21.71	21.65	21.65	21±1	21.93	21.98	21.97	22±1
HSUPA Subtest-1	21.37	21.33	21.40	21±1	21.55	21.68	21.69	22±1
HSUPA Subtest-2	21.33	21.30	21.35	21±1	21.51	21.65	21.65	22±1
HSUPA Subtest-3	21.30	21.27	21.31	21±1	21.47	21.61	21.62	22±1
HSUPA Subtest-4	21.28	21.25	21.28	21±1	21.45	21.58	21.57	22±1
HSUPA Subtest-5	21.24	21.22	21.24	21±1	21.42	21.55	21.55	22±1

WCDMA - Average Power (dBm)				
Band	WCDMA BandIV			
Channel	1312	1413	1513	Tune up Power tolerant
Frequency (MHz)	1712.4	1732.6	1752.6	/
RMC 12.2k	22.77	22.80	22.85	22±1
HSDPA Subtest-1	21.70	21.69	21.74	21±1
HSDPA Subtest-2	21.68	21.66	21.71	21±1
HSDPA Subtest-3	21.61	21.62	21.68	21±1
HSDPA Subtest-4	21.60	21.60	21.63	21±1
HSUPA Subtest-1	21.30	21.27	21.33	21±1
HSUPA Subtest-2	21.27	21.24	21.31	21±1
HSUPA Subtest-3	21.23	21.21	21.28	21±1
HSUPA Subtest-4	21.21	21.18	21.24	21±1
HSUPA Subtest-5	21.20	21.15	21.22	21±1

LTE Power Reduction

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signalling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
--					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE Band 2:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	18607	1850.7	QPSK	1	0	21.96	21.5±1	/
				1	2	22.17	21.5±1	/
				1	5	21.98	21.5±1	/
				3	0	22.01	21.5±1	/
				3	1	22.08	21.5±1	/
				3	2	22.08	21.5±1	/
				6	0	21.04	20.5±1	1.0
			16QAM	1	0	21	20.5±1	1.0
				1	2	21.18	20.5±1	1.0
				1	5	21.05	20.5±1	1.0
				3	0	21.25	20.5±1	1.0
				3	1	21.26	20.5±1	1.0
				3	2	21.25	20.5±1	1.0
				6	0	20.23	20.5±1	1.0
	18900	1880	QPSK	1	0	21.89	21.5±1	/
				1	2	22.09	21.5±1	/
				1	5	21.89	21.5±1	/
				3	0	21.99	21.5±1	/
				3	1	22.04	21.5±1	/
				3	2	21.96	21.5±1	/
				6	0	21.04	20.5±1	1.0
			16QAM	1	0	21.07	20.5±1	1.0
				1	2	21.21	20.5±1	1.0
				1	5	21.03	20.5±1	1.0
				3	0	21.02	20.5±1	1.0
				3	1	21.02	20.5±1	1.0
				3	2	21.04	20.5±1	1.0
				6	0	20.16	20.5±1	1.0
	19193	1909.3	QPSK	1	0	21.91	21.5±1	/
				1	2	22.08	21.5±1	/
				1	5	21.91	21.5±1	/
				3	0	21.92	21.5±1	/
				3	1	22	21.5±1	/
				3	2	21.46	21.5±1	/
				6	0	21.12	20.5±1	1.0
			16QAM	1	0	21.29	20.5±1	1.0
				1	2	21.44	20.5±1	1.0
				1	5	21.25	20.5±1	1.0
				3	0	21.14	20.5±1	1.0
				3	1	21.16	20.5±1	1.0
				3	2	21.12	20.5±1	1.0
				6	0	19.92	20.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	18615	1851.5	QPSK	1	0	22.03	21.5±1	/
				1	8	22.04	21.5±1	/
				1	14	22.04	21.5±1	/
				6	0	21.13	20.5±1	1.0
				6	4	21.17	20.5±1	1.0
				6	9	21.12	20.5±1	1.0
				15	0	21.13	20.5±1	1.0
			16QAM	1	0	21.07	20.5±1	1.0
				1	8	20.99	20.5±1	1.0
				1	14	21.03	20.5±1	1.0
				6	0	20.23	20.5±1	1.0
				6	4	20.27	20.5±1	1.0
				6	9	20.24	20.5±1	1.0
				15	0	20.13	20.5±1	1.0
	18900	1880	QPSK	1	0	22.04	21.5±1	/
				1	8	22.03	21.5±1	/
				1	14	22.02	21.5±1	/
				6	0	21.07	20.5±1	1.0
				6	4	21.15	20.5±1	1.0
				6	9	21.1	20.5±1	1.0
				15	0	21.08	20.5±1	1.0
			16QAM	1	0	21.4	20.5±1	1.0
				1	8	21.42	20.5±1	1.0
				1	14	21.43	20.5±1	1.0
				6	0	20.18	20.5±1	1.0
				6	4	20.18	20.5±1	1.0
				6	9	20.14	20.5±1	1.0
				15	0	20.11	20.5±1	1.0
	19185	1908.5	QPSK	1	0	22.01	21.5±1	/
				1	8	21.99	21.5±1	/
				1	14	22.02	21.5±1	/
				6	0	21.09	20.5±1	1.0
				6	4	21.12	20.5±1	1.0
				6	9	21.04	20.5±1	1.0
				15	0	21.07	20.5±1	1.0
			16QAM	1	0	21.07	20.5±1	1.0
				1	8	21.01	20.5±1	1.0
				1	14	21.01	20.5±1	1.0
				6	0	20.08	20.5±1	1.0
				6	4	20.15	20.5±1	1.0
				6	9	20.11	20.5±1	1.0
				15	0	20.04	20.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	18625	1852.5	QPSK	1	0	22.01	21.5±1	/
				1	12	22.15	21.5±1	/
				1	24	21.99	21.5±1	/
				12	0	21.14	20.5±1	1.0
				12	6	21.18	20.5±1	1.0
				12	11	21.13	20.5±1	1.0
				25	0	21.13	20.5±1	1.0
			16QAM	1	0	21.25	20.5±1	1.0
				1	12	21.36	20.5±1	1.0
				1	24	21.19	20.5±1	1.0
				12	0	20.16	20.5±1	1.0
				12	6	20.22	20.5±1	1.0
				12	11	20.15	20.5±1	1.0
				25	0	20.16	20.5±1	1.0
	18900	1880	QPSK	1	0	22.01	21.5±1	/
				1	12	22.05	21.5±1	/
				1	24	22.05	21.5±1	/
				12	0	21.07	20.5±1	1.0
				12	6	21.12	20.5±1	1.0
				12	11	21.06	20.5±1	1.0
				25	0	21.09	20.5±1	1.0
			16QAM	1	0	21.47	20.5±1	1.0
				1	12	21.27	20.5±1	1.0
				1	24	21.24	20.5±1	1.0
				12	0	20.21	20.5±1	1.0
				12	6	20.24	20.5±1	1.0
				12	11	20.17	20.5±1	1.0
				25	0	20.18	20.5±1	1.0
	19175	1907.5	QPSK	1	0	21.92	21.5±1	/
				1	12	22.03	21.5±1	/
				1	24	21.94	21.5±1	/
				12	0	21.05	20.5±1	1.0
				12	6	21.13	20.5±1	1.0
				12	11	21.05	20.5±1	1.0
				25	0	21.09	20.5±1	1.0
			16QAM	1	0	21.1	20.5±1	1.0
				1	12	21.19	20.5±1	1.0
				1	24	21.09	20.5±1	1.0
				12	0	20.09	20.5±1	1.0
				12	6	20.14	20.5±1	1.0
				12	11	20.06	20.5±1	1.0
				25	0	20.01	20.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	18650	1855	QPSK	1	0	22.11	21.5±1	/
				1	24	22.31	21.5±1	/
				1	49	22.04	21.5±1	/
				25	0	21.15	20.5±1	1.0
				25	12	21.22	20.5±1	1.0
				25	24	21.15	20.5±1	1.0
				50	0	21.22	20.5±1	1.0
			16QAM	1	0	21.08	20.5±1	1.0
				1	24	21.29	20.5±1	1.0
				1	49	21.05	20.5±1	1.0
				25	0	20.19	20.5±1	1.0
				25	12	20.24	20.5±1	1.0
				25	24	20.21	20.5±1	1.0
				50	0	20.2	20.5±1	1.0
	18900	1880	QPSK	1	0	22.04	21.5±1	/
				1	24	22.23	21.5±1	/
				1	49	22.05	21.5±1	/
				25	0	21.12	20.5±1	1.0
				25	12	21.17	20.5±1	1.0
				25	24	21.12	20.5±1	1.0
				50	0	21.15	20.5±1	1.0
			16QAM	1	0	21.44	20.5±1	1.0
				1	24	21.48	20.5±1	1.0
				1	49	21.45	20.5±1	1.0
				25	0	20.17	20.5±1	1.0
				25	12	20.19	20.5±1	1.0
				25	24	20.12	20.5±1	1.0
				50	0	20.16	20.5±1	1.0
	19150	1905	QPSK	1	0	22.03	21.5±1	/
				1	24	22.21	21.5±1	/
				1	49	22.04	21.5±1	/
				25	0	21.2	20.5±1	1.0
				25	12	21.11	20.5±1	1.0
				25	24	21.14	20.5±1	1.0
				50	0	21.15	20.5±1	1.0
			16QAM	1	0	21.03	20.5±1	1.0
				1	24	21.19	20.5±1	1.0
				1	49	21.02	20.5±1	1.0
				25	0	20.29	20.5±1	1.0
				25	12	20.19	20.5±1	1.0
				25	24	20.19	20.5±1	1.0
				50	0	20.15	20.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	18675	1857.5	QPSK	1	0	22.03	21.5±1	/
				1	37	22.13	21.5±1	/
				1	74	21.98	21.5±1	/
				36	0	21.22	20.5±1	1.0
				36	16	21.27	20.5±1	1.0
				36	35	21.2	20.5±1	1.0
				75	0	21.23	20.5±1	1.0
			16QAM	1	0	21.04	20.5±1	1.0
				1	37	21.09	20.5±1	1.0
				1	74	21.02	20.5±1	1.0
				36	0	20.18	20.5±1	1.0
				36	16	20.24	20.5±1	1.0
				36	35	20.15	20.5±1	1.0
				75	0	20.22	20.5±1	1.0
	18900	1880	QPSK	1	0	22.01	21.5±1	/
				1	37	22.06	21.5±1	/
				1	74	21.94	21.5±1	/
				36	0	21.21	20.5±1	1.0
				36	16	21.22	20.5±1	1.0
				36	35	21.16	20.5±1	1.0
				75	0	21.21	20.5±1	1.0
			16QAM	1	0	21.39	20.5±1	1.0
				1	37	21.45	20.5±1	1.0
				1	74	21.33	20.5±1	1.0
				36	0	20.17	20.5±1	1.0
				36	16	20.19	20.5±1	1.0
				36	35	20.19	20.5±1	1.0
				75	0	20.2	20.5±1	1.0
	19125	1902.5	QPSK	1	0	21.95	21.5±1	/
				1	37	22.01	21.5±1	/
				1	74	21.95	21.5±1	/
				36	0	21.24	20.5±1	1.0
				36	16	21.17	20.5±1	1.0
				36	35	21.16	20.5±1	1.0
				75	0	21.21	20.5±1	1.0
			16QAM	1	0	21.32	20.5±1	1.0
				1	37	21.41	20.5±1	1.0
				1	74	21.33	20.5±1	1.0
				36	0	20.1	20.5±1	1.0
				36	16	20.09	20.5±1	1.0
				36	35	20.06	20.5±1	1.0
				75	0	20.12	20.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	18700	1860	QPSK	1	0	21.91	21.5±1	/
				1	49	22.37	21.5±1	/
				1	99	21.81	21.5±1	/
				50	0	21.18	20.5±1	1.0
				50	24	21.19	20.5±1	1.0
				50	49	21.09	20.5±1	1.0
				100	0	21.14	20.5±1	1.0
			16QAM	1	0	21.48	20.5±1	1.0
				1	49	21.42	20.5±1	1.0
				1	99	21.37	20.5±1	1.0
				50	0	20.2	20.5±1	1.0
				50	24	20.25	20.5±1	1.0
				50	49	20.11	20.5±1	1.0
				100	0	20.22	20.5±1	1.0
	18900	1880	QPSK	1	0	21.88	21.5±1	/
				1	49	22.44	21.5±1	/
				1	99	21.84	21.5±1	/
				50	0	21.18	20.5±1	1.0
				50	24	21.47	20.5±1	1.0
				50	49	21.09	20.5±1	1.0
				100	0	21.13	20.5±1	1.0
			16QAM	1	0	21.34	20.5±1	1.0
				1	49	21.43	20.5±1	1.0
				1	99	21.25	20.5±1	1.0
				50	0	20.2	20.5±1	1.0
				50	24	20.18	20.5±1	1.0
				50	49	20.11	20.5±1	1.0
				100	0	20.19	20.5±1	1.0
	19100	1900	QPSK	1	0	21.73	21.5±1	/
				1	49	22.34	21.5±1	/
				1	99	21.75	21.5±1	/
				50	0	21.19	20.5±1	1.0
				50	24	21.09	20.5±1	1.0
				50	49	20.97	20.5±1	1.0
				100	0	21.14	20.5±1	1.0
			16QAM	1	0	21.17	20.5±1	1.0
				1	49	21.45	20.5±1	1.0
				1	99	21.16	20.5±1	1.0
				50	0	20.17	20.5±1	1.0
				50	24	20.08	20.5±1	1.0
				50	49	19.96	20.5±1	1.0
				100	0	20.13	20.5±1	1.0

LTE Band 4:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	19957	1710.7	QPSK	1	0	22.16	22.0±1	/
				1	2	22.38	22.0±1	/
				1	5	22.15	22.0±1	/
				3	0	22.25	22.0±1	/
				3	1	22.29	22.0±1	/
				3	2	22.22	22.0±1	/
			16QAM	6	0	21.25	21.0±1	1.0
				1	0	21.29	21.0±1	1.0
				1	2	21.31	21.0±1	1.0
				1	5	21.31	21.0±1	1.0
				3	0	21.32	21.0±1	1.0
				3	1	21.32	21.0±1	1.0
				3	2	21.3	21.0±1	1.0
				6	0	20.4	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.08	22.0±1	/
				1	2	22.21	22.0±1	/
				1	5	22.09	22.0±1	/
				3	0	22.17	22.0±1	/
				3	1	22.21	22.0±1	/
				3	2	22.16	22.0±1	/
			16QAM	6	0	21.2	21.0±1	1.0
				1	0	21.5	21.0±1	1.0
				1	2	21.71	21.0±1	1.0
				1	5	21.49	21.0±1	1.0
				3	0	21.39	21.0±1	1.0
				3	1	21.39	21.0±1	1.0
				3	2	21.4	21.0±1	1.0
				6	0	20.1	21.0±1	1.0
	20393	1754.3	QPSK	1	0	22.12	22.0±1	/
				1	2	22.31	22.0±1	/
				1	5	22.11	22.0±1	/
				3	0	22.17	22.0±1	/
				3	1	22.21	22.0±1	/
				3	2	22.22	22.0±1	/
			16QAM	6	0	21.19	21.0±1	1.0
				1	0	21.15	21.0±1	1.0
				1	2	21.37	21.0±1	1.0
				1	5	21.17	21.0±1	1.0
				3	0	21.39	21.0±1	1.0
				3	1	21.43	21.0±1	1.0
				3	2	21.39	21.0±1	1.0
				6	0	20.38	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	19965	1711.5	QPSK	1	0	22.21	22.0±1	/
				1	8	22.16	22.0±1	/
				1	14	22.11	22.0±1	/
				6	0	21.26	21.0±1	1.0
				6	4	21.29	21.0±1	1.0
				6	9	21.25	21.0±1	1.0
				15	0	21.23	21.0±1	1.0
			16QAM	1	0	21.17	21.0±1	1.0
				1	8	21.13	21.0±1	1.0
				1	14	21.07	21.0±1	1.0
				8	0	20.37	21.0±1	1.0
				8	4	20.4	21.0±1	1.0
				8	9	20.35	21.0±1	1.0
				15	0	20.29	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.14	22.0±1	/
				1	8	22.13	22.0±1	/
				1	14	22.12	22.0±1	/
				6	0	21.21	21.0±1	1.0
				6	4	21.23	21.0±1	1.0
				6	9	21.22	21.0±1	1.0
				15	0	21.18	21.0±1	1.0
			16QAM	1	0	21.55	21.0±1	1.0
				1	8	21.57	21.0±1	1.0
				1	14	21.54	21.0±1	1.0
				6	0	20.31	21.0±1	1.0
				6	4	20.36	21.0±1	1.0
				6	9	20.29	21.0±1	1.0
				15	0	20.23	21.0±1	1.0
	20385	1753.5	QPSK	1	0	22.22	22.0±1	/
				1	8	22.18	22.0±1	/
				1	14	22.21	22.0±1	/
				6	0	21.24	21.0±1	1.0
				6	4	21.32	21.0±1	1.0
				6	9	21.22	21.0±1	1.0
				15	0	21.25	21.0±1	1.0
			16QAM	1	0	21.28	21.0±1	1.0
				1	8	21.25	21.0±1	1.0
				1	14	21.22	21.0±1	1.0
				8	0	20.29	21.0±1	1.0
				8	4	20.31	21.0±1	1.0
				8	9	20.25	21.0±1	1.0
				15	0	20.2	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	19975	1712.5	QPSK	1	0	22.12	22.0±1	/
				1	49	22.21	22.0±1	/
				1	99	22.08	22.0±1	/
				12	0	21.18	21.0±1	1.0
				12	24	21.27	21.0±1	1.0
				12	49	21.17	21.0±1	1.0
				25	0	21.19	21.0±1	1.0
			16QAM	1	0	21.32	21.0±1	1.0
				1	49	21.39	21.0±1	1.0
				1	99	21.28	21.0±1	1.0
				12	0	20.26	21.0±1	1.0
				12	24	20.32	21.0±1	1.0
				12	49	20.23	21.0±1	1.0
				25	0	20.21	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.05	22.0±1	/
				1	49	22.2	22.0±1	/
				1	99	22.09	22.0±1	/
				12	0	21.15	21.0±1	1.0
				12	24	21.24	21.0±1	1.0
				12	49	21.13	21.0±1	1.0
				25	0	21.13	21.0±1	1.0
			16QAM	1	0	21.61	21.0±1	1.0
				1	49	21.72	21.0±1	1.0
				1	99	21.59	21.0±1	1.0
				12	0	20.31	21.0±1	1.0
				12	24	20.39	21.0±1	1.0
				12	49	20.26	21.0±1	1.0
				25	0	20.25	21.0±1	1.0
	20375	1752.5	QPSK	1	0	22.08	22.0±1	/
				1	49	22.18	22.0±1	/
				1	99	22.12	22.0±1	/
				12	0	21.19	21.0±1	1.0
				12	24	21.29	21.0±1	1.0
				12	49	21.15	21.0±1	1.0
				25	0	21.22	21.0±1	1.0
			16QAM	1	0	21.26	21.0±1	1.0
				1	49	21.41	21.0±1	1.0
				1	99	21.27	21.0±1	1.0
				12	0	20.26	21.0±1	1.0
				12	24	20.32	21.0±1	1.0
				12	49	20.24	21.0±1	1.0
				25	0	20.15	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20000	1715	QPSK	1	0	22.18	22.0±1	/
				1	49	22.26	22.0±1	/
				1	99	22.14	22.0±1	/
				25	0	21.16	21.0±1	1.0
				25	24	21.22	21.0±1	1.0
				25	49	21.21	21.0±1	1.0
				50	0	21.16	21.0±1	1.0
			16QAM	1	0	21.16	21.0±1	1.0
				1	49	21.25	21.0±1	1.0
				1	99	21.13	21.0±1	1.0
				25	0	20.2	21.0±1	1.0
				25	24	20.25	21.0±1	1.0
				25	49	20.22	21.0±1	1.0
				50	0	20.2	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.14	22.0±1	/
				1	49	22.26	22.0±1	/
				1	99	22.1	22.0±1	/
				25	0	21.17	21.0±1	1.0
				25	24	21.19	21.0±1	1.0
				25	49	21.15	21.0±1	1.0
				50	0	21.18	21.0±1	1.0
			16QAM	1	0	21.53	21.0±1	1.0
				1	49	21.67	21.0±1	1.0
				1	99	21.49	21.0±1	1.0
				25	0	20.24	21.0±1	1.0
				25	24	20.27	21.0±1	1.0
				25	49	20.23	21.0±1	1.0
				50	0	20.24	21.0±1	1.0
	20350	1750	QPSK	1	0	22.08	22.0±1	/
				1	49	22.29	22.0±1	/
				1	99	22.17	22.0±1	/
				25	0	21.2	21.0±1	1.0
				25	24	21.24	21.0±1	1.0
				25	49	21.16	21.0±1	1.0
				50	0	21.18	21.0±1	1.0
			16QAM	1	0	21.11	21.0±1	1.0
				1	49	21.38	21.0±1	1.0
				1	99	21.21	21.0±1	1.0
				25	0	20.3	21.0±1	1.0
				25	24	20.33	21.0±1	1.0
				25	49	20.24	21.0±1	1.0
				50	0	20.26	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20025	1717.5	QPSK	1	0	22.1	22.0±1	/
				1	49	22.18	22.0±1	/
				1	99	22.01	22.0±1	/
				36	0	21.23	21.0±1	1.0
				36	24	21.31	21.0±1	1.0
				36	49	21.3	21.0±1	1.0
				75	0	21.32	21.0±1	1.0
			16QAM	1	0	21.07	21.0±1	1.0
				1	49	21.16	21.0±1	1.0
				1	99	21.01	21.0±1	1.0
				36	0	20.18	21.0±1	1.0
				36	24	20.28	21.0±1	1.0
				36	49	20.27	21.0±1	1.0
				75	0	20.22	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.03	22.0±1	/
				1	49	22.16	22.0±1	/
				1	99	21.99	22.0±1	/
				36	0	21.2	21.0±1	1.0
				36	24	21.27	21.0±1	1.0
				36	49	21.23	21.0±1	1.0
				75	0	21.24	21.0±1	1.0
			16QAM	1	0	21.45	21.0±1	1.0
				1	49	21.55	21.0±1	1.0
				1	99	21.4	21.0±1	1.0
				36	0	20.23	21.0±1	1.0
				36	24	20.3	21.0±1	1.0
				36	49	20.22	21.0±1	1.0
				75	0	20.25	21.0±1	1.0
	20325	1747.5	QPSK	1	0	22	22.0±1	/
				1	49	22.17	22.0±1	/
				1	99	22.07	22.0±1	/
				36	0	21.26	21.0±1	1.0
				36	24	21.26	21.0±1	1.0
				36	49	21.27	21.0±1	1.0
				75	0	21.27	21.0±1	1.0
			16QAM	1	0	21.42	21.0±1	1.0
				1	49	21.6	21.0±1	1.0
				1	99	21.52	21.0±1	1.0
				36	0	20.19	21.0±1	1.0
				36	24	20.23	21.0±1	1.0
				36	49	20.17	21.0±1	1.0
				75	0	20.23	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20050	1720	QPSK	1	0	21.93	22.0±1	/
				1	49	22.72	22.0±1	/
				1	99	21.91	22.0±1	/
				50	0	21.15	21.0±1	1.0
				50	24	21.27	21.0±1	1.0
				50	49	21.21	21.0±1	1.0
				100	0	21.22	21.0±1	1.0
			16QAM	1	0	21.48	21.0±1	1.0
				1	49	21.91	21.0±1	1.0
				1	99	21.46	21.0±1	1.0
				50	0	20.22	21.0±1	1.0
				50	24	20.28	21.0±1	1.0
				50	49	20.27	21.0±1	1.0
				100	0	20.27	21.0±1	1.0
	20175	1732.5	QPSK	1	0	21.91	22.0±1	/
				1	49	22.93	22.0±1	/
				1	99	21.89	22.0±1	/
				50	0	21.15	21.0±1	1.0
				50	24	21.91	21.0±1	1.0
				50	49	21.14	21.0±1	1.0
				100	0	21.2	21.0±1	1.0
			16QAM	1	0	21.37	21.0±1	1.0
				1	49	21.72	21.0±1	1.0
				1	99	21.34	21.0±1	1.0
				50	0	20.23	21.0±1	1.0
				50	24	20.29	21.0±1	1.0
				50	49	20.18	21.0±1	1.0
				100	0	20.21	21.0±1	1.0
	20300	1745	QPSK	1	0	22.75	22.0±1	/
				1	49	22.81	22.0±1	/
				1	99	21.84	22.0±1	/
				50	0	21.21	21.0±1	1.0
				50	24	21.16	21.0±1	1.0
				50	49	21.12	21.0±1	1.0
				100	0	21.18	21.0±1	1.0
			16QAM	1	0	21.21	21.0±1	1.0
				1	49	21.65	21.0±1	1.0
				1	99	21.34	21.0±1	1.0
				50	0	20.21	21.0±1	1.0
				50	24	20.17	21.0±1	1.0
				50	49	20.11	21.0±1	1.0
				100	0	20.2	21.0±1	1.0

LTE Band 5:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	20407	824.7	QPSK	1	0	22.28	22.0±1	/
				1	2	22.41	22.0±1	/
				1	5	22.27	22.0±1	/
				3	0	22.37	22.0±1	/
				3	1	22.5	22.0±1	/
				3	2	22.34	22.0±1	/
			16QAM	6	0	21.45	21.0±1	1.0
				1	0	21.47	21.0±1	1.0
				1	2	21.82	21.0±1	1.0
				1	5	21.53	21.0±1	1.0
				3	0	21.5	21.0±1	1.0
				3	1	21.54	21.0±1	1.0
				3	2	21.41	21.0±1	1.0
				6	0	20.6	21.0±1	1.0
	20525	836.5	QPSK	1	0	22.45	22.0±1	/
				1	2	22.6	22.0±1	/
				1	5	22.48	22.0±1	/
				3	0	22.53	22.0±1	/
				3	1	22.57	22.0±1	/
				3	2	22.43	22.0±1	/
			16QAM	6	0	21.56	21.0±1	1.0
				1	0	21.81	21.0±1	1.0
				1	2	21.96	21.0±1	1.0
				1	5	21.83	21.0±1	1.0
				3	0	21.71	21.0±1	1.0
				3	1	21.62	21.0±1	1.0
				3	2	21.63	21.0±1	1.0
				6	0	20.47	21.0±1	1.0
	20634	848.3	QPSK	1	0	22.42	22.0±1	/
				1	2	22.62	22.0±1	/
				1	5	22.45	22.0±1	/
				3	0	22.54	22.0±1	/
				3	1	22.58	22.0±1	/
				3	2	22.57	22.0±1	/
			16QAM	6	0	21.64	21.0±1	1.0
				1	0	21.56	21.0±1	1.0
				1	2	21.58	21.0±1	1.0
				1	5	21.46	21.0±1	1.0
				3	0	21.64	21.0±1	1.0
				3	1	21.61	21.0±1	1.0
				3	2	21.69	21.0±1	1.0
				6	0	20.74	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	20415	825.5	QPSK	1	0	22.57	22.0±1	/
				1	8	22.55	22.0±1	/
				1	14	22.5	22.0±1	/
				6	0	21.65	21.0±1	1.0
				6	4	21.72	21.0±1	1.0
				6	9	21.65	21.0±1	1.0
				15	0	21.63	21.0±1	1.0
			16QAM	1	0	21.56	21.0±1	1.0
				1	8	21.58	21.0±1	1.0
				1	14	21.52	21.0±1	1.0
				8	0	20.6	21.0±1	1.0
				8	4	20.69	21.0±1	1.0
				8	9	20.64	21.0±1	1.0
				15	0	20.54	21.0±1	1.0
	20525	836.5	QPSK	1	0	22.53	22.0±1	/
				1	8	22.53	22.0±1	/
				1	14	22.49	22.0±1	/
				6	0	21.6	21.0±1	1.0
				6	4	21.65	21.0±1	1.0
				6	9	21.61	21.0±1	1.0
				15	0	21.57	21.0±1	1.0
			16QAM	1	0	21.9	21.0±1	1.0
				1	8	21.93	21.0±1	1.0
				1	14	21.88	21.0±1	1.0
				6	0	20.7	21.0±1	1.0
				6	4	20.7	21.0±1	1.0
				6	9	20.66	21.0±1	1.0
				15	0	20.62	21.0±1	1.0
	20635	847.5	QPSK	1	0	22.6	22.0±1	/
				1	8	22.61	22.0±1	/
				1	14	22.59	22.0±1	/
				6	0	21.67	21.0±1	1.0
				6	4	21.7	21.0±1	1.0
				6	9	21.66	21.0±1	1.0
				15	0	21.65	21.0±1	1.0
			16QAM	1	0	21.67	21.0±1	1.0
				1	8	21.69	21.0±1	1.0
				1	14	21.59	21.0±1	1.0
				8	0	20.69	21.0±1	1.0
				8	4	20.74	21.0±1	1.0
				8	9	20.65	21.0±1	1.0
				15	0	20.58	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	20425	826.5	QPSK	1	0	22.32	22.0±1	/
				1	49	22.48	22.0±1	/
				1	99	22.41	22.0±1	/
				12	0	21.57	21.0±1	1.0
				12	24	21.65	21.0±1	1.0
				12	49	21.6	21.0±1	1.0
				25	0	21.61	21.0±1	1.0
			16QAM	1	0	21.66	21.0±1	1.0
				1	49	21.8	21.0±1	1.0
				1	99	21.71	21.0±1	1.0
				12	0	20.63	21.0±1	1.0
				12	24	20.72	21.0±1	1.0
				12	49	20.71	21.0±1	1.0
				25	0	20.66	21.0±1	1.0
	20525	836.5	QPSK	1	0	22.55	22.0±1	/
				1	49	22.62	22.0±1	/
				1	99	22.51	22.0±1	/
				12	0	21.62	21.0±1	1.0
				12	24	21.66	21.0±1	1.0
				12	49	21.58	21.0±1	1.0
				25	0	21.6	21.0±1	1.0
			16QAM	1	0	21.94	21.0±1	1.0
				1	49	21.89	21.0±1	1.0
				1	99	21.95	21.0±1	1.0
				12	0	20.71	21.0±1	1.0
				12	24	20.76	21.0±1	1.0
				12	49	20.58	21.0±1	1.0
				25	0	20.39	21.0±1	1.0
	20625	846.5	QPSK	1	0	22.22	22.0±1	/
				1	49	22.5	22.0±1	/
				1	99	22.38	22.0±1	/
				12	0	21.6	21.0±1	1.0
				12	24	21.65	21.0±1	1.0
				12	49	21.61	21.0±1	1.0
				25	0	21.67	21.0±1	1.0
			16QAM	1	0	21.69	21.0±1	1.0
				1	49	21.75	21.0±1	1.0
				1	99	21.72	21.0±1	1.0
				12	0	20.72	21.0±1	1.0
				12	24	20.78	21.0±1	1.0
				12	49	20.72	21.0±1	1.0
				25	0	20.69	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20450	829	QPSK	1	0	22.71	22.0±1	/
				1	49	22.69	22.0±1	/
				1	99	22.39	22.0±1	/
				25	0	21.8	21.0±1	1.0
				25	24	21.75	21.0±1	1.0
				25	49	21.79	21.0±1	1.0
				50	0	21.66	21.0±1	1.0
			16QAM	1	0	21.43	21.0±1	1.0
				1	49	21.49	21.0±1	1.0
				1	99	21.35	21.0±1	1.0
				25	0	20.57	21.0±1	1.0
				25	24	20.54	21.0±1	1.0
				25	49	20.61	21.0±1	1.0
				50	0	20.57	21.0±1	1.0
	20525	836.5	QPSK	1	0	22.38	22.0±1	/
				1	49	22.96	22.0±1	/
				1	99	22.45	22.0±1	/
				25	0	21.55	21.0±1	1.0
				25	24	21.91	21.0±1	1.0
				25	49	21.51	21.0±1	1.0
				50	0	21.54	21.0±1	1.0
			16QAM	1	0	21.81	21.0±1	1.0
				1	49	21.89	21.0±1	1.0
				1	99	21.83	21.0±1	1.0
				25	0	20.57	21.0±1	1.0
				25	24	20.57	21.0±1	1.0
				25	49	20.58	21.0±1	1.0
				50	0	20.52	21.0±1	1.0
	20600	844	QPSK	1	0	22.52	22.0±1	/
				1	49	22.65	22.0±1	/
				1	99	22.58	22.0±1	/
				25	0	21.66	21.0±1	1.0
				25	24	21.63	21.0±1	1.0
				25	49	21.62	21.0±1	1.0
				50	0	21.62	21.0±1	1.0
			16QAM	1	0	21.51	21.0±1	1.0
				1	49	21.78	21.0±1	1.0
				1	99	21.71	21.0±1	1.0
				25	0	20.85	21.0±1	1.0
				25	24	20.83	21.0±1	1.0
				25	49	20.81	21.0±1	1.0
				50	0	20.79	21.0±1	1.0

LTE Band 7:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	20775	2502.5	QPSK	1	0	22.15	22.0±1	/
				1	49	22.22	22.0±1	/
				1	99	22.15	22.0±1	/
				12	0	21.2	21.0±1	1.0
				12	24	21.32	21.0±1	1.0
				12	49	21.25	21.0±1	1.0
				25	0	21.26	21.0±1	1.0
			16QAM	1	0	21.3	21.0±1	1.0
				1	49	21.43	21.0±1	1.0
				1	99	21.33	21.0±1	1.0
				12	0	20.27	21.0±1	1.0
				12	24	20.37	21.0±1	1.0
				12	49	20.31	21.0±1	1.0
				25	0	20.21	21.0±1	1.0
	21100	2535	QPSK	1	0	22.09	22.0±1	/
				1	49	22.21	22.0±1	/
				1	99	22.08	22.0±1	/
				12	0	21.15	21.0±1	1.0
				12	24	21.21	21.0±1	1.0
				12	49	21.17	21.0±1	1.0
				25	0	21.16	21.0±1	1.0
			16QAM	1	0	21.27	21.0±1	1.0
				1	49	21.33	21.0±1	1.0
				1	99	21.24	21.0±1	1.0
				12	0	20.24	21.0±1	1.0
				12	24	20.31	21.0±1	1.0
				12	49	20.24	21.0±1	1.0
				25	0	20.19	21.0±1	1.0
	21425	2567.5	QPSK	1	0	22.04	22.0±1	/
				1	49	22.11	22.0±1	/
				1	99	22	22.0±1	/
				12	0	21.11	21.0±1	1.0
				12	24	21.12	21.0±1	1.0
				12	49	21.01	21.0±1	1.0
				25	0	21.09	21.0±1	1.0
			16QAM	1	0	21.55	21.0±1	1.0
				1	49	21.62	21.0±1	1.0
				1	99	21.48	21.0±1	1.0
				12	0	20.28	21.0±1	1.0
				12	24	20.25	21.0±1	1.0
				12	49	20.17	21.0±1	1.0
				25	0	20.18	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20800	2505	QPSK	1	0	22.26	22.0±1	/
				1	49	22.41	22.0±1	/
				1	99	22.17	22.0±1	/
				25	0	21.27	21.0±1	1.0
				25	24	21.32	21.0±1	1.0
				25	49	21.35	21.0±1	1.0
				50	0	21.35	21.0±1	1.0
			16QAM	1	0	21.17	21.0±1	1.0
				1	49	21.32	21.0±1	1.0
				1	99	21.1	21.0±1	1.0
				25	0	20.33	21.0±1	1.0
				25	24	20.36	21.0±1	1.0
				25	49	20.38	21.0±1	1.0
				50	0	20.31	21.0±1	1.0
	21100	2535	QPSK	1	0	22.15	22.0±1	/
				1	49	22.35	22.0±1	/
				1	99	22.17	22.0±1	/
				25	0	21.26	21.0±1	1.0
				25	24	21.21	21.0±1	1.0
				25	49	21.2	21.0±1	1.0
				50	0	21.22	21.0±1	1.0
			16QAM	1	0	21.53	21.0±1	1.0
				1	49	21.67	21.0±1	1.0
				1	99	21.51	21.0±1	1.0
				25	0	20.32	21.0±1	1.0
				25	24	20.3	21.0±1	1.0
				25	49	20.28	21.0±1	1.0
				50	0	20.27	21.0±1	1.0
	21400	2565	QPSK	1	0	22.12	22.0±1	/
				1	49	22.28	22.0±1	/
				1	99	22.07	22.0±1	/
				25	0	21.21	21.0±1	1.0
				25	24	21.15	21.0±1	1.0
				25	49	21.05	21.0±1	1.0
				50	0	21.1	21.0±1	1.0
			16QAM	1	0	21.08	21.0±1	1.0
				1	49	21.28	21.0±1	1.0
				1	99	21.06	21.0±1	1.0
				25	0	20.3	21.0±1	1.0
				25	24	20.3	21.0±1	1.0
				25	49	20.15	21.0±1	1.0
				50	0	20.16	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20825	2507.5	QPSK	1	0	22.17	22.0±1	/
				1	49	22.17	22.0±1	/
				1	99	22.13	22.0±1	/
				36	0	21.27	21.0±1	1.0
				36	24	21.33	21.0±1	1.0
				36	49	21.34	21.0±1	1.0
				75	0	21.32	21.0±1	1.0
			16QAM	1	0	21.08	21.0±1	1.0
				1	49	21.17	21.0±1	1.0
				1	99	21.03	21.0±1	1.0
				36	0	20.27	21.0±1	1.0
				36	24	20.31	21.0±1	1.0
				36	49	20.27	21.0±1	1.0
				75	0	20.34	21.0±1	1.0
	21100	2535	QPSK	1	0	22.05	22.0±1	/
				1	49	22.22	22.0±1	/
				1	99	22.08	22.0±1	/
				36	0	21.28	21.0±1	1.0
				36	24	21.24	21.0±1	1.0
				36	49	21.22	21.0±1	1.0
				75	0	21.22	21.0±1	1.0
			16QAM	1	0	21.46	21.0±1	1.0
				1	49	21.55	21.0±1	1.0
				1	99	21.43	21.0±1	1.0
				36	0	20.26	21.0±1	1.0
				36	24	20.27	21.0±1	1.0
				36	49	20.26	21.0±1	1.0
				75	0	20.19	21.0±1	1.0
	21375	2562.5	QPSK	1	0	22.05	22.0±1	/
				1	49	22.12	22.0±1	/
				1	99	21.96	22.0±1	/
				36	0	21.22	21.0±1	1.0
				36	24	21.19	21.0±1	1.0
				36	49	21.11	21.0±1	1.0
				75	0	21.15	21.0±1	1.0
			16QAM	1	0	21.41	21.0±1	1.0
				1	49	21.49	21.0±1	1.0
				1	99	21.36	21.0±1	1.0
				36	0	20.15	21.0±1	1.0
				36	24	20.13	21.0±1	1.0
				36	49	20.05	21.0±1	1.0
				75	0	20.14	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20850	2510	QPSK	1	0	22.02	22.0±1	/
				1	49	22.86	22.0±1	/
				1	99	21.98	22.0±1	/
				50	0	21.19	21.0±1	1.0
				50	24	21.24	21.0±1	1.0
				50	49	21.25	21.0±1	1.0
				100	0	21.2	21.0±1	1.0
			16QAM	1	0	21.53	21.0±1	1.0
				1	49	21.81	21.0±1	1.0
				1	99	21.5	21.0±1	1.0
				50	0	20.21	21.0±1	1.0
				50	24	20.29	21.0±1	1.0
				50	49	20.3	21.0±1	1.0
				100	0	20.26	21.0±1	1.0
	21100	2535	QPSK	1	0	22.51	22.0±1	/
				1	49	22.92	22.0±1	/
				1	99	21.95	22.0±1	/
				50	0	21.21	21.0±1	1.0
				50	24	21.94	21.0±1	1.0
				50	49	21.15	21.0±1	1.0
				100	0	21.17	21.0±1	1.0
			16QAM	1	0	21.31	21.0±1	1.0
				1	49	21.78	21.0±1	1.0
				1	99	21.38	21.0±1	1.0
				50	0	20.24	21.0±1	1.0
				50	24	20.25	21.0±1	1.0
				50	49	20.16	21.0±1	1.0
				100	0	20.19	21.0±1	1.0
	21350	2560	QPSK	1	0	21.83	22.0±1	/
				1	49	22.24	22.0±1	/
				1	99	21.78	22.0±1	/
				50	0	21.14	21.0±1	1.0
				50	24	21.14	21.0±1	1.0
				50	49	20.93	21.0±1	1.0
				100	0	21.05	21.0±1	1.0
			16QAM	1	0	21.21	21.0±1	1.0
				1	49	21.6	21.0±1	1.0
				1	99	21.21	21.0±1	1.0
				50	0	20.14	21.0±1	1.0
				50	24	20.12	21.0±1	1.0
				50	49	20.92	21.0±1	1.0
				100	0	20.09	21.0±1	1.0

WIFI Mode (2.4G)

Mode	Channel number	Frequency (MHz)	Data rate(Mbps)	Average Output Power(dBm)	Average Tune up limited(dBm)
802.11b	1	2412	1	18.11	18.5±1
	6	2437	1	19.12	18.5±1
	11	2462	1	18.70	18.5±1
802.11g	1	2412	6	17.96	17.0±1
	6	2437	6	17.42	17.0±1
	11	2462	6	16.82	17.0±1
802.11n(HT20)	1	2412	MCS0	17.72	17.0±1
	6	2437	MCS0	17.87	17.0±1
	11	2462	MCS0	16.99	16.0±1
802.11n(HT40)	3	2422	MCS0	15.52	16.0±1
	6	2437	MCS0	15.27	16.0±1
	9	2452	MCS0	15.17	16.0±1

Remark:11n(HT40) channel:3/4/5/6/7/8/9

Bluetooth Measurement Result

Mode	Frequency (MHz)	Average Output Power(dBm)	Tune up limited(dBm)
GFSK	2402	5.24	6.0±1
	2441	6.66	6.0±1
	2480	-0.93	-1.0±1
$\pi/4$ DQPSK	2402	4.94	4.0±1
	2441	6.99	6.0±1
	2480	-0.39	-1.0±1
8DPSK	2402	4.84	4.0±1
	2441	6.94	6.0±1
	2480	-0.66	-1.0±1


BLE Measurement Result

Channel number	Frequency (MHz)	Average Output Power(dBm)	Tune up limited(dBm)
0	2402	-3.86	-3.0±1
19	2440	-3.31	-3.0±1
39	2480	-6.10	-6.0±1

Note:5G WIFI Power tested results please refer to “TECNO_WTS19X12087975W_LC7 FCC SAR” test report.

12 Exposure Conditions Consideration

EUT antenna location:



Test position consideration:

Distance of EUT antenna-to-edge/surface(mm), Test distance:10mm						
Antennas	Back side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	1.5	7	1	40.5	1	153
WLAN	1.5	7	43.5	1	1	153
Bluetooth	1.5	7	43.5	1	1	153

Test distance:10mm						
Antennas	Back side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	YES	YES	YES	NO	YES	NO
WLAN	YES	YES	NO	YES	YES	NO
Bluetooth	NO	NO	NO	NO	NO	NO

Note:

1. Head/Body SAR/Hotspot mode assessments are required.
2. Referring to KDB 941225 D06v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.
3. Per KDB 447498 D01v06, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user, which is 0 mm for head SAR, 10 mm for body SAR.

RF Exposure

Mobile Phone -LC7, FCC ID: 2ADYY-LC7

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Exclusion Thresholds = $P\sqrt{F} / D$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

Test Distance (5mm)

Mode	MAX Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Exclusion Thresholds	Limit
2.4G WIFI	19.12	18.5±1	19.5	89.13	27.828	3
Bluetooth	6.99	6.0±1	7	5.01	1.565	3
BLE	-3.31	-3.0±1	-2	0.63	0.197	3

Test Distance (10mm)

Mode	MAX Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Exclusion Thresholds	Limit
2.4G WIFI	19.12	18.5±1	19.5	89.13	13.914	3
Bluetooth	6.99	6.0±1	7	5.01	0.783	3
BLE	-3.31	-3.0±1	-2	0.63	0.099	3

Result: 2.4G WIFI SAR measurement is required.

Note: 5G WIFI RF exposure assessment please refer to "TECNO_WTS19X12087975W_LC7 FCC SAR" test report.

13 SAR Test Results

Test Condition:

1. SAR Measurement
The distance between the EUT and the antenna of the emulator is more than 50 cm and the output power radiated from the emulator antenna is at least 30 dB less than the output power of EUT.
2. Environmental Conditions

Temperature	23°C
Relative Humidity	57%
Atmospheric Pressure	1019mbar
3. Test Date : 2019-12-23~2020-01-02
Tested By : Andy Feng

Generally Test Procedures:

1. Establish communication link between EUT and base station emulation by air link.
2. Place the EUT in the selected test position. (Cheek, tilt or flat)
3. Perform SAR testing at middle or highest output power channel under the selected test mode. If the measured 1-g SAR is ≤ 0.8 W/kg, then testing for the other channel will not be performed.
4. When SAR is < 0.8 W/kg, no repeated SAR measurement is required

For WCDMA test:

1. KDB941225 D01-Body SAR is not required for HSDPA when the average output of each RF channel with HSDPA active is less than 0.25dB higher than measured without HSDPA using 12.2kbps RMC or the maximum SAR for 12.2kbps RMC $< 75\%$ of the SAR limit.
2. KDB941225 D01-Body SAR is not required for handset with HSPA capabilities when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25dB higher than that measure without HSUPA/HSDPA using 12.2kbps RMC AND THE maximum SAR for 12.2kbps RMC is $< 75\%$ of the SAR limit

For LTE test:

1. According to FCC KDB 941225 D05v02r05:
 - a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
 - b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
 - c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
 - d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.
 - e. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

SAR Summary Test Result:**Table 5: SAR Values of GSM 850MHz Band**

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	190	836.6	Voice call	34	33.52	0.436	0.49	1
	Tilt	190	836.6	Voice call	34	33.52	0.256	0.29	--
Left Head	Cheek	190	836.6	Voice call	34	33.52	0.427	0.48	--
	Tilt	190	836.6	Voice call	34	33.52	0.247	0.28	--
Right Head	Cheek	190	836.6	GPRS 4 slots	34	33.52	0.404	0.45	--
	Tilt	190	836.6	GPRS 4 slots	34	33.52	0.269	0.30	--
Left Head	Cheek	190	836.6	GPRS 4 slots	34	33.52	0.245	0.27	--
	Tilt	190	836.6	GPRS 4 slots	34	33.52	0.210	0.23	--
Body-worn (10mm Separation)	Front Side	190	836.6	GPRS 4 slots	31	30.92	0.173	0.18	2
	Back Side	190	836.6	GPRS 4 slots	31	30.92	0.156	0.16	--
Hotspot (10mm Separation)	Front Side	190	836.6	GPRS 4 slots	31	30.92	0.173	0.18	2
	Back Side	190	836.6	GPRS 4 slots	31	30.92	0.156	0.16	--
	Left Edge	190	836.6	GPRS 4 slots	31	30.92	0.114	0.12	--
	Top Edge	190	836.6	GPRS 4 slots	31	30.92	0.158	0.16	--

Table 6: SAR Values of GSM 1900MHz Band

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	661	1880	Voice call	30	29.91	0.024	0.03	--
	Tilt	661	1880	Voice call	30	29.91	0.014	0.02	--
Left Head	Cheek	661	1880	Voice call	30	29.91	0.007	0.01	--
	Tilt	661	1880	Voice call	30	29.91	0.005	0.01	--
Right Head	Cheek	661	1880	GPRS 4 slots	30	29.91	0.021	0.03	--
	Tilt	661	1880	GPRS 4 slots	30	29.91	0.025	0.03	3
Left Head	Cheek	661	1880	GPRS 4 slots	30	29.91	0.020	0.02	--
	Tilt	661	1880	GPRS 4 slots	30	29.91	0.018	0.02	--
Body-worn (10mm Separation)	Front Side	661	1880	GPRS 4 slots	28	27.52	0.017	0.02	--
	Back Side	661	1880	GPRS 4 slots	28	27.52	0.022	0.03	4
Hotspot (10mm Separation)	Front Side	661	1880	GPRS 4 slots	28	27.52	0.017	0.02	--
	Back Side	661	1880	GPRS 4 slots	28	27.52	0.022	0.03	4
	Left Edge	661	1880	GPRS 4 slots	28	27.52	0.015	0.02	--
	Top Edge	661	1880	GPRS 4 slots	28	27.52	0.012	0.02	--

Table 7: SAR Values of WCDMA BAND V

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	4183	836.6	RMC 12.2kbps	24	23.17	0.332	0.40	--
	Tilt	4183	836.6	RMC 12.2kbps	24	23.17	0.125	0.15	--
Left Head	Cheek	4183	836.6	RMC 12.2kbps	24	23.17	0.332	0.40	5
	Tilt	4183	836.6	RMC 12.2kbps	24	23.17	0.196	0.24	--
Body-worn (10mm Separation)	Front Side	4183	836.6	RMC 12.2kbps	24	23.17	0.100	0.12	--
	Back Side	4183	836.6	RMC 12.2kbps	24	23.17	0.150	0.18	6
Hotspot (10mm Separation)	Front Side	4183	836.6	RMC 12.2kbps	24	23.17	0.100	0.12	--
	Back Side	4183	836.6	RMC 12.2kbps	24	23.17	0.150	0.18	6
	Left Edge	4183	836.6	RMC 12.2kbps	24	23.17	0.011	0.01	--
	Top Edge	4183	836.6	RMC 12.2kbps	24	23.17	0.107	0.13	--

Table 8: SAR Values of WCDMA BAND II

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	9400	1880	RMC 12.2kbps	23	22.84	0.335	0.35	--
	Tilt	9400	1880	RMC 12.2kbps	23	22.84	0.547	0.57	7
Left Head	Cheek	9400	1880	RMC 12.2kbps	23	22.84	0.269	0.28	--
	Tilt	9400	1880	RMC 12.2kbps	23	22.84	0.343	0.36	--
Body-worn (10mm Separation)	Front Side	9400	1880	RMC 12.2kbps	23	22.84	0.016	0.02	--
	Back Side	9400	1880	RMC 12.2kbps	23	22.84	0.018	0.02	8
Hotspot (10mm Separation)	Front Side	9400	1880	RMC 12.2kbps	23	22.84	0.016	0.02	--
	Back Side	9400	1880	RMC 12.2kbps	23	22.84	0.018	0.02	--
	Left Edge	9400	1880	RMC 12.2kbps	23	22.84	0.011	0.01	--
	Top Edge	9400	1880	RMC 12.2kbps	23	22.84	0.024	0.03	9

Table 9: SAR Values of WCDMA BAND IV

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	1413	1732.6	RMC 12.2kbps	23	22.80	0.457	0.48	--
	Tilt	1413	1732.6	RMC 12.2kbps	23	22.80	0.635	0.66	10
Left Head	Cheek	1413	1732.6	RMC 12.2kbps	23	22.80	0.256	0.27	--
	Tilt	1413	1732.6	RMC 12.2kbps	23	22.80	0.381	0.40	--
Body-worn (10mm Separation)	Front Side	1413	1732.6	RMC 12.2kbps	23	22.80	0.013	0.02	--
	Back Side	1413	1732.6	RMC 12.2kbps	23	22.80	0.014	0.02	11
Hotspot (10mm Separation)	Front Side	1413	1732.6	RMC 12.2kbps	23	22.80	0.013	0.02	--
	Back Side	1413	1732.6	RMC 12.2kbps	23	22.80	0.014	0.02	--
	Left Edge	1413	1732.6	RMC 12.2kbps	23	22.80	0.008	0.01	--
	Top Edge	1413	1732.6	RMC 12.2kbps	23	22.80	0.024	0.03	12

Table 10: SAR Values of LTE BAND 2 , 20MHz ,QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
			CH.	MHz	Maximum Turn-up Power(dBm)	Measured output power(dBm)		Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head	Cheek	18900	1880	22.5	22.44	0	0.458	0.46	--
		Tilt	18900	1880	22.5	22.44	0	0.613	0.62	13
	Left Head	Cheek	18900	1880	22.5	22.44	0	0.311	0.32	--
		Tilt	18900	1880	22.5	22.44	0	0.373	0.38	--
	Body-worn (10mm Separation)	Front Side	18900	1880	22.5	22.44	0	0.011	0.01	--
		Back Side	18900	1880	22.5	22.44	0	0.016	0.02	14
	Hotspot (10mm Separation)	Front Side	18900	1880	22.5	22.44	0	0.011	0.01	--
		Back Side	18900	1880	22.5	22.44	0	0.016	0.02	--
		Left Edge	18900	1880	22.5	22.44	0	0.012	0.01	--
		Top Edge	18900	1880	22.5	22.44	0	0.020	0.02	15
50%RB #24	Right Head	Cheek	18900	1880	21.5	21.47	1	0.414	0.42	--
		Tilt	18900	1880	21.5	21.47	1	0.582	0.59	--
	Left Head	Cheek	18900	1880	21.5	21.47	1	0.289	0.29	--
		Tilt	18900	1880	21.5	21.47	1	0.325	0.33	--
	Body-worn (10mm Separation)	Front Side	18900	1880	21.5	21.47	1	0.007	0.01	--
		Back Side	18900	1880	21.5	21.47	1	0.012	0.02	--
	Hotspot (10mm Separation)	Front Side	18900	1880	21.5	21.47	1	0.007	0.01	--
		Back Side	18900	1880	21.5	21.47	1	0.012	0.02	--
		Left Edge	18900	1880	21.5	21.47	1	0.008	0.01	--
		Top Edge	18900	1880	21.5	21.47	1	0.015	0.02	--

Table 11: SAR Values of LTE BAND 4, 20MHz ,QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
			CH.	MHz	Maximum Turn-up Power(dBm)	Measured output power(dBm)		Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head	Cheek	20175	1732.5	23	22.93	0	0.330	0.34	--
		Tilt	20175	1732.5	23	22.93	0	0.339	0.34	16
	Left Head	Cheek	20175	1732.5	23	22.93	0	0.289	0.29	--
		Tilt	20175	1732.5	23	22.93	0	0.230	0.23	--
	Body-worn (10mm Separation)	Front Side	20175	1732.5	23	22.93	0	0.011	0.02	--
		Back Side	20175	1732.5	23	22.93	0	0.015	0.02	17
	Hotspot (10mm Separation)	Front Side	20175	1732.5	23	22.93	0	0.011	0.02	--
		Back Side	20175	1732.5	23	22.93	0	0.015	0.02	--
		Left Edge	20175	1732.5	23	22.93	0	0.011	0.02	--
		Top Edge	20175	1732.5	23	22.93	0	0.031	0.04	18
50%RB #24	Right Head	Cheek	20175	1732.5	22	21.91	1	0.288	0.29	--
		Tilt	20175	1732.5	22	21.91	1	0.294	0.30	--
	Left Head	Cheek	20175	1732.5	22	21.91	1	0.277	0.28	--
		Tilt	20175	1732.5	22	21.91	1	0.201	0.21	--
	Body-worn (10mm Separation)	Front Side	20175	1732.5	22	21.91	1	0.009	0.01	--
		Back Side	20175	1732.5	22	21.91	1	0.011	0.02	--
	Hotspot (10mm Separation)	Front Side	20175	1732.5	22	21.91	1	0.009	0.01	--
		Back Side	20175	1732.5	22	21.91	1	0.011	0.02	--
		Left Edge	20175	1732.5	22	21.91	1	0.007	0.01	--
		Top Edge	20175	1732.5	22	21.91	1	0.025	0.03	--

Table 12: SAR Values of LTE BAND 5 , 20MHz ,QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
			CH.	MHz	Maximum Turn-up Power(dBm)	Measured output power(dBm)		Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head	Cheek	20525	836.5	23	22.96	0	0.401	0.41	19
		Tilt	20525	836.5	23	22.96	0	0.289	0.29	--
	Left Head	Cheek	20525	836.5	23	22.96	0	0.346	0.35	--
		Tilt	20525	836.5	23	22.96	0	0.314	0.32	--
	Body-worn (10mm Separation)	Front Side	20525	836.5	23	22.96	0	0.093	0.10	--
		Back Side	20525	836.5	23	22.96	0	0.156	0.16	20
	Hotspot (10mm Separation)	Front Side	20525	836.5	23	22.96	0	0.093	0.10	--
		Back Side	20525	836.5	23	22.96	0	0.156	0.16	20
		Left Edge	20525	836.5	23	22.96	0	0.058	0.06	--
		Top Edge	20525	836.5	23	22.96	0	0.111	0.12	--
50%RB #24	Right Head	Cheek	20525	836.5	22	21.91	1	0.367	0.37	--
		Tilt	20525	836.5	22	21.91	1	0.256	0.26	--
	Left Head	Cheek	20525	836.5	22	21.91	1	0.311	0.32	--
		Tilt	20525	836.5	22	21.91	1	0.297	0.30	--
	Body-worn (10mm Separation)	Front Side	20525	836.5	22	21.91	1	0.078	0.08	--
		Back Side	20525	836.5	22	21.91	1	0.140	0.15	--
	Hotspot (10mm Separation)	Front Side	20525	836.5	22	21.91	1	0.078	0.08	--
		Back Side	20525	836.5	22	21.91	1	0.140	0.15	--
		Left Edge	20525	836.5	22	21.91	1	0.041	0.05	--
		Top Edge	20525	836.5	22	21.91	1	0.099	0.10	--

Table 13: SAR Values of LTE BAND 7 , 20MHz ,QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
			CH.	MHz	Maximum Turn-up Power(dBm)	Measured output power(dBm)		Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head	Cheek	21100	2535	23	22.92	0	0.299	0.30	--
		Tilt	21100	2535	23	22.92	0	0.325	0.33	21
	Left Head	Cheek	21100	2535	23	22.92	0	0.124	0.13	--
		Tilt	21100	2535	23	22.92	0	0.159	0.16	--
	Body-worn (10mm Separation)	Front Side	21100	2535	23	22.92	0	0.013	0.02	--
		Back Side	21100	2535	23	22.92	0	0.044	0.05	22
	Hotspot (10mm Separation)	Front Side	21100	2535	23	22.92	0	0.013	0.02	--
		Back Side	21100	2535	23	22.92	0	0.044	0.05	22
		Left Edge	21100	2535	23	22.92	0	0.032	0.04	--
		Top Edge	21100	2535	23	22.92	0	0.024	0.03	--
50%RB #24	Right Head	Cheek	21100	2535	22	21.94	1	0.256	0.26	--
		Tilt	21100	2535	22	21.94	1	0.301	0.31	--
	Left Head	Cheek	21100	2535	22	21.94	1	0.104	0.11	--
		Tilt	21100	2535	22	21.94	1	0.132	0.14	--
	Body-worn (10mm Separation)	Front Side	21100	2535	22	21.94	1	0.008	0.01	--
		Back Side	21100	2535	22	21.94	1	0.039	0.04	--
	Hotspot (10mm Separation)	Front Side	21100	2535	22	21.94	1	0.008	0.01	--
		Back Side	21100	2535	22	21.94	1	0.039	0.04	--
		Left Edge	21100	2535	22	21.94	1	0.029	0.03	--
		Top Edge	21100	2535	22	21.94	1	0.020	0.03	--

Table 14: SAR Values of 2.4G WIFI

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)		Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	Mid	2437	DSSS	19.5	19.12	0.019	0.02	--
	Tilt	Mid	2437	DSSS	19.5	19.12	0.016	0.02	--
Left Head	Cheek	Mid	2437	DSSS	19.5	19.12	0.043	0.05	23
	Tilt	Mid	2437	DSSS	19.5	19.12	0.038	0.04	--
Body-worn (10mm Separation)	Front Side	Mid	2437	DSSS	19.5	19.12	0.011	0.01	--
	Back Side	Mid	2437	DSSS	19.5	19.12	0.047	0.05	24
Hotspot (10mm Separation)	Front Side	Mid	2437	DSSS	19.5	19.12	0.011	0.01	--
	Back Side	Mid	2437	DSSS	19.5	19.12	0.047	0.05	24
	Right Edge	Mid	2437	DSSS	19.5	19.12	0.035	0.04	--
	Top Edge	Mid	2437	DSSS	19.5	19.12	0.028	0.03	--

Note: 1. According to KDB 648474-D04 Handset SAR v01r03 section 1.5, the diagonal dimension of this device is > 16.0 cm, but the hotspot mode 1-g reported SAR is **0.05** W < 1.2 W, so the 10-g extremity SAR is not required.

2. 5G WIFI SAR tested results please refer to "TECNO_WTS19X12087975W_LC7 FCC SAR" test report.

Measurement variability consideration

Refer to FCC KDB 248227 section 5.2.1~5.2.2:

802.11b DSSS SAR Test Requirements:

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure.

SAR test reduction is determined according to the following:

1) When the reported SAR of the highest measured maximum output power channel (section 3.1) for the exposure configuration is ≤ 0.8 W/kg,

no further SAR testing is required for 802.11b DSSS in that exposure configuration.

2) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg,

SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3).

SAR is not required for the following 2.4 GHz OFDM conditions.

1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.

2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Note: 802.11b DSSS SAR test is required. The highest reported SAR for DSSS* the ratio of OFDM to DSSS(Max output power) is $0.05 \times 0.766 = 0.04$ W/Kg < 1.2 W/Kg, so the OFDM SAR test is not required.

According to KDB 865664 D01v01r04 section 2.8.1, repeated measurements are required following the procedures as below:

Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.

When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.

Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

No Repeated SAR:

Simultaneous Transmission SAR Analysis.

List of Mode for Simultaneous Multi-band Transmission:

No.	Configurations	Head SAR	Body-worn SAR	Hotspot SAR
1	GSM(Voice) + WLAN 2.4GHz(Data)	Yes	-	-
2	GPRS (Data) + WLAN 2.4GHz(Data)	Yes	Yes	Yes
3	GSM(Voice) + Bluetooth(Data)	Yes	-	-
4	GPRS (Data) + Bluetooth(Data)	Yes	Yes	Yes
5	WCDMA (Voice) + WLAN 2.4GHz(Data)	Yes	-	-
6	WCDMA (Data) + WLAN 2.4GHz(Data)	-	Yes	Yes
7	WCDMA (Voice) + Bluetooth(Data)	Yes	-	-
8	WCDMA (Data) + Bluetooth(Data)	-	Yes	Yes
9	LTE (Data) + WLAN 2.4GHz(Data)	Yes	Yes	Yes
10	LTE (Data) + Bluetooth(Data)	Yes	Yes	Yes

Remark:

1. GSM/ WCDMA/LTE share the same antenna, and cannot transmit simultaneously.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. According to the KDB 447498 D01 v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(\text{GHz})/x}$]
W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 v06 as below:

Bluetooth:

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	X	SAR(1g) 5mm	SAR(1g) 10mm
7.0	5.01	5/10	2.441	7.5	0.21	0.10

5. The maximum SAR summation is calculated based on the same configuration and test position

Head SAR Simultaneous WWAN and 2.4G WIFI

Position	WWAN (maximum)		2.4G WIFI(0mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850	0.49	0.02	0.51
Right Tilt	GPRS850	0.30	0.02	0.32
Left Cheek	GSM850	0.48	0.05	0.53
Left Tilt	GSM850	0.28	0.04	0.32
Right Cheek	GPRS1900	0.03	0.02	0.05
Right Tilt	GPRS1900	0.03	0.02	0.05
Left Cheek	GPRS1900	0.02	0.05	0.07
Left Tilt	GPRS1900	0.02	0.04	0.06
Right Cheek	WCDMA Band V	0.40	0.02	0.42
Right Tilt	WCDMA Band V	0.15	0.02	0.17
Left Cheek	WCDMA Band V	0.40	0.05	0.45
Left Tilt	WCDMA Band V	0.24	0.04	0.28
Right Cheek	WCDMA Band II	0.35	0.02	0.37
Right Tilt	WCDMA Band II	0.57	0.02	0.59
Left Cheek	WCDMA Band II	0.28	0.05	0.33
Left Tilt	WCDMA Band II	0.36	0.04	0.40
Right Cheek	WCDMA Band IV	0.48	0.02	0.50
Right Tilt	WCDMA Band IV	0.66	0.02	0.68
Left Cheek	WCDMA Band IV	0.27	0.05	0.32
Left Tilt	WCDMA Band IV	0.40	0.04	0.44
Right Cheek	LTE BAND 2(1RB)	0.46	0.02	0.48
Right Tilt	LTE BAND 2(1RB)	0.62	0.02	0.64
Left Cheek	LTE BAND 2(1RB)	0.32	0.05	0.37
Left Tilt	LTE BAND 2(1RB)	0.38	0.04	0.42
Right Cheek	LTE BAND 4(1RB)	0.34	0.02	0.36
Right Tilt	LTE BAND 4(1RB)	0.34	0.02	0.36
Left Cheek	LTE BAND 4(1RB)	0.29	0.05	0.34
Left Tilt	LTE BAND 4(1RB)	0.23	0.04	0.27
Right Cheek	LTE BAND 5(1RB)	0.41	0.02	0.43
Right Tilt	LTE BAND 5(1RB)	0.29	0.02	0.31
Left Cheek	LTE BAND 5(1RB)	0.35	0.05	0.40
Left Tilt	LTE BAND 5(1RB)	0.32	0.04	0.36
Right Cheek	LTE BAND 7(1RB)	0.30	0.02	0.32
Right Tilt	LTE BAND 7(1RB)	0.33	0.02	0.35
Left Cheek	LTE BAND 7(1RB)	0.13	0.05	0.18
Left Tilt	LTE BAND 7(1RB)	0.16	0.04	0.20

WWAN and 5G WIFI

Position	WWAN (maximum)		5G WIFI(0mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850	0.49	0.34	0.83
Right Tilt	GPRS850	0.30	0.22	0.52
Left Cheek	GSM850	0.48	0.55	1.03
Left Tilt	GSM850	0.28	0.38	0.66
Right Cheek	GPRS1900	0.03	0.34	0.37
Right Tilt	GPRS1900	0.03	0.22	0.25
Left Cheek	GPRS1900	0.02	0.55	0.57
Left Tilt	GPRS1900	0.02	0.38	0.40
Right Cheek	WCDMA Band V	0.40	0.34	0.74
Right Tilt	WCDMA Band V	0.15	0.22	0.37
Left Cheek	WCDMA Band V	0.40	0.55	0.95
Left Tilt	WCDMA Band V	0.24	0.38	0.62
Right Cheek	WCDMA Band II	0.35	0.34	0.69
Right Tilt	WCDMA Band II	0.57	0.22	0.79
Left Cheek	WCDMA Band II	0.28	0.55	0.83
Left Tilt	WCDMA Band II	0.36	0.38	0.74
Right Cheek	WCDMA Band IV	0.48	0.34	0.82
Right Tilt	WCDMA Band IV	0.66	0.22	0.88
Left Cheek	WCDMA Band IV	0.27	0.55	0.82
Left Tilt	WCDMA Band IV	0.40	0.38	0.78
Right Cheek	LTE BAND 2(1RB)	0.46	0.34	0.80
Right Tilt	LTE BAND 2(1RB)	0.62	0.22	0.84
Left Cheek	LTE BAND 2(1RB)	0.32	0.55	0.87
Left Tilt	LTE BAND 2(1RB)	0.38	0.38	0.76
Right Cheek	LTE BAND 4(1RB)	0.34	0.34	0.68
Right Tilt	LTE BAND 4(1RB)	0.34	0.22	0.56
Left Cheek	LTE BAND 4(1RB)	0.29	0.55	0.84
Left Tilt	LTE BAND 4(1RB)	0.23	0.38	0.61
Right Cheek	LTE BAND 5(1RB)	0.41	0.34	0.75
Right Tilt	LTE BAND 5(1RB)	0.29	0.22	0.51
Left Cheek	LTE BAND 5(1RB)	0.35	0.55	0.90
Left Tilt	LTE BAND 5(1RB)	0.32	0.38	0.70
Right Cheek	LTE BAND 7(1RB)	0.30	0.34	0.64
Right Tilt	LTE BAND 7(1RB)	0.33	0.22	0.55
Left Cheek	LTE BAND 7(1RB)	0.13	0.55	0.68
Left Tilt	LTE BAND 7(1RB)	0.16	0.38	0.54

WWAN and BT

Position	WWAN (maximum)		BT(0mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850	0.49	0.21	0.70
Right Tilt	GSM1900	0.03	0.21	0.24
Left Cheek	WCDMA Band V	0.40	0.21	0.61
Right Tilt	WCDMA Band II	0.57	0.21	0.78
Right Tilt	WCDMA Band IV	0.66	0.21	0.87
Right Tilt	LTE BAND 2(1RB)	0.62	0.21	0.83
Right Tilt	LTE BAND 4(1RB)	0.34	0.21	0.55
Right Cheek	LTE BAND 5(1RB)	0.41	0.21	0.62
Right Tilt	LTE BAND 7(1RB)	0.33	0.21	0.54

Remark: BT the 1g SAR value is not being captured by the measurement system, the 1g-SAR value is conservatively used for simultaneous transmission analysis.

Body-worn SAR Simultaneous WWAN and 2.4G WIFI

Position	WWAN (maximum)		2.4G WIFI(10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GPRS850	0.18	0.01	0.19
Back		0.16	0.05	0.21
Front	GPRS1900	0.02	0.01	0.03
Back		0.03	0.05	0.08
Front	WCDMA Band V	0.12	0.01	0.13
Back		0.18	0.05	0.23
Front	WCDMA Band II	0.02	0.01	0.03
Back		0.02	0.05	0.07
Front	WCDMA Band IV	0.02	0.01	0.03
Back		0.02	0.05	0.07
Front	LTE BAND 2(1RB)	0.01	0.01	0.02
Back		0.02	0.05	0.07
Front	LTE BAND 4(1RB)	0.02	0.01	0.03
Back		0.02	0.05	0.07
Front	LTE BAND 5(1RB)	0.10	0.01	0.11
Back		0.16	0.05	0.21
Front	LTE BAND 7(1RB)	0.02	0.01	0.03
Back		0.05	0.05	0.10

WWAN and 5G WIFI

Position	WWAN (maximum)		5G WIFI(10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GPRS850	0.18	0.07	0.25
Back		0.16	0.20	0.36
Front	GPRS1900	0.02	0.07	0.09
Back		0.03	0.20	0.23
Front	WCDMA Band V	0.12	0.07	0.19
Back		0.18	0.20	0.38
Front	WCDMA Band II	0.02	0.07	0.09
Back		0.02	0.20	0.22
Front	WCDMA Band IV	0.02	0.07	0.09
Back		0.02	0.20	0.22
Front	LTE BAND 2(1RB)	0.01	0.07	0.08
Back		0.02	0.20	0.22
Front	LTE BAND 4(1RB)	0.02	0.07	0.09
Back		0.02	0.20	0.22
Front	LTE BAND 5(1RB)	0.10	0.07	0.17
Back		0.16	0.20	0.36

Front	LTE BAND 7(1RB)	0.02	0.07	0.09
Back		0.05	0.20	0.25

WWAN and BT

Position	WWAN (maximum)		BT(10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GPRS850	0.18	0.10	0.28
Back	GPRS1900	0.03	0.10	0.13
Back	WCDMA Band V	0.18	0.10	0.28
Back	WCDMA Band II	0.02	0.10	0.12
Back	WCDMA Band IV	0.02	0.10	0.12
Back	LTE BAND 2(1RB)	0.02	0.10	0.12
Back	LTE BAND 4(1RB)	0.02	0.10	0.12
Back	LTE BAND 5(1RB)	0.16	0.10	0.26
Back	LTE BAND 7(1RB)	0.05	0.10	0.15

Remark: BT the 1g SAR value is not being captured by the measurement system, the 1g-SAR value is conservatively used for simultaneous transmission analysis.

Hotspot SAR Simultaneous WWAN and 2.4G WIFI

Position	WWAN (maximum)		2.4G WIFI(10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GPRS850	0.18	0.01	0.19
Back		0.16	0.05	0.21
Right		-	0.04	0.04
Left		0.12	-	0.12
Top		0.16	0.03	0.19
Bottom		-	-	-
Front	GPRS1900	0.02	0.01	0.03
Back		0.03	0.05	0.08
Right		-	0.04	0.04
Left		0.02	-	0.02
Top		0.02	0.03	0.05
Bottom		-	-	-
Front	WCDMA Band V	0.12	0.01	0.13
Back		0.18	0.05	0.23
Right		-	0.04	0.04
Left		0.01	-	0.01
Top		0.13	0.03	0.16
Bottom		-	-	-
Front	WCDMA Band II	0.02	0.01	0.03
Back		0.02	0.05	0.07
Right		-	0.04	0.04
Left		0.01	-	0.01
Top		0.03	0.03	0.06
Bottom		-	-	-
Front	WCDMA Band IV	0.02	0.01	0.03
Back		0.02	0.05	0.07
Right		-	0.04	0.04
Left		0.01	-	0.01
Top		0.03	0.03	0.06
Bottom		-	-	-
Front	LTE BAND 2(1RB)	0.01	0.01	0.02
Back		0.02	0.05	0.07
Right		-	0.04	0.04
Left		0.01	-	0.01
Top		0.02	0.03	0.05
Bottom		-	-	-
Front	LTE BAND 4(1RB)	0.02	0.01	0.03
Back		0.02	0.05	0.07
Right		-	0.04	0.04
Left		0.02	-	0.02
Top		0.04	0.03	0.07
Bottom		-	-	-

Front	LTE BAND 5(1RB)	0.10	0.01	0.11
Back		0.16	0.05	0.21
Right		-	0.04	0.04
Left		0.06	-	0.06
Top		0.12	0.03	0.15
Bottom		-	-	-
Front	LTE BAND 7(1RB)	0.02	0.01	0.03
Back		0.05	0.05	0.10
Right		-	0.04	0.04
Left		0.04	-	0.04
Top		0.03	0.03	0.06
Bottom		-	-	-

WWAN and 5G WIFI

Position	WWAN (maximum)		5G WIFI(10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GPRS850	0.18	0.07	0.25
Back		0.16	0.20	0.36
Right		-	0.13	0.13
Left		0.12	-	0.12
Top		0.16	0.07	0.23
Bottom		-	-	-
Front	GPRS1900	0.02	0.07	0.09
Back		0.03	0.20	0.23
Right		-	0.13	0.13
Left		0.02	-	0.02
Top		0.02	0.07	0.09
Bottom		-	-	-
Front	WCDMA Band V	0.12	0.07	0.19
Back		0.18	0.20	0.38
Right		-	0.13	0.13
Left		0.01	-	0.01
Top		0.13	0.07	0.20
Bottom		-	-	-
Front	WCDMA Band II	0.02	0.07	0.09
Back		0.02	0.20	0.22
Right		-	0.13	0.13
Left		0.01	-	0.01
Top		0.03	0.07	0.10
Bottom		-	-	-
Front	WCDMA Band IV	0.02	0.07	0.09
Back		0.02	0.20	0.22
Right		-	0.13	0.13
Left		0.01	-	0.01
Top		0.03	0.07	0.10
Bottom		-	-	-
Front	LTE BAND 2(1RB)	0.01	0.07	0.08
Back		0.02	0.20	0.22

Right		-	0.13	0.13
Left		0.01	-	0.01
Top		0.02	0.07	0.09
Bottom		-	-	-
Front	LTE BAND 4(1RB)	0.02	0.07	0.09
Back		0.02	0.20	0.22
Right		-	0.13	0.13
Left		0.02	-	0.02
Top		0.04	0.07	0.11
Bottom		-	-	-
Front	LTE BAND 5(1RB)	0.10	0.07	0.17
Back		0.16	0.20	0.36
Right		-	0.13	0.13
Left		0.06	-	0.06
Top		0.12	0.07	0.19
Bottom		-	-	-
Front	LTE BAND 7(1RB)	0.02	0.07	0.09
Back		0.05	0.20	0.25
Right		-	0.13	0.13
Left		0.04	-	0.04
Top		0.03	0.07	0.10
Bottom		-	-	-

WWAN and BT


Position	WWAN (maximum)		BT(10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GPRS850	0.18	0.10	0.28
Back	GPRS1900	0.03	0.10	0.13
Back	WCDMA Band V	0.18	0.10	0.28
Top	WCDMA Band II	0.03	0.10	0.13
Top	WCDMA Band IV	0.03	0.10	0.13
Top	LTE BAND 2(1RB)	0.02	0.10	0.12
Top	LTE BAND 4(1RB)	0.04	0.10	0.14
Back	LTE BAND 5(1RB)	0.16	0.10	0.26
Back	LTE BAND 7(1RB)	0.05	0.10	0.15


Remark: BT the 1g SAR value is not being captured by the measurement system, the 1g-SAR value is conservatively used for simultaneous transmission analysis.


14 SAR Measurement Reference


References


1. FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
2. IEEE Std. C95.1-2005, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz”, 2005
3. IEEE Std. 1528-2013, “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, June 2013
4. IEC 62209-2, “Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices—Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate(SAR) for wireless communication devices used in close proximity to the human body(frequency range of 30MHz to 6GHz)”, April 2010
5. FCC KDB 447498 D01 v06, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, Oct 23th, 2015
6. FCC KDB 941225 D01 v03r01, “3G SAR Measurement Procedures”, Oct 23th, 2015
7. FCC KDB 941225 D05 v02r05, “SAR Evaluation Considerations for LTE Devices”, Dec 16th, 2015
8. FCC KDB 941225 D06 v02r01, “SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities”, Oct 23th, 2015
9. FCC KDB865664 D01 v01r04, “SAR Measurement Requirements 100MHz to 6GHz”, Aug 7th, 2015
10. FCC KDB865664 D02 v01r02, “RF Exposure Compliance Reporting and Documentation Considerations ”, Oct 23th, 2015
11. FCC KDB648474 D04 v01r03, “SAR Evaluation Considerations for Wireless Handsets”, Oct 23th, 2015
12. FCC KDB 248227 D01 v02r02, SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters, Oct 23th, 2015.


Maximum SAR measurement Plots**Plot 1: GSM850MHz, Middle channel (Right Head , Cheek)****Product Description: Mobile Phone****Test Date: 2019-12-23**


Plot 2: GPRS850MHz, Middle channel (Body-worn/Hotspot, Front Surface)**Product Description: Mobile Phone****Test Date: 2019-12-23**


Plot 3: GPRS1900, Middle channel (Right Head Tilt)**Product Description: Mobile Phone****Test Date: 2020-01-02**


Plot 4: GPRS1900, Middle channel (Body-worn/ Hotspot, Back Surface)**Product Description: Mobile Phone****Test Date: 2020-01-02**


Plot 5: WCDMA BAND V, Middle channel (Left Head Cheek)**Product Description: Mobile Phone****Test Date: 2019-12-23**


Plot 6: WCDMA BAND V, Middle channel (Body-worn/Hotspot, Back Surface)**Product Description: Mobile Phone****Test Date: 2019-12-23**


Plot 7: WCDMA BAND II , Middle channel (Right Head Tilt)**Product Description: Mobile Phone****Test Date: 2020-01-02**


Plot 8: WCDMA BAND II, Middle channel (Body-worn, Back Surface)**Product Description: Mobile Phone****Test Date: 2020-01-02**


Plot 9: WCDMA BAND II, Middle channel (Hotspot, Top Edge)**Product Description: Mobile Phone****Test Date: 2020-01-02**


Plot 10: WCDMA BAND IV, Mid channel (Right Head Tilt)**Product Description: Mobile Phone****Test Date: 2019-12-24**


Plot 11: WCDMA BAND IV, Middle channel (Body-worn, Back Surface)**Product Description: Mobile Phone****Test Date: 2019-12-24**

Plot 12: WCDMA BAND IV, Middle channel (Hotspot, Top Edge)**Product Description: Mobile Phone****Test Date: 2019-12-24**


Plot 13:LTE BAND 2, Middle channel (Right Head Tilt)**Product Description:Mobile Phone****Test Date: 2020-01-02**


Plot 14:LTE BAND 2, Middle channel (Body-worn, Back Surface)**Product Description:Mobile Phone****Test Date: 2020-01-02**


Plot 15:LTE BAND 2, Middle channel (Hotspot, Top Edge)**Product Description:Mobile Phone****Test Date: 2020-01-02**


Plot 16:LTE BAND 4, Middle channel (Right Head Tilt)**Product Description:Mobile Phone****Test Date: 2019-12-24**


Plot 17:LTE BAND 4, Middle channel (Body-worn, Back Surface)
Product Description:Mobile Phone
Test Date: 2019-12-24





Plot 18:LTE BAND 4, Middle channel (Hotspot, Top Edge)**Product Description:Mobile Phone****Test Date: 2019-12-24**

Plot 19: LTE BAND 5, Middle channel (Right Head Cheek)**Product Description: Mobile Phone****Test Date: 2019-12-18**

Plot 20: LTE BAND 5, Middle channel (Body-worn/Hotspot, Back Surface)**Product Description: Mobile Phone****Test Date: 2019-12-18**

Plot 21:LTE BAND 7, Middle channel (Right Head Tilt)**Product Description: Mobile Phone****Test Date: 2020-01-02**

Plot 22:LTE BAND 7, Middle channel (Body-worn/ Hotspot, Back Surface)**Product Description: Mobile Phone****Test Date: 2020-01-02**

Plot 23:802.11b, Mid channel (Left Head Cheek)**Product Description: Mobile Phone****Test Date: 2019-12-31**

Plot 24:802.11b, Mid channel (Body-worn/Hotspot, Back Surface)**Product Description: Mobile Phone****Test Date: 2019-12-31**