

TEST REPORT

FCC ID: 2ADYY-SE-KEYBOARD

Product: MEGAPAD SE Bluetooth Keyboard

Model No.: MEGAPAD SE Keyboard

Trade Mark: TECNO

Report No.: WSCT-ANAB-R&E250800068A-15B

Issued Date: 26 August 2025

Issued for:

TECNO MOBILE LIMITED

FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI
STREET FOTAN NT HONGKONG

Issued By:

World Standardization Certification & Testing Group(Shenzhen) Co.,Ltd.
Building A-B,Baoli'an Industrial Park,No.58 and 60,Tangtou Avenue, Shiyan
Street, Bao'an District, Shenzhen City, Guangdong Province, China

TEL: +86-755-26996192

FAX: +86-755-86376605



Note: This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. This document may be altered or revised by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

1. Test Certification	3
2. GENERAL DESCRIPTION OF EUT	4
3. Test Result Summary	5
4. TEST METHODOLOGY	6
4.1. CONFIGURATION OF SYSTEM UNDER TEST	7
4.2. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	8
5. MEASUREMENT INSTRUMENTS	9
6. Facilities and Accreditations	10
6.1. FACILITIES	10
6.2. ACCREDITATIONS	10
6.3. MEASUREMENT UNCERTAINTY	11
7. EMC EMISSION TEST	12
7.1. CONDUCTED EMISSION MEASUREMENT	12
7.3. RADIATED EMISSION MEASUREMENT	16

Report No.: WSCT-ANAB-R&E250800068A-15B

Issued: 26 August 2025

Revised: None

1. Test Certification

Product: MEGAPAD SE Bluetooth Keyboard
Model No.: MEGAPAD SE Keyboard
Trade Mark: TECNO
Applicant: TECNO MOBILE LIMITED
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG
Manufacturer: TECNO MOBILE LIMITED
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG
Date of Test: 12 August 2025 to 26 August 2025
Applicable Standards: FCC CFR Title 47 Part 15 Subpart B

The above equipment has been tested by World Standardization Certification & Testing Group(Shenzhen) Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

Jiang Guanliang

(Jiang Guanliang)

Checked By:

Chen Xu

(Chen Xu)

Approved By:

Qin Shuiquan

(Qin Shuiquan)

Date:

26 August 2025



2. GENERAL DESCRIPTION OF EUT

Product Name:	MEGAPAD SE Bluetooth Keyboard
Model :	MEGAPAD SE Keyboard
Trade Mark:	TECNO
Software Version	001
Hardware Version	001
Operating Voltage	Li-ion Polymer Battery: 333437PG Nominal Voltage: 3.7V Rated Energy: 1.6Wh Rated Capacity: 430mAh Limited Charge Voltage: 4.2V
Remark:	N/A.

3. Test Result Summary

Requirement	CFR 47 Section	Result
CONDUCTED EMISSION	§15.107	PASS
RADIATED EMISSION	§15.109	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.


4. TEST METHODOLOGY

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	Charging
Mode 2	Tablet

4.1. CONFIGURATION OF SYSTEM UNDER TEST

Configuration Setup 1:



Configuration Setup2 :



(EUT: MEGAPAD SE Bluetooth Keyboard)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
Power	1	0.5m USB cable,unshielded	/

4.2. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	/	XCU32	/	/

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

5. MEASUREMENT INSTRUMENTS

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibrated	Calibrated until
Test software	--	EZ-EMC	CON-03A	--	--
ESCI Test Receiver	R&S	ESCI	100005	11/05/2024	11/04/2025
LISN	AFJ	LS16	16010222119	11/05/2024	11/04/2025
LISN(EUT)	Mestec	AN3016	04/10040	11/05/2024	11/04/2025
pre-amplifier	CDSI	PAP-1G18-38	--	11/05/2024	11/04/2025
System Controller	CT	SC100	-	11/05/2024	11/04/2025
Bi-log Antenna	Chase	CBL6111C	2576	11/05/2024	11/04/2025
Spectrum analyzer	R&S	FSU26	200409	11/05/2024	11/04/2025
Horn Antenna	SCHWARZBECK	9120D	1141	11/05/2024	11/04/2025
Bi-log Antenna	SCHWARZBECK	VULB9168	01488	11/05/2024	11/04/2025
Pre Amplifier	H.P.	HP8447E	2945A02715	11/05/2024	11/04/2025
9*6*6 Anechoic	--	--	--	11/05/2024	11/04/2025

6. Facilities and Accreditations

6.1. Facilities

All measurement facilities used to collect the measurement data are located at **World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtou Avenue, Shiyan Street, Bao'an District, Shenzhen City, Guangdong Province, China**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:2017.

USA

ANAB - Certificate Number: AT-3951

China

CNAS (Registration Number: L3732)

Canada

ISED (CAB identifier: CN0178)

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.wsct-cert.com>

6.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission Test	$\pm 3.2\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1GHz)	$\pm 4.7\text{dB}$
5	All emissions, radiated(>1GHz)	$\pm 4.7\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2.0\%$

7. EMC EMISSION TEST

7.1. CONDUCTED EMISSION MEASUREMENT

7.1.1. POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.


TEST SETUP



7.2. Test Results

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 1(the worst case)

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.3180	30.82	0.04	30.86	59.76	-28.90	QP
2		0.3379	19.89	0.04	19.93	49.25	-29.32	AVG
3		0.3980	38.17	0.05	38.22	57.89	-19.67	QP
4	*	0.3980	28.90	0.05	28.95	47.89	-18.94	AVG
5		1.0180	23.44	0.15	23.59	46.00	-22.41	AVG
6		1.0380	34.39	0.15	34.54	56.00	-21.46	QP
7		1.6980	21.61	0.07	21.68	46.00	-24.32	AVG
8		2.3900	32.50	0.03	32.53	56.00	-23.47	QP
9		3.0420	19.01	0.04	19.05	46.00	-26.95	AVG
10		4.3740	28.63	0.05	28.68	56.00	-27.32	QP
11		7.8580	12.41	0.06	12.47	50.00	-37.53	AVG
12		9.5020	26.29	0.06	26.35	60.00	-33.65	QP

Report No.: WSCT-ANAB-R&E250800068A-15B

Issued: 26 August 2025

Revised: None

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.3140	30.29	0.04	30.33	59.86	-29.53	QP
2		0.3300	16.23	0.04	16.27	49.45	-33.18	AVG
3	*	0.3980	37.69	0.05	37.74	57.89	-20.15	QP
4		0.3980	23.24	0.05	23.29	47.89	-24.60	AVG
5		1.0020	34.31	0.15	34.46	56.00	-21.54	QP
6		1.0300	18.07	0.15	18.22	46.00	-27.78	AVG
7		2.4940	32.48	0.03	32.51	56.00	-23.49	QP
8		3.1260	15.83	0.04	15.87	46.00	-30.13	AVG
9		4.4980	30.50	0.05	30.55	56.00	-25.45	QP
10		8.2660	14.15	0.06	14.21	50.00	-35.79	AVG
11		9.4020	27.86	0.06	27.92	60.00	-32.08	QP
12		14.6540	5.22	0.05	5.27	50.00	-44.73	AVG

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

7.3. RADIATED EMISSION MEASUREMENT

7.3.1. Radiated Emission Limits

The field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1Hz for Average


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

TEST SETUP

(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



Report No.: WSCT-ANAB-R&E250800068A-15B

Issued: 26 August 2025

Revised: None


7.3.2. Test Results

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 2(the worst case)

Please refer to following diagram for individual


Below 1GHz

Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	50.3700	34.72	-7.51	27.21	40.00	-12.79	QP
2		97.9000	38.16	-11.42	26.74	43.50	-16.76	QP
3		259.8900	31.13	-8.13	23.00	46.00	-23.00	QP
4		553.8000	27.25	-0.07	27.18	46.00	-18.82	QP
5		762.3500	25.90	4.09	29.99	46.00	-16.01	QP
6		945.6800	25.69	7.25	32.94	46.00	-13.06	QP

Vertical:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	33.8800	49.21	-20.53	28.68	40.00	-11.32	QP
2		145.4299	45.34	-19.96	25.38	43.50	-18.12	QP
3		466.5000	43.87	-18.43	25.44	46.00	-20.56	QP
4		680.8700	47.02	-17.30	29.72	46.00	-16.28	QP
5		869.0500	48.24	-16.18	32.06	46.00	-13.94	QP
6		988.3600	49.78	-15.35	34.43	54.00	-19.57	QP

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)

TEST RESULTS

Above 1GHz(1~26GHz) :(Mode 2—worst case)

Note: The spurious above 6G is noise only, do not show on the report.

Horizontal:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1445.000	39.87	-7.42	32.45	74.00	-41.55	peak
2	1445.000	30.33	-7.42	22.91	54.00	-31.09	AVG
3	2092.500	39.70	-2.14	37.56	74.00	-36.44	peak
4	2092.500	29.69	-2.14	27.55	54.00	-26.45	AVG
5	2433.750	46.46	-3.94	42.52	74.00	-31.48	peak
6	2433.750	44.99	-3.94	41.05	54.00	-12.95	AVG
7	3691.875	36.19	-0.32	35.87	74.00	-38.13	peak
8	3691.875	27.85	-0.32	27.53	54.00	-26.47	AVG
9	4586.250	36.01	3.38	39.39	74.00	-34.61	peak
10	4586.250	26.68	3.38	30.06	54.00	-23.94	AVG
11	5744.375	43.04	8.09	51.13	74.00	-22.87	peak
12 *	5744.375	36.38	8.09	44.47	54.00	-9.53	AVG

Report No.: WSCT-ANAB-R&E250800068A-15B

Issued: 26 August 2025

Revised: None

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1561.875	41.16	-7.40	33.76	74.00	-40.24	peak
2	1561.875	29.60	-7.40	22.20	54.00	-31.80	AVG
3	2136.250	38.93	-1.41	37.52	74.00	-36.48	peak
4	2136.250	29.94	-1.41	28.53	54.00	-25.47	AVG
5	2438.125	44.20	-3.91	40.29	74.00	-33.71	peak
6	2438.125	40.16	-3.91	36.25	54.00	-17.75	AVG
7	3561.875	36.85	-0.87	35.98	74.00	-38.02	peak
8	3561.875	26.91	-0.87	26.04	54.00	-27.96	AVG
9	4724.375	34.98	4.00	38.98	74.00	-35.02	peak
10	4724.375	25.70	4.00	29.70	54.00	-24.30	AVG
11	5744.375	43.98	8.09	52.07	74.00	-21.93	peak
12 *	5744.375	38.35	8.09	46.44	54.00	-7.56	AVG

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Freq. = Emission frequency in MHz

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Over= Emission Level - Limit.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

*******END OF REPORT*******