



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



SAR TEST REPORT

Applicant: TECNO MOBILE LIMITED

Address: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG

FCC ID: 2ADYY-T1102

Product Name: Tablet

Standard(s): 47 CFR Part 2(2.1093)

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: 2503W27143E-20

Date Of Issue: 2025/09/03

Reviewed By: Ken Zong

Ken Zong

Title: SAR Engineer

Approved By: Karl Gong

Karl Gong

Title: SAR Engineer

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China

Tel: +86-769-83085888

www.ccttt.com.cn

SAR TEST RESULTS SUMMARY

Operation Frequency Bands	Highest Reported 1g SAR (W/kg)		Limits (W/kg)
	Body-Supported (Gap 0mm)		
GSM 850	0.68		1.6
PCS 1900	0.66		
WCDMA Band 2	0.88		
WCDMA Band 4	0.48		
WCDMA Band 5	0.77		
LTE Band 2	1.02		
LTE Band 26&5	0.91		
LTE Band 7	0.79		
LTE Band 12&17	0.79		
LTE Band 13	0.66		
LTE Band 38	1.01		
LTE Band 41	0.99		
LTE Band 66&4	1.08		
Wi-Fi 2.4G	0.50		
Wi-Fi 5.2G	0.24		
Wi-Fi 5.3G	0.26		
Wi-Fi 5.6G	0.30		
Wi-Fi 5.8G	0.34		
Maximum Simultaneous Transmission SAR			
Items	Body-Supported (Gap 0mm)	Hotspot (Gap 0mm)	Limits
Sum SAR(W/kg)	1.44	1.44	1.6
SPLSR	N/A		0.04
EUT Received Date:	2025/08/22		
Tested Date:	2025/08/28 ~ 2025/08/31		
Tested Result:	Pass		

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Each test item follows the test standard(s) without deviation.

CONTENTS

SAR TEST RESULTS SUMMARY	2
DOCUMENT REVISION HISTORY	6
1. GENERAL INFORMATION	7
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	7
1.2 TEST SPECIFICATION, METHODS AND PROCEDURES	8
1.3 SAR LIMITS.....	9
2. SAR MEASUREMENT SYSTEM	10
3. EQUIPMENT LIST AND CALIBRATION	17
3.1 EQUIPMENTS LIST & CALIBRATION INFORMATION	17
4. SAR MEASUREMENT SYSTEM VERIFICATION	18
4.1 LIQUID VERIFICATION	18
4.2 SYSTEM ACCURACY VERIFICATION	21
4.3 SAR SYSTEM VALIDATION DATA.....	22
5. EUT TEST STRATEGY AND METHODOLOGY	30
5.1 TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS	30
5.2 TEST DISTANCE FOR SAR EVALUATION.....	30
5.3 SAR EVALUATION PROCEDURE	31
6. CONDUCTED OUTPUT POWER MEASUREMENT	32
6.1 TEST PROCEDURE	32
6.2 DESCRIPTION OF TEST CONFIGURATION.....	33
6.3 MAXIMUM TARGET OUTPUT POWER.....	39
6.4 TEST RESULTS:	41
7. Standalone SAR test exclusion considerations.....	71
7.1 ANTENNA DISTANCE TO EDGE	71
7.2 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	71
7.3 STANDALONE SAR ESTIMATION:	72
7.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS:.....	73
7.5 SAR TEST EXCLUSION FOR THE EUT EDGE CONSIDERATIONS RESULT	74
8. SAR MEASUREMENT RESULTS	75
8.1 SAR TEST DATA	75
9. Measurement Variability	88

10. DUT HOLDER PERTURBATIONS	89
11. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION	90
12. SAR Plots	91
APPENDIX A MEASUREMENT UNCERTAINTY	109
APPENDIX B EUT TEST POSITION PHOTOS	110
APPENDIX C CALIBRATION CERTIFICATES	113

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2503W27143E-20	Original Report	2025/09/03

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Tablet
EUT Model:	T1102
Trade Mark:	TECNO
Device Type:	Portable
Exposure Category:	Population / Uncontrolled
Antenna Type(s):	Internal Antenna
Body-Worn Accessories:	None
Operation modes:	GSM Voice, GPRS/EDGE Data, WCDMA(R99 (Voice+Data), HSDPA/HSUPA/DC-HSDPA/HSPA+), FDD-LTE, TDD-LTE, WLAN, Bluetooth
Frequency Band:	GSM 850: 824-849 MHz(TX); 869-894 MHz(RX) PCS 1900: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 4: 1710-1755MHz(TX) ; 2110-2155 MHz(RX) WCDMA Band 5: 824-849 MHz(TX); 869-894 MHz(RX) LTE Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) LTE Band 4: 1710-1755MHz(TX) ; 2110-2155 MHz(RX) LTE Band 5: 824-849 MHz(TX); 869-894 MHz(RX) LTE Band 7: 2500-2570 MHz(TX); 2620-2690 MHz(RX) LTE Band 12: 699-716 MHz(TX); 729-746 MHz(RX) LTE Band 13: 777-787 MHz(TX); 746-756 MHz(RX) LTE Band 17: 704-716 MHz(TX); 734-746 MHz(RX) LTE Band 26: 814-849 MHz(TX); 859-894 MHz(RX) LTE Band 38: 2570-2620 MHz(TX/RX) LTE Band 41: 2496-2690 MHz(TX/RX) LTE Band 66: 1710-1780 MHz(TX); 2110-2180 MHz(RX) WLAN 2.4G: 2412 MHz-2462 MHz(TX/RX) WLAN 5.2G: 5150 MHz-5250 MHz(TX/RX) WLAN 5.3G: 5250-5350 MHz(TX/RX) WLAN 5.6G: 5470-5725MHz(TX/RX) WLAN 5.8G: 5725 MHz-5850 MHz(TX/RX) Bluetooth: 2402 MHz-2480 MHz(TX/RX) BLE 1M: 2402 MHz-2480 MHz(TX/RX)
Dimensions (L*W*H):	255 mm (L) * 166 mm (W) * 12 mm (H)
Rated Input Voltage:	DC 3.85 V from Rechargeable Battery
Serial Number:	38S6-1
Normal Operation:	Body Supported

1.2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE 1528-2013, the following FCC Published RF exposure KDB procedures:

KDB 447498 D01 General RF Exposure Guidance v06
KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
KDB 865664 D02 RF Exposure Reporting v01r02
KDB 941225 D01 3G SAR Procedures v03r01
KDB 941225 D05 SAR for LTE Devices v02r05
KDB 616217 D04 SAR for laptop and Tablets v01r02
KDB 248227 D01 802.11 Wi-Fi SAR v02r02

TCB Workshop April 2019: RF Exposure Procedures

1.3 SAR Limits

FCC Limit

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg for 1g SAR applied to the EUT.


2. SAR MEASUREMENT SYSTEM

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



DASY5 System Description

The DASY5 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY5 Measurement Server

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized point out, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

ES3DV3 E-Field Probes

Frequency	10 MHz - 4 GHz Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 2.0 mm
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones
Compatibility	DASY3, DASY4, DASY52, DASY6, DASY8 SAR, EASY6, EASY4/MRI

EX3DV4 E-Field Probes

Frequency	4 MH - 10 GHz Linearity: ± 0.2 dB (30 MHz to 10 GHz)
Directivity	± 0.1 dB in TSL (rotation around probe axis)
Dynamic Range	Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52, DASY6, DASY8 SAR, EASY6, EASY4/MRI

SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness increases to 6 mm). The phantom has three measurement areas:

- _ Left Head
- _ Right Head
- _ Flat phantom

The phantom table for the DASY systems based on the robots have the size of 100 x 50 x 85 cm (L x W x H). For easy dislocation these tables have fork lift cut outs at the bottom.

The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)



A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible. Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.

Robots

The DASY5 system uses the high precision industrial robot. The robot offers the same features important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The above mentioned robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is contained on the CDs delivered along with the robot. Paper manuals are available upon request direct from Staubli.

SAR Scan Procedures

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 1.4 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm $\pm$ 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm $\pm$ 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

			$\leq 3 \text{ GHz}$	$> 3 \text{ GHz}$
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1) \text{ mm}$	
Minimum zoom scan volume	x, y, z		$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB Publication 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power Drift Measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x 7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE 1528-2013

Recommended Tissue Dielectric Parameters for Head liquid

Table 3—Target dielectric properties of head tissue-equivalent material in the 300 MHz to 6000 MHz frequency range

Frequency (MHz)	Relative permittivity (ϵ_r)	Conductivity (σ) (S/m)
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1500	40.4	1.23
1640	40.2	1.31
1750	40.1	1.37
1800	40.0	1.40
1900	40.0	1.40
2000	40.0	1.40
2100	39.8	1.49
2300	39.5	1.67
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27
6000	35.1	5.48

NOTE—For convenience, permittivity and conductivity values at some frequencies that are not part of the original data from Drossos et al. [B60] or the extension to 5800 MHz are provided (i.e., the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6000 MHz that were linearly extrapolated from the values at 3000 MHz and 5800 MHz.

3. EQUIPMENT LIST AND CALIBRATION

3.1 Equipments List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52.10	N/A	NCR	NCR
DASY5 Measurement Server	DASY5 4.5.12	1567	NCR	NCR
Data Acquisition Electronics	DAE4	1354	2024/12/3	2025/12/2
E-Field Probe	ES3DV3	3157	2024/11/22	2025/11/21
E-Field Probe	EX3DV4	3701	2024/10/17	2025/10/16
Mounting Device	MD4HHTV5	BJPCTC0152	NCR	NCR
Twin SAM	Twin SAM V5.0	1412	NCR	NCR
Dipole, 750 MHz	D750V3	1230	2023/3/24	2026/3/23
Dipole, 1750 MHz	D1750V2	1200	2023/3/27	2026/3/26
Dipole, 1900 MHz	D1900V2	5d251	2023/3/27	2026/3/26
Dipole, 2450 MHz	D2450V2	1102	2023/3/27	2026/3/26
Dipole, 2600 MHz	D2600V2	1206	2023/3/27	2026/3/26
Dipole, 5GHz	D5GHzV2	1245	2023/8/23	2026/8/22
Simulated Tissue Liquid Head(500-9500 MHz)	HBBL600-10000V6	220420-2	Each Time	/
Network Analyzer	8753B	2828A00170	2024/10/17	2025/10/16
Dielectric assessment kit	1319	SM DAK 040 CA	NCR	NCR
MXG Vector Signal Generator	N5182B	MY51350142	2025/1/9	2026/1/8
Power Meter	ML2495A	1106009	2025/8/5	2026/8/4
USB Average Power Sensor	U2001H	MY50000432	2025/3/31	2026/3/30
Power Amplifier	ZVA-183-S+	5969001149	NCR	NCR
Directional Coupler	4226-20	03328	NCR	NCR
Attenuator	20dB, 100W	LN749	NCR	NCR
Attenuator	6dB, 150W	2754	NCR	NCR
Thermometer	DTM3000	3892	2025/3/31	2026/3/30
Thermo-hygrometer	HTC-1	NA	2025/3/31	2026/3/30
Spectrum Analyzer	FSU26	100147	2025/3/31	2026/3/30


The Dipole calibration methods and procedures used were as detailed in:

FCC KDB Publication Number: “KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz”

1. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20 dB minimum return-loss requirement.
2. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.

4. SAR MEASUREMENT SYSTEM VERIFICATION

4.1 Liquid Verification



Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
704	Simulated Tissue Liquid Head	43.344	0.873	42.15	0.89	2.83	-1.91	± 5
707.5	Simulated Tissue Liquid Head	43.205	0.878	42.13	0.89	2.55	-1.35	± 5
711	Simulated Tissue Liquid Head	42.072	0.883	42.11	0.89	-0.09	-0.79	± 5
750	Simulated Tissue Liquid Head	42.894	0.887	41.9	0.89	2.37	-0.34	± 5
782	Simulated Tissue Liquid Head	42.744	0.892	41.75	0.89	2.38	0.22	± 5
821.5	Simulated Tissue Liquid Head	42.337	0.907	41.56	0.9	1.87	0.78	± 5
824.2	Simulated Tissue Liquid Head	42.208	0.912	41.55	0.9	1.58	1.33	± 5
826.4	Simulated Tissue Liquid Head	42.073	0.913	41.54	0.9	1.28	1.44	± 5
831.5	Simulated Tissue Liquid Head	41.801	0.924	41.52	0.9	0.68	2.67	± 5
836.6	Simulated Tissue Liquid Head	41.753	0.929	41.5	0.9	0.61	3.22	± 5
841.5	Simulated Tissue Liquid Head	41.617	0.936	41.5	0.91	0.28	2.86	± 5
846.6	Simulated Tissue Liquid Head	41.574	0.94	41.5	0.91	0.18	3.3	± 5
848.8	Simulated Tissue Liquid Head	41.545	0.941	41.5	0.91	0.11	3.41	± 5

*Liquid Verification above was performed on 2025/08/28.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
1712.4	Simulated Tissue Liquid Head	41.228	1.329	40.13	1.35	2.74	-1.56	± 5
1720	Simulated Tissue Liquid Head	41.141	1.336	40.13	1.35	2.52	-1.04	± 5
1732.6	Simulated Tissue Liquid Head	40.837	1.353	40.12	1.36	1.79	-0.51	± 5
1745	Simulated Tissue Liquid Head	40.59	1.366	40.1	1.37	1.22	-0.29	± 5
1750	Simulated Tissue Liquid Head	40.549	1.382	40.1	1.37	1.12	0.88	± 5
1752.6	Simulated Tissue Liquid Head	40.251	1.399	40.09	1.37	0.4	2.12	± 5
1770	Simulated Tissue Liquid Head	40.033	1.408	40.06	1.38	-0.07	2.03	± 5

*Liquid Verification above was performed on 2025/08/29.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
1850.2	Simulated Tissue Liquid Head	40.426	1.378	40	1.4	1.07	-1.57	± 5
1852.4	Simulated Tissue Liquid Head	40.389	1.379	40	1.4	0.97	-1.5	± 5
1860	Simulated Tissue Liquid Head	39.942	1.393	40	1.4	-0.15	-0.5	± 5
1880	Simulated Tissue Liquid Head	39.728	1.412	40	1.4	-0.68	0.86	± 5
1900	Simulated Tissue Liquid Head	39.462	1.418	40	1.4	-1.34	1.29	± 5
1907.6	Simulated Tissue Liquid Head	39.307	1.425	40	1.4	-1.73	1.79	± 5
1909.8	Simulated Tissue Liquid Head	39.261	1.431	40	1.4	-1.85	2.21	± 5

*Liquid Verification above was performed on 2025/08/29.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
2412	Simulated Tissue Liquid Head	40.231	1.755	39.28	1.77	2.42	-0.85	± 5
2437	Simulated Tissue Liquid Head	40.172	1.796	39.23	1.79	2.4	0.34	± 5
2450	Simulated Tissue Liquid Head	39.863	1.827	39.2	1.8	1.69	1.5	± 5
2462	Simulated Tissue Liquid Head	39.799	1.832	39.18	1.81	1.58	1.22	± 5
2506	Simulated Tissue Liquid Head	39.557	1.841	39.13	1.86	1.09	-1.02	± 5
2510	Simulated Tissue Liquid Head	39.466	1.864	39.12	1.86	0.88	0.22	± 5
2535	Simulated Tissue Liquid Head	39.308	1.867	39.09	1.89	0.56	-1.22	± 5
2549.5	Simulated Tissue Liquid Head	39.249	1.873	39.07	1.91	0.46	-1.94	± 5

*Liquid Verification above was performed on 2025/08/30.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
2560	Simulated Tissue Liquid Head	39.026	1.882	39.05	1.92	-0.06	-1.98	± 5
2580	Simulated Tissue Liquid Head	38.931	1.912	39.03	1.94	-0.25	-1.44	± 5
2593	Simulated Tissue Liquid Head	38.791	1.944	39.01	1.95	-0.56	-0.31	± 5
2595	Simulated Tissue Liquid Head	38.599	1.986	39.01	1.95	-1.05	1.85	± 5
2600	Simulated Tissue Liquid Head	38.464	2.006	39	1.96	-1.37	2.35	± 5
2610	Simulated Tissue Liquid Head	38.314	2.015	38.99	1.97	-1.73	2.28	± 5
2636.5	Simulated Tissue Liquid Head	38.159	2.023	38.95	2	-2.03	1.15	± 5
2680	Simulated Tissue Liquid Head	38.096	2.065	38.9	2.05	-2.07	0.73	± 5

*Liquid Verification above was performed on 2025/08/30.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
5190	Simulated Tissue Liquid Head	35.999	4.577	36.01	4.65	-0.03	-1.57	± 5
5230	Simulated Tissue Liquid Head	35.918	4.623	35.97	4.69	-0.14	-1.43	± 5
5250	Simulated Tissue Liquid Head	36.887	4.907	35.95	4.71	2.61	4.18	± 5
5270	Simulated Tissue Liquid Head	35.815	4.661	35.93	4.73	-0.32	-1.46	± 5
5310	Simulated Tissue Liquid Head	35.696	4.701	35.89	4.77	-0.54	-1.45	± 5

*Liquid Verification above was performed on 2025/08/31.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
5510	Simulated Tissue Liquid Head	35.221	4.946	35.64	4.98	-1.18	-0.68	± 5
5550	Simulated Tissue Liquid Head	35.116	5.004	35.58	5.02	-1.3	-0.32	± 5
5600	Simulated Tissue Liquid Head	35.008	5.075	35.5	5.07	-1.39	0.1	± 5
5670	Simulated Tissue Liquid Head	34.848	5.134	35.43	5.14	-1.64	-0.12	± 5
5710	Simulated Tissue Liquid Head	34.841	5.176	35.39	5.18	-1.55	-0.08	± 5
5750	Simulated Tissue Liquid Head	34.721	5.233	35.35	5.22	-1.78	0.25	± 5
5755	Simulated Tissue Liquid Head	34.706	5.237	35.35	5.23	-1.82	0.13	± 5
5795	Simulated Tissue Liquid Head	34.941	5.296	35.31	5.27	-1.05	0.49	± 5

*Liquid Verification above was performed on 2025/08/31.


4.2 System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- $s = 15 \text{ mm} \pm 0,2 \text{ mm}$ for $300 \text{ MHz} \leq f \leq 1\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $1\,000 \text{ MHz} < f \leq 3\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $3\,000 \text{ MHz} < f \leq 6\,000 \text{ MHz}$.

System Verification Setup Block Diagram



System Accuracy Check Results

Date	Frequency Band	Liquid Type	Input Power (mW)	Measured SAR (W/kg)	Normalized to 1W (W/kg)	Target Value (W/kg)	Delta (%)	Tolerance (%)
2025/08/28	750 MHz	Simulated Tissue Liquid Head	100	1g 0.832	8.32	8.49	-2.00	± 10
2025/08/29	1750 MHz	Simulated Tissue Liquid Head	100	1g 3.71	37.1	35.8	3.63	± 10
2025/08/29	1900 MHz	Simulated Tissue Liquid Head	100	1g 4.07	40.7	38.9	4.63	± 10
2025/08/30	2450 MHz	Simulated Tissue Liquid Head	100	1g 5.26	52.6	50.9	3.34	± 10
2025/08/30	2600 MHz	Simulated Tissue Liquid Head	100	1g 5.68	56.8	56	1.43	± 10
2025/08/31	5250 MHz	Simulated Tissue Liquid Head	100	1g 7.72	77.2	78	-1.03	± 10
2025/08/31	5600 MHz	Simulated Tissue Liquid Head	100	1g 8.03	80.3	81	-0.86	± 10
2025/08/31	5750 MHz	Simulated Tissue Liquid Head	100	1g 7.66	76.6	77.8	-1.54	± 10

*The SAR values above are normalized to 1 Watt forward power.

4.3 SAR SYSTEM VALIDATION DATA

System Performance 750 MHz Head

DUT: D750V3; Type: 750 MHz; Serial: 1230


Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 750$ MHz; $\sigma = 0.887$ S/m; $\epsilon_r = 42.894$; $\rho = 1000$ kg/m³;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(6.45, 6.45, 6.45) @750 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection);
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.891 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 33.94 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 1.26 W/kg
SAR(1 g) = 0.832 W/kg; SAR(10 g) = 0.543 W/kg
Smallest distance from peaks to all points 3 dB below = 16.7 mm
Ratio of SAR at M2 to SAR at M1 = 57.4%
Maximum value of SAR (measured) = 0.974 W/kg



System Performance 1750 MHz Head**DUT: D1750V2; Type: 1750 MHz; Serial: 1200**


Communication System: CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1750$ MHz; $\sigma = 1.382$ S/m; $\epsilon_r = 40.549$; $\rho = 1000$ kg/m³;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(5.41, 5.41, 5.41) @1750 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection);
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (5x6x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 5.26 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 54.19 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 6.70 W/kg
SAR(1 g) = 3.71 W/kg; SAR(10 g) = 2 W/kg
Smallest distance from peaks to all points 3 dB below = 12.6 mm
Ratio of SAR at M2 to SAR at M1 = 58.5%
Maximum value of SAR (measured) = 5.64 W/kg



System Performance 1900 MHz Head**DUT: D1900V2; Type: 1900 MHz; Serial: 5d251**

Communication System: CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1900$ MHz; $\sigma = 1.418$ S/m; $\epsilon_r = 39.462$; $\rho = 1000$ kg/m³;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(5.15, 5.15, 5.15) @1900 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection);
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (5x8x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 4.43 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 60.25 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 7.08 W/kg

SAR(1 g) = 4.07 W/kg; SAR(10 g) = 2.11 W/kg

Smallest distance from peaks to all points 3 dB below = 10.8 mm

Ratio of SAR at M2 to SAR at M1 = 59%

Maximum value of SAR (measured) = 4.59 W/kg



0 dB = 4.59 W/kg = 6.62 dBW/kg

System Performance 2450MHz Head**DUT: D2450V2; Type: 2450 MHz; Serial: 1102**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.827$ S/m; $\epsilon_r = 39.863$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(4.75, 4.75, 4.75) @2450 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (6x7x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 7.09 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.29 V/m; Power Drift = 0.02 dB


Peak SAR (extrapolated) = 10.5 W/kg

SAR(1 g) = 5.26 W/kg; SAR(10 g) = 2.49 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 49.8%

Maximum value of SAR (measured) = 8.63 W/kg



System Performance 2600 MHz Head**DUT: D2600V2; Type: 2600 MHz; Serial: 1206**


Communication System: CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2600$ MHz; $\sigma = 2.006$ S/m; $\epsilon_r = 38.464$; $\rho = 1000$ kg/m³;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(4.55, 4.55, 4.55) @2600 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (6x8x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 8.95 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 51.08 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 12.1 W/kg
SAR(1 g) = 5.68 W/kg; SAR(10 g) = 2.5 W/kg
Smallest distance from peaks to all points 3 dB below = 8.6 mm
Ratio of SAR at M2 to SAR at M1 = 46.5%
Maximum value of SAR (measured) = 9.61 W/kg



System Performance 5250 MHz Head**DUT: D5GHzV2; Type: 5250 MHz; Serial: 1245**


Communication System: CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5250$ MHz; $\sigma = 4.907$ S/m; $\epsilon_r = 36.887$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3701; ConvF(5.36, 5.36, 5.36) @5250 MHz; Calibrated: 2024/10/17
- Sensor-Surface: 1.4mm (Mechanical Surface Detection);
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 21.2 W/kg

Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
Reference Value = 39.76 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 37.8 W/kg
SAR(1 g) = 7.72 W/kg; SAR(10 g) = 2.18 W/kg
Smallest distance from peaks to all points 3 dB below = 7 mm
Ratio of SAR at M2 to SAR at M1 = 48.5%
Maximum value of SAR (measured) = 21.2 W/kg



System Performance 5600MHz Head**DUT: D5GHzV2; Type: 5600MHz; Serial: SN: 1245**


Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5600$ MHz; $\sigma = 5.075$ S/m; $\epsilon_r = 35.008$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3701; ConvF(4.75, 4.75, 4.75) @ 5600 MHz; Calibrated: 2024/10/17
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 21.4 W/kg

Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
Reference Value = 40.17 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 40.8 W/kg
SAR(1 g) = 8.03 W/kg; SAR(10 g) = 2.25 W/kg
Smallest distance from peaks to all points 3 dB below = 7.2 mm
Ratio of SAR at M2 to SAR at M1 = 47%
Maximum value of SAR (measured) = 21.8 W/kg



System Performance 5750MHz Head**DUT: D5GHzV2; Type: 5750MHz; Serial: SN: 1245**


Communication System: UID 0, CW (0); Frequency: 5750 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5750$ MHz; $\sigma = 5.233$ S/m; $\epsilon_r = 34.721$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3701; ConvF(4.87, 4.87, 4.87) @ 5750 MHz; Calibrated: 2024/10/17
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 19.8 W/kg

Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm
Reference Value = 38.56 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 35.4 W/kg
SAR(1 g) = 7.66 W/kg; SAR(10 g) = 2.07 W/kg
Smallest distance from peaks to all points 3 dB below = 9.4 mm
Ratio of SAR at M2 to SAR at M1 = 49.1%
Maximum value of SAR (measured) = 20.2 W/kg



5. EUT TEST STRATEGY AND METHODOLOGY

5.1 Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

5.2 Test Distance for SAR Evaluation

In this case the EUT(Equipment Under Test) is set directly against the phantom, the test distance is 0mm.

5.3 SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.


All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

6. CONDUCTED OUTPUT POWER MEASUREMENT


6.1 Test Procedure

The RF output of the transmitter was connected to the input of the Wireless Communication Test Set through Attenuator.



GSM/WCDMA/LTE

The RF output of the transmitter was connected to the input port of the USB Average Power Sensor through Attenuator.



BT/WLAN

6.2 Description of Test Configuration

EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in each operation mode.
Equipment Modifications:	No
EUT Exercise Software:	No
The maximum power was configured per 3GPP Standard for each operation modes as below setting:	
GSM/GPRS/EGPRS	
Function: Menu select > GSM Mobile Station > GSM 850/1900	
Press Connection control to choose the different menus	
Press RESET > choose all the reset all settings	
Connection Press Signal Off to turn off the signal and change settings	
Network Support > GSM + GPRS or GSM + EGSM	
Main Service > Packet Data	
Service selection > Test Mode A – Auto Slot Config. off	
MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting	
> Slot configuration > Uplink/Gamma > 33 dBm for GPRS 850 > 30 dBm for GPRS 1900 > 27 dBm for EGPRS 850 > 26 dBm for EGPRS 1900	
BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel	
Frequency Offset > + 0 Hz	
Mode > BCCH and TCH	
BCCH Level > -85 dBm (May need to adjust if link is not stable)	
BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]	
Channel Type > Off	
P0 > 4 dB	
Slot Config> Unchanged (if already set under MS signal)	
TCH > choose desired test channel	
Hopping > Off	
Main Timeslot > 3	
Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)	
Bit Stream > 2E9-1 PSR Bit Stream	
AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input	
Connection Press Sign	

WCDMA-Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β / β_d	8/15

WCDMA HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	1 /15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

WCDMA HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2		4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30 15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs}=\beta_{hs}/\beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate k ps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI's	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18		E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		

HSPA+

Sub-test	β_c (Note 3)	β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).

Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default.

Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

TDD-LTE

LTE TDD Band 41 supports 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special subframe configurations.

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS		UpPTS		UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$20480 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

We used configuration 0 for LTE Band 41&38 SAR test, that is 63.33%(1:1.58)for duty cycle.

6.3 Maximum Target Output Power

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
GSM 850	33.5	33.5	33.5
GPRS 1 TX Slot	33.3	33.3	33.3
GPRS 2 TX Slot	31.5	31.5	31.5
GPRS 3 TX Slot	29.5	29.5	29.5
GPRS 4 TX Slot	28.2	28.2	28.2
EDGE 1 TX Slot	27.1	27.1	27.1
EDGE 2 TX Slot	25.7	25.7	25.7
EDGE 3 TX Slot	24.1	24.1	24.1
EDGE 4 TX Slot	22.8	22.8	22.8
GSM 1900	29.5	29.5	29.5
GPRS 1 TX Slot	29.5	29.5	29.5
GPRS 2 TX Slot	28	28	28
GPRS 3 TX Slot	26.4	26.4	26.4
GPRS 4 TX Slot	24.9	24.9	24.9
EDGE 1 TX Slot	26.1	26.1	26.1
EDGE 2 TX Slot	24.9	24.9	24.9
EDGE 3 TX Slot	22.9	22.9	22.9
EDGE 4 TX Slot	21.9	21.9	21.9
WCDMA Band 2	22.8	22.8	22.8
HSDPA	21.3	21.3	21.3
HSUPA	20.8	20.8	20.8
DC-HSDPA	21.2	21.2	21.2
HSPA+	21.1	21.1	21.1
WCDMA Band 4	22.9	22.9	22.9
HSDPA	21.5	21.5	21.5
HSUPA	21	21	21
DC-HSDPA	22.1	22.1	22.1
HSPA+	21.2	21.2	21.2
WCDMA Band 5	23.3	23.3	23.3
HSDPA	21.9	21.9	21.9
HSUPA	21.4	21.4	21.4
DC-HSDPA	21.5	21.5	21.5
HSPA+	21.4	21.4	21.4
LTE Band 2	22.5	22.5	22.5
LTE Band 4	23.3	23.3	23.3
LTE Band 5	23.4	23.4	23.4
LTE Band 7	21.8	21.8	21.8

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
LTE Band 12	23	23	23
LTE Band 13	22.7	22.7	22.7
LTE Band 17	23	23	23
LTE Band 26	23.7	23.7	23.7
LTE Band 38	23.3	23.3	23.3
LTE Band 41	23.1	23.1	23.1
LTE Band 66	23.3	23.3	23.3
WLAN 2.4G(802.11b)	10	10	10
WLAN 2.4G(802.11g)	9.5	9.5	9.5
WLAN 2.4G(802.11n ht20)	9.1	9.1	9.1
WLAN 5.2G(802.11a)	10	10	10.6
WLAN 5.2G(802.11n ht20)	9.8	9.8	10.5
WLAN 5.2G(802.11n ht40)	10.9	/	10.9
WLAN 5.2G(802.11ac80)	/	10.6	/
WLAN 5.3G(802.11a)	12	12	12
WLAN 5.3G(802.11n ht20)	11.8	11.8	11.8
WLAN 5.3G(802.11n ht40)	12.8	/	12.8
WLAN 5.3G(802.11ac80)	/	12.6	/
WLAN 5.6G(802.11a)	14.3	14.3	13.2
WLAN 5.6G(802.11n ht20)	14.2	14.2	13
WLAN 5.6G(802.11n ht40)	15	15	14.5
WLAN 5.6G(802.11ac80)	14.9	14.9	13.8
WLAN 5.8G(802.11a)	12.2	12.2	12.2
WLAN 5.8G(802.11n ht20)	12	12	12
WLAN 5.8G(802.11n ht40)	13	/	13
WLAN 5.8G(802.11ac80)	/	12.7	/
Bluetooth BDR(GFSK)	6.5	6.0	6.0
Bluetooth EDR($\pi/4$ -DQPSK)	6.5	6.0	6.0
Bluetooth EDR(8DPSK)	7.5	6.5	6.5
BLE 1M	0	0	0

Note: The Maximum Target Power for LTE bands corresponds to their maximum power in QPSK modes with maximum bandwidth.

6.4 Test Results:

GSM:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
GSM 850	128	824.2	33.39
	190	836.6	33.26
	251	848.8	33.24
PCS 1900	512	1850.2	29.32
	661	1880	29.26
	810	1909.8	29.42

GPRS:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	33.24	31.36	29.34	28.07
	190	836.6	33.19	31.17	29.17	28.07
	251	848.8	33.18	31.32	29.39	28.06
PCS 1900	512	1850.2	29.21	27.76	26.13	24.64
	661	1880	29.43	27.78	26.11	24.45
	810	1909.8	29.27	27.90	26.31	24.75

EGPRS:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	26.88	25.37	23.97	22.65
	190	836.6	26.98	25.43	23.91	22.45
	251	848.8	26.91	25.57	23.92	22.62
PCS 1900	512	1850.2	25.90	24.77	22.77	21.70
	661	1880	25.85	24.82	22.74	21.77
	810	1909.8	25.95	24.78	22.80	21.46

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

The time based average power for GSM

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
GSM 850	128	824.2	24.39
	190	836.6	24.26
	251	848.8	24.24
PCS 1900	512	1850.2	20.32
	661	1880	20.26
	810	1909.8	20.42

The time based average power for GPRS

Band	Channel No.	Frequency (MHz)	Time based average Power (dBm)			
			1 slot	2 slot	3 slots	4 slots
GSM 850	128	824.2	24.24	25.36	25.09	25.07
	190	836.6	24.19	25.17	24.92	25.07
	251	848.8	24.18	25.32	25.14	25.06
PCS 1900	512	1850.2	20.21	21.76	21.88	21.64
	661	1880	20.43	21.78	21.86	21.45
	810	1909.8	20.27	21.9	22.06	21.75

The time based average power for EGPRS

Band	Channel No.	Frequency (MHz)	Time based average Power (dBm)			
			1 slot	2 slot	3 slots	4 slots
GSM 850	128	824.2	17.88	19.37	19.72	19.65
	190	836.6	17.98	19.43	19.66	19.45
	251	848.8	17.91	19.57	19.67	19.62
PCS 1900	512	1850.2	16.9	18.77	18.52	18.7
	661	1880	16.85	18.82	18.49	18.77
	810	1909.8	16.95	18.78	18.55	18.46

Note:

1. Radio Communication Analyzer (MT8820C) was used for the measurement of GSM peak and average output power for active timeslots.
2. For GSM voice, 1 timeslot has been activated with power level 5 (850 MHz band) and 0 (1900 MHz band).
3. For GPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 3 (850 MHz band) and 3 (1900 MHz band).
4. For EGPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 6 (850 MHz band) and 5 (1900 MHz band).
5. According to KDB941225 D01-SAR for EGPRS mode are not required when the source-based time-averaged output power for data mode is lower than that in the normal GPRS mode.

WCDMA:**WCDMA Band 2:**

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA R99	22.47	22.68	22.53
HSDPA Subtest 1	20.94	21.03	21.02
HSDPA Subtest 2	21.09	21.24	21.03
HSDPA Subtest 3	20.91	21.15	20.97
HSDPA Subtest 4	20.95	21.14	21.06
HSUPA Subtest 1	20.65	20.59	20.60
HSUPA Subtest 2	20.55	20.69	20.59
HSUPA Subtest 3	20.63	20.64	20.52
HSUPA Subtest 4	20.54	20.62	20.57
HSUPA Subtest 5	20.47	20.62	20.58
DC-HSDPA Subset 1	20.99	21.02	20.98
DC-HSDPA Subset 2	20.88	20.88	20.97
DC-HSDPA Subset 3	21.06	21.05	20.90
DC-HSDPA Subset 4	20.84	20.96	20.86
HSPA+ Subtest 1	21.00	20.98	20.92

WCDMA Band 4:

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA R99	22.74	22.75	22.61
HSDPA Subtest 1	21.20	20.96	21.32
HSDPA Subtest 2	21.29	21.24	21.20
HSDPA Subtest 3	21.07	21.36	21.08
HSDPA Subtest 4	21.16	21.28	20.99
HSUPA Subtest 1	20.79	20.74	20.71
HSUPA Subtest 2	20.80	20.80	20.76
HSUPA Subtest 3	20.81	20.85	20.77
HSUPA Subtest 4	20.74	20.73	20.60
HSUPA Subtest 5	20.71	20.77	20.71
DC-HSDPA Subset 1	21.04	21.03	20.88
DC-HSDPA Subset 2	20.99	20.96	21.03
DC-HSDPA Subset 3	20.98	21.01	20.98
DC-HSDPA Subset 4	21.98	20.95	21.08
HSPA+ Subtest 1	21.06	20.99	21.07

WCDMA Band 5:

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA R99	23.21	23.04	23.12
HSDPA Subtest 1	21.4	21.26	21.53
HSDPA Subtest 2	21.67	21.81	21.66
HSDPA Subtest 3	21.53	21.68	21.61
HSDPA Subtest 4	21.6	21.74	21.49
HSUPA Subtest 1	21.25	21.2	21.26
HSUPA Subtest 2	21.14	21.19	21.14
HSUPA Subtest 3	21.18	21.2	21.25
HSUPA Subtest 4	21.15	21.34	21.17
HSUPA Subtest 5	21.16	21.3	21.15
DC-HSDPA Subset 1	21.35	21.28	21.34
DC-HSDPA Subset 2	21.31	21.25	21.23
DC-HSDPA Subset 3	21.18	21.23	21.34
DC-HSDPA Subset 4	21.21	21.38	21.28
HSPA+ Subtest 1	21.15	21.32	21.01

Note:

1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in all 1.
2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/DC-HSDPA/HSPA+ when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

LTE Band 2:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	21.31	20.53	21.12
		RB1#3	21.43	21.66	21.59
		RB1#5	21.3	21.64	21.57
		RB3#0	21.33	21.68	21.52
		RB3#3	21.43	21.61	21.37
		RB6#0	20.55	20.6	20.53
	16-QAM	RB1#0	20.19	20.37	20.66
		RB1#3	20.35	20.49	20.86
		RB1#5	20.21	20.66	20.81
		RB3#0	20.89	20.98	20.87
		RB3#3	21	21.02	20.76
		RB6#0	19.42	20.19	19.52
3M	QPSK	RB1#0	21.5	21.73	21.61
		RB1#8	21.72	22.01	21.5
		RB1#14	21.47	21.86	21.71
		RB6#0	20.62	20.86	20.76
		RB6#9	20.65	20.76	20.61
		RB15#0	20.56	20.67	20.55
	16-QAM	RB1#0	20.47	20.7	20.5
		RB1#8	20.4	20.91	20.16
		RB1#14	20.48	20.75	19.99
		RB6#0	19.36	19.47	19.5
		RB6#9	19.08	19.52	19.44
		RB15#0	19.63	19.84	19.56
5M	QPSK	RB1#0	21.48	21.59	21.35
		RB1#13	21.6	21.98	21.65
		RB1#24	21.17	21.7	21.01
		RB15#0	20.68	20.76	20.75
		RB15#10	20.72	20.71	20.67
		RB25#0	20.62	20.87	20.55
	16-QAM	RB1#0	20.51	20.23	20.55
		RB1#13	20.65	20.64	20.9
		RB1#24	19.97	19.84	20.06
		RB15#0	19.29	19.62	19.38
		RB15#10	19.44	19.72	19.43
		RB25#0	19.53	19.82	19.73

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	21.53	21.75	21.83
		RB1#25	21.66	22.21	22.03
		RB1#49	21.46	21.82	21.41
		RB25#0	20.7	20.82	20.84
		RB25#25	20.62	20.87	20.6
		RB50#0	20.72	20.82	20.58
	16-QAM	RB1#0	20.57	20.66	20.87
		RB1#25	20.34	21.68	20.75
		RB1#49	20.38	20.93	20.57
		RB25#0	19.77	20.04	19.77
		RB25#25	19.89	19.72	19.7
		RB50#0	19.75	19.76	19.51
15M	QPSK	RB1#0	21.74	22	21.99
		RB1#38	22.41	22.22	22.12
		RB1#74	21.9	21.81	21.6
		RB36#0	20.65	20.91	20.7
		RB36#39	20.73	20.66	20.7
		RB75#0	20.67	20.58	20.64
	16-QAM	RB1#0	20.8	20.79	21.06
		RB1#38	20.86	21.15	20.99
		RB1#74	21	20.58	20
		RB36#0	19.78	19.79	19.65
		RB36#39	19.64	19.57	19.55
		RB75#0	19.73	19.67	19.65
20M	QPSK	RB1#0	21.83	22.06	22.11
		RB1#50	21.91	22.21	22.14
		RB1#99	21.85	22.13	21.97
		RB50#0	21.41	22.01	21.79
		RB50#50	21.29	21.62	21.57
		RB100#0	21.17	22.06	21.12
	16-QAM	RB1#0	20.14	20.78	20.42
		RB1#50	20.27	20.73	20.33
		RB1#99	20.32	20.24	20.04
		RB50#0	19.62	19.77	19.66
		RB50#50	19.75	19.85	19.57
		RB100#0	19.84	19.69	19.63

LTE Band 4:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	22.95	22.93	23.10
		RB1#3	23.08	23.13	21.64
		RB1#5	22.94	22.08	21.68
		RB3#0	23.03	22.01	21.82
		RB3#3	22.93	21.83	21.75
		RB6#0	22.01	21.73	21.76
	16-QAM	RB1#0	22.05	20.62	20.63
		RB1#3	21.90	20.72	20.57
		RB1#5	21.70	20.54	20.46
		RB3#0	22.06	20.71	20.81
		RB3#3	22.14	20.75	20.77
		RB6#0	21.05	19.54	19.68
3M	QPSK	RB1#0	22.60	22.75	22.50
		RB1#8	22.49	22.19	21.61
		RB1#14	22.62	22.86	21.91
		RB6#0	21.79	21.91	21.68
		RB6#9	21.69	21.78	21.86
		RB15#0	21.72	21.85	21.78
	16-QAM	RB1#0	20.62	20.91	20.45
		RB1#8	20.51	20.94	20.43
		RB1#14	20.50	20.93	20.59
		RB6#0	19.84	19.53	19.76
		RB6#9	19.87	19.51	19.64
		RB15#0	19.80	19.84	19.66
5M	QPSK	RB1#0	22.74	22.76	22.07
		RB1#13	22.83	22.08	22.48
		RB1#24	22.73	22.67	22.38
		RB15#0	21.77	21.81	21.76
		RB15#10	21.96	21.90	21.93
		RB25#0	21.89	21.82	21.67
	16-QAM	RB1#0	20.28	20.08	20.66
		RB1#13	20.00	20.35	21.08
		RB1#24	20.33	19.97	20.62
		RB15#0	20.00	19.64	19.61
		RB15#10	19.95	19.62	19.77
		RB25#0	19.56	20.06	19.79

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	22.95	22.82	22.79
		RB1#25	22.02	22.58	22.90
		RB1#49	22.88	22.65	22.96
		RB25#0	21.91	21.91	21.79
		RB25#25	21.75	21.90	21.62
		RB50#0	21.42	21.71	21.73
	16-QAM	RB1#0	20.72	20.87	20.63
		RB1#25	20.69	21.47	20.87
		RB1#49	20.85	20.86	20.38
		RB25#0	19.99	19.93	19.64
		RB25#25	19.96	19.83	19.75
		RB50#0	19.98	19.92	19.58
15M	QPSK	RB1#0	22.89	22.08	22.05
		RB1#38	22.91	22.26	22.10
		RB1#74	22.94	21.88	22.04
		RB36#0	21.90	21.77	21.61
		RB36#39	21.80	21.90	21.78
		RB75#0	21.96	21.83	21.68
	16-QAM	RB1#0	21.17	21.13	21.17
		RB1#38	21.42	21.75	21.08
		RB1#74	21.08	20.83	20.73
		RB36#0	20.04	19.78	19.71
		RB36#39	19.65	19.52	19.61
		RB75#0	19.88	19.75	19.70
20M	QPSK	RB1#0	22.51	22.62	22.56
		RB1#50	22.80	22.00	22.37
		RB1#99	22.68	22.43	22.78
		RB50#0	21.94	21.94	21.62
		RB50#50	21.97	21.92	21.77
		RB100#0	21.78	21.83	21.77
	16-QAM	RB1#0	20.31	20.62	20.55
		RB1#50	20.67	21.05	20.65
		RB1#99	20.48	20.66	20.42
		RB50#0	19.74	19.99	19.74
		RB50#50	19.53	19.64	19.72
		RB100#0	20.00	19.68	19.97

LTE Band 5:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	22.62	23.27	22.98
		RB1#3	22.74	22.65	22.53
		RB1#5	22.49	22.48	22.31
		RB3#0	22.63	22.63	22.66
		RB3#3	22.71	22.69	22.63
		RB6#0	21.85	21.62	21.61
	16-QAM	RB1#0	21.56	21.39	21.23
		RB1#3	21.73	21.67	21.41
		RB1#5	21.65	21.43	21.29
		RB3#0	21.82	21.90	21.81
		RB3#3	21.88	21.86	21.42
		RB6#0	20.98	20.76	20.73
3M	QPSK	RB1#0	22.65	22.73	22.46
		RB1#8	22.71	22.78	22.46
		RB1#14	22.62	22.61	22.41
		RB6#0	21.88	21.71	21.62
		RB6#9	21.89	21.67	21.79
		RB15#0	21.86	21.76	21.59
	16-QAM	RB1#0	21.71	21.83	21.73
		RB1#8	21.76	22.02	21.69
		RB1#14	21.69	21.76	21.68
		RB6#0	20.95	20.84	20.86
		RB6#9	20.90	20.76	20.84
		RB15#0	20.91	20.72	20.93
5M	QPSK	RB1#0	22.73	22.48	22.12
		RB1#13	22.89	23.00	22.43
		RB1#24	22.52	22.27	22.15
		RB15#0	21.96	21.85	21.59
		RB15#10	21.92	21.78	21.66
		RB25#0	21.99	21.81	21.67
	16-QAM	RB1#0	21.84	21.35	21.65
		RB1#13	21.75	21.51	22.29
		RB1#24	20.92	20.79	21.58
		RB15#0	21.07	20.69	20.45
		RB15#10	21.01	20.79	20.77
		RB25#0	20.75	21.04	20.63

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	22.68	22.83	22.40
		RB1#25	22.63	23.06	22.74
		RB1#49	22.32	22.42	22.54
		RB25#0	21.82	21.73	21.67
		RB25#25	21.90	21.77	21.60
		RB50#0	21.87	21.65	21.68
	16-QAM	RB1#0	21.69	21.73	21.78
		RB1#25	21.60	22.13	21.86
		RB1#49	21.62	21.63	21.76
		RB25#0	21.03	21.06	20.84
		RB25#25	21.11	20.75	20.81
		RB50#0	20.88	20.71	20.86

LTE Band 7:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	20.62	20.69	20.68
		RB1#13	20.86	21.09	20.88
		RB1#24	20.29	20.42	20.47
		RB15#0	19.91	20.06	19.85
		RB15#10	20.04	20.14	19.94
		RB25#0	19.92	19.95	19.81
	16-QAM	RB1#0	20.23	19.93	19.56
		RB1#13	20.46	19.98	19.66
		RB1#24	19.4	19.12	18.93
		RB15#0	18.9	19.05	18.66
		RB15#10	18.82	19.06	18.61
		RB25#0	19.07	19.04	18.88
10M	QPSK	RB1#0	21.05	21.19	20.95
		RB1#25	20.82	21.49	21.35
		RB1#49	20.68	20.88	20.98
		RB25#0	20.09	20.17	20.09
		RB25#25	19.91	20.13	20.19
		RB50#0	19.89	20.17	20.09
	16-QAM	RB1#0	19.72	20.21	20.08
		RB1#25	19.58	21.01	20.26
		RB1#49	19.58	20.19	19.68
		RB25#0	18.97	19.39	19.37
		RB25#25	18.97	19.11	19.07
		RB50#0	18.98	19.14	19.02
15M	QPSK	RB1#0	21.07	21	21.24
		RB1#38	21.68	21.52	21.32
		RB1#74	21.1	21.18	21.24
		RB36#0	19.98	20.25	20.01
		RB36#39	20	20.33	19.93
		RB75#0	20.05	20.13	20.08
	16-QAM	RB1#0	20.54	20.29	20.34
		RB1#38	20.15	20.95	20.62
		RB1#74	20.21	20.01	19.52
		RB36#0	18.91	19.14	19.1
		RB36#39	18.95	19.23	19.16
		RB75#0	19.09	19.06	18.89

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
20M	QPSK	RB1#0	21.35	21.16	21.21
		RB1#50	21.42	21.43	21.53
		RB1#99	21.24	21.23	21.29
		RB50#0	21.06	21.35	21.13
		RB50#50	20.95	21.05	20.96
		RB100#0	20.76	20.68	20.97
	16-QAM	RB1#0	19.76	19.87	19.53
		RB1#50	19.75	20.52	19.84
		RB1#99	19.62	19.84	19.31
		RB50#0	19	19.34	19.02
		RB50#50	18.82	19.12	18.94
		RB100#0	19.02	19.08	19.1

LTE Band 12:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	22.30	22.90	22.73
		RB1#3	22.51	22.68	22.61
		RB1#5	22.50	22.61	22.37
		RB3#0	22.20	22.62	22.38
		RB3#3	22.32	22.64	22.30
		RB6#0	21.61	22.01	21.44
	16-QAM	RB1#0	21.31	21.65	21.77
		RB1#3	21.26	21.50	21.59
		RB1#5	21.22	21.44	21.60
		RB3#0	21.77	21.57	21.43
		RB3#3	21.66	21.58	21.39
		RB6#0	20.89	20.77	20.18
3M	QPSK	RB1#0	22.50	22.46	22.41
		RB1#8	22.46	22.61	22.41
		RB1#14	22.50	22.59	22.28
		RB6#0	21.54	21.68	21.58
		RB6#9	21.44	21.89	21.60
		RB15#0	21.53	21.76	21.46
	16-QAM	RB1#0	21.79	21.83	21.61
		RB1#8	21.73	21.83	21.42
		RB1#14	21.59	21.97	21.53
		RB6#0	20.91	20.75	20.63
		RB6#9	20.80	20.79	20.54
		RB15#0	20.72	20.78	20.60
5M	QPSK	RB1#0	22.16	22.08	22.32
		RB1#13	22.54	22.75	22.62
		RB1#24	22.29	21.97	22.25
		RB15#0	21.62	21.63	21.65
		RB15#10	21.55	21.71	21.77
		RB25#0	21.40	21.85	21.59
	16-QAM	RB1#0	21.22	21.80	21.58
		RB1#13	21.47	22.11	21.70
		RB1#24	20.76	21.49	20.82
		RB15#0	20.22	20.64	20.79
		RB15#10	20.24	20.66	20.67
		RB25#0	20.64	20.61	20.58

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	22.41	22.58	22.64
		RB1#25	22.63	22.77	22.74
		RB1#49	22.44	22.64	22.33
		RB25#0	21.92	22.57	22.38
		RB25#25	21.86	22.31	22.19
		RB50#0	21.71	21.94	21.78
	16-QAM	RB1#0	21.33	21.53	21.63
		RB1#25	21.55	22.18	21.74
		RB1#49	21.49	21.33	21.22
		RB25#0	20.76	20.82	20.88
		RB25#25	20.72	20.67	20.64
		RB50#0	20.62	20.53	20.76

LTE Band 13:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	21.89	/	22.18
		RB1#13	22.59	/	22.58
		RB1#24	21.92	/	21.92
		RB15#0	21.93	/	21.65
		RB15#10	21.84	/	21.5
		RB25#0	21.79	/	21.81
	16-QAM	RB1#0	21.85	/	21.76
		RB1#13	22.26	/	21.45
		RB1#24	21.61	/	20.93
		RB15#0	20.7	/	20.8
		RB15#10	20.54	/	20.85
		RB25#0	20.91	/	20.48
10M	QPSK	RB1#0	/	22.26	/
		RB1#25	/	22.44	/
		RB1#49	/	22.04	/
		RB25#0	/	22.18	/
		RB25#25	/	21.93	/
		RB50#0	/	21.74	/
	16-QAM	RB1#0	/	21.6	/
		RB1#25	/	21.81	/
		RB1#49	/	21.51	/
		RB25#0	/	20.9	/
		RB25#25	/	20.92	/
		RB50#0	/	20.67	/

LTE Band 17:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	22.25	22.55	22.54
		RB1#13	22.62	22.79	22.84
		RB1#24	22.08	22.41	22.42
		RB15#0	21.66	21.67	21.5
		RB15#10	21.64	21.74	21.6
		RB25#0	21.61	21.51	21.58
	16-QAM	RB1#0	21.73	21.22	21.57
		RB1#13	22.06	21.42	22.09
		RB1#24	21.34	21.28	20.87
		RB15#0	20.55	20.68	20.53
		RB15#10	20.64	20.65	20.59
		RB25#0	20.69	20.48	20.63
10M	QPSK	RB1#0	22.8	22.91	22.67
		RB1#25	22.92	22.96	22.94
		RB1#49	22.66	22.75	22.64
		RB25#0	21.69	21.77	21.73
		RB25#25	21.74	21.7	21.72
		RB50#0	21.75	21.74	21.75
	16-QAM	RB1#0	21.7	21.54	21.71
		RB1#25	21.53	22.05	21.97
		RB1#49	21.7	21.47	21.09
		RB25#0	21.1	20.74	20.64
		RB25#25	21.02	20.88	20.94
		RB50#0	20.76	20.86	20.91

LTE Band 26:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	23.17	23.07	23.06
		RB1#3	23.24	23.4	23.03
		RB1#5	23.12	23.36	23.02
		RB3#0	22.99	23.18	22.91
		RB3#3	23.17	23.31	22.95
		RB6#0	22.07	22.1	22.08
	16-QAM	RB1#0	21.97	22.57	21.78
		RB1#3	21.99	22.47	22.06
		RB1#5	22.05	22.38	21.9
		RB3#0	21.97	22.5	22.25
		RB3#3	21.95	22.36	22.31
		RB6#0	21.11	21.01	21.03
3M	QPSK	RB1#0	23.46	23.17	23.25
		RB1#8	23.45	23.01	22.92
		RB1#14	23.54	23.18	22.9
		RB6#0	22.25	22.49	21.96
		RB6#9	22.17	22.23	21.96
		RB15#0	22.2	22.11	22
	16-QAM	RB1#0	22.61	22.01	22.15
		RB1#8	22.38	21.52	22.08
		RB1#14	22.41	21.47	22.23
		RB6#0	21.15	21.32	20.8
		RB6#9	20.88	21.41	21.05
		RB15#0	21.12	21.25	21.14
5M	QPSK	RB1#0	23.17	23.31	22.85
		RB1#13	23.08	23.55	23.04
		RB1#24	22.99	23.27	22.86
		RB15#0	22.2	22.22	22.16
		RB15#10	22.34	22.34	22.1
		RB25#0	22.31	22.42	22.01
	16-QAM	RB1#0	22.26	21.82	21.93
		RB1#13	22.49	22.05	22.01
		RB1#24	22.18	21.74	21.31
		RB15#0	20.9	21.21	21.15
		RB15#10	21.1	21.24	20.94
		RB25#0	21.43	21.39	21.25

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	23.46	23.07	23.1
		RB1#25	23.45	23.39	23.04
		RB1#49	23.62	23.11	22.86
		RB25#0	22.23	22.4	22.15
		RB25#25	22.43	22.37	22.12
		RB50#0	22.15	22.27	22.14
	16-QAM	RB1#0	22.23	22.49	21.95
		RB1#25	22.65	22.34	21.86
		RB1#49	22.58	21.94	21.89
		RB25#0	21.31	21.09	21.37
		RB25#25	21.42	21.35	21.12
		RB50#0	21.27	21.12	21.1
15M	QPSK	RB1#0	23.39	23.45	23.23
		RB1#37	23.58	23.52	23.44
		RB1#74	23.44	23.37	22.32
		RB36#0	23.23	23.01	22.97
		RB36#39	23.25	23.22	22.99
		RB75#0	22.72	23.08	22.84
	16-QAM	RB1#0	21.97	22.32	22.11
		RB1#37	22.17	22.71	22.11
		RB1#74	22.21	22.09	21.93
		RB36#0	20.96	20.92	20.91
		RB36#39	21.12	20.75	20.99
		RB75#0	21.13	21.03	20.98

LTE Band 38:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	22.25	22.29	22.38
		RB1#13	22.46	22.84	23
		RB1#24	22.26	22.22	22.49
		RB15#0	21.34	21.95	21.8
		RB15#10	21.31	21.86	22.01
		RB25#0	21.44	21.74	21.91
	16-QAM	RB1#0	21.6	21.24	21.38
		RB1#13	21.72	21.71	21.61
		RB1#24	21.65	21.36	21.53
		RB15#0	20.3	20.35	20.57
		RB15#10	20.5	20.32	20.39
		RB25#0	20.2	20.64	20.69
10M	QPSK	RB1#0	22.46	22.21	22.6
		RB1#25	22.8	22.56	22.56
		RB1#49	22.62	22.48	22.77
		RB25#0	21.53	21.83	21.73
		RB25#25	21.41	21.71	21.68
		RB50#0	21.49	21.86	21.81
	16-QAM	RB1#0	21.76	21.12	21.37
		RB1#25	21.96	22.07	21.48
		RB1#49	21.83	21.42	20.97
		RB25#0	20.31	20.44	20.61
		RB25#25	20.5	20.63	20.59
		RB50#0	20.4	20.77	20.71
15M	QPSK	RB1#0	22.71	22.35	22.65
		RB1#38	22.47	22.98	22.84
		RB1#74	22.36	22.86	22.74
		RB36#0	21.47	21.81	22.01
		RB36#39	21.33	21.65	21.89
		RB75#0	21.35	21.48	21.89
	16-QAM	RB1#0	21.9	21.94	21.3
		RB1#38	22.22	22.12	21.57
		RB1#74	21.82	22.49	21.01
		RB36#0	20.24	20.67	20.8
		RB36#39	20.26	20.74	20.58
		RB75#0	20.28	20.5	20.74

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
20M	QPSK	RB1#0	22.86	22.79	22.9
		RB1#50	22.82	22.92	23.09
		RB1#99	23.06	22.96	23.16
		RB50#0	22.84	22.78	22.82
		RB50#50	22.46	22.56	22.71
		RB100#0	22.24	22.68	22.61
	16-QAM	RB1#0	21.5	21.19	20.84
		RB1#50	21.67	21.4	21.3
		RB1#99	21.43	21.46	21.11
		RB50#0	20.45	20.75	20.75
		RB50#50	20.47	20.79	20.77
		RB100#0	20.32	20.61	20.64

LTE Band 41:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	2549.5 MHz (dBm)	Middle Channel (dBm)	2636.5 MHz (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	22.13	22.11	22.14	22.26	22.14
		RB1#13	21.56	22.54	22.26	22.98	22.26
		RB1#24	21.68	22.54	22.09	22.21	22.06
		RB15#0	21.73	21.73	21.30	21.82	21.27
		RB15#10	21.64	21.65	21.22	21.81	21.36
		RB25#0	21.17	21.19	21.13	21.82	21.27
	16-QAM	RB1#0	20.21	20.18	21.47	21.44	21.47
		RB1#13	20.31	20.30	21.63	21.49	21.57
		RB1#24	20.37	20.24	21.49	21.37	21.59
		RB15#0	19.42	19.55	20.39	20.54	20.48
		RB15#10	19.57	19.50	20.53	20.44	20.53
		RB25#0	19.71	19.63	20.02	20.78	20.05
10M	QPSK	RB1#0	21.81	21.83	22.25	22.79	22.12
		RB1#25	21.94	22.10	22.21	23.02	22.27
		RB1#49	22.15	22.08	22.06	22.65	22.12
		RB25#0	21.19	21.19	21.33	21.87	21.26
		RB25#25	21.25	21.20	21.28	21.86	21.33
		RB50#0	21.14	21.14	21.26	21.78	21.25
	16-QAM	RB1#0	20.93	20.99	20.79	22.50	20.90
		RB1#25	21.31	21.23	20.75	22.70	20.62
		RB1#49	21.23	21.35	20.45	22.53	20.40
		RB25#0	19.77	19.80	20.34	20.83	20.32
		RB25#25	19.96	19.95	20.25	20.74	20.29
		RB50#0	19.83	19.84	20.38	20.80	20.31
15M	QPSK	RB1#0	21.65	21.52	22.32	22.69	22.28
		RB1#38	21.94	22.03	22.24	22.86	22.31
		RB1#74	21.98	22.12	22.22	22.54	22.17
		RB36#0	21.25	21.27	21.27	21.69	21.27
		RB36#39	21.22	21.18	21.23	21.78	21.23
		RB75#0	21.13	21.19	21.30	21.63	21.37
	16-QAM	RB1#0	20.77	20.76	20.97	22.55	21.05
		RB1#38	21.01	21.11	20.73	22.22	20.71
		RB1#74	20.99	21.00	20.67	22.32	20.61
		RB36#0	19.90	19.83	20.23	20.52	20.17
		RB36#39	19.92	19.90	20.44	20.69	20.41
		RB75#0	19.78	19.89	20.42	20.71	20.40

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	2549.5 MHz (dBm)	Middle Channel (dBm)	2636.5 MHz (dBm)	High Channel (dBm)
20M	QPSK	RB1#0	22.01	22.08	22.53	22.86	22.27
		RB1#50	22.07	22.15	22.78	22.67	22.62
		RB1#99	22.19	22.26	22.81	22.74	22.68
		RB50#0	21.96	21.92	22.42	22.57	22.48
		RB50#50	21.96	22.02	22.79	22.69	22.58
		RB100#0	21.23	21.33	22.35	21.93	22.13
	16-QAM	RB1#0	20.83	20.72	20.54	21.84	20.38
		RB1#50	21.18	21.20	20.73	21.71	20.70
		RB1#99	21.14	21.07	20.41	21.79	20.42
		RB50#0	19.72	19.81	20.47	20.74	20.32
		RB50#50	19.88	19.89	20.34	20.91	20.43
		RB100#0	19.79	19.68	20.33	20.84	20.31

LTE Band 66:


Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	22.88	22.49	22.63
		RB1#3	23.03	22.66	22.90
		RB1#5	23.06	22.56	22.84
		RB3#0	22.82	22.87	22.58
		RB3#3	22.86	22.68	22.63
		RB6#0	21.56	21.74	21.42
	16-QAM	RB1#0	21.96	21.60	21.63
		RB1#3	21.87	21.61	21.90
		RB1#5	21.80	21.47	21.78
		RB3#0	21.43	21.94	21.69
		RB3#3	21.44	21.80	21.52
		RB6#0	20.56	20.77	20.31
3M	QPSK	RB1#0	22.75	22.92	22.59
		RB1#8	22.77	23.08	22.75
		RB1#14	22.88	22.79	22.62
		RB6#0	21.89	21.70	21.54
		RB6#9	21.89	21.77	21.64
		RB15#0	21.74	21.76	21.57
	16-QAM	RB1#0	21.52	21.76	21.74
		RB1#8	21.51	21.85	21.26
		RB1#14	21.74	21.67	21.46
		RB6#0	20.38	20.78	20.87
		RB6#9	20.42	20.95	20.67
		RB15#0	20.50	20.94	20.70
5M	QPSK	RB1#0	22.64	22.49	22.57
		RB1#13	23.07	22.90	22.75
		RB1#24	22.56	22.72	22.01
		RB15#0	21.87	21.69	21.62
		RB15#10	21.90	21.66	21.69
		RB25#0	21.78	21.89	21.71
	16-QAM	RB1#0	21.35	21.45	21.54
		RB1#13	21.51	21.45	21.80
		RB1#24	20.65	21.06	21.09
		RB15#0	20.52	20.74	20.50
		RB15#10	20.60	20.78	20.56
		RB25#0	20.76	20.88	20.72

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	22.79	22.82	22.51
		RB1#25	23.04	22.75	22.95
		RB1#49	23.11	22.88	22.57
		RB25#0	21.85	21.69	21.57
		RB25#25	21.73	21.83	21.68
		RB50#0	21.74	21.81	21.68
	16-QAM	RB1#0	21.50	21.85	21.49
		RB1#25	21.46	22.50	21.92
		RB1#49	21.54	21.92	21.53
		RB25#0	20.98	20.74	20.76
		RB25#25	20.99	20.73	20.68
		RB50#0	20.64	20.87	20.58
15M	QPSK	RB1#0	22.91	22.98	22.73
		RB1#38	23.10	23.21	22.86
		RB1#74	22.79	22.77	22.54
		RB36#0	21.85	21.81	21.62
		RB36#39	21.78	21.62	21.64
		RB75#0	21.91	21.67	21.76
	16-QAM	RB1#0	21.98	22.09	22.00
		RB1#38	22.09	22.54	21.79
		RB1#74	21.99	21.73	21.13
		RB36#0	20.80	20.75	20.78
		RB36#39	20.79	20.74	20.70
		RB75#0	20.79	20.70	20.73
20M	QPSK	RB1#0	22.51	22.52	22.67
		RB1#50	22.92	22.99	22.75
		RB1#99	22.51	22.48	22.57
		RB50#0	22.32	22.26	22.35
		RB50#50	21.91	21.84	21.98
		RB100#0	21.86	21.79	21.69
	16-QAM	RB1#0	21.42	21.44	21.13
		RB1#50	21.61	21.99	21.20
		RB1#99	21.50	21.48	21.12
		RB50#0	20.65	20.67	20.53
		RB50#50	20.63	21.00	20.56
		RB100#0	20.76	20.78	20.70

WLAN 2.4G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11b	2412	1Mbps	98.06%	9.84
	2437			9.67
	2462			9.86
802.11g	2412	6Mbps	/	9.32
	2437			9.15
	2462			9.14
802.11n ht20	2412	MCS0	/	8.96
	2437			8.85
	2462			8.97

Note: 802.11b mode duty cycle is 98.06%, as shown below



ProjectNo.:2503W27143E Tester:Ken

Date: 28.AUG.2025 21:54:16

Wi-Fi 5.2G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11a	5180	6Mbps	/	9.78
	5200			9.84
	5240			10.52
802.11n20	5180	MCS0	/	9.57
	5200			9.63
	5240			10.34
802.11n40	5190	MCS0	96.33	10.69
	5230			10.85
802.11ac80	5210	MCS0	/	10.51

Wi-Fi 5.3G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11a	5260	6Mbps	/	11.82
	5280			11.86
	5320			11.78
802.11n20	5260	MCS0	/	11.67
	5280			11.62
	5320			11.59
802.11n40	5270	MCS0	96.33	12.71
	5310			12.66
802.11ac80	5290	MCS0	/	12.48

Wi-Fi 5.6G:


Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11a	5500	6Mbps	/	14.07
	5580			14.22
	5700			13.12
	5720			12.53
802.11n20	5500	MCS0	/	13.84
	5580			14.02
	5700			12.93
	5720			12.18
802.11n40	5510	MCS0	96.33	14.88
	5550			14.96
	5670			14.34
	5710			13.66
802.11ac80	5530	MCS0	/	14.71
	5610			14.48
	5690			13.69

Wi-Fi 5.8G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11a	5745	6Mbps	/	12.09
	5785			11.99
	5825			11.84
802.11n20	5745	MCS0	/	11.82
	5785			11.79
	5825			11.62
802.11n40	5755	MCS0	96.33	12.89
	5795			12.57
802.11ac80	5775	MCS0	/	12.62

Note: The system support 802.11a/n ht20/n ht40/ac vht20/vht40/vht80, the vht20/vht40 were reduced since the identical parameters with 802.11n ht20 and ht40.

Note: 802.11n40 mode duty cycle is 96.33%, as shown below



ProjectNo.:2503W27143E Tester:Ken


Date: 10.NOV.2025 21:26:31

Bluetooth:

Mode	Channel frequency (MHz)	RF Output Power (dBm)
BDR(GFSK)	2402	5.77
	2441	5.06
	2480	5.23
EDR($\pi/4$ -DQPSK)	2402	5.72
	2441	4.99
	2480	5.18
EDR(8DPSK)	2402	6.47
	2441	5.74
	2480	5.96
BLE_1M	2402	-0.19
	2440	-1.02
	2480	-1.16

7. Standalone SAR test exclusion considerations

Antennas Location:



7.1 Antenna Distance To Edge

Antenna Distance To Edge(mm)						
Antenna	Front	Back	Left	Right	Top	Bottom
WWAN(GSM/WCDMA/LTE) Antenna	< 5	< 5	< 5	210	< 5	162
WLAN & BT Antenna	< 5	< 5	< 5	248	< 5	130

7.2 Standalone SAR test exclusion considerations

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
WLAN 2.4G	2462	10	10	0	3.1	3	NO
WLAN 5.2G	5240	10.9	12.3	0	5.6	3	NO
WLAN 5.3G	5320	12.8	19.05	0	8.8	3	NO
WLAN 5.6G	5720	15	31.62	0	15.1	3	NO
WLAN 5.8G	5825	13	19.95	0	9.6	3	NO
Bluetooth	2480	7.5	5.62	0	1.8	3	YES

Note: The bluetooth based peak power for calculation, and Wi-Fi based average power for calculation.

NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

7.3 Standalone SAR estimation:

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Estimated 1-g (W/kg)
BT	2480	7.5	5.62	0	0.24

Note: The bluetooth based peak power for calculation, and Wi-Fi based average power for calculation.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$
 $[\sqrt{f(\text{GHz})}/x]$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

7.4 Standalone SAR test exclusion considerations:

Mode	Frequency (MHz)	Target Power (dBm)	Target Power (mW)	Test exclusion Threshold (mm)
GSM 850	848.8	25.5	354.81	84.0
PCS 1900	1909.8	22.15	164.06	55.6
WCDMA Band 2	1907.6	22.8	190.55	58.2
WCDMA Band 4	1752.6	22.9	194.98	58.2
WCDMA Band 5	846.6	23.3	213.80	59.0
LTE Band 2	1900	22.5	177.83	57.0
LTE Band 4	1745	23.3	213.80	60.1
LTE Band 5	844	23.4	218.78	59.9
LTE Band 7	2560	21.8	151.36	55.8
LTE Band 12	711	23	199.53	54.6
LTE Band 13	782	22.7	186.21	53.2
LTE Band 17	711	23	199.53	54.6
LTE Band 26	841.5	23.7	234.42	62.7
LTE Band 38	2610	23.3	213.80	62.1
LTE Band 41	2680	23.1	204.17	62.3
LTE Band 66	1770	23.3	213.80	60.2
WLAN 2.4G	2462	10	10	5.2
WLAN 5.2G	5240	10.9	12.3	9.4
WLAN 5.3G	5320	12.8	19.05	14.7
WLAN 5.6G	5720	15	31.62	25.3
WLAN 5.8G	5825	13	19.95	16.1

Note: The maximum time based average power is used for calculation.

SAR test exclusion for the EUT edge considerations detail:**Distance < 50mm (To Edges)**

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

5. The Time based average Power is used for calculation

Distance > 50mm (To Edges)

At 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following:

a) $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]$ mW, at 100 MHz to 1500 MHz

b) $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10]$ mW at > 1500 MHz and ≤ 6 GHz

7.5 SAR test exclusion for the EUT edge considerations Result

According to KDB 616217 Section 4.3, SAR evaluation for the front surface of Tablet display screens are generally not necessary.

Mode	Back Edge	Left Edge	Right Edge	Top Edge	Bottom Edge
GSM 850	Required	Required	Exclusion	Required	Exclusion
PCS1900	Required	Required	Exclusion	Required	Exclusion
WCDMA Band 2	Required	Required	Exclusion	Required	Exclusion
WCDMA Band 4	Required	Required	Exclusion	Required	Exclusion
WCDMA Band 5	Required	Required	Exclusion	Required	Exclusion
LTE Band 2	Required	Required	Exclusion	Required	Exclusion
LTE Band 5	Required	Required	Exclusion	Required	Exclusion
LTE Band 7	Required	Required	Exclusion	Required	Exclusion
LTE Band 12&17	Required	Required	Exclusion	Required	Exclusion
LTE Band 13	Required	Required	Exclusion	Required	Exclusion
LTE Band 26	Required	Required	Exclusion	Required	Exclusion
LTE Band 38	Required	Required	Exclusion	Required	Exclusion
LTE Band 41	Required	Required	Exclusion	Required	Exclusion
LTE Band 66&4	Required	Required	Exclusion	Required	Exclusion
WLAN 2.4G	Required	Required	Exclusion	Required	Exclusion
WLAN 5.2G	Required	Required	Exclusion	Required	Exclusion
WLAN 5.3G	Required	Required	Exclusion	Required	Exclusion
WLAN 5.6G	Required	Required	Exclusion	Required	Exclusion
WLAN 5.8G	Required	Required	Exclusion	Required	Exclusion
Bluetooth	Exclusion*	Exclusion*	Exclusion*	Exclusion*	Exclusion*

Note:

Required: The distance is less than **Test Exclusion Distance**, the SAR test is required.

Exclusion: The distance is large than **Test Exclusion Distance**, SAR test is not required.

Exclusion*: SAR test exclusion evaluation has been done above.

8. SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

8.1 SAR Test Data

Environmental Conditions

Temperature:	21.6-22.4 °C	21.2-21.8 °C	21.6-22.4 °C	21.2-21.8 °C
Relative Humidity:	39 %	41 %	39 %	41 %
ATM Pressure:	100.9 kPa	100.3 kPa	100.9 kPa	100.2 kPa
Test Date:	2025/08/28	2025/08/29	2025/08/30	2025/08/31

Testing was performed by Wen Chen, Leo Lu, Aixlee Li, Ken Zong.

GSM 850:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	31.17	31.5	1.079	0.534	0.58	/
	848.8	GPRS	/	/	/	/	/	/
Body Left (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	31.17	31.5	1.079	0.529	0.57	/
	848.8	GPRS	/	/	/	/	/	/
Body Top (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	31.17	31.5	1.079	0.626	0.68	1#
	848.8	GPRS	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is $> 0.5\text{ dB}$, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 3DL+2UL is the worst case.
6. The max. time based average power of GSM/GPRS/EDGE mode was selected to Body SAR testing.

PCS 1900:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	26.11	26.4	1.069	0.615	0.66	2#
	1909.8	GPRS	/	/	/	/	/	/
Body Left (0mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	26.11	26.4	1.069	0.205	0.22	/
	1909.8	GPRS	/	/	/	/	/	/
Body Top (0mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	26.11	26.4	1.069	0.397	0.43	/
	1909.8	GPRS	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is $> 0.5\text{ dB}$, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.
6. The max. time based average power of GSM/GPRS/EDGE mode was selected to Body SAR testing.

WCDMA Band 2:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1852.4	RMC	22.47	22.8	1.079	0.578	0.62	/
	1880	RMC	22.68	22.8	1.028	0.798	0.82	/
	1907.6	RMC	22.53	22.8	1.064	0.823	0.88	3#
Body Left (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	22.68	22.8	1.028	0.318	0.33	/
	1907.6	RMC	/	/	/	/	/	/
Body Top (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	22.68	22.8	1.028	0.514	0.53	/
	1907.6	RMC	/	/	/	/	/	/

WCDMA Band 4:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	22.75	22.9	1.035	0.468	0.48	4#
	1752.6	RMC	/	/	/	/	/	/
Body Left (0mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	22.75	22.9	1.035	0.137	0.14	/
	1752.6	RMC	/	/	/	/	/	/
Body Top (0mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	22.75	22.9	1.035	0.421	0.44	/
	1752.6	RMC	/	/	/	/	/	/

WCDMA Band 5:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.04	23.3	1.062	0.656	0.70	/
	846.6	RMC	/	/	/	/	/	/
Body Left (0mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.04	23.3	1.062	0.724	0.77	5#
	846.6	RMC	/	/	/	/	/	/
Body Top (0mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.04	23.3	1.062	0.561	0.60	/
	846.6	RMC	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same antenna while testing SAR.
3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in all 1.
4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/DC-HSDPA/HSPA+ when the maximum average output of each RF channel is less than $\frac{1}{4}$ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is $< 75\%$ of SAR limit.
5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

LTE Band 2:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1860	20	1RB	21.91	22.5	1.146	0.699	0.80	/
	1880	20	1RB	22.21	22.5	1.069	0.955	1.02	6#
	1900	20	1RB	22.14	22.5	1.086	0.823	0.89	/
	1880	20	50%RB	22.01	22.5	1.119	0.709	0.79	/
	1880	20	100%RB	22.06	22.5	1.107	0.887	0.98	/
Body Left (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	22.21	22.5	1.069	0.335	0.36	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	22.01	22.5	1.119	0.264	0.30	/
Body Top (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	22.21	22.5	1.069	0.669	0.72	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	22.01	22.5	1.119	0.6	0.67	/

LTE Band 7:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	21.43	21.8	1.089	0.553	0.60	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	21.35	21.8	1.109	0.393	0.44	/
Body Left (0mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	21.43	21.8	1.089	0.098	0.11	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	21.35	21.8	1.109	0.065	0.07	/
Body Top (0mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	21.43	21.8	1.089	0.726	0.79	7#
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	21.35	21.8	1.109	0.71	0.79	/

LTE Band 12&17:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	22.77	23	1.054	0.723	0.76	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.57	23	1.104	0.691	0.76	/
Body Left (0mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	22.77	23	1.054	0.65	0.69	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.57	23	1.104	0.602	0.66	/
Body Top (0mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	22.77	23	1.054	0.748	0.79	8#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.57	23	1.104	0.711	0.78	/

Note: The LTE Band 17 is a subset of LTE Band 12, with the same modulation type, and the rated output power of LTE band 17 is not greater than LTE band 12, so LTE band 17 does not need to be tested.

LTE Band 13:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	782	10	1RB	22.44	22.7	1.062	0.471	0.50	/
	782	10	50%RB	22.18	22.7	1.127	0.46	0.52	/
Body Left (0mm)	782	10	1RB	22.44	22.7	1.062	0.472	0.50	/
	782	10	50%RB	22.18	22.7	1.127	0.466	0.53	/
Body Top (0mm)	782	10	1RB	22.44	22.7	1.062	0.599	0.64	/
	782	10	50%RB	22.18	22.7	1.127	0.587	0.66	9#

LTE Band 26&5:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	821.5	15	1RB	23.58	23.7	1.028	0.889	0.91	10#
	831.5	15	1RB	23.52	23.7	1.042	0.778	0.81	/
	841.5	15	1RB	23.44	23.7	1.062	0.77	0.82	/
	831.5	15	50%RB	23.22	23.7	1.117	0.715	0.80	/
	831.5	15	100%RB	23.08	23.7	1.153	0.709	0.82	/
Body Left (0mm)	821.5	15	1RB	23.58	23.7	1.028	0.678	0.70	/
	831.5	15	1RB	23.52	23.7	1.042	0.792	0.83	/
	841.5	15	1RB	23.44	23.7	1.062	0.657	0.70	/
	831.5	15	50%RB	23.22	23.7	1.117	0.647	0.72	/
Body Top (0mm)	821.5	15	1RB	/	/	/	/	/	/
	831.5	15	1RB	23.52	23.7	1.042	0.751	0.78	/
	841.5	15	1RB	/	/	/	/	/	/
	831.5	15	50%RB	23.22	23.7	1.117	0.7	0.78	/

Note: The LTE Band 5 is a subset of LTE Band 26, with the same modulation type, and the rated output power of LTE band 5 is not greater than LTE band 26, so LTE band 5 does not need to be tested.

LTE Band 38:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	2580	20	1RB	23.06	23.3	1.057	0.836	0.88	/
	2595	20	1RB	22.96	23.3	1.081	0.869	0.94	/
	2610	20	1RB	23.16	23.3	1.033	0.909	0.94	/
	2580	20	50%RB	22.84	23.3	1.112	0.834	0.93	/
	2595	20	50%RB	22.78	23.3	1.127	0.847	0.95	/
	2610	20	50%RB	22.82	23.3	1.117	0.905	1.01	11#
	2595	20	100%RB	22.68	23.3	1.153	0.853	0.98	/
Body Left (0mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	22.96	23.3	1.081	0.211	0.23	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	22.78	23.3	1.127	0.208	0.23	/
Body Top (0mm)	2580	20	1RB	23.06	23.3	1.057	0.872	0.92	/
	2595	20	1RB	22.96	23.3	1.081	0.862	0.93	/
	2610	20	1RB	23.16	23.3	1.033	0.9	0.93	/
	2580	20	50%RB	22.84	23.3	1.112	0.851	0.95	/
	2595	20	50%RB	22.78	23.3	1.127	0.862	0.97	/
	2610	20	50%RB	22.82	23.3	1.117	0.871	0.97	/
	2595	20	100%RB	22.68	23.3	1.153	0.812	0.94	/

LTE Band 41:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	2506	20	1RB	22.19	23.1	1.233	0.756	0.93	/
	2549.5	20	1RB	22.26	23.1	1.213	0.762	0.92	/
	2593	20	1RB	22.81	23.1	1.069	0.858	0.92	/
	2636.5	20	1RB	22.74	23.1	1.086	0.889	0.97	/
	2680	20	1RB	22.68	23.1	1.102	0.895	0.99	12#
	2593	20	50%RB	22.79	23.1	1.074	0.711	0.76	/
	2593	20	100%RB	22.35	23.1	1.189	0.649	0.77	/
Body Left (0mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	22.81	23.1	1.069	0.183	0.20	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	22.79	23.1	1.074	0.177	0.19	/
Body Top (0mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	22.81	23.1	1.069	0.75	0.80	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	22.79	23.1	1.074	0.744	0.80	/

Note: 1. The frequency range of LTE Band 41 is 2496~ 2690MHz. Per KDB 447498 D01, according to the following for mulacalculate N_c is 5.

KDB procedures, the following should be applied to determine the number of required test channels. The test channels should be evenly spread across the transmission frequency band of each wireless mode.¹⁴

$$N_c = \text{Round} \left\{ \left[100(f_{\text{high}} - f_{\text{low}}) / f_c \right]^{0.5} \times (f_c / 100)^{0.2} \right\},$$

where

- N_c is the number of test channels, rounded to the nearest integer,
- f_{high} and f_{low} are the highest and lowest channel frequencies within the transmission band,
- f_c is the mid-band channel frequency,
- all frequencies are in MHz.

2. The power class 3 used for LTE Band 41 SAR testing.

LTE Band 66&4:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1720	20	1RB	22.92	23.3	1.091	0.744	0.81	/
	1745	20	1RB	22.99	23.3	1.074	1.01	1.08	13#
	1770	20	1RB	22.75	23.3	1.135	0.823	0.93	/
	1720	20	50%RB	22.32	23.3	1.253	0.78	0.98	/
	1745	20	50%RB	22.26	23.3	1.271	0.853	1.08	/
	1770	20	50%RB	22.35	23.3	1.245	0.848	1.06	/
	1745	20	100%RB	21.79	23.3	1.416	0.558	0.79	/
Body Left (0mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	22.99	23.3	1.074	0.223	0.24	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	22.26	23.3	1.271	0.144	0.18	/
Body Top (0mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	22.99	23.3	1.074	0.743	0.80	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	22.26	23.3	1.271	0.478	0.61	/

Note: The LTE Band 4 is a subset of LTE Band 66, with the same modulation type, and the rated output power of LTE band 4 is not greater than LTE band 66, so LTE band 4 does not need to be tested.

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02r05.
3. KDB 941225 D05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is $> 0.5\text{ dB}$ higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is $> 1.45\text{ W/kg}$
4. KDB 941225 D05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is $< 1.45\text{ W/kg}$, tests for the remaining required test channels are optional.
5. KDB 941225 D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are $\leq 0.8\text{ W/kg}$.
6. KDB 941225 D05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
7. KDB 941225 D05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> 0.5\text{ dB}$ higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is $> 1.45\text{ W/kg}$.

WIFI 2.4G:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	9.67	10	1.079	1.02	0.327	0.36	/
	2462	802.11b	/	/	/	/	/	/	/
Body Left (0mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	9.67	10	1.079	1.02	0.455	0.50	14#
	2462	802.11b	/	/	/	/	/	/	/
Body Top (0mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	9.67	10	1.079	1.02	0.057	0.06	/
	2462	802.11b	/	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/kg}$, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. According to KDB 248227 D01, for SAR testing of WLAN with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".

WIFI 5.2G:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	5190	802.11n40	/	/	/	/	/	/	/
	5230	802.11n40	10.85	10.9	1.012	1.038	0.231	0.24	15#
Body Left (0mm)	5190	802.11n40	/	/	/	/	/	/	/
	5230	802.11n40	10.85	10.9	1.012	1.038	0.021	0.02	/
Body Top (0mm)	5190	802.11n40	/	/	/	/	/	/	/
	5230	802.11n40	10.85	10.9	1.012	1.038	< 0.01	0.01	/

WIFI 5.3G:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	5270	802.11n40	12.71	12.8	1.021	1.038	0.249	0.26	16#
	5310	802.11n40	/	/	/	/	/	/	/
Body Left (0mm)	5270	802.11n40	12.71	12.8	1.021	1.038	0.215	0.23	/
	5310	802.11n40	/	/	/	/	/	/	/
Body Top (0mm)	5270	802.11n40	12.71	12.8	1.021	1.038	0.013	0.01	/
	5310	802.11n40	/	/	/	/	/	/	/

WIFI 5.6G:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	5510	802.11n40	/	/	/	/	/	/	/
	5550	802.11n40	14.96	15	1.009	1.038	0.283	0.30	17#
	5670	802.11n40	/	/	/	/	/	/	/
	5710	802.11n40	/	/	/	/	/	/	/
Body Left (0mm)	5510	802.11n40	/	/	/	/	/	/	/
	5550	802.11n40	14.96	15	1.009	1.038	0.195	0.20	/
	5670	802.11n40	/	/	/	/	/	/	/
	5710	802.11n40	/	/	/	/	/	/	/
Body Top (0mm)	5510	802.11n40	/	/	/	/	/	/	/
	5550	802.11n40	14.96	15	1.009	1.038	< 0.01	0.01	/
	5670	802.11n40	/	/	/	/	/	/	/
	5710	802.11n40	/	/	/	/	/	/	/

WIFI 5.8G:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	5755	802.11n40	12.89	13	1.026	1.038	0.32	0.34	18#
	5795	802.11n40	/	/	/	/	/	/	/
Body Left (0mm)	5755	802.11n40	12.89	13	1.026	1.038	0.205	0.22	/
	5795	802.11n40	/	/	/	/	/	/	/
Body Top (0mm)	5755	802.11n40	12.89	13	1.026	1.038	< 0.01	0.01	/
	5795	802.11n40	/	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/kg}$, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/n20/n40/a20/ac40/ac80 mode is use for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band, 802.11n40 is the initial position for the SAR test.
4. According KDB 248227 D01, for SAR testing of 5G WIFI 802.11n40 signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".

9. Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Note: The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The Highest Measured SAR Configuration in Each Frequency Band

Body

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
750 MHz	LTE Band 26&5	821.5	Body Back	0.889	0.83	1.07
1750 MHz	LTE Band 66&4	1745	Body Back	1.01	0.957	1.06
1900 MHz	LTE Band 2	1880	Body Back	0.955	0.931	1.03
2600 MHz	LTE Band 41	2680	Body Back	0.895	0.889	1.01

Note:

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20 .
2. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
3. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements.

10. DUT HOLDER PERTURBATIONS

In accordance with TCB workshop October 2016:

- 1) SAR perturbation due to test device holders, depending on antenna locations, buttons locations on phones or device, form factor (e.g. dongles etc.), the measured SAR could be influenced by the relative positions of the test device and its holder
- 2) SAR measurement standards have included protocols to evaluate this with a flat phantom, with and without the device holder
- 3) When the highest reported SAR of an antenna is > 1.2 W/kg, holder perturbation verification is required for each antenna, using the highest SAR configuration among all applicable frequency bands in the same exact device and holder positions used for head and body SAR measurements; i.e. same device/button locations in the holder

Per IEEE 1528: 2013/Annex E/E.4.1.1: Device holder perturbation tolerance for a specific test device: Type B

When it is unknown if a device holder perturbs the fields of a test device, the SAR uncertainty shall be assessed with a flat phantom (see Clause 5) by comparing the SAR with and without the device holder according to the following tests:

The SAR tolerance for device holder disturbance is computed using Equation (E.21) and entered in the corresponding row of the appropriate uncertainty table with an assumed rectangular probability distribution and $\nu_i = \infty$ degrees of freedom:

$$SAR_{\text{tolerance}}[\%] = 100 \times \left(\frac{SAR_{\text{w/holder}} - SAR_{\text{w/o holder}}}{SAR_{\text{w/o holder}}} \right) \quad (\text{E.21})$$

The Highest Measured SAR Configuration among all applicable Frequency Band

Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		The Device holder perturbation uncertainty
			With holder	Without holder	
/	/	/	/	/	/

11. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

Simultaneous Transmission:

Description of Simultaneous Transmit Capabilities		
Transmitter Combination	Simultaneous?	Hotspot?
WWAN(GSM/WCDMA/LTE) + Bluetooth	√	×
WWAN(GSM/WCDMA/LTE) + WLAN 2.4G/5G	√	√
WLAN + Bluetooth	×	×

Note: KDB 616217 D04 The standalone and simultaneous transmission SAR tests required for Tablets are more conservative than the hotspot mode use configurations; therefore, additional testing for hotspot SAR is not required. WLAN 5.3G/5.6G does not support hotspots.

Simultaneous SAR test exclusion considerations:

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
WWAN(GSM/WCDMA/LTE) + Bluetooth	Body Back	1.08	0.24	1.32
	Body Left	0.83	0.24	1.07
	Body Top	0.97	0.24	1.21
WWAN(GSM/WCDMA/LTE) + WLAN 2.4G Hotspot	Body Back	1.08	0.36	1.44
	Body Left	0.83	0.50	1.33
	Body Top	0.97	0.06	1.03
WWAN(GSM/WCDMA/LTE) + WLAN 5.2G Hotspot	Body Back	1.08	0.24	1.32
	Body Left	0.83	0.02	0.85
	Body Top	0.97	0.01	0.98
WWAN(GSM/WCDMA/LTE) + WLAN 5.3G	Body Back	1.08	0.26	1.34
	Body Left	0.83	0.23	1.06
	Body Top	0.97	0.01	0.98
WWAN(GSM/WCDMA/LTE) + WLAN 5.6G	Body Back	1.08	0.30	1.38
	Body Left	0.83	0.20	1.03
	Body Top	0.97	0.01	0.98
WWAN(GSM/WCDMA/LTE) + WLAN 5.8G Hotspot	Body Back	1.08	0.34	1.42
	Body Left	0.83	0.22	1.05
	Body Top	0.97	0.01	0.98

Conclusion:

Sum of SAR: Σ SAR $\leq$ 1.6 W/kg therefore simultaneous transmission SAR with Volume Scans is **not required**.

12. SAR Plots

Plot 1#: GSM 850 Mid _ Body Top

DUT: Tablet; **Type:** T1102; **Serial:** 38S6-1

Communication System: UID 0, Generic GPRS-2 slots (0); Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 836.6$ MHz; $\sigma = 0.929$ S/m; $\epsilon_r = 41.753$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(6.45, 6.45, 6.45) @ 836.6 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.332 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 33.59 V/m; Power Drift = -0.14 dB


Peak SAR (extrapolated) = 2.05 W/kg

SAR(1 g) = 0.626 W/kg; SAR(10 g) = 0.250 W/kg

Smallest distance from peaks to all points 3 dB below = 8.8 mm

Ratio of SAR at M2 to SAR at M1 = 31.1%

Maximum value of SAR (measured) = 1.08 W/kg



0 dB = 1.08 W/kg = 0.33 dBW/kg

Plot 2#: PCS 1900 Mid _ Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic GPRS-3 slots (0); Frequency: 1880 MHz; Duty Cycle: 1:2.66

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.412$ S/m; $\epsilon_r = 39.728$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(5.15, 5.15, 5.15) @ 1880 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.713 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.693 V/m; Power Drift = -0.17 dB


Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.615 W/kg; SAR(10 g) = 0.285 W/kg

Smallest distance from peaks to all points 3 dB below = 8.8 mm

Ratio of SAR at M2 to SAR at M1 = 44%

Maximum value of SAR (measured) = 0.804 W/kg



Plot 3#: WCDMA Band 2 High _ Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic WCDMA (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1907.6$ MHz; $\sigma = 1.425$ S/m; $\epsilon_r = 39.307$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(5.15, 5.15, 5.15) @ 1907.6 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.707 W/kg

Zoom Scan (7x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.643 V/m; Power Drift = -0.19 dB


Peak SAR (extrapolated) = 1.99 W/kg

SAR(1 g) = 0.823 W/kg; SAR(10 g) = 0.381 W/kg

Smallest distance from peaks to all points 3 dB below = 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 46.3%

Maximum value of SAR (measured) = 1.14 W/kg



0 dB = 1.14 W/kg = 0.57 dBW/kg

Plot 4#: WCDMA Band 4 Mid _ Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1732.6$ MHz; $\sigma = 1.353$ S/m; $\epsilon_r = 40.837$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(5.41, 5.41, 5.41) @ 1732.6 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.420 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.151 V/m; Power Drift = 0.14 dB


Peak SAR (extrapolated) = 1.15 W/kg

SAR(1 g) = 0.468 W/kg; SAR(10 g) = 0.211 W/kg

Smallest distance from peaks to all points 3 dB below = 8.8 mm

Ratio of SAR at M2 to SAR at M1 = 50.4%

Maximum value of SAR (measured) = 0.601 W/kg



Plot 5#: WCDMA Band 5 Mid _ Body Left**DUT: Tablet; Type: T1102; Serial: 38S6-1**


Communication System: UID 0, Generic WCDMA (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 0.929 \text{ S/m}$; $\epsilon_r = 41.753$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(6.45, 6.45, 6.45) @ 836.6 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (6x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.566 W/kg **Zoom Scan (6x6x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 22.37 V/m ; Power Drift = -0.20 dB Peak SAR (extrapolated) = 3.53 W/kg **SAR(1 g) = 0.724 W/kg ; SAR(10 g) = 0.252 W/kg** Smallest distance from peaks to all points 3 dB below = 10.8 mm Ratio of SAR at M2 to SAR at M1 = 32.3% Maximum value of SAR (measured) = 1.36 W/kg  $0 \text{ dB} = 1.36 \text{ W/kg} = 1.34 \text{ dBW/kg}$

Plot 6#: LTE Band 2 1RB Mid_ Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic FDD-LTE (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.412$ S/m; $\epsilon_r = 39.728$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(5.15, 5.15, 5.15) @ 1880 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.19 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.340 V/m; Power Drift = 0.09 dB


Peak SAR (extrapolated) = 2.50 W/kg

SAR(1 g) = 0.955 W/kg; SAR(10 g) = 0.417 W/kg

Smallest distance from peaks to all points 3 dB below = 9.2 mm

Ratio of SAR at M2 to SAR at M1 = 43.5%

Maximum value of SAR (measured) = 1.31 W/kg



Plot 7#: LTE Band 7 1RB Mid _ Body Top**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic FDD-LTE (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 1.867$ S/m; $\epsilon_r = 39.308$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(4.75, 4.75, 4.75) @ 2535 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (7x15x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.904 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.75 V/m; Power Drift = -0.18 dB


Peak SAR (extrapolated) = 2.19 W/kg

SAR(1 g) = 0.726 W/kg; SAR(10 g) = 0.322 W/kg

Smallest distance from peaks to all points 3 dB below = 5.1 mm

Ratio of SAR at M2 to SAR at M1 = 41.7%

Maximum value of SAR (measured) = 1.12 W/kg



0 dB = 1.12 W/kg = 0.49 dBW/kg

Plot 8#: LTE Band 12 1RB Mid _ Body Top**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic FDD-LTE (0); Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 707.5$ MHz; $\sigma = 0.878$ S/m; $\epsilon_r = 43.205$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(6.45, 6.45, 6.45) @ 707.5 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.877 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.83 V/m; Power Drift = 0.19 dB


Peak SAR (extrapolated) = 3.13 W/kg

SAR(1 g) = 0.748 W/kg; SAR(10 g) = 0.267 W/kg

Smallest distance from peaks to all points 3 dB below = 10.1 mm

Ratio of SAR at M2 to SAR at M1 = 37.6%

Maximum value of SAR (measured) = 1.13 W/kg



0 dB = 1.13 W/kg = 0.53 dBW/kg

Plot 9#: LTE Band 13 50%RB Mid _ Body Top**DUT: Tablet; Type: T1102; Serial: 38S6-1**


Communication System: UID 0, Generic FDD-LTE (0); Frequency: 782 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 782 \text{ MHz}$; $\sigma = 0.892 \text{ S/m}$; $\epsilon_r = 42.744$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(6.45, 6.45, 6.45) @ 782 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (6x12x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.655 W/kg **Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 25.99 V/m ; Power Drift = 0.19 dB Peak SAR (extrapolated) = 2.40 W/kg **SAR(1 g) = 0.587 W/kg ; SAR(10 g) = 0.214 W/kg** Smallest distance from peaks to all points 3 dB below = 8.4 mm Ratio of SAR at M2 to SAR at M1 = 38.2% Maximum value of SAR (measured) = 0.884 W/kg 

Plot 10#: LTE Band 26 1RB Low _ Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic FDD-LTE (0); Frequency: 821.5 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 821.5$ MHz; $\sigma = 0.907$ S/m; $\epsilon_r = 42.337$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(6.45, 6.45, 6.45) @ 821.5 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.815 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.23 V/m; Power Drift = 0.04 dB


Peak SAR (extrapolated) = 2.64 W/kg

SAR(1 g) = 0.889 W/kg; SAR(10 g) = 0.429 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 40.1%

Maximum value of SAR (measured) = 1.11 W/kg



Plot 11#: LTE Band 38 50%RB High _ Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic TDD-LTE (0); Frequency: 2610 MHz; Duty Cycle: 1:1.58

Medium parameters used: $f = 2610$ MHz; $\sigma = 2.015$ S/m; $\epsilon_r = 38.314$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(4.55, 4.55, 4.55) @ 2610 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (11x14x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 1.06 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.211 V/m; Power Drift = -0.13 dB


Peak SAR (extrapolated) = 1.88 W/kg

SAR(1 g) = 0.905 W/kg; SAR(10 g) = 0.452 W/kg

Smallest distance from peaks to all points 3 dB below = 8.5 mm

Ratio of SAR at M2 to SAR at M1 = 57.4%

Maximum value of SAR (measured) = 1.18 W/kg



Plot 12#: LTE Band 41 1RB High_ Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, Generic TDD-LTE (0); Frequency: 2680 MHz; Duty Cycle: 1:1.58

Medium parameters used: $f = 2680$ MHz; $\sigma = 2.065$ S/m; $\epsilon_r = 38.096$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(4.55, 4.55, 4.55) @ 2680 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (11x14x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.956 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.00 dB


Peak SAR (extrapolated) = 1.92 W/kg

SAR(1 g) = 0.895 W/kg; SAR(10 g) = 0.445 W/kg

Smallest distance from peaks to all points 3 dB below = 7.6 mm

Ratio of SAR at M2 to SAR at M1 = 55.6%

Maximum value of SAR (measured) = 1.15 W/kg



Plot 13#: LTE Band 66 1RB Mid _ Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**


Communication System: UID 0, Generic FDD-LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745 \text{ MHz}$; $\sigma = 1.366 \text{ S/m}$; $\epsilon_r = 40.59$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(5.41, 5.41, 5.41) @ 1745 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x12x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.927 W/kg **Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 2.189 V/m ; Power Drift = 0.13 dB Peak SAR (extrapolated) = 2.72 W/kg **SAR(1 g) = 1.01 W/kg ; SAR(10 g) = 0.446 W/kg** Smallest distance from peaks to all points 3 dB below = 8.8 mm Ratio of SAR at M2 to SAR at M1 = 43.4% Maximum value of SAR (measured) = 1.46 W/kg  $0 \text{ dB} = 1.46 \text{ W/kg} = 1.64 \text{ dBW/kg}$

Plot 14#: 2.4G WiFi Mid_ Body Left**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, 802.11 b(0); Frequency: 2437 MHz; Duty Cycle: 1:1.02

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.796$ S/m; $\epsilon_r = 40.172$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3157; ConvF(4.75, 4.75, 4.75) @ 2437 MHz; Calibrated: 2024/11/22
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (7x15x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.612 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.749 V/m; Power Drift = 0.13 dB


Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.455 W/kg; SAR(10 g) = 0.184 W/kg

Smallest distance from peaks to all points 3 dB below = 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 43.7%

Maximum value of SAR (measured) = 0.677 W/kg



Plot 15#: 5.2G WIFI Mode n40 Mid Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, 5.2G WiFi (0); Frequency: 5230 MHz; Duty Cycle: 1:1.038

Medium parameters used: $f = 5230$ MHz; $\sigma = 4.623$ S/m; $\epsilon_r = 35.918$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3701; ConvF(5.36, 5.36, 5.36) @ 5230 MHz; Calibrated: 2024/10/17
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (10x10x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.452 W/kg

Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.09 dB


Peak SAR (extrapolated) = 0.885 W/kg

SAR(1 g) = 0.231 W/kg; SAR(10 g) = 0.072 W/kg

Smallest distance from peaks to all points 3 dB below = 5.1 mm

Ratio of SAR at M2 to SAR at M1 = 59.4%

Maximum value of SAR (measured) = 0.532 W/kg



0 dB = 0.532 W/kg = -2.74 dBW/kg

Plot 16#: 5.3G WIFI Mode n40 Mid Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**


Communication System: UID 0, 5.3G WiFi (0); Frequency: 5270 MHz; Duty Cycle: 1:1.038

Medium parameters used: $f = 5270 \text{ MHz}$; $\sigma = 4.661 \text{ S/m}$; $\epsilon_r = 35.815$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3701; ConvF(5.36, 5.36, 5.36) @ 5270 MHz; Calibrated: 2024/10/17
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (10x10x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$ Maximum value of SAR (measured) = 0.548 W/kg **Zoom Scan (8x8x12)/Cube 0:** Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$ Reference Value = 0 V/m ; Power Drift = 0.09 dB Peak SAR (extrapolated) = 1.00 W/kg **SAR(1 g) = 0.249 W/kg ; SAR(10 g) = 0.068 W/kg** Smallest distance from peaks to all points 3 dB below = 5.7 mm Ratio of SAR at M2 to SAR at M1 = 56.8% Maximum value of SAR (measured) = 0.634 W/kg  $0 \text{ dB} = 0.634 \text{ W/kg} = -1.98 \text{ dBW/kg}$

Plot 17#: 5.6G WIFI Mode n40 Mid Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**

Communication System: UID 0, 5.6G WiFi (0); Frequency: 5550 MHz; Duty Cycle: 1:1.038

Medium parameters used: $f = 5550$ MHz; $\sigma = 5.004$ S/m; $\epsilon_r = 35.116$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3701; ConvF(4.75, 4.75, 4.75) @ 5550 MHz; Calibrated: 2024/10/17
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (10x10x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.545 W/kg

Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0.3220 V/m; Power Drift = 0.13 dB


Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 0.283 W/kg; SAR(10 g) = 0.061 W/kg

Smallest distance from peaks to all points 3 dB below = 5.6 mm

Ratio of SAR at M2 to SAR at M1 = 50.8%

Maximum value of SAR (measured) = 0.817 W/kg



Plot 18#: 5.8G WIFI Mode n40 Mid Body Back**DUT: Tablet; Type: T1102; Serial: 38S6-1**


Communication System: UID 0, 5.8G Wi-Fi (0); Frequency: 5755 MHz; Duty Cycle: 1:1.038

Medium parameters used: $f = 5755 \text{ MHz}$; $\sigma = 5.237 \text{ S/m}$; $\epsilon_r = 34.706$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3701; ConvF(4.87, 4.87, 4.87) @ 5755 MHz; Calibrated: 2024/10/17
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2024/12/3
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Area Scan (10x10x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$ Maximum value of SAR (measured) = 0.678 W/kg **Zoom Scan (8x8x12)/Cube 0:** Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$ Reference Value = 1.342 V/m ; Power Drift = 0.15 dB Peak SAR (extrapolated) = 1.95 W/kg **SAR(1 g) = 0.320 W/kg ; SAR(10 g) = 0.068 W/kg** Smallest distance from peaks to all points 3 dB below = 5.4 mm Ratio of SAR at M2 to SAR at M1 = 50.3% Maximum value of SAR (measured) = 1.01 W/kg  $0 \text{ dB} = 1.01 \text{ W/kg} = 0.04 \text{ dBW/kg}$

APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.


Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Source of uncertainty	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.3	6.3
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions– reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Post-processing	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Test sample related							
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Device holder uncertainty	5.2	N	1	1	1	5.2	5.2
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Liquid conductivity target)	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2
Liquid conductivity meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity target)	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4
Liquid permittivity meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Combined standard uncertainty		RSS				12.2	12.0
Expanded uncertainty 95 % confidence interval)						24.1	23.7

APPENDIX B EUT TEST POSITION PHOTOS

Liquid depth $\geq 15\text{cm}$

Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412



Body Back Setup Photo (0mm)



Body Top Setup Photo (0mm)



Body Left Setup Photo (0mm)



APPENDIX C CALIBRATION CERTIFICATES

Please Refer to the Attachment.

******* END OF REPORT *******