

FCC RF Test Report

(GSM)

Report No.: JYTSZ-R12-2400779

Applicant: TECNO MOBILE LIMITED

Address of Applicant: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE
19-25 SHAN MEI STREET FOTAN NT HONGKONG

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: AE11

Trade Mark: TECNO

FCC ID: 2ADYY-YY5-AE11

Applicable Standards: FCC CFR Title 47 Part 2, 22H, 24E

Date of Sample Receipt: 02 Jul., 2024

Date of Test: 03 Jul., to 13 Aug., 2024

Date of Report Issued: 14 Aug., 2024

Test Result: PASS

Tested by:

Liu Liang
Project Engineer
Detong Zhao
Senior Engineer
Junce Wei
Manager

Date:

14 Aug., 2024

Reviewed by:

Date:

14 Aug., 2024

Approved by:

Date:

14 Aug., 2024

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	14 Aug., 2024	Original

2 Contents

	Page
Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode and Environment	5
3.4 Description of Test Auxiliary Equipment	5
3.5 Measurement Uncertainty	5
3.6 Additions to, Deviations, or Exclusions from the Method	5
3.7 Laboratory Facility	5
3.8 Laboratory Location.....	6
3.9 Test Instruments List	6
4 Measurement Setup and Procedure	8
4.1 Test Channel	8
4.2 Test Setup	8
4.3 Test Procedure	10
5 Test Results.....	11
5.1 Summary	11
5.1.1 Clause and Data Summary.....	11
5.1.2 Test Limit.....	12
5.2 Field Strength of Spurious Radiation Measurement Spot-check	13
5.3 Radiated Power Output Spot-check.....	15
5.3.1 Test Result.....	15

3 General Information

3.1 Client Information

Applicant:	TECNO MOBILE LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Manufacturer:	TECNO MOBILE LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Factory:	SHENZHEN TECNO TECHNOLOGY CO., LTD.
Address:	101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China

3.2 General Description of E.U.T.

Product Name:	Mobile Phone	
Model No.:	AE11	
Operation Frequency Range:	GSM850:	824.2 MHz - 848.8 MHz
	PCS1900:	1850.2 MHz - 1909.8 MHz
Modulation Type:	☒ Voice(GMSK) ☒ GPRS(GMSK) ☒ EGPRS(GMSK, 8PSK)	
Antenna Type:	Internal Antenna	
Antenna Gain:	GSM 850:	ANT3 Unflip: -7.03 dBi (declare by Applicant)
		ANT3 Flip: -11.78 dBi (declare by Applicant)
	PCS1900:	ANT5 Unflip: -2.10 dBi (declare by Applicant)
		ANT5 Flip: -6.81 dBi (declare by Applicant)
Power Supply:	Rechargeable Li-ion Polymer Battery DC3.91V, 3410mAh & Rechargeable Li-ion Polymer Battery DC3.91V, 1180mAh	
AC Adapter:	Model: U700TSA Input: AC100-240V, 50/60Hz, 2.0A Output: DC 5.0V, 3.0A 15.0W or 5.0-10.0V, 7.0A MAX or 11.0V, 6.4A MAX or 4.0-20.0V, 3.5A 70.0W MAX	
Test Sample Condition:	The test samples were provided in good working order with no visible defects.	

3.3 Test Mode and Environment

Test Mode:	
GSM mode:	Keep the EUT communication with simulated station in GSM mode
GPRS mode:	Keep the EUT communication with simulated station in GPRS mode
EGPRS mode:	Keep the EUT communication with simulated station in EGPRS mode
Remark: The EUT has been tested under continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for these modes. Just the worst case position (H mode) shown in report.	
Operating Environment:	
Temperature:	Normal: 15℃ ~ 35℃, Extreme: -30℃ ~ +50℃
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar
Voltage:	Nominal: 3.91 Vdc, Extreme: Low 3.45 Vdc, High 4.50 Vdc
Test Engineer:	Lao Lu (Conducted measurement) Alan Chen (Radiated measurement)

3.4 Description of Test Auxiliary Equipment

Test Equipment	Manufacturer	Model No.	Serial No.
Simulated Station	Anritsu	MT8820C	6201026545

3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Radiated Emission (30MHz ~ 200MHz) (3m SAC)	4.6 dB
Radiated Emission (200MHz ~ 1000MHz) (3m SAC)	5.8 dB
Radiated Emission (1GHz ~ 6GHz) (3m SAC)	4.5 dB
Radiated Emission (6GHz ~ 18GHz) (3m SAC)	4.7 dB
Radiated Emission (18GHz ~ 40GHz) (3m SAC)	5.34 dB
Radiated Emission (30MHz ~ 1GHz) (3m FAR)	3.43 dB
Radiated Emission (1GHz ~ 6GHz) (3m FAR)	4.95 dB
Radiated Emission (6GHz ~ 18GHz) (3m FAR)	5.23 dB
Note: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.	

3.6 Additions to, Deviations, or Exclusions from the Method

No

3.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test

scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2026
Loop Antenna	Schwarzbeck	FMZB 1519 B	WXJ002-4	01-05-2024	01-04-2025
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	01-09-2024	01-08-2025
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	07-01-2024	06-30-2027
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	12-27-2023	12-26-2024
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	12-27-2023	12-26-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	12-27-2023	12-26-2024
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ004-2	09-25-2023	09-24-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-17-2024	01-16-2025
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Radiated Emission(3m FAR):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m FAR	YUNYI	9m*6m*6m	WXJ097	06-15-2023	06-14-2028
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ097-2	06-26-2024	06-25-2025
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	07-01-2024	06-30-2027
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ097-3	06-16-2024	06-15-2025
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-3	12-28-2023	12-27-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	12-28-2023	12-27-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-6	12-28-2023	12-27-2024
Pre-amplifier (30MHz ~ 1GHz)	YUNYI	PAM-310N	WXJ097-5	04-24-2024	04-23-2025
Pre-amplifier (1GHz ~ 18GHz)	YUNYI	PAM-118N	WXJ097-6	04-24-2024	04-23-2025
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	12-27-2023	12-26-2024
EMI Test Receiver	Rohde & Schwarz	ESCI3	WXJ003	12-27-2023	12-26-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	12-27-2023	12-26-2024
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ081-1	06-11-2024	06-10-2025
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-13M	WXG097-1	08-01-2023	07-31-2024
				07-30-2024	07-29-2025
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG097-2	08-01-2023	07-31-2024
				07-30-2024	07-29-2025
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG097-3	08-01-2023	07-31-2024
				07-30-2024	07-29-2025
High Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	

Low Band Reject Filter Group	Tonscend	JS0806-F	WXJ097-4	N/A
Test Software	Tonscend	TS+	Version: 5.0.0	

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Keysight	N9020A	WXJ094	09-25-2023	09-24-2024
Simulated Station	Rohde & Schwarz	CMW500	WXJ081	06-11-2024	06-10-2025
Temperature Humidity Chamber	ZHONG ZHI	CZ-A-80D	WXJ032-3	01-09-2023	01-08-2025
DC Power Supply	Keysight	E3642A	WXJ025-2	N/A	
RF Control Unit	Tonscend	JS0806-1	WXG010	N/A	
Band Reject Filter Group	Tonscend	JS0806-F	WXG010-1	N/A	
Test Software	Tonscend	TS+	Version: 2.6.9.0526		

4 Measurement Setup and Procedure

4.1 Test Channel

According to ANSI C63.26-2015 chapter 5.1.2.1 Table 2 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:


GSM850					
Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
128	824.2	190	836.6	251	848.8

PCS1900					
Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
512	1850.2	661	1880.0	810	1909.8


4.2 Test Setup

1) Radiated emission measurement:


Below 1GHz (3m SAC)



Above 1GHz (3m SAC)



2) Conducted test method



4.3 Test Procedure

Test method	Test step
Radiated emission	For below 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: 1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
Conducted test method	1. The GSM antenna port of EUT was connected to the test port of the test system through an RF cable. 2. The EUT is keeping in continuous transmission mode and tested in all modulation modes. 3. Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.

5 Test Results

5.1 Summary

5.1.1 Clause and Data Summary

This report is revised according to the JYTSZ-R12-2400299 report, FCC ID: 2ADYY-AE11 issued by JianYan Testing Group Shenzhen Co., Ltd. Differences: FCC ID: 2ADYY-YYA-AE11 is in FCC ID: 2ADYY-AE11 models based on the change T6601/T6602/T6603/C3929/F6201/F6202/F6204/F6205/C3259/C3217/L3211 components of value, and changes the NFC antenna, so need to spot-check GSM Conducted Output Power and Field Strength of Spurious Radiation.

Test items	Standard clause	Test data	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	See SAR Report	Pass
RF Output Power	Part 2.1046 Part 22.913 (a)(5) Part 24.232 (c)	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.
Peak-to-Average Power Ratio	Part 24.232 (d)	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.
Modulation Characteristics	Part 2.1047	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.
26dB Emission Bandwidth 99% Occupied Bandwidth	Part 2.1049	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.
Out of Band Emission at Antenna Terminals	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.
Frequency Stability vs. Temperature	Part 22.355 Part 24.235 Part 2.1055(a)(1)(b)	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.
Frequency Stability vs. Voltage	Part 22.355 Part 24.235 Part 2.1055(d)(2)	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.	Please refer to report JYTSZ-R12-2400299, FCC ID: 2ADYY-AE11.
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (Fundamental Frequency below 1GHz)/1.0dB (Fundamental Frequency above 1GHz) (provided by the customer). 3. Please refer to FCC ID: 2ADYY-AE11, report No.: JYTSZ-R12-2400299 issue by JianYan Testing Group Shenzhen Co., Ltd.			
Test Method:	ANSI/TIA-603-E-2016 ANSI C63.26-2015		

5.1.2 Test Limit

Items	Limit																																
RF Output Power	GSM850: 7W ERP PCS1900: 2W EIRP																																
Peak-to-Average Power Ratio	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB																																
Modulation Characteristics	N/A																																
26dB Emission Bandwidth 99% Occupied Bandwidth	N/A																																
Out of Band Emission at Antenna Terminals	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.																																
Field Strength of Spurious Radiation																																	
Frequency Stability vs. Temperature	GSM850: Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section. TABLE C-1—FREQUENCY TOLERANCE FOR TRANSMITTERS IN THE PUBLIC MOBILE SERVICES <table><tr><th>Frequency range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile >3 watts (ppm)</th><th>Mobile ≤3 watts (ppm)</th></tr><tr><td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr><tr><td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr><tr><td>450 to 512</td><td>2.5</td><td>5.0</td><td>5.0</td></tr><tr><td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr><tr><td>928 to 929</td><td>5.0</td><td>n/a</td><td>n/a</td></tr><tr><td>929 to 960</td><td>1.5</td><td>n/a</td><td>n/a</td></tr><tr><td>2110 to 2220</td><td>10.0</td><td>n/a</td><td>n/a</td></tr></table> PCS1900: The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.	Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	450 to 512	2.5	5.0	5.0	821 to 896	1.5	2.5	2.5	928 to 929	5.0	n/a	n/a	929 to 960	1.5	n/a	n/a	2110 to 2220	10.0	n/a	n/a
Frequency range (MHz)		Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)																													
25 to 50	20.0	20.0	50.0																														
50 to 450	5.0	5.0	50.0																														
450 to 512	2.5	5.0	5.0																														
821 to 896	1.5	2.5	2.5																														
928 to 929	5.0	n/a	n/a																														
929 to 960	1.5	n/a	n/a																														
2110 to 2220	10.0	n/a	n/a																														
Frequency Stability vs. Voltage																																	

5.2 Field Strength of Spurious Radiation Measurement Spot-check

GSM850						
Lowest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.40	-40.97	-11.55	-52.52	-13.00	39.52	Vertical
2472.60	-38.30	-8.68	-46.98	-13.00	33.98	Vertical
3296.80	-53.77	-3.87	-57.64	-13.00	44.64	Vertical
1648.40	-42.91	-10.88	-53.79	-13.00	40.79	Horizontal
2472.60	-40.72	-9.15	-49.87	-13.00	36.87	Horizontal
3296.80	-50.06	-3.93	-53.99	-13.00	40.99	Horizontal
Middle channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.20	-40.21	-10.70	-50.91	-13.00	37.91	Vertical
2509.80	-37.82	-8.66	-46.48	-13.00	33.48	Vertical
3346.40	-53.55	-3.33	-56.88	-13.00	43.88	Vertical
1673.20	-42.90	-10.28	-53.18	-13.00	40.18	Horizontal
2509.80	-40.84	-8.73	-49.57	-13.00	36.57	Horizontal
3346.40	-50.18	-3.42	-53.60	-13.00	40.60	Horizontal
Highest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.60	-39.85	-9.90	-49.75	-13.00	36.75	Vertical
2546.40	-38.28	-8.40	-46.68	-13.00	33.68	Vertical
3395.20	-53.74	-2.55	-56.29	-13.00	43.29	Vertical
1697.60	-42.95	-9.70	-52.65	-13.00	39.65	Horizontal
2546.40	-40.81	-8.17	-48.98	-13.00	35.98	Horizontal
3395.20	-50.33	-2.62	-52.95	-13.00	39.95	Horizontal
Remark: 1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report.						

PCS1900						
Lowest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.40	-50.86	-0.34	-51.20	-13.00	38.20	Vertical
5550.60	-53.74	4.15	-49.59	-13.00	36.59	Vertical
3700.40	-54.82	-0.16	-54.98	-13.00	41.98	Horizontal
5550.60	-46.29	4.05	-42.24	-13.00	29.24	Horizontal
Middle channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-51.65	-1.01	-52.66	-13.00	39.66	Vertical
5640.00	-53.78	3.96	-49.82	-13.00	36.82	Vertical
3760.00	-54.34	-0.56	-54.90	-13.00	41.90	Horizontal
5640.00	-46.27	4.14	-42.13	-13.00	29.13	Horizontal
Highest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.60	-53.93	-0.53	-54.46	-13.00	41.46	Vertical
5729.40	-54.18	3.44	-50.74	-13.00	37.74	Vertical
3819.60	-54.55	-0.06	-54.61	-13.00	41.61	Horizontal
5729.40	-46.71	3.82	-42.89	-13.00	29.89	Horizontal
Remark: 1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report.						

5.3 Radiated Power Output Spot-check

5.3.1 Test Result

Band	Channel	PCL	Conducted Power (dBm)	Unflip ERP/EIRP (dBm)	Flip ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	33.22	24.04	19.29	38.45	PASS
GSM850	190	5	33.20	24.02	19.27	38.45	PASS
GSM850	251	5	33.12	23.94	19.19	38.45	PASS
GSM1900	512	0	30.54	28.44	23.73	33.00	PASS
GSM1900	661	0	30.69	28.59	23.88	33.00	PASS
GSM1900	810	0	30.38	28.28	23.57	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	Unflip ERP/EIRP (dBm)	Flip ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	33.21	24.03	19.28	38.45	PASS
GPRS850	128	5	2	32.48	23.3	18.55	38.45	PASS
GPRS850	128	5	3	30.76	21.58	16.83	38.45	PASS
GPRS850	128	5	4	29.73	20.55	15.8	38.45	PASS
GPRS850	190	5	1	33.18	24	19.25	38.45	PASS
GPRS850	190	5	2	32.46	23.28	18.53	38.45	PASS
GPRS850	190	5	3	30.73	21.55	16.8	38.45	PASS
GPRS850	190	5	4	29.70	20.52	15.77	38.45	PASS
GPRS850	251	5	1	33.08	23.9	19.15	38.45	PASS
GPRS850	251	5	2	32.35	23.17	18.42	38.45	PASS
GPRS850	251	5	3	30.65	21.47	16.72	38.45	PASS
GPRS850	251	5	4	29.61	20.43	15.68	38.45	PASS
GPRS1900	512	0	1	30.57	28.47	23.76	33.00	PASS
GPRS1900	512	0	2	29.83	27.73	23.02	33.00	PASS
GPRS1900	512	0	3	27.98	25.88	21.17	33.00	PASS
GPRS1900	512	0	4	26.93	24.83	20.12	33.00	PASS
GPRS1900	661	0	1	30.71	28.61	23.9	33.00	PASS
GPRS1900	661	0	2	29.99	27.89	23.18	33.00	PASS
GPRS1900	661	0	3	28.19	26.09	21.38	33.00	PASS
GPRS1900	661	0	4	27.15	25.05	20.34	33.00	PASS
GPRS1900	810	0	1	30.36	28.26	23.55	33.00	PASS
GPRS1900	810	0	2	29.66	27.56	22.85	33.00	PASS
GPRS1900	810	0	3	27.89	25.79	21.08	33.00	PASS

GPRS1900	810	0	4	26.88	24.78	20.07	33.00	PASS
----------	-----	---	---	-------	-------	-------	-------	------

Band	Channel	PCL	Slot	Conducted Power (dBm)	Unflip ERP/EIRP (dBm)	Flip ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
EGPRS850	128	8	1	27.91	18.73	13.98	38.45	PASS
EGPRS850	128	8	2	26.76	17.58	12.83	38.45	PASS
EGPRS850	128	8	3	24.52	15.34	10.59	38.45	PASS
EGPRS850	128	8	4	23.21	14.03	9.28	38.45	PASS
EGPRS850	190	8	1	27.92	18.74	13.99	38.45	PASS
EGPRS850	190	8	2	26.78	17.6	12.85	38.45	PASS
EGPRS850	190	8	3	24.56	15.38	10.63	38.45	PASS
EGPRS850	190	8	4	23.24	14.06	9.31	38.45	PASS
EGPRS850	251	8	1	27.86	18.68	13.93	38.45	PASS
EGPRS850	251	8	2	26.74	17.56	12.81	38.45	PASS
EGPRS850	251	8	3	24.45	15.27	10.52	38.45	PASS
EGPRS850	251	8	4	23.20	14.02	9.27	38.45	PASS
EGPRS1900	512	2	1	26.83	24.73	20.02	33.00	PASS
EGPRS1900	512	2	2	25.65	23.55	18.84	33.00	PASS
EGPRS1900	512	2	3	23.21	21.11	16.4	33.00	PASS
EGPRS1900	512	2	4	21.77	19.67	14.96	33.00	PASS
EGPRS1900	661	2	1	27.00	24.9	20.19	33.00	PASS
EGPRS1900	661	2	2	25.86	23.76	19.05	33.00	PASS
EGPRS1900	661	2	3	23.49	21.39	16.68	33.00	PASS
EGPRS1900	661	2	4	22.06	19.96	15.25	33.00	PASS
EGPRS1900	810	2	1	27.31	25.21	20.5	33.00	PASS
EGPRS1900	810	2	2	26.20	24.1	19.39	33.00	PASS
EGPRS1900	810	2	3	23.84	21.74	17.03	33.00	PASS
EGPRS1900	810	2	4	22.48	20.38	15.67	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)

-----End of report-----